DOU YEE
ENTERPRISES (S) PTE LTD

2304 Bedok Reservoir Road, Bedok Industrial Park C, Singapore 479223
Tel: (65) 64442678 Fax: (65) 67437172
Email: marketing@douyee.com.sg Website: www.douyee.com

Product Data Sheet

PRODUCT CODE / PART NUMBER: DY6008-HS778C-35M-EVA/NBR-S1PLSRFOHRO-SK-SIZE

PRODUCT: Static Dissipative Safety Shoes

BRAND NAME: **EUROSTAT®** *Safetykey*

FEATURES:

This safety shoe is made of Action Nubuck, Action Embossed Leather, Fly-Knitting Acrylic, Composite Toe Cap, Composite Midplate, Sandwich Mesh Lining, High Density Foam Insoles, PU Midsole and Nitrile Rubber (NBR) Outsole

- 200J Impact Resistance
- 15KN Compression Resistance
- 1100N Penetration Resistance
- Light Weight, Excellent Comfort
- Resistant to Oil and Most Chemicals
- Non-Marking and Slip Resistant Outsole (SRC)



Specifications

Item	Properties / Typical Values	Test Method
Materials	Upper : Action Nubuck, Action Embossed Leather, Fly-Knitting Acrylic Toe Cap : Composite Midplate : Composite Insole : High Density Foam Midsole : Static Dissipative PU Outsole : Static Dissipative Nitrile Rubber (NBR)	
Footwear only Resistance	$< 1.0 \times 10^9$ ohms	ANSI/ESD STM9.1
Footwear System Resistance	$< 3.5 \times 10^7$ ohms	ANSI/ESD STM9.1
Electrical System Resistance of a person wearing footwear while standing on conductive flooring	$< 3.5 \times 10^7$ ohms	ANSI/ESD STM97.1
Color	Upper : Black/Grey Midsole : Black Outsole : Black	
Sizes (European)	36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46 & 47	
Conformity	1) The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article Annex V, including the application clauses of the Essential Health and Safety Requirements of the PPE Regulation EU 2016/425 for Category II products. This has been shown through satisfactory testing to EN ISO 20345:2011 and examination of the Technical File Documentation (Category: S1P SRC HRO) 2) SIRIM MS ISO 20345: 2008 (License No.: PC004375)	

NBR OUTSOLE	COMPOSITE MIDPLATE	WIDER COMPOSITE TOE CAP
		

Size	36	37	38	39	40	41	42	43	44	45	46	47
Average weight per pair (g)	820	860	880	940	960	980	1020	1080	1120	1160	1200	1220

Date: 2025 / 2026