



Eidgenössische Technische Hochschule Zürich
Swiss Federal Institute of Technology Zurich

Lecture with Computer Exercises:
Modelling and Simulating Social Systems with MATLAB

Project Report

Modeling of a passenger ship evacuation

Manuela Eugster, Andreas Reber, Raphael Brechbuehler,
Fabian Schmid

Zurich
November 19, 2012

Agreement for free-download

We hereby agree to make our source code for this project freely available for download from the web pages of the SOMS chair. Furthermore, we assure that all source code is written by ourselves and is not violating any copyright restrictions.

Manuela Eugster

Andreas Reber

Raphael Brechbuehler

Fabian Schmid



Eidgenössische Technische Hochschule Zürich
Swiss Federal Institute of Technology Zurich

Declaration of Originality

This sheet must be signed and enclosed with every piece of written work submitted at ETH.

I hereby declare that the written work I have submitted entitled

Modeling of a ship evacuation

is original work which I alone have authored and which is written in my own words.*

Author(s)

Last name

Eugster

Brechbuehler

Reber

Schmid

First name

Manuela

Raphael

Andreas

Fabian

Supervising lecturer

Last name

Balietti

Donnay

First name

Stefano

Karsten

With the signature I declare that I have been informed regarding normal academic citation rules and that I have read and understood the information on 'Citation etiquette' (http://www.ethz.ch/students/exams/plagiarism_s_en.pdf). The citation conventions usual to the discipline in question here have been respected.

The above written work may be tested electronically for plagiarism.

Zurich, 20.11.2012

Place and date

Signature

2. Brechbuehler
A. Reber
F. Schmid
M. Eugster

*Co-authored work: The signatures of all authors are required. Each signature attests to the originality of the entire piece of written work in its final form.

Print form

Contents

1	Abstract	5
2	Individual contributions	5
3	Introduction and Motivations	5
3.1	Introduction	5
3.2	Motivation	6
3.3	Fundamental Questions	6
4	Description of the Model	6
4.1	General Model	6
5	Implementation	7
6	Simulation Results and Discussion	7
6.1	Expected Results	7
6.2	Simulation Results	8
6.3	Comparison	8
6.4	Discussion	8
7	Summary and Outlook	8
7.1	Summary	8
7.2	Outlook	8
8	References	8

1 Abstract

2 Individual contributions

The whole project was completed as a team. For sure we took into consideration all the personal backgrounds and knowledge. That is the reason why Raphael and Manuela focused on implenting the computer code. Whereas Andreas and Fabian concentrated on providing background information, compared the results with the reality and doing its verification.

3 Introduction and Motivations

3.1 Introduction

The evacuation of a passenger liner due to fire, sinking or other issues leads to several problems. A large amount of passengers try to safe their lives and get to a rescue boat. Narrow and branched floors, smoke, inflowing water, the absence of illumination, rude passengers and so forth can make the evacuation difficult and reduce the number of survivors. There are a lot of norms how to minimize the harm of such an evacuation. For example there are rules on the number of rescue boats dependent on the amount of passengers [3]. With dry runs the staff is prepared for the case of emergency et cetera. In real life ship corridor reproduction, the behavior of distressed people is studied. Another approach is to model such ship evacuations numerically on the computer. As an example the software maritimeEXODUS by a development team from the University of Greenwich is a PC based evacuation and pedestrian dynamics model that is capable of simulating individual people, behaviour and vessel details. The model includes aspects of people-people, people-structure and people-environment interaction. It is capable of simulating thousands of people in very large ship geometries and can incorporate interaction with fire hazard data such as smoke, heat and toxic gases and angle of heel [6]. Our approach is similarly to model a passenger ship with a common geometrical outline and ground view. In an optimization process we will thereafter look for an ideal ground view, rescue boat distribution and their size to minimize the time needed for evacuation. Finally we will make a statement on possible improvements.

3.2 Motivation

Even though modern ocean liners are considered to be safe, the latest occasions attested that there is still potential for evacuation and safety improvements [7]. Certainly we know that this science is very advanced and practised since the sinking of the Titanic. Nevertheless knowing that there are still bottlenecks on the ships we are very motivated to detect and eliminate them with our mathematical models.

3.3 Fundamental Questions

To find these bottlenecks we run a mathematical model of a ship structure with several decks and its passengers [5]. After we localised these places we are interested in the answers of the following questions:

How much time can be saved by varying the dependent variables mentioned below:

- How much people can be saved by changing the disposition of the specific room types?
- Where are the bottlenecks during the evacuation? How can they be avoided?

What is the influence of the rescue boats?

- Are small or bigger boats better?
- Where do they have to be positioned?

If we have time to spare we analyse the difference between uncontrolled and controlled passenger flow:

- Is the crew able to prevent chaos in the evacuation process?
- What is the best way to lead the passengers out of the ship?

In addition we are keen to know if our model is a good abstraction of the reality?

4 Description of the Model

4.1 General Model

We will base the modeling part on the work done by a group of former "MSSSM" students, by name Hans Hardmeier, Andrin Jenal, Beat Kueng and Felix Thaler. [2] In their work "Modeling Situations of Evacuation in a Multi-level Building" they

wrote a computer program in c with a MATLAB surface to rapidly simulate the evacuation of multi-level buildings.

Similar to the building we necessarily need an implementation of a common ship shape [5]. In order to make strong conclusions we want to keep the following variables independent:

- Number of passengers
- Overall capacity of the rescue boats
- Ship size and shape
- Area used by specific rooms (coaches for passengers, lounge area, corridors)

Our target is to decrease the evacuation time. Measurements will be made on the time to evacuate:

- 10%
- 50%
- 90%
- 100% of all passengers.

In order to optimize the evacuation time, we change the following dependent variables:

- Disposition of the specific room types (e.g. changing the geometry of the corridors without changing the total area used for corridors)
- Rescue boat size, number and position
- Control of the passenger flow by crew members (e.g. is there staff to lead the passengers and how are they doing it?)

5 Implementation

6 Simulation Results and Discussion

6.1 Expected Results

- Even though modern ships are quite optimized in regard to evacuation time, they are always a compromise between safety and luxury. Therefore we are convinced to find a superior adjustment of the decks geometries to increase the survival rate.

- Since the rescue boats can not be averaged but are rather concentrated over one or two decks, we consider the staircases as the bottlenecks.
- In alinging this variables we are persuaded of a reduction of the overall evacuation time.
- We suppose that smaller and evenly spread rescue boats combined with a higher quantity will scale the evacuation time down. Certainly there is going to be an optimum in size which we are willing to find.
- By controlling the rescue we assume to detect a huge decrease in evacuation time. Further we have the hypothesis that disorder can be minimized. The crew who is familiar with the decks and the emergency exits is able to guide the passengers in minimum time to the rescue boats.
- There are many parameters we do not model in our simulation. For example fire and smoke, the tilt of the ship or handicapped and petrified passengers are disregarded. By leaving out this details we get a very simplified model. However, by starting the optimization process by data of a nowadays passenger liner [5] we hope to see some real evacuation dynamics in this system and therefore make conclusion on the fundamental questions.

6.2 Simulation Results

6.3 Comparison

6.4 Discussion

7 Summary and Outlook

7.1 Summary

7.2 Outlook

8 References

References

- [1] Helbing, Dirk (1995): Social Force Model for Pedestrians Dynamics.
- [2] Hardmeier,Jenal,Kueng,Thaler (2012): Modelling Situations of Evacuation in a Multi-level Building.

- [3] SOLAS (1974): International Convention for the Safety of Life at Sea. [http://www.imo.org/about/conventions/listofconventions/pages/international-convention-for-the-safety-of-life-at-sea-\(solas\)-1974.aspx](http://www.imo.org/about/conventions/listofconventions/pages/international-convention-for-the-safety-of-life-at-sea-(solas)-1974.aspx)
- [4] SHIP EVACUATION: <http://www.shipevacuation.com/>
- [5] CRUISE DECK PLANS PUBLIC SITE: <http://www.cruisedeckplans.com/DP/Main/decks.php?ship=Costa%20Serena>
- [6] University of Greenwich (2011): maritimeEXODUS. http://fseg.gre.ac.uk/fire/marine_evac_model.html
- [7] Haverie of Costa Concordia (2012): http://de.wikipedia.org/wiki/Costa_Concordia#Havarie_2012