

```
ejercicio 1
[7]: :t True
:t "Hola mundo"
:t [1,2,3]

True :: Bool
"Hola mundo" :: String
[1,2,3] :: forall (a). Num a => [a]

[21]: a = [1,2,3]
      b = [4,5]
      c = a ++ b
      return c

[1,2,3,4,5]

[10]: doble :: Int -> Int
      doble x = x ^ 2
      doble 2

4

[22]: esMayorEdad :: Int -> Bool
      esMayorEdad edad = edad >= 18
      esMayorEdad 15

False

[23]: areaCirculo :: Float -> Float
      areaCirculo x = (x ^ 2) * pi
      areaCirculo 7

153.93805
```

```
File Edit View Run Kernel Tabs Settings Help
ejercicio 1
[24]: head [10,20,30,40]
      tail [10,20,30,40]
      take 3 [1..10]
      drop 4 [1..10]
      length [1,2,3,4,5]

10
[20,30,40]
[1,2,3]
[5,6,7,8,9,10]
5

[45]: primerElemento :: [a] -> a
      primerElemento (x:_) = x
      primerElemento [] = 1

1

[46]: productolista :: [Int] -> Int
      productolista [] = 1
      productolista (x:xs) = x * productolista xs
      productolista [2,4,6]

Use foldr
Found: productolista [] = 1
      productolista (x:xs) = x * productolista xs
      productolista xs = foldr (*) 1 xs
48

[50]: eliminarNegativos :: [Int] -> [Int]
      eliminarNegativos [] = []
      eliminarNegativos (x:xs)
      | x > 0 = x : eliminarNegativos xs
      | otherwise = eliminarNegativos xs
      eliminarNegativos [-1,2,-8,3]

[2,3]

[51]: invertir :: [a] -> [a]
      invertir [] = []
      invertir (x:xs) = invertir xs ++ [x]
      invertir [2,9,3,4]

[4,3,5,2]
```