



# MASTER VECTOR BRAND GUIDELINES

RECONSTRUCTION SPECIFICATION V1.0

Corporate identity production manual

Digital, print, environmental and merchandise use

# 01 Master identity

The primary portrait lockup preserves the supplied composition and hierarchy.



## PRIMARY MASTER

Use the full-colour master whenever the original ocean setting is appropriate.

All master lettering is converted to vector outlines.

No raster images, clipping masks or embedded bitmap layers are used.

Keep the artwork proportional. Never stretch, rotate, crop or rearrange elements.

## CLEAR SPACE

Minimum clear space = the cap-height of the letter A (X) on every side.

Do not place text, trim edges or competing graphics inside this zone.

## MINIMUM SIZE

Print full lockup: 30 mm wide minimum.

Digital full lockup: 180 px wide minimum.

Below 48 px, use the approved favicon crop without wordmark.

## 02 Official colours

Values are normalized from the supplied compressed artwork; Pantone matches are visual approximations.



### SUN

HEX #F0400B RGB 240/64/11

CMYK 0/85/100/0

PANTONE 172 C approx.



### SKY

HEX #034D78 RGB 3/77/120

CMYK 98/64/33/15

PANTONE 7692 C approx.



### OCEAN

HEX #02337F RGB 2/51/127

CMYK 100/78/15/3

PANTONE 2945 C approx.



### COBALT

HEX #0055A4 RGB 0/85/164

CMYK 100/67/0/6

PANTONE 300 C approx.



### AQUA

HEX #00A6C7 RGB 0/166/199

CMYK 84/13/20/0

PANTONE 3125 C approx.



### DEEP BLUE

HEX #001B53 RGB 0/27/83

CMYK 100/90/25/35

PANTONE 2767 C approx.



### PANEL

HEX #071919 RGB 7/25/25

CMYK 85/55/55/85

PANTONE Black 6 C approx.



### WHITE

HEX #FFFFFF RGB 255/255/255

CMYK 0/0/0/0

Opaque White

Always proof Pantone and CMYK output against a calibrated physical swatch and the printer's substrate/profile.

## 03 Approved variations

Select the version that preserves maximum contrast and recognition.



PRIMARY



REVERSE



BLACK



GOLD

## 04 Correct and incorrect usage

Brand consistency depends on preserving geometry, contrast and hierarchy.



**CORRECT:** approved reverse artwork on brand navy



### PROHIBITED

- Do not stretch or condense.
- Do not recolour individual elements.
- Do not add effects, shadows or outlines.
- Do not alter typography or spacing.
- Do not place on low-contrast imagery.
- Do not crop the full lockup except for the favicon asset.

# 05 Production and accessibility

Use the master format suited to the reproduction process.

## PRINT

Use CMYK PDF or EPS. Confirm bleed in the final layout, not in the logo file. For signage and wraps, scale the vector master. For embroidery, digitize from the Black or White version and proof stitch density.

## DIGITAL

Use SVG where supported. Use PNG for social, email and booking platforms. Use the favicon package below 48 px. Keep sufficient contrast against backgrounds and preserve clear space.

## ACCESSIBILITY

Maintain at least 4.5:1 contrast for adjacent text in applications. The logo wordmark is artwork, not a replacement for accessible HTML text. Include the business name as alt text.

## RECONSTRUCTION PROVENANCE

The only supplied authority was a 579 x 641 compressed JPEG. Geometry, font identity, photographic ocean detail and spot inks cannot be recovered as original mathematical data from that file. This V1.0 package is a manual production reconstruction and must be approved by the trademark owner before designation as the permanent legal master.