Spatial representation with the Python Basemap and PyNGL libraries

Nicolas Barrier

UMR MARBEC

nicolas.barrier@ird.fr

April 4, 2019





Description

The Basemap library is the mapping extension of the standard graphic library

Pros

- It is now quite easy to install by using Anaconda
- Very simple to use
- Multiple map backgrounds can be used (from TIFF image for instance)
- Comes with usefull tool (distance calculations, etc.)

Cons


- Rendering is not always perfect
- No Masked Lambert Conformal projection
- Need to switch from geographical to map coordinates
- Need to navigate between Matplotlib and Basemap methods/functions



Example

```
1 import matplotlib.pyplot as plt
 2 from mpl_toolkits.basemap import Basemap
 4 # map initialisation
   m = Basemap(llcrnrlon=np.min(lon), llcrnrlat=np.min(lat),
 6
               urcrnrlon=np.max(lon), urcrnrlat=np.max(lat),
 7
               projection='cvl', resolution='c')
 8
 9 # conversion from geo. to map coordinate
10 lon2d, lat2d = np.meshgrid(lon, lat) # needs 2D coord. arrays
11 \times v = m(lon2d, lat2d)
12
13 # map background
14 m.fillcontinents(color='gray', lake color='gray')
15
16 # drawing contour lines
17 cs = m.contour(x, y, z, colors='k', linewidths=0.5)
18 plt.clabel(cs. fmt='%.2f')
19
20 # drawing quiver plot
21 g = plt.quiver(x, v, u, v, z, cmap=plt.cm.get cmap('hsv'), scale=1000, zorder
        =1000)
22 a.set clim(0, 50)
23 cb = m.colorbar(q)
24 keys = plt.quiverkey(q, -131, 21, 70,
25
           'Wind speed\n(50 m/s)', coordinates='data')
```

Example



Description

The NCAR Graphic library is a very powerfull library for graphics, especially mapping. It is available in Python through the PyNGL library.

Pros

- It is now quite easy to install by using Anaconda
- Very nice rendering
- The drawing of velocity fields is very easy (curlyvectors, etc.)
- Many examples are provided in the gallery

Cons

- Not compatible with the default Python graphic library Matplotlib
- Heavy code! To use only for paper plots (not for working material)
- Only 256 colors can be used




Simple map

```
import Ngl
   wks_type = "png"
   wks = Ngl.open_wks(wks_type, "conmasklc")
5
6
  res = Ngl.Resources()
  res.nglDraw = False
  res.nglFrame = False
                           = "LambertConformal"
   res.mpProjection
12
  res.mpLimitMode
                           = "LatLon"
                                          # limit map via lat/lon
  res.mpMinLatF
                           = 10.
                                          # map area
  res.mpMaxLatF
                           = 75
                                          # latitudes
16 res.mpMinLonF
                           = 60.
                                          # and
                           = 165.
  res.mpMaxLonF
                                          # longitudes
18
   res.nglMaskLambertConformal = True
   res.nglMaskLambertConformalOutlineOn = True
  res.tiMainString
                            = "Map example"
  res.tiMainFontHeightF
                          = 0.010
24
   map = Ngl.map(wks,res)
26
   Ngl.draw(map)
28 Ngl.frame(wks)
```

Simple map

Map example



More complicated example

366 lines of code later (cf. plot_currents_pyngl.py)...

