

Passed all tests! 🗸

```
1 #include
2 int main()
3 * {
4    int f,i;
5    float a,b;
6    scanf("%d %d %f %f",&f,&i,&a,&b);
7    a=f*12;
8   b=(i+a)*2.54;
9    printf("%0.2f",b);
10    return 0;
11 }
```

Answer: (penalty regime: 0 %)

	architecture.	own.		
		1 -		
	20 1			
		110		
		-		
		16 -		
	STREET	112	4)-00227	
7.76		T		
0	Ln .			
		7	-	
			_	
			-	
			u	
			Input	
			_	
			_	
		-		
		I Comment		
	1.		-	
	_		ш	
	0		•	_ =
			~	- 1
	7		-	
	167.64		Expected	
	170		~	
	0		U	- 4
			2	
	4-0		-	
1		2	_	
			m.	
		- 1	_	
100111		3 1-13	ο.	
			_	-
			- 2-	
	1.1		-	
			Got	
	0	1 -11		
	11.		_	
	~		•	
	A LA LA	4-19	_	I I
		1:		- 83
	O1			
	167.64			- 11
	+			112
				-
				- 1
	,			
				1
	`			
				1
				- 1
				- 6
	N. Comming			


	τ		Ė	
	۵			
Į	,)		
Ş	_	,		
ſ	Ţ	,		
í	Č	2		
1	1	,		
:	_	_		
-	T	Ü	•	
2	τ	۰		
ŗ	Ľ	,		
٤	Ì	2		
ί	,	ï		
•	-	_		
	<			
	•	•		

				<	
			6	100	Input
4	16	600	94	106	Expected
4	16	600	94	106	Got

<pre>#Includexstdio:h> int main() { int a,b; scamf("%d %d",&a,&b); printf("%d",a+b); printf("\n&d",a-b); printf("\n&d",a-b</pre>		. 8 9 10	7 6 5 4	4	1
	return 0;	<pre>printf("\n%d",a*b); printf("\n%d",a/b); printf("\n%d",a%b);</pre>	<pre>scanf("%d %d",&a,&b) printf("%d",a+b); printf("\n%d",a-b);</pre>	<pre>int main() { int a h:</pre>	#include <stdio.h></stdio.h>
		سیوسرد. آزار از از پارای د			
LONGOVO LONGOVO					

```
1 #include<stdio.h>
2 int main()
3 * {
4    int N;
5    float R,D,T;
6    scanf("%d %f %f %f",&N,&R,&D,&T);
7    R=N*3.49;
9    T=R-D;
10    printf("Regular price: %0.2f",R);
11    printf("\nDiscount: %0.2f",D);
12    printf("\nTotal: %.2f",T);
13    return 0;
14 }
```

		✓ 10	
		10	Input
Total: 13.96	Discount: 20.94	Regular price: 34.90 Regular price: 34.90 🗸	Input Expected
Total: 13.96	Discount: 20.94	negular price:	Got
	4	34.90 🗸	



Passed all tests! ✓

€Z

Input Expected Got

<

100

YES

YES

<

<

100


8

8

<

90

Answer: (penalty regime: 0 %)



```
1 #includexstdio.n>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d %d %d",&a,&b,&c);
6     if(a>b && a>c)
7     printf("%d",a);
9     else if(b>a && b>c)
9     printf("%d",b);
10     else
11     printf("%d",c);
12     return 0;
```

W

Passed all tests! ✓