



[Translation Api](#)

## Post Request

Post : {{base\_url}}rest/all/V1/translation

```
{
  "translation": {
    "string": "Augusta Pullover Jacket",
    "translate": "سترة أوغوستا",
    "store_id": "0",
    "locale": "ar_SA"
  }
}
```

## Post Response

```
{
  "id": "1",
  "string": "Augusta Pullover Jacket",
  "translate": "سترة أوغوستا",
  "store_id": "0",
  "locale": "ar_SA"
}
```

- **Id**: Auto Generate Id In Response
- **string** : Original Text for your project
- **Translate** : Translate text for your project
- **Store\_id** : Your store Id (like 0 1 2)
- **Local** : your local store code (like en\_US)

## Get Request

Get : {{base\_url}}rest/all/V1/translation/{Id}

{{base\_url}}rest/all/V1/translation/1

## Get Response

```
{
  "id": "1",
  "string": "Augusta Pullover Jacket",
  "translate": "سترة أوغوستا",
  "store_id": "0",
  "locale": "ar_SA"
}
```

- You can pass the endpoint with id and get response for all value

## Put Request

Put : {{base\_url}}rest/all/V1/translation/{Id}

```
{
  "translation": {
    "id": "1",
    "string": "Augusta Pullover Jacket",
    "translate": "سترة أوغوستا",
    "store_id": "0",
    "locale": "ar_SA"
  }
}
```

## Put Response

```
{  
  "id": "163",  
  "string": "Augusta Pullover Jacket",  
  "translate": "سترة أوغوستا",  
  "store_id": "2",  
  "locale": "ar_SA"  
}
```

- You can change value and check the response

## Delete Request

Delete : `{{base_url}}rest/all/V1/translation/{Id}`

`{{base_url}}rest/all/V1/translation/1`

## Delete Response

`true`

- You can pass the endpoint with id and get response true value it means successfully value