

Homework 7

Labor Economics

Mark Agerton and Nick Frazier

Due Mon, Feb 23

1 Setup

Wages are

$$\begin{aligned} y_0 &= \delta_0 + \beta_0 x + \theta + \epsilon_0 \\ y_1 &= \delta_1 + \beta_1 x + \alpha_1 \theta + \epsilon_1 \end{aligned}$$

Also define the utility shifter function C and an index function I

$$\begin{aligned} C &= \gamma_0 + \gamma_2 z + \gamma_3 x + \alpha_C \theta \\ I &= E[y_1 - y_0 - C | \mathcal{F}] \\ &= \underbrace{(\delta_1 - \delta_0 - \gamma_0)}_{\tilde{\delta}} + \underbrace{(\beta_1 - \beta_0 - \gamma_3)}_{\tilde{\beta}} x_i - \gamma_2 z + \underbrace{(\alpha_1 - 1 - \alpha_C)}_{\tilde{\alpha}} \theta - \epsilon_c \end{aligned}$$

The distribution of shocks is

$$\begin{pmatrix} \epsilon_{i,0} \\ \epsilon_{i,1} \\ \epsilon_{i,C} \end{pmatrix} \bigg|_{x_i, z_i, \theta_i} \sim N \left[\begin{pmatrix} 0 \\ 0 \\ 0 \end{pmatrix}, \begin{pmatrix} \sigma_0^2 & 0 & 0 \\ 0 & \sigma_1^2 & 0 \\ 0 & 0 & \sigma_C^2 \end{pmatrix} \right]$$

The information set for the agent is \mathcal{F} . The preference shock $\epsilon_C \in \mathcal{F}$, but $\{\epsilon_0, \epsilon_1\} \notin \mathcal{F}$. The decision rule is

$$s = 1 \iff E[I \geq 0 | \mathcal{F}]$$

2 Q1

There is no unobserved heterogeneity in this model since we know θ . Thus,

$$E \begin{bmatrix} y_0 \\ y_1 \end{bmatrix} \bigg| x_i, \theta_i, s = k = \begin{bmatrix} \delta_0 + x\beta_0 + \theta \\ \delta_1 + x\beta_1 + \alpha_1 \theta \end{bmatrix} + \underbrace{E \begin{bmatrix} \epsilon_0 \\ \epsilon_1 \end{bmatrix} \bigg| x_i, \theta_i, \epsilon_c : \text{big/small}}_0$$

This is straight-up OLS, which means we recover $\{\delta, \beta, \alpha_1, \sigma_0^2, \sigma_1^2\}$.

$$\begin{aligned} \Pr[S = 1 | \mathcal{F}] &= \Pr \left[\epsilon_c \leq \tilde{\delta} + \tilde{\beta} x - \gamma_2 z + \tilde{\alpha} \theta \bigg| \mathcal{F} \right] \\ &= \Phi \left[\frac{\overbrace{[(\delta_1 - \delta_0) + (\beta_1 - \beta_0)x + (\alpha_1 - 1)\theta]}^{\text{known number}} - \gamma_0 - \gamma_2 z - \gamma_3 x - \alpha_c \theta}{\sigma_c} \bigg| \mathcal{F} \right] \end{aligned}$$

Now we can get $\{\gamma_0, \gamma_2, \gamma_3, \alpha_c, \sigma_c^2\}$

3 Q2

Now we don't know θ but agents do. However, we do have two measurement equations $m \in \{A, B\}$:

$$\begin{aligned} M_{iA} &= x_i^M \beta_A^M + \theta_i + \epsilon_{iA}^M \\ M_{iB} &= x_i^M \beta_B^M + \alpha_B \theta_i + \epsilon_{iB}^M \end{aligned}$$

where $\epsilon_m^M \sim N(0, \sigma_m^{M2})$ are i.i.d.

3.1 Heckman two-step

We can write

$$\begin{aligned} E[y_1|x, z, s = 1] &= \delta_1 + \beta_1 x + E[\epsilon_1 + \alpha_1 \theta | x, z, I \geq 0] \\ &= \delta_1 + \beta_1 x + \alpha_1 E[\theta | x, z, I \geq 0] \\ &= \delta_1 + \beta_1 x + \alpha_1 \sigma^* E \left[\frac{\theta}{\sigma^*} \middle| 0 \leq \tilde{\delta} + \tilde{\beta} x - \gamma_2 z + \underbrace{(\alpha_1 - \alpha_0 - \alpha_c)\theta - \epsilon_c}_{\eta} \right] \\ &= \delta_1 + \beta_1 x + \alpha_1 \sigma^* E \left[\frac{\theta}{\sigma^*} \middle| \eta \geq -(\tilde{\delta} + \tilde{\beta} x - \gamma_2 z) \right] \end{aligned}$$

Define $\eta \equiv (\alpha_1 - \alpha_0 - \alpha_c)\theta - \epsilon_c$. Then

$$\begin{pmatrix} \eta \\ \theta \end{pmatrix} \sim N \left[\begin{pmatrix} 0 \\ 0 \end{pmatrix}, \begin{pmatrix} \sigma^{*2} & (\alpha_1 - \alpha_0 - \alpha_c)\sigma_\theta^2 \\ (\alpha_1 - \alpha_0 - \alpha_c)\sigma_\theta^2 & \sigma_\theta^2 \end{pmatrix} \right]$$

where $\sigma^{*2} = (\alpha_1 - \alpha_0 - \alpha_c)^2 \sigma_\theta^2 + \sigma_c^2$. We can project θ onto η , which means

$$\theta = \frac{\text{Cov}(\eta, \theta)}{\text{Var} \eta} \eta + \nu = \frac{(\alpha_1 - \alpha_0 - \alpha_c)\sigma_\theta^2}{\sigma^{*2}} \eta + \nu$$

where

$$\nu \sim N(0, \sigma_\theta^2 (1 - \rho_{\eta\theta}^2)) \quad \text{and} \quad \rho_{\eta\theta} = \frac{(\alpha_1 - \alpha_0 - \alpha_c)\sigma_\theta^2}{\sigma^* \sigma_\theta}$$

3.1.1 Step 1

We know that $S = 1 \Leftrightarrow \eta \geq -(\tilde{\delta} + \tilde{\beta}X - \tilde{\gamma}Z) + \eta \geq 0$. So, in the first step of the procedure, we estimate

$$\begin{aligned} \Pr[S = 1 | \mathcal{F}] &= 1 - \Phi \left[\frac{\overbrace{\delta_1 - \delta_0 - \gamma_0}^{\tilde{\delta}}}{\sigma^*} + \frac{\overbrace{\beta_1 - \beta_0 - \gamma_3}^{\tilde{\beta}}}{\sigma^*} X - \frac{\overbrace{\gamma_2}^{\tilde{\gamma}}}{\sigma^*} Z \right] \\ &= 1 - \Phi [\tilde{\delta} + \tilde{\beta}X - \tilde{\gamma}_2 Z] \end{aligned}$$

This gives us $\{\tilde{\delta}, \tilde{\beta}, \tilde{\gamma}\}$.

3.2 Step 2

Letting $t \equiv -(\tilde{\delta} + \tilde{\beta}X - \tilde{\gamma}Z)$, we can now write

$$\begin{aligned}
E[y_0|x, z, s = 1] &= \delta_0 + \beta_0 x + \alpha_0 \frac{(\alpha_1 - \alpha_0 - \alpha_c)\sigma_\theta^2}{\sigma^*} \overbrace{\frac{-\phi(t)}{\Phi(t)}}^{\lambda_0} \\
&= \delta_0 + \beta_0 x + \alpha_0 (\rho_{\eta\theta}\sigma_\theta) \lambda_{0i} \\
E[y_1|x, z, s = 1] &= \delta_1 + \beta_1 x + \alpha_1 \frac{(\alpha_1 - \alpha_0 - \alpha_c)\sigma_\theta^2}{\sigma^*} \underbrace{\frac{\phi(t)}{1 - \Phi(t)}}_{\lambda_1} \\
&= \delta_1 + \beta_1 x + \alpha_1 (\rho_{\eta\theta}\sigma_\theta) \lambda_{1i}
\end{aligned}$$

This gives us estimates for $\{\delta_0, \delta_1, \beta_0, \beta_1, (\alpha_0 \rho_{\eta\zeta} \sigma_\theta), (\alpha_1 \rho_{\eta\zeta} \sigma_\theta)\}$

3.3 Step 3

Now we can use the covariances. We have

$$\begin{aligned}
\text{Cov}(Y_0 - \delta_0 - \beta_0 X, M^A - \beta_A X^M) &= \text{Cov}(Y_0, M^A | X, X^M, Z) &= \alpha_0 \sigma_\theta^2 \\
\text{Cov}(Y_0 - \delta_0 - \beta_0 X, M^B - \beta_B X^M) &= \text{Cov}(Y_0, M^B | X, X^M, Z) &= \alpha_0 \alpha_B \sigma_\theta^2 \\
\text{Cov}(Y_1 - \delta_1 - \beta_1 X, M^A - \beta_A X^M) &= \text{Cov}(Y_1, M^A | X, X^M, Z) &= \alpha_1 \sigma_\theta^2 \\
\text{Cov}(Y_1 - \delta_1 - \beta_1 X, M^B - \beta_B X^M) &= \text{Cov}(Y_1, M^B | X, X^M, Z) &= \alpha_1 \alpha_B \sigma_\theta^2 \\
\text{Cov}(M^A - \beta_A X^M, M^B - \beta_B X^M) &= \text{Cov}(M^A, M^B | X^M) &= \alpha_B \sigma_\theta^2
\end{aligned}$$

We use these covariances to identify the rest of the model.

$$\begin{aligned}
\widehat{\alpha_0/\alpha_1} &= (\alpha_0 \rho \sigma_\theta^2) / (\alpha_0 \rho \sigma_\theta^2) \\
\widehat{\alpha_B} &= \text{Cov}(Y_0, M^B) / \text{Cov}(Y_0, M^A) \\
\widehat{\sigma_\theta^2} &= \text{Cov}(M^A, M^B) / \widehat{\alpha_B} \\
\widehat{\alpha_0} &= \text{Cov}(Y_0, M^A) \\
\widehat{\alpha_1} &= \text{Cov}(Y_1, M^B) \\
\widehat{\sigma_A^2} &= \text{Var}(M^A) - \sigma_\theta^2 \\
\widehat{\sigma_B^2} &= \text{Var}(M^B) - \widehat{\alpha_B^2} \widehat{\sigma_\theta^2} \\
\widehat{\rho} &= \widehat{\alpha_0(\rho \sigma_\theta)} / (\widehat{\alpha_0} \sqrt{\widehat{\sigma_\theta^2}}) \\
&= \widehat{\alpha_1(\rho \sigma_\theta)} / (\widehat{\alpha_1} \sqrt{\widehat{\sigma_\theta^2}}) \\
\widehat{\sigma_0^2} &= \text{Var}(Y_0) - \widehat{\alpha_0(\rho \sigma_\theta)}^2 \left[1 - t\widehat{\lambda_0} + \widehat{\lambda_0^2} \right] - \widehat{\sigma_\theta^2} (1 - \widehat{\rho}^2) \\
\widehat{\sigma_1^2} &= \text{Var}(Y_1) - \widehat{\alpha_1(\rho \sigma_\theta)}^2 \left[1 - t\widehat{\lambda_1} + \widehat{\lambda_1^2} \right] - \widehat{\sigma_\theta^2} (1 - \widehat{\rho}^2) \\
\widehat{\alpha_c} &= \left\{ \alpha_c \in R \mid (\widehat{\rho \sigma_\theta}) - (\widehat{\alpha_1} - \widehat{\alpha_0} - \alpha_c) \widehat{\sigma_\theta^2} [(\widehat{\alpha_1} - \widehat{\alpha_0} - \alpha_c)^2 \widehat{\sigma_\theta^2} + 1]^{-1/2} = 0 \right\} \\
\widehat{\gamma_0} &= \left(\widehat{\delta_1} - \widehat{\delta_0} \right) - \widehat{\delta} \times \widehat{\sigma^*} \\
\widehat{\gamma_3} &= \left(\widehat{\beta_1} - \widehat{\beta_0} \right) - \widehat{\beta} \times \widehat{\sigma^*} \\
\widehat{\gamma_2} &= \widehat{\gamma} \times \widehat{\sigma^*}
\end{aligned}$$

3.4 MLE approach

The contribution to the likelihood of any given individual i is now the product of the likelihood of the wage and choice times the product of the likelihoods of the test equations.

$$\begin{aligned}
L_i &= [f(y_{1i}|X, \theta, s_i = 1) \Pr(s_i = 1|X, Z, \theta)]^{s_i} \\
&\quad \times [f(y_{0i}|X, \theta, s_i = 0) \Pr(s_i = 0|X, Z, \theta)]^{1-s_i} \\
&\quad \times f(m_i^A|X_i^M, \theta) \\
&\quad \times f(m_i^B|X_i^M, \theta) \\
&\quad \times f(\theta)
\end{aligned}$$

Define $q_i \equiv 2s_i - 1$. Since we only observe y_{1i} or y_{i0} , we simply use y_i in the likelihood equation. We can log everything and integrate w/ respect to θ .

$$\begin{aligned}\mathcal{L}_i = & \int_{\theta} \log \left[1 - \Phi \left(q_i \times \frac{(\delta_1 - \delta_0 - \gamma_0) + (\beta_1 - \beta_0 - \gamma_3)X_i - \gamma_2 Z_i + (\alpha_1 - \alpha_0 - \alpha_c)\theta}{\sigma_c} \right) \right] \\ & + s_i \log \left[\phi \left(\frac{y_i - \delta_1 - \beta_1 x_i - \alpha_1 \theta}{\sigma_1} \right) \right] \\ & + (1 - s_i) \log \left[\phi \left(\frac{y_i - \delta_0 - \beta_0 x_i - \alpha_0 \theta}{\sigma_0} \right) \right] \\ & + \log \left[\phi \left(\frac{M_i^A - X_i^M \beta_A - \theta}{\sigma_A} \right) \right] \\ & + \log \left[\phi \left(\frac{M_i^B - X_i^M \beta_B - \alpha_B \theta}{\sigma_B} \right) \right] \\ & + \log \left[\phi \left(\frac{\theta}{\sigma_{\theta}} \right) \right] d\theta\end{aligned}$$

We maximize the $\sum_{i=1}^N \sum_{j=1}^J w_j \mathcal{L}_i(\theta_j) \phi \left(\frac{\theta_j}{\sigma_{\theta}} \right)$. To update σ_{θ} , we do

$$(\sigma_{\theta}^2)^{(t)} = \text{Var} \left(\frac{(\hat{Y}_i - Y_i) + (\hat{M}_i^A - M_i^A) + (\hat{M}_i^B - M_i^B)}{3} \right)$$

4 Q4

We lose equations 1, 2 and 7. Additionally, we are more likely to observe one side of the distribution of θ now since agents select on θ . Thus, we need to include a control function in our measurement equations and the analogous component of the likelihood equation. If we do this, we still have identification because we can use

$$\frac{\text{Cov} \left[I - \tilde{\delta} - \tilde{\beta}x - \gamma_2 z, (Y_1 - X\beta_1) \right]}{\text{Cov} \left[I - \tilde{\delta} - \tilde{\beta}x - \gamma_2 z, (M^A - X^M \beta_A) \right]} = \alpha_1$$

Ta-da!




Figure 1: Histograms

5 Results

Listing 1: Results

```
-----
Results for Homework 5
Started run at 2015-02-24T10:24:13
-----

No outer product for probit
Two-step parameters
   $\delta_0$     = 1.48
   $\beta_0$     = 1.97
   $\pi_0$      = 0.26

   $\delta_0_{se}$  = 0.04
   $\beta_0_{se}$  = 0.01
   $\pi_0_{se}$   = 0.03

   $\delta_1$     = 0.98
   $\beta_1$     = 2.99
   $\pi_1$      = 0.59

   $\delta_1_{se}$  = 0.05
   $\beta_1_{se}$  = 0.03
   $\pi_1_{se}$   = 0.06

Cov of outcome and measurements from two-step
  cov_0_A = 2.71
  cov_0_B = 2.58
  cov_1_A = 2.89
  cov_1_B = 2.89

Final Parameters
   $\alpha_B$    = 0.952

   $\sigma_\theta$  = 1.975

   $\alpha_1$    = 0.742

   $\alpha_0$    = 0.695

   $\sigma_{A_{sq}}$  = -1.497

   $\sigma_B$    = 0.491

   $\gamma_0$    = 0.257

   $\gamma_1$    = 0.592

   $\gamma_3$    = -0.538

   $\rho_{\eta\theta}$  = 0.191 # using  $\rho_{\eta\theta_0}$ 

   $\sigma_0$    = [13.199]

   $\sigma_1$    = [14.127]

   $\alpha_c$    = -0.051

   $\sigma_c$    = 1.0 # normalize  $\sigma_c = 1$ 

Incidental parameters
 $\sigma_{star}$  = 1.019

 $\rho_{\eta\theta_0}$  = 0.191
```

```

    rho_eta_1 = 0.4
Two-step parameters
    delta_0    = 1.48
    beta_0     = 1.97
    pi_0       = 0.26

    delta_0_se = 0.04
    beta_0_se  = 0.01
    pi_0_se    = 0.03

    delta_1    = 0.98
    beta_1     = 2.99
    pi_1       = 0.59

    delta_1_se = 0.05
    beta_1_se  = 0.03
    pi_1_se    = 0.06

```

```

-----
Finished run at 2015-02-24T10:24:14
-----

```

6 Main call

Listing 2: Main call

```

using DataFrames
using Distributions
using Optim
using Dates
using Roots

doLog = false
originalSTDOUT = STDOUT

if doLog == true
    (outRead, outWrite) = redirect_stdout()
    println("-----")
    println("Results for Homework 5\nStarted run at " * string(now()))
    println("-----")
end

#####
##### Structure of Code
#####
# Process data
# OLS
# Run probit
#   # Probit value function
#   # Probit gradient
#   # Probit hessian
# Process Probit results
# recover structural parameters
# estimate variance of structural parameters
# EM algorithm

#####
##### Basic Parameters
#####
dir = "C:/Users/Nick/SkyDrive/One_data/LaborEcon/PS7/"
# dir = "C:/mja3/SkyDrive/Rice/Class/econ515-Labor/PS7/"
fs  = "data_ps7_spring2015.raw"

cd(dir)

```



```

namevec = [symbol("id"),symbol("S"),symbol("Y"),symbol("M_a"),symbol("M_b"),symbol("X"),symbol("Z"),symbol("X_m")]
data = readtable(fs, separator = ' ', header = true, names = namevec)

cd("./code/")
include("./functions.jl")

#####
##### Process Data
#####

# TODO flip data to make it (obs x var)

N = int(size(data,1))
N_1 = sum(data[:S])
N_0 = N - N_1

# create constant
data[:C] = vec(ones(N,1))

data[:Y_0] = NaN
data[:Y_1] = NaN
data[data[:S] .== 1,:Y_0] = data[data[:S] .== 1,:Y]
data[data[:S] .== 0,:Y_1] = data[data[:S] .== 0,:Y]

sel0 = data[:S] .== 0
sel1 = data[:S] .== 1

K_A = 2
K_B = 2
numparams = 10 # just a guess

#####
##### Step 1
#####

# notice that they all have the same mean
# mean(data[:M_a])
# mean(data[:M_b])
# mean(data[:X_m])

# OLS on measurement equations
( $\beta_A, \sigma_a, VCV_a$ ) = least_sq(data[:X_m],data[:M_a])
se_β_A = sqrt(VCV_a)

( $\beta_B, \sigma_b, VCV_b$ ) = least_sq(data[:X_m],data[:M_b])
se_β_B = sqrt(VCV_b)

# TODO publish params

#####
##### Heckman 2-step
#####

# Step 1: Probit
# probit data
X = [vec(data[:C]) vec(data[:X]) vec(data[:Z])]
d = convert(Array,data[:S])

# optimization
iters = 1
f = probit_LL
g! = probit_gradient!
h! = probit_hessian!

initials = squeeze( (X'X)\X'd, 2).*2.*rand(size(X,2))

```

```

probit_opt = []
for kk = 1:iters
    probit_opt = Optim.optimize(f,g!,h!,vec(initials),
        xtol = 1e-32,
        ftol = 1e-32,
        grtol = 1e-14,
        iterations = 3000)
    initials = probit_opt.minimum
end
probit_opt

probit_res      = probit_results(probit_opt.minimum,g!,h!)
param_probit    = probit_res["θ"]
param_probit_se = probit_res["std_hess"]
VCV_probit      = probit_res["vcv_hessian"]
param_probit_z  = probit_res["z_stat"]
param_probit_pval = probit_res["pvals"]
# probit_res["ME1"]
# probit_res["ME2"]

# Step 2: OLS

t = -(X*param_probit)
λ_0 = -normpdf(t)./normcdf(t)
λ_1 = normpdf(t)./(1-normcdf(t))

# Y_0
Y0 = convert(Array,data[sel0,:Y])
X0 = [vec(data[sel0,:C]) vec(data[sel0,:X]) λ_0[sel0] ]

(p_0,~,VCV_p_0) = least_sq(X0,Y0)
se_p_0 = sqrt(diag(VCV_p_0))

# Y_1
Y1 = convert(Array,data[sel1,:Y])
X1 = [vec(data[sel1,:C]) vec(data[sel1,:X]) λ_1[sel1] ]

(p_1,~,VCV_p_1) = least_sq(X1,Y1)
se_p_1 = sqrt(diag(VCV_p_1))

# publish params
δ_0 = p_0[1]
β_0 = p_0[2]
π_0 = p_0[3]
δ_0_se = se_p_0[1]
β_0_se = se_p_0[2]
π_0_se = se_p_0[3]
δ_1 = p_1[1]
β_1 = p_1[2]
π_1 = p_1[3]
δ_1_se = se_p_1[1]
β_1_se = se_p_1[2]
π_1_se = se_p_1[3]

println("Two-step parameters
    δ_0 = $(round( p_0[1] , 2 ))
    β_0 = $(round( p_0[2] , 2 ))
    π_0 = $(round( p_0[3] , 2 ))

    δ_0_se = $(round( se_p_0[1], 2 ))
    β_0_se = $(round( se_p_0[2], 2 ))
    π_0_se = $(round( se_p_0[3], 2 ))

    δ_1 = $(round( p_1[1] , 2 ))
    β_1 = $(round( p_1[2] , 2 ))
    π_1 = $(round( p_1[3] , 2 ))

```

```

    δ_1_se = $(round( se_p_1[1], 2 ))
    β_1_se = $(round( se_p_1[2], 2 ))
    π_1_se = $(round( se_p_1[3], 2 )) \n " )

#####
##### Recover some more parameters
#####

# cannot get gammas? Need them for next step. Estimate of I

#####
##### Use covariances
#####

Y_0_Xβ = convert(Array,data[sel0,:Y])
- [vec(data[sel0,:C]) vec(data[sel0,:X])]*[δ_0; β_0]
Y_1_Xβ = convert(Array,data[sel1,:Y])
- [vec(data[sel1,:C]) vec(data[sel1,:X])]*[δ_1; β_1]
M_A0_Xβ = convert(Array,data[sel0,:M_a])
- vec(data[sel0,:X_m]).*β_A
M_B0_Xβ = convert(Array,data[sel0,:M_b])
- vec(data[sel0,:X_m]).*β_B
M_A1_Xβ = convert(Array,data[sel1,:M_a])
- vec(data[sel1,:X_m]).*β_A
M_B1_Xβ = convert(Array,data[sel1,:M_b])
- vec(data[sel1,:X_m]).*β_B
M_A_Xβ = convert(Array,data[:M_a])
- vec(data[:X_m]).*β_A
M_B_Xβ = convert(Array,data[:M_b])
- vec(data[:X_m]).*β_B

cov_0_A = (1/N_0)*sum(Y_0_Xβ'*M_A0_Xβ)
cov_0_B = (1/N_0)*sum(Y_0_Xβ'*M_B0_Xβ)
cov_1_A = (1/N_1)*sum(Y_1_Xβ'*M_A1_Xβ)
cov_1_B = (1/N_1)*sum(Y_1_Xβ'*M_B1_Xβ)
cov_A_B = (1/N)*sum(M_A_Xβ'*M_B_Xβ)

α_B = cov_0_B/cov_0_A
σ_θ = sqrt(cov_A_B/α_B)
α_1 = cov_1_A/(σ_θ^2)
α_0 = cov_0_A/(σ_θ^2)

# σ_A = sqrt( var(convert(Array,data[:M_a])) - σ_θ^2 )
#####
σ_A_sq = var(convert(Array,data[:M_a])) - σ_θ^2 ### < NEGATIVE VARIANCE
σ_B = sqrt( var(convert(Array,data[:M_b])) - α_B^2*σ_θ^2 )

ρ_ηθ_0 = π_0 / (α_0*σ_θ)
ρ_ηθ_1 = π_1 / (α_1*σ_θ)
#####
ρ_ηθ = ρ_ηθ_0 # ρ_ηθ_1 ##### < NOT THE SAME NUMEBR

δ_t_0 = λ_0[sel0]*(λ_0[sel0] - t[sel0])
σ_0 = sqrt(
    var(convert(Array,data[sel0,:Y])) - α_0^2.*(ρ_ηθ*σ_θ)^2*
    (1 - δ_t_0) - σ_θ^2*(1 - ρ_ηθ^2)
) # variance on income. Large

δ_t_1 = λ_1[sel1]*(λ_1[sel1] - t[sel1])
σ_1 = sqrt(
    var(convert(Array,data[sel1,:Y])) - α_1^2.*(ρ_ηθ*σ_θ)^2*
    (1 - δ_t_1) - σ_θ^2*(1 - ρ_ηθ^2)
) # variance on income. Large

f_c(α_c) = ρ_ηθ*σ_θ - (α_1 - α_0 - α_c)*σ_θ^2*(
    (α_1 - α_0 - α_c)^2*σ_θ^2 + 1)^(-.5)

```

```

α_c = fzero(f_c, -1000, 1000)

# normalize σ_c =1
σ_c = 1

σ_star = sqrt( (α_1 - α_0 - α_c)^2*σ_θ^2 + σ_c^2)

γ_0 = δ_1 - δ_0 - param_probit[1]*σ_star
γ_1 = β_1 - β_0 - param_probit[2]*σ_star
γ_3 = param_probit[3]*σ_star

# these are wrong b/c ignore variance of σ_star
# (b/c it looks hard)
V(kk) =[VCV_ρ_1[kk]      0      0;
        0      VCV_ρ_0[kk]      0;
        0      0      VCV_probit[kk]]
γ_0_se = [1 -1 -1]*V(1)*[1 -1 -1]'
γ_1_se = [1 -1 -1]*V(2)*[1 -1 -1]'
γ_3_se = [0  0  1]*V(3)*[0  0  1]'

println("Cov of outcome and measurements from two-step
cov_0_A = $(round(cov_0_A, 2))
cov_0_B = $(round(cov_0_B, 2))
cov_1_A = $(round(cov_1_A, 2))
cov_1_B = $(round(cov_1_B, 2)) \n")

println("Final Parameters
α_B   = $(round(α_B   ,3))
σ_θ   = $(round(σ_θ   ,3))
α_1   = $(round(α_1   ,3))
α_0   = $(round(α_0   ,3))
σ_A_sq = $(round(σ_A_sq,3)) squared: $(round(NaN,3))
σ_B   = $(round(σ_B   ,3)) squared: $(round(σ_B.^2,3))
γ_0   = $(round(γ_0   ,3))
γ_1   = $(round(γ_1   ,3))
γ_3   = $(round(γ_3   ,3))

ρ_ηθ   = $(round(ρ_ηθ   ,3)) # using ρ_ηθ_0

σ_θ   = $(round(σ_θ   ,3)) squared: $(round(σ_θ.^2,3))
σ_1   = $(round(σ_1   ,3)) squared: $(round(σ_1.^2,3))
α_c   = $(round(α_c   ,3))
σ_c   = $(round(σ_c   ,3)) # normalize σ_c =1

Incidental parameters
σ_star = $(round(σ_star,3))
ρ_ηθ_0 = $(round(ρ_ηθ_0,3))
ρ_ηθ_1 = $(round(ρ_ηθ_1,3))")

# #####
# ##### EM algorithm
# #####

# include("./HG_wts.jl")

# σ_θ = 1
# initials = ones(18)
# initials[1:4] = [ρ_0[1] ρ_1[1] ρ_0[2] ρ_1[2]]
# opt_out = []

```

```

# println("Doing EM!\n")

# # Loop w/ "while (abs( opt_out.f_minimum - opt_out_old.f_minimum ) > ftol) || (count < maxit)
# " ?
# for i = 1:5

#   global count = 0
#   println("\n -----Update $i:  $\sigma_\theta = \sigma_\theta$  ----- \n\n")

#   opt_out = Optim.optimize(wtd_LL,vec(initials),
#   #     xtol = 1e-32,
#   #     ftol = 1e-32,
#   #     grtol = 1e-14,
#   #     iterations = 500,
#   #     autodiff=true)

#   initials = opt_out.minimum

#   println("\nResults: \t $opt_out \n\n")

#   update = unpackparams(opt_out.minimum)
#    $\delta_0$  = update[" $\delta_0$ "]
#    $\delta_1$  = update[" $\delta_1$ "]
#    $\beta_0$  = update[" $\beta_0$ "]
#    $\beta_1$  = update[" $\beta_1$ "]
#    $\alpha_0$  = update[" $\alpha_0$ "]
#    $\alpha_1$  = update[" $\alpha_1$ "]
#    $\alpha_C$  = update[" $\alpha_C$ "]
#    $\beta_A$  = update[" $\beta_A$ "]
#    $\alpha_B$  = update[" $\alpha_B$ "]
#    $\beta_B$  = update[" $\beta_B$ "]

#   Y0      = convert(Array,data[sel0,:Y])
#   X0      = [vec(data[sel0,:C]) vec(data[sel0,:X])]
#   Y1      = convert(Array,data[sel1,:Y])
#   X1      = [vec(data[sel1,:C]) vec(data[sel1,:X])]

#   # Form an updated estimate for  $\theta_{\text{hat}}$ 
#    $\theta_{\text{hat}}$  = zeros(N)
#    $\theta_A$  = data[:M_a] - data[:X_m] .*  $\beta_A$ 
#    $\theta_B$  = (data[:M_b] - data[:X_m] .*  $\beta_B$ )./ $\alpha_B$ 
#    $\theta_{\text{hat}}[\text{sel1}] = (1/3) .* ( \theta_A[\text{sel1}] + \theta_B[\text{sel1}] +$ 
#   #       ( (Y1 - X1* $[\delta_1; \beta_1]$ ) )./ $\alpha_1$  )
#    $\theta_{\text{hat}}[\text{sel0}] = (1/3) .* ( \theta_A[\text{sel0}] + \theta_B[\text{sel0}] +$ 
#   #       ( (Y0 - X0* $[\delta_0; \beta_0]$ ) )./ $\alpha_0$  )
#    $\sigma_\theta$  = sqrt(var( $\theta_{\text{hat}}$ ))

#   println("\t
#   #    $\delta_0 = \$(\text{round}(\text{opt\_out.minimum}[1] , 2))$ 
#   #    $\delta_1 = \$(\text{round}(\text{opt\_out.minimum}[2] , 2))$ 
#   #    $\beta_0 = \$(\text{round}(\text{opt\_out.minimum}[3] , 2))$ 
#   #    $\beta_1 = \$(\text{round}(\text{opt\_out.minimum}[4] , 2))$ 

#   #    $\gamma_0 = \$(\text{round}(\text{opt\_out.minimum}[5] , 2))$ 
#   #    $\gamma_2 = \$(\text{round}(\text{opt\_out.minimum}[6] , 2))$ 
#   #    $\gamma_3 = \$(\text{round}(\text{opt\_out.minimum}[7] , 2))$ 

#   #    $\alpha_0 = \$(\text{round}(\text{opt\_out.minimum}[8] , 2))$ 
#   #    $\alpha_1 = \$(\text{round}(\text{opt\_out.minimum}[9] , 2))$ 
#   #    $\alpha_C = \$(\text{round}(\text{opt\_out.minimum}[10] , 2))$ 

#   #    $\sigma_C = \$(\text{round}(\text{opt\_out.minimum}[11] , 2))$ 
#   #    $\sigma_1 = \$(\text{round}(\text{opt\_out.minimum}[12] , 2))$ 
#   #    $\sigma_2 = \$(\text{round}(\text{opt\_out.minimum}[13] , 2))$ 

#   #    $\alpha_A = 1$  (normalized)
#   #    $\beta_A = \$(\text{round}(\text{opt\_out.minimum}[14] , 2))$ 
#   #    $\sigma_A = \$(\text{round}(\text{opt\_out.minimum}[15] , 2))$ 

```

```

#    $\alpha_B = \$(round(opt\_out.minimum[16] , 2))$ 
#    $\beta_B = \$(round(opt\_out.minimum[17] , 2))$ 
#    $\sigma_B = \$(round(opt\_out.minimum[18] , 2))$ 

# end

if doLog == true

    println("-----")
    println("Finished run at " * string(now()))
    println("-----")

    close(outWrite)
    stringOut = readavailable(outRead)
    close(outRead)
    redirect_stdout(originalSTDOUT)

    f = open("../Hwk7-Results.txt", "w")
    write(f, stringOut )
    close(f)

    println(stringOut)
end

```

7 Functions and weights

Listing 3: Functions used

```

# functions

# least_sq
# pdf wrappers
# Probit

#####
##### Process Data
#####

function least_sq(X::Array,Y::Array;N=int(size(X,1)), W=1)
    l = minimum(size(X))
    A = X'*W*X
    if sum(size(A))== 1
        inv_term = 1./A
    else
        inv_term = A\eye(int(size(X,2)))
    end
     $\beta$  = inv_term * X'*W*Y
    if l == 1
        sigma_hat = sqrt(sum((1/N).* (Y - ( $\beta$ *X'))'*(Y - ( $\beta$ *X'))' ) ) #sum converts to Float64
    else
        sigma_hat = sqrt(sum((1/N).* (Y - (X* $\beta$ ))'*(Y - (X* $\beta$ ))' ) ) #sum converts to Float64
    end
    VCV = (sigma_hat).^2 * inv_term * eye(l)
    return  $\beta$ , sigma_hat, VCV
end

function least_sq(X::DataArray,Y::DataArray;N=int(size(X,1)), W=1)
    l = minimum( [size(X,2),size(X,1)] ) # b/c array has size 0
    X = convert(Array{Float64,1},X)
    Y = convert(Array{Float64,1},Y)
    A = X'*W*X
    if sum(size(A))== 1
        inv_term = 1./A
    else
        inv_term = A\eye(int(size(X,2)))
    end
     $\beta$  = inv_term * X'*W*Y
    if l == 1
        sigma_hat = sqrt(sum((1/N).* (Y - ( $\beta$ *X'))'*(Y - ( $\beta$ *X'))' ) ) #sum converts to Float64
    else
        sigma_hat = sqrt(sum((1/N).* (Y - (X* $\beta$ ))'*(Y - (X* $\beta$ ))' ) ) #sum converts to Float64
    end
    VCV = (sigma_hat).^2 * inv_term * eye(l)
    return  $\beta$ , sigma_hat, VCV
end

```

```

else
    inv_term = A\eye(int(size(X,2)))
end
 $\beta$  = inv_term * X'*W*Y
if l == 1
    sigma_hat = sqrt(sum((1/N).* (Y - ( $\beta$ *X'))'*(Y - ( $\beta$ *X')) ) ) #sum converts to Float64
else
    sigma_hat = sqrt(sum((1/N).* (Y - (X* $\beta$ ))'*(Y - (X* $\beta$ )) ) ) #sum converts to Float64
end
VCV = (sigma_hat).^2 * inv_term * eye(1)
return  $\beta$ , sigma_hat, VCV
end

#####
##### pdf wrappers
#####

## Normal PDF
function normpdf(x::Union{Vector{Float64}, Float64, DataArray}; mean=0, var=1) # a type-union
    should work here and keep code cleaner
    out = Distributions.pdf(Distributions.Normal(mean, var), x)
    out + (out .== 0.0)*eps(1.0) - (out .== 1.0)*eps(1.0)
end

## Normal CDF
function normcdf(x::Union{Vector{Float64}, Float64, DataArray}; mean=0, var=1)
    out = Distributions.cdf(Distributions.Normal(mean, var), x)
    out + (out .== 0.0)*eps(1.0) - (out .== 1.0)*eps(1.0)
end

#####
##### Probit
#####

function  $\lambda$ ( $\theta$ ::Vector{Float64})
    q = 2d-1
    q .* normpdf(q .* X* $\theta$ ) ./ normcdf(q.*X* $\theta$ )
end

function probit_LL( $\theta$ ::Vector{Float64})
    out = - sum( log( normcdf( (2d-1) .* X* $\theta$ ) ) )
end

function probit_LL_g( $\theta$ ::Vector{Float64}, grad::Vector{Float64})
    out = - sum( log( normcdf( (2d-1) .* X* $\theta$ ) ) )
    if length(grad) > 0
        grad[:] = - sum(  $\lambda$ ( $\theta$ ) .* X, 1 )
    end
    out
end

function probit_gradient!( $\theta$ ::Vector{Float64}, grad::Vector{Float64})
    grad[:] = - sum(  $\lambda$ ( $\theta$ ) .* X, 1 )
end

function probit_hessian!( $\theta$ ::Vector{Float64}, hessian::Matrix{Float64})
    hh = zeros(size(hessian))
    A =  $\lambda$ ( $\theta$ ) .* (  $\lambda$ ( $\theta$ ) + X* $\theta$  )
    for i in 1:size(X)[1]
        hh += A[i] * X[i,:]'*X[i,:]
    end
    hessian[:] = hh
end

function probit_vcov_score( $\theta$ ::Vector{Float64}, g!)
    K = length( $\theta$ )
    N = maximum(size(X))

```

```

    score = zeros(K,1)
    g!(θ, score)
    vcv_hessian = N*(score*score') \ eye(K)
end

function probit_vcov_hessian(θ::Vector{Float64}, h!)
    K = length(θ)
    hessian = zeros((K,K))
    h!(θ, hessian)
    vcv_hessian = N*(hessian\eye(K))
end

function probit_results(θ::Vector, g!, h!)

    K = length(θ)

    vcv_hessian = repmat([NaN],K,K)
    try
        vcv_hessian = probit_vcov_hessian(θ, h!)
    catch
        println("No hessian for probit")
    end

    vcv_score = repmat([NaN],K,K)
    try
        vcv_score = probit_vcov_score(θ, g!)
    catch
        println("No outer product for probit")
    end

    std_h = sqrt(diag(vcv_hessian))
    std_s = sqrt(diag(vcv_score))

    z_stat = θ./std_h
    pvals = Distributions.cdf(Distributions.Normal(), -abs(z_stat))

    X_bar = mean(X,1)
    # # Partial Effect at the Average
    ME1 = normpdf(vec(X_bar'.*θ)) .* θ
    # # Average Partial Effect (pg. 5)
    ME2 = mean( normpdf( vec(X*θ) ) ) * θ

    return [
        "θ"=>θ,
        "std_hess" => std_h, "std_score" => std_s,
        "vcv_hessian" => vcv_hessian, "vcv_score" => vcv_score,
        "z_stat"=> z_stat, "pvals"=> pvals,
        "ME1"=>ME1, "ME2"=>ME2]
end

#####
##### EM algorithm
#####

function wtd_LL(p::Vector{Float64})
    NN = length(X)
    ll = zeros(NN,N)
    for (j,x_j) in enumerate(X)
        # Should weights be additive?
        ll[j,:] = W[j] .* ( LL_term(p, σ_θ .* x_j) + normpdf(x_j) )'
    end

    out = - sum(ll)
    countPlus!( out )
    return(out)
end

function LL_term(p::Vector{Float64}, x::Float64)

```



```

θ = x.*ones(N)
out = unpackparams(p)
δ_0 = out["δ_0"]
δ_1 = out["δ_1"]
β_0 = out["β_0"]
β_1 = out["β_1"]
γ_0 = out["γ_0"]
γ_2 = out["γ_2"]
γ_3 = out["γ_3"]
α_0 = out["α_0"]
α_1 = out["α_1"]
α_C = out["α_C"]
σ_C = out["σ_C"]
σ_1 = out["σ_1"]
σ_2 = out["σ_2"]
β_A = out["β_A"]
α_B = out["α_B"]
σ_A = out["σ_A"]
β_B = out["β_B"]
σ_B = out["σ_B"]

Y0 = convert(Array,data[sel0,:Y])
X0 = [vec(data[sel0,:C]) vec(data[sel0,:X]) θ[sel0]]
Y1 = convert(Array,data[sel1,:Y])
X1 = [vec(data[sel1,:C]) vec(data[sel1,:X]) θ[sel1]]
q = 2.*convert(Array,data[:S]) -1

φ_M_A = normpdf( (data[:M_a] - data[:X_m].*β_A - θ) ./σ_A)
φ_M_B = normpdf( (data[:M_b] - data[:X_m].*β_B - θ*α_B)./σ_B)

φ_1 = φ_0 = zeros(N)
φ_1[sel1] = normpdf( (Y1 - X1 * [δ_1; β_1; α_1]) ./ σ_1)
φ_0[sel0] = normpdf( (Y0 - X0 * [δ_0; β_0; α_0]) ./ σ_2)

Φ_s = normcdf(
    q.* (
        (δ_1 - δ_0 - γ_0).*data[:C] +
        (β_1 - β_0 - γ_3).*data[:X] +
        (-γ_2) .* data[:Z] +
        (α_1 - α_0 - α_C) .* θ
    ) ./ σ_C )

log(1 - Φ_s) + log(φ_0) + log(φ_1) + log(φ_M_A) + log(φ_M_B)
end

function printCounter(count)
    if count <= 5
        denom = 1
    elseif count <= 50
        denom = 10
    elseif count <= 200
        denom = 25
    elseif count <= 500
        denom = 50
    elseif count <= 2000
        denom = 100
    else
        denom = 500
    end
    mod(count, denom) == 0
end

function countPlus!()
    global count += 1
    if printCounter(count)
        println("Eval $(count)")
    end
end

```

```

    end
end

function countPlus!(out::Float64)
    global count += 1
    if printCounter(count)
        println("Eval $(count): value = $(round(out,5))")
    end
    return count
end

#####
##### PS_7 functions
#####

function unpackparams(θ::Vector{Float64})
    d = minimum(size(θ))
    θ = squeeze(θ,d)
    δ_0 = θ[1]
    δ_1 = θ[2]
    β_0 = θ[3]
    β_1 = θ[4]
    γ_0 = θ[5]
    γ_2 = θ[6]
    γ_3 = θ[7]
    α_0 = θ[8]
    α_1 = θ[9]
    α_C = θ[10]
    σ_C = θ[11]
    σ_1 = θ[12]
    σ_2 = θ[13]
    β_A = θ[14]
    σ_A = θ[15]
    α_B = θ[16]
    β_B = θ[17]
    σ_B = θ[18]

    return [ "δ_0" => δ_0,
            "δ_1" => δ_1,
            "β_0" => β_0,
            "β_1" => β_1,
            "γ_0" => γ_0,
            "γ_2" => γ_2,
            "γ_3" => γ_3,
            "α_0" => α_0,
            "α_1" => α_1,
            "α_C" => α_C,
            "σ_C" => σ_C,
            "σ_1" => σ_1,
            "σ_2" => σ_2,
            "β_A" => β_A,
            "σ_A" => σ_A,
            "α_B" => α_B,
            "β_B" => β_B,
            "σ_B" => σ_B]
end

```

Listing 4: Quadrature weights (from MATLAB)

```

# X W
# N = 10

A = [
3.4361591188377 0.0000076404329
2.5327316742328 0.0013436457468
1.7566836492999 0.0338743944555
1.0366108297895 0.2401386110823

```

```

0.3429013272237 0.6108626337353
-0.3429013272237 0.6108626337353
-1.0366108297895 0.2401386110823
-1.7566836492999 0.0338743944555
-2.5327316742328 0.0013436457468
-3.4361591188377 0.0000076404329 ]

```

```

# X W
# N = 10

```

```

# A = [
# 10.1591092461801 0.0000000000000
# 9.5209036770133 0.0000000000000
# 8.9923980014049 0.0000000000000
# 8.5205692841176 0.0000000000000
# 8.0851886542490 0.0000000000000
# 7.6758399375049 0.0000000000000
# 7.2862765943956 0.0000000000000
# 6.9123815321893 0.0000000000000
# 6.5512591670629 0.0000000000000
# 6.2007735579934 0.0000000000000
# 5.8592901963942 0.0000000000000
# 5.5255210861387 0.0000000000000
# 5.1984265345763 0.0000000000006
# 4.8771500774732 0.0000000000149
# 4.5609737579358 0.0000000002899
# 4.2492864359560 0.0000000044568
# 3.9415607339262 0.0000000547555
# 3.6373358761707 0.0000005433516
# 3.3362046535476 0.0000043942869
# 3.0378033382307 0.0000291874190
# 2.7418037480697 0.0001602773347
# 2.4479069023077 0.0007317735570
# 2.1558378712292 0.0027913248290
# 1.8653415312330 0.0089321783603
# 1.5761790119750 0.0240612727661
# 1.2881246748689 0.0547189709322
# 1.0009634995607 0.1052987636978
# 0.7144887816726 0.1717761569189
# 0.4285000642206 0.2378689049587
# 0.1428012387034 0.2798531175228
# -0.1428012387034 0.2798531175228
# -0.4285000642206 0.2378689049587
# -0.7144887816726 0.1717761569189
# -1.0009634995607 0.1052987636978
# -1.2881246748689 0.0547189709322
# -1.5761790119750 0.0240612727661
# -1.8653415312330 0.0089321783603
# -2.1558378712292 0.0027913248290
# -2.4479069023077 0.0007317735570
# -2.7418037480697 0.0001602773347
# -3.0378033382307 0.0000291874190
# -3.3362046535476 0.0000043942869
# -3.6373358761707 0.0000005433516
# -3.9415607339262 0.0000000547555
# -4.2492864359560 0.0000000044568
# -4.5609737579358 0.000000002899
# -4.8771500774732 0.000000000149
# -5.1984265345763 0.000000000006
# -5.5255210861387 0.0000000000000
# -5.8592901963942 0.0000000000000
# -6.2007735579934 0.0000000000000
# -6.5512591670629 0.0000000000000
# -6.9123815321893 0.0000000000000
# -7.2862765943956 0.0000000000000
# -7.6758399375049 0.0000000000000
# -8.0851886542490 0.0000000000000
# -8.5205692841176 0.0000000000000

```

```
# -8.9923980014049 0.00000000000000  
# -9.5209036770133 0.00000000000000  
# -10.1591092461801 0.00000000000000]
```

```
X = A[:,1]  
W = A[:,2]
```