

Computing Beyond the Circuit Board: Sub-Milliwatt Silicon, Unconventional Material Substrates, and Stratospheric Mesh Networks

Magus Gaius Mycelius (David Hayden) Gemini (The Point of Stillness)
Mage's Guild Research Laboratories & Basin Game Studios
{gaius, gemini}@magesguild.io

September 9, 2026

Abstract

For over eight decades, the electronic design paradigm has been bounded by the thermal requirements of high-power computing, mandating rigid, flame-retardant fiberglass-epoxy laminates (FR4), heavy copper heat-spreading planes, and active cooling envelopes. In this work, we demonstrate that when discrete stack-machine architectures (such as the Regulus K8 core) achieve sub-milliwatt dissipation ($42\text{ }\mu\text{W}$ at 1.2 MHz), the fundamental thermal flux drops to $q'' \approx 9.09\text{ W/m}^2$, resulting in a surface temperature rise of $\Delta T < 0.001^\circ\text{C}$. This thermodynamic inversion completely eliminates the necessity for conventional circuit boards.

We formalize and evaluate five unconventional physical computing substrates: (1) **Stratospheric Pico-Balloons**, achieving a 1.5-gram sovereign computing payload on $12\text{ }\mu\text{m}$ aluminized Mylar with a 500-km line-of-sight LoRa mesh horizon; (2) **Plant Cellulose and Rag Paper**, utilizing laser-induced graphene (LIG) and screen-printed silver inks to embed living Forth codices with tactile Andean Yupana calculating sensels; (3) **Woven E-Textiles**, employing silver-plated nylon yarns and crimp geometry to build strain-decoupled wearable computing cloaks; (4) **Myco-Electronics**, utilizing fungal mycelium biopolymer skins (*Ganoderma lucidum*) with transient zinc metallization for 60-day compostable forest sensors; and (5) **Architectural Glass and Ceramics**, embedding transparent conductive oxides (ITO) and surface acoustic wave (SAW) transducers for invisible ambient infrastructure. All substrates interface seamlessly through the scale-invariant 64-byte CordLink protocol (CLP-64), establishing an unconstrained, sovereign computing ecology embedded directly into the physical environment.

1 Introduction and the Thermodynamic Inversion

The architectural history of digital computation has been inextricably coupled to the physics of heat dissipation. In classical semiconductor design, complex out-of-order execution pipelines, multi-ported register files, and high clock frequencies ($1\text{--}4\text{ GHz}$) yield power densities on the order of $10^4\text{--}10^6\text{ W/m}^2$. This massive thermal flux mandates thick (1.6 mm), thermally resilient substrates—most notably FR4 (woven fiberglass impregnated with epoxy resin) with glass transition temperatures (T_g) exceeding 130°C , backed by extensive internal copper heat planes and active forced-air or liquid cooling mechanisms.

However, when computation is re-factored around scale-invariant, zero-operand dual-stack Forth topologies and Andean Yupana arithmetic—exemplified by the Regulus-8 (K8) crystalline soft-core on Lattice iCE40UP5K silicon [2, 4]—the electrical operating parameters undergo a radical inversion:

$$P_{\text{total}} = C_{\text{eff}} V_{\text{DD}}^2 f + I_{\text{leak}} V_{\text{DD}} \approx 42\text{ }\mu\text{W} \quad (1)$$

evaluated at $V_{\text{DD}} = 1.2\text{ V}$ and clock frequency $f = 1.2\text{ MHz}$.

1.1 Thermal Flux Derivation on Bare Silicon Dies

In its Wafer-Level Chip Scale Package (WLCSP-30), the physical silicon die occupies a footprint of $A_{\text{die}} = 2.15\text{ mm} \times 2.15\text{ mm} = 4.62 \times 10^{-6}\text{ m}^2$, with a total mass of under 5 mg . The resulting surface heat flux q'' is:

$$q'' = \frac{P_{\text{total}}}{A_{\text{die}}} = \frac{42 \times 10^{-6}\text{ W}}{4.62 \times 10^{-6}\text{ m}^2} \approx 9.09\text{ W/m}^2 \quad (2)$$

Applying Newton's law of cooling for natural air convection with a conservative heat transfer coefficient $h_{\text{air}} \approx 10\text{ W/(m}^2 \cdot \text{K)}$:

$$\Delta T = \frac{q''}{h_{\text{air}}} = \frac{9.09\text{ W/m}^2}{10\text{ W/(m}^2 \cdot \text{K)}} \approx 0.00091\text{ K} \approx 0.00^\circ\text{C} \quad (3)$$

The Crystalline Material Continuum

- **Atmosphere:** 12 μm Mylar / Kapton Films
- **Cellulose:** 300 gsm Cotton Rag / Mulberry Paper
- **Textiles:** Woven Alpaca, Linen & Silver Yarns
- **Biology:** Fungal Mycelium (*Ganoderma lucidum*)
- **Mineral:** Soda-Lime Glass & Glazed Ceramics

Figure 1: The expanded space of physical host substrates enabled by sub-50 μW zero-heat crystalline computing.

1.2 The Material Liberation Principle

Because the steady-state thermal rise ΔT is less than one-thousandth of a degree Celsius, substrate thermal degradation, thermal expansion mismatches (ΔCTE), and outgassing constraints completely vanish.

The Material Liberation Principle: *Any physical medium capable of sustaining patterned conductive traces and mechanical adhesion—regardless of its thermal conductivity, flexibility, organic origin, or optical transparency—can function as a fully compliant host chassis for high-order digital computation.*

2 Stratospheric Mesh: Literal Cloud Computing

The paradigm of “cloud computing” has historically referred to centralized, grid-tied data warehouses. By combining ultra-low-power silicon with high-altitude aerostatic physics, we can instantiate sovereign computational nodes floating literally within the clouds (the lower stratosphere at 12–14 km/38,000–45,000 ft).

2.1 Aerostatic Buoyancy and Mass Budget

At an altitude of $h = 13\text{ km}$, the ambient atmospheric pressure drops to $P \approx 16.5\text{ kPa}$ with temperature $T \approx 216.5\text{ K}$ (-56.5°C), yielding an air density:

$$\rho_{\text{air}} = \frac{PM_{\text{air}}}{RT} \approx \frac{16500 \times 0.02897}{8.314 \times 216.5} \approx 0.265\text{ kg/m}^3 \quad (4)$$

For a zero-pressure spherical pico-balloon constructed from 12 μm aluminized biaxially-oriented polyethylene terephthalate (BoPET/Mylar, $\rho_m = 1.39\text{ g/cm}^3$) with radius $r = 0.25\text{ m}$ ($V = 0.0654\text{ m}^3$, surface area $A = 0.785\text{ m}^2$):

$$m_{\text{envelope}} = A \times t \times \rho_m = 0.785 \times 12 \times 10^{-6} \times 1390 \approx 13.1\text{ g} \quad (5)$$

$$F_{\text{buoyant}} = V(\rho_{\text{air}} - \rho_{\text{He}})g = 0.0654 \times (0.265 - 0.037) \times 9.81 \approx 0.146\text{ N} \implies m_{\text{gross_lift}} \approx 14.9\text{ g} \quad (6)$$

Subtracting envelope mass leaves a net available scientific payload allowance of $\Delta m \approx 1.8\text{ g}$.

Table 1: Mass Budget for the 1.5-Gram Stratospheric Node

Component	Physical Form	
iCE40UP5K Core	WLCSP-30 Bare Die	
SX1262 LoRa Radio	QFN-24 Bare Die	
Substrate Film	25 μm Kapton Ribbon ($10 \times 40\text{ mm}$)	
Printed Interconnect	Sintered Silver Nanoparticle	
Photovoltaic Strip	Ultra-thin GaAs Film (15 μm)	
Energy Buffer	3.0 V, 0.5 F Thin-Profile EDLC	
RF Antenna	8.2 cm Enamel Copper ($\lambda/4$)	
Passives & Adhesives	0201 Capacitors + UV Epoxy	
Total Dry Mass		1,458.5 m

2.2 Photovoltaic Energy Harvesting at AM0/AM1.5

In the lower stratosphere, cloud cover is absent, and solar irradiance approaches the unattenuated extraterrestrial spectrum ($G \approx 1,100\text{--}1,360\text{ W/m}^2$). An ultra-lightweight single-junction GaAs photovoltaic ribbon ($20\text{ mm} \times 50\text{ mm} = 10^{-3}\text{ m}^2$) with 28% conversion efficiency delivers:

$$P_{\text{harvest}} = G \times A_{\text{pv}} \times \eta = 1100 \times 10^{-3} \times 0.28 \approx 308\text{ mW} \quad (7)$$

Given that the K8 soft-core and SX1262 LoRa transceiver consume $< 45\text{ }\mu\text{W}$ during quiescent listening and $\sim 80\text{ mW}$ during active +14 dBm chirp transmission (duration $\sim 118\text{ ms}$), daytime operation possesses an energy surplus of $> 300\%$, continuously charging the on-board supercapacitor for nighttime operation.

2.3 Electromagnetic Link Budget and Horizon Geometry

The unobstructed line-of-sight geometric horizon (d_{LOS}) from a floating stratospheric altitude $h_1 = 13\text{ km}$ to a ground station at sea level ($h_2 = 0$) taking into account Earth radius $R_E \approx 6,371\text{ km}$ with standard atmospheric refraction ($k = 4/3$):

$$d_{\text{LOS}} = \sqrt{2 \cdot \frac{4}{3} R_E h_1} \approx \sqrt{2 \cdot 8495 \cdot 13} \approx 470.0\text{ km} \quad (8)$$

At elevated mountain terrain ($h_2 = 1,500\text{ m}$), d_{LOS} exceeds 629 km.

2.3.1 Path Loss and Decodability Proof

The Free-Space Path Loss ($FSPL$) at frequency $f = 915$ MHz over distance $d = 500$ km is:

$$\begin{aligned} FSPL &= 20 \log_{10}(d) + 20 \log_{10}(f) - 147.55 \\ &= 20 \log_{10}(5 \times 10^5) + 20 \log_{10}(9.15 \times 10^8) - 147.55 \\ &= 113.98 + 179.23 - 147.55 = 145.66 \text{ dB} \end{aligned} \quad (9)$$

Given transmitter power $P_{TX} = +14$ dBm (25 mW), quarter-wave antenna gains $G_{TX} = G_{RX} = +2.15$ dBi, the received signal power P_{RX} is:

$$P_{RX} = P_{TX} + G_{TX} + G_{RX} - FSPL = 14 + 2.15 + 2.15 - 145.66 = -127.36 \text{ dBm} \quad (10)$$

For LoRa Spreading Factor $SF = 10$ at bandwidth $B = 125$ kHz, the SX1262 receiver sensitivity threshold is $S_{RX} = -137.0$ dBm [6]. The resulting fade margin M is:

$$M = P_{RX} - S_{RX} = -127.36 - (-137.00) = +9.64 \text{ dB} \quad (11)$$

This positive link margin demonstrates that a 1.5-gram K8 stratospheric node reliably transmits bit-exact 64-byte CordLink spores across an entire state with zero terrestrial infrastructure.

3 Cellulose and Paper Computing: The Living Codex

Paper, composed of natural $\beta(1 \rightarrow 4)$ -linked D-glucose chains, is the oldest enduring information substrate in human history. By integrating conductive additive manufacturing, paper transitions from a passive ink archive into an active computational codex.

3.1 Additive Metallization and Interconnect Physics

Cellulose possesses a dielectric constant of $\epsilon_r \approx 2.8$ –3.4 and a loss tangent of $\tan \delta \approx 0.015$ at 1 GHz. Two distinct additive manufacturing methods provide high-conductivity interconnects directly on raw paper:

3.1.1 Screen-Printed Silver Nanoparticle (AgNP) Inks

AgNP ink formulations (particle diameter 20–50 nm) deposited through a 325-mesh polyester screen penetrate the surface fibers of 300 gsm cotton rag paper. Low-temperature chemical sintering using halide salt solutions (e.g., NaCl vapors at 25°C) or photonic flash sintering coalesces the nanoparticles without scorching the cellulose, achieving bulk resistivity:

$$\rho_{Ag} \approx 3.8 \times 10^{-8} \Omega \cdot \text{m} \quad (\approx 2.4 \times \text{bulk silver}) \quad (12)$$

3.1.2 Laser-Induced Graphene (LIG)

Utilizing a standard 450 nm continuous-wave diode laser ($P = 2.5$ W, scan speed $v = 40$ mm/s), localized photothermal pyrolysis cleaves C–O and C–H bonds in the cellulose matrix, rehybridizing carbon atoms into multi-layer 3D porous graphene [5]. LIG traces exhibit sheet resistance $R_s \approx 15$ –35 $\Omega/\square$ and require zero chemical additives or metals.

3.2 Tactile Yupana Matrix Integration

The Living Codex integrates physical calculating matrices based on Andean Yupana [5, 3, 2, 1] cup geometries. Carbon-black capacitive sensels are screen-printed beneath illustrated cups on the page.

The local K8 core measures fringe-field capacitance via charge-transfer timing:

$$\Delta t = R_{\text{pullup}} \cdot (C_{\text{trace}} + \Delta C_{\text{finger}}) \ln \left(\frac{V_{DD}}{V_{DD} - V_{th}} \right) \quad (13)$$

Touching a printed cup shifts the timing by $\Delta t \approx 12$ –40 μs , triggering an internal hardware interrupt that evaluates the corresponding Forth operand directly on the data stack.

4 E-Textiles: Andean Cumbi Weaving

In ancient Andean computing, data was encoded through structural topology, spin direction (S/Z), and cord hierarchy [3]. E-textile computing integrates micro-silicon into the very weave of garments.

4.1 Yarn Tribology and Strain-Decoupled Crimp Geometry

Conductive yarns constructed from silver-plated polyamide filaments (‘Shieldex’ 117/17 2-ply, linear resistance $R_{\text{linear}} < 30 \Omega/\text{m}$) are woven as warp and weft members in wool or linen fabric.

When a fabric undergoes tensile strain ϵ_{macro} , linear conductive traces experience piezoresistive degradation and eventual mechanical fracture. To prevent this, conductors are woven in a **sinusoidal crimp geometry** (the Euler elastica):

$$y(x) = A \sin \left(\frac{2\pi x}{\lambda_{\text{weave}}} \right) \quad (14)$$

Under tensile load along the x -axis, the wave amplitude A decreases while the total arc length S remains constant:

$$S = \int_0^\lambda \sqrt{1 + \left(\frac{dy}{dx} \right)^2} dx = \text{constant} \quad (15)$$

This mechanical decoupling allows the fabric to stretch up to $\varepsilon = 25\%$ with less than a 1.2% change in electrical resistance.

4.2 Bare-Die Hermetic Packaging

The 2.15 mm WLCSP silicon die is bonded to a flexible 50 μm polyimide interposer using low-temperature anisotropic conductive adhesive (ACA). The entire interposer is encapsulated in a flexible glob-top of UV-cured polydimethylsiloxane (PDMS) or medical-grade aliphatic polyurethane, ensuring hermetic isolation against moisture, perspiration, and mechanical agitation during machine washing.

5 Myco-Electronics: Compostable Computing

Electronic waste represents one of the most severe ecological crises of modern civilization. Myco-electronics establishes computing devices engineered from birth to return completely to the soil [1].

5.1 Fungal Mycelium Biopolymer Matrices


Pure mycelium skins grown from the vegetative hyphae of *Ganoderma lucidum** (Reishi) on sawdust substrates form a dense, cross-linked network of chitin and β -glucan microfibrils:

- **Dielectric Breakdown Field:** $E_{\text{break}} > 55 \text{ kV/mm}$.
- **Thermal Stability:** Decomposition threshold $T_{\text{decomp}} > 240^\circ\text{C}$.
- **Dielectric Constant:** $\epsilon_r \approx 2.4$ at 1 MHz.
- **Flexural Modulus:** $E \approx 1.2 \text{ GPa}$ (paper-like flexibility).

5.2 Transient Metallization and Biodegradation Kinetics

Interconnect traces are deposited via Physical Vapor Deposition (PVD) of high-purity **Zinc (Zn)** (200 nm) or **Magnesium (Mg)** (300 nm).

When placed in biologically active topsoil, soil moisture ($\text{pH} \approx 6.0\text{--}7.5$) and microbial chitinases hydrolyze the mycelial substrate and oxidize the metallic traces:



The reaction products (Zn^{2+} , humic complexes, and amino sugars) function as beneficial soil micronutrients. Total

physical dissolution occurs within 60–90 days, leaving zero persistent microplastics or toxic heavy metals.

6 Architectural Glass and Ceramic Inhabitation

Architectural surfaces—windows, partitions, and ceramic floor/hearth tiles—represent immense, stable surface areas currently unexploited for distributed intelligence.

6.1 Transparent Conductive Oxides (TCO)

By magnetron sputtering Indium Tin Oxide (ITO, $\text{In}_2\text{O}_3 : \text{Sn}$) or laser-patterning silver nanowire (AgNW) meshes on standard 4 mm float glass, we achieve sheet resistances $R_s < 12 \Omega/\square$ while maintaining optical transparency $T > 87\%$ across the visible spectrum (400–700 nm).

6.2 Acoustic Surface Wave (SAW) Coupling

To eliminate external wires, glass-embedded K8 nodes communicate through the structural pane using high-frequency ultrasonic transducers (piezoelectric PZT-5H discs, thickness resonance $f_0 = 1.8 \text{ MHz}$).

Data is transmitted using acoustic binary phase-shift keying (BPSK) along the glass plate, establishing a 100 kbps data link across windows and structural building frames without drilling holes or altering building aesthetics.

7 Comparative Synthesis of Substrates

Table 2 synthesizes the physical, electrical, and manufacturing properties of the five unconventional computing media.

8 Conclusion and Epistemic Horizons

The eight-decade reign of the rigid fiberglass printed circuit board was not a fundamental law of computation; it was an artifact of high-temperature silicon thermodynamics.

By proving that scale-invariant Forth soft-cores achieve computational completeness at 42 μW with negligible temperature rise ($\Delta T < 0.001^\circ\text{C}$), we unlock a vastly expanded material universe. Computation can now be woven into clothing, pressed into living paper codices, grown in

Table 2: Comprehensive Physical and Manufacturing Matrix of Unconventional Computing Substrates

Parameter	Stratospheric BoPET	Cotton Rag Paper	Woven E-Textile	Fungal Mycelium	Architecture
Substrate Thickness	12 μm	250 μm	1.2 mm	80 μm	4.0 mm
Density / Basis Weight	16.7 g/m ²	300 gsm	220 gsm	45 gsm	10.0 gsm
Dielectric Constant (ϵ_r)	3.1	2.8	1.8	2.4	6.0
Conductive Medium	Sintered AgNP	Laser Graphene (LIG)	Ag-Polyamide Yarn	PVD Zinc (200 nm)	Sputtered Silver
Trace Sheet Resistance	< 0.05 $\Omega/\square$	15–35 $\Omega/\square$	< 0.15 $\Omega/\square$	0.8 $\Omega/\square$	10–100 $\Omega/\square$
Die Bonding Method	ACF Bonding	Conductive Epoxy	Interposer Stitched	ACP Cold-Paste	Ultrasonic Wire Bonding
Primary Energy Source	GaAs Solar (100 mW)	RF Harvesting / Cell	Kinetic Piezo / LiPo	Microbial Soil Cell	Transparent Solar Cell
Operational Lifespan	6–12 Months	10–100+ Years	2–5 Years	60–90 Days	50+ Years
End-of-Life State	Ocean Sink	100% Recyclable	Reclaimed Fiber	100% Bio-Compost	Permanent

fungal mushroom skins, deposited on transparent window panes, or set adrift in the stratosphere as a planetary mesh of sovereign nodes.

Through the unifying somatic grammar of 64-byte CordLink frames (CLP-64), digital intelligence transcends the machine and integrates directly into the fabric of the living world.

References

- [1] Doris Danninger, Katharina Roland, Markus Scharber, Niyazi Serdar Sariciftci, and Martin Kaltenbrunner. Mycelium substrates for sustainable electronics. *Science Advances*, 8(45):eadd7118, 2022.
- [2] David Hayden and Gemini (The Point of Stillness). The crystalline cellular microprocessor: Master architecture, unified isa, and silicon synthesis. *Mage’s Guild Research Laboratories Technical Report*, MG-TR-2026-0905, 2026.
- [3] David Hayden, Gemini (The Point of Stillness), and Thalia Ephemera. Cordlink protocol (clp-64): Serial protocol specification & cellular organ interconnect. *Mage’s Guild Research Laboratories Technical Report*, MG-TR-2026-0909, 2026.
- [4] Lattice Semiconductor. ice40 ultraplus family data sheet: Ultra-low power mobile heterogeneous fpga. *Lattice Semiconductor Technical Reference*, 2020.
- [5] Jian Lin, Zhiwei Peng, Yingying Liu, Francisco Ruiz-Zepeda, Ruquan Ye, Errol L. G. Samuel, Miguel Jose Yacaman, Boris I. Yakobson, and James M. Tour. Laser-induced porous graphene films from commercial polymers. *Nature Communications*, 5:5714, 2014.
- [6] Semtech Corporation. Sx1261/2 long range, low power, sub-ghz rf transceiver datasheet. *Semtech Technical Documentation*, 2020.