

Rajalakshmi Engineering College

Name: magesh v
Email: 240801187@rajalakshmi.edu.in
Roll no: 240801187
Phone: 6381572897
Branch: REC
Department: I ECE FB
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_MCQ

Attempt : 2
Total Mark : 15
Marks Obtained : 0

Section 1 : MCQ

1. Which of the following is the correct in-order traversal of a binary search tree with nodes: 9, 3, 5, 11, 8, 4, 2?

Answer

Status : Skipped

Marks : 0/1

2. Find the postorder traversal of the given binary search tree.

Answer

-

Status : -

Marks : 0/1

3. Find the post-order traversal of the given binary search tree.

Answer

-

Status : -

Marks : 0/1

4. Which of the following is the correct post-order traversal of a binary search tree with nodes: 50, 30, 20, 55, 32, 52, 57?

Answer

-

Status : -

Marks : 0/1

5. The preorder traversal of a binary search tree is 15, 10, 12, 11, 20, 18, 16, 19. Which one of the following is the postorder traversal of the tree?

Answer

-

Status : -

Marks : 0/1

6. Find the preorder traversal of the given binary search tree.

Answer

-

Status : -

Marks : 0/1

7. Find the in-order traversal of the given binary search tree.

Answer

-

Status : -

Marks : 0/1

8. Find the pre-order traversal of the given binary search tree.

Answer

-

Status : -

Marks : 0/1

9. Which of the following operations can be used to traverse a Binary Search Tree (BST) in ascending order?

Answer

-

Status : -

Marks : 0/1

10. While inserting the elements 71, 65, 84, 69, 67, 83 in an empty binary search tree (BST) in the sequence shown, the element in the lowest level is _____.

Answer

-

Status : -

Marks : 0/1

11. How many distinct binary search trees can be created out of 4 distinct keys?

Answer

-

Status : -

Marks : 0/1

12. Which of the following is a valid preorder traversal of the binary search tree with nodes: 18, 28, 12, 11, 16, 14, 17?

Answer

-

Status : -

Marks : 0/1

13. In a binary search tree with nodes 18, 28, 12, 11, 16, 14, 17, what is the value of the left child of the node 16?

Answer

-

Status : -

Marks : 0/1

14. While inserting the elements 5, 4, 2, 8, 7, 10, 12 in a binary search tree, the element at the lowest level is _____.

Answer

-

Status : -

Marks : 0/1

15. Which of the following is the correct pre-order traversal of a binary search tree with nodes: 50, 30, 20, 55, 32, 52, 57?

Answer

-

Status : -

Marks : 0/1

Rajalakshmi Engineering College

Name: magesh v
Email: 240801187@rajalakshmi.edu.in
Roll no: 240801187
Phone: 6381572897
Branch: REC
Department: I ECE FB
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_COD_Question 1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

John is learning about Binary Search Trees (BST) in his computer science class. He wants to create a program that allows users to delete a node with a given value from a BST and print the remaining nodes using an in-order traversal.

Implement a function to help him delete a node with a given value from a BST.

Input Format

The first line of input consists of an integer N, representing the number of nodes in the BST.

The second line consists of N space-separated integers, representing the values of the BST nodes.

The third line consists of an integer V, which is the value to delete from the BST.

Output Format

The output prints the space-separated values in the BST in an in-order traversal, after the deletion of the specified value.

If the specified value is not available in the tree, print the given input values in-order traversal.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
10 5 15 2 7
15
Output: 2 5 7 10

Answer

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct TreeNode {
    int data;
    struct TreeNode* left;
    struct TreeNode* right;
};
```

```
struct TreeNode* createNode(int key) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct
TreeNode));
    newNode->data = key;
    newNode->left = newNode->right = NULL;
    return newNode;
}
```

```
struct TreeNode* insert(struct TreeNode* root, int key)
{ if (root == NULL) return createNode(key);
```

```
if (key < root->data) root->left = insert(root->left, key);
else if (key > root->data) root->right = insert(root->right, key);
return root; }
```

```
struct TreeNode* findMin(struct TreeNode* node)
{ while (node && node->left != NULL) node = node->left;
return node;
}
```

```
struct TreeNode* deleteNode(struct TreeNode* root, int key)
{ if (root == NULL) return root;
if (key < root->data) root->left = deleteNode(root->left, key);
else if (key > root->data) root->right = deleteNode(root->right, key);
else { if (root->left == NULL) { struct TreeNode* temp = root->right; free(root);
return temp; } else if (root->right == NULL) { struct TreeNode* temp = root->left;
free(root); return temp; } struct TreeNode* temp = findMin(root->right); root->data
= temp->data; root->right = deleteNode(root->right, temp->data); } return root; }
```

```
void inorderTraversal(struct TreeNode* root)
{ if (root != NULL) { inorderTraversal(root->left);
printf("%d ", root->data);
inorderTraversal(root->right);
}
```

```
}
```

```
int main()
{
    int N, rootValue, V;
    scanf("%d", &N);
    struct TreeNode* root = NULL;
    for (int i = 0; i < N; i++) {
        int key;
        scanf("%d", &key);
        if (i == 0) rootValue = key;
        root = insert(root, key);
    }
    scanf("%d", &V);
    root = deleteNode(root, V);
    inorderTraversal(root);
}
```

```
} return 0;
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: magesh v
Email: 240801187@rajalakshmi.edu.in
Roll no: 240801187
Phone: 6381572897
Branch: REC
Department: I ECE FB
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_COD_Question 2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Mike is learning about Binary Search Trees (BSTs) and wants to implement various operations on them. He wants to write a basic program for creating a BST, inserting nodes, and printing the tree in the pre-order traversal.

Write a program to help him solve this program.

Input Format

The first line of input consists of an integer N, representing the number of values to insert into the BST.

The second line consists of N space-separated integers, representing the values to insert into the BST.

Output Format

The output prints the space-separated values of the BST in the pre-order traversal.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

3 1 5 2 4

Output: 3 1 2 5 4

Answer

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* left;
    struct Node* right;
};
```

```
struct Node* createNode(int value) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = value;
    newNode->left = newNode->right = NULL;
    return newNode;
}
```

```
struct Node* insert(struct Node* root, int value) {
    if (root == NULL) {
        return createNode(value);
    }
    if (value < root->data) {
        root->left = insert(root->left, value);
    } else {
        root->right = insert(root->right, value);
    }
    return root;
}
```

```
void printPreorder(struct Node* root) {  
    if (root != NULL) {  
        printf("%d ", root->data);  
        printPreorder(root->left);  
        printPreorder(root->right);  
    }  
}
```

```
int main() {  
    struct Node* root = NULL;  
  
    int n;  
    scanf("%d", &n);  
  
    for (int i = 0; i < n; i++) {  
        int value;  
        scanf("%d", &value);  
        root = insert(root, value);  
    }  
  
    printPreorder(root);  
    return 0;  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: magesh v
Email: 240801187@rajalakshmi.edu.in
Roll no: 240801187
Phone: 6381572897
Branch: REC
Department: I ECE FB
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

You are required to implement basic operations on a Binary Search Tree (BST), like insertion and searching.

Insertion: Given a list of integers, construct a Binary Search Tree by repeatedly inserting each integer into the tree according to the rules of a BST.

Searching: Given an integer, search for its presence in the constructed Binary Search Tree. Print whether the integer is found or not.

Write a program to calculate this efficiently.

Input Format

The first line of input consists of an integer n, representing the number of nodes

in the binary search tree.

The second line consists of the values of the nodes, separated by space as integers.

The third line consists of an integer representing, the value that is to be searched.

Output Format

The output prints, "Value <value> is found in the tree." if the given value is present, otherwise it prints: "Value <value> is not found in the tree."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 7

8 3 10 1 6 14 23

6

Output: Value 6 is found in the tree.

Answer

```
struct Node* insertNode(struct Node* root, int value)
{
    if (root == NULL)
    {
        return createNode(value);
    }
    if (value < root->data)
    { root->left = insertNode(root->left, value);
    }
    else
    { root->right = insertNode(root->right, value);
    }
    return root;
}
```

```
struct Node* searchNode(struct Node* root, int value)
{
    if (root == NULL || root->data == value)
    {
```

```
return root; }  
if (value < root->data)  
{ return searchNode(root->left, value); }  
else { return searchNode(root->right, value); }  
  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: magesh v
Email: 240801187@rajalakshmi.edu.in
Roll no: 240801187
Phone: 6381572897
Branch: REC
Department: I ECE FB
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_COD_Question 4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

John, a computer science student, is learning about binary search trees (BST) and their properties. He decides to write a program to create a BST, display it in post-order traversal, and find the minimum value present in the tree.

Help him by implementing the program.

Input Format

The first line of input consists of an integer N, representing the number of elements to insert into the BST.

The second line consists of N space-separated integers data, which is the data to be inserted into the BST.

Output Format

The first line of output prints the space-separated elements of the BST in post-order traversal.

The second line prints the minimum value found in the BST.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3

5 10 15

Output: 15 10 5

The minimum value in the BST is: 5

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int data;  
    struct Node* left;  
    struct Node* right;  
};
```

```
struct Node* createNode(int data) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    newNode->data = data;  
    newNode->left = newNode->right = NULL;  
    return newNode;  
}
```

```
struct Node* insert(struct Node* root, int data) {  
    if (root == NULL) {  
        struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
        newNode->data = data;  
        newNode->left = newNode->right = NULL;  
        return newNode;  
    }  
    if (data < root->data)
```



```

        root->left = insert(root->left, data);
    else
        root->right = insert(root->right, data);
    return root;
}

void displayTreePostOrder(struct Node* root) {
    if (root != NULL) {
        displayTreePostOrder(root->left);
        displayTreePostOrder(root->right);
        printf("%d ", root->data);
    }
}

int findMinValue(struct Node* root) {
    if (root == NULL) {
        printf("Tree is empty\n");
        return -1;
    }
    while (root->left != NULL)
        root = root->left;
    return root->data;
}

int main() {
    struct Node* root = NULL;
    int n, data;
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d", &data);
        root = insert(root, data);
    }

    displayTreePostOrder(root);
    printf("\n");

    int minValue = findMinValue(root);
    printf("The minimum value in the BST is: %d", minValue);

    return 0;
}

```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: magesh v
Email: 240801187@rajalakshmi.edu.in
Roll no: 240801187
Phone: 6381572897
Branch: REC
Department: I ECE FB
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_COD_Question 5

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In his computer science class, John is learning about Binary Search Trees (BST). He wants to build a BST and find the maximum value in the tree.

Help him by writing a program to insert nodes into a BST and find the maximum value in the tree.

Input Format

The first line of input consists of an integer N, representing the number of nodes in the BST.

The second line consists of N space-separated integers, representing the values of the nodes to insert into the BST.

Output Format

The output prints the maximum value in the BST.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

10 5 15 2 7

Output: 15

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct TreeNode {  
    int data;  
    struct TreeNode* left;  
    struct TreeNode* right;  
};
```

```
struct TreeNode* createNode(int key) {  
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct  
TreeNode));  
    newNode->data = key;  
    newNode->left = newNode->right = NULL;  
    return newNode;  
}
```

```
struct TreeNode* insert(struct TreeNode* root, int key) {  
    if (root == NULL) {  
        return createNode(key);  
    }  
    if (key < root->data) {  
        root->left = insert(root->left, key);  
    } else {  
        root->right = insert(root->right, key);  
    }  
    return root;  
}
```

```
int findMax(struct TreeNode* root) {
    if (root == NULL) {
        return -1;
    }
    while (root->right != NULL) {
        root = root->right;
    }
    return root->data;
}
```

```
int main() {
    int N, rootValue;
    scanf("%d", &N);

    struct TreeNode* root = NULL;

    for (int i = 0; i < N; i++) {
        int key;
        scanf("%d", &key);
        if (i == 0) rootValue = key;
        root = insert(root, key);
    }

    int maxVal = findMax(root);
    if (maxVal != -1) {
        printf("%d", maxVal);
    }

    return 0;
}
```

Status : Correct

Marks : 10/10