

```
=====
FILE: data\output\canonical_model.json
ENCODING: utf-8
=====
```

```
{
  "records": [
    {
      "name": "COVERAGE",
      "primary_key": null,
      "record_id": null,
      "location_mode": null,
      "fields": [
        {
          "name": "SELECTION_DATE_0400",
          "datatype": "DATE",
          "length": null,
          "scale": null,
          "occurs": false,
          "occurs_max": null
        },
        {
          "name": "TERMINATION_DATE_0400",
          "datatype": "DATE",
          "length": null,
          "scale": null,
          "occurs": false,
          "occurs_max": null
        },
        {
          "name": "TYPE_0400",
          "datatype": "CHAR",
          "length": 1,
          "scale": null,
          "occurs": false,
          "occurs_max": null
        },
        {
          "name": "INS_PLAN_CODE_0400",
          "datatype": "VARCHAR",
          "length": 3,
          "scale": null,
          "occurs": false,
          "occurs_max": null
        }
      ]
    },
    {
      "name": "DENTAL_CLAIM",
      "primary_key": null,
      "record_id": null,
      "location_mode": null,
      "fields": [
        {
          "name": "CLAIM_DATE_0405",
          "datatype": "DATE",
          "length": null,
          "scale": null,
          "occurs": false,
          "occurs_max": null
        },
        {
          "name": "PATIENT_BIRTH_DATE_0405",
          "datatype": "DATE",
          "length": null,
          "scale": null,
          "occurs": false,
          "occurs_max": null
        },
        {
          "name": "SERVICE_DATE_0405",
          "datatype": "DATE",
          "length": null,
          "scale": null,
          "occurs": false,
          "occurs_max": null
        }
      ]
    }
  ]
}
```

```

},
{
  "name": "PATIENT_FIRST_NAME_0405",
  "datatype": "VARCHAR",
  "length": 10,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "PATIENT_LAST_NAME_0405",
  "datatype": "VARCHAR",
  "length": 15,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "PATIENT_SEX_0405",
  "datatype": "CHAR",
  "length": 1,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "RELATION_TO_EMPLOYEE_0405",
  "datatype": "VARCHAR",
  "length": 10,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "DENTIST_FIRST_NAME_0405",
  "datatype": "VARCHAR",
  "length": 10,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "DENTIST_LAST_NAME_0405",
  "datatype": "VARCHAR",
  "length": 15,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "DENTIST_STREET_0405",
  "datatype": "VARCHAR",
  "length": 20,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "DENTIST_CITY_0405",
  "datatype": "VARCHAR",
  "length": 15,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "DENTIST_STATE_0405",
  "datatype": "VARCHAR",
  "length": 2,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "DENTIST_ZIP_FIRST_FIVE_0405",
  "datatype": "VARCHAR",

```

```

        "length": 5,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "DENTIST_ZIP_LAST_FOUR_0405",
        "datatype": "VARCHAR",
        "length": 4,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "DENTIST_LICENSE_NUMBER_0405",
        "datatype": "SMALLINT",
        "length": null,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "NUMBER_OF_PROCEDURES_0405",
        "datatype": "DECIMAL",
        "length": 1,
        "scale": 0,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "TOOTH_NUMBER_0405",
        "datatype": "SMALLINT",
        "length": null,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "PROCEDURE_CODE_0405",
        "datatype": "SMALLINT",
        "length": null,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "DESCRIPTION_OF_SERVICE_0405",
        "datatype": "VARCHAR",
        "length": 60,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "FEE_0405",
        "datatype": "DECIMAL",
        "length": 2,
        "scale": 2,
        "occurs": false,
        "occurs_max": null
    }
}
],
{
    "name": "DEPARTMENT",
    "primary_key": "DEPT_ID_0410",
    "record_id": null,
    "location_mode": null,
    "fields": [
        {
            "name": "DEPT_ID_0410",
            "datatype": "SMALLINT",
            "length": null,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        }
    ]
}

```

```

    },
    {
      "name": "DEPT_NAME_0410",
      "datatype": "VARCHAR",
      "length": 45,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "DEPT_HEAD_ID_0410",
      "datatype": "SMALLINT",
      "length": null,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    }
  ]
},
{
  "name": "EMPLOYEE",
  "primary_key": "EMP_ID_0415",
  "record_id": null,
  "location_mode": null,
  "fields": [
    {
      "name": "START_DATE_0415",
      "datatype": "DATE",
      "length": null,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "TERMINATION_DATE_0415",
      "datatype": "DATE",
      "length": null,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "BIRTH_DATE_0415",
      "datatype": "DATE",
      "length": null,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "EMP_ID_0415",
      "datatype": "SMALLINT",
      "length": null,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "EMP_FIRST_NAME_0415",
      "datatype": "VARCHAR",
      "length": 10,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "EMP_LAST_NAME_0415",
      "datatype": "VARCHAR",
      "length": 15,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "EMP_STREET_0415",
      "datatype": "VARCHAR",

```

```

        "length": 20,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "EMP_CITY_0415",
        "datatype": "VARCHAR",
        "length": 15,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "EMP_STATE_0415",
        "datatype": "VARCHAR",
        "length": 2,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "EMP_ZIP_FIRST_FIVE_0415",
        "datatype": "VARCHAR",
        "length": 5,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "EMP_ZIP_LAST_FOUR_0415",
        "datatype": "VARCHAR",
        "length": 4,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "EMP_PHONE_0415",
        "datatype": "SMALLINT",
        "length": null,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "STATUS_0415",
        "datatype": "VARCHAR",
        "length": 2,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "SS_NUMBER_0415",
        "datatype": "SMALLINT",
        "length": null,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    }
]
},
{
    "name": "EMPOSITION",
    "primary_key": null,
    "record_id": null,
    "location_mode": null,
    "fields": [
        {
            "name": "START_DATE_0420",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        }
    ]
}

```

```

    },
    {
      "name": "FINISH_DATE_0420",
      "datatype": "DATE",
      "length": null,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "SALARY_GRADE_0420",
      "datatype": "SMALLINT",
      "length": null,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "SALARY_AMOUNT_0420",
      "datatype": "DECIMAL",
      "length": 2,
      "scale": 2,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "BONUS_PERCENT_0420",
      "datatype": "DECIMAL",
      "length": 3,
      "scale": 3,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "COMMISSION_PERCENT_0420",
      "datatype": "DECIMAL",
      "length": 3,
      "scale": 3,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "OVERTIME_RATE_0420",
      "datatype": "DECIMAL",
      "length": 3,
      "scale": 2,
      "occurs": false,
      "occurs_max": null
    }
  ]
},
{
  "name": "EXPERTISE",
  "primary_key": null,
  "record_id": null,
  "location_mode": null,
  "fields": [
    {
      "name": "EXPERTISE_DATE_0425",
      "datatype": "DATE",
      "length": null,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "SKILL_LEVEL_0425",
      "datatype": "VARCHAR",
      "length": 2,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    }
  ]
}
],
{

```

```

"name": "HOSPITAL_CLAIM",
"primary_key": null,
"record_id": null,
"location_mode": null,
"fields": [
  {
    "name": "CLAIM_DATE_0430",
    "datatype": "DATE",
    "length": null,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "PATIENT_BIRTH_DATE_0430",
    "datatype": "DATE",
    "length": null,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "ADMIT_DATE_0430",
    "datatype": "DATE",
    "length": null,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "DISCHARGE_DATE_0430",
    "datatype": "DATE",
    "length": null,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "PATIENT_FIRST_NAME_0430",
    "datatype": "VARCHAR",
    "length": 10,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "PATIENT_LAST_NAME_0430",
    "datatype": "VARCHAR",
    "length": 15,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "PATIENT_SEX_0430",
    "datatype": "CHAR",
    "length": 1,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "RELATION_TO_EMPLOYEE_0430",
    "datatype": "VARCHAR",
    "length": 10,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "HOSPITAL_NAME_0430",
    "datatype": "VARCHAR",
    "length": 25,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  }
]

```

```

},
{
  "name": "HOSP_STREET_0430",
  "datatype": "VARCHAR",
  "length": 20,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "HOSP_CITY_0430",
  "datatype": "VARCHAR",
  "length": 15,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "HOSP_STATE_0430",
  "datatype": "VARCHAR",
  "length": 2,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "HOSP_ZIP_FIRST_FIVE_0430",
  "datatype": "VARCHAR",
  "length": 5,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "HOSP_ZIP_LAST_FOUR_0430",
  "datatype": "VARCHAR",
  "length": 4,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "DIAGNOSIS_0430",
  "datatype": "VARCHAR",
  "length": 120,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "WARD_DAYS_0430",
  "datatype": "DECIMAL",
  "length": 5,
  "scale": 0,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "WARD_RATE_0430",
  "datatype": "DECIMAL",
  "length": 2,
  "scale": 2,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "WARD_TOTAL_0430",
  "datatype": "DECIMAL",
  "length": 2,
  "scale": 2,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "SEMI_DAYS_0430",
  "datatype": "DECIMAL",

```



```

        "length": 5,
        "scale": 0,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "SEMI_RATE_0430",
        "datatype": "DECIMAL",
        "length": 2,
        "scale": 2,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "SEMI_TOTAL_0430",
        "datatype": "DECIMAL",
        "length": 2,
        "scale": 2,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "DELIVERY_COST_0430",
        "datatype": "DECIMAL",
        "length": 2,
        "scale": 2,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "ANESTHESIA_COST_0430",
        "datatype": "DECIMAL",
        "length": 2,
        "scale": 2,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "LAB_COST_0430",
        "datatype": "DECIMAL",
        "length": 2,
        "scale": 2,
        "occurs": false,
        "occurs_max": null
    }
]
},
{
    "name": "INSURANCE_PLAN",
    "primary_key": "INS_PLAN_CODE_0435",
    "record_id": null,
    "location_mode": null,
    "fields": [
        {
            "name": "INS_PLAN_CODE_0435",
            "datatype": "VARCHAR",
            "length": 3,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        },
        {
            "name": "INS_CO_NAME_0435",
            "datatype": "VARCHAR",
            "length": 45,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        },
        {
            "name": "INS_CO_STREET_0435",
            "datatype": "VARCHAR",
            "length": 20,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        }
    ]
}

```

```

},
{
  "name": "INS_CO_CITY_0435",
  "datatype": "VARCHAR",
  "length": 15,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "INS_CO_STATE_0435",
  "datatype": "VARCHAR",
  "length": 2,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "INS_CO_ZIP_FIRST_FIVE_0435",
  "datatype": "VARCHAR",
  "length": 5,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "INS_CO_ZIP_LAST_FOUR_0435",
  "datatype": "VARCHAR",
  "length": 4,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "INS_CO_PHONE_0435",
  "datatype": "SMALLINT",
  "length": null,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "GROUP_NUMBER_0435",
  "datatype": "SMALLINT",
  "length": null,
  "scale": null,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "DEDUCT_0435",
  "datatype": "DECIMAL",
  "length": 2,
  "scale": 2,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "MAXIMUM_LIFE_COST_0435",
  "datatype": "DECIMAL",
  "length": 2,
  "scale": 2,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "FAMILY_COST_0435",
  "datatype": "DECIMAL",
  "length": 2,
  "scale": 2,
  "occurs": false,
  "occurs_max": null
},
{
  "name": "DEP_COST_0435",
  "datatype": "DECIMAL",

```

```

        "length": 2,
        "scale": 2,
        "occurs": false,
        "occurs_max": null
    }
]
},
{
    "name": "JOB",
    "primary_key": "JOB_ID_0440",
    "record_id": null,
    "location_mode": null,
    "fields": [
        {
            "name": "JOB_ID_0440",
            "datatype": "SMALLINT",
            "length": null,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        },
        {
            "name": "TITLE_0440",
            "datatype": "VARCHAR",
            "length": 20,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        },
        {
            "name": "DESCRIPTION_LINE_0440",
            "datatype": "VARCHAR",
            "length": 120,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        },
        {
            "name": "REQUIREMENT_LINE_0440",
            "datatype": "VARCHAR",
            "length": 120,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        },
        {
            "name": "MINIMUM_SALARY_0440",
            "datatype": "DECIMAL",
            "length": 2,
            "scale": 2,
            "occurs": false,
            "occurs_max": null
        },
        {
            "name": "MAXIMUM_SALARY_0440",
            "datatype": "DECIMAL",
            "length": 2,
            "scale": 2,
            "occurs": false,
            "occurs_max": null
        },
        {
            "name": "SALARY_GRADES_0440",
            "datatype": "SMALLINT",
            "length": null,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        },
        {
            "name": "NUMBER_OF_POSITIONS_0440",
            "datatype": "SMALLINT",
            "length": null,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        }
    ]
}

```

```

    },
    {
      "name": "NUMBER_OPEN_0440",
      "datatype": "SMALLINT",
      "length": null,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    }
  ]
},
{
  "name": "NON_HOSP_CLAIM",
  "primary_key": null,
  "record_id": null,
  "location_mode": null,
  "fields": [
    {
      "name": "CLAIM_DATE_0445",
      "datatype": "DATE",
      "length": null,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "PATIENT_BIRTH_DATE_0445",
      "datatype": "DATE",
      "length": null,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "SERVICE_DATE_0445",
      "datatype": "DATE",
      "length": null,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "PATIENT_FIRST_NAME_0445",
      "datatype": "VARCHAR",
      "length": 10,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "PATIENT_LAST_NAME_0445",
      "datatype": "VARCHAR",
      "length": 15,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "PATIENT_SEX_0445",
      "datatype": "CHAR",
      "length": 1,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "RELATION_TO_EMPLOYEE_0445",
      "datatype": "VARCHAR",
      "length": 10,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "PHYSICIAN_FIRST_NAME_0445",
      "datatype": "VARCHAR",

```

```

    "length": 10,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "PHYSICIAN_LAST_NAME_0445",
    "datatype": "VARCHAR",
    "length": 15,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "PHYSICIAN_STREET_0445",
    "datatype": "VARCHAR",
    "length": 20,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "PHYSICIAN_CITY_0445",
    "datatype": "VARCHAR",
    "length": 15,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "PHYSICIAN_STATE_0445",
    "datatype": "VARCHAR",
    "length": 2,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "PHYSICIAN_ZIP_FIRST_FIVE_0445",
    "datatype": "VARCHAR",
    "length": 5,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "PHYSICIAN_ZIP_LAST_FOUR_0445",
    "datatype": "VARCHAR",
    "length": 4,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "PHYSICIAN_ID_0445",
    "datatype": "SMALLINT",
    "length": null,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "DIAGNOSIS_0445",
    "datatype": "VARCHAR",
    "length": 120,
    "scale": null,
    "occurs": false,
    "occurs_max": null
  },
  {
    "name": "NUMBER_OF_PROCEDURES_0445",
    "datatype": "DECIMAL",
    "length": 1,
    "scale": 0,
    "occurs": false,
    "occurs_max": null
  }

```

```

    },
    {
      "name": "PROCEDURE_CODE_0445",
      "datatype": "SMALLINT",
      "length": null,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "DESCRIPTION_OF_SERVICE_0445",
      "datatype": "VARCHAR",
      "length": 60,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "FEE_0445",
      "datatype": "DECIMAL",
      "length": 2,
      "scale": 2,
      "occurs": false,
      "occurs_max": null
    }
  ]
},
{
  "name": "OFFICE",
  "primary_key": "OFFICE_CODE_0450",
  "record_id": null,
  "location_mode": null,
  "fields": [
    {
      "name": "OFFICE_CODE_0450",
      "datatype": "VARCHAR",
      "length": 3,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "OFFICE_STREET_0450",
      "datatype": "VARCHAR",
      "length": 20,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "OFFICE_CITY_0450",
      "datatype": "VARCHAR",
      "length": 15,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "OFFICE_STATE_0450",
      "datatype": "VARCHAR",
      "length": 2,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "OFFICE_ZIP_FIRST_FIVE_0450",
      "datatype": "VARCHAR",
      "length": 5,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    },
    {
      "name": "OFFICE_ZIP_LAST_FOUR_0450",
      "datatype": "VARCHAR",

```

```

        "length": 4,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "OFFICE_PHONE_0450",
        "datatype": "SMALLINT",
        "length": null,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "OFFICE_AREA_CODE_0450",
        "datatype": "VARCHAR",
        "length": 3,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    },
    {
        "name": "SPEED_DIAL_0450",
        "datatype": "VARCHAR",
        "length": 3,
        "scale": null,
        "occurs": false,
        "occurs_max": null
    }
]
},
{
    "name": "SKILL",
    "primary_key": "SKILL_ID_0455",
    "record_id": null,
    "location_mode": null,
    "fields": [
        {
            "name": "SKILL_ID_0455",
            "datatype": "SMALLINT",
            "length": null,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        },
        {
            "name": "SKILL_NAME_0455",
            "datatype": "VARCHAR",
            "length": 12,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        },
        {
            "name": "SKILL_DESCRIPTION_0455",
            "datatype": "VARCHAR",
            "length": 60,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        }
    ]
},
{
    "name": "STRUCTURE",
    "primary_key": null,
    "record_id": null,
    "location_mode": null,
    "fields": [
        {
            "name": "STRUCTURE_DATE_0460",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "occurs": false,
            "occurs_max": null
        }
    ]
}

```

```

    },
    {
      "name": "STRUCTURE_CODE_0460",
      "datatype": "VARCHAR",
      "length": 2,
      "scale": null,
      "occurs": false,
      "occurs_max": null
    }
  ]
},
"sets": [
  {
    "name": "DEPT-EMPLOYEE",
    "owner_record": "DEPARTMENT",
    "member_record": "EMPLOYEE",
    "order_mode": null
  },
  {
    "name": "MANAGES",
    "owner_record": "EMPLOYEE",
    "member_record": "STRUCTURE",
    "order_mode": null
  },
  {
    "name": "OFFICE-EMPLOYEE",
    "owner_record": "OFFICE",
    "member_record": "EMPLOYEE",
    "order_mode": null
  },
  {
    "name": "EMP-EXPERTISE",
    "owner_record": "EMPLOYEE",
    "member_record": "EXPERTISE",
    "order_mode": null
  },
  {
    "name": "SKILL-EXPERTISE",
    "owner_record": "SKILL",
    "member_record": "EXPERTISE",
    "order_mode": null
  },
  {
    "name": "EMP-EMPOSITION",
    "owner_record": "EMPLOYEE",
    "member_record": "EMPOSITION",
    "order_mode": null
  },
  {
    "name": "REPORTS-TO",
    "owner_record": "EMPLOYEE",
    "member_record": "STRUCTURE",
    "order_mode": null
  },
  {
    "name": "EMP-COVERAGE",
    "owner_record": "EMPLOYEE",
    "member_record": "COVERAGE",
    "order_mode": null
  },
  {
    "name": "JOB-EMPOSITION",
    "owner_record": "JOB",
    "member_record": "EMPOSITION",
    "order_mode": null
  },
  {
    "name": "COVERAGE-CLAIMS",
    "owner_record": "COVERAGE",
    "member_record": "DENTAL_CLAIM",
    "order_mode": null
  },
  {
    "name": "COVERAGE-CLAIMS",
    "owner_record": "COVERAGE",

```



```

    "member_record": "HOSPITAL_CLAIM",
    "order_mode": null
  },
  {
    "name": "COVERAGE-CLAIMS",
    "owner_record": "COVERAGE",
    "member_record": "NON_HOSP_CLAIM",
    "order_mode": null
  }
],
"relationships": [
  {
    "set_name": "DEPT-EMPLOYEE",
    "parent_record": "DEPARTMENT",
    "child_record": "EMPLOYEE",
    "cardinality": "1:N"
  },
  {
    "set_name": "MANAGES",
    "parent_record": "EMPLOYEE",
    "child_record": "STRUCTURE",
    "cardinality": "1:N"
  },
  {
    "set_name": "OFFICE-EMPLOYEE",
    "parent_record": "OFFICE",
    "child_record": "EMPLOYEE",
    "cardinality": "1:N"
  },
  {
    "set_name": "EMP-EXPERTISE",
    "parent_record": "EMPLOYEE",
    "child_record": "EXPERTISE",
    "cardinality": "1:N"
  },
  {
    "set_name": "SKILL-EXPERTISE",
    "parent_record": "SKILL",
    "child_record": "EXPERTISE",
    "cardinality": "1:N"
  },
  {
    "set_name": "EMP-EMPOSITION",
    "parent_record": "EMPLOYEE",
    "child_record": "EMPOSITION",
    "cardinality": "1:N"
  },
  {
    "set_name": "REPORTS-TO",
    "parent_record": "EMPLOYEE",
    "child_record": "STRUCTURE",
    "cardinality": "1:N"
  },
  {
    "set_name": "EMP-COVERAGE",
    "parent_record": "EMPLOYEE",
    "child_record": "COVERAGE",
    "cardinality": "1:N"
  },
  {
    "set_name": "JOB-EMPOSITION",
    "parent_record": "JOB",
    "child_record": "EMPOSITION",
    "cardinality": "1:N"
  },
  {
    "set_name": "COVERAGE-CLAIMS",
    "parent_record": "COVERAGE",
    "child_record": "DENTAL_CLAIM",
    "cardinality": "1:N"
  },
  {
    "set_name": "COVERAGE-CLAIMS",
    "parent_record": "COVERAGE",
    "child_record": "HOSPITAL_CLAIM",
    "cardinality": "1:N"
  }
]

```

```

    },
    {
        "set_name": "COVERAGE-CLAIMS",
        "parent_record": "COVERAGE",
        "child_record": "NON_HOSP_CLAIM",
        "cardinality": "1:N"
    }
]
}

```

```

=====
FILE: data\output\converted_db2_cobol.cb1
ENCODING: utf-8
=====

```

```

*RETRIEVAL
*DMLIST
*NO-ACTIVITY-LOG
*SCHEMA-COMMENTS
IDENTIFICATION DIVISION.
PROGRAM-ID. DEPTRPT.
AUTHOR. CA.
DATE-WRITTEN. APRIL 1995.
REMARKS. THIS PROGRAM DEMONSTRATES
CA IDMS DATABASE ACCESS USING
COBOL DML STATEMENTS. IT READS
DEPARTMENT ID NUMBERS AND RETRIEVES
RELATED RECORD OCCURRENCES,
PRINTING A REPORT THAT INCLUDES
DEPARTMENT, EMPLOYEE, JOB, AND
OFFICE INFORMATION.
*****
ENVIRONMENT DIVISION.
INPUT-OUTPUT SECTION.
FILE-CONTROL.
SELECT DEPT-FILE-IN ASSIGN TO INFILE.
SELECT DEPT-FILE-OUT ASSIGN TO OUTFILE.
SELECT ERR-FILE-OUT ASSIGN TO ERRFILE.
*****

DATA DIVISION.

FILE SECTION.
FD DEPT-FILE-IN
RECORD CONTAINS 80
BLOCK CONTAINS 80 CHARACTERS
RECORDING MODE IS F
LABEL RECORDS ARE OMITTED.
01 DEPT-REC-IN.
02 DEPT-ID-IN PIC 9(4).
02 DEPT-IN-FILLER PIC X(76).
FD DEPT-FILE-OUT
RECORD CONTAINS 133
BLOCK CONTAINS 133 CHARACTERS
RECORDING MODE IS F
LABEL RECORDS ARE OMITTED.
01 DEPT-REC-OUT.
02 CC PIC X.
02 PRINT-LINE PIC X(132).
FD ERR-FILE-OUT
RECORD CONTAINS 133
BLOCK CONTAINS 133 CHARACTERS
RECORDING MODE IS F
LABEL RECORDS ARE OMITTED.
01 ERR-REC-OUT.
02 ERR-CC PIC X.
02 ERR-LINE PIC X(132).
*****
WORKING-STORAGE SECTION.
01 EOF-SW PIC X VALUE 'N'.
88 END-OF-FILE VALUE 'Y'.
01 LINE-COUNT PIC 99 VALUE 0.
01 ERR-LINE-COUNT PIC 99 VALUE 0.
01 LINE-MAX PIC 99 VALUE 50.
*****

```

```

01 DEPT-HEADER.
05 FILLER PIC X(30) VALUE SPACES.
05 FILLER PIC X(13) VALUE 'DEPARTMENT ID'.
05 FILLER PIC X(10) VALUE SPACES.
05 FILLER PIC X(9) VALUE 'DEPT NAME'.
05 FILLER PIC X(70) VALUE SPACES.
01 DEPT-DETAIL-LINE.
05 FILLER PIC X(33) VALUE SPACES.
05 DEPT-ID-OUT PIC X(4).
05 FILLER PIC X(16) VALUE SPACES.
05 DEPT-NAME-OUT PIC X(45).
05 FILLER PIC X(34) VALUE SPACES.
01 EMP-HEADER.
05 FILLER PIC X(5) VALUE SPACES.
05 FILLER PIC X(6) VALUE 'EMP ID'.
05 FILLER PIC X(2) VALUE SPACES.
05 FILLER PIC X(9) VALUE 'LAST NAME'.
05 FILLER PIC X(8) VALUE SPACES.
05 FILLER PIC X(10) VALUE 'FIRST NAME'.
05 FILLER PIC X(3) VALUE SPACES.
05 FILLER PIC X(10) VALUE 'START DATE'.
05 FILLER PIC X(2) VALUE SPACES.
05 FILLER PIC X(9) VALUE 'JOB TITLE'.
05 FILLER PIC X(13) VALUE SPACES.
05 FILLER PIC X(14) VALUE 'OFFICE ADDRESS'.
05 FILLER PIC X(42) VALUE SPACES.
01 EMP-DETAIL-LINE.
05 FILLER PIC X(5) VALUE SPACES.
05 ID-OUT PIC X(4).
05 FILLER PIC X(4) VALUE SPACES.
05 LAST-OUT PIC X(15).
05 FILLER PIC X(2) VALUE SPACES.
05 FIRST-OUT PIC X(10).
05 FILLER PIC X(3) VALUE SPACES.
05 SD-OUT.
10 SD-MM PIC XX.
10 FILLER PIC X VALUE '/'.
10 SD-DD PIC XX.
10 FILLER PIC X VALUE '/'.
10 SD-YY PIC XX.
05 FILLER PIC X(4) VALUE SPACES.
05 TITLE-OUT PIC X(20).
05 FILLER PIC X(2) VALUE SPACES.
05 OFF-ADDRESS-OUT.
10 STREET-OUT PIC X(20).
10 FILLER PIC XX VALUE SPACES.
10 CITY-OUT PIC X(15).
10 FILLER PIC XX VALUE SPACES.
10 STATE-OUT PIC XX.
10 FILLER PIC XX VALUE SPACES.
10 ZIP-OUT PIC X(5).
05 FILLER PIC X(8) VALUE SPACES.
01 ERR-HEADER-1.
05 FILLER PIC X(40) VALUE SPACES.
05 FILLER PIC X(12) VALUE 'ERROR REPORT'.
05 FILLER PIC X(80) VALUE SPACES.
01 ERR-HEADER-2.
05 FILLER PIC X(10) VALUE SPACES.
05 FILLER PIC X(4) VALUE '*** '.
05 FILLER PIC X(51)
VALUE 'THIS REPORT LISTS EMPTY AND NONEXISTENT DEPARTMENTS'.
05 FILLER PIC X(4) VALUE ' ***'.
05 FILLER PIC X(63) VALUE SPACES.
01 ERR-HEADER-3.
05 FILLER PIC X(20) VALUE SPACES.
05 FILLER PIC X(7) VALUE 'DEPT ID'.
05 FILLER PIC X(9) VALUE SPACES.
05 FILLER PIC X(7) VALUE 'MESSAGE'.
05 FILLER PIC X(89) VALUE SPACES.
01 ERR-DETAIL-LINE.
05 FILLER PIC X(20) VALUE SPACES.
05 ERR-ID-OUT PIC X(4).
05 FILLER PIC X(12) VALUE SPACES.
05 ERR-MESS-OUT PIC X(15).
05 FILLER PIC X(79) VALUE SPACES.
*****

```

```

01 MESSAGES.
05 NO-JOB-MESSAGE.
10 FILLER PIC X(20)
VALUE 'NO JOB ASSIGNED'.
05 NO-OFFICE-MESSAGE.
10 FILLER PIC X(20)
VALUE 'NO OFFICE ASSIGNED'.
05 NO-DEPT-MESSAGE.
10 FILLER PIC X(15)
VALUE 'DOES NOT EXIST'.
05 NO-EMP-MESSAGE.
10 FILLER PIC X(15)
VALUE 'IS EMPTY'.
05 NO-INPUT-MESSAGE.
10 FILLER PIC XX VALUE SPACES.
10 FILLER PIC X(11)
VALUE '=====> '.
10 FILLER PIC X(8)
VALUE 'NO INPUT'.
10 FILLER PIC X(11)
VALUE ' <====='.
10 FILLER PIC X(100)
VALUE SPACES.

```

EJECT

```

*****
* DB2 SQLCA, HOST VARIABLES, AND CURSORS
*****

```

```

EXEC SQL
  INCLUDE SQLCA
END-EXEC.
EXEC SQL
  BEGIN DECLARE SECTION
END-EXEC.

```

01 HV-DEPARTMENT.

```

05 HV-DEPARTMENT-DEPT-ID-0410          PIC S9(4) COMP.
05 HV-DEPARTMENT-DEPT-NAME-0410        PIC X(45).
05 HV-DEPARTMENT-DEPT-HEAD-ID-0410     PIC S9(4) COMP.

```

01 HV-EMPLOYEE.

```

05 HV-EMPLOYEE-START-DATE-0415         PIC X(10).
05 HV-EMPLOYEE-TERMINATION-DATE-0415   PIC X(10).
05 HV-EMPLOYEE-BIRTH-DATE-0415        PIC X(10).
05 HV-EMPLOYEE-EMP-ID-0415             PIC S9(4) COMP.
05 HV-EMPLOYEE-EMP-FIRST-NAME-0415     PIC X(10).
05 HV-EMPLOYEE-EMP-LAST-NAME-0415      PIC X(15).
05 HV-EMPLOYEE-EMP-STREET-0415         PIC X(20).
05 HV-EMPLOYEE-EMP-CITY-0415           PIC X(15).
05 HV-EMPLOYEE-EMP-STATE-0415          PIC X(2).
05 HV-EMPLOYEE-EMP-ZIP-FIRST-FIVE-0415 PIC X(5).
05 HV-EMPLOYEE-EMP-ZIP-LAST-FOUR-0415  PIC X(4).
05 HV-EMPLOYEE-EMP-PHONE-0415          PIC S9(4) COMP.
05 HV-EMPLOYEE-STATUS-0415             PIC X(2).
05 HV-EMPLOYEE-SS-NUMBER-0415          PIC S9(4) COMP.
05 HV-EMPLOYEE-DEPT-ID-0410            PIC S9(4) COMP.
05 HV-EMPLOYEE-OFFICE-CODE-0450        PIC X(3).

```

01 HV-EMPOSITION.

```

05 HV-EMPOSITION-START-DATE-0420       PIC X(10).
05 HV-EMPOSITION-FINISH-DATE-0420      PIC X(10).
05 HV-EMPOSITION-SALARY-GRADE-0420     PIC S9(4) COMP.
05 HV-EMPOSITION-SALARY-AMOUNT-0420    PIC S9(1)V9(2) COMP-3.
05 HV-EMPOSITION-BONUS-PERCENT-0420    PIC S9(1)V9(3) COMP-3.
05 HV-EMPOSITION-COMMISSION-PERCENT-0420 PIC S9(1)V9(3) COMP-3.
05 HV-EMPOSITION-OVERTIME-RATE-0420    PIC S9(1)V9(2) COMP-3.
05 HV-EMPOSITION-EMP-ID-0415           PIC S9(4) COMP.
05 HV-EMPOSITION-JOB-ID-0440           PIC S9(4) COMP.

```

01 HV-JOB.

```

05 HV-JOB-JOB-ID-0440                  PIC S9(4) COMP.
05 HV-JOB-TITLE-0440                   PIC X(20).
05 HV-JOB-DESCRIPTION-LINE-0440        PIC X(120).
05 HV-JOB-REQUIREMENT-LINE-0440      PIC X(120).
05 HV-JOB-MINIMUM-SALARY-0440          PIC S9(1)V9(2) COMP-3.
05 HV-JOB-MAXIMUM-SALARY-0440         PIC S9(1)V9(2) COMP-3.

```

05 HV-JOB-SALARY-GRADES-0440	PIC S9(4) COMP.
05 HV-JOB-NUMBER-OF-POSITIONS-0440	PIC S9(4) COMP.
05 HV-JOB-NUMBER-OPEN-0440	PIC S9(4) COMP.
01 HV-OFFICE.	
05 HV-OFFICE-OFFICE-CODE-0450	PIC X(3).
05 HV-OFFICE-OFFICE-STREET-0450	PIC X(20).
05 HV-OFFICE-OFFICE-CITY-0450	PIC X(15).
05 HV-OFFICE-OFFICE-STATE-0450	PIC X(2).
05 HV-OFFICE-OFFICE-ZIP-FIRST-FIVE-0450	PIC X(5).
05 HV-OFFICE-OFFICE-ZIP-LAST-FOUR-0450	PIC X(4).
05 HV-OFFICE-OFFICE-PHONE-0450	PIC S9(4) COMP.
05 HV-OFFICE-OFFICE-AREA-CODE-0450	PIC X(3).
05 HV-OFFICE-SPEED-DIAL-0450	PIC X(3).
01 NI-DEPARTMENT-DEPT-NAME-0410	PIC S9(4) COMP.
01 NI-DEPARTMENT-DEPT-HEAD-ID-0410	PIC S9(4) COMP.
01 NI-EMPLOYEE-TERMINATION-DATE-0415	PIC S9(4) COMP.
01 NI-EMPLOYEE-BIRTH-DATE-0415	PIC S9(4) COMP.
01 NI-EMPLOYEE-EMP-FIRST-NAME-0415	PIC S9(4) COMP.
01 NI-EMPLOYEE-EMP-LAST-NAME-0415	PIC S9(4) COMP.
01 NI-EMPLOYEE-EMP-STREET-0415	PIC S9(4) COMP.
01 NI-EMPLOYEE-EMP-CITY-0415	PIC S9(4) COMP.
01 NI-EMPLOYEE-EMP-STATE-0415	PIC S9(4) COMP.
01 NI-EMPLOYEE-EMP-ZIP-FIRST-FIVE-0415	PIC S9(4) COMP.
01 NI-EMPLOYEE-EMP-ZIP-LAST-FOUR-0415	PIC S9(4) COMP.
01 NI-EMPLOYEE-EMP-PHONE-0415	PIC S9(4) COMP.
01 NI-EMPLOYEE-STATUS-0415	PIC S9(4) COMP.
01 NI-EMPLOYEE-SS-NUMBER-0415	PIC S9(4) COMP.
01 NI-EMPLOYEE-DEPT-ID-0410	PIC S9(4) COMP.
01 NI-EMPLOYEE-OFFICE-CODE-0450	PIC S9(4) COMP.
01 NI-EMPOSITION-FINISH-DATE-0420	PIC S9(4) COMP.
01 NI-EMPOSITION-SALARY-GRADE-0420	PIC S9(4) COMP.
01 NI-EMPOSITION-SALARY-AMOUNT-0420	PIC S9(4) COMP.
01 NI-EMPOSITION-BONUS-PERCENT-0420	PIC S9(4) COMP.
01 NI-EMPOSITION-COMMISSION-PERCENT-0420	PIC S9(4) COMP.
01 NI-EMPOSITION-OVERTIME-RATE-0420	PIC S9(4) COMP.
01 NI-EMPOSITION-EMP-ID-0415	PIC S9(4) COMP.
01 NI-EMPOSITION-JOB-ID-0440	PIC S9(4) COMP.
01 NI-JOB-TITLE-0440	PIC S9(4) COMP.
01 NI-JOB-DESCRIPTION-LINE-0440	PIC S9(4) COMP.
01 NI-JOB-REQUIREMENT-LINE-0440	PIC S9(4) COMP.
01 NI-JOB-MINIMUM-SALARY-0440	PIC S9(4) COMP.
01 NI-JOB-MAXIMUM-SALARY-0440	PIC S9(4) COMP.
01 NI-JOB-SALARY-GRADES-0440	PIC S9(4) COMP.
01 NI-JOB-NUMBER-OF-POSITIONS-0440	PIC S9(4) COMP.
01 NI-JOB-NUMBER-OPEN-0440	PIC S9(4) COMP.
01 NI-OFFICE-OFFICE-STREET-0450	PIC S9(4) COMP.
01 NI-OFFICE-OFFICE-CITY-0450	PIC S9(4) COMP.
01 NI-OFFICE-OFFICE-STATE-0450	PIC S9(4) COMP.
01 NI-OFFICE-OFFICE-ZIP-FIRST-FIVE-0450	PIC S9(4) COMP.
01 NI-OFFICE-OFFICE-ZIP-LAST-FOUR-0450	PIC S9(4) COMP.
01 NI-OFFICE-OFFICE-PHONE-0450	PIC S9(4) COMP.
01 NI-OFFICE-OFFICE-AREA-CODE-0450	PIC S9(4) COMP.
01 NI-OFFICE-SPEED-DIAL-0450	PIC S9(4) COMP.
EXEC SQL	
END DECLARE SECTION	
END-EXEC.	
EXEC SQL	
DECLARE C-DEPT-EMPLOYEE CURSOR FOR	
SELECT START_DATE_0415,	
TERMINATION_DATE_0415,	
BIRTH_DATE_0415,	
EMP_ID_0415,	
EMP_FIRST_NAME_0415,	
EMP_LAST_NAME_0415,	
EMP_STREET_0415,	
EMP_CITY_0415,	
EMP_STATE_0415,	
EMP_ZIP_FIRST_FIVE_0415,	
EMP_ZIP_LAST_FOUR_0415,	
EMP_PHONE_0415,	
STATUS_0415,	
SS_NUMBER_0415,	
DEPT_ID_0410,	
OFFICE_CODE_0450	

```

        FROM EMPLOYEE
        WHERE DEPT_ID_0410 = :HV-DEPARTMENT-DEPT-ID-0410
        ORDER BY DEPT_ID_0410
END-EXEC.

PROCEDURE DIVISION.
*****
* PROCEDURE DIVISION GENERAL STRATEGY: *
* *
* 1) READ DEPT-ID-IN, WHICH CONTAINS THE *
* DEPT-ID NUMBER *
* *
* 2) ACCESS THE DATABASE USING THE DEPT-ID NUMBER *
* WITH AN OBTAIN CALC ON THE DEPARTMENT RECORD *
* *
* 3) ACCESS ALL EMPLOYEES IN THE DEPT-EMPLOYEE SET *
* AND RETRIEVE RELATED JOB AND OFFICE DATA *
* *
* 4) PRINT A REPORT FOR EACH DEPARTMENT *
* *
* 5) PRINT AN ERROR REPORT FOR EMPTY DEPARTMENTS *
* AND NONEXISTENT DEPARTMENTS (NO MATCHING *
* DEPT-ID) *
*****
FETCH-DEPT-EMPLOYEE.
    EXEC SQL
        FETCH C-DEPT-EMPLOYEE
        INTO :HV-EMPLOYEE-START-DATE-0415,
            :HV-EMPLOYEE-TERMINATION-DATE-0415 :NI-EMPLOYEE-TERMINATION-DATE-0415,
            :HV-EMPLOYEE-BIRTH-DATE-0415 :NI-EMPLOYEE-BIRTH-DATE-0415,
            :HV-EMPLOYEE-EMP-ID-0415,
            :HV-EMPLOYEE-EMP-FIRST-NAME-0415 :NI-EMPLOYEE-EMP-FIRST-NAME-0415,
            :HV-EMPLOYEE-EMP-LAST-NAME-0415 :NI-EMPLOYEE-EMP-LAST-NAME-0415,
            :HV-EMPLOYEE-EMP-STREET-0415 :NI-EMPLOYEE-EMP-STREET-0415,
            :HV-EMPLOYEE-EMP-CITY-0415 :NI-EMPLOYEE-EMP-CITY-0415,
            :HV-EMPLOYEE-EMP-STATE-0415 :NI-EMPLOYEE-EMP-STATE-0415,
            :HV-EMPLOYEE-EMP-ZIP-FIRST-FIVE-0415 :NI-EMPLOYEE-EMP-ZIP-FIRST-FIVE-0415,
            :HV-EMPLOYEE-EMP-ZIP-LAST-FOUR-0415 :NI-EMPLOYEE-EMP-ZIP-LAST-FOUR-0415,
            :HV-EMPLOYEE-EMP-PHONE-0415 :NI-EMPLOYEE-EMP-PHONE-0415,
            :HV-EMPLOYEE-STATUS-0415 :NI-EMPLOYEE-STATUS-0415,
            :HV-EMPLOYEE-SS-NUMBER-0415 :NI-EMPLOYEE-SS-NUMBER-0415,
            :HV-EMPLOYEE-DEPT-ID-0410 :NI-EMPLOYEE-DEPT-ID-0410,
            :HV-EMPLOYEE-OFFICE-CODE-0450 :NI-EMPLOYEE-OFFICE-CODE-0450
    END-EXEC.
    IF SQLCODE NOT = 0 AND SQLCODE NOT = 100
        PERFORM SQL-ERROR
    END-IF.
MAIN-LINE.
    PERFORM INIT-FILES.
    IF END-OF-FILE
        PERFORM EMPTY-INPUT-PROCESSING
    ELSE
        PERFORM INIT-DB2-SETUP
        PERFORM U220-ERR-HEADER
        PERFORM DEPT-PROCESSING THRU DEPT-PROCESSING-EXIT
UNTIL END-OF-FILE.
    PERFORM END-PROCESSING.
    GOBACK.
INIT-DB2-SETUP.
    CONTINUE.
INIT-FILES.
    OPEN INPUT DEPT-FILE-IN.
    OPEN OUTPUT DEPT-FILE-OUT.
    OPEN OUTPUT ERR-FILE-OUT.
    MOVE SPACES TO PRINT-LINE.
    MOVE SPACES TO ERR-LINE.
    READ DEPT-FILE-IN
        AT END MOVE 'Y' TO EOF-SW.
EMPTY-INPUT-PROCESSING.
    MOVE NO-INPUT-MESSAGE TO PRINT-LINE.
    MOVE '1' TO CC.
    PERFORM U000-WRITE-LINE.
*****
* THIS PARAGRAPH ACCESSES THE DATABASE USING THE DEPT-ID-0415 *
* CALCKEY VALUE. *
*****

```

```

DEPT-PROCESSING.
  MOVE DEPT-ID-IN TO HV-DEPARTMENT-DEPT-ID-0410.
  EXEC SQL
    SELECT DEPT_ID_0410,
           DEPT_NAME_0410,
           DEPT_HEAD_ID_0410
  INTO :HV-DEPARTMENT-DEPT-ID-0410,
       :HV-DEPARTMENT-DEPT-NAME-0410 :NI-DEPARTMENT-DEPT-NAME-0410,
       :HV-DEPARTMENT-DEPT-HEAD-ID-0410 :NI-DEPARTMENT-DEPT-HEAD-ID-0410
  FROM DEPARTMENT
  WHERE DEPT_ID_0410 = :HV-DEPARTMENT-DEPT-ID-0410
END-EXEC.
IF SQLCODE = 100
  PERFORM NO-DEPT-PROCESSING
ELSE
  IF SQLCODE NOT = 0
    PERFORM SQL-ERROR
  ELSE
    EXEC SQL
      OPEN C-DEPT-EMPLOYEE
    END-EXEC.
  IF SQLCODE NOT = 0
    PERFORM SQL-ERROR
  ELSE
    PERFORM FETCH-DEPT-EMPLOYEE

  IF SQLCODE = 100
    PERFORM EMPTY-SET
  ELSE
    PERFORM U020-VALID-HEADER
    MOVE HV-DEPARTMENT-DEPT-ID-0410 TO DEPT-ID-OUT
    MOVE HV-DEPARTMENT-DEPT-NAME-0410 TO DEPT-NAME-OUT
    MOVE DEPT-DETAIL-LINE TO PRINT-LINE
    PERFORM U000-WRITE-LINE
    PERFORM U030-EMP-HEADERS

  PERFORM UNTIL SQLCODE = 100
    PERFORM SET-WALK THRU SET-WALK-EXIT
    PERFORM FETCH-DEPT-EMPLOYEE
  END-PERFORM
END-IF.
EXEC SQL
  CLOSE C-DEPT-EMPLOYEE
END-EXEC.
END-IF.
END-IF.
END-IF.
READ DEPT-FILE-IN
  AT END MOVE 'Y' TO EOF-SW.
DEPT-PROCESSING-EXIT.
EXIT.
*****
* THIS PARAGRAPH RETRIEVES EMPLOYEE, JOB, AND OFFICE DATA *
* FOR EACH EMPLOYEE IN THE DEPT-EMPLOYEE SET. *
*****
SET-WALK.
  CONTINUE.
  MOVE HV-EMPLOYEE-EMP-ID-0415 TO ID-OUT.
  MOVE HV-EMPLOYEE-EMP-LAST-NAME-0415 TO LAST-OUT.
  MOVE HV-EMPLOYEE-EMP-FIRST-NAME-0415 TO FIRST-OUT.
  MOVE HV-EMPLOYEE-START-DATE-0415(3:2) TO SD-YY.
  MOVE HV-EMPLOYEE-START-DATE-0415(6:2) TO SD-MM.
  MOVE HV-EMPLOYEE-START-DATE-0415(9:2) TO SD-DD.
  EXEC SQL
    SELECT START_DATE_0420,
           FINISH_DATE_0420,
           SALARY_GRADE_0420,
           SALARY_AMOUNT_0420,
           BONUS_PERCENT_0420,
           COMMISSION_PERCENT_0420,
           OVERTIME_RATE_0420,
           EMP_ID_0415,
           JOB_ID_0440
  INTO :HV-EMPOSITION-START-DATE-0420,
       :HV-EMPOSITION-FINISH-DATE-0420 :NI-EMPOSITION-FINISH-DATE-0420,
       :HV-EMPOSITION-SALARY-GRADE-0420 :NI-EMPOSITION-SALARY-GRADE-0420,

```

```

:HV-EMPOSITION-SALARY-AMOUNT-0420 :NI-EMPOSITION-SALARY-AMOUNT-0420,
:HV-EMPOSITION-BONUS-PERCENT-0420 :NI-EMPOSITION-BONUS-PERCENT-0420,
:HV-EMPOSITION-COMMISSION-PERCENT-0420 :NI-EMPOSITION-COMMISSION-PERCENT-0420,
:HV-EMPOSITION-OVERTIME-RATE-0420 :NI-EMPOSITION-OVERTIME-RATE-0420,
:HV-EMPOSITION-EMP-ID-0415 :NI-EMPOSITION-EMP-ID-0415,
:HV-EMPOSITION-JOB-ID-0440 :NI-EMPOSITION-JOB-ID-0440
FROM EMPOSITION
WHERE EMP_ID_0415 = :HV-EMPLOYEE-EMP-ID-0415
ORDER BY EMP_ID_0415
FETCH FIRST 1 ROW ONLY
END-EXEC.
IF SQLCODE = 100
MOVE NO-JOB-MESSAGE TO TITLE-OUT
ELSE
IF SQLCODE NOT = 0
PERFORM SQL-ERROR
ELSE
EXEC SQL
    SELECT JOB_ID_0440,
    TITLE_0440,
    DESCRIPTION_LINE_0440,
    REQUIREMENT_LINE_0440,
    MINIMUM_SALARY_0440,
    MAXIMUM_SALARY_0440,
    SALARY_GRADES_0440,
    NUMBER_OF_POSITIONS_0440,
    NUMBER_OPEN_0440
INTO :HV-JOB-JOB-ID-0440,
:HV-JOB-TITLE-0440 :NI-JOB-TITLE-0440,
:HV-JOB-DESCRIPTION-LINE-0440 :NI-JOB-DESCRIPTION-LINE-0440,
:HV-JOB-REQUIREMENT-LINE-0440 :NI-JOB-REQUIREMENT-LINE-0440,
:HV-JOB-MINIMUM-SALARY-0440 :NI-JOB-MINIMUM-SALARY-0440,
:HV-JOB-MAXIMUM-SALARY-0440 :NI-JOB-MAXIMUM-SALARY-0440,
:HV-JOB-SALARY-GRADES-0440 :NI-JOB-SALARY-GRADES-0440,
:HV-JOB-NUMBER-OF-POSITIONS-0440 :NI-JOB-NUMBER-OF-POSITIONS-0440,
:HV-JOB-NUMBER-OPEN-0440 :NI-JOB-NUMBER-OPEN-0440
FROM JOB
WHERE JOB_ID_0440 = :HV-EMPOSITION-JOB-ID-0440
END-EXEC.
IF SQLCODE = 100
MOVE NO-JOB-MESSAGE TO TITLE-OUT
ELSE
IF SQLCODE NOT = 0
PERFORM SQL-ERROR
ELSE
CONTINUE.
END-IF.
END-IF.
END-IF.
END-IF.
MOVE HV-JOB-TITLE-0440 TO TITLE-OUT.
IF NI-EMPLOYEE-OFFICE-CODE-0450 < 0
MOVE NO-OFFICE-MESSAGE TO STREET-OUT
MOVE SPACES TO CITY-OUT
MOVE SPACES TO STATE-OUT
MOVE SPACES TO ZIP-OUT
ELSE
EXEC SQL
    SELECT OFFICE_CODE_0450,
    OFFICE_STREET_0450,
    OFFICE_CITY_0450,
    OFFICE_STATE_0450,
    OFFICE_ZIP_FIRST_FIVE_0450,
    OFFICE_ZIP_LAST_FOUR_0450,
    OFFICE_PHONE_0450,
    OFFICE_AREA_CODE_0450,
    SPEED_DIAL_0450
INTO :HV-OFFICE-OFFICE-CODE-0450,
:HV-OFFICE-OFFICE-STREET-0450 :NI-OFFICE-OFFICE-STREET-0450,
:HV-OFFICE-OFFICE-CITY-0450 :NI-OFFICE-OFFICE-CITY-0450,
:HV-OFFICE-OFFICE-STATE-0450 :NI-OFFICE-OFFICE-STATE-0450,
:HV-OFFICE-OFFICE-ZIP-FIRST-FIVE-0450 :NI-OFFICE-OFFICE-ZIP-FIRST-FIVE-0450,
:HV-OFFICE-OFFICE-ZIP-LAST-FOUR-0450 :NI-OFFICE-OFFICE-ZIP-LAST-FOUR-0450,
:HV-OFFICE-OFFICE-PHONE-0450 :NI-OFFICE-OFFICE-PHONE-0450,
:HV-OFFICE-OFFICE-AREA-CODE-0450 :NI-OFFICE-OFFICE-AREA-CODE-0450,
:HV-OFFICE-SPEED-DIAL-0450 :NI-OFFICE-SPEED-DIAL-0450

```



```

        FROM OFFICE
        WHERE OFFICE_CODE_0450 = :HV-EMPLOYEE-OFFICE-CODE-0450
END-EXEC.
IF SQLCODE = 0
CONTINUE.
ELSE
MOVE NO-OFFICE-MESSAGE TO STREET-OUT
MOVE SPACES TO CITY-OUT
MOVE SPACES TO STATE-OUT
MOVE SPACES TO ZIP-OUT
END-IF.
END-IF.
MOVE HV-OFFICE-OFFICE-STREET-0450 TO STREET-OUT
MOVE HV-OFFICE-OFFICE-CITY-0450 TO CITY-OUT
MOVE HV-OFFICE-OFFICE-STATE-0450 TO STATE-OUT
MOVE HV-OFFICE-OFFICE-ZIP-FIRST-FIVE-0450 TO ZIP-OUT
MOVE EMP-DETAIL-LINE TO PRINT-LINE.
PERFORM U000-WRITE-LINE.
SET-WALK-EXIT.
EXIT.
END-PROCESSING.
CLOSE DEPT-FILE-OUT.
CLOSE ERR-FILE-OUT.
CLOSE DEPT-FILE-IN.
EMPTY-SET.
MOVE SPACES TO ERR-LINE.
MOVE HV-DEPARTMENT-DEPT-ID-0410 TO ERR-ID-OUT.
MOVE NO-EMP-MESSAGE TO ERR-MESS-OUT.
MOVE ERR-DETAIL-LINE TO ERR-LINE.
PERFORM U200-WRITE-ERR-LINE.
NO-DEPT-PROCESSING.
MOVE DEPT-ID-IN TO ERR-ID-OUT.
MOVE NO-DEPT-MESSAGE TO ERR-MESS-OUT.
MOVE ERR-DETAIL-LINE TO ERR-LINE.
PERFORM U200-WRITE-ERR-LINE.
U000-WRITE-LINE.
WRITE DEPT-REC-OUT AFTER POSITIONING CC.
IF CC = '1'
THEN MOVE 0 TO LINE-COUNT
ELSE IF CC = ' '
THEN ADD 1 TO LINE-COUNT
ELSE IF CC = '0'
THEN ADD 2 TO LINE-COUNT.
IF LINE-COUNT > LINE-MAX
THEN PERFORM U010-NEW-PAGE-ROUTINE.
U010-NEW-PAGE-ROUTINE.
PERFORM U020-VALID-HEADER.
MOVE DEPT-DETAIL-LINE TO PRINT-LINE.
PERFORM U000-WRITE-LINE.
PERFORM U030-EMP-HEADERS.
U020-VALID-HEADER.
MOVE DEPT-HEADER TO PRINT-LINE.
MOVE '1' TO CC.
PERFORM U000-WRITE-LINE.
MOVE ' ' TO CC.
U030-EMP-HEADERS.
MOVE '0' TO CC.
MOVE EMP-HEADER TO PRINT-LINE.
PERFORM U000-WRITE-LINE.
MOVE SPACES TO PRINT-LINE.
MOVE ' ' TO CC.
PERFORM U000-WRITE-LINE.
U200-WRITE-ERR-LINE.
WRITE ERR-REC-OUT AFTER POSITIONING ERR-CC.
IF ERR-CC = '1'
THEN MOVE 0 TO ERR-LINE-COUNT
ELSE IF ERR-CC = ' '
THEN ADD 1 TO ERR-LINE-COUNT
ELSE IF ERR-CC = '0'
THEN ADD 2 TO ERR-LINE-COUNT.
IF ERR-LINE-COUNT > LINE-MAX
THEN
PERFORM U220-ERR-HEADER.
U220-ERR-HEADER.
MOVE ERR-HEADER-1 TO ERR-LINE.
MOVE '1' TO ERR-CC.

```

```

PERFORM U200-WRITE-ERR-LINE.
MOVE '0' TO ERR-CC.
MOVE ERR-HEADER-2 TO ERR-LINE.
PERFORM U200-WRITE-ERR-LINE.
MOVE ERR-HEADER-3 TO ERR-LINE.
PERFORM U200-WRITE-ERR-LINE.
MOVE SPACES TO ERR-LINE.
MOVE ' ' TO ERR-CC.
PERFORM U200-WRITE-ERR-LINE.

```

SQL-ERROR.

```

MOVE SPACES TO ERR-LINE.
MOVE 'SQL ERROR' TO ERR-MESS-OUT.
MOVE ERR-DETAIL-LINE TO ERR-LINE.
PERFORM U200-WRITE-ERR-LINE.

```

SQL-ERROR-EXIT.

EXIT.

```

=====
FILE: data\output\db2_ddl.sql
ENCODING: utf-8
=====

```

CREATE TABLE COVERAGE

```

(
    COVERAGE_ID BIGINT NOT NULL,
    SELECTION_DATE_0400 DATE,
    TERMINATION_DATE_0400 DATE,
    TYPE_0400 CHAR(1),
    INS_PLAN_CODE_0400 VARCHAR(3),
    EMP_ID_0415 SMALLINT,
    PRIMARY KEY (COVERAGE_ID)
);

```

CREATE TABLE DENTAL_CLAIM

```

(
    CLAIM_DATE_0405 DATE,
    PATIENT_BIRTH_DATE_0405 DATE,
    SERVICE_DATE_0405 DATE,
    PATIENT_FIRST_NAME_0405 VARCHAR(10),
    PATIENT_LAST_NAME_0405 VARCHAR(15),
    PATIENT_SEX_0405 CHAR(1),
    RELATION_TO_EMPLOYEE_0405 VARCHAR(10),
    DENTIST_FIRST_NAME_0405 VARCHAR(10),
    DENTIST_LAST_NAME_0405 VARCHAR(15),
    DENTIST_STREET_0405 VARCHAR(20),
    DENTIST_CITY_0405 VARCHAR(15),
    DENTIST_STATE_0405 VARCHAR(2),
    DENTIST_ZIP_FIRST_FIVE_0405 VARCHAR(5),
    DENTIST_ZIP_LAST_FOUR_0405 VARCHAR(4),
    DENTIST_LICENSE_NUMBER_0405 SMALLINT,
    NUMBER_OF_PROCEDURES_0405 DECIMAL(1,0),
    TOOTH_NUMBER_0405 SMALLINT,
    PROCEDURE_CODE_0405 SMALLINT,
    DESCRIPTION_OF_SERVICE_0405 VARCHAR(60),
    FEE_0405 DECIMAL(2,2),
    COVERAGE_ID BIGINT
);

```

CREATE TABLE DEPARTMENT

```

(
    DEPT_ID_0410 SMALLINT NOT NULL,
    DEPT_NAME_0410 VARCHAR(45),
    DEPT_HEAD_ID_0410 SMALLINT,
    PRIMARY KEY (DEPT_ID_0410)
);

```

CREATE TABLE EMPLOYEE

```

(
    START_DATE_0415 DATE,
    TERMINATION_DATE_0415 DATE,
    BIRTH_DATE_0415 DATE,
    EMP_ID_0415 SMALLINT NOT NULL,
    EMP_FIRST_NAME_0415 VARCHAR(10),

```

```

EMP_LAST_NAME_0415 VARCHAR(15),
EMP_STREET_0415 VARCHAR(20),
EMP_CITY_0415 VARCHAR(15),
EMP_STATE_0415 VARCHAR(2),
EMP_ZIP_FIRST_FIVE_0415 VARCHAR(5),
EMP_ZIP_LAST_FOUR_0415 VARCHAR(4),
EMP_PHONE_0415 SMALLINT,
STATUS_0415 VARCHAR(2),
SS_NUMBER_0415 SMALLINT,
DEPT_ID_0410 SMALLINT,
OFFICE_CODE_0450 VARCHAR(3),
PRIMARY KEY (EMP_ID_0415)
);

CREATE TABLE EMPOSITION
(
    START_DATE_0420 DATE,
    FINISH_DATE_0420 DATE,
    SALARY_GRADE_0420 SMALLINT,
    SALARY_AMOUNT_0420 DECIMAL(2,2),
    BONUS_PERCENT_0420 DECIMAL(3,3),
    COMMISSION_PERCENT_0420 DECIMAL(3,3),
    OVERTIME_RATE_0420 DECIMAL(3,2),
    EMP_ID_0415 SMALLINT,
    JOB_ID_0440 SMALLINT
);

CREATE TABLE EXPERTISE
(
    EXPERTISE_DATE_0425 DATE,
    SKILL_LEVEL_0425 VARCHAR(2),
    EMP_ID_0415 SMALLINT,
    SKILL_ID_0455 SMALLINT
);

CREATE TABLE HOSPITAL_CLAIM
(
    CLAIM_DATE_0430 DATE,
    PATIENT_BIRTH_DATE_0430 DATE,
    ADMIT_DATE_0430 DATE,
    DISCHARGE_DATE_0430 DATE,
    PATIENT_FIRST_NAME_0430 VARCHAR(10),
    PATIENT_LAST_NAME_0430 VARCHAR(15),
    PATIENT_SEX_0430 CHAR(1),
    RELATION_TO_EMPLOYEE_0430 VARCHAR(10),
    HOSPITAL_NAME_0430 VARCHAR(25),
    HOSP_STREET_0430 VARCHAR(20),
    HOSP_CITY_0430 VARCHAR(15),
    HOSP_STATE_0430 VARCHAR(2),
    HOSP_ZIP_FIRST_FIVE_0430 VARCHAR(5),
    HOSP_ZIP_LAST_FOUR_0430 VARCHAR(4),
    DIAGNOSIS_0430 VARCHAR(120),
    WARD_DAYS_0430 DECIMAL(5,0),
    WARD_RATE_0430 DECIMAL(2,2),
    WARD_TOTAL_0430 DECIMAL(2,2),
    SEMI_DAYS_0430 DECIMAL(5,0),
    SEMI_RATE_0430 DECIMAL(2,2),
    SEMI_TOTAL_0430 DECIMAL(2,2),
    DELIVERY_COST_0430 DECIMAL(2,2),
    ANESTHESIA_COST_0430 DECIMAL(2,2),
    LAB_COST_0430 DECIMAL(2,2),
    COVERAGE_ID BIGINT
);

CREATE TABLE INSURANCE_PLAN
(
    INS_PLAN_CODE_0435 VARCHAR(3) NOT NULL,
    INS_CO_NAME_0435 VARCHAR(45),
    INS_CO_STREET_0435 VARCHAR(20),
    INS_CO_CITY_0435 VARCHAR(15),
    INS_CO_STATE_0435 VARCHAR(2),
    INS_CO_ZIP_FIRST_FIVE_0435 VARCHAR(5),
    INS_CO_ZIP_LAST_FOUR_0435 VARCHAR(4),
    INS_CO_PHONE_0435 SMALLINT,
    GROUP_NUMBER_0435 SMALLINT,
    DEDUCT_0435 DECIMAL(2,2),

```

```

        MAXIMUM_LIFE_COST_0435 DECIMAL(2,2),
        FAMILY_COST_0435 DECIMAL(2,2),
        DEP_COST_0435 DECIMAL(2,2),
        PRIMARY KEY (INS_PLAN_CODE_0435)
    );

CREATE TABLE JOB
(
    JOB_ID_0440 SMALLINT NOT NULL,
    TITLE_0440 VARCHAR(20),
    DESCRIPTION_LINE_0440 VARCHAR(120),
    REQUIREMENT_LINE_0440 VARCHAR(120),
    MINIMUM_SALARY_0440 DECIMAL(2,2),
    MAXIMUM_SALARY_0440 DECIMAL(2,2),
    SALARY_GRADES_0440 SMALLINT,
    NUMBER_OF_POSITIONS_0440 SMALLINT,
    NUMBER_OPEN_0440 SMALLINT,
    PRIMARY KEY (JOB_ID_0440)
);

CREATE TABLE NON_HOSP_CLAIM
(
    CLAIM_DATE_0445 DATE,
    PATIENT_BIRTH_DATE_0445 DATE,
    SERVICE_DATE_0445 DATE,
    PATIENT_FIRST_NAME_0445 VARCHAR(10),
    PATIENT_LAST_NAME_0445 VARCHAR(15),
    PATIENT_SEX_0445 CHAR(1),
    RELATION_TO_EMPLOYEE_0445 VARCHAR(10),
    PHYSICIAN_FIRST_NAME_0445 VARCHAR(10),
    PHYSICIAN_LAST_NAME_0445 VARCHAR(15),
    PHYSICIAN_STREET_0445 VARCHAR(20),
    PHYSICIAN_CITY_0445 VARCHAR(15),
    PHYSICIAN_STATE_0445 VARCHAR(2),
    PHYSICIAN_ZIP_FIRST_FIVE_0445 VARCHAR(5),
    PHYSICIAN_ZIP_LAST_FOUR_0445 VARCHAR(4),
    PHYSICIAN_ID_0445 SMALLINT,
    DIAGNOSIS_0445 VARCHAR(120),
    NUMBER_OF_PROCEDURES_0445 DECIMAL(1,0),
    PROCEDURE_CODE_0445 SMALLINT,
    DESCRIPTION_OF_SERVICE_0445 VARCHAR(60),
    FEE_0445 DECIMAL(2,2),
    COVERAGE_ID BIGINT
);

CREATE TABLE OFFICE
(
    OFFICE_CODE_0450 VARCHAR(3) NOT NULL,
    OFFICE_STREET_0450 VARCHAR(20),
    OFFICE_CITY_0450 VARCHAR(15),
    OFFICE_STATE_0450 VARCHAR(2),
    OFFICE_ZIP_FIRST_FIVE_0450 VARCHAR(5),
    OFFICE_ZIP_LAST_FOUR_0450 VARCHAR(4),
    OFFICE_PHONE_0450 SMALLINT,
    OFFICE_AREA_CODE_0450 VARCHAR(3),
    SPEED_DIAL_0450 VARCHAR(3),
    PRIMARY KEY (OFFICE_CODE_0450)
);

CREATE TABLE SKILL
(
    SKILL_ID_0455 SMALLINT NOT NULL,
    SKILL_NAME_0455 VARCHAR(12),
    SKILL_DESCRIPTION_0455 VARCHAR(60),
    PRIMARY KEY (SKILL_ID_0455)
);

CREATE TABLE STRUCTURE
(
    STRUCTURE_DATE_0460 DATE,
    STRUCTURE_CODE_0460 VARCHAR(2),
    MANAGES_EMP_ID_0415 SMALLINT,
    REPORTS_TO_EMP_ID_0415 SMALLINT
);

```

```

ALTER TABLE COVERAGE ADD FOREIGN KEY (EMP_ID_0415) REFERENCES EMPLOYEE (EMP_ID_0415);
ALTER TABLE COVERAGE ADD FOREIGN KEY (INS_PLAN_CODE_0400) REFERENCES INSURANCE_PLAN (INS_PLAN_CODE_0435);
ALTER TABLE DENTAL_CLAIM ADD FOREIGN KEY (COVERAGE_ID) REFERENCES COVERAGE (COVERAGE_ID);
ALTER TABLE EMPLOYEE ADD FOREIGN KEY (DEPT_ID_0410) REFERENCES DEPARTMENT (DEPT_ID_0410);
ALTER TABLE EMPLOYEE ADD FOREIGN KEY (OFFICE_CODE_0450) REFERENCES OFFICE (OFFICE_CODE_0450);
ALTER TABLE EMPOSITION ADD FOREIGN KEY (EMP_ID_0415) REFERENCES EMPLOYEE (EMP_ID_0415);
ALTER TABLE EMPOSITION ADD FOREIGN KEY (JOB_ID_0440) REFERENCES JOB (JOB_ID_0440);
ALTER TABLE EXPERTISE ADD FOREIGN KEY (EMP_ID_0415) REFERENCES EMPLOYEE (EMP_ID_0415);
ALTER TABLE EXPERTISE ADD FOREIGN KEY (SKILL_ID_0455) REFERENCES SKILL (SKILL_ID_0455);
ALTER TABLE HOSPITAL_CLAIM ADD FOREIGN KEY (COVERAGE_ID) REFERENCES COVERAGE (COVERAGE_ID);
ALTER TABLE NON_HOSP_CLAIM ADD FOREIGN KEY (COVERAGE_ID) REFERENCES COVERAGE (COVERAGE_ID);
ALTER TABLE STRUCTURE ADD FOREIGN KEY (MANAGES_EMP_ID_0415) REFERENCES EMPLOYEE (EMP_ID_0415);
ALTER TABLE STRUCTURE ADD FOREIGN KEY (REPORTS_TO_EMP_ID_0415) REFERENCES EMPLOYEE (EMP_ID_0415);

```

```

=====
FILE: data\output\phase2_metadata.json
ENCODING: utf-8
=====

```

```

{
  "version": "1.0",
  "generated_at": "2026-07-23T11:24:59.689661Z",
  "source": "PHASE1",
  "schema_source": "PHASE1_CANONICAL_DB2_METADATA",
  "record_table_map": {
    "COVERAGE": "COVERAGE",
    "DENTAL_CLAIM": "DENTAL_CLAIM",
    "DEPARTMENT": "DEPARTMENT",
    "EMPLOYEE": "EMPLOYEE",
    "EMPOSITION": "EMPOSITION",
    "EXPERTISE": "EXPERTISE",
    "HOSPITAL_CLAIM": "HOSPITAL_CLAIM",
    "INSURANCE_PLAN": "INSURANCE_PLAN",
    "JOB": "JOB",
    "NON_HOSP_CLAIM": "NON_HOSP_CLAIM",
    "OFFICE": "OFFICE",
    "SKILL": "SKILL",
    "STRUCTURE": "STRUCTURE"
  },
  "records": [
    {
      "name": "COVERAGE",
      "table": "COVERAGE",
      "primary_key": "COVERAGE_ID",
      "fields": [
        {
          "name": "COVERAGE_ID",
          "column": "COVERAGE_ID",
          "datatype": "BIGINT",
          "length": 18,
          "scale": 0,
          "nullable": false,
          "primary_key": true
        }
      ],
      {
        "name": "SELECTION_DATE_0400",
        "column": "SELECTION_DATE_0400",
        "datatype": "DATE",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
      },
      {
        "name": "TERMINATION_DATE_0400",
        "column": "TERMINATION_DATE_0400",
        "datatype": "DATE",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
      },
      {
        "name": "TYPE_0400",
        "column": "TYPE_0400",

```

```

        "datatype": "CHAR(1)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "INS_PLAN_CODE_0400",
        "column": "INS_PLAN_CODE_0400",
        "datatype": "VARCHAR(3)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "EMP_ID_0415",
        "column": "EMP_ID_0415",
        "datatype": "SMALLINT",
        "length": 4,
        "scale": 0,
        "nullable": true,
        "primary_key": false
    }
]
},
{
    "name": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "primary_key": null,
    "fields": [
        {
            "name": "CLAIM_DATE_0405",
            "column": "CLAIM_DATE_0405",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "PATIENT_BIRTH_DATE_0405",
            "column": "PATIENT_BIRTH_DATE_0405",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "SERVICE_DATE_0405",
            "column": "SERVICE_DATE_0405",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "PATIENT_FIRST_NAME_0405",
            "column": "PATIENT_FIRST_NAME_0405",
            "datatype": "VARCHAR(10)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "PATIENT_LAST_NAME_0405",
            "column": "PATIENT_LAST_NAME_0405",
            "datatype": "VARCHAR(15)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        }
    ],

```

```

{
  "name": "PATIENT_SEX_0405",
  "column": "PATIENT_SEX_0405",
  "datatype": "CHAR(1)",
  "length": null,
  "scale": null,
  "nullable": true,
  "primary_key": false
},
{
  "name": "RELATION_TO_EMPLOYEE_0405",
  "column": "RELATION_TO_EMPLOYEE_0405",
  "datatype": "VARCHAR(10)",
  "length": null,
  "scale": null,
  "nullable": true,
  "primary_key": false
},
{
  "name": "DENTIST_FIRST_NAME_0405",
  "column": "DENTIST_FIRST_NAME_0405",
  "datatype": "VARCHAR(10)",
  "length": null,
  "scale": null,
  "nullable": true,
  "primary_key": false
},
{
  "name": "DENTIST_LAST_NAME_0405",
  "column": "DENTIST_LAST_NAME_0405",
  "datatype": "VARCHAR(15)",
  "length": null,
  "scale": null,
  "nullable": true,
  "primary_key": false
},
{
  "name": "DENTIST_STREET_0405",
  "column": "DENTIST_STREET_0405",
  "datatype": "VARCHAR(20)",
  "length": null,
  "scale": null,
  "nullable": true,
  "primary_key": false
},
{
  "name": "DENTIST_CITY_0405",
  "column": "DENTIST_CITY_0405",
  "datatype": "VARCHAR(15)",
  "length": null,
  "scale": null,
  "nullable": true,
  "primary_key": false
},
{
  "name": "DENTIST_STATE_0405",
  "column": "DENTIST_STATE_0405",
  "datatype": "VARCHAR(2)",
  "length": null,
  "scale": null,
  "nullable": true,
  "primary_key": false
},
{
  "name": "DENTIST_ZIP_FIRST_FIVE_0405",
  "column": "DENTIST_ZIP_FIRST_FIVE_0405",
  "datatype": "VARCHAR(5)",
  "length": null,
  "scale": null,
  "nullable": true,
  "primary_key": false
},
{
  "name": "DENTIST_ZIP_LAST_FOUR_0405",
  "column": "DENTIST_ZIP_LAST_FOUR_0405",
  "datatype": "VARCHAR(4)",

```

```

        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "DENTIST_LICENSE_NUMBER_0405",
        "column": "DENTIST_LICENSE_NUMBER_0405",
        "datatype": "SMALLINT",
        "length": 4,
        "scale": 0,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "NUMBER_OF_PROCEDURES_0405",
        "column": "NUMBER_OF_PROCEDURES_0405",
        "datatype": "DECIMAL(1,0)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "TOOTH_NUMBER_0405",
        "column": "TOOTH_NUMBER_0405",
        "datatype": "SMALLINT",
        "length": 4,
        "scale": 0,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "PROCEDURE_CODE_0405",
        "column": "PROCEDURE_CODE_0405",
        "datatype": "SMALLINT",
        "length": 4,
        "scale": 0,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "DESCRIPTION_OF_SERVICE_0405",
        "column": "DESCRIPTION_OF_SERVICE_0405",
        "datatype": "VARCHAR(60)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "FEE_0405",
        "column": "FEE_0405",
        "datatype": "DECIMAL(2,2)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "COVERAGE_ID",
        "column": "COVERAGE_ID",
        "datatype": "BIGINT",
        "length": 18,
        "scale": 0,
        "nullable": true,
        "primary_key": false
    }
]
},
{
    "name": "DEPARTMENT",
    "table": "DEPARTMENT",
    "primary_key": "DEPT_ID_0410",
    "fields": [
        {

```



```

        "name": "DEPT_ID_0410",
        "column": "DEPT_ID_0410",
        "datatype": "SMALLINT",
        "length": 4,
        "scale": 0,
        "nullable": false,
        "primary_key": true
    },
    {
        "name": "DEPT_NAME_0410",
        "column": "DEPT_NAME_0410",
        "datatype": "VARCHAR(45)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "DEPT_HEAD_ID_0410",
        "column": "DEPT_HEAD_ID_0410",
        "datatype": "SMALLINT",
        "length": 4,
        "scale": 0,
        "nullable": true,
        "primary_key": false
    }
]
},
{
    "name": "EMPLOYEE",
    "table": "EMPLOYEE",
    "primary_key": "EMP_ID_0415",
    "fields": [
        {
            "name": "START_DATE_0415",
            "column": "START_DATE_0415",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "TERMINATION_DATE_0415",
            "column": "TERMINATION_DATE_0415",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "BIRTH_DATE_0415",
            "column": "BIRTH_DATE_0415",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "EMP_ID_0415",
            "column": "EMP_ID_0415",
            "datatype": "SMALLINT",
            "length": 4,
            "scale": 0,
            "nullable": false,
            "primary_key": true
        },
        {
            "name": "EMP_FIRST_NAME_0415",
            "column": "EMP_FIRST_NAME_0415",
            "datatype": "VARCHAR(10)",
            "length": null,
            "scale": null,
            "nullable": true,

```

```

    "primary_key": false
  },
  {
    "name": "EMP_LAST_NAME_0415",
    "column": "EMP_LAST_NAME_0415",
    "datatype": "VARCHAR(15)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "EMP_STREET_0415",
    "column": "EMP_STREET_0415",
    "datatype": "VARCHAR(20)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "EMP_CITY_0415",
    "column": "EMP_CITY_0415",
    "datatype": "VARCHAR(15)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "EMP_STATE_0415",
    "column": "EMP_STATE_0415",
    "datatype": "VARCHAR(2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "EMP_ZIP_FIRST_FIVE_0415",
    "column": "EMP_ZIP_FIRST_FIVE_0415",
    "datatype": "VARCHAR(5)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "EMP_ZIP_LAST_FOUR_0415",
    "column": "EMP_ZIP_LAST_FOUR_0415",
    "datatype": "VARCHAR(4)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "EMP_PHONE_0415",
    "column": "EMP_PHONE_0415",
    "datatype": "SMALLINT",
    "length": 4,
    "scale": 0,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "STATUS_0415",
    "column": "STATUS_0415",
    "datatype": "VARCHAR(2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "SS_NUMBER_0415",

```

```

        "column": "SS_NUMBER_0415",
        "datatype": "SMALLINT",
        "length": 4,
        "scale": 0,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "DEPT_ID_0410",
        "column": "DEPT_ID_0410",
        "datatype": "SMALLINT",
        "length": 4,
        "scale": 0,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "OFFICE_CODE_0450",
        "column": "OFFICE_CODE_0450",
        "datatype": "VARCHAR(3)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    }
]
},
{
    "name": "EMPOSITION",
    "table": "EMPOSITION",
    "primary_key": null,
    "fields": [
        {
            "name": "START_DATE_0420",
            "column": "START_DATE_0420",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "FINISH_DATE_0420",
            "column": "FINISH_DATE_0420",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "SALARY_GRADE_0420",
            "column": "SALARY_GRADE_0420",
            "datatype": "SMALLINT",
            "length": 4,
            "scale": 0,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "SALARY_AMOUNT_0420",
            "column": "SALARY_AMOUNT_0420",
            "datatype": "DECIMAL(2,2)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "BONUS_PERCENT_0420",
            "column": "BONUS_PERCENT_0420",
            "datatype": "DECIMAL(3,3)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        }
    ]
}

```

```

    },
    {
      "name": "COMMISSION_PERCENT_0420",
      "column": "COMMISSION_PERCENT_0420",
      "datatype": "DECIMAL(3,3)",
      "length": null,
      "scale": null,
      "nullable": true,
      "primary_key": false
    },
    {
      "name": "OVERTIME_RATE_0420",
      "column": "OVERTIME_RATE_0420",
      "datatype": "DECIMAL(3,2)",
      "length": null,
      "scale": null,
      "nullable": true,
      "primary_key": false
    },
    {
      "name": "EMP_ID_0415",
      "column": "EMP_ID_0415",
      "datatype": "SMALLINT",
      "length": 4,
      "scale": 0,
      "nullable": true,
      "primary_key": false
    },
    {
      "name": "JOB_ID_0440",
      "column": "JOB_ID_0440",
      "datatype": "SMALLINT",
      "length": 4,
      "scale": 0,
      "nullable": true,
      "primary_key": false
    }
  ]
},
{
  "name": "EXPERTISE",
  "table": "EXPERTISE",
  "primary_key": null,
  "fields": [
    {
      "name": "EXPERTISE_DATE_0425",
      "column": "EXPERTISE_DATE_0425",
      "datatype": "DATE",
      "length": null,
      "scale": null,
      "nullable": true,
      "primary_key": false
    },
    {
      "name": "SKILL_LEVEL_0425",
      "column": "SKILL_LEVEL_0425",
      "datatype": "VARCHAR(2)",
      "length": null,
      "scale": null,
      "nullable": true,
      "primary_key": false
    },
    {
      "name": "EMP_ID_0415",
      "column": "EMP_ID_0415",
      "datatype": "SMALLINT",
      "length": 4,
      "scale": 0,
      "nullable": true,
      "primary_key": false
    },
    {
      "name": "SKILL_ID_0455",
      "column": "SKILL_ID_0455",
      "datatype": "SMALLINT",
      "length": 4,

```

```

        "scale": 0,
        "nullable": true,
        "primary_key": false
    }
]
},
{
    "name": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "primary_key": null,
    "fields": [
        {
            "name": "CLAIM_DATE_0430",
            "column": "CLAIM_DATE_0430",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "PATIENT_BIRTH_DATE_0430",
            "column": "PATIENT_BIRTH_DATE_0430",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "ADMIT_DATE_0430",
            "column": "ADMIT_DATE_0430",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "DISCHARGE_DATE_0430",
            "column": "DISCHARGE_DATE_0430",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "PATIENT_FIRST_NAME_0430",
            "column": "PATIENT_FIRST_NAME_0430",
            "datatype": "VARCHAR(10)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "PATIENT_LAST_NAME_0430",
            "column": "PATIENT_LAST_NAME_0430",
            "datatype": "VARCHAR(15)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "PATIENT_SEX_0430",
            "column": "PATIENT_SEX_0430",
            "datatype": "CHAR(1)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "RELATION_TO_EMPLOYEE_0430",

```

```

    "column": "RELATION_TO_EMPLOYEE_0430",
    "datatype": "VARCHAR(10)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "HOSPITAL_NAME_0430",
    "column": "HOSPITAL_NAME_0430",
    "datatype": "VARCHAR(25)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "HOSP_STREET_0430",
    "column": "HOSP_STREET_0430",
    "datatype": "VARCHAR(20)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "HOSP_CITY_0430",
    "column": "HOSP_CITY_0430",
    "datatype": "VARCHAR(15)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "HOSP_STATE_0430",
    "column": "HOSP_STATE_0430",
    "datatype": "VARCHAR(2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "HOSP_ZIP_FIRST_FIVE_0430",
    "column": "HOSP_ZIP_FIRST_FIVE_0430",
    "datatype": "VARCHAR(5)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "HOSP_ZIP_LAST_FOUR_0430",
    "column": "HOSP_ZIP_LAST_FOUR_0430",
    "datatype": "VARCHAR(4)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "DIAGNOSIS_0430",
    "column": "DIAGNOSIS_0430",
    "datatype": "VARCHAR(120)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "WARD_DAYS_0430",
    "column": "WARD_DAYS_0430",
    "datatype": "DECIMAL(5,0)",
    "length": null,
    "scale": null,

```

```

    "nullable": true,
    "primary_key": false
  },
  {
    "name": "WARD_RATE_0430",
    "column": "WARD_RATE_0430",
    "datatype": "DECIMAL(2,2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "WARD_TOTAL_0430",
    "column": "WARD_TOTAL_0430",
    "datatype": "DECIMAL(2,2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "SEMI_DAYS_0430",
    "column": "SEMI_DAYS_0430",
    "datatype": "DECIMAL(5,0)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "SEMI_RATE_0430",
    "column": "SEMI_RATE_0430",
    "datatype": "DECIMAL(2,2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "SEMI_TOTAL_0430",
    "column": "SEMI_TOTAL_0430",
    "datatype": "DECIMAL(2,2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "DELIVERY_COST_0430",
    "column": "DELIVERY_COST_0430",
    "datatype": "DECIMAL(2,2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "ANESTHESIA_COST_0430",
    "column": "ANESTHESIA_COST_0430",
    "datatype": "DECIMAL(2,2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "LAB_COST_0430",
    "column": "LAB_COST_0430",
    "datatype": "DECIMAL(2,2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {

```

```

        "name": "COVERAGE_ID",
        "column": "COVERAGE_ID",
        "datatype": "BIGINT",
        "length": 18,
        "scale": 0,
        "nullable": true,
        "primary_key": false
    }
]
},
{
    "name": "INSURANCE_PLAN",
    "table": "INSURANCE_PLAN",
    "primary_key": "INS_PLAN_CODE_0435",
    "fields": [
        {
            "name": "INS_PLAN_CODE_0435",
            "column": "INS_PLAN_CODE_0435",
            "datatype": "VARCHAR(3)",
            "length": null,
            "scale": null,
            "nullable": false,
            "primary_key": true
        },
        {
            "name": "INS_CO_NAME_0435",
            "column": "INS_CO_NAME_0435",
            "datatype": "VARCHAR(45)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "INS_CO_STREET_0435",
            "column": "INS_CO_STREET_0435",
            "datatype": "VARCHAR(20)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "INS_CO_CITY_0435",
            "column": "INS_CO_CITY_0435",
            "datatype": "VARCHAR(15)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "INS_CO_STATE_0435",
            "column": "INS_CO_STATE_0435",
            "datatype": "VARCHAR(2)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "INS_CO_ZIP_FIRST_FIVE_0435",
            "column": "INS_CO_ZIP_FIRST_FIVE_0435",
            "datatype": "VARCHAR(5)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "INS_CO_ZIP_LAST_FOUR_0435",
            "column": "INS_CO_ZIP_LAST_FOUR_0435",
            "datatype": "VARCHAR(4)",
            "length": null,
            "scale": null,
            "nullable": true,

```



```

    "primary_key": false
  },
  {
    "name": "INS_CO_PHONE_0435",
    "column": "INS_CO_PHONE_0435",
    "datatype": "SMALLINT",
    "length": 4,
    "scale": 0,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "GROUP_NUMBER_0435",
    "column": "GROUP_NUMBER_0435",
    "datatype": "SMALLINT",
    "length": 4,
    "scale": 0,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "DEDUCT_0435",
    "column": "DEDUCT_0435",
    "datatype": "DECIMAL(2,2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "MAXIMUM_LIFE_COST_0435",
    "column": "MAXIMUM_LIFE_COST_0435",
    "datatype": "DECIMAL(2,2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "FAMILY_COST_0435",
    "column": "FAMILY_COST_0435",
    "datatype": "DECIMAL(2,2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "DEP_COST_0435",
    "column": "DEP_COST_0435",
    "datatype": "DECIMAL(2,2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  }
]
},
{
  "name": "JOB",
  "table": "JOB",
  "primary_key": "JOB_ID_0440",
  "fields": [
    {
      "name": "JOB_ID_0440",
      "column": "JOB_ID_0440",
      "datatype": "SMALLINT",
      "length": 4,
      "scale": 0,
      "nullable": false,
      "primary_key": true
    },
    {
      "name": "TITLE_0440",
      "column": "TITLE_0440",
      "datatype": "VARCHAR(20)",

```

```

        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "DESCRIPTION_LINE_0440",
        "column": "DESCRIPTION_LINE_0440",
        "datatype": "VARCHAR(120)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "REQUIREMENT_LINE_0440",
        "column": "REQUIREMENT_LINE_0440",
        "datatype": "VARCHAR(120)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "MINIMUM_SALARY_0440",
        "column": "MINIMUM_SALARY_0440",
        "datatype": "DECIMAL(2,2)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "MAXIMUM_SALARY_0440",
        "column": "MAXIMUM_SALARY_0440",
        "datatype": "DECIMAL(2,2)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "SALARY_GRADES_0440",
        "column": "SALARY_GRADES_0440",
        "datatype": "SMALLINT",
        "length": 4,
        "scale": 0,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "NUMBER_OF_POSITIONS_0440",
        "column": "NUMBER_OF_POSITIONS_0440",
        "datatype": "SMALLINT",
        "length": 4,
        "scale": 0,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "NUMBER_OPEN_0440",
        "column": "NUMBER_OPEN_0440",
        "datatype": "SMALLINT",
        "length": 4,
        "scale": 0,
        "nullable": true,
        "primary_key": false
    }
]
},
{
    "name": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "primary_key": null,
    "fields": [
        {

```

```

    "name": "CLAIM_DATE_0445",
    "column": "CLAIM_DATE_0445",
    "datatype": "DATE",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "PATIENT_BIRTH_DATE_0445",
    "column": "PATIENT_BIRTH_DATE_0445",
    "datatype": "DATE",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "SERVICE_DATE_0445",
    "column": "SERVICE_DATE_0445",
    "datatype": "DATE",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "PATIENT_FIRST_NAME_0445",
    "column": "PATIENT_FIRST_NAME_0445",
    "datatype": "VARCHAR(10)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "PATIENT_LAST_NAME_0445",
    "column": "PATIENT_LAST_NAME_0445",
    "datatype": "VARCHAR(15)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "PATIENT_SEX_0445",
    "column": "PATIENT_SEX_0445",
    "datatype": "CHAR(1)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "RELATION_TO_EMPLOYEE_0445",
    "column": "RELATION_TO_EMPLOYEE_0445",
    "datatype": "VARCHAR(10)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "PHYSICIAN_FIRST_NAME_0445",
    "column": "PHYSICIAN_FIRST_NAME_0445",
    "datatype": "VARCHAR(10)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "PHYSICIAN_LAST_NAME_0445",
    "column": "PHYSICIAN_LAST_NAME_0445",
    "datatype": "VARCHAR(15)",
    "length": null,

```

```

    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "PHYSICIAN_STREET_0445",
    "column": "PHYSICIAN_STREET_0445",
    "datatype": "VARCHAR(20)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "PHYSICIAN_CITY_0445",
    "column": "PHYSICIAN_CITY_0445",
    "datatype": "VARCHAR(15)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "PHYSICIAN_STATE_0445",
    "column": "PHYSICIAN_STATE_0445",
    "datatype": "VARCHAR(2)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "PHYSICIAN_ZIP_FIRST_FIVE_0445",
    "column": "PHYSICIAN_ZIP_FIRST_FIVE_0445",
    "datatype": "VARCHAR(5)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "PHYSICIAN_ZIP_LAST_FOUR_0445",
    "column": "PHYSICIAN_ZIP_LAST_FOUR_0445",
    "datatype": "VARCHAR(4)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "PHYSICIAN_ID_0445",
    "column": "PHYSICIAN_ID_0445",
    "datatype": "SMALLINT",
    "length": 4,
    "scale": 0,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "DIAGNOSIS_0445",
    "column": "DIAGNOSIS_0445",
    "datatype": "VARCHAR(120)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
  {
    "name": "NUMBER_OF_PROCEDURES_0445",
    "column": "NUMBER_OF_PROCEDURES_0445",
    "datatype": "DECIMAL(1,0)",
    "length": null,
    "scale": null,
    "nullable": true,
    "primary_key": false
  },
},

```

```

{
  "name": "PROCEDURE_CODE_0445",
  "column": "PROCEDURE_CODE_0445",
  "datatype": "SMALLINT",
  "length": 4,
  "scale": 0,
  "nullable": true,
  "primary_key": false
},
{
  "name": "DESCRIPTION_OF_SERVICE_0445",
  "column": "DESCRIPTION_OF_SERVICE_0445",
  "datatype": "VARCHAR(60)",
  "length": null,
  "scale": null,
  "nullable": true,
  "primary_key": false
},
{
  "name": "FEE_0445",
  "column": "FEE_0445",
  "datatype": "DECIMAL(2,2)",
  "length": null,
  "scale": null,
  "nullable": true,
  "primary_key": false
},
{
  "name": "COVERAGE_ID",
  "column": "COVERAGE_ID",
  "datatype": "BIGINT",
  "length": 18,
  "scale": 0,
  "nullable": true,
  "primary_key": false
}
]
},
{
  "name": "OFFICE",
  "table": "OFFICE",
  "primary_key": "OFFICE_CODE_0450",
  "fields": [
    {
      "name": "OFFICE_CODE_0450",
      "column": "OFFICE_CODE_0450",
      "datatype": "VARCHAR(3)",
      "length": null,
      "scale": null,
      "nullable": false,
      "primary_key": true
    },
    {
      "name": "OFFICE_STREET_0450",
      "column": "OFFICE_STREET_0450",
      "datatype": "VARCHAR(20)",
      "length": null,
      "scale": null,
      "nullable": true,
      "primary_key": false
    },
    {
      "name": "OFFICE_CITY_0450",
      "column": "OFFICE_CITY_0450",
      "datatype": "VARCHAR(15)",
      "length": null,
      "scale": null,
      "nullable": true,
      "primary_key": false
    },
    {
      "name": "OFFICE_STATE_0450",
      "column": "OFFICE_STATE_0450",
      "datatype": "VARCHAR(2)",
      "length": null,
      "scale": null,

```

```

        "nullable": true,
        "primary_key": false
    },
    {
        "name": "OFFICE_ZIP_FIRST_FIVE_0450",
        "column": "OFFICE_ZIP_FIRST_FIVE_0450",
        "datatype": "VARCHAR(5)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "OFFICE_ZIP_LAST_FOUR_0450",
        "column": "OFFICE_ZIP_LAST_FOUR_0450",
        "datatype": "VARCHAR(4)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "OFFICE_PHONE_0450",
        "column": "OFFICE_PHONE_0450",
        "datatype": "SMALLINT",
        "length": 4,
        "scale": 0,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "OFFICE_AREA_CODE_0450",
        "column": "OFFICE_AREA_CODE_0450",
        "datatype": "VARCHAR(3)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    },
    {
        "name": "SPEED_DIAL_0450",
        "column": "SPEED_DIAL_0450",
        "datatype": "VARCHAR(3)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    }
]
},
{
    "name": "SKILL",
    "table": "SKILL",
    "primary_key": "SKILL_ID_0455",
    "fields": [
        {
            "name": "SKILL_ID_0455",
            "column": "SKILL_ID_0455",
            "datatype": "SMALLINT",
            "length": 4,
            "scale": 0,
            "nullable": false,
            "primary_key": true
        },
        {
            "name": "SKILL_NAME_0455",
            "column": "SKILL_NAME_0455",
            "datatype": "VARCHAR(12)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "SKILL_DESCRIPTION_0455",
            "column": "SKILL_DESCRIPTION_0455",

```

```

        "datatype": "VARCHAR(60)",
        "length": null,
        "scale": null,
        "nullable": true,
        "primary_key": false
    }
]
},
{
    "name": "STRUCTURE",
    "table": "STRUCTURE",
    "primary_key": null,
    "fields": [
        {
            "name": "STRUCTURE_DATE_0460",
            "column": "STRUCTURE_DATE_0460",
            "datatype": "DATE",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "STRUCTURE_CODE_0460",
            "column": "STRUCTURE_CODE_0460",
            "datatype": "VARCHAR(2)",
            "length": null,
            "scale": null,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "MANAGES_EMP_ID_0415",
            "column": "MANAGES_EMP_ID_0415",
            "datatype": "SMALLINT",
            "length": 4,
            "scale": 0,
            "nullable": true,
            "primary_key": false
        },
        {
            "name": "REPORTS_TO_EMP_ID_0415",
            "column": "REPORTS_TO_EMP_ID_0415",
            "datatype": "SMALLINT",
            "length": 4,
            "scale": 0,
            "nullable": true,
            "primary_key": false
        }
    ]
}
],
"relationships": [
    {
        "set_name": "DEPT_EMPLOYEE",
        "parent_record": "DEPARTMENT",
        "child_record": "EMPLOYEE",
        "parent_key": "DEPT_ID_0410",
        "child_fk": "DEPT_ID_0410",
        "cardinality": "1:N",
        "order_by": [
            "DEPT_ID_0410"
        ]
    },
    {
        "set_name": "MANAGES",
        "parent_record": "EMPLOYEE",
        "child_record": "STRUCTURE",
        "parent_key": "EMP_ID_0415",
        "child_fk": null,
        "cardinality": "1:N",
        "order_by": []
    },
    {
        "set_name": "OFFICE_EMPLOYEE",
        "parent_record": "OFFICE",

```

```

    "child_record": "EMPLOYEE",
    "parent_key": "OFFICE_CODE_0450",
    "child_fk": "OFFICE_CODE_0450",
    "cardinality": "1:N",
    "order_by": [
        "OFFICE_CODE_0450"
    ]
},
{
    "set_name": "EMP_EXPERTISE",
    "parent_record": "EMPLOYEE",
    "child_record": "EXPERTISE",
    "parent_key": "EMP_ID_0415",
    "child_fk": "EMP_ID_0415",
    "cardinality": "1:N",
    "order_by": [
        "EMP_ID_0415"
    ]
},
{
    "set_name": "SKILL_EXPERTISE",
    "parent_record": "SKILL",
    "child_record": "EXPERTISE",
    "parent_key": "SKILL_ID_0455",
    "child_fk": "SKILL_ID_0455",
    "cardinality": "1:N",
    "order_by": [
        "SKILL_ID_0455"
    ]
},
{
    "set_name": "EMP_EMPOSITION",
    "parent_record": "EMPLOYEE",
    "child_record": "EMPOSITION",
    "parent_key": "EMP_ID_0415",
    "child_fk": "EMP_ID_0415",
    "cardinality": "1:N",
    "order_by": [
        "EMP_ID_0415"
    ]
},
{
    "set_name": "REPORTS_TO",
    "parent_record": "EMPLOYEE",
    "child_record": "STRUCTURE",
    "parent_key": "EMP_ID_0415",
    "child_fk": null,
    "cardinality": "1:N",
    "order_by": []
},
{
    "set_name": "EMP_COVERAGE",
    "parent_record": "EMPLOYEE",
    "child_record": "COVERAGE",
    "parent_key": "EMP_ID_0415",
    "child_fk": "EMP_ID_0415",
    "cardinality": "1:N",
    "order_by": [
        "EMP_ID_0415"
    ]
},
{
    "set_name": "JOB_EMPOSITION",
    "parent_record": "JOB",
    "child_record": "EMPOSITION",
    "parent_key": "JOB_ID_0440",
    "child_fk": "JOB_ID_0440",
    "cardinality": "1:N",
    "order_by": [
        "JOB_ID_0440"
    ]
},
{
    "set_name": "COVERAGE_CLAIMS",
    "parent_record": "COVERAGE",
    "child_record": "DENTAL_CLAIM",

```



```

    "parent_key": "COVERAGE_ID",
    "child_fk": "COVERAGE_ID",
    "cardinality": "1:N",
    "order_by": [
        "COVERAGE_ID"
    ]
},
{
    "set_name": "COVERAGE_CLAIMS",
    "parent_record": "COVERAGE",
    "child_record": "HOSPITAL_CLAIM",
    "parent_key": "COVERAGE_ID",
    "child_fk": "COVERAGE_ID",
    "cardinality": "1:N",
    "order_by": [
        "COVERAGE_ID"
    ]
},
{
    "set_name": "COVERAGE_CLAIMS",
    "parent_record": "COVERAGE",
    "child_record": "NON_HOSP_CLAIM",
    "parent_key": "COVERAGE_ID",
    "child_fk": "COVERAGE_ID",
    "cardinality": "1:N",
    "order_by": [
        "COVERAGE_ID"
    ]
}
],
"field_map": {
    "TYPE_0400": {
        "host": "HV-COVERAGE-TYPE",
        "record": "COVERAGE",
        "table": "COVERAGE",
        "column": "TYPE_0400",
        "legacy_field": "TYPE_0400"
    },
    "TYPE": {
        "host": "HV-COVERAGE-TYPE",
        "record": "COVERAGE",
        "table": "COVERAGE",
        "column": "TYPE_0400",
        "legacy_field": "TYPE_0400"
    },
    "INS_PLAN_CODE_0400": {
        "host": "HV-COVERAGE-INS-PLAN-CODE",
        "record": "COVERAGE",
        "table": "COVERAGE",
        "column": "INS_PLAN_CODE_0400",
        "legacy_field": "INS_PLAN_CODE_0400"
    },
    "INS_PLAN_CODE": {
        "host": "HV-INSURANCE-PLAN-INS-PLAN-CODE",
        "record": "INSURANCE_PLAN",
        "table": "INSURANCE_PLAN",
        "column": "INS_PLAN_CODE_0435",
        "legacy_field": "INS_PLAN_CODE_0435"
    },
    "PATIENT_FIRST_NAME_0405": {
        "host": "HV-DENTAL-CLAIM-PATIENT-FIRST-NAME",
        "record": "DENTAL_CLAIM",
        "table": "DENTAL_CLAIM",
        "column": "PATIENT_FIRST_NAME_0405",
        "legacy_field": "PATIENT_FIRST_NAME_0405"
    },
    "PATIENT_FIRST_NAME": {
        "host": "HV-NON-HOSP-CLAIM-PATIENT-FIRST-NAME",
        "record": "NON_HOSP_CLAIM",
        "table": "NON_HOSP_CLAIM",
        "column": "PATIENT_FIRST_NAME_0445",
        "legacy_field": "PATIENT_FIRST_NAME_0445"
    },
    "PATIENT_LAST_NAME_0405": {
        "host": "HV-DENTAL-CLAIM-PATIENT-LAST-NAME",
        "record": "DENTAL_CLAIM",

```

```

    "table": "DENTAL_CLAIM",
    "column": "PATIENT_LAST_NAME_0405",
    "legacy_field": "PATIENT_LAST_NAME_0405"
  },
  "PATIENT_LAST_NAME": {
    "host": "HV-NON-HOSP-CLAIM-PATIENT-LAST-NAME",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PATIENT_LAST_NAME_0445",
    "legacy_field": "PATIENT_LAST_NAME_0445"
  },
  "PATIENT_SEX_0405": {
    "host": "HV-DENTAL-CLAIM-PATIENT-SEX",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "PATIENT_SEX_0405",
    "legacy_field": "PATIENT_SEX_0405"
  },
  "PATIENT_SEX": {
    "host": "HV-NON-HOSP-CLAIM-PATIENT-SEX",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PATIENT_SEX_0445",
    "legacy_field": "PATIENT_SEX_0445"
  },
  "RELATION_TO_EMPLOYEE_0405": {
    "host": "HV-DENTAL-CLAIM-RELATION-TO-EMPLOYEE",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "RELATION_TO_EMPLOYEE_0405",
    "legacy_field": "RELATION_TO_EMPLOYEE_0405"
  },
  "RELATION_TO_EMPLOYEE": {
    "host": "HV-NON-HOSP-CLAIM-RELATION-TO-EMPLOYEE",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "RELATION_TO_EMPLOYEE_0445",
    "legacy_field": "RELATION_TO_EMPLOYEE_0445"
  },
  "DENTIST_FIRST_NAME_0405": {
    "host": "HV-DENTAL-CLAIM-DENTIST-FIRST-NAME",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_FIRST_NAME_0405",
    "legacy_field": "DENTIST_FIRST_NAME_0405"
  },
  "DENTIST_FIRST_NAME": {
    "host": "HV-DENTAL-CLAIM-DENTIST-FIRST-NAME",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_FIRST_NAME_0405",
    "legacy_field": "DENTIST_FIRST_NAME_0405"
  },
  "DENTIST_LAST_NAME_0405": {
    "host": "HV-DENTAL-CLAIM-DENTIST-LAST-NAME",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_LAST_NAME_0405",
    "legacy_field": "DENTIST_LAST_NAME_0405"
  },
  "DENTIST_LAST_NAME": {
    "host": "HV-DENTAL-CLAIM-DENTIST-LAST-NAME",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_LAST_NAME_0405",
    "legacy_field": "DENTIST_LAST_NAME_0405"
  },
  "DENTIST_STREET_0405": {
    "host": "HV-DENTAL-CLAIM-DENTIST-STREET",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_STREET_0405",
    "legacy_field": "DENTIST_STREET_0405"
  },
  "DENTIST_STREET": {
    "host": "HV-DENTAL-CLAIM-DENTIST-STREET",

```

```

    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_STREET_0405",
    "legacy_field": "DENTIST_STREET_0405"
  },
  "DENTIST_CITY_0405": {
    "host": "HV-DENTAL-CLAIM-DENTIST-CITY",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_CITY_0405",
    "legacy_field": "DENTIST_CITY_0405"
  },
  "DENTIST_CITY": {
    "host": "HV-DENTAL-CLAIM-DENTIST-CITY",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_CITY_0405",
    "legacy_field": "DENTIST_CITY_0405"
  },
  "DENTIST_STATE_0405": {
    "host": "HV-DENTAL-CLAIM-DENTIST-STATE",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_STATE_0405",
    "legacy_field": "DENTIST_STATE_0405"
  },
  "DENTIST_STATE": {
    "host": "HV-DENTAL-CLAIM-DENTIST-STATE",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_STATE_0405",
    "legacy_field": "DENTIST_STATE_0405"
  },
  "DENTIST_ZIP_FIRST_FIVE_0405": {
    "host": "HV-DENTAL-CLAIM-DENTIST-ZIP-FIRST-FIVE",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_ZIP_FIRST_FIVE_0405",
    "legacy_field": "DENTIST_ZIP_FIRST_FIVE_0405"
  },
  "DENTIST_ZIP_FIRST_FIVE": {
    "host": "HV-DENTAL-CLAIM-DENTIST-ZIP-FIRST-FIVE",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_ZIP_FIRST_FIVE_0405",
    "legacy_field": "DENTIST_ZIP_FIRST_FIVE_0405"
  },
  "DENTIST_ZIP_LAST_FOUR_0405": {
    "host": "HV-DENTAL-CLAIM-DENTIST-ZIP-LAST-FOUR",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_ZIP_LAST_FOUR_0405",
    "legacy_field": "DENTIST_ZIP_LAST_FOUR_0405"
  },
  "DENTIST_ZIP_LAST_FOUR": {
    "host": "HV-DENTAL-CLAIM-DENTIST-ZIP-LAST-FOUR",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_ZIP_LAST_FOUR_0405",
    "legacy_field": "DENTIST_ZIP_LAST_FOUR_0405"
  },
  "DENTIST_LICENSE_NUMBER_0405": {
    "host": "HV-DENTAL-CLAIM-DENTIST-LICENSE-NUMBER",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_LICENSE_NUMBER_0405",
    "legacy_field": "DENTIST_LICENSE_NUMBER_0405"
  },
  "DENTIST_LICENSE_NUMBER": {
    "host": "HV-DENTAL-CLAIM-DENTIST-LICENSE-NUMBER",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DENTIST_LICENSE_NUMBER_0405",
    "legacy_field": "DENTIST_LICENSE_NUMBER_0405"
  },
  "NUMBER_OF_PROCEDURES_0405": {

```

```

    "host": "HV-DENTAL-CLAIM-NUMBER-OF-PROCEDURES",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "NUMBER_OF_PROCEEDURES_0405",
    "legacy_field": "NUMBER_OF_PROCEEDURES_0405"
  },
  "NUMBER_OF_PROCEEDURES": {
    "host": "HV-NON-HOSP-CLAIM-NUMBER-OF-PROCEDURES",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "NUMBER_OF_PROCEEDURES_0445",
    "legacy_field": "NUMBER_OF_PROCEEDURES_0445"
  },
  "TOOTH_NUMBER_0405": {
    "host": "HV-DENTAL-CLAIM-TOOTH-NUMBER",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "TOOTH_NUMBER_0405",
    "legacy_field": "TOOTH_NUMBER_0405"
  },
  "TOOTH_NUMBER": {
    "host": "HV-DENTAL-CLAIM-TOOTH-NUMBER",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "TOOTH_NUMBER_0405",
    "legacy_field": "TOOTH_NUMBER_0405"
  },
  "PROCEDURE_CODE_0405": {
    "host": "HV-DENTAL-CLAIM-PROCEDURE-CODE",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "PROCEDURE_CODE_0405",
    "legacy_field": "PROCEDURE_CODE_0405"
  },
  "PROCEDURE_CODE": {
    "host": "HV-NON-HOSP-CLAIM-PROCEDURE-CODE",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PROCEDURE_CODE_0445",
    "legacy_field": "PROCEDURE_CODE_0445"
  },
  "DESCRIPTION_OF_SERVICE_0405": {
    "host": "HV-DENTAL-CLAIM-DESCRIPTION-OF-SERVICE",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "DESCRIPTION_OF_SERVICE_0405",
    "legacy_field": "DESCRIPTION_OF_SERVICE_0405"
  },
  "DESCRIPTION_OF_SERVICE": {
    "host": "HV-NON-HOSP-CLAIM-DESCRIPTION-OF-SERVICE",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "DESCRIPTION_OF_SERVICE_0445",
    "legacy_field": "DESCRIPTION_OF_SERVICE_0445"
  },
  "FEE_0405": {
    "host": "HV-DENTAL-CLAIM-FEE",
    "record": "DENTAL_CLAIM",
    "table": "DENTAL_CLAIM",
    "column": "FEE_0405",
    "legacy_field": "FEE_0405"
  },
  "FEE": {
    "host": "HV-NON-HOSP-CLAIM-FEE",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "FEE_0445",
    "legacy_field": "FEE_0445"
  },
  "DEPT_ID_0410": {
    "host": "HV-DEPARTMENT-DEPT-ID",
    "record": "DEPARTMENT",
    "table": "DEPARTMENT",
    "column": "DEPT_ID_0410",
    "legacy_field": "DEPT_ID_0410"
  },

```

```

"DEPT_ID": {
  "host": "HV-DEPARTMENT-DEPT-ID",
  "record": "DEPARTMENT",
  "table": "DEPARTMENT",
  "column": "DEPT_ID_0410",
  "legacy_field": "DEPT_ID_0410"
},
"DEPT_NAME_0410": {
  "host": "HV-DEPARTMENT-DEPT-NAME",
  "record": "DEPARTMENT",
  "table": "DEPARTMENT",
  "column": "DEPT_NAME_0410",
  "legacy_field": "DEPT_NAME_0410"
},
"DEPT_NAME": {
  "host": "HV-DEPARTMENT-DEPT-NAME",
  "record": "DEPARTMENT",
  "table": "DEPARTMENT",
  "column": "DEPT_NAME_0410",
  "legacy_field": "DEPT_NAME_0410"
},
"DEPT_HEAD_ID_0410": {
  "host": "HV-DEPARTMENT-DEPT-HEAD-ID",
  "record": "DEPARTMENT",
  "table": "DEPARTMENT",
  "column": "DEPT_HEAD_ID_0410",
  "legacy_field": "DEPT_HEAD_ID_0410"
},
"DEPT_HEAD_ID": {
  "host": "HV-DEPARTMENT-DEPT-HEAD-ID",
  "record": "DEPARTMENT",
  "table": "DEPARTMENT",
  "column": "DEPT_HEAD_ID_0410",
  "legacy_field": "DEPT_HEAD_ID_0410"
},
"EMP_ID_0415": {
  "host": "HV-EMPLOYEE-EMP-ID",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_ID_0415",
  "legacy_field": "EMP_ID_0415"
},
"EMP_ID": {
  "host": "HV-EMPLOYEE-EMP-ID",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_ID_0415",
  "legacy_field": "EMP_ID_0415"
},
"EMP_FIRST_NAME_0415": {
  "host": "HV-EMPLOYEE-EMP-FIRST-NAME",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_FIRST_NAME_0415",
  "legacy_field": "EMP_FIRST_NAME_0415"
},
"EMP_FIRST_NAME": {
  "host": "HV-EMPLOYEE-EMP-FIRST-NAME",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_FIRST_NAME_0415",
  "legacy_field": "EMP_FIRST_NAME_0415"
},
"EMP_LAST_NAME_0415": {
  "host": "HV-EMPLOYEE-EMP-LAST-NAME",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_LAST_NAME_0415",
  "legacy_field": "EMP_LAST_NAME_0415"
},
"EMP_LAST_NAME": {
  "host": "HV-EMPLOYEE-EMP-LAST-NAME",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_LAST_NAME_0415",
  "legacy_field": "EMP_LAST_NAME_0415"
}

```

```

},
"EMP_STREET_0415": {
  "host": "HV-EMPLOYEE-EMP-STREET",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_STREET_0415",
  "legacy_field": "EMP_STREET_0415"
},
"EMP_STREET": {
  "host": "HV-EMPLOYEE-EMP-STREET",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_STREET_0415",
  "legacy_field": "EMP_STREET_0415"
},
"EMP_CITY_0415": {
  "host": "HV-EMPLOYEE-EMP-CITY",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_CITY_0415",
  "legacy_field": "EMP_CITY_0415"
},
"EMP_CITY": {
  "host": "HV-EMPLOYEE-EMP-CITY",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_CITY_0415",
  "legacy_field": "EMP_CITY_0415"
},
"EMP_STATE_0415": {
  "host": "HV-EMPLOYEE-EMP-STATE",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_STATE_0415",
  "legacy_field": "EMP_STATE_0415"
},
"EMP_STATE": {
  "host": "HV-EMPLOYEE-EMP-STATE",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_STATE_0415",
  "legacy_field": "EMP_STATE_0415"
},
"EMP_ZIP_FIRST_FIVE_0415": {
  "host": "HV-EMPLOYEE-EMP-ZIP-FIRST-FIVE",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_ZIP_FIRST_FIVE_0415",
  "legacy_field": "EMP_ZIP_FIRST_FIVE_0415"
},
"EMP_ZIP_FIRST_FIVE": {
  "host": "HV-EMPLOYEE-EMP-ZIP-FIRST-FIVE",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_ZIP_FIRST_FIVE_0415",
  "legacy_field": "EMP_ZIP_FIRST_FIVE_0415"
},
"EMP_ZIP_LAST_FOUR_0415": {
  "host": "HV-EMPLOYEE-EMP-ZIP-LAST-FOUR",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_ZIP_LAST_FOUR_0415",
  "legacy_field": "EMP_ZIP_LAST_FOUR_0415"
},
"EMP_ZIP_LAST_FOUR": {
  "host": "HV-EMPLOYEE-EMP-ZIP-LAST-FOUR",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_ZIP_LAST_FOUR_0415",
  "legacy_field": "EMP_ZIP_LAST_FOUR_0415"
},
"EMP_PHONE_0415": {
  "host": "HV-EMPLOYEE-EMP-PHONE",
  "record": "EMPLOYEE",
  "table": "EMPLOYEE",
  "column": "EMP_PHONE_0415",

```

```

    "legacy_field": "EMP_PHONE_0415"
  },
  "EMP_PHONE": {
    "host": "HV-EMPLOYEE-EMP-PHONE",
    "record": "EMPLOYEE",
    "table": "EMPLOYEE",
    "column": "EMP_PHONE_0415",
    "legacy_field": "EMP_PHONE_0415"
  },
  "STATUS_0415": {
    "host": "HV-EMPLOYEE-STATUS",
    "record": "EMPLOYEE",
    "table": "EMPLOYEE",
    "column": "STATUS_0415",
    "legacy_field": "STATUS_0415"
  },
  "STATUS": {
    "host": "HV-EMPLOYEE-STATUS",
    "record": "EMPLOYEE",
    "table": "EMPLOYEE",
    "column": "STATUS_0415",
    "legacy_field": "STATUS_0415"
  },
  "SS_NUMBER_0415": {
    "host": "HV-EMPLOYEE-SS-NUMBER",
    "record": "EMPLOYEE",
    "table": "EMPLOYEE",
    "column": "SS_NUMBER_0415",
    "legacy_field": "SS_NUMBER_0415"
  },
  "SS_NUMBER": {
    "host": "HV-EMPLOYEE-SS-NUMBER",
    "record": "EMPLOYEE",
    "table": "EMPLOYEE",
    "column": "SS_NUMBER_0415",
    "legacy_field": "SS_NUMBER_0415"
  },
  "SALARY_GRADE_0420": {
    "host": "HV-EMPOSITION-SALARY-GRADE",
    "record": "EMPOSITION",
    "table": "EMPOSITION",
    "column": "SALARY_GRADE_0420",
    "legacy_field": "SALARY_GRADE_0420"
  },
  "SALARY_GRADE": {
    "host": "HV-EMPOSITION-SALARY-GRADE",
    "record": "EMPOSITION",
    "table": "EMPOSITION",
    "column": "SALARY_GRADE_0420",
    "legacy_field": "SALARY_GRADE_0420"
  },
  "SALARY_AMOUNT_0420": {
    "host": "HV-EMPOSITION-SALARY-AMOUNT",
    "record": "EMPOSITION",
    "table": "EMPOSITION",
    "column": "SALARY_AMOUNT_0420",
    "legacy_field": "SALARY_AMOUNT_0420"
  },
  "SALARY_AMOUNT": {
    "host": "HV-EMPOSITION-SALARY-AMOUNT",
    "record": "EMPOSITION",
    "table": "EMPOSITION",
    "column": "SALARY_AMOUNT_0420",
    "legacy_field": "SALARY_AMOUNT_0420"
  },
  "BONUS_PERCENT_0420": {
    "host": "HV-EMPOSITION-BONUS-PERCENT",
    "record": "EMPOSITION",
    "table": "EMPOSITION",
    "column": "BONUS_PERCENT_0420",
    "legacy_field": "BONUS_PERCENT_0420"
  },
  "BONUS_PERCENT": {
    "host": "HV-EMPOSITION-BONUS-PERCENT",
    "record": "EMPOSITION",
    "table": "EMPOSITION",

```

```

    "column": "BONUS_PERCENT_0420",
    "legacy_field": "BONUS_PERCENT_0420"
  },
  "COMMISSION_PERCENT_0420": {
    "host": "HV-EMPOSITION-COMMISSION-PERCENT",
    "record": "EMPOSITION",
    "table": "EMPOSITION",
    "column": "COMMISSION_PERCENT_0420",
    "legacy_field": "COMMISSION_PERCENT_0420"
  },
  "COMMISSION_PERCENT": {
    "host": "HV-EMPOSITION-COMMISSION-PERCENT",
    "record": "EMPOSITION",
    "table": "EMPOSITION",
    "column": "COMMISSION_PERCENT_0420",
    "legacy_field": "COMMISSION_PERCENT_0420"
  },
  "OVERTIME_RATE_0420": {
    "host": "HV-EMPOSITION-OVERTIME-RATE",
    "record": "EMPOSITION",
    "table": "EMPOSITION",
    "column": "OVERTIME_RATE_0420",
    "legacy_field": "OVERTIME_RATE_0420"
  },
  "OVERTIME_RATE": {
    "host": "HV-EMPOSITION-OVERTIME-RATE",
    "record": "EMPOSITION",
    "table": "EMPOSITION",
    "column": "OVERTIME_RATE_0420",
    "legacy_field": "OVERTIME_RATE_0420"
  },
  "SKILL_LEVEL_0425": {
    "host": "HV-EXPERTISE-SKILL-LEVEL",
    "record": "EXPERTISE",
    "table": "EXPERTISE",
    "column": "SKILL_LEVEL_0425",
    "legacy_field": "SKILL_LEVEL_0425"
  },
  "SKILL_LEVEL": {
    "host": "HV-EXPERTISE-SKILL-LEVEL",
    "record": "EXPERTISE",
    "table": "EXPERTISE",
    "column": "SKILL_LEVEL_0425",
    "legacy_field": "SKILL_LEVEL_0425"
  },
  "PATIENT_FIRST_NAME_0430": {
    "host": "HV-HOSPITAL-CLAIM-PATIENT-FIRST-NAME",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "PATIENT_FIRST_NAME_0430",
    "legacy_field": "PATIENT_FIRST_NAME_0430"
  },
  "PATIENT_LAST_NAME_0430": {
    "host": "HV-HOSPITAL-CLAIM-PATIENT-LAST-NAME",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "PATIENT_LAST_NAME_0430",
    "legacy_field": "PATIENT_LAST_NAME_0430"
  },
  "PATIENT_SEX_0430": {
    "host": "HV-HOSPITAL-CLAIM-PATIENT-SEX",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "PATIENT_SEX_0430",
    "legacy_field": "PATIENT_SEX_0430"
  },
  "RELATION_TO_EMPLOYEE_0430": {
    "host": "HV-HOSPITAL-CLAIM-RELATION-TO-EMPLOYEE",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "RELATION_TO_EMPLOYEE_0430",
    "legacy_field": "RELATION_TO_EMPLOYEE_0430"
  },
  "HOSPITAL_NAME_0430": {
    "host": "HV-HOSPITAL-CLAIM-HOSPITAL-NAME",
    "record": "HOSPITAL_CLAIM",

```



```

    "table": "HOSPITAL_CLAIM",
    "column": "HOSPITAL_NAME_0430",
    "legacy_field": "HOSPITAL_NAME_0430"
  },
  "HOSPITAL_NAME": {
    "host": "HV-HOSPITAL-CLAIM-HOSPITAL-NAME",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "HOSPITAL_NAME_0430",
    "legacy_field": "HOSPITAL_NAME_0430"
  },
  "HOSP_STREET_0430": {
    "host": "HV-HOSPITAL-CLAIM-HOSP-STREET",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "HOSP_STREET_0430",
    "legacy_field": "HOSP_STREET_0430"
  },
  "HOSP_STREET": {
    "host": "HV-HOSPITAL-CLAIM-HOSP-STREET",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "HOSP_STREET_0430",
    "legacy_field": "HOSP_STREET_0430"
  },
  "HOSP_CITY_0430": {
    "host": "HV-HOSPITAL-CLAIM-HOSP-CITY",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "HOSP_CITY_0430",
    "legacy_field": "HOSP_CITY_0430"
  },
  "HOSP_CITY": {
    "host": "HV-HOSPITAL-CLAIM-HOSP-CITY",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "HOSP_CITY_0430",
    "legacy_field": "HOSP_CITY_0430"
  },
  "HOSP_STATE_0430": {
    "host": "HV-HOSPITAL-CLAIM-HOSP-STATE",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "HOSP_STATE_0430",
    "legacy_field": "HOSP_STATE_0430"
  },
  "HOSP_STATE": {
    "host": "HV-HOSPITAL-CLAIM-HOSP-STATE",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "HOSP_STATE_0430",
    "legacy_field": "HOSP_STATE_0430"
  },
  "HOSP_ZIP_FIRST_FIVE_0430": {
    "host": "HV-HOSPITAL-CLAIM-HOSP-ZIP-FIRST-FIVE",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "HOSP_ZIP_FIRST_FIVE_0430",
    "legacy_field": "HOSP_ZIP_FIRST_FIVE_0430"
  },
  "HOSP_ZIP_FIRST_FIVE": {
    "host": "HV-HOSPITAL-CLAIM-HOSP-ZIP-FIRST-FIVE",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "HOSP_ZIP_FIRST_FIVE_0430",
    "legacy_field": "HOSP_ZIP_FIRST_FIVE_0430"
  },
  "HOSP_ZIP_LAST_FOUR_0430": {
    "host": "HV-HOSPITAL-CLAIM-HOSP-ZIP-LAST-FOUR",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "HOSP_ZIP_LAST_FOUR_0430",
    "legacy_field": "HOSP_ZIP_LAST_FOUR_0430"
  },
  "HOSP_ZIP_LAST_FOUR": {
    "host": "HV-HOSPITAL-CLAIM-HOSP-ZIP-LAST-FOUR",

```

```

    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "HOSP_ZIP_LAST_FOUR_0430",
    "legacy_field": "HOSP_ZIP_LAST_FOUR_0430"
  },
  "DIAGNOSIS_0430": {
    "host": "HV-HOSPITAL-CLAIM-DIAGNOSIS",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "DIAGNOSIS_0430",
    "legacy_field": "DIAGNOSIS_0430"
  },
  "DIAGNOSIS": {
    "host": "HV-NON-HOSP-CLAIM-DIAGNOSIS",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "DIAGNOSIS_0445",
    "legacy_field": "DIAGNOSIS_0445"
  },
  "WARD_DAYS_0430": {
    "host": "HV-HOSPITAL-CLAIM-WARD-DAYS",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "WARD_DAYS_0430",
    "legacy_field": "WARD_DAYS_0430"
  },
  "WARD_DAYS": {
    "host": "HV-HOSPITAL-CLAIM-WARD-DAYS",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "WARD_DAYS_0430",
    "legacy_field": "WARD_DAYS_0430"
  },
  "WARD_RATE_0430": {
    "host": "HV-HOSPITAL-CLAIM-WARD-RATE",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "WARD_RATE_0430",
    "legacy_field": "WARD_RATE_0430"
  },
  "WARD_RATE": {
    "host": "HV-HOSPITAL-CLAIM-WARD-RATE",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "WARD_RATE_0430",
    "legacy_field": "WARD_RATE_0430"
  },
  "WARD_TOTAL_0430": {
    "host": "HV-HOSPITAL-CLAIM-WARD-TOTAL",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "WARD_TOTAL_0430",
    "legacy_field": "WARD_TOTAL_0430"
  },
  "WARD_TOTAL": {
    "host": "HV-HOSPITAL-CLAIM-WARD-TOTAL",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "WARD_TOTAL_0430",
    "legacy_field": "WARD_TOTAL_0430"
  },
  "SEMI_DAYS_0430": {
    "host": "HV-HOSPITAL-CLAIM-SEMI-DAYS",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "SEMI_DAYS_0430",
    "legacy_field": "SEMI_DAYS_0430"
  },
  "SEMI_DAYS": {
    "host": "HV-HOSPITAL-CLAIM-SEMI-DAYS",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "SEMI_DAYS_0430",
    "legacy_field": "SEMI_DAYS_0430"
  },
  "SEMI_RATE_0430": {

```

```

    "host": "HV-HOSPITAL-CLAIM-SEMI-RATE",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "SEMI_RATE_0430",
    "legacy_field": "SEMI_RATE_0430"
  },
  "SEMI_RATE": {
    "host": "HV-HOSPITAL-CLAIM-SEMI-RATE",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "SEMI_RATE_0430",
    "legacy_field": "SEMI_RATE_0430"
  },
  "SEMI_TOTAL_0430": {
    "host": "HV-HOSPITAL-CLAIM-SEMI-TOTAL",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "SEMI_TOTAL_0430",
    "legacy_field": "SEMI_TOTAL_0430"
  },
  "SEMI_TOTAL": {
    "host": "HV-HOSPITAL-CLAIM-SEMI-TOTAL",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "SEMI_TOTAL_0430",
    "legacy_field": "SEMI_TOTAL_0430"
  },
  "DELIVERY_COST_0430": {
    "host": "HV-HOSPITAL-CLAIM-DELIVERY-COST",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "DELIVERY_COST_0430",
    "legacy_field": "DELIVERY_COST_0430"
  },
  "DELIVERY_COST": {
    "host": "HV-HOSPITAL-CLAIM-DELIVERY-COST",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "DELIVERY_COST_0430",
    "legacy_field": "DELIVERY_COST_0430"
  },
  "ANESTHESIA_COST_0430": {
    "host": "HV-HOSPITAL-CLAIM-ANESTHESIA-COST",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "ANESTHESIA_COST_0430",
    "legacy_field": "ANESTHESIA_COST_0430"
  },
  "ANESTHESIA_COST": {
    "host": "HV-HOSPITAL-CLAIM-ANESTHESIA-COST",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "ANESTHESIA_COST_0430",
    "legacy_field": "ANESTHESIA_COST_0430"
  },
  "LAB_COST_0430": {
    "host": "HV-HOSPITAL-CLAIM-LAB-COST",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "LAB_COST_0430",
    "legacy_field": "LAB_COST_0430"
  },
  "LAB_COST": {
    "host": "HV-HOSPITAL-CLAIM-LAB-COST",
    "record": "HOSPITAL_CLAIM",
    "table": "HOSPITAL_CLAIM",
    "column": "LAB_COST_0430",
    "legacy_field": "LAB_COST_0430"
  },
  "INS_PLAN_CODE_0435": {
    "host": "HV-INSURANCE-PLAN-INS-PLAN-CODE",
    "record": "INSURANCE_PLAN",
    "table": "INSURANCE_PLAN",
    "column": "INS_PLAN_CODE_0435",
    "legacy_field": "INS_PLAN_CODE_0435"
  },

```

```

"INS_CO_NAME_0435": {
  "host": "HV-INSURANCE-PLAN-INS-CO-NAME",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_NAME_0435",
  "legacy_field": "INS_CO_NAME_0435"
},
"INS_CO_NAME": {
  "host": "HV-INSURANCE-PLAN-INS-CO-NAME",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_NAME_0435",
  "legacy_field": "INS_CO_NAME_0435"
},
"INS_CO_STREET_0435": {
  "host": "HV-INSURANCE-PLAN-INS-CO-STREET",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_STREET_0435",
  "legacy_field": "INS_CO_STREET_0435"
},
"INS_CO_STREET": {
  "host": "HV-INSURANCE-PLAN-INS-CO-STREET",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_STREET_0435",
  "legacy_field": "INS_CO_STREET_0435"
},
"INS_CO_CITY_0435": {
  "host": "HV-INSURANCE-PLAN-INS-CO-CITY",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_CITY_0435",
  "legacy_field": "INS_CO_CITY_0435"
},
"INS_CO_CITY": {
  "host": "HV-INSURANCE-PLAN-INS-CO-CITY",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_CITY_0435",
  "legacy_field": "INS_CO_CITY_0435"
},
"INS_CO_STATE_0435": {
  "host": "HV-INSURANCE-PLAN-INS-CO-STATE",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_STATE_0435",
  "legacy_field": "INS_CO_STATE_0435"
},
"INS_CO_STATE": {
  "host": "HV-INSURANCE-PLAN-INS-CO-STATE",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_STATE_0435",
  "legacy_field": "INS_CO_STATE_0435"
},
"INS_CO_ZIP_FIRST_FIVE_0435": {
  "host": "HV-INSURANCE-PLAN-INS-CO-ZIP-FIRST-FIVE",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_ZIP_FIRST_FIVE_0435",
  "legacy_field": "INS_CO_ZIP_FIRST_FIVE_0435"
},
"INS_CO_ZIP_FIRST_FIVE": {
  "host": "HV-INSURANCE-PLAN-INS-CO-ZIP-FIRST-FIVE",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_ZIP_FIRST_FIVE_0435",
  "legacy_field": "INS_CO_ZIP_FIRST_FIVE_0435"
},
"INS_CO_ZIP_LAST_FOUR_0435": {
  "host": "HV-INSURANCE-PLAN-INS-CO-ZIP-LAST-FOUR",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_ZIP_LAST_FOUR_0435",
  "legacy_field": "INS_CO_ZIP_LAST_FOUR_0435"
}

```

```

},
"INS_CO_ZIP_LAST_FOUR": {
  "host": "HV-INSURANCE-PLAN-INS-CO-ZIP-LAST-FOUR",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_ZIP_LAST_FOUR_0435",
  "legacy_field": "INS_CO_ZIP_LAST_FOUR_0435"
},
"INS_CO_PHONE_0435": {
  "host": "HV-INSURANCE-PLAN-INS-CO-PHONE",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_PHONE_0435",
  "legacy_field": "INS_CO_PHONE_0435"
},
"INS_CO_PHONE": {
  "host": "HV-INSURANCE-PLAN-INS-CO-PHONE",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "INS_CO_PHONE_0435",
  "legacy_field": "INS_CO_PHONE_0435"
},
"GROUP_NUMBER_0435": {
  "host": "HV-INSURANCE-PLAN-GROUP-NUMBER",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "GROUP_NUMBER_0435",
  "legacy_field": "GROUP_NUMBER_0435"
},
"GROUP_NUMBER": {
  "host": "HV-INSURANCE-PLAN-GROUP-NUMBER",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "GROUP_NUMBER_0435",
  "legacy_field": "GROUP_NUMBER_0435"
},
"DEDUCT_0435": {
  "host": "HV-INSURANCE-PLAN-DEDUCT",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "DEDUCT_0435",
  "legacy_field": "DEDUCT_0435"
},
"DEDUCT": {
  "host": "HV-INSURANCE-PLAN-DEDUCT",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "DEDUCT_0435",
  "legacy_field": "DEDUCT_0435"
},
"MAXIMUM_LIFE_COST_0435": {
  "host": "HV-INSURANCE-PLAN-MAXIMUM-LIFE-COST",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "MAXIMUM_LIFE_COST_0435",
  "legacy_field": "MAXIMUM_LIFE_COST_0435"
},
"MAXIMUM_LIFE_COST": {
  "host": "HV-INSURANCE-PLAN-MAXIMUM-LIFE-COST",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "MAXIMUM_LIFE_COST_0435",
  "legacy_field": "MAXIMUM_LIFE_COST_0435"
},
"FAMILY_COST_0435": {
  "host": "HV-INSURANCE-PLAN-FAMILY-COST",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "FAMILY_COST_0435",
  "legacy_field": "FAMILY_COST_0435"
},
"FAMILY_COST": {
  "host": "HV-INSURANCE-PLAN-FAMILY-COST",
  "record": "INSURANCE_PLAN",
  "table": "INSURANCE_PLAN",
  "column": "FAMILY_COST_0435",

```

```

    "legacy_field": "FAMILY_COST_0435"
  },
  "DEP_COST_0435": {
    "host": "HV-INSURANCE-PLAN-DEP-COST",
    "record": "INSURANCE_PLAN",
    "table": "INSURANCE_PLAN",
    "column": "DEP_COST_0435",
    "legacy_field": "DEP_COST_0435"
  },
  "DEP_COST": {
    "host": "HV-INSURANCE-PLAN-DEP-COST",
    "record": "INSURANCE_PLAN",
    "table": "INSURANCE_PLAN",
    "column": "DEP_COST_0435",
    "legacy_field": "DEP_COST_0435"
  },
  "JOB_ID_0440": {
    "host": "HV-JOB-JOB-ID",
    "record": "JOB",
    "table": "JOB",
    "column": "JOB_ID_0440",
    "legacy_field": "JOB_ID_0440"
  },
  "JOB_ID": {
    "host": "HV-JOB-JOB-ID",
    "record": "JOB",
    "table": "JOB",
    "column": "JOB_ID_0440",
    "legacy_field": "JOB_ID_0440"
  },
  "TITLE_0440": {
    "host": "HV-JOB-TITLE",
    "record": "JOB",
    "table": "JOB",
    "column": "TITLE_0440",
    "legacy_field": "TITLE_0440"
  },
  "TITLE": {
    "host": "HV-JOB-TITLE",
    "record": "JOB",
    "table": "JOB",
    "column": "TITLE_0440",
    "legacy_field": "TITLE_0440"
  },
  "DESCRIPTION_LINE_0440": {
    "host": "HV-JOB-DESCRIPTION-LINE",
    "record": "JOB",
    "table": "JOB",
    "column": "DESCRIPTION_LINE_0440",
    "legacy_field": "DESCRIPTION_LINE_0440"
  },
  "DESCRIPTION_LINE": {
    "host": "HV-JOB-DESCRIPTION-LINE",
    "record": "JOB",
    "table": "JOB",
    "column": "DESCRIPTION_LINE_0440",
    "legacy_field": "DESCRIPTION_LINE_0440"
  },
  "REQUIREMENT_LINE_0440": {
    "host": "HV-JOB-REQUIREMENT-LINE",
    "record": "JOB",
    "table": "JOB",
    "column": "REQUIREMENT_LINE_0440",
    "legacy_field": "REQUIREMENT_LINE_0440"
  },
  "REQUIREMENT_LINE": {
    "host": "HV-JOB-REQUIREMENT-LINE",
    "record": "JOB",
    "table": "JOB",
    "column": "REQUIREMENT_LINE_0440",
    "legacy_field": "REQUIREMENT_LINE_0440"
  },
  "MINIMUM_SALARY_0440": {
    "host": "HV-JOB-MINIMUM-SALARY",
    "record": "JOB",
    "table": "JOB",

```

```

    "column": "MINIMUM_SALARY_0440",
    "legacy_field": "MINIMUM_SALARY_0440"
  },
  "MINIMUM_SALARY": {
    "host": "HV-JOB-MINIMUM-SALARY",
    "record": "JOB",
    "table": "JOB",
    "column": "MINIMUM_SALARY_0440",
    "legacy_field": "MINIMUM_SALARY_0440"
  },
  "MAXIMUM_SALARY_0440": {
    "host": "HV-JOB-MAXIMUM-SALARY",
    "record": "JOB",
    "table": "JOB",
    "column": "MAXIMUM_SALARY_0440",
    "legacy_field": "MAXIMUM_SALARY_0440"
  },
  "MAXIMUM_SALARY": {
    "host": "HV-JOB-MAXIMUM-SALARY",
    "record": "JOB",
    "table": "JOB",
    "column": "MAXIMUM_SALARY_0440",
    "legacy_field": "MAXIMUM_SALARY_0440"
  },
  "SALARY_GRADES_0440": {
    "host": "HV-JOB-SALARY-GRADES",
    "record": "JOB",
    "table": "JOB",
    "column": "SALARY_GRADES_0440",
    "legacy_field": "SALARY_GRADES_0440"
  },
  "SALARY_GRADES": {
    "host": "HV-JOB-SALARY-GRADES",
    "record": "JOB",
    "table": "JOB",
    "column": "SALARY_GRADES_0440",
    "legacy_field": "SALARY_GRADES_0440"
  },
  "NUMBER_OF_POSITIONS_0440": {
    "host": "HV-JOB-NUMBER-OF-POSITIONS",
    "record": "JOB",
    "table": "JOB",
    "column": "NUMBER_OF_POSITIONS_0440",
    "legacy_field": "NUMBER_OF_POSITIONS_0440"
  },
  "NUMBER_OF_POSITIONS": {
    "host": "HV-JOB-NUMBER-OF-POSITIONS",
    "record": "JOB",
    "table": "JOB",
    "column": "NUMBER_OF_POSITIONS_0440",
    "legacy_field": "NUMBER_OF_POSITIONS_0440"
  },
  "NUMBER_OPEN_0440": {
    "host": "HV-JOB-NUMBER-OPEN",
    "record": "JOB",
    "table": "JOB",
    "column": "NUMBER_OPEN_0440",
    "legacy_field": "NUMBER_OPEN_0440"
  },
  "NUMBER_OPEN": {
    "host": "HV-JOB-NUMBER-OPEN",
    "record": "JOB",
    "table": "JOB",
    "column": "NUMBER_OPEN_0440",
    "legacy_field": "NUMBER_OPEN_0440"
  },
  "PATIENT_FIRST_NAME_0445": {
    "host": "HV-NON-HOSP-CLAIM-PATIENT-FIRST-NAME",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PATIENT_FIRST_NAME_0445",
    "legacy_field": "PATIENT_FIRST_NAME_0445"
  },
  "PATIENT_LAST_NAME_0445": {
    "host": "HV-NON-HOSP-CLAIM-PATIENT-LAST-NAME",
    "record": "NON_HOSP_CLAIM",

```

```

    "table": "NON_HOSP_CLAIM",
    "column": "PATIENT_LAST_NAME_0445",
    "legacy_field": "PATIENT_LAST_NAME_0445"
  },
  "PATIENT_SEX_0445": {
    "host": "HV-NON-HOSP-CLAIM-PATIENT-SEX",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PATIENT_SEX_0445",
    "legacy_field": "PATIENT_SEX_0445"
  },
  "RELATION_TO_EMPLOYEE_0445": {
    "host": "HV-NON-HOSP-CLAIM-RELATION-TO-EMPLOYEE",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "RELATION_TO_EMPLOYEE_0445",
    "legacy_field": "RELATION_TO_EMPLOYEE_0445"
  },
  "PHYSICIAN_FIRST_NAME_0445": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-FIRST-NAME",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_FIRST_NAME_0445",
    "legacy_field": "PHYSICIAN_FIRST_NAME_0445"
  },
  "PHYSICIAN_FIRST_NAME": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-FIRST-NAME",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_FIRST_NAME_0445",
    "legacy_field": "PHYSICIAN_FIRST_NAME_0445"
  },
  "PHYSICIAN_LAST_NAME_0445": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-LAST-NAME",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_LAST_NAME_0445",
    "legacy_field": "PHYSICIAN_LAST_NAME_0445"
  },
  "PHYSICIAN_LAST_NAME": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-LAST-NAME",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_LAST_NAME_0445",
    "legacy_field": "PHYSICIAN_LAST_NAME_0445"
  },
  "PHYSICIAN_STREET_0445": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-STREET",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_STREET_0445",
    "legacy_field": "PHYSICIAN_STREET_0445"
  },
  "PHYSICIAN_STREET": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-STREET",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_STREET_0445",
    "legacy_field": "PHYSICIAN_STREET_0445"
  },
  "PHYSICIAN_CITY_0445": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-CITY",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_CITY_0445",
    "legacy_field": "PHYSICIAN_CITY_0445"
  },
  "PHYSICIAN_CITY": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-CITY",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_CITY_0445",
    "legacy_field": "PHYSICIAN_CITY_0445"
  },
  "PHYSICIAN_STATE_0445": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-STATE",

```



```

    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_STATE_0445",
    "legacy_field": "PHYSICIAN_STATE_0445"
  },
  "PHYSICIAN_STATE": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-STATE",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_STATE_0445",
    "legacy_field": "PHYSICIAN_STATE_0445"
  },
  "PHYSICIAN_ZIP_FIRST_FIVE_0445": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-ZIP-FIRST-FIVE",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_ZIP_FIRST_FIVE_0445",
    "legacy_field": "PHYSICIAN_ZIP_FIRST_FIVE_0445"
  },
  "PHYSICIAN_ZIP_FIRST_FIVE": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-ZIP-FIRST-FIVE",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_ZIP_FIRST_FIVE_0445",
    "legacy_field": "PHYSICIAN_ZIP_FIRST_FIVE_0445"
  },
  "PHYSICIAN_ZIP_LAST_FOUR_0445": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-ZIP-LAST-FOUR",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_ZIP_LAST_FOUR_0445",
    "legacy_field": "PHYSICIAN_ZIP_LAST_FOUR_0445"
  },
  "PHYSICIAN_ZIP_LAST_FOUR": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-ZIP-LAST-FOUR",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_ZIP_LAST_FOUR_0445",
    "legacy_field": "PHYSICIAN_ZIP_LAST_FOUR_0445"
  },
  "PHYSICIAN_ID_0445": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-ID",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_ID_0445",
    "legacy_field": "PHYSICIAN_ID_0445"
  },
  "PHYSICIAN_ID": {
    "host": "HV-NON-HOSP-CLAIM-PHYSICIAN-ID",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PHYSICIAN_ID_0445",
    "legacy_field": "PHYSICIAN_ID_0445"
  },
  "DIAGNOSIS_0445": {
    "host": "HV-NON-HOSP-CLAIM-DIAGNOSIS",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "DIAGNOSIS_0445",
    "legacy_field": "DIAGNOSIS_0445"
  },
  "NUMBER_OF_PROCEDURES_0445": {
    "host": "HV-NON-HOSP-CLAIM-NUMBER-OF-PROCEDURES",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "NUMBER_OF_PROCEDURES_0445",
    "legacy_field": "NUMBER_OF_PROCEDURES_0445"
  },
  "PROCEDURE_CODE_0445": {
    "host": "HV-NON-HOSP-CLAIM-PROCEDURE-CODE",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "PROCEDURE_CODE_0445",
    "legacy_field": "PROCEDURE_CODE_0445"
  },
  "DESCRIPTION_OF_SERVICE_0445": {

```

```

    "host": "HV-NON-HOSP-CLAIM-DESCRIPTION-OF-SERVICE",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "DESCRIPTION_OF_SERVICE_0445",
    "legacy_field": "DESCRIPTION_OF_SERVICE_0445"
  },
  "FEE_0445": {
    "host": "HV-NON-HOSP-CLAIM-FEE",
    "record": "NON_HOSP_CLAIM",
    "table": "NON_HOSP_CLAIM",
    "column": "FEE_0445",
    "legacy_field": "FEE_0445"
  },
  "OFFICE_CODE_0450": {
    "host": "HV-OFFICE-OFFICE-CODE",
    "record": "OFFICE",
    "table": "OFFICE",
    "column": "OFFICE_CODE_0450",
    "legacy_field": "OFFICE_CODE_0450"
  },
  "OFFICE_CODE": {
    "host": "HV-OFFICE-OFFICE-CODE",
    "record": "OFFICE",
    "table": "OFFICE",
    "column": "OFFICE_CODE_0450",
    "legacy_field": "OFFICE_CODE_0450"
  },
  "OFFICE_STREET_0450": {
    "host": "HV-OFFICE-OFFICE-STREET",
    "record": "OFFICE",
    "table": "OFFICE",
    "column": "OFFICE_STREET_0450",
    "legacy_field": "OFFICE_STREET_0450"
  },
  "OFFICE_STREET": {
    "host": "HV-OFFICE-OFFICE-STREET",
    "record": "OFFICE",
    "table": "OFFICE",
    "column": "OFFICE_STREET_0450",
    "legacy_field": "OFFICE_STREET_0450"
  },
  "OFFICE_CITY_0450": {
    "host": "HV-OFFICE-OFFICE-CITY",
    "record": "OFFICE",
    "table": "OFFICE",
    "column": "OFFICE_CITY_0450",
    "legacy_field": "OFFICE_CITY_0450"
  },
  "OFFICE_CITY": {
    "host": "HV-OFFICE-OFFICE-CITY",
    "record": "OFFICE",
    "table": "OFFICE",
    "column": "OFFICE_CITY_0450",
    "legacy_field": "OFFICE_CITY_0450"
  },
  "OFFICE_STATE_0450": {
    "host": "HV-OFFICE-OFFICE-STATE",
    "record": "OFFICE",
    "table": "OFFICE",
    "column": "OFFICE_STATE_0450",
    "legacy_field": "OFFICE_STATE_0450"
  },
  "OFFICE_STATE": {
    "host": "HV-OFFICE-OFFICE-STATE",
    "record": "OFFICE",
    "table": "OFFICE",
    "column": "OFFICE_STATE_0450",
    "legacy_field": "OFFICE_STATE_0450"
  },
  "OFFICE_ZIP_FIRST_FIVE_0450": {
    "host": "HV-OFFICE-OFFICE-ZIP-FIRST-FIVE",
    "record": "OFFICE",
    "table": "OFFICE",
    "column": "OFFICE_ZIP_FIRST_FIVE_0450",
    "legacy_field": "OFFICE_ZIP_FIRST_FIVE_0450"
  },

```

```

"OFFICE_ZIP_FIRST_FIVE": {
  "host": "HV-OFFICE-OFFICE-ZIP-FIRST-FIVE",
  "record": "OFFICE",
  "table": "OFFICE",
  "column": "OFFICE_ZIP_FIRST_FIVE_0450",
  "legacy_field": "OFFICE_ZIP_FIRST_FIVE_0450"
},
"OFFICE_ZIP_LAST_FOUR_0450": {
  "host": "HV-OFFICE-OFFICE-ZIP-LAST-FOUR",
  "record": "OFFICE",
  "table": "OFFICE",
  "column": "OFFICE_ZIP_LAST_FOUR_0450",
  "legacy_field": "OFFICE_ZIP_LAST_FOUR_0450"
},
"OFFICE_ZIP_LAST_FOUR": {
  "host": "HV-OFFICE-OFFICE-ZIP-LAST-FOUR",
  "record": "OFFICE",
  "table": "OFFICE",
  "column": "OFFICE_ZIP_LAST_FOUR_0450",
  "legacy_field": "OFFICE_ZIP_LAST_FOUR_0450"
},
"OFFICE_PHONE_0450": {
  "host": "HV-OFFICE-OFFICE-PHONE",
  "record": "OFFICE",
  "table": "OFFICE",
  "column": "OFFICE_PHONE_0450",
  "legacy_field": "OFFICE_PHONE_0450"
},
"OFFICE_PHONE": {
  "host": "HV-OFFICE-OFFICE-PHONE",
  "record": "OFFICE",
  "table": "OFFICE",
  "column": "OFFICE_PHONE_0450",
  "legacy_field": "OFFICE_PHONE_0450"
},
"OFFICE_AREA_CODE_0450": {
  "host": "HV-OFFICE-OFFICE-AREA-CODE",
  "record": "OFFICE",
  "table": "OFFICE",
  "column": "OFFICE_AREA_CODE_0450",
  "legacy_field": "OFFICE_AREA_CODE_0450"
},
"OFFICE_AREA_CODE": {
  "host": "HV-OFFICE-OFFICE-AREA-CODE",
  "record": "OFFICE",
  "table": "OFFICE",
  "column": "OFFICE_AREA_CODE_0450",
  "legacy_field": "OFFICE_AREA_CODE_0450"
},
"SPEED_DIAL_0450": {
  "host": "HV-OFFICE-SPEED-DIAL",
  "record": "OFFICE",
  "table": "OFFICE",
  "column": "SPEED_DIAL_0450",
  "legacy_field": "SPEED_DIAL_0450"
},
"SPEED_DIAL": {
  "host": "HV-OFFICE-SPEED-DIAL",
  "record": "OFFICE",
  "table": "OFFICE",
  "column": "SPEED_DIAL_0450",
  "legacy_field": "SPEED_DIAL_0450"
},
"SKILL_ID_0455": {
  "host": "HV-SKILL-SKILL-ID",
  "record": "SKILL",
  "table": "SKILL",
  "column": "SKILL_ID_0455",
  "legacy_field": "SKILL_ID_0455"
},
"SKILL_ID": {
  "host": "HV-SKILL-SKILL-ID",
  "record": "SKILL",
  "table": "SKILL",
  "column": "SKILL_ID_0455",
  "legacy_field": "SKILL_ID_0455"
}

```

```

    },
    "SKILL_NAME_0455": {
        "host": "HV-SKILL-SKILL-NAME",
        "record": "SKILL",
        "table": "SKILL",
        "column": "SKILL_NAME_0455",
        "legacy_field": "SKILL_NAME_0455"
    },
    "SKILL_NAME": {
        "host": "HV-SKILL-SKILL-NAME",
        "record": "SKILL",
        "table": "SKILL",
        "column": "SKILL_NAME_0455",
        "legacy_field": "SKILL_NAME_0455"
    },
    "SKILL_DESCRIPTION_0455": {
        "host": "HV-SKILL-SKILL-DESCRIPTION",
        "record": "SKILL",
        "table": "SKILL",
        "column": "SKILL_DESCRIPTION_0455",
        "legacy_field": "SKILL_DESCRIPTION_0455"
    },
    "SKILL_DESCRIPTION": {
        "host": "HV-SKILL-SKILL-DESCRIPTION",
        "record": "SKILL",
        "table": "SKILL",
        "column": "SKILL_DESCRIPTION_0455",
        "legacy_field": "SKILL_DESCRIPTION_0455"
    },
    "STRUCTURE_CODE_0460": {
        "host": "HV-STRUCTURE-STRUCTURE-CODE",
        "record": "STRUCTURE",
        "table": "STRUCTURE",
        "column": "STRUCTURE_CODE_0460",
        "legacy_field": "STRUCTURE_CODE_0460"
    },
    "STRUCTURE_CODE": {
        "host": "HV-STRUCTURE-STRUCTURE-CODE",
        "record": "STRUCTURE",
        "table": "STRUCTURE",
        "column": "STRUCTURE_CODE_0460",
        "legacy_field": "STRUCTURE_CODE_0460"
    }
},
"calc_key_map": {
    "DEPARTMENT": {
        "record": "DEPARTMENT",
        "table": "DEPARTMENT",
        "key": "DEPT_ID_0410",
        "host": "HV-DEPARTMENT-DEPT-ID"
    },
    "EMPLOYEE": {
        "record": "EMPLOYEE",
        "table": "EMPLOYEE",
        "key": "EMP_ID_0415",
        "host": "HV-EMPLOYEE-EMP-ID"
    },
    "INSURANCE_PLAN": {
        "record": "INSURANCE_PLAN",
        "table": "INSURANCE_PLAN",
        "key": "INS_PLAN_CODE_0435",
        "host": "HV-INSURANCE-PLAN-INS-PLAN-CODE"
    },
    "JOB": {
        "record": "JOB",
        "table": "JOB",
        "key": "JOB_ID_0440",
        "host": "HV-JOB-JOB-ID"
    },
    "OFFICE": {
        "record": "OFFICE",
        "table": "OFFICE",
        "key": "OFFICE_CODE_0450",
        "host": "HV-OFFICE-OFFICE-CODE"
    },
    "SKILL": {

```

```

    "record": "SKILL",
    "table": "SKILL",
    "key": "SKILL_ID_0455",
    "host": "HV-SKILL-SKILL-ID"
  }
},
"set_ordering_map": {
  "DEPT_EMPLOYEE": {
    "order_by": [
      "DEPT_ID_0410"
    ]
  },
  "MANAGES": {
    "order_by": []
  },
  "OFFICE_EMPLOYEE": {
    "order_by": [
      "OFFICE_CODE_0450"
    ]
  },
  "EMP_EXPERTISE": {
    "order_by": [
      "EMP_ID_0415"
    ]
  },
  "SKILL_EXPERTISE": {
    "order_by": [
      "SKILL_ID_0455"
    ]
  },
  "EMP_EMPOSITION": {
    "order_by": [
      "EMP_ID_0415"
    ]
  },
  "REPORTS_TO": {
    "order_by": []
  },
  "EMP_COVERAGE": {
    "order_by": [
      "EMP_ID_0415"
    ]
  },
  "JOB_EMPOSITION": {
    "order_by": [
      "JOB_ID_0440"
    ]
  },
  "COVERAGE_CLAIMS": {
    "order_by": [
      "COVERAGE_ID"
    ]
  }
},
"navigation_intent": {
  "DEPT_EMPLOYEE": {
    "access_pattern": "SET_NAVIGATION",
    "parent_record": "DEPARTMENT",
    "child_record": "EMPLOYEE",
    "parent_key": "DEPT_ID_0410",
    "child_fk": "DEPT_ID_0410",
    "order_by": [
      "DEPT_ID_0410"
    ]
  },
  "MANAGES": {
    "access_pattern": "SET_NAVIGATION",
    "parent_record": "EMPLOYEE",
    "child_record": "STRUCTURE",
    "parent_key": "EMP_ID_0415",
    "child_fk": null,
    "order_by": []
  },
  "OFFICE_EMPLOYEE": {
    "access_pattern": "SET_NAVIGATION",
    "parent_record": "OFFICE",

```

```

    "child_record": "EMPLOYEE",
    "parent_key": "OFFICE_CODE_0450",
    "child_fk": "OFFICE_CODE_0450",
    "order_by": [
        "OFFICE_CODE_0450"
    ]
},
"EMP_EXPERTISE": {
    "access_pattern": "SET_NAVIGATION",
    "parent_record": "EMPLOYEE",
    "child_record": "EXPERTISE",
    "parent_key": "EMP_ID_0415",
    "child_fk": "EMP_ID_0415",
    "order_by": [
        "EMP_ID_0415"
    ]
},
"SKILL_EXPERTISE": {
    "access_pattern": "SET_NAVIGATION",
    "parent_record": "SKILL",
    "child_record": "EXPERTISE",
    "parent_key": "SKILL_ID_0455",
    "child_fk": "SKILL_ID_0455",
    "order_by": [
        "SKILL_ID_0455"
    ]
},
"EMP_EMPOSITION": {
    "access_pattern": "SET_NAVIGATION",
    "parent_record": "EMPLOYEE",
    "child_record": "EMPOSITION",
    "parent_key": "EMP_ID_0415",
    "child_fk": "EMP_ID_0415",
    "order_by": [
        "EMP_ID_0415"
    ]
},
"REPORTS_TO": {
    "access_pattern": "SET_NAVIGATION",
    "parent_record": "EMPLOYEE",
    "child_record": "STRUCTURE",
    "parent_key": "EMP_ID_0415",
    "child_fk": null,
    "order_by": []
},
"EMP_COVERAGE": {
    "access_pattern": "SET_NAVIGATION",
    "parent_record": "EMPLOYEE",
    "child_record": "COVERAGE",
    "parent_key": "EMP_ID_0415",
    "child_fk": "EMP_ID_0415",
    "order_by": [
        "EMP_ID_0415"
    ]
},
"JOB_EMPOSITION": {
    "access_pattern": "SET_NAVIGATION",
    "parent_record": "JOB",
    "child_record": "EMPOSITION",
    "parent_key": "JOB_ID_0440",
    "child_fk": "JOB_ID_0440",
    "order_by": [
        "JOB_ID_0440"
    ]
},
"COVERAGE_CLAIMS": {
    "access_pattern": "SET_NAVIGATION",
    "parent_record": "COVERAGE",
    "child_record": "NON_HOSP_CLAIM",
    "parent_key": "COVERAGE_ID",
    "child_fk": "COVERAGE_ID",
    "order_by": [
        "COVERAGE_ID"
    ]
}
},

```

```

"nullable_fk_map": {
  "COVERAGE.EMP_ID_0415": true,
  "COVERAGE.INS_PLAN_CODE_0400": true,
  "DENTAL_CLAIM.COVERAGE_ID": true,
  "EMPLOYEE.DEPT_ID_0410": true,
  "EMPLOYEE.OFFICE_CODE_0450": true,
  "EMPOSITION.EMP_ID_0415": true,
  "EMPOSITION.JOB_ID_0440": true,
  "EXPERTISE.EMP_ID_0415": true,
  "EXPERTISE.SKILL_ID_0455": true,
  "HOSPITAL_CLAIM.COVERAGE_ID": true,
  "NON_HOSP_CLAIM.COVERAGE_ID": true,
  "STRUCTURE.MANAGES_EMP_ID_0415": true,
  "STRUCTURE.REPORTS_TO_EMP_ID_0415": true
},
"date_part_map": {
  "SELECTION_YEAR_0400": {
    "host": "HV-COVERAGE-SELECTION-DATE",
    "table": "COVERAGE",
    "column": "SELECTION_DATE_0400",
    "date_part": "YEAR",
    "substring_start": 3,
    "substring_length": 2
  },
  "SELECTION_MONTH_0400": {
    "host": "HV-COVERAGE-SELECTION-DATE",
    "table": "COVERAGE",
    "column": "SELECTION_DATE_0400",
    "date_part": "MONTH",
    "substring_start": 6,
    "substring_length": 2
  },
  "SELECTION_DAY_0400": {
    "host": "HV-COVERAGE-SELECTION-DATE",
    "table": "COVERAGE",
    "column": "SELECTION_DATE_0400",
    "date_part": "DAY",
    "substring_start": 9,
    "substring_length": 2
  },
  "TERMINATION_YEAR_0400": {
    "host": "HV-COVERAGE-TERMINATION-DATE",
    "table": "COVERAGE",
    "column": "TERMINATION_DATE_0400",
    "date_part": "YEAR",
    "substring_start": 3,
    "substring_length": 2
  },
  "TERMINATION_MONTH_0400": {
    "host": "HV-COVERAGE-TERMINATION-DATE",
    "table": "COVERAGE",
    "column": "TERMINATION_DATE_0400",
    "date_part": "MONTH",
    "substring_start": 6,
    "substring_length": 2
  },
  "TERMINATION_DAY_0400": {
    "host": "HV-COVERAGE-TERMINATION-DATE",
    "table": "COVERAGE",
    "column": "TERMINATION_DATE_0400",
    "date_part": "DAY",
    "substring_start": 9,
    "substring_length": 2
  },
  "CLAIM_YEAR_0405": {
    "host": "HV-DENTAL-CLAIM-CLAIM-DATE",
    "table": "DENTAL_CLAIM",
    "column": "CLAIM_DATE_0405",
    "date_part": "YEAR",
    "substring_start": 3,
    "substring_length": 2
  },
  "CLAIM_MONTH_0405": {
    "host": "HV-DENTAL-CLAIM-CLAIM-DATE",
    "table": "DENTAL_CLAIM",
    "column": "CLAIM_DATE_0405",

```

```

    "date_part": "MONTH",
    "substring_start": 6,
    "substring_length": 2
  },
  "CLAIM_DAY_0405": {
    "host": "HV-DENTAL-CLAIM-CLAIM-DATE",
    "table": "DENTAL_CLAIM",
    "column": "CLAIM_DATE_0405",
    "date_part": "DAY",
    "substring_start": 9,
    "substring_length": 2
  },
  "PATIENT_BIRTH_YEAR_0405": {
    "host": "HV-DENTAL-CLAIM-PATIENT-BIRTH-DATE",
    "table": "DENTAL_CLAIM",
    "column": "PATIENT_BIRTH_DATE_0405",
    "date_part": "YEAR",
    "substring_start": 3,
    "substring_length": 2
  },
  "PATIENT_BIRTH_MONTH_0405": {
    "host": "HV-DENTAL-CLAIM-PATIENT-BIRTH-DATE",
    "table": "DENTAL_CLAIM",
    "column": "PATIENT_BIRTH_DATE_0405",
    "date_part": "MONTH",
    "substring_start": 6,
    "substring_length": 2
  },
  "PATIENT_BIRTH_DAY_0405": {
    "host": "HV-DENTAL-CLAIM-PATIENT-BIRTH-DATE",
    "table": "DENTAL_CLAIM",
    "column": "PATIENT_BIRTH_DATE_0405",
    "date_part": "DAY",
    "substring_start": 9,
    "substring_length": 2
  },
  "SERVICE_YEAR_0405": {
    "host": "HV-DENTAL-CLAIM-SERVICE-DATE",
    "table": "DENTAL_CLAIM",
    "column": "SERVICE_DATE_0405",
    "date_part": "YEAR",
    "substring_start": 3,
    "substring_length": 2
  },
  "SERVICE_MONTH_0405": {
    "host": "HV-DENTAL-CLAIM-SERVICE-DATE",
    "table": "DENTAL_CLAIM",
    "column": "SERVICE_DATE_0405",
    "date_part": "MONTH",
    "substring_start": 6,
    "substring_length": 2
  },
  "SERVICE_DAY_0405": {
    "host": "HV-DENTAL-CLAIM-SERVICE-DATE",
    "table": "DENTAL_CLAIM",
    "column": "SERVICE_DATE_0405",
    "date_part": "DAY",
    "substring_start": 9,
    "substring_length": 2
  },
  "START_YEAR_0415": {
    "host": "HV-EMPLOYEE-START-DATE",
    "table": "EMPLOYEE",
    "column": "START_DATE_0415",
    "date_part": "YEAR",
    "substring_start": 3,
    "substring_length": 2
  },
  "START_MONTH_0415": {
    "host": "HV-EMPLOYEE-START-DATE",
    "table": "EMPLOYEE",
    "column": "START_DATE_0415",
    "date_part": "MONTH",
    "substring_start": 6,
    "substring_length": 2
  },

```



```

"START_DAY_0415": {
  "host": "HV-EMPLOYEE-START-DATE",
  "table": "EMPLOYEE",
  "column": "START_DATE_0415",
  "date_part": "DAY",
  "substring_start": 9,
  "substring_length": 2
},
"TERMINATION_YEAR_0415": {
  "host": "HV-EMPLOYEE-TERMINATION-DATE",
  "table": "EMPLOYEE",
  "column": "TERMINATION_DATE_0415",
  "date_part": "YEAR",
  "substring_start": 3,
  "substring_length": 2
},
"TERMINATION_MONTH_0415": {
  "host": "HV-EMPLOYEE-TERMINATION-DATE",
  "table": "EMPLOYEE",
  "column": "TERMINATION_DATE_0415",
  "date_part": "MONTH",
  "substring_start": 6,
  "substring_length": 2
},
"TERMINATION_DAY_0415": {
  "host": "HV-EMPLOYEE-TERMINATION-DATE",
  "table": "EMPLOYEE",
  "column": "TERMINATION_DATE_0415",
  "date_part": "DAY",
  "substring_start": 9,
  "substring_length": 2
},
"BIRTH_YEAR_0415": {
  "host": "HV-EMPLOYEE-BIRTH-DATE",
  "table": "EMPLOYEE",
  "column": "BIRTH_DATE_0415",
  "date_part": "YEAR",
  "substring_start": 3,
  "substring_length": 2
},
"BIRTH_MONTH_0415": {
  "host": "HV-EMPLOYEE-BIRTH-DATE",
  "table": "EMPLOYEE",
  "column": "BIRTH_DATE_0415",
  "date_part": "MONTH",
  "substring_start": 6,
  "substring_length": 2
},
"BIRTH_DAY_0415": {
  "host": "HV-EMPLOYEE-BIRTH-DATE",
  "table": "EMPLOYEE",
  "column": "BIRTH_DATE_0415",
  "date_part": "DAY",
  "substring_start": 9,
  "substring_length": 2
},
"START_YEAR_0420": {
  "host": "HV-EMPOSITION-START-DATE",
  "table": "EMPOSITION",
  "column": "START_DATE_0420",
  "date_part": "YEAR",
  "substring_start": 3,
  "substring_length": 2
},
"START_MONTH_0420": {
  "host": "HV-EMPOSITION-START-DATE",
  "table": "EMPOSITION",
  "column": "START_DATE_0420",
  "date_part": "MONTH",
  "substring_start": 6,
  "substring_length": 2
},
"START_DAY_0420": {
  "host": "HV-EMPOSITION-START-DATE",
  "table": "EMPOSITION",
  "column": "START_DATE_0420",

```

```

    "date_part": "DAY",
    "substring_start": 9,
    "substring_length": 2
  },
  "FINISH_YEAR_0420": {
    "host": "HV-EMPOSITION-FINISH-DATE",
    "table": "EMPOSITION",
    "column": "FINISH_DATE_0420",
    "date_part": "YEAR",
    "substring_start": 3,
    "substring_length": 2
  },
  "FINISH_MONTH_0420": {
    "host": "HV-EMPOSITION-FINISH-DATE",
    "table": "EMPOSITION",
    "column": "FINISH_DATE_0420",
    "date_part": "MONTH",
    "substring_start": 6,
    "substring_length": 2
  },
  "FINISH_DAY_0420": {
    "host": "HV-EMPOSITION-FINISH-DATE",
    "table": "EMPOSITION",
    "column": "FINISH_DATE_0420",
    "date_part": "DAY",
    "substring_start": 9,
    "substring_length": 2
  },
  "EXPERTISE_YEAR_0425": {
    "host": "HV-EXPERTISE-EXPERTISE-DATE",
    "table": "EXPERTISE",
    "column": "EXPERTISE_DATE_0425",
    "date_part": "YEAR",
    "substring_start": 3,
    "substring_length": 2
  },
  "EXPERTISE_MONTH_0425": {
    "host": "HV-EXPERTISE-EXPERTISE-DATE",
    "table": "EXPERTISE",
    "column": "EXPERTISE_DATE_0425",
    "date_part": "MONTH",
    "substring_start": 6,
    "substring_length": 2
  },
  "EXPERTISE_DAY_0425": {
    "host": "HV-EXPERTISE-EXPERTISE-DATE",
    "table": "EXPERTISE",
    "column": "EXPERTISE_DATE_0425",
    "date_part": "DAY",
    "substring_start": 9,
    "substring_length": 2
  },
  "CLAIM_YEAR_0430": {
    "host": "HV-HOSPITAL-CLAIM-CLAIM-DATE",
    "table": "HOSPITAL_CLAIM",
    "column": "CLAIM_DATE_0430",
    "date_part": "YEAR",
    "substring_start": 3,
    "substring_length": 2
  },
  "CLAIM_MONTH_0430": {
    "host": "HV-HOSPITAL-CLAIM-CLAIM-DATE",
    "table": "HOSPITAL_CLAIM",
    "column": "CLAIM_DATE_0430",
    "date_part": "MONTH",
    "substring_start": 6,
    "substring_length": 2
  },
  "CLAIM_DAY_0430": {
    "host": "HV-HOSPITAL-CLAIM-CLAIM-DATE",
    "table": "HOSPITAL_CLAIM",
    "column": "CLAIM_DATE_0430",
    "date_part": "DAY",
    "substring_start": 9,
    "substring_length": 2
  },

```

```

"PATIENT_BIRTH_YEAR_0430": {
  "host": "HV-HOSPITAL-CLAIM-PATIENT-BIRTH-DATE",
  "table": "HOSPITAL_CLAIM",
  "column": "PATIENT_BIRTH_DATE_0430",
  "date_part": "YEAR",
  "substring_start": 3,
  "substring_length": 2
},
"PATIENT_BIRTH_MONTH_0430": {
  "host": "HV-HOSPITAL-CLAIM-PATIENT-BIRTH-DATE",
  "table": "HOSPITAL_CLAIM",
  "column": "PATIENT_BIRTH_DATE_0430",
  "date_part": "MONTH",
  "substring_start": 6,
  "substring_length": 2
},
"PATIENT_BIRTH_DAY_0430": {
  "host": "HV-HOSPITAL-CLAIM-PATIENT-BIRTH-DATE",
  "table": "HOSPITAL_CLAIM",
  "column": "PATIENT_BIRTH_DATE_0430",
  "date_part": "DAY",
  "substring_start": 9,
  "substring_length": 2
},
"ADMIT_YEAR_0430": {
  "host": "HV-HOSPITAL-CLAIM-ADMIT-DATE",
  "table": "HOSPITAL_CLAIM",
  "column": "ADMIT_DATE_0430",
  "date_part": "YEAR",
  "substring_start": 3,
  "substring_length": 2
},
"ADMIT_MONTH_0430": {
  "host": "HV-HOSPITAL-CLAIM-ADMIT-DATE",
  "table": "HOSPITAL_CLAIM",
  "column": "ADMIT_DATE_0430",
  "date_part": "MONTH",
  "substring_start": 6,
  "substring_length": 2
},
"ADMIT_DAY_0430": {
  "host": "HV-HOSPITAL-CLAIM-ADMIT-DATE",
  "table": "HOSPITAL_CLAIM",
  "column": "ADMIT_DATE_0430",
  "date_part": "DAY",
  "substring_start": 9,
  "substring_length": 2
},
"DISCHARGE_YEAR_0430": {
  "host": "HV-HOSPITAL-CLAIM-DISCHARGE-DATE",
  "table": "HOSPITAL_CLAIM",
  "column": "DISCHARGE_DATE_0430",
  "date_part": "YEAR",
  "substring_start": 3,
  "substring_length": 2
},
"DISCHARGE_MONTH_0430": {
  "host": "HV-HOSPITAL-CLAIM-DISCHARGE-DATE",
  "table": "HOSPITAL_CLAIM",
  "column": "DISCHARGE_DATE_0430",
  "date_part": "MONTH",
  "substring_start": 6,
  "substring_length": 2
},
"DISCHARGE_DAY_0430": {
  "host": "HV-HOSPITAL-CLAIM-DISCHARGE-DATE",
  "table": "HOSPITAL_CLAIM",
  "column": "DISCHARGE_DATE_0430",
  "date_part": "DAY",
  "substring_start": 9,
  "substring_length": 2
},
"CLAIM_YEAR_0445": {
  "host": "HV-NON-HOSP-CLAIM-CLAIM-DATE",
  "table": "NON_HOSP_CLAIM",
  "column": "CLAIM_DATE_0445",

```

```

    "date_part": "YEAR",
    "substring_start": 3,
    "substring_length": 2
  },
  "CLAIM_MONTH_0445": {
    "host": "HV-NON-HOSP-CLAIM-CLAIM-DATE",
    "table": "NON_HOSP_CLAIM",
    "column": "CLAIM_DATE_0445",
    "date_part": "MONTH",
    "substring_start": 6,
    "substring_length": 2
  },
  "CLAIM_DAY_0445": {
    "host": "HV-NON-HOSP-CLAIM-CLAIM-DATE",
    "table": "NON_HOSP_CLAIM",
    "column": "CLAIM_DATE_0445",
    "date_part": "DAY",
    "substring_start": 9,
    "substring_length": 2
  },
  "PATIENT_BIRTH_YEAR_0445": {
    "host": "HV-NON-HOSP-CLAIM-PATIENT-BIRTH-DATE",
    "table": "NON_HOSP_CLAIM",
    "column": "PATIENT_BIRTH_DATE_0445",
    "date_part": "YEAR",
    "substring_start": 3,
    "substring_length": 2
  },
  "PATIENT_BIRTH_MONTH_0445": {
    "host": "HV-NON-HOSP-CLAIM-PATIENT-BIRTH-DATE",
    "table": "NON_HOSP_CLAIM",
    "column": "PATIENT_BIRTH_DATE_0445",
    "date_part": "MONTH",
    "substring_start": 6,
    "substring_length": 2
  },
  "PATIENT_BIRTH_DAY_0445": {
    "host": "HV-NON-HOSP-CLAIM-PATIENT-BIRTH-DATE",
    "table": "NON_HOSP_CLAIM",
    "column": "PATIENT_BIRTH_DATE_0445",
    "date_part": "DAY",
    "substring_start": 9,
    "substring_length": 2
  },
  "SERVICE_YEAR_0445": {
    "host": "HV-NON-HOSP-CLAIM-SERVICE-DATE",
    "table": "NON_HOSP_CLAIM",
    "column": "SERVICE_DATE_0445",
    "date_part": "YEAR",
    "substring_start": 3,
    "substring_length": 2
  },
  "SERVICE_MONTH_0445": {
    "host": "HV-NON-HOSP-CLAIM-SERVICE-DATE",
    "table": "NON_HOSP_CLAIM",
    "column": "SERVICE_DATE_0445",
    "date_part": "MONTH",
    "substring_start": 6,
    "substring_length": 2
  },
  "SERVICE_DAY_0445": {
    "host": "HV-NON-HOSP-CLAIM-SERVICE-DATE",
    "table": "NON_HOSP_CLAIM",
    "column": "SERVICE_DATE_0445",
    "date_part": "DAY",
    "substring_start": 9,
    "substring_length": 2
  },
  "STRUCTURE_YEAR_0460": {
    "host": "HV-STRUCTURE-STRUCTURE-DATE",
    "table": "STRUCTURE",
    "column": "STRUCTURE_DATE_0460",
    "date_part": "YEAR",
    "substring_start": 3,
    "substring_length": 2
  },

```

```

"STRUCTURE_MONTH_0460": {
  "host": "HV-STRUCTURE-STRUCTURE-DATE",
  "table": "STRUCTURE",
  "column": "STRUCTURE_DATE_0460",
  "date_part": "MONTH",
  "substring_start": 6,
  "substring_length": 2
},
"STRUCTURE_DAY_0460": {
  "host": "HV-STRUCTURE-STRUCTURE-DATE",
  "table": "STRUCTURE",
  "column": "STRUCTURE_DATE_0460",
  "date_part": "DAY",
  "substring_start": 9,
  "substring_length": 2
}
},
"output_semantics": {
  "generated_by": "idms-db2-modernizer-phase1",
  "usage": "IDMS retrieval COBOL to DB2 embedded SQL conversion",
  "physical_types_source": "DB2_DDL",
  "logical_mapping_source": "PHASE1_CANONICAL_METADATA"
},
"paragraph_operation_graph": {},
"validation_messages": []
}

```

```

=====
FILE: installed.txt
ENCODING: utf-8
=====

```

```

aistudio-sdk==0.3.8
altair==6.2.1
annotated-doc==0.0.4
annotated-types==0.7.0
anyio==4.14.0
ast-serialize==0.5.0
astor==0.8.1
attrs==26.1.0
bce-python-sdk==0.9.72
blinker==1.9.0
cachetools==7.1.4
certifi==2026.6.17
cffi==2.0.0
cfgv==3.5.0
chardet==7.4.3
charset-normalizer==3.4.7
click==8.4.1
colorama==0.4.6
colorlog==6.10.1
coverage==7.14.1
crc32c==2.8
cryptography==49.0.0
decorator==5.3.1
distlib==0.4.3
easyocr==1.7.2
et-xmlfile==2.0.0
filelock==3.29.4
fsspec==2026.6.0
future==1.0.0
gitdb==4.0.12
gitpython==3.1.50
graphviz==0.21
h11==0.16.0
hf-xet==1.5.1
httpcore==1.0.9
httptools==0.8.0
httpx==0.28.1
huggingface-hub==1.19.0
identify==2.6.19
idna==3.18
imageio==2.37.3
imagesize==2.0.0
iniconfig==2.3.0

```

itsdangerous==2.2.0
jinja2==3.1.6
jsonschema==4.26.0
jsonschema-specifications==2025.9.1
lazy-loader==0.5
librt==0.11.0
markdown-it-py==4.2.0
markupsafe==3.0.3
mdurl==0.1.2
modelscope==1.37.1
mpmath==1.3.0
mypy==2.1.0
mypy-extensions==1.1.0
narwhals==2.22.1
networkx==3.6.1
ninja==1.13.0
nodeenv==1.10.0
numpy==2.4.6
opencv-contrib-python==4.10.0.84
opencv-python==4.13.0.92
opencv-python-headless==4.13.0.92
openpyxl==3.1.5
opt-einsum==3.3.0
packaging==26.2
paddleocr==3.4.1
paddlepaddle==3.0.0
paddlex==3.4.3
pandas==3.0.3
pathspec==1.1.1
pdfminer-six==20260107
pdfplumber==0.11.10
pillow==12.2.0
platformdirs==4.10.0
pluggy==1.6.0
pre-commit==4.6.0
prettytable==3.17.0
protobuf==7.35.1
psutil==7.2.2
py-cpuinfo==9.0.0
pyarrow==24.0.0
pyclipper==1.4.0
pycparser==3.0
pycryptodome==3.23.0
pydantic==2.13.4
pydantic-core==2.46.4
pydantic-settings==2.14.1
pydeck==0.9.2
pygments==2.20.0
pymupdf==1.27.2.3
pypdfium2==5.10.1
pytest==9.1.0
pytest-cov==7.1.0
pytest-mock==3.15.1
python-bidi==0.6.10
python-dateutil==2.9.0.post0
python-discovery==1.4.2
python-dotenv==1.2.2
python-multipart==0.0.32
pyyaml==6.0.2
referencing==0.37.0
reportlab==4.5.1
requests==2.34.2
rich==15.0.0
rpds-py==2026.5.1
ruamel-yaml==0.19.1
ruff==0.15.17
safetensors==0.8.0
scikit-image==0.26.0
scipy==1.17.1
setuptools==81.0.0
shapely==2.1.2
shellingham==1.5.4
six==1.17.0
smmap==5.0.3
starlette==1.3.1
streamlit==1.58.0

```

structlog==26.1.0
sympy==1.14.0
tenacity==9.1.4
tiffiff==2026.6.1
toml==0.10.2
torch==2.12.1
torchvision==0.27.1
tqdm==4.68.3
typer==0.25.1
typing-extensions==4.15.0
typing-inspection==0.4.2
tzdata==2026.2
ujson==5.13.0
urllib3==2.7.0
uvicorn==0.49.0
virtualenv==21.5.1
watchdog==6.0.0
wcwidth==0.8.1
websockets==16.0

```

```

=====
FILE: main.py
ENCODING: utf-8
=====

```

```

from idms_modernizer.services.metadata_service import (
    MetadataService
)

from idms_modernizer.services.validation_service import (
    ValidationService
)

from idms_modernizer.ui.metadata_page import (
    render_metadata
)

from idms_modernizer.ui.upload_page import (
    render_upload_page
)

metadata_service = MetadataService()

validator = ValidationService()

pdf_path = render_upload_page()

if pdf_path:
    metadata = (
        metadata_service.build_metadata(
            pdf_path
        )
    )

    validator.validate_metadata(
        metadata
    )

    render_metadata(
        metadata
    )

```

```

=====
FILE: pyproject.toml
ENCODING: utf-8
=====

```

```

[project]
name = "idms-db2-modernizer"
version = "0.1.0"
description = "Add your description here"
readme = "README.md"
requires-python = ">=3.12"

```

```

dependencies = [
    "graphviz>=0.21",
    "networkx>=3.6.1",
    "pdfplumber>=0.11.10",
    "pydantic>=2.13.4",
    "pydantic-settings>=2.14.1",
    "streamlit>=1.58.0",
]

[tool.setuptools]
package-dir = {"" = "src"}

[tool.setuptools.packages.find]
where = ["src"]

[dependency-groups]
dev = [
    "pytest>=9.1.0",
    "pdfminer.six>=20250506",
]

=====
FILE: readme
ENCODING: utf-8
=====

set PYTHONPATH=src
python -m streamlit run src\idms_modernizer\app.py --server.port 8502

.venv\Scripts\Activate
python -m streamlit run app\streamlit_app.py

python src\tools\audit_hardcoding.py

python -m streamlit run app\streamlit_app.py --server.port 8502

streamlit run src\idms_modernizer\ui\schema_listing_only_app.py

taskkill /F /IM python.exe
--

=====
FILE: README.md
ENCODING: utf-8
=====

[Empty file]

=====
FILE: src\idms_db2_converter\__init__.py
ENCODING: utf-8
=====

[Empty file]

=====
FILE: src\idms_db2_converter\exceptions.py
ENCODING: utf-8
=====

class ConversionError(Exception):
    """Raised when IDMS to DB2 conversion fails."""

```



```
=====
FILE: src\idms_db2_converter\generators\__init__.py
ENCODING: utf-8
=====
```

[Empty file]

```
=====
FILE: src\idms_db2_converter\generators\cobol_builder.py
ENCODING: utf-8
=====
```

```
from __future__ import annotations

from dataclasses import dataclass, field
from typing import Protocol
```

```
class CobolNode(Protocol):
```

```
    def render(
        self,
        indent: int = 7,
        final: bool = False
    ) -> list[str]:
        ...
```

```
def pad(
    indent: int
) -> str:

    return " " * indent
```

```
def ensure_period(
    value: str
) -> str:

    value = value.rstrip()

    if value.endswith("."):
        return value

    return value + "."
```

```
@dataclass
class PreRenderedBlock:
```

```
    lines: list[str]

    def render(
        self,
        indent: int = 7,
        final: bool = False
    ) -> list[str]:

        result = list(
            self.lines
        )

        if final and result:
            result[-1] = ensure_period(
                result[-1]
            )

        return result
```

```
@dataclass
class RawLines:
```

```
    lines: list[str]
```

```

def render(
    self,
    indent: int = 7,
    final: bool = False
) -> list[str]:

    result: list[str] = []

    for line in self.lines:
        if line.strip():
            result.append(
                pad(indent) + line.strip()
            )
        else:
            result.append("")

    if final and result:
        result[-1] = ensure_period(
            result[-1]
        )

    return result

```

```

@dataclass
class Move:

    source: str
    target: str

    def render(
        self,
        indent: int = 7,
        final: bool = False
    ) -> list[str]:

        return [
            f"{pad(indent)}MOVE {self.source} TO {self.target}."
        ]

```

```

@dataclass
class Perform:

    paragraph: str

    def render(
        self,
        indent: int = 7,
        final: bool = False
    ) -> list[str]:

        return [
            f"{pad(indent)}PERFORM {self.paragraph}."
        ]

```

```

@dataclass
class Continue:

    def render(
        self,
        indent: int = 7,
        final: bool = False
    ) -> list[str]:

        return [
            f"{pad(indent)}CONTINUE."
        ]

```

```

@dataclass
class ReadAtEndMove:

    file_name: str
    source: str

```

```

target: str

def render(
    self,
    indent: int = 7,
    final: bool = False
) -> list[str]:

    source = self.source

    if (
        len(source) == 1
        and not source.startswith('"')
        and not source.endswith('"')
    ):
        source = f"'{source}'"

    return [
        f"{pad(indent)}READ {self.file_name} AT END MOVE {source} TO {self.target}."
    ]

```

```

@dataclass
class Write:

    record: str
    source: str | None = None

    def render(
        self,
        indent: int = 7,
        final: bool = False
    ) -> list[str]:

        if self.source:
            return [
                f"{pad(indent)}WRITE {self.record} FROM {self.source}."
            ]

        return [
            f"{pad(indent)}WRITE {self.record}."
        ]

```

```

@dataclass
class ExecSql:

    sql: str

    def render(
        self,
        indent: int = 7,
        final: bool = False
    ) -> list[str]:

        normalized_lines = self._normalize_sql_lines(
            self.sql
        )

        result: list[str] = []

        for line in normalized_lines:
            if line.strip():
                result.append(
                    pad(indent) + line.rstrip()
                )
            else:
                result.append("")

        if final and result:
            result[-1] = ensure_period(
                result[-1]
            )

        return result

```

```

def _normalize_sql_lines(
    self,
    sql: str
) -> list[str]:

    raw_lines = sql.splitlines()

    stripped_lines = [
        line.rstrip()
        for line in raw_lines
        if line.strip()
    ]

    if not stripped_lines:
        return []

    min_indent = min(
        len(line) - len(line.lstrip(" "))
        for line in stripped_lines
    )

    normalized: list[str] = []

    for line in raw_lines:
        if line.strip():
            normalized.append(
                line[min_indent:].rstrip()
            )
        else:
            normalized.append("")

    return normalized

```

```

@dataclass
class IfBlock:

    condition: str
    then_body: list[CobolNode] = field(
        default_factory=list
    )
    else_body: list[CobolNode] = field(
        default_factory=list
    )

    def render(
        self,
        indent: int = 7,
        final: bool = False
    ) -> list[str]:

        result: list[str] = [
            f"{pad(indent)}IF {self.condition}"
        ]

        result.extend(
            render_nodes(
                self.then_body,
                indent + 3
            )
        )

        if self.else_body:
            result.append(
                f"{pad(indent)}ELSE"
            )

            result.extend(
                render_nodes(
                    self.else_body,
                    indent + 3
                )
            )

        terminator = "END-IF."

```

```

        if not final:
            terminator = "END-IF"

        result.append(
            f"{pad(indent)}{terminator}"
        )

        return result

def with_prefix(
    self,
    prefix: CobolNode
) -> PrefixedBlock:

    return PrefixedBlock(
        prefix=prefix,
        block=self
    )

```

```

@dataclass
class PrefixedBlock:

    prefix: CobolNode
    block: CobolNode

    def render(
        self,
        indent: int = 7,
        final: bool = False
    ) -> list[str]:

        result: list[str] = []

        result.extend(
            self.prefix.render(
                indent=indent
            )
        )

        result.append("")

        result.extend(
            self.block.render(
                indent=indent,
                final=final
            )
        )

        return result

```

```

@dataclass
class PerformUntil:

    condition: str
    body: list[CobolNode] = field(
        default_factory=list
    )

    def render(
        self,
        indent: int = 7,
        final: bool = False
    ) -> list[str]:

        result: list[str] = [
            f"{pad(indent)}PERFORM UNTIL {self.condition}"
        ]

        result.extend(
            render_nodes(
                self.body,
                indent + 3
            )
        )

        return result

```

```

        terminator = "END-PERFORM."

    if not final:
        terminator = "END-PERFORM"

    result.append(
        f"{pad(indent)}{terminator}"
    )

    return result

```

```

@dataclass
class Paragraph:

    name: str
    body: list[CobolNode] = field(
        default_factory=list
    )

    def render(
        self,
        indent: int = 7,
        final: bool = False
    ) -> list[str]:

        result: list[str] = [
            f"{self.name}."
        ]

        if self.body:
            result.extend(
                render_nodes(
                    self.body,
                    indent,
                    terminate_last=True
                )
            )

        return result

```

```

def render_nodes(
    nodes: list[CobolNode],
    indent: int = 7,
    terminate_last: bool = False
) -> list[str]:

    result: list[str] = []

    for index, node in enumerate(nodes):
        is_last = (
            terminate_last
            and index == len(nodes) - 1
        )

        result.extend(
            node.render(
                indent=indent,
                final=is_last
            )
        )

    return result

```

```

def render_paragraph(
    name: str,
    nodes: list[CobolNode]
) -> str:

    paragraph = Paragraph(
        name=name,
        body=nodes
    )

```

```

return "\n".join(
    paragraph.render()
)

```

```

=====
FILE: src\idms_db2_converter\generators\cursors.py
ENCODING: utf-8
=====

```

```

from idms_db2_converter.exceptions import ConversionError
from idms_db2_converter.generators.formatting import comma_block
from idms_db2_converter.generators.naming import Naming
from idms_db2_converter.models import SchemaModel

```

```

class CursorGenerator:

```

```

    """
    Generates DECLARE CURSOR statements for IDMS set navigation.

```

```

    This version selects all child columns from the final schema so the fetch
    paragraph can populate all host variables needed later by field rewriting.
    """

```

```

def generate(
    self,
    schema: SchemaModel,
    used_sets: list[str]
) -> str:

```

```

    print("USING CURSOR_GENERATOR VERSION ALL-COLUMNS-2026-07-01")

```

```

    blocks: list[str] = []
    seen: set[str] = set()

```

```

    for set_name in used_sets:
        set_name = set_name.upper()

```

```

        if set_name in seen:
            continue

```

```

        seen.add(set_name)

```

```

        relationship = schema.relationships.get(set_name)

```

```

        if not relationship:
            raise ConversionError(
                f"Set {set_name} missing from schema relationships."
            )

```

```

        if not relationship.parent_key or not relationship.child_fk:
            raise ConversionError(
                f"Set {set_name} missing parent_key or child_fk."
            )

```

```

        child_record = schema.records.get(
            self._physical_record_name(
                schema,
                relationship.child_record
            )
        )

```

```

        if not child_record:
            raise ConversionError(
                f"Child record {relationship.child_record} missing."
            )

```

```

        columns = list(child_record.fields.keys())

```

```

        parent_host = Naming.hv(
            relationship.parent_record,
            relationship.parent_key
        )

```

```

        lines = [

```

```

        "            EXEC SQL",
        f"            DECLARE {Naming.cursor(set_name)} CURSOR FOR"
    ]

    lines.extend(
        comma_block(
            items=columns,
            first_prefix="        SELECT ",
            next_prefix="        "
        )
    )

    lines.append(
        f"            FROM {self._table_name(schema, relationship.child_record)}"
    )

    lines.append(
        f"            WHERE {relationship.child_fk} = :{parent_host}"
    )

    if relationship.order_by:
        lines.append(
            f"            ORDER BY {' ', ' '.join(relationship.order_by)}"
        )

    lines.append(
        "        END-EXEC."
    )

    blocks.append(
        "\n".join(lines)
    )

    return "\n\n".join(blocks)

def _table_name(
    self,
    schema: SchemaModel,
    record_name: str
) -> str:

    mapped = schema.record_table_map.get(
        record_name
    )

    if mapped:
        return mapped

    normalized = record_name.replace(
        "-",
        "_",
    ).upper()

    mapped = schema.record_table_map.get(
        normalized
    )

    if mapped:
        return mapped

    return normalized

def _physical_record_name(
    self,
    schema: SchemaModel,
    logical_record_name: str
) -> str:

    logical_record_name = logical_record_name.upper()

    mapped = schema.record_table_map.get(
        logical_record_name
    )

    if mapped and mapped in schema.records:
        return mapped

```



```

normalized = logical_record_name.replace(
    "-",
    " "
)

mapped = schema.record_table_map.get(
    normalized
)

if mapped and mapped in schema.records:
    return mapped

if logical_record_name in schema.records:
    return logical_record_name

if normalized in schema.records:
    return normalized

return logical_record_name

```

```

=====
FILE: src\idms_db2_converter\generators\fetch_paragraphs.py
ENCODING: utf-8
=====

```

```

from idms_db2_converter.generators.naming import Naming
from idms_db2_converter.models import SchemaModel

```

```

class FetchParagraphGenerator:
    """
    Generates complete FETCH paragraphs for cursor-based IDMS set walking.

    Guarantees:
    - FETCH statement has END-EXEC.
    - SQLCODE handling is emitted after FETCH.
    - INTO list matches every selected column in the cursor.
    """

    def __init__(
        self,
        schema: SchemaModel
    ):
        self.schema = schema

    def paragraph_name(
        self,
        set_name: str
    ) -> str:

        return f"FETCH-{set_name}".upper()

    def generate(
        self,
        used_sets: list[str]
    ) -> str:

        print(
            "USING FETCH_PARAGRAPH_GENERATOR VERSION COMPLETE-SQLCODE-2026-07-01"
        )

        paragraphs: list[str] = []
        seen: set[str] = set()

        for set_name in used_sets:
            set_name = set_name.upper()

            if set_name in seen:
                continue

            seen.add(set_name)

            if set_name not in self.schema.relationships:
                continue

```

```

        paragraph = self._generate_one(
            set_name
        )

        if paragraph.strip():
            paragraphs.append(
                paragraph
            )

    return "\n\n".join(
        paragraphs
    )

def _generate_one(
    self,
    set_name: str
) -> str:

    relationship = self.schema.relationships[
        set_name
    ]

    child_record_name = self._physical_record_name(
        relationship.child_record
    )

    child_record = self.schema.records.get(
        child_record_name
    )

    if child_record is None:
        return ""

    into_items: list[str] = []

    for column_name, column in child_record.fields.items():
        host = (
            f":{Naming.hv(relationship.child_record, column_name)}"
        )

        if column.nullable:
            host += (
                f" :{Naming.ni(relationship.child_record, column_name)}"
            )

        into_items.append(
            host
        )

    lines: list[str] = [
        f"{self.paragraph_name(set_name)}.",
        "    EXEC SQL",
        f"        FETCH {Naming.cursor(set_name)}"
    ]

    for index, item in enumerate(into_items):
        suffix = "," if index < len(into_items) - 1 else ""

        if index == 0:
            lines.append(
                f"            INTO {item}{suffix}"
            )
        else:
            lines.append(
                f"                {item}{suffix}"
            )

    lines.extend(
        [
            "        END-EXEC.",
            "",
            "        IF SQLCODE NOT = 0 AND SQLCODE NOT = 100",
            "            PERFORM SQL-ERROR",
            "        END-IF."
        ]
    )

```

```

    )

    return "\n".join(
        lines
    )

def _physical_record_name(
    self,
    logical_record_name: str
) -> str:

    logical_record_name = logical_record_name.upper()

    mapped = self.schema.record_table_map.get(
        logical_record_name
    )

    if mapped and mapped in self.schema.records:
        return mapped

    normalized = logical_record_name.replace(
        "-",
        " "
    )

    mapped = self.schema.record_table_map.get(
        normalized
    )

    if mapped and mapped in self.schema.records:
        return mapped

    if logical_record_name in self.schema.records:
        return logical_record_name

    if normalized in self.schema.records:
        return normalized

    return logical_record_name

```

```

=====
FILE: src\idms_db2_converter\generators\formatting.py
ENCODING: utf-8
=====

```

```

def comma_block(
    items: list[str],
    first_prefix: str = "",
    next_prefix: str = "",
) -> list[str]:
    """
    Format a list of SQL items as comma-separated lines.

    Example:
        comma_block(
            items=["EMP_ID", "EMP_NAME", "DEPT_ID"],
            first_prefix="SELECT ",
            next_prefix="      "
        )

    Returns:
        [
            "SELECT EMP_ID,",
            "      EMP_NAME,",
            "      DEPT_ID"
        ]
    """

    if not items:
        return []

    lines: list[str] = []

    for index, item in enumerate(items):
        prefix = first_prefix if index == 0 else next_prefix

```

```

        suffix = "," if index < len(items) - 1 else ""

        lines.append(
            f"{prefix}{item}{suffix}"
        )

    return lines

```

```

=====
FILE: src\idms_db2_converter\generators\host_variables.py
ENCODING: utf-8
=====

```

```

from idms_db2_converter.generators.naming import Naming
from idms_db2_converter.models import SchemaModel

```

```

class HostVariableGenerator:

```

```

    """
    Generates COBOL host variables for DB2 embedded SQL.

```

```

    Rules:

```

- Generates SQLCA.
- Generates BEGIN DECLARE SECTION and END DECLARE SECTION.
- Generates all columns for each used record.
- Uses Naming.normalize for group names and field names.
- Converts underscores to hyphens for COBOL data names.
- Generates null indicators for nullable columns.

```

    """

```

```

    def generate(
        self,
        schema: SchemaModel,
        used_records: list[str],
    ) -> str:
        lines: list[str] = [
            "      EXEC SQL",
            "          INCLUDE SQLCA",
            "      END-EXEC.",
            "      EXEC SQL",
            "          BEGIN DECLARE SECTION",
            "      END-EXEC.",
            "",
        ]

        null_indicators: list[str] = []
        emitted_null_indicators: set[str] = set()

        physical_records = self.resolve_used_records(
            schema=schema,
            used_records=used_records,
        )

        for logical_record_name, physical_record_name in physical_records:
            if physical_record_name not in schema.records:
                continue

            record = schema.records[physical_record_name]
            logical_group_name = Naming.normalize(
                logical_record_name,
            )

            lines.append(
                f"      01 HV-{logical_group_name}."
            )

            for column_name, column in record.fields.items():
                host_variable = Naming.hv(
                    logical_record_name,
                    column_name,
                )

                lines.extend(
                    self.column_to_cobol(

```

```

        hv=host_variable,
        datatype=column.datatype,
        length=column.length,
        scale=column.scale,
    )
)

if column.nullable:
    null_indicator = Naming.ni(
        logical_record_name,
        column_name,
    )

    if null_indicator not in emitted_null_indicators:
        emitted_null_indicators.add(
            null_indicator,
        )

        null_indicators.append(
            f"      01 {null_indicator:<45} PIC S9(4) COMP."
        )

    lines.append(
        "",
    )

if null_indicators:
    lines.extend(
        null_indicators,
    )

lines.extend(
    [
        "      EXEC SQL",
        "      END DECLARE SECTION",
        "      END-EXEC.",
    ]
)

return "\n".join(lines)

def resolve_used_records(
    self,
    schema: SchemaModel,
    used_records: list[str],
) -> list[tuple[str, str]]:
    result: list[tuple[str, str]] = []
    seen: set[tuple[str, str]] = set()

    for logical_record_name in used_records:
        if not logical_record_name:
            continue

        physical_record_name = self.physical_record_name(
            schema=schema,
            logical_record_name=logical_record_name,
        )

        key = (
            logical_record_name.upper(),
            physical_record_name.upper(),
        )

        if key in seen:
            continue

        seen.add(
            key,
        )

        result.append(
            (
                logical_record_name.upper(),
                physical_record_name,
            )
        )

```

```

    return result

def physical_record_name(
    self,
    schema: SchemaModel,
    logical_record_name: str,
) -> str:
    logical_record_name = logical_record_name.upper()

    mapped = schema.record_table_map.get(
        logical_record_name,
    )

    if mapped and mapped in schema.records:
        return mapped

    normalized = logical_record_name.replace(
        "-",
        "_",
    )

    mapped = schema.record_table_map.get(
        normalized,
    )

    if mapped and mapped in schema.records:
        return mapped

    if logical_record_name in schema.records:
        return logical_record_name

    if normalized in schema.records:
        return normalized

    hyphen_name = logical_record_name.replace(
        "-",
        "-",
    )

    if hyphen_name in schema.records:
        return hyphen_name

    return logical_record_name

def column_to_cobol(
    self,
    hv: str,
    datatype: str | None,
    length: int | None,
    scale: int | None,
) -> list[str]:
    datatype = (
        datatype
        or "CHAR"
    ).upper()

    if datatype in {
        "CHAR",
        "CHARACTER",
    }:
        return [
            f"          05 {hv:<45} PIC X({length or 1})."
        ]

    if datatype in {
        "VARCHAR",
        "LONG VARCHAR",
    }:
        return [
            f"          05 {hv:<45} PIC X({length or 255})."
        ]

    if datatype in {
        "DATE",
    }:

```

```

        return [
            f"          05 {hv:<45} PIC X(10)."

```

```

        scale
        if scale is not None
        else 0
    )

    integer_digits = max(
        actual_precision - actual_scale,
        1,
    )

    if actual_scale > 0:
        return [
            f"          05 {hv:<45} PIC S9({integer_digits})V9({actual_scale}) COMP-3."
        ]

    return [
        f"          05 {hv:<45} PIC S9({actual_precision}) COMP-3."
    ]

```

```

=====
FILE: src\idms_db2_converter\generators\naming.py
ENCODING: utf-8
=====

```

```
import re
```

```

class Naming:
    @staticmethod
    def normalize(
        value: str | None,
    ) -> str:
        if not value:
            return ""

        normalized = str(value).strip().upper()
        normalized = normalized.replace("_", "-")
        normalized = normalized.replace(" ", "-")
        normalized = re.sub(
            r"^[A-Z0-9-]",
            "-",
            normalized,
        )
        normalized = re.sub(
            r"-+",
            "-",
            normalized,
        )

        return normalized.strip("-")

    @staticmethod
    def hv(
        record: str,
        field: str,
    ) -> str:
        record_name = Naming.normalize(
            record,
        )

        field_name = Naming.normalize(
            field,
        )

        return f"HV-{record_name}-{field_name}"

    @staticmethod
    def ni(
        record: str,
        field: str,
    ) -> str:
        record_name = Naming.normalize(
            record,
        )

```



```

        field_name = Naming.normalize(
            field,
        )

        return f"NI-{record_name}-{field_name}"

    @staticmethod
    def cursor(
        set_name: str,
    ) -> str:
        return f"C-{Naming.normalize(set_name)}"

```

```

=====
FILE: src\idms_db2_converter\generators\sql_snippets.py
ENCODING: utf-8
=====

```

```

from idms_db2_converter.exceptions import ConversionError
from idms_db2_converter.generators.formatting import comma_block
from idms_db2_converter.generators.naming import Naming
from idms_db2_converter.models import SchemaModel

```

```

class SqlSnippets:
    """
    Generates embedded SQL snippets with full SELECT and INTO lists.
    """

    def __init__(
        self,
        schema: SchemaModel
    ):
        self.schema = schema

    def select_for_record_by_pk(
        self,
        record_name: str
    ) -> str:

        physical_record_name = self.physical_record_name(
            record_name
        )

        record = self.schema.records.get(
            physical_record_name
        )

        if not record:
            raise ConversionError(
                f"Record {record_name} missing from schema."
            )

        if not record.primary_key:
            raise ConversionError(
                f"Record {record_name} has no primary key."
            )

        columns = list(record.fields.keys())

        into_items = [
            self.host_with_indicator(
                logical_record_name=record_name,
                column_name=column_name,
                nullable=record.fields[column_name].nullable
            )
            for column_name in columns
        ]

        lines = [
            "EXEC SQL"
        ]

        lines.extend(
            comma_block(
                items=columns,
            )
        )

```

```

        first_prefix="    SELECT ",
        next_prefix="        "
    )
)

lines.extend(
    comma_block(
        items=into_items,
        first_prefix="        INTO ",
        next_prefix="        "
    )
)

lines.append(
    f"    FROM {physical_record_name}"
)

lines.append(
    f"    WHERE {record.primary_key} = :{Naming.hv(record_name, record.primary_key)}"
)

lines.append(
    "END-EXEC."
)

return "\n".join(lines)

def select_first_child_for_set(
    self,
    set_name: str
) -> str:

    set_name = set_name.upper()

    relationship = self.schema.relationships.get(
        set_name
    )

    if not relationship:
        raise ConversionError(
            f"Set {set_name} missing from schema relationships."
        )

    child_record_name = self.physical_record_name(
        relationship.child_record
    )

    child_record = self.schema.records.get(
        child_record_name
    )

    if not child_record:
        raise ConversionError(
            f"Child record {relationship.child_record} missing from schema."
        )

    columns = list(child_record.fields.keys())

    into_items = [
        self.host_with_indicator(
            logical_record_name=relationship.child_record,
            column_name=column_name,
            nullable=child_record.fields[column_name].nullable
        )
        for column_name in columns
    ]

    parent_host = Naming.hv(
        relationship.parent_record,
        relationship.parent_key
    )

    lines = [
        "EXEC SQL"
    ]

```

```

lines.extend(
    comma_block(
        items=columns,
        first_prefix="    SELECT ",
        next_prefix="        "
    )
)

lines.extend(
    comma_block(
        items=into_items,
        first_prefix="    INTO ",
        next_prefix="        "
    )
)

lines.append(
    f"    FROM {child_record_name}"
)

lines.append(
    f"    WHERE {relationship.child_fk} = :{parent_host}"
)

if relationship.order_by:
    lines.append(
        f"    ORDER BY {' ', ' '.join(relationship.order_by)}"
    )

lines.append(
    "    FETCH FIRST 1 ROW ONLY"
)

lines.append(
    "END-EXEC."
)

return "\n".join(lines)

def select_for_owner(
    self,
    set_name: str
) -> str:

    set_name = set_name.upper()

    relationship = self.schema.relationships.get(
        set_name
    )

    if not relationship:
        raise ConversionError(
            f"Set {set_name} missing from schema relationships."
        )

    parent_record_name = self.physical_record_name(
        relationship.parent_record
    )

    parent_record = self.schema.records.get(
        parent_record_name
    )

    if not parent_record:
        raise ConversionError(
            f"Parent record {relationship.parent_record} missing from schema."
        )

    columns = list(parent_record.fields.keys())

    into_items = [
        self.host_with_indicator(
            logical_record_name=relationship.parent_record,
            column_name=column_name,
            nullable=parent_record.fields[column_name].nullable
        )
    ]

```

```

        for column_name in columns
    ]

    child_host = Naming.hv(
        relationship.child_record,
        relationship.child_fk
    )

    lines = [
        "EXEC SQL"
    ]

    lines.extend(
        comma_block(
            items=columns,
            first_prefix="    SELECT ",
            next_prefix="        "
        )
    )

    lines.extend(
        comma_block(
            items=into_items,
            first_prefix="        INTO ",
            next_prefix="            "
        )
    )

    lines.append(
        f"    FROM {parent_record_name}"
    )

    lines.append(
        f"    WHERE {relationship.parent_key} = :{child_host}"
    )

    lines.append(
        "END-EXEC."
    )

    return "\n".join(lines)

def fetch_for_set(
    self,
    set_name: str
) -> str:

    set_name = set_name.upper()

    relationship = self.schema.relationships.get(
        set_name
    )

    if not relationship:
        raise ConversionError(
            f"Set {set_name} missing from schema relationships."
        )

    child_record_name = self.physical_record_name(
        relationship.child_record
    )

    child_record = self.schema.records.get(
        child_record_name
    )

    if not child_record:
        raise ConversionError(
            f"Child record {relationship.child_record} missing from schema."
        )

    into_items = [
        self.host_with_indicator(
            logical_record_name=relationship.child_record,
            column_name=column_name,
            nullable=column.nullable

```

```

        )
        for column_name, column in child_record.fields.items()
    ]

    lines = [
        "EXEC SQL",
        f"      FETCH {Naming.cursor(set_name)}"
    ]

    lines.extend(
        comma_block(
            items=into_items,
            first_prefix="      INTO ",
            next_prefix="      "
        )
    )

    lines.append(
        "END-EXEC."
    )

    return "\n".join(lines)

def nullable_fk_indicator_for_set(
    self,
    set_name: str
) -> str | None:

    relationship = self.schema.relationships.get(
        set_name.upper()
    )

    if not relationship:
        return None

    child_record_name = self.physical_record_name(
        relationship.child_record
    )

    child_record = self.schema.records.get(
        child_record_name
    )

    if not child_record:
        return None

    child_fk = relationship.child_fk

    if not child_fk:
        return None

    column = child_record.fields.get(
        child_fk
    )

    if not column:
        return None

    if not column.nullable:
        return None

    return Naming.ni(
        relationship.child_record,
        child_fk
    )

def physical_record_name(
    self,
    logical_record_name: str
) -> str:

    logical_record_name = logical_record_name.upper()

    mapped = self.schema.record_table_map.get(
        logical_record_name
    )

```

```

        if mapped and mapped in self.schema.records:
            return mapped

        normalized = logical_record_name.replace(
            "-",
            " ",
            "-"
        )

        mapped = self.schema.record_table_map.get(
            normalized
        )

        if mapped and mapped in self.schema.records:
            return mapped

        if logical_record_name in self.schema.records:
            return logical_record_name

        if normalized in self.schema.records:
            return normalized

        return logical_record_name

def host_with_indicator(
    self,
    logical_record_name: str,
    column_name: str,
    nullable: bool
) -> str:

    host = f":{Naming.hv(logical_record_name, column_name)}"

    if nullable:
        host = f"{host} :{Naming.ni(logical_record_name, column_name)}"

    return host

```

```

=====
FILE: src\idms_db2_converter\models.py
ENCODING: utf-8
=====

```

```

from dataclasses import dataclass, field
from typing import Dict, List, Optional

```

```

@dataclass
class Column:
    name: str
    datatype: str
    length: Optional[int] = None
    scale: Optional[int] = None
    nullable: bool = True
    primary_key: bool = False
    generated: bool = False
    source_kind: str = ""

@dataclass
class Record:
    name: str
    primary_key: Optional[str] = None
    fields: Dict[str, Column] = field(default_factory=dict)

    # New composite PK support.
    # Existing code can continue using primary_key.
    primary_keys: List[str] = field(default_factory=list)

    def effective_primary_keys(self) -> List[str]:
        keys: List[str] = []

        if self.primary_keys:
            keys.extend(self.primary_keys)

```

```

        if self.primary_key and self.primary_key not in keys:
            keys.append(self.primary_key)

    return keys

def set_primary_keys(self, keys: List[str]) -> None:
    cleaned: List[str] = []

    for key in keys or []:
        if not key:
            continue

        normalized = str(key).upper()

        if normalized in cleaned:
            continue

        cleaned.append(normalized)

    self.primary_keys = cleaned
    self.primary_key = cleaned[0] if cleaned else None

    for key in cleaned:
        if key in self.fields:
            self.fields[key].primary_key = True
            self.fields[key].nullable = False

@dataclass
class Relationship:
    set_name: str
    parent_record: str
    child_record: str
    cardinality: Optional[str] = None

    # Backward-compatible single key fields.
    parent_key: Optional[str] = None
    child_fk: Optional[str] = None

    # New composite relationship support.
    parent_keys: List[str] = field(default_factory=list)
    child_fks: List[str] = field(default_factory=list)

    order_by: List[str] = field(default_factory=list)

    def effective_parent_keys(self) -> List[str]:
        keys: List[str] = []

        if self.parent_keys:
            keys.extend(self.parent_keys)

        if self.parent_key and self.parent_key not in keys:
            keys.append(self.parent_key)

        return keys

    def effective_child_fks(self) -> List[str]:
        keys: List[str] = []

        if self.child_fks:
            keys.extend(self.child_fks)

        if self.child_fk and self.child_fk not in keys:
            keys.append(self.child_fk)

        return keys

@dataclass
class SchemaModel:
    records: Dict[str, Record] = field(default_factory=dict)
    relationships: Dict[str, Relationship] = field(default_factory=dict)

    field_map: Dict[str, dict] = field(default_factory=dict)
    record_table_map: Dict[str, str] = field(default_factory=dict)
    calc_key_map: Dict[str, dict] = field(default_factory=dict)

```

```

# Existing Phase 2 metadata maps.
set_ordering_map: Dict[str, dict] = field(default_factory=dict)
navigation_intent: Dict[str, dict] = field(default_factory=dict)
nullable_fk_map: Dict[str, dict] = field(default_factory=dict)
date_part_map: Dict[str, dict] = field(default_factory=dict)
output_semantics: Dict[str, dict] = field(default_factory=dict)
paragraph_operation_graph: Dict[str, list] = field(default_factory=dict)
validation_messages: List[str] = field(default_factory=list)

# New key metadata from Phase 1.
table_key_map: Dict[str, dict] = field(default_factory=dict)

schema_source: Optional[str] = None

def has_schema_objects(self) -> bool:
    return bool(self.records or self.relationships)

def is_empty(self) -> bool:
    return not self.has_schema_objects()

def add_validation_message(self, message: str) -> None:
    if not hasattr(self, "validation_messages"):
        self.validation_messages = []

    self.validation_messages.append(message)

@dataclass
class CobolAnalysis:
    program_id: Optional[str] = None

    idms_records: List[str] = field(default_factory=list)
    obtain_calc_records: List[str] = field(default_factory=list)
    obtain_next: List[tuple[str, str]] = field(default_factory=list)
    obtain_owner_sets: List[str] = field(default_factory=list)
    find_first_sets: List[str] = field(default_factory=list)

    store_records: List[str] = field(default_factory=list)
    modify_records: List[str] = field(default_factory=list)
    erase_records: List[str] = field(default_factory=list)
    ready_update_areas: List[str] = field(default_factory=list)

    field_references: List[str] = field(default_factory=list)
    idms_fields: List[str] = field(default_factory=list)

@dataclass
class Paragraph:
    name: str
    text: str

=====
FILE: src\idms_db2_converter\parsers\__init__.py
ENCODING: utf-8
=====

[Empty file]

=====
FILE: src\idms_db2_converter\parsers\canonical_parser.py
ENCODING: utf-8
=====

import json

from idms_db2_converter.exceptions import ConversionError
from idms_db2_converter.models import Column, Record, Relationship, SchemaModel

class CanonicalParser:
    def parse(self, text: str) -> SchemaModel:
        try:
            payload = json.loads(text)

```



```

except json.JSONDecodeError as exc:
    raise ConversionError(f"Invalid canonical JSON: {exc}") from exc

schema = SchemaModel()

self._parse_records(payload, schema)
self._parse_relationships(payload, schema)
self._parse_field_map(payload, schema)

return schema

def _parse_records(self, payload: dict, schema: SchemaModel) -> None:
    for record_json in payload.get("records", []):
        record_name = record_json["name"].upper()
        primary_key = self._upper_or_none(record_json.get("primary_key"))

        fields = {}

        for field_json in record_json.get("fields", []):
            field_name = field_json["name"].upper()

            nullable = field_json.get("nullable")
            if nullable is None:
                nullable = field_name != primary_key

            fields[field_name] = Column(
                name=field_name,
                datatype=field_json["datatype"].upper(),
                length=field_json.get("length"),
                scale=field_json.get("scale"),
                nullable=bool(nullable),
            )

        schema.records[record_name] = Record(
            name=record_name,
            primary_key=primary_key,
            fields=fields,
        )

def _parse_relationships(self, payload: dict, schema: SchemaModel) -> None:
    for rel_json in payload.get("relationships", []):
        set_name = rel_json["set_name"].upper()
        parent_record = rel_json["parent_record"].upper()
        child_record = rel_json["child_record"].upper()

        parent_key = self._upper_or_none(rel_json.get("parent_key"))
        child_fk = self._upper_or_none(rel_json.get("child_fk"))

        if not parent_key:
            parent_key = self._resolve_parent_key(schema, parent_record)

        if not child_fk:
            child_fk = self._resolve_child_fk(
                schema=schema,
                parent_record=parent_record,
                child_record=child_record,
            )

        order_by = [
            value.upper()
            for value in rel_json.get("order_by", [])
        ]

        if not order_by and child_fk:
            order_by = [child_fk]

        schema.relationships[set_name] = Relationship(
            set_name=set_name,
            parent_record=parent_record,
            child_record=child_record,
            cardinality=rel_json.get("cardinality"),
            parent_key=parent_key,
            child_fk=child_fk,
            order_by=order_by,
        )

```

```

def _parse_field_map(self, payload: dict, schema: SchemaModel) -> None:
    schema.field_map = {
        key.upper(): value
        for key, value in payload.get("field_map", {}).items()
    }

def _resolve_parent_key(
    self,
    schema: SchemaModel,
    parent_record: str,
) -> str | None:
    record = schema.records.get(parent_record)

    if not record:
        return None

    return record.primary_key

def _resolve_child_fk(
    self,
    schema: SchemaModel,
    parent_record: str,
    child_record: str,
) -> str | None:
    parent = schema.records.get(parent_record)
    child = schema.records.get(child_record)

    if not parent or not child or not parent.primary_key:
        return None

    if parent.primary_key in child.fields:
        return parent.primary_key

    return None

def _upper_or_none(self, value: str | None) -> str | None:
    return value.upper() if value else None

```

```

=====
FILE: src\idms_db2_converter\parsers\cobol_parser.py
ENCODING: utf-8
=====

```

```
import re
```

```
from idms_db2_converter.models import CobolAnalysis, Paragraph
```

```
class CobolParser:
```

```
    """
```

```
    Parses IDMS COBOL.
```

```
    Captures:
```

- PROGRAM-ID
- COPY IDMS RECORD usage
- OBTAIN CALC record usage
- OBTAIN NEXT record WITHIN set
- OBTAIN OWNER WITHIN set
- FIND FIRST WITHIN set
- STORE record usage
- MODIFY record usage
- ERASE record usage
- READY AREA ... USAGE-MODE IS UPDATE
- Paragraphs
- IDMS schema-suffixed field references in PROCEDURE DIVISION

```
    Important:
```

- This parser does not hard-code record suffix to record-name mappings.
 - Record/field inference should come from schema metadata, not from demo data.
- ```
 """
```

```

 PROGRAM_ID = re.compile(
 r"^\s*PROGRAM-ID\.\s*([A-Z0-9-]+\.\.?)",
 re.IGNORECASE | re.MULTILINE,
)

```

```

COPY_RECORD = re.compile(
 r"^\\s*(?:01\\s+)?COPY\\s+IDMS\\s+RECORD\\s+([A-Z0-9-]+)\\.?.?",
 re.IGNORECASE | re.MULTILINE,
)

OBTAIN_CALC = re.compile(
 r"^\\s*OBTAIN\\s+CALC\\s+([A-Z0-9-]+)\\.?.?\\s*$",
 re.IGNORECASE | re.MULTILINE,
)

OBTAIN_NEXT = re.compile(
 r"^\\s*OBTAIN\\s+NEXT\\s+([A-Z0-9-]+)\\s+WITHIN\\s+([A-Z0-9-]+)\\.?.?\\s*$",
 re.IGNORECASE | re.MULTILINE,
)

OBTAIN_OWNER = re.compile(
 r"^\\s*OBTAIN\\s+OWNER\\s+WITHIN\\s+([A-Z0-9-]+)\\.?.?\\s*$",
 re.IGNORECASE | re.MULTILINE,
)

FIND_FIRST = re.compile(
 r"^\\s*FIND\\s+FIRST\\s+WITHIN\\s+([A-Z0-9-]+)\\.?.?\\s*$",
 re.IGNORECASE | re.MULTILINE,
)

STORE_RECORD = re.compile(
 r"^\\s*STORE\\s+([A-Z0-9-]+)\\.?.?\\s*$",
 re.IGNORECASE | re.MULTILINE,
)

MODIFY_RECORD = re.compile(
 r"^\\s*MODIFY\\s+([A-Z0-9-]+)\\.?.?\\s*$",
 re.IGNORECASE | re.MULTILINE,
)

ERASE_RECORD = re.compile(
 r"^\\s*ERASE\\s+([A-Z0-9-]+)\\.?.?\\s*$",
 re.IGNORECASE | re.MULTILINE,
)

READY_UPDATE_AREA = re.compile(
 r"""
 ^\\s*READY\\s+AREA\\s+([A-Z0-9-]+)\\.?.?\\s*
 (?:\\n\\s*USAGE-MODE\\s+IS\\s+UPDATE\\.?.?\\s*)?
 """,
 re.IGNORECASE | re.MULTILINE | re.VERBOSE,
)

PARAGRAPH_HEADER = re.compile(
 r"^\\s*([A-Z0-9-]+)\\.?.?\\s*$",
 re.IGNORECASE | re.MULTILINE,
)

IDMS_SCHEMA_FIELD = re.compile(
 r"\\b[A-Z][A-Z0-9]*(?:-[A-Z0-9]+)*-\\d{4}\\b",
 re.IGNORECASE,
)

PROCEDURE_DIVISION = re.compile(
 r"^\\s*PROCEDURE\\s+DIVISION\\.?.?\\s*$",
 re.IGNORECASE | re.MULTILINE,
)

def parse(
 self,
 cobol: str,
) -> CobolAnalysis:
 source = self.remove_comment_lines(
 cobol,
)

 program_match = self.PROGRAM_ID.search(
 source,
)

```

```

analysis = CobolAnalysis(
 program_id=self._upper_or_none(
 program_match.group(1)
 if program_match
 else None
),
 idms_records=self._unique(
 self.COPY_RECORD.findall(source),
),
 obtain_calc_records=self._unique(
 self.OBTAIN_CALC.findall(source),
),
 obtain_next=[
 (
 record.upper(),
 set_name.upper(),
)
 for record, set_name in self.OBTAIN_NEXT.findall(source)
],
 obtain_owner_sets=self._unique(
 self.OBTAIN_OWNER.findall(source),
),
 find_first_sets=self._unique(
 self.FIND_FIRST.findall(source),
),
 store_records=self._unique(
 self.STORE_RECORD.findall(source),
),
 modify_records=self._unique(
 self.MODIFY_RECORD.findall(source),
),
 erase_records=self._unique(
 self.ERASE_RECORD.findall(source),
),
 ready_update_areas=self._unique(
 self.READY_UPDATE_AREA.findall(source),
),
)

self._attach_field_references(
 analysis=analysis,
 cobol=source,
)

return analysis

def paragraphs(
 self,
 cobol: str,
) -> list[Paragraph]:
 source = self.remove_comment_lines(
 cobol,
)

 matches = list(
 self.PARAGRAPH_HEADER.finditer(source),
)

 paragraphs: list[Paragraph] = []

 for index, match in enumerate(matches):
 name = match.group(1).upper()
 start = match.start()

 if index + 1 < len(matches):
 end = matches[index + 1].start()
 else:
 end = len(source)

 paragraphs.append(
 Paragraph(
 name=name,
 text=source[start:end],
)
)

```

```

 return paragraphs

def remove_comment_lines(
 self,
 cobol: str,
) -> str:
 lines: list[str] = []

 for line in cobol.splitlines():
 stripped = line.strip()

 if not stripped:
 lines.append(line)
 continue

 if stripped.startswith("*"):
 continue

 lines.append(line)

 return "\n".join(lines)

def _attach_field_references(
 self,
 analysis: CobolAnalysis,
 cobol: str,
) -> None:
 procedure_text = self._procedure_division_text(
 cobol,
)

 field_references = self._unique(
 self.IDMS_SCHEMA_FIELD.findall(
 procedure_text,
)
)

 try:
 analysis.field_references = field_references
 except Exception:
 pass

 try:
 analysis.idms_fields = field_references
 except Exception:
 pass

 record_names = set(
 analysis.idms_records,
)

 for record in analysis.obtain_calc_records:
 record_names.add(
 record,
)

 for record, _ in analysis.obtain_next:
 record_names.add(
 record,
)

 for record in getattr(
 analysis,
 "store_records",
 [],
):
 record_names.add(
 record,
)

 for record in getattr(
 analysis,
 "modify_records",
 [],
):
 record_names.add(

```

```

 record,
)

 for record in getattr(
 analysis,
 "erase_records",
 [],
):
 record_names.add(
 record,
)

 try:
 analysis.idms_records = sorted(
 record_names,
)
 except Exception:
 pass

def _procedure_division_text(
 self,
 cobol: str,
) -> str:
 match = self.PROCEDURE_DIVISION.search(
 cobol,
)

 if not match:
 return cobol

 return cobol[match.start():]

def _unique(
 self,
 values,
) -> list[str]:
 seen = set()
 result: list[str] = []

 for value in values:
 upper_value = value.upper()

 if upper_value not in seen:
 seen.add(
 upper_value,
)

 result.append(
 upper_value,
)

 return result

def _upper_or_none(
 self,
 value: str | None,
) -> str | None:
 return value.upper() if value else None

```

```

=====
FILE: src\idms_db2_converter\parsers\ddl_parser.py
ENCODING: utf-8
=====

```

```

import re

from idms_db2_converter.exceptions import ConversionError
from idms_db2_converter.models import (
 Column,
 Record,
 Relationship,
 SchemaModel
)

```

```

class DDLParser:
 """
 Robust DB2 DDL parser for Phase 2.

 This version uses manual datatype parsing instead of fragile regex-only
 datatype parsing.

 Fixes:
 - VARCHAR(3) being skipped
 - VARCHAR(45) being skipped
 - CHAR(1) being skipped
 - DECIMAL(18,0) being skipped
 - Missing columns in final Phase 2 schema
 """

 DEBUG = True

 INLINE_PRIMARY_KEY = re.compile(
 r"\bPRIMARY\s+KEY\b",
 re.IGNORECASE
)

 INLINE_NOT_NULL = re.compile(
 r"\bNOT\s+NULL\b",
 re.IGNORECASE
)

 TABLE_PRIMARY_KEY = re.compile(
 r"\bPRIMARY\s+KEY\s*$(?P<columns>.*?)$",
 re.IGNORECASE | re.DOTALL
)

 TABLE_FOREIGN_KEY = re.compile(
 r"""
 \bFOREIGN\s+KEY\s*
 $(?P<child_cols>.*?)$
 \s+REFERENCES\s+
 (?P<parent_table>(?:[A-Z0-9_]+\.)?[A-Z0-9_]+)
 \s*
 $(?P<parent_cols>.*?)$
 """,
 re.IGNORECASE | re.DOTALL | re.VERBOSE
)

 ALTER_TABLE_FK = re.compile(
 r"""
 \bALTER\s+TABLE\s+
 (?P<child_table>(?:[A-Z0-9_]+\.)?[A-Z0-9_]+)
 .*?
 \bFOREIGN\s+KEY\s*
 $(?P<child_cols>.*?)$
 \s+REFERENCES\s+
 (?P<parent_table>(?:[A-Z0-9_]+\.)?[A-Z0-9_]+)
 \s*
 $(?P<parent_cols>.*?)$
 """,
 re.IGNORECASE | re.DOTALL | re.VERBOSE
)

 CONSTRAINT_STARTERS = {
 "CONSTRAINT",
 "PRIMARY",
 "FOREIGN",
 "UNIQUE",
 "CHECK"
 }

 def parse(
 self,
 ddl: str
) -> SchemaModel:

 self._debug(
 "USING DDL_PARSER VERSION MANUAL-DATATYPE-2026-07-01"
)

```

```

schema = SchemaModel()
schema.schema_source = "DDL"

if ddl is None:
 ddl = ""

self._debug(
 f"DDL INPUT LENGTH: {len(ddl)}"
)

self._debug(
 f"DDL HAS CREATE TABLE: {'CREATE TABLE' in ddl.upper()}"
)

ddl = self.remove_comments(
 ddl
)

create_statements = self._extract_create_table_statements(
 ddl
)

self._debug(
 f"DDL PARSER CREATE TABLE COUNT: {len(create_statements)}"
)

for statement in create_statements:
 table_name = statement["table_name"]
 body = statement["body"]

 self._debug(
 f"DDL PARSER START TABLE: {table_name}"
)

 record = Record(
 name=table_name,
 primary_key=None,
 fields={}
)

 schema.record_table_map[
 table_name
] = table_name

 entries = self.split_entries(
 body
)

 self._debug(
 f"DDL PARSER TABLE {table_name} ENTRY COUNT: {len(entries)}"
)

 pending_foreign_keys: list[dict] = []

 for entry in entries:
 entry = entry.strip()

 if not entry:
 continue

 first_word = self._first_word(
 entry
)

 if first_word in self.CONSTRAINT_STARTERS:
 self._parse_constraint_entry(
 record=record,
 entry=entry,
 pending_foreign_keys=pending_foreign_keys
)
 continue

 column = self._parse_column_entry(
 entry=entry,
 table_name=table_name
)

```



```

 if column is None:
 continue

 record.fields[
 column.name
] = column

 if self.INLINE_PRIMARY_KEY.search(entry):
 record.primary_key = column.name
 column.nullable = False

 schema.records[
 table_name
] = record

 self._debug(
 f"DDL PARSER TABLE {table_name}: "
 f"{len(record.fields)} columns, PK={record.primary_key}"
)

 for field_name, field in record.fields.items():
 self._debug(
 f" COLUMN {field_name}: "
 f"{field.datatype}({field.length},{field.scale}) "
 f"NULLABLE={field.nullable}"
)

 for foreign_key in pending_foreign_keys:
 self._add_relationship(
 schema=schema,
 child_table=table_name,
 child_fk=foreign_key["child_fk"],
 parent_table=foreign_key["parent_table"],
 parent_key=foreign_key["parent_key"]
)

 self._parse_alter_table_foreign_keys(
 ddl=ddl,
 schema=schema
)

 self._validate(
 schema
)

 if "CREATE TABLE" in ddl.upper() and not schema.records:
 raise ConversionError(
 "DDL text was provided and contains CREATE TABLE, but no tables were parsed."
)

 return schema

def remove_comments(
 self,
 ddl: str
) -> str:

 ddl = re.sub(
 r"--.*?$",
 "",
 ddl,
 flags=re.MULTILINE
)

 ddl = re.sub(
 r"/*.*?*/",
 "",
 ddl,
 flags=re.DOTALL
)

 return ddl

def _extract_create_table_statements(
 self,

```

```

ddl: str
) -> list[dict]:

 results: list[dict] = []

 pattern = re.compile(
 r"\bCREATE\s+TABLE\s+(?P<table>(?:[A-Z0-9_]+\.)?[A-Z0-9_]+)",
 re.IGNORECASE
)

 for match in pattern.finditer(ddl):
 table_name = self._normalize_name(
 match.group("table")
)

 open_index = ddl.find(
 "(",
 match.end()
)

 if open_index < 0:
 self._debug(
 f"DDL PARSER TABLE {table_name}: no opening parenthesis found"
)
 continue

 close_index = self._find_matching_parenthesis(
 text=ddl,
 open_index=open_index
)

 if close_index < 0:
 self._debug(
 f"DDL PARSER TABLE {table_name}: no closing parenthesis found"
)
 continue

 body = ddl[
 open_index + 1:close_index
]

 results.append(
 {
 "table_name": table_name,
 "body": body
 }
)

 return results

def _find_matching_parenthesis(
 self,
 text: str,
 open_index: int
) -> int:

 depth = 0
 quote = None

 for index in range(open_index, len(text)):
 char = text[index]

 if quote:
 if char == quote:
 quote = None
 continue

 if char in {
 '"',
 "'",
 }:
 quote = char
 continue

 if char == "(":
 depth += 1

```

```

 continue

 if char == ")":
 depth -= 1

 if depth == 0:
 return index

 return -1

def split_entries(
 self,
 body: str
) -> list[str]:

 entries: list[str] = []
 current: list[str] = []
 depth = 0
 quote = None

 for char in body:
 if quote:
 current.append(char)

 if char == quote:
 quote = None

 continue

 if char in {
 "'",
 '"',
 }:
 quote = char
 current.append(char)
 continue

 if char == "(":
 depth += 1
 current.append(char)
 continue

 if char == ")":
 depth -= 1
 current.append(char)
 continue

 if char == "," and depth == 0:
 entry = "".join(current).strip()

 if entry:
 entries.append(entry)

 current = []
 continue

 current.append(char)

 entry = "".join(current).strip()

 if entry:
 entries.append(entry)

 return entries

def _parse_constraint_entry(
 self,
 record: Record,
 entry: str,
 pending_foreign_keys: list[dict]
) -> None:

 primary_key_match = self.TABLE_PRIMARY_KEY.search(
 entry
)

```

```

if primary_key_match:
 primary_key = self._first_column(
 primary_key_match.group("columns")
)

 if primary_key:
 record.primary_key = primary_key

 if primary_key in record.fields:
 record.fields[
 primary_key
].nullable = False

 self._debug(
 f"DDL PARSER PRIMARY KEY FOR {record.name}: {record.primary_key}"
)

 return

foreign_key_match = self.TABLE_FOREIGN_KEY.search(
 entry
)

if foreign_key_match:
 child_fk = self._first_column(
 foreign_key_match.group("child_cols")
)

 parent_table = self._normalize_name(
 foreign_key_match.group("parent_table")
)

 parent_key = self._first_column(
 foreign_key_match.group("parent_cols")
)

 if child_fk and parent_table and parent_key:
 pending_foreign_keys.append(
 {
 "child_fk": child_fk,
 "parent_table": parent_table,
 "parent_key": parent_key
 }
)

 self._debug(
 f"DDL PARSER FK: {child_fk} -> {parent_table}({parent_key})"
)

 return

def _parse_alter_table_foreign_keys(
 self,
 ddl: str,
 schema: SchemaModel
) -> None:

 for match in self.ALTER_TABLE_FK.finditer(ddl):
 child_table = self._normalize_name(
 match.group("child_table")
)

 child_fk = self._first_column(
 match.group("child_cols")
)

 parent_table = self._normalize_name(
 match.group("parent_table")
)

 parent_key = self._first_column(
 match.group("parent_cols")
)

 if not child_table:
 continue

```

```

 if not child_fk:
 continue

 if not parent_table:
 continue

 if not parent_key:
 continue

 self._add_relationship(
 schema=schema,
 child_table=child_table,
 child_fk=child_fk,
 parent_table=parent_table,
 parent_key=parent_key
)

def _add_relationship(
 self,
 schema: SchemaModel,
 child_table: str,
 child_fk: str,
 parent_table: str,
 parent_key: str
) -> None:

 child_table = self._normalize_name(child_table)
 child_fk = self._normalize_name(child_fk)
 parent_table = self._normalize_name(parent_table)
 parent_key = self._normalize_name(parent_key)

 set_name = f"{parent_table}-{child_table}"

 schema.relationships[set_name] = Relationship(
 set_name=set_name,
 parent_record=parent_table,
 child_record=child_table,
 cardinality="1:N",
 parent_key=parent_key,
 child_fk=child_fk,
 order_by=[child_fk]
)

def _parse_column_entry(
 self,
 entry: str,
 table_name: str
) -> Column | None:

 entry = entry.strip()

 if not entry:
 return None

 match = re.match(
 r"^(?P<name>[A-Z0-9_]+)\s+(?P<datatype>.+)$",
 entry,
 flags=re.IGNORECASE | re.DOTALL
)

 if not match:
 self._debug(
 f"DDL PARSER SKIPPED ENTRY IN {table_name}: no column match. ENTRY={repr(entry)}"
)
 return None

 column_name = self._normalize_name(
 match.group("name")
)

 datatype_text = match.group("datatype").strip()

 datatype, length, scale = self._parse_datatype(
 datatype_text
)

```

```

if datatype is None:
 self._debug_unrecognized_datatype(
 table_name=table_name,
 column_name=column_name,
 datatype_text=datatype_text
)
 return None

nullable = not bool(
 self.INLINE_NOT_NULL.search(entry)
)

return Column(
 name=column_name,
 datatype=datatype,
 length=length,
 scale=scale,
 nullable=nullable
)

def _parse_datatype(
 self,
 datatype_text: str
) -> tuple[str | None, int | None, int | None]:

 text = self._normalize_datatype_text(
 datatype_text
)

 if not text:
 return (
 None,
 None,
 None
)

 datatype_name = self._leading_word(
 text
)

 if datatype_name in {
 "VARCHAR",
 "CHAR",
 "CHARACTER"
 }:
 length = self._manual_first_parenthesized_int(
 text
)

 if datatype_name == "CHARACTER":
 datatype_name = "CHAR"

 if length is None and datatype_name == "CHAR":
 length = 1

 if length is not None:
 return (
 datatype_name,
 length,
 None
)

 if datatype_name in {
 "DECIMAL",
 "NUMERIC"
 }:
 precision_scale = self._manual_precision_scale(
 text
)

 if precision_scale is not None:
 precision, scale = precision_scale

 return (
 "DECIMAL",

```

```

 precision,
 scale
)

if datatype_name == "SMALLINT":
 return (
 "SMALLINT",
 4,
 0
)

if datatype_name in {
 "INTEGER",
 "INT"
}:
 return (
 "INTEGER",
 9,
 0
)

if datatype_name == "BIGINT":
 return (
 "BIGINT",
 18,
 0
)

if datatype_name == "DATE":
 return (
 "DATE",
 None,
 None
)

if datatype_name == "TIMESTAMP":
 return (
 "TIMESTAMP",
 None,
 None
)

if datatype_name == "TIME":
 return (
 "TIME",
 None,
 None
)

return (
 None,
 None,
 None
)

def _normalize_datatype_text(
 self,
 datatype_text: str
) -> str:

 text = datatype_text or ""

 text = str(text).strip().upper()

 text = text.replace(" ", "(")
 text = text.replace(" ", ")")
 text = text.replace(" ", ",")
 text = text.replace("\u00a0", " ")

 text = re.sub(
 r"\s+",
 " ",
 text
)

 text = re.sub(

```

```

 r"\bNOT\s+NULL\b",
 "",
 text,
 flags=re.IGNORECASE
)

 text = re.sub(
 r"\bPRIMARY\s+KEY\b",
 "",
 text,
 flags=re.IGNORECASE
)

 text = re.sub(
 r"\bDEFAULT\b.*$",
 "",
 text,
 flags=re.IGNORECASE
)

 return text.strip()

def _leading_word(
 self,
 text: str
) -> str:

 result = []

 for char in text:
 if char.isalpha():
 result.append(char)
 continue

 break

 return "".join(result).upper()

def _manual_first_parenthesized_int(
 self,
 text: str
) -> int | None:

 open_index = text.find("(")

 if open_index < 0:
 return None

 close_index = text.find(")", open_index + 1)

 if close_index < 0:
 return None

 content = text[
 open_index + 1:close_index
].strip()

 if not content.isdigit():
 return None

 return int(content)

def _manual_precision_scale(
 self,
 text: str
) -> tuple[int, int] | None:

 open_index = text.find("(")

 if open_index < 0:
 return None

 close_index = text.find(")", open_index + 1)

 if close_index < 0:
 return None

```



```

content = text[
 open_index + 1:close_index
].strip()

parts = [
 part.strip()
 for part in content.split(",")
]

if len(parts) != 2:
 return None

if not parts[0].isdigit():
 return None

if not parts[1].isdigit():
 return None

return (
 int(parts[0]),
 int(parts[1])
)

def _validate(
 self,
 schema: SchemaModel
) -> None:

 errors: list[str] = []

 for record in schema.records.values():
 if record.primary_key and record.primary_key not in record.fields:
 errors.append(
 f"{record.name} primary key {record.primary_key} is not declared as a column."
)

 for field_name, field in record.fields.items():
 if not field.datatype:
 errors.append(
 f"{record.name}.{field_name} has no datatype."
)

 if errors:
 raise ConversionError(
 "\n".join(errors)
)

def _first_word(
 self,
 entry: str
) -> str:

 tokens = entry.strip().split()

 if not tokens:
 return ""

 return self._normalize_name(
 tokens[0]
)

def _first_column(
 self,
 text: str
) -> str | None:

 if not text:
 return None

 first = text.split(",")[0].strip()

 if not first:
 return None

 return self._normalize_name(

```

```

 first
)

def _normalize_name(
 self,
 value: str | None
) -> str:

 if not value:
 return ""

 value = str(value).strip()
 value = value.strip("'")
 value = value.strip('"')
 value = value.strip("`")
 value = value.strip("[")
 value = value.strip("]")

 if "." in value:
 value = value.split(".")[1]

 return value.upper()

def _debug(
 self,
 message: str
) -> None:

 if self.DEBUG:
 print(message)

def _debug_unrecognized_datatype(
 self,
 table_name: str,
 column_name: str,
 datatype_text: str
) -> None:

 if not self.DEBUG:
 return

 normalized = self._normalize_datatype_text(
 datatype_text
)

 char_codes = [
 ord(char)
 for char in datatype_text
]

 print(
 "DDL PARSER SKIPPED COLUMN "
 f"{table_name}.{column_name}: "
 f"raw={repr(datatype_text)} "
 f"normalized={repr(normalized)} "
 f"leading={repr(self._leading_word(normalized))} "
 f"char_codes={char_codes}"
)

```

```

=====
FILE: src\idms_db2_converter\parsers\idms_schema_parser.py
ENCODING: utf-8
=====

```

```
import re
```

```

from idms_db2_converter.generators.naming import Naming
from idms_db2_converter.models import Column, Record, Relationship, SchemaModel

```

```

class IdmsSchemaParser:
 RECORD_HEADER = re.compile(
 r"^RECORD NAME\.\.+s+([A-Z0-9-]+)",
 re.IGNORECASE | re.MULTILINE,
)

```

```

LOCATION_CALC = re.compile(
 r"LOCATION MODE\.\s+CALC USING\s+([A-Z0-9-]+)",
 re.IGNORECASE,
)

DBKEY_SET_ROLE = re.compile(
 r"^\s+([A-Z0-9-]+)\s+(?:INDEX\s+)?(OWNER|MEMBER)\b",
 re.IGNORECASE | re.MULTILINE,
)

DATA_LINE_PREFIX = re.compile(
 r"^\s*(0[2-5])\s+([A-Z0-9-]+)\s+(.*)$",
 re.IGNORECASE,
)

PICTURE_FIND = re.compile(
 r"S?9$\d+$V9$\d+$|"
 r"S?9$\d+$V9+|"
 r"S?9+V9$\d+$|"
 r"S?9+V9+|"
 r"S?V9$\d+$|"
 r"S?V9+|"
 r"S?9$\d+$|"
 r"S?9+|"
 r"X$\d+$|"
 r"X+",
 re.IGNORECASE,
)

DATE_PARTS = {
 "YEAR": {
 "substring_start": 1,
 "substring_length": 4,
 },
 "MONTH": {
 "substring_start": 5,
 "substring_length": 2,
 },
 "DAY": {
 "substring_start": 7,
 "substring_length": 2,
 },
}

def parse(self, text: str) -> SchemaModel:
 schema = SchemaModel()
 schema.schema_source = "IDMS_SCHEMA"

 blocks = self._record_blocks(text)
 set_roles: dict[str, dict[str, str]] = {}

 for record_name, block in blocks:
 self._parse_record(schema, record_name, block)
 self._collect_set_roles(set_roles, record_name, block)

 self._build_relationships(schema, set_roles)

 if hasattr(schema, "add_validation_message"):
 schema.add_validation_message("Schema built from IDMS schema listing.")

 return schema

def _record_blocks(self, text: str) -> list[tuple[str, str]]:
 matches = list(self.RECORD_HEADER.finditer(text))
 result = []

 for index, match in enumerate(matches):
 record_name = match.group(1).upper()
 start = match.start()
 end = matches[index + 1].start() if index + 1 < len(matches) else len(text)

 result.append((record_name, text[start:end]))

 return result

```

```

def _parse_record(
 self,
 schema: SchemaModel,
 record_name: str,
 block: str,
) -> None:
 primary_key = None

 calc_match = self.LOCATION_CALC.search(block)

 if calc_match:
 primary_key = self._normalize_column(calc_match.group(1))

 record = Record(
 name=record_name,
 primary_key=primary_key,
 fields={},
)

 schema.record_table_map[record_name] = self._normalize_table(record_name)

 active_date_groups: dict[int, dict[str, str]] = {}

 for line in block.splitlines():
 parsed = self._parse_data_item_line(line)

 if not parsed:
 continue

 level = parsed["level"]
 raw_field_name = parsed["field_name"]
 body = parsed["body"]
 storage_length = parsed["length"]

 self._close_inactive_date_groups(active_date_groups, level)

 if raw_field_name == "FILLER":
 continue

 usage = self._extract_usage(body)
 picture = self._extract_picture(body)
 column_name = self._normalize_column(raw_field_name)

 if self._is_date_group(raw_field_name, picture, storage_length):
 if column_name not in record.fields:
 record.fields[column_name] = Column(
 name=column_name,
 datatype="CHAR",
 length=8,
 scale=None,
 nullable=False,
)

 host = Naming.hv(record_name, column_name)
 self._add_field_map(schema, raw_field_name, host)

 active_date_groups[level] = {
 "raw_field_name": raw_field_name,
 "column_name": column_name,
 "host": host,
 }

 continue

 date_group = self._nearest_date_group(active_date_groups)

 if date_group and self._is_date_part(raw_field_name):
 self._add_date_part_map(
 schema=schema,
 idms_field=raw_field_name,
 host=date_group["host"],
)
 continue

 if not picture:
 continue

```

```

 datatype, column_length, scale = self._map_picture(
 picture=picture,
 usage=usage,
 storage_length=storage_length,
)

 if column_name not in record.fields:
 record.fields[column_name] = Column(
 name=column_name,
 datatype=datatype,
 length=column_length,
 scale=scale,
 nullable=False,
)

 self._add_field_map(
 schema=schema,
 idms_field=raw_field_name,
 host=Naming.hv(record_name, column_name),
)

 if primary_key and primary_key not in record.fields:
 record.fields[primary_key] = Column(
 name=primary_key,
 datatype="CHAR",
 length=12,
 scale=None,
 nullable=False,
)

 schema.records[record_name] = record

def _parse_data_item_line(self, line: str) -> dict | None:
 match = self.DATA_LINE_PREFIX.match(line)

 if not match:
 return None

 level = int(match.group(1))
 field_name = match.group(2).upper()
 remainder = match.group(3).strip()

 if field_name == "FILLER":
 return None

 parts = remainder.split()

 if len(parts) < 2:
 return None

 if not parts[-1].isdigit() or not parts[-2].isdigit():
 return None

 length = int(parts[-1])
 start = int(parts[-2])
 body = " ".join(parts[:-2])

 return {
 "level": level,
 "field_name": field_name,
 "body": body,
 "start": start,
 "length": length,
 }

def _collect_set_roles(
 self,
 set_roles: dict[str, dict[str, str]],
 record_name: str,
 block: str,
) -> None:
 for match in self.DBKEY_SET_ROLE.finditer(block):
 set_name = match.group(1).upper()
 role = match.group(2).upper()

```

```

 if set_name == "CALC":
 continue

 set_roles.setdefault(set_name, {})

 if role == "OWNER":
 set_roles[set_name]["owner"] = record_name

 if role == "MEMBER":
 set_roles[set_name]["member"] = record_name

def _build_relationships(
 self,
 schema: SchemaModel,
 set_roles: dict[str, dict[str, str]],
) -> None:
 for set_name, roles in set_roles.items():
 owner = roles.get("owner")
 member = roles.get("member")

 if not owner or not member:
 continue

 if owner not in schema.records or member not in schema.records:
 continue

 owner_record = schema.records[owner]
 member_record = schema.records[member]

 parent_key = owner_record.primary_key

 if not parent_key:
 continue

 child_fk = parent_key

 if child_fk not in member_record.fields:
 parent_column = owner_record.fields.get(parent_key)

 member_record.fields[child_fk] = Column(
 name=child_fk,
 datatype=parent_column.datatype if parent_column else "CHAR",
 length=parent_column.length if parent_column else 12,
 scale=parent_column.scale if parent_column else None,
 nullable=True,
)

 schema.relationships[set_name] = Relationship(
 set_name=set_name,
 parent_record=owner,
 child_record=member,
 cardinality="1:N",
 parent_key=parent_key,
 child_fk=child_fk,
 order_by=[child_fk],
)

def _extract_usage(self, body: str) -> str:
 upper = body.upper()

 if "COMP-3" in upper:
 return "COMP-3"

 if re.search(r"\bCOMP\b", upper):
 return "COMP"

 return "DISPLAY"

def _extract_picture(self, body: str) -> str | None:
 upper = body.upper()
 matches = list(self.PICTURE_FIND.finditer(upper))

 if not matches:
 return None

 valid_matches = []

```

```

for match in matches:
 value = match.group(0).upper()
 start = match.start()
 end = match.end()

 before = upper[start - 1] if start > 0 else " "
 after = upper[end] if end < len(upper) else " "

 if before.isalnum() or before in {"-", "_":
 continue

 if after.isalnum() or after in {"-", "_":
 continue

 valid_matches.append(value)

if not valid_matches:
 return None

return valid_matches[-1]

def _map_picture(
 self,
 picture: str,
 usage: str,
 storage_length: int,
) -> tuple[str, int | None, int | None]:
 picture = picture.upper()
 usage = usage.upper()

 if picture.startswith("X"):
 length_match = re.search(r"X$(\d+)$", picture)

 if length_match:
 return "CHAR", int(length_match.group(1)), None

 return "CHAR", len(picture), None

 if "9" in picture:
 precision = self._numeric_precision(picture)
 scale = self._numeric_scale(picture)

 if usage == "DISPLAY":
 return "CHAR", storage_length, None

 if usage == "COMP":
 return "INTEGER", None, None

 return "DECIMAL", precision, scale

 return "CHAR", storage_length, None

def _numeric_precision(self, picture: str) -> int:
 picture = picture.upper().replace("S", "")

 if "V" in picture:
 before_v, after_v = picture.split("V", 1)
 else:
 before_v = picture
 after_v = ""

 return self._count_9_digits(before_v) + self._count_9_digits(after_v)

def _numeric_scale(self, picture: str) -> int:
 picture = picture.upper().replace("S", "")

 if "V" not in picture:
 return 0

 after_v = picture.split("V", 1)[1]

 return self._count_9_digits(after_v)

def _count_9_digits(self, value: str) -> int:
 total = 0

```

```

for match in re.finditer(r"9$(\d+)$|9", value):
 if match.group(1):
 total += int(match.group(1))
 else:
 total += 1

return total

def _is_date_group(
 self,
 raw_field_name: str,
 picture: str | None,
 storage_length: int,
) -> bool:
 normalized = self._normalize_column(raw_field_name)

 return (
 picture is None
 and normalized.endswith("DATE")
 and storage_length == 8
)

def _is_date_part(self, raw_field_name: str) -> bool:
 normalized = self._normalize_column(raw_field_name)

 return (
 normalized.endswith("_YEAR")
 or normalized.endswith("_MONTH")
 or normalized.endswith("_DAY")
)

def _add_date_part_map(
 self,
 schema: SchemaModel,
 idms_field: str,
 host: str,
) -> None:
 normalized = self._normalize_column(idms_field)

 if normalized.endswith("_YEAR"):
 part = "YEAR"
 elif normalized.endswith("_MONTH"):
 part = "MONTH"
 elif normalized.endswith("_DAY"):
 part = "DAY"
 else:
 return

 schema.date_part_map[idms_field.upper()] = {
 "host": host,
 "substring_start": self.DATE_PARTS[part]["substring_start"],
 "substring_length": self.DATE_PARTS[part]["substring_length"],
 }

def _add_field_map(
 self,
 schema: SchemaModel,
 idms_field: str,
 host: str,
) -> None:
 schema.field_map[idms_field.upper()] = {
 "host": host,
 }

def _close_inactive_date_groups(
 self,
 active_date_groups: dict[int, dict[str, str]],
 current_level: int,
) -> None:
 closed_levels = [
 level
 for level in active_date_groups
 if level >= current_level
]

```



```

 for level in closed_levels:
 del active_date_groups[level]

 def _nearest_date_group(
 self,
 active_date_groups: dict[int, dict[str, str]],
) -> dict[str, str] | None:
 if not active_date_groups:
 return None

 nearest_level = max(active_date_groups.keys())

 return active_date_groups[nearest_level]

 def _normalize_table(self, record_name: str) -> str:
 return record_name.upper().replace("-", "_")

 def _normalize_column(self, field_name: str) -> str:
 value = field_name.upper()
 value = re.sub(r"-\d{4}$", "", value)

 return value.replace("-", "_")

```

```

=====
FILE: src\idms_db2_converter\parsers\phase2_metadata_parser.py
ENCODING: utf-8
=====

```

```

import json

from idms_db2_converter.exceptions import ConversionError
from idms_db2_converter.models import (
 Column,
 Record,
 Relationship,
 SchemaModel,
)

class Phase2MetadataParser:
 """
 Parses Phase 2 metadata JSON produced by Phase 1.

 Generic behavior only:
 - No hardcoded DB2 table names.
 - No hardcoded DB2 column names.
 - No hardcoded business record names.
 - Uses only names present in payload:
 records, fields, relationships, table_key_map, field_map, etc.

 Supports:
 - records / tables / db2_tables
 - primary_key and primary_keys
 - relationships / sets / db2_relationships
 - parent_key / parent_keys
 - child_fk / child_fks
 - record_table_map
 - field_map
 - calc_key_map
 - table_key_map
 - set_ordering_map
 - navigation_intent
 - nullable_fk_map
 - date_part_map
 - output_semantics
 - paragraph_operation_graph
 - validation_messages
 """

 def parse_as_schema(
 self,
 text: str,
) -> SchemaModel:
 schema = SchemaModel()

```

```

if not text or not text.strip():
 return schema

try:
 payload = json.loads(text)
except json.JSONDecodeError as exc:
 raise ConversionError(
 f"Invalid Phase 2 metadata JSON: {exc}"
) from exc

if not isinstance(payload, dict):
 raise ConversionError(
 "Invalid Phase 2 metadata JSON: root must be an object."
)

self._parse_records(
 payload=payload,
 schema=schema,
)

self._merge_table_key_map(
 payload=payload,
 schema=schema,
)

self._parse_relationships(
 payload=payload,
 schema=schema,
)

self._merge_record_table_map(
 payload=payload,
 schema=schema,
)

self._merge_field_map(
 payload=payload,
 schema=schema,
)

self._merge_calc_key_map(
 payload=payload,
 schema=schema,
)

self._merge_table_key_map_to_schema(
 payload=payload,
 schema=schema,
)

self._merge_set_ordering_map(
 payload=payload,
 schema=schema,
)

self._merge_navigation_intent(
 payload=payload,
 schema=schema,
)

self._merge_nullable_fk_map(
 payload=payload,
 schema=schema,
)

self._merge_date_part_map(
 payload=payload,
 schema=schema,
)

self._merge_output_semantics(
 payload=payload,
 schema=schema,
)

self._merge_paragraph_operation_graph(

```

```

 payload=payload,
 schema=schema,
)

 self._merge_validation_messages(
 payload=payload,
 schema=schema,
)

 self._apply_key_flags(
 schema=schema,
)

 schema.schema_source = "PHASE2_METADATA"

 return schema

def _parse_records(
 self,
 payload: dict,
 schema: SchemaModel,
) -> None:
 record_items = (
 payload.get("records")
 or payload.get("tables")
 or payload.get("db2_tables")
 or []
)

 if isinstance(record_items, dict):
 record_items = list(record_items.values())

 for record_json in record_items:
 if not isinstance(record_json, dict):
 continue

 record_name = self.normalize_name(
 self._get_first_non_empty(
 source=record_json,
 keys=[
 "name",
 "record",
 "table",
 "table_name",
 "record_name",
],
)
)

 if not record_name:
 continue

 primary_keys = self._extract_primary_keys(
 source=record_json,
)

 fields = self._parse_fields(
 record_json=record_json,
 primary_keys=primary_keys,
)

 primary_key = primary_keys[0] if primary_keys else None

 record = Record(
 name=record_name,
 primary_key=primary_key,
 primary_keys=primary_keys,
 fields=fields,
)

 record.set_primary_keys(
 keys=primary_keys,
)

 schema.records[record_name] = record

```

```

def _parse_fields(
 self,
 record_json: dict,
 primary_keys: list[str],
) -> dict[str, Column]:
 fields: dict[str, Column] = {}

 field_items = (
 record_json.get("fields")
 or record_json.get("columns")
 or []
)

 if isinstance(field_items, dict):
 field_items = list(field_items.values())

 primary_key_set = {
 self.normalize_name(primary_key)
 for primary_key in primary_keys
 if primary_key
 }

 for field_json in field_items:
 if not isinstance(field_json, dict):
 continue

 field_name = self.normalize_name(
 self._get_first_non_empty(
 source=field_json,
 keys=[
 "name",
 "field",
 "column",
 "column_name",
],
)
)

 if not field_name:
 continue

 datatype = (
 self._get_first_non_empty(
 source=field_json,
 keys=[
 "datatype",
 "data_type",
 "type",
],
)
 or "CHAR"
)

 datatype = str(datatype).upper()

 nullable = field_json.get("nullable")

 if nullable is None:
 nullable = field_name not in primary_key_set

 primary_key_flag = bool(
 field_json.get("primary_key", False)
 or field_name in primary_key_set
)

 fields[field_name] = Column(
 name=field_name,
 datatype=datatype,
 length=self._safe_int_or_none(
 field_json.get("length"),
),
 scale=self._safe_int_or_none(
 field_json.get("scale"),
),
 nullable=bool(nullable) if not primary_key_flag else False,
 primary_key=primary_key_flag,

```

```

 generated=bool(field_json.get("generated", False)),
 source_kind=str(field_json.get("source_kind", "") or ""),
)

 return fields

def _parse_relationships(
 self,
 payload: dict,
 schema: SchemaModel,
) -> None:
 relationship_items = (
 payload.get("relationships")
 or payload.get("sets")
 or payload.get("db2_relationships")
 or []
)

 if isinstance(relationship_items, dict):
 relationship_items = list(relationship_items.values())

 for rel_json in relationship_items:
 if not isinstance(rel_json, dict):
 continue

 set_name = self.normalize_name(
 self._get_first_non_empty(
 source=rel_json,
 keys=[
 "set_name",
 "name",
 "set",
],
)
)

 parent_record = self.normalize_name(
 self._get_first_non_empty(
 source=rel_json,
 keys=[
 "parent_record",
 "owner_record",
 "parent",
 "owner",
 "parent_table",
],
)
)

 child_record = self.normalize_name(
 self._get_first_non_empty(
 source=rel_json,
 keys=[
 "child_record",
 "member_record",
 "child",
 "member",
 "child_table",
],
)
)

 if not set_name or not parent_record or not child_record:
 continue

 parent_keys = self._extract_key_list(
 source=rel_json,
 plural_keys=[
 "parent_keys",
 "owner_keys",
],
 single_keys=[
 "parent_key",
 "owner_key",
],
)

```

```

child_fks = self._extract_key_list(
 source=rel_json,
 plural_keys=[
 "child_fks",
 "member_fks",
 "foreign_keys",
],
 single_keys=[
 "child_fk",
 "member_fk",
 "foreign_key",
],
)

if not parent_keys:
 parent_key = self._resolve_parent_key(
 schema=schema,
 parent_record=parent_record,
)

 if parent_key:
 parent_keys = [parent_key]

if not child_fks:
 child_fk = self._resolve_child_fk(
 schema=schema,
 parent_record=parent_record,
 child_record=child_record,
 parent_keys=parent_keys,
)

 if child_fk:
 child_fks = [child_fk]

order_by = [
 self.normalize_name(value)
 for value in rel_json.get("order_by", []) or []
 if value
]

if not order_by and child_fks:
 order_by = child_fks.copy()

parent_key_single = parent_keys[0] if parent_keys else None
child_fk_single = child_fks[0] if child_fks else None

schema.relationships[set_name] = Relationship(
 set_name=set_name,
 parent_record=parent_record,
 child_record=child_record,
 cardinality=rel_json.get("cardinality") or "1:N",
 parent_key=parent_key_single,
 child_fk=child_fk_single,
 parent_keys=parent_keys,
 child_fks=child_fks,
 order_by=order_by,
)

def _merge_table_key_map(
 self,
 payload: dict,
 schema: SchemaModel,
) -> None:
 table_key_map = payload.get("table_key_map") or {}

 if not isinstance(table_key_map, dict):
 return

 for table_name_raw, key_payload in table_key_map.items():
 table_name = self.normalize_name(table_name_raw)

 if not table_name:
 continue

 if not isinstance(key_payload, dict):

```

```

 continue

 primary_keys = self._extract_key_list(
 source=key_payload,
 plural_keys=[
 "primary_keys",
 "pk_columns",
],
 single_keys=[
 "primary_key",
 "pk",
],
)

 if not primary_keys:
 continue

 record = schema.records.get(table_name)

 if record is None:
 continue

 record.set_primary_keys(
 keys=primary_keys,
)

def _merge_table_key_map_to_schema(
 self,
 payload: dict,
 schema: SchemaModel,
) -> None:
 table_key_map = payload.get("table_key_map") or {}

 if not isinstance(table_key_map, dict):
 return

 schema.table_key_map = {}

 for table_name, value in table_key_map.items():
 normalized_table_name = self.normalize_name(table_name)

 if not normalized_table_name:
 continue

 if isinstance(value, dict):
 schema.table_key_map[normalized_table_name] = self._normalize_nested(
 value=value,
)
 else:
 schema.table_key_map[normalized_table_name] = value

def _merge_record_table_map(
 self,
 payload: dict,
 schema: SchemaModel,
) -> None:
 for key, value in (payload.get("record_table_map") or {}).items():
 schema.record_table_map[self.normalize_name(key)] = self.normalize_name(value)

def _merge_field_map(
 self,
 payload: dict,
 schema: SchemaModel,
) -> None:
 for key, value in (payload.get("field_map") or {}).items():
 schema.field_map[self.normalize_name(key)] = value

def _merge_calc_key_map(
 self,
 payload: dict,
 schema: SchemaModel,
) -> None:
 for key, value in (payload.get("calc_key_map") or {}).items():
 schema.calc_key_map[self.normalize_name(key)] = value

def _merge_set_ordering_map(

```

```

self,
payload: dict,
schema: SchemaModel,
) -> None:
 for key, value in (payload.get("set_ordering_map") or {}).items():
 schema.set_ordering_map[self.normalize_name(key)] = value

 relationship = schema.relationships.get(
 self.normalize_name(key),
)

 if relationship is None:
 continue

 if isinstance(value, dict):
 parent_keys = self._extract_key_list(
 source=value,
 plural_keys=[
 "parent_keys",
],
 single_keys=[
 "parent_key",
],
)

 child_fks = self._extract_key_list(
 source=value,
 plural_keys=[
 "child_fks",
],
 single_keys=[
 "child_fk",
],
)

 if parent_keys:
 relationship.parent_keys = parent_keys
 relationship.parent_key = parent_keys[0]

 if child_fks:
 relationship.child_fks = child_fks
 relationship.child_fk = child_fks[0]

 order_by = value.get("order_by") or []

 if order_by:
 relationship.order_by = [
 self.normalize_name(item)
 for item in order_by
 if item
]

def _merge_navigation_intent(
 self,
 payload: dict,
 schema: SchemaModel,
) -> None:
 value = payload.get("navigation_intent") or {}

 if isinstance(value, dict):
 schema.navigation_intent = value

def _merge_nullable_fk_map(
 self,
 payload: dict,
 schema: SchemaModel,
) -> None:
 value = payload.get("nullable_fk_map") or {}

 if isinstance(value, dict):
 schema.nullable_fk_map = value

def _merge_date_part_map(
 self,
 payload: dict,
 schema: SchemaModel,

```



```

) -> None:
 value = payload.get("date_part_map") or {}

 if isinstance(value, dict):
 schema.date_part_map = {
 self.normalize_name(key): item
 for key, item in value.items()
 }

def _merge_output_semantics(
 self,
 payload: dict,
 schema: SchemaModel,
) -> None:
 value = payload.get("output_semantics") or {}

 if isinstance(value, dict):
 schema.output_semantics = value

def _merge_paragraph_operation_graph(
 self,
 payload: dict,
 schema: SchemaModel,
) -> None:
 value = payload.get("paragraph_operation_graph") or {}

 if isinstance(value, dict):
 schema.paragraph_operation_graph = value

def _merge_validation_messages(
 self,
 payload: dict,
 schema: SchemaModel,
) -> None:
 messages = payload.get("validation_messages") or []

 if isinstance(messages, list):
 schema.validation_messages.extend(
 str(message)
 for message in messages
)

def _apply_key_flags(
 self,
 schema: SchemaModel,
) -> None:
 for record in schema.records.values():
 primary_keys = record.effective_primary_keys()

 for primary_key in primary_keys:
 if primary_key not in record.fields:
 continue

 record.fields[primary_key].primary_key = True
 record.fields[primary_key].nullable = False

 if not record.primary_key and primary_keys:
 record.primary_key = primary_keys[0]

def _resolve_parent_key(
 self,
 schema: SchemaModel,
 parent_record: str,
) -> str | None:
 record = schema.records.get(parent_record)

 if not record:
 return None

 primary_keys = record.effective_primary_keys()

 if primary_keys:
 return primary_keys[0]

 return record.primary_key

```

```

def _resolve_child_fk(
 self,
 schema: SchemaModel,
 parent_record: str,
 child_record: str,
 parent_keys: list[str],
) -> str | None:
 child = schema.records.get(child_record)

 if not child:
 return None

 for parent_key in parent_keys or []:
 if parent_key in child.fields:
 return parent_key

 parent = schema.records.get(parent_record)

 if parent is None:
 return None

 parent_effective_keys = parent.effective_primary_keys()

 for parent_key in parent_effective_keys:
 if parent_key in child.fields:
 return parent_key

 parent_base_keys = {
 self.remove_record_suffix(parent_key): parent_key
 for parent_key in parent_effective_keys
 if parent_key
 }

 for child_field_name in child.fields:
 child_base_name = self.remove_record_suffix(child_field_name)

 if child_base_name in parent_base_keys:
 return child_field_name

 return None

def _extract_primary_keys(
 self,
 source: dict,
) -> list[str]:
 return self._extract_key_list(
 source=source,
 plural_keys=[
 "primary_keys",
 "pk_columns",
],
 single_keys=[
 "primary_key",
 "pk",
],
)

def _extract_key_list(
 self,
 source: dict,
 plural_keys: list[str],
 single_keys: list[str],
) -> list[str]:
 values: list[str] = []

 for key in plural_keys:
 raw_value = source.get(key)

 if raw_value is None:
 continue

 if isinstance(raw_value, list):
 for item in raw_value:
 normalized = self.normalize_name(item)

 if normalized and normalized not in values:

```

```

 values.append(normalized)

 elif isinstance(raw_value, str):
 normalized = self.normalize_name(raw_value)

 if normalized and normalized not in values:
 values.append(normalized)

for key in single_keys:
 raw_value = source.get(key)

 if raw_value is None:
 continue

 normalized = self.normalize_name(raw_value)

 if normalized and normalized not in values:
 values.append(normalized)

return values

def _get_first_non_empty(
 self,
 source: dict,
 keys: list[str],
) -> str | None:
 for key in keys:
 value = source.get(key)

 if value is None:
 continue

 if isinstance(value, str):
 if value.strip():
 return value

 else:
 return str(value)

 return None

def _normalize_nested(
 self,
 value,
):
 if isinstance(value, dict):
 return {
 self.normalize_name(key): self._normalize_nested(item)
 for key, item in value.items()
 }

 if isinstance(value, list):
 return [
 self._normalize_nested(item)
 for item in value
]

 if isinstance(value, str):
 return self.normalize_name(value)

 return value

def _safe_int_or_none(
 self,
 value,
) -> int | None:
 try:
 if value is None:
 return None

 return int(value)
 except Exception:
 return None

def normalize_name(
 self,

```

```

 value,
) -> str:
 if value is None:
 return ""

 text = str(value).strip().upper()

 if not text:
 return ""

 text = text.replace("-", "_")
 text = text.replace(" ", "_")

 while "__" in text:
 text = text.replace("__", "_")

 return text.strip("_")

def remove_record_suffix(
 self,
 value: str,
) -> str:
 text = self.normalize_name(value)

 if not text:
 return ""

 parts = text.rsplit("_", 1)

 if len(parts) == 2 and parts[1].isdigit() and len(parts[1]) == 4:
 return parts[0]

 return text

```

```

=====
FILE: src\idms_db2_converter\services__init__.py
ENCODING: utf-8
=====

```

[Empty file]

```

=====
FILE: src\idms_db2_converter\services\conversion_service.py
ENCODING: utf-8
=====

```

```

from copy import deepcopy
from time import perf_counter
from idms_db2_converter.exceptions import ConversionError
from idms_db2_converter.models import SchemaModel
from idms_db2_converter.parsers.cobol_parser import CobolParser
from idms_db2_converter.parsers.canonical_parser import CanonicalParser
from idms_db2_converter.parsers.ddl_parser import DDLParser
from idms_db2_converter.parsers.phase2_metadata_parser import Phase2MetadataParser
from idms_db2_converter.parsers.idms_schema_parser import IdmsSchemaParser
from idms_db2_converter.services.relationship_resolver import RelationshipResolver
from idms_db2_converter.services.schema_merger import SchemaMerger
from idms_db2_converter.transformers.retrieval_transformer import RetrievalTransformer
from idms_db2_converter.validators.output_validator import OutputValidator
from idms_db2_converter.validators.schema_validator import SchemaValidator

```

```

class ConversionService:
 DEBUG_SCHEMA = False

 def convert_retrieval(
 self,
 cobol_text: str,
 canonical_json: str,
 phase2_metadata_json: str | None = None,
 ddl_text: str | None = None,
 idms_schema_text: str | None = None,
 relationship_overrides_json: str | None = None,
 target_program: str | None = None,
) -> str:

```

```

) -> tuple[str, list[str]]:
 timings: list[str] = []
 total_start = perf_counter()
 step_start = perf_counter()

 def add_timing(
 label: str,
) -> None:
 nonlocal step_start

 elapsed = perf_counter() - step_start
 message = f"Phase 2 - {label}: {elapsed:.2f} seconds"

 print(
 message,
)

 timings.append(
 message,
)

 step_start = perf_counter()

 analysis = CobolParser().parse(
 cobol_text,
)

 add_timing(
 "COBOL parse",
)

 schema_builder = (
 getattr(
 self,
 "_build_schema_from_available_sources",
 None,
)
 or getattr(
 self,
 "build_schema_from_available_sources",
)
)

 schema = schema_builder(
 canonical_json=canonical_json,
 phase2_metadata_json=phase2_metadata_json,
 ddl_text=ddl_text,
 idms_schema_text=idms_schema_text,
)

 add_timing(
 "Build schema from available sources",
)

 if self.DEBUG_SCHEMA:
 self.debug_schema(
 schema,
)

 add_timing(
 "Debug schema",
)

 if (
 relationship_overrides_json
 and relationship_overrides_json.strip()
):
 schema = RelationshipResolver().apply_overrides(
 schema=schema,
 relationship_overrides_json=relationship_overrides_json,
)

 add_timing(
 "Apply relationship overrides",
)

```

```

schema = RelationshipResolver().resolve_cobol_sets(
 schema=schema,
 analysis=analysis,
)

add_timing(
 "Resolve COBOL sets",
)

schema_errors = SchemaValidator().validate(
 schema,
 analysis,
)

add_timing(
 "Schema validation",
)

if schema_errors:
 raise ConversionError(
 "\n".join(schema_errors),
)

converted = RetrievalTransformer(
 schema,
 analysis,
).transform(
 cobol=cobol_text,
 target_program=target_program,
)

add_timing(
 "Retrieval transformer",
)

output_errors = OutputValidator().validate(
 converted,
)

add_timing(
 "Output validation",
)

validation_messages = []

validation_messages.extend(
 getattr(
 schema,
 "validation_messages",
 [],
)
)

validation_messages.extend(
 output_errors,
)

total_elapsed = perf_counter() - total_start

timings.append(
 f"Phase 2 - TOTAL: {total_elapsed:.2f} seconds",
)

print("=" * 80)
print("PHASE 2 TIMINGS")
print("=" * 80)

for timing in timings:
 print(
 timing,
)

validation_messages.extend(
 timings,
)

```

```

 return converted, validation_messages

def _build_schema_from_available_sources(
 self,
 canonical_json: str | None,
 phase2_metadata_json: str | None,
 ddl_text: str | None,
 idms_schema_text: str | None,
) -> SchemaModel:
 canonical_has_text = bool(canonical_json and canonical_json.strip())
 metadata_has_text = bool(phase2_metadata_json and phase2_metadata_json.strip())
 ddl_has_text = bool(ddl_text and ddl_text.strip())
 idms_schema_has_text = bool(idms_schema_text and idms_schema_text.strip())

 canonical_schema = SchemaModel()
 metadata_schema = SchemaModel()
 ddl_schema = SchemaModel()
 idms_schema = SchemaModel()

 if canonical_has_text:
 canonical_schema = CanonicalParser().parse(canonical_json)
 canonical_schema.schema_source = "CANONICAL"

 if metadata_has_text:
 metadata_schema = Phase2MetadataParser().parse_as_schema(
 phase2_metadata_json
)
 metadata_schema.schema_source = "PHASE2_METADATA"

 if ddl_has_text:
 ddl_schema = DDLParser().parse(ddl_text)

 if self._has_schema_objects(ddl_schema):
 ddl_schema.schema_source = "DDL"
 elif self._looks_like_idms_schema(ddl_text):
 idms_schema = IdmsSchemaParser().parse(ddl_text)
 idms_schema.schema_source = "IDMS_SCHEMA"
 elif "CREATE TABLE" in ddl_text.upper():
 raise ConversionError(
 "DDL text was provided and contains CREATE TABLE, but no tables were parsed."
)

 if idms_schema_has_text:
 idms_schema = IdmsSchemaParser().parse(idms_schema_text)
 idms_schema.schema_source = "IDMS_SCHEMA"

 if self._has_schema_objects(ddl_schema):
 base_schema = ddl_schema
 base_schema.schema_source = "DDL"

 if self._has_schema_objects(canonical_schema):
 base_schema = self._merge_non_physical_metadata(
 physical_schema=base_schema,
 overlay=canonical_schema,
)

 if metadata_has_text:
 base_schema = Phase2MetadataParser().parse_into_schema(
 text=phase2_metadata_json,
 schema=base_schema,
)

 if self._has_schema_objects(idms_schema):
 base_schema = SchemaMerger().merge_physical_with_idms(
 physical_schema=base_schema,
 idms_schema=idms_schema,
)

 return base_schema

 if self._has_schema_objects(canonical_schema):
 base_schema = canonical_schema

 if metadata_has_text:
 base_schema = Phase2MetadataParser().parse_into_schema(
 text=phase2_metadata_json,

```

```

 schema=base_schema,
)

 if self._has_schema_objects(idms_schema):
 base_schema = self._merge_schema(base_schema, idms_schema)

 return base_schema

if self._has_schema_objects(metadata_schema):
 base_schema = metadata_schema

 if self._has_schema_objects(idms_schema):
 base_schema = self._merge_schema(base_schema, idms_schema)

 return base_schema

if self._has_schema_objects(idms_schema):
 return idms_schema

raise ConversionError(
 "No usable schema source found. Provide canonical model JSON, "
 "Phase 2 metadata JSON with records/relationships, DB2 DDL, "
 "or IDMS schema listing."
)

def _merge_schema(
 self,
 base: SchemaModel,
 overlay: SchemaModel,
) -> SchemaModel:
 merged = deepcopy(base)

 for record_name, overlay_record in overlay.records.items():
 if record_name in merged.records:
 merged.records[record_name].primary_key = (
 overlay_record.primary_key
 or merged.records[record_name].primary_key
)

 for field_name, overlay_field in overlay_record.fields.items():
 merged.records[record_name].fields[field_name] = overlay_field
 else:
 merged.records[record_name] = overlay_record

 for set_name, overlay_rel in overlay.relationships.items():
 if set_name not in merged.relationships:
 merged.relationships[set_name] = overlay_rel
 continue

 rel = merged.relationships[set_name]
 rel.parent_record = overlay_rel.parent_record or rel.parent_record
 rel.child_record = overlay_rel.child_record or rel.child_record
 rel.parent_key = overlay_rel.parent_key or rel.parent_key
 rel.child_fk = overlay_rel.child_fk or rel.child_fk
 rel.cardinality = overlay_rel.cardinality or rel.cardinality

 if overlay_rel.order_by:
 rel.order_by = overlay_rel.order_by

 self._merge_dict(merged.field_map, overlay.field_map)
 self._merge_dict(merged.record_table_map, overlay.record_table_map)
 self._merge_dict(merged.calc_key_map, overlay.calc_key_map)
 self._merge_dict(merged.set_ordering_map, overlay.set_ordering_map)
 self._merge_dict(merged.navigation_intent, overlay.navigation_intent)
 self._merge_dict(merged.nullable_fk_map, overlay.nullable_fk_map)
 self._merge_dict(merged.date_part_map, overlay.date_part_map)
 self._merge_dict(merged.output_semantics, overlay.output_semantics)
 self._merge_dict(
 merged.paragraph_operation_graph,
 overlay.paragraph_operation_graph,
)

 if hasattr(merged, "validation_messages") and hasattr(
 overlay,
 "validation_messages",
):

```



```

 merged.validation_messages.extend(overlay.validation_messages)

 if not getattr(merged, "schema_source", None):
 merged.schema_source = getattr(overlay, "schema_source", None)

 return merged

def _merge_non_physical_metadata(
 self,
 physical_schema: SchemaModel,
 overlay: SchemaModel,
) -> SchemaModel:
 merged = deepcopy(physical_schema)

 self._merge_dict(merged.field_map, overlay.field_map)

 for key, value in overlay.record_table_map.items():
 if key not in merged.record_table_map:
 merged.record_table_map[key] = value

 self._merge_dict(merged.calc_key_map, overlay.calc_key_map)
 self._merge_dict(merged.set_ordering_map, overlay.set_ordering_map)
 self._merge_dict(merged.navigation_intent, overlay.navigation_intent)
 self._merge_dict(merged.nullable_fk_map, overlay.nullable_fk_map)
 self._merge_dict(merged.date_part_map, overlay.date_part_map)
 self._merge_dict(merged.output_semantics, overlay.output_semantics)
 self._merge_dict(
 merged.paragraph_operation_graph,
 overlay.paragraph_operation_graph,
)

 for set_name, relationship in overlay.relationships.items():
 if set_name not in merged.relationships:
 merged.relationships[set_name] = relationship

 if hasattr(merged, "validation_messages") and hasattr(
 overlay,
 "validation_messages",
):
 merged.validation_messages.extend(overlay.validation_messages)

 merged.schema_source = "DDL+CANONICAL_METADATA"

 return merged

def _merge_dict(self, target: dict, source: dict) -> None:
 for key, value in source.items():
 target[key] = value

def _has_schema_objects(self, schema: SchemaModel) -> bool:
 if hasattr(schema, "has_schema_objects"):
 return schema.has_schema_objects()

 return bool(schema.records or schema.relationships)

def _looks_like_idms_schema(self, text: str | None) -> bool:
 if not text:
 return False

 upper = text.upper()

 return (
 "RECORD NAME" in upper
 and "DBKEY POSITIONS" in upper
 and "DATA ITEM" in upper
)

def _debug_schema(self, schema: SchemaModel) -> None:
 print("FINAL SCHEMA SOURCE:", getattr(schema, "schema_source", None))
 print("RECORD COUNT:", len(schema.records))
 print("RELATIONSHIP COUNT:", len(schema.relationships))
 print("RECORD TABLE MAP COUNT:", len(schema.record_table_map))
 print("FIELD MAP COUNT:", len(schema.field_map))
 print("DATE PART MAP COUNT:", len(schema.date_part_map))

 for record_name in sorted(schema.records.keys()):

```

```

 record = schema.records[record_name]
 print(f"RECORD: {record_name} PK={record.primary_key}")

 for field_name in sorted(record.fields.keys()):
 field = record.fields[field_name]
 print(
 " FIELD:",
 field_name,
 field.datatype,
 field.length,
 field.scale,
 "NULLABLE=",
 field.nullable,
)

 print("RELATIONSHIPS:")

 for set_name in sorted(schema.relationships.keys()):
 rel = schema.relationships[set_name]
 print(
 " REL:",
 set_name,
 rel.parent_record,
 rel.parent_key,
 "->",
 rel.child_record,
 rel.child_fk,
)

```

```

=====
FILE: src\idms_db2_converter\services\relationship_resolver.py
ENCODING: utf-8
=====

```

```
import json
```

```

from idms_db2_converter.exceptions import ConversionError
from idms_db2_converter.models import CobolAnalysis, Relationship, SchemaModel

```

```
class RelationshipResolver:
```

```
 """
```

```
 Resolves COBOL IDMS set names to schema relationships.
```

```
 No business-specific set names are hard-coded.
```

```
 Resolution order:
```

1. Use exact set name if already present.
2. Use relationship overrides if provided.
3. Use DDL-derived relationships if a COBOL set can be matched unambiguously.

```
 """
```

```
def apply_overrides(
```

```
 self,
```

```
 schema: SchemaModel,
```

```
 relationship_overrides_json: str,
```

```
) -> SchemaModel:
```

```
 try:
```

```
 payload = json.loads(relationship_overrides_json)
```

```
 except json.JSONDecodeError as exc:
```

```
 raise ConversionError(f"Invalid relationship override JSON: {exc}") from exc
```

```
 self._apply_record_aliases(schema, payload)
```

```
 for item in payload.get("relationships", []):
```

```
 self._apply_relationship_override(schema, item)
```

```
 return schema
```

```
def resolve_cobol_sets(
```

```
 self,
```

```
 schema: SchemaModel,
```

```
 analysis: CobolAnalysis,
```

```
) -> SchemaModel:
```

```
 references = self._collect_set_references(analysis)
```

```

for set_name, child_records in references.items():
 if set_name in schema.relationships:
 continue

 matched = self._find_unambiguous_relationship(
 schema=schema,
 set_name=set_name,
 child_records=child_records,
)

 if not matched:
 continue

 schema.relationships[set_name] = Relationship(
 set_name=set_name,
 parent_record=matched.parent_record,
 child_record=matched.child_record,
 cardinality=matched.cardinality,
 parent_key=matched.parent_key,
 child_fk=matched.child_fk,
 order_by=matched.order_by,
)

 schema.add_validation_message(
 f"Set {set_name} resolved from existing schema relationship "
 f"{matched.parent_record}-{matched.child_record}."
)

return schema

def _collect_set_references(
 self,
 analysis: CobolAnalysis,
) -> dict[str, set[str]]:
 references: dict[str, set[str]] = {}

 for record_name, set_name in analysis.obtain_next:
 references.setdefault(set_name, set()).add(record_name)

 for set_name in analysis.obtain_owner_sets:
 references.setdefault(set_name, set())

 for set_name in analysis.find_first_sets:
 references.setdefault(set_name, set())

 return references

def _apply_record_aliases(self, schema: SchemaModel, payload: dict) -> None:
 for item in payload.get("record_aliases", []):
 record_name = item["record"].upper()
 table_name = item["table"].upper()

 if table_name not in schema.records:
 raise ConversionError(
 f"Record alias {record_name} references unknown table {table_name}."
)

 schema.records[record_name] = schema.records[table_name]
 schema.record_table_map[record_name] = table_name

def _apply_relationship_override(self, schema: SchemaModel, item: dict) -> None:
 set_name = item["set_name"].upper()

 parent_record = self._upper_or_none(item.get("parent_record"))
 child_record = self._upper_or_none(item.get("child_record"))
 parent_key = self._upper_or_none(item.get("parent_key"))
 child_fk = self._upper_or_none(item.get("child_fk"))
 order_by = [value.upper() for value in item.get("order_by", [])]

 if set_name in schema.relationships:
 rel = schema.relationships[set_name]

 if parent_record:
 rel.parent_record = parent_record

```

```

 if child_record:
 rel.child_record = child_record

 if parent_key:
 rel.parent_key = parent_key

 if child_fk:
 rel.child_fk = child_fk

 if order_by:
 rel.order_by = order_by

 return

if parent_record and child_record:
 self._create_explicit_relationship(
 schema=schema,
 set_name=set_name,
 parent_record=parent_record,
 child_record=child_record,
 parent_key=parent_key,
 child_fk=child_fk,
 order_by=order_by,
)
 return

matched = self._find_relationship_by_keys(
 schema=schema,
 parent_key=parent_key,
 child_fk=child_fk,
)

if matched:
 schema.relationships[set_name] = Relationship(
 set_name=set_name,
 parent_record=matched.parent_record,
 child_record=matched.child_record,
 cardinality=matched.cardinality,
 parent_key=parent_key or matched.parent_key,
 child_fk=child_fk or matched.child_fk,
 order_by=order_by or matched.order_by,
)
 return

raise ConversionError(
 f"Override references set {set_name}, but it could not be resolved. "
 "Provide parent_record and child_record, or provide keys matching a DDL foreign key."
)

def _create_explicit_relationship(
 self,
 schema: SchemaModel,
 set_name: str,
 parent_record: str,
 child_record: str,
 parent_key: str | None,
 child_fk: str | None,
 order_by: list[str],
) -> None:
 if parent_record not in schema.records:
 raise ConversionError(
 f"Set {set_name} parent_record {parent_record} is not present in schema."
)

 if child_record not in schema.records:
 raise ConversionError(
 f"Set {set_name} child_record {child_record} is not present in schema."
)

 parent = schema.records[parent_record]
 child = schema.records[child_record]

 resolved_parent_key = parent_key or parent.primary_key

 if not resolved_parent_key:
 raise ConversionError(

```

```

 f"Set {set_name} cannot resolve parent_key."
)

 resolved_child_fk = child_fk

 if not resolved_child_fk and resolved_parent_key in child.fields:
 resolved_child_fk = resolved_parent_key

 if not resolved_child_fk:
 raise ConversionError(
 f"Set {set_name} cannot resolve child_fk."
)

 schema.relationships[set_name] = Relationship(
 set_name=set_name,
 parent_record=parent_record,
 child_record=child_record,
 cardinality="1:N",
 parent_key=resolved_parent_key,
 child_fk=resolved_child_fk,
 order_by=order_by or [resolved_child_fk],
)

def _find_relationship_by_keys(
 self,
 schema: SchemaModel,
 parent_key: str | None,
 child_fk: str | None,
) -> Relationship | None:
 if not parent_key and not child_fk:
 return None

 matches = []

 for rel in schema.relationships.values():
 if parent_key and rel.parent_key != parent_key:
 continue

 if child_fk and rel.child_fk != child_fk:
 continue

 matches.append(rel)

 if len(matches) == 1:
 return matches[0]

 if len(matches) > 1:
 raise ConversionError(
 "Relationship override is ambiguous. Add parent_record and child_record."
)

 return None

def _find_unambiguous_relationship(
 self,
 schema: SchemaModel,
 set_name: str,
 child_records: set[str],
) -> Relationship | None:
 candidates = list(schema.relationships.values())

 if child_records:
 filtered = [
 rel
 for rel in candidates
 if rel.child_record in child_records
]

 if filtered:
 candidates = filtered

 if len(candidates) == 1:
 return candidates[0]

 scored = []

```

```

 for rel in candidates:
 score = self._score_relationship(set_name, rel)

 if score > 0:
 scored.append((score, rel))

 if not scored:
 return None

 scored.sort(key=lambda item: item[0], reverse=True)

 top_score = scored[0][0]
 top_matches = [
 rel
 for score, rel in scored
 if score == top_score
]

 if len(top_matches) == 1:
 return top_matches[0]

 return None

def _score_relationship(self, set_name: str, rel: Relationship) -> int:
 tokens = [
 token
 for token in set_name.replace("_", "-").split("-")
 if token
]

 searchable_values = [
 rel.parent_record,
 rel.child_record,
 rel.parent_key or "",
 rel.child_fk or "",
]

 score = 0

 for token in tokens:
 for value in searchable_values:
 if self._token_matches(token, value):
 score += 1

 return score

def _token_matches(self, token: str, value: str) -> bool:
 token = token.upper()
 value = value.upper()

 return token in value or value in token

def _upper_or_none(self, value: str | None) -> str | None:
 return value.upper() if value else None

```

```

=====
FILE: src\idms_db2_converter\services\schema_merger.py
ENCODING: utf-8
=====

```

```

from copy import deepcopy
import re

from idms_db2_converter.generators.naming import Naming
from idms_db2_converter.models import Relationship, SchemaModel

```

```

class SchemaMerger:
 """
 Merge DB2 DDL schema with IDMS schema listing.

 Rules:
 - DDL wins for physical column definitions.
 - IDMS wins for legacy field names, IDMS set names, and field_map.
 """

```

```

def merge_physical_with_idms(
 self,
 physical_schema: SchemaModel,
 idms_schema: SchemaModel,
) -> SchemaModel:
 merged = deepcopy(physical_schema)

 if not getattr(merged, "schema_source", None):
 merged.schema_source = "DDL"

 merged.schema_source = f"{merged.schema_source}+IDMS_SCHEMA"

 self._build_record_table_map(merged, idms_schema)
 self._build_field_map_from_idms_to_physical(merged, idms_schema)
 self._build_date_part_map_from_idms_to_physical(merged, idms_schema)
 self._preserve_idms_set_names(merged, idms_schema)
 self._merge_validation_messages(merged, idms_schema)

 return merged

def _build_record_table_map(
 self,
 merged: SchemaModel,
 idms_schema: SchemaModel,
) -> None:
 for idms_record_name in idms_schema.records:
 physical_record_name = self._find_matching_record(
 schema=merged,
 record_name=idms_record_name,
)

 if physical_record_name:
 merged.record_table_map[idms_record_name] = physical_record_name
 else:
 merged.record_table_map[idms_record_name] = self._table_name(
 idms_record_name
)

def _build_field_map_from_idms_to_physical(
 self,
 merged: SchemaModel,
 idms_schema: SchemaModel,
) -> None:
 for idms_record_name in idms_schema.records:
 physical_record_name = merged.record_table_map.get(idms_record_name)

 if not physical_record_name:
 continue

 if physical_record_name not in merged.records:
 continue

 physical_record = merged.records[physical_record_name]

 for idms_field_name, meta in idms_schema.field_map.items():
 idms_host = str(meta.get("host", "")).upper()

 if not self._host_belongs_to_record(idms_host, idms_record_name):
 continue

 normalized_idms_field = self._normalize_field_name(idms_field_name)

 physical_column = self._find_physical_column(
 physical_record=physical_record,
 normalized_idms_field=normalized_idms_field,
 idms_host=idms_host,
 idms_record_name=idms_record_name,
)

 if not physical_column:
 continue

 merged.field_map[idms_field_name.upper()] = {
 "host": Naming.hv(idms_record_name, physical_column)
 }

```

```

def _build_date_part_map_from_idms_to_physical(
 self,
 merged: SchemaModel,
 idms_schema: SchemaModel,
) -> None:
 for idms_field_name, meta in idms_schema.date_part_map.items():
 idms_host = str(meta.get("host", "")).upper()

 idms_record_name = self._find_record_for_host(
 host=idms_host,
 record_names=list(idms_schema.records.keys()),
)

 if not idms_record_name:
 continue

 physical_record_name = merged.record_table_map.get(idms_record_name)

 if not physical_record_name:
 continue

 if physical_record_name not in merged.records:
 continue

 physical_record = merged.records[physical_record_name]

 idms_column = self._column_from_host(idms_host, idms_record_name)

 if not idms_column:
 continue

 physical_column = self._find_physical_column(
 physical_record=physical_record,
 normalized_idms_field=idms_column,
 idms_host=idms_host,
 idms_record_name=idms_record_name,
)

 if not physical_column:
 continue

 column = physical_record.fields[physical_column]

 substring_start = meta.get("substring_start")
 substring_length = meta.get("substring_length")

 if column.datatype.upper() == "DATE":
 part = self._date_part_name(idms_field_name)

 if part == "YEAR":
 substring_start = 3
 substring_length = 2
 elif part == "MONTH":
 substring_start = 6
 substring_length = 2
 elif part == "DAY":
 substring_start = 9
 substring_length = 2

 merged.date_part_map[idms_field_name.upper()] = {
 "host": Naming.hv(idms_record_name, physical_column),
 "substring_start": substring_start,
 "substring_length": substring_length,
 }

def _preserve_idms_set_names(
 self,
 merged: SchemaModel,
 idms_schema: SchemaModel,
) -> None:
 for set_name, idms_rel in idms_schema.relationships.items():
 idms_parent = idms_rel.parent_record
 idms_child = idms_rel.child_record

 physical_parent = merged.record_table_map.get(idms_parent)

```



```

physical_child = merged.record_table_map.get(idms_child)

if not physical_parent or not physical_child:
 continue

ddl_rel = self._find_relationship_by_records(
 schema=merged,
 parent_record=physical_parent,
 child_record=physical_child,
)

if ddl_rel:
 parent_key = ddl_rel.parent_key
 child_fk = ddl_rel.child_fk
 order_by = ddl_rel.order_by
else:
 parent_key = self._find_matching_column_name(
 record=merged.records[physical_parent],
 name=idms_rel.parent_key or "",
)

 child_fk = self._find_matching_column_name(
 record=merged.records[physical_child],
 name=idms_rel.child_fk or idms_rel.parent_key or "",
)

 order_by = [child_fk] if child_fk else []

if not parent_key or not child_fk:
 continue

merged.relationships[set_name] = Relationship(
 set_name=set_name,
 parent_record=idms_parent,
 child_record=idms_child,
 cardinality=idms_rel.cardinality or "1:N",
 parent_key=parent_key,
 child_fk=child_fk,
 order_by=order_by or [child_fk],
)

def _find_physical_column(
 self,
 physical_record,
 normalized_idms_field: str,
 idms_host: str,
 idms_record_name: str,
) -> str | None:
 direct = self._find_matching_column_name(
 record=physical_record,
 name=normalized_idms_field,
)

 if direct:
 return direct

 from_host = self._column_from_host(idms_host, idms_record_name)

 if from_host:
 direct = self._find_matching_column_name(
 record=physical_record,
 name=from_host,
)

 if direct:
 return direct

 singular = self._singularize(normalized_idms_field)

 if singular != normalized_idms_field:
 direct = self._find_matching_column_name(
 record=physical_record,
 name=singular,
)

 if direct:

```

```

 return direct

 return self._find_flattened_occurs_column(
 physical_record=physical_record,
 name=normalized_idms_field,
)

def _find_flattened_occurs_column(
 self,
 physical_record,
 name: str,
) -> str | None:
 candidates = [
 column_name
 for column_name in physical_record.fields
 if column_name.upper().startswith(name.upper() + "_")
]

 if not candidates:
 singular = self._singularize(name)
 candidates = [
 column_name
 for column_name in physical_record.fields
 if column_name.upper().startswith(singular.upper() + "_")
]

 if not candidates:
 return None

 return sorted(candidates)[0]

def _find_matching_record(
 self,
 schema: SchemaModel,
 record_name: str,
) -> str | None:
 record_name = record_name.upper()

 if record_name in schema.records:
 return record_name

 normalized = self._normalize_record_name(record_name)

 for candidate in schema.records:
 if self._normalize_record_name(candidate) == normalized:
 return candidate

 return None

def _find_matching_column_name(
 self,
 record,
 name: str,
) -> str | None:
 normalized = self._normalize_field_name(name)

 if normalized in record.fields:
 return normalized

 for column_name in record.fields:
 if column_name.upper() == normalized:
 return column_name

 return None

def _find_relationship_by_records(
 self,
 schema: SchemaModel,
 parent_record: str,
 child_record: str,
) -> Relationship | None:
 normalized_parent = self._normalize_record_name(parent_record)
 normalized_child = self._normalize_record_name(child_record)

 for relationship in schema.relationships.values():
 if (

```

```

 self._normalize_record_name(relationship.parent_record)
 == normalized_parent
 and self._normalize_record_name(relationship.child_record)
 == normalized_child
):
 return relationship

 return None

def _host_belongs_to_record(
 self,
 host: str,
 record_name: str,
) -> bool:
 normalized_host = self._normalize_token(host)
 normalized_record = self._normalize_token(record_name)

 return normalized_host.startswith(f"HV_{normalized_record}_")

def _find_record_for_host(
 self,
 host: str,
 record_names: list[str],
) -> str | None:
 normalized_host = self._normalize_token(host)

 for record_name in sorted(record_names, key=len, reverse=True):
 normalized_record = self._normalize_token(record_name)

 if normalized_host.startswith(f"HV_{normalized_record}_"):
 return record_name

 return None

def _column_from_host(
 self,
 host: str,
 record_name: str,
) -> str | None:
 normalized_host = self._normalize_token(host)
 normalized_record = self._normalize_token(record_name)

 prefix = f"HV_{normalized_record}_"

 if not normalized_host.startswith(prefix):
 return None

 return normalized_host[len(prefix):].upper()

def _date_part_name(
 self,
 idms_field_name: str,
) -> str | None:
 normalized = self._normalize_field_name(idms_field_name)

 if normalized.endswith("_YEAR"):
 return "YEAR"

 if normalized.endswith("_MONTH"):
 return "MONTH"

 if normalized.endswith("_DAY"):
 return "DAY"

 return None

def _normalize_token(
 self,
 value: str,
) -> str:
 return value.upper().replace("-", "_")

def _normalize_record_name(
 self,
 value: str,
) -> str:

```

```

 return value.upper().replace("-", "_")

def _normalize_field_name(
 self,
 value: str,
) -> str:
 value = value.upper()
 value = re.sub(r"-\d{4}$", "", value)
 return value.replace("-", "_")

def _singularize(
 self,
 value: str,
) -> str:
 value = value.upper()

 if value.endswith("IES"):
 return value[:-3] + "Y"

 if value.endswith("S"):
 return value[:-1]

 return value

def _table_name(
 self,
 record_name: str,
) -> str:
 return record_name.upper().replace("-", "_")

def _merge_validation_messages(
 self,
 merged: SchemaModel,
 overlay: SchemaModel,
) -> None:
 if hasattr(merged, "validation_messages") and hasattr(
 overlay,
 "validation_messages",
):
 merged.validation_messages.extend(overlay.validation_messages)

```

```

=====
FILE: src\idms_db2_converter\transformers__init__.py
ENCODING: utf-8
=====

```

[Empty file]

```

=====
FILE: src\idms_db2_converter\transformers\cobol_cleanup.py
ENCODING: utf-8
=====

```

```
import re
```

```

class CobolCleanup:
 """
 Final cleanup pass for generated COBOL.

 Goals:
 - Preserve EXEC SQL blocks.
 - Normalize PROCEDURE DIVISION formatting.
 - Fix END-IF, ELSE, CONTINUE, EXIT, GOBACK indentation.
 - Fix SQL indentation for common SQL clauses.
 - Fix READ ... AT END indentation.
 - Fix paragraph header concatenation.
 - Avoid changing DATA DIVISION and WORKING-STORAGE declarations.
 """

 EXEC_SQL_START = re.compile(
 r"^\s*EXEC\s+SQL\b",
 re.IGNORECASE,
)

```

```

EXEC_SQL_END = re.compile(
 r"^\\s*END-EXEC\\.?\\s*$",
 re.IGNORECASE,
)

PROCEDURE_DIVISION = re.compile(
 r"^\\s*PROCEDURE\\s+DIVISION\\.",
 re.IGNORECASE | re.MULTILINE,
)

PARAGRAPH_HEADER = re.compile(
 r"^\\s*[A-Z0-9-]+\\.\\s*$",
 re.IGNORECASE,
)

COMMENT_LINE = re.compile(
 r"^\\s**",
)

DEBUG_DISPLAY_LINE = re.compile(
 r"^\\s*D\\s+DISPLAY\\b",
 re.IGNORECASE,
)

def clean(
 self,
 text: str,
) -> str:
 text = self.fix_continue_concatenation(
 text,
)

 text = self.fix_paragraph_header_concatenation(
 text,
)

 text = self.repair_read_at_end(
 text,
)

 text = self.remove_end_processing_sqlcode_guard(
 text,
)

 text = self.normalize_procedure_division(
 text,
)

 text = self.fix_db2_check_status(
 text,
)

 text = self.force_procedure_keyword_indentation(
 text,
)

 text = self.normalize_sql_spacing(
 text,
)

 text = self.normalize_blank_lines(
 text,
)

 text = self.trim_trailing_spaces(
 text,
)

 return text

def normalize_procedure_division(
 self,
 text: str,
) -> str:
 match = self.PROCEDURE_DIVISION.search(

```

```

 text,
)

 if not match:
 return text

 before = text[:match.start()]
 procedure = text[match.start():]

 procedure = self.normalize_lines(
 procedure,
)

 return before + procedure

def normalize_lines(
 self,
 text: str,
) -> str:
 lines = text.splitlines()
 output: list[str] = []

 in_exec_sql = False

 for line in lines:
 stripped = line.strip()

 if not stripped:
 output.append("")
 continue

 if self.EXEC_SQL_START.match(line):
 in_exec_sql = True
 output.append(
 "EXEC SQL",
)
 continue

 if in_exec_sql:
 output.append(
 self.normalize_exec_sql_line(
 stripped,
)
)

 if self.EXEC_SQL_END.match(line):
 in_exec_sql = False

 continue

 if self.COMMENT_LINE.match(line):
 output.append(line)
 continue

 if self.DEBUG_DISPLAY_LINE.match(line):
 output.append(stripped)
 continue

 if self.PARAGRAPH_HEADER.match(line):
 output.append(stripped)
 continue

 output.append(
 self.normalize_procedure_line(
 stripped,
)
)

 return "\n".join(output)

def normalize_exec_sql_line(
 self,
 stripped: str,
) -> str:
 upper = stripped.upper()

```

```

if upper == "EXEC SQL":
 return " EXEC SQL"

if upper in {
 "END-EXEC",
 "END-EXEC.",
}:
 return " END-EXEC."

if upper == "COMMIT":
 return " COMMIT"

if upper in {
 "(",
 ")"",
}:
 return " " + stripped

if stripped.startswith(":"):
 return " " + stripped

if re.match(
 r"^[A-Z0-9_]+,?$",
 stripped,
 flags=re.IGNORECASE,
):
 return " " + stripped

if re.match(
 r"^(DECLARE|FETCH|OPEN|CLOSE|INSERT|UPDATE|DELETE|INCLUDE|BEGIN|END)\b",
 stripped,
 flags=re.IGNORECASE,
):
 return " " + stripped

if re.match(
 r"^SELECT\b",
 stripped,
 flags=re.IGNORECASE,
):
 return " " + stripped

if re.match(
 r"^(INTO|FROM|WHERE|ORDER\s+BY|FETCH\s+FIRST|SET|VALUES)\b",
 stripped,
 flags=re.IGNORECASE,
):
 return " " + stripped

if re.match(
 r"^[A-Z0-9_]+\s*=",
 stripped,
 flags=re.IGNORECASE,
):
 return " " + stripped

return " " + stripped

def normalize_procedure_line(
 self,
 stripped: str,
) -> str:
 upper = stripped.upper()

 if upper == "PROCEDURE DIVISION.":
 return "PROCEDURE DIVISION."

 if upper in {
 "END-IF",
 "END-IF.",
 }:
 return " END-IF."

 if upper in {
 "END-PERFORM",
 "END-PERFORM.",
 }

```

```

):
 return " END-PERFORM"

 if upper == "ELSE":
 return " ELSE"

 if upper in {
 "CONTINUE",
 "CONTINUE.",
 }:
 return " CONTINUE."

 if upper in {
 "EXIT",
 "EXIT.",
 }:
 return " EXIT."

 if upper in {
 "GOBACK",
 "GOBACK.",
 }:
 return " GOBACK."

 if upper == "THEN":
 return " THEN"

 if upper.startswith("THEN "):
 return " " + stripped

 if upper.startswith("AT END "):
 return " " + stripped

 if upper.startswith("DISPLAY "):
 return " " + stripped

 if self.is_common_procedure_statement(
 upper,
):
 return " " + stripped

 return stripped

def is_common_procedure_statement(
 self,
 upper: str,
) -> bool:
 prefixes = (
 "IF ",
 "MOVE ",
 "PERFORM ",
 "READ ",
 "WRITE ",
 "OPEN ",
 "CLOSE ",
 "ADD ",
 "SUBTRACT ",
 "MULTIPLY ",
 "DIVIDE ",
 "COMPUTE ",
 "GO TO ",
 "SET ",
 "CALL ",
 "EVALUATE ",
 "WHEN ",
 "END-EVALUATE",
 "PERFORM UNTIL ",
)

 return upper.startswith(prefixes)

def fix_db2_check_status(
 self,
 text: str,
) -> str:
 pattern = re.compile(

```



```

 r"""
 ^\s*DB2-CHECK-STATUS\.\s*
 \n\s*IF\s+SQLCODE\s+NOT\s*=\s*\0\s*
 \n\s*DISPLAY\s+'DB2\s+SQL\s+ERROR\s+SQLCODE='\s+SQLCODE\s*
 \n\s*END-IF\.?
 """,
 re.IGNORECASE | re.MULTILINE | re.VERBOSE,
)

 replacement = "\n".join(
 [
 "DB2-CHECK-STATUS.",
 " IF SQLCODE NOT = 0",
 " DISPLAY 'DB2 SQL ERROR SQLCODE=' SQLCODE",
 " END-IF.",
]
)

 return pattern.sub(
 replacement,
 text,
)

def repair_read_at_end(
 self,
 text: str,
) -> str:
 lines = text.splitlines()
 output: list[str] = []

 in_exec_sql = False

 for line in lines:
 stripped = line.strip()

 if self.EXEC_SQL_START.match(line):
 in_exec_sql = True
 output.append(line)
 continue

 if in_exec_sql:
 output.append(line)

 if self.EXEC_SQL_END.match(line):
 in_exec_sql = False

 continue

 if re.match(
 r"^AT\s+END\b",
 stripped,
 flags=re.IGNORECASE,
):
 output.append(
 " " + stripped,
)
 continue

 output.append(line)

 return "\n".join(output)

def remove_end_processing_sqlcode_guard(
 self,
 text: str,
) -> str:
 pattern = re.compile(
 r"""
 (\n\s*END-PROCESSING\.\s*)
 \n\s*IF\s+SQLCODE\s+NOT\s*=\s*\0\s*
 \n\s*PERFORM\s+SQL-ERROR\.\?\s*
 \n\s*END-IF\.?
 """,
 re.IGNORECASE | re.MULTILINE | re.VERBOSE,
)

```



```

)

procedure = re.sub(
 r"(?im)^\s*ELSE\s*$",
 " ELSE",
 procedure,
)

procedure = re.sub(
 r"(?im)^\s*GOBACK\.\?\s*$",
 " GOBACK.",
 procedure,
)

procedure = re.sub(
 r"(?im)^\s*EXIT\.\?\s*$",
 " EXIT.",
 procedure,
)

procedure = re.sub(
 r"(?im)^\s*DISPLAY\s+'DB2 SQL ERROR SQLCODE='\s+SQLCODE\s*$",
 " DISPLAY 'DB2 SQL ERROR SQLCODE=' SQLCODE",
 procedure,
)

procedure = re.sub(
 r"(?im)^\s*PERFORM\s+SQL-ERROR\.\?\s*$",
 " PERFORM SQL-ERROR",
 procedure,
)

return before + procedure

def normalize_sql_spacing(
 self,
 text: str,
) -> str:
 text = re.sub(
 r"(?im)^\s{12,}COMMIT\s*$",
 " COMMIT",
 text,
)

 text = re.sub(
 r"(?im)^\s{12,}VALUES\s*$",
 " VALUES",
 text,
)

 return text

def normalize_blank_lines(
 self,
 text: str,
) -> str:
 text = re.sub(
 r"\n{3,}",
 "\n\n",
 text,
)

 text = re.sub(
 r"\n\s+\n",
 "\n\n",
 text,
)

 return text

def trim_trailing_spaces(
 self,
 text: str,
) -> str:
 return re.sub(
 r"[\t]+$",

```

```

 "",
 text,
 flags=re.MULTILINE,
)

```

```

=====
FILE: src\idms_db2_converter\transformers\dml_transformer.py
ENCODING: utf-8
=====

```

```
import re
```

```

from idms_db2_converter.exceptions import ConversionError
from idms_db2_converter.generators.naming import Naming
from idms_db2_converter.models import CobolAnalysis, SchemaModel

```

```
class DmlTransformer:
```

```
 """
```

```
 Converts IDMS update DML to DB2 embedded SQL.
```

```
 Supported mappings:
```

```

- STORE record -> INSERT
- MODIFY record -> UPDATE
- ERASE record -> DELETE
- READY AREA ... USAGE-MODE IS UPDATE -> CONTINUE
- FINISH -> COMMIT for update programs

```

```
 Important behavior:
```

```

- MODIFY updates only fields moved in the same paragraph before MODIFY.
- If changed fields cannot be detected, MODIFY falls back to non-key fields.
- Primary key resolution prefers ID columns such as EMP_ID_0415.
 """

```

```

STORE_RECORD = re.compile(
 r"^\s*STORE\s+([A-Z0-9-]+)\.?\s*$",
 re.IGNORECASE | re.MULTILINE,
)

```

```

MODIFY_RECORD = re.compile(
 r"^\s*MODIFY\s+([A-Z0-9-]+)\.?\s*$",
 re.IGNORECASE | re.MULTILINE,
)

```

```

ERASE_RECORD = re.compile(
 r"^\s*ERASE\s+([A-Z0-9-]+)\.?\s*$",
 re.IGNORECASE | re.MULTILINE,
)

```

```

READY_UPDATE_BLOCK = re.compile(
 r"""
 ^\s*READY\s+AREA\s+([A-Z0-9-]+)\.?\s*
 (?:\n\s*USAGE-MODE\s+IS\s+UPDATE\.?\s*)?
 (?:\n\s*PERFORM\s+IDMS-STATUS\.?\s*)?
 """,
 re.IGNORECASE | re.MULTILINE | re.VERBOSE,
)

```

```

READY_AREA_LINE = re.compile(
 r"^\s*READY\s+AREA\s+([A-Z0-9-]+)\.?\s*$",
 re.IGNORECASE | re.MULTILINE,
)

```

```

USAGE_MODE_UPDATE_LINE = re.compile(
 r"^\s*USAGE-MODE\s+IS\s+UPDATE\.?\s*$",
 re.IGNORECASE | re.MULTILINE,
)

```

```

FINISH_LINE = re.compile(
 r"^\s*FINISH\.?\s*$",
 re.IGNORECASE | re.MULTILINE,
)

```

```

IDMS_STATUS_PERFORM = re.compile(
 r"^\s*PERFORM\s+IDMS-STATUS\.?\s*$",

```

```

 re.IGNORECASE | re.MULTILINE,
)

 PARAGRAPH_HEADER = re.compile(
 r"^\s*[A-Z0-9-]+\.\s*$",
 re.IGNORECASE | re.MULTILINE,
)

 MOVE_TO_TARGET = re.compile(
 r"^\s*MOVE\s+.+\?\s+TO\s+([A-Z0-9_-]+\.\?\s*$",
 re.IGNORECASE,
)

 def __init__(
 self,
 schema: SchemaModel,
 analysis: CobolAnalysis,
) -> None:
 self.schema = schema
 self.analysis = analysis

 def has_update_dml(
 self,
) -> bool:
 return bool(
 getattr(self.analysis, "store_records", [])
 or getattr(self.analysis, "modify_records", [])
 or getattr(self.analysis, "erase_records", [])
 or getattr(self.analysis, "ready_update_areas", [])
)

 def transform(
 self,
 text: str,
) -> str:
 if not self.has_update_dml():
 return text

 text = self.remove_ready_update_area(text)
 text = self.replace_store(text)
 text = self.replace_modify(text)
 text = self.replace_erase(text)
 text = self.replace_finish_with_commit(text)
 text = self.remove_residual_idms_status(text)
 text = self.remove_residual_ready_update_lines(text)
 text = self.fix_continue_concatenation(text)
 text = self.fix_status_paragraph_formatting(text)
 text = self.insert_db2_check_status_paragraph(text)
 text = self.normalize_blank_lines(text)

 return text

 def remove_ready_update_area(
 self,
 text: str,
) -> str:
 return self.READY_UPDATE_BLOCK.sub(
 "\n CONTINUE.\n",
 text,
)

 def remove_residual_ready_update_lines(
 self,
 text: str,
) -> str:
 text = self.READY_AREA_LINE.sub(
 " CONTINUE.",
 text,
)

 text = self.USAGE_MODE_UPDATE_LINE.sub(
 "",
 text,
)

 return text

```

```

def replace_store(
 self,
 text: str,
) -> str:
 def replacement(match: re.Match) -> str:
 record_name = match.group(1).upper()
 return self.insert_sql(record_name)

 return self.STORE_RECORD.sub(
 replacement,
 text,
)

def replace_modify(
 self,
 text: str,
) -> str:
 matches = list(
 self.MODIFY_RECORD.finditer(text),
)

 if not matches:
 return text

 pieces: list[str] = []
 last_position = 0

 for match in matches:
 record_name = match.group(1).upper()

 pieces.append(
 text[last_position:match.start()],
)

 changed_columns = self.changed_columns_before_modify(
 text=text,
 modify_position=match.start(),
 logical_record_name=record_name,
)

 pieces.append(
 self.update_sql(
 logical_record_name=record_name,
 changed_columns=changed_columns,
),
)

 last_position = match.end()

 pieces.append(
 text[last_position:],
)

 return "".join(pieces)

def replace_erase(
 self,
 text: str,
) -> str:
 def replacement(match: re.Match) -> str:
 record_name = match.group(1).upper()
 return self.delete_sql(record_name)

 return self.ERASE_RECORD.sub(
 replacement,
 text,
)

def replace_finish_with_commit(
 self,
 text: str,
) -> str:
 return self.FINISH_LINE.sub(
 self.commit_sql(),
 text,
)

```

```

)

def remove_residual_idms_status(
 self,
 text: str,
) -> str:
 return self.IDMS_STATUS_PERFORM.sub(
 "",
 text,
)

def fix_continue_concatenation(
 self,
 text: str,
) -> str:
 text = re.sub(
 r"CONTINUE\\.s*PERFORM\s+IDMS-STATUS\\.?",
 "CONTINUE.",
 text,
 flags=re.IGNORECASE,
)

 text = re.sub(
 r"CONTINUE\.[A-Z0-9-]+\.",
 r"CONTINUE.\n1",
 text,
 flags=re.IGNORECASE,
)

 return text

def fix_status_paragraph_formatting(
 self,
 text: str,
) -> str:
 text = re.sub(
 r"(?m)^END-IF\.",
 " END-IF.",
 text,
)

 return text

def insert_sql(
 self,
 logical_record_name: str,
) -> str:
 physical_record_name = self.physical_record_name(
 logical_record_name,
)

 record = self.schema.records.get(
 physical_record_name,
)

 if not record:
 raise ConversionError(
 f"STORE references missing record {logical_record_name}."
)

 columns = list(
 record.fields.keys(),
)

 if not columns:
 raise ConversionError(
 f"STORE record {logical_record_name} has no DB2 columns."
)

 value_items = [
 self.host_with_indicator(
 logical_record_name=logical_record_name,
 column_name=column_name,
 nullable=record.fields[column_name].nullable,
)
 for column_name in columns
]

```

```

]

lines: list[str] = [
 "EXEC SQL",
 f"INSERT INTO {physical_record_name}",
 "(",
]

lines.extend(
 self.sql_list_lines(
 items=columns,
 indent=" ",
)
)

lines.extend(
 [
 ")",
 "VALUES",
 "(",
]
)

lines.extend(
 self.sql_list_lines(
 items=value_items,
 indent=" ",
)
)

lines.extend(
 [
 ")",
 "END-EXEC.",
 "PERFORM DB2-CHECK-STATUS.",
]
)

return "\n".join(lines)

def update_sql(
 self,
 logical_record_name: str,
 changed_columns: list[str],
) -> str:
 physical_record_name = self.physical_record_name(
 logical_record_name,
)

 record = self.schema.records.get(
 physical_record_name,
)

 if not record:
 raise ConversionError(
 f"MODIFY references missing record {logical_record_name}."
)

 primary_key = self.resolve_primary_key(
 logical_record_name=logical_record_name,
 physical_record_name=physical_record_name,
)

 if not primary_key:
 raise ConversionError(
 f"MODIFY record {logical_record_name} has no primary key."
)

 update_columns = [
 column_name
 for column_name in changed_columns
 if column_name in record.fields
 and column_name != primary_key
]

 if not update_columns:

```



```

 update_columns = [
 column_name
 for column_name in record.fields.keys()
 if column_name != primary_key
]

 if not update_columns:
 raise ConversionError(
 f"MODIFY record {logical_record_name} has no update columns."
)

 key_host = Naming.hv(
 logical_record_name,
 primary_key,
)

 lines: list[str] = [
 " EXEC SQL",
 f" UPDATE {physical_record_name}",
]

 for index, column_name in enumerate(update_columns):
 column = record.fields[column_name]

 host = self.host_with_indicator(
 logical_record_name=logical_record_name,
 column_name=column_name,
 nullable=column.nullable,
)

 suffix = "," if index < len(update_columns) - 1 else ""

 if index == 0:
 lines.append(
 f" SET {column_name} =",
)
 else:
 lines.append(
 f" {column_name} =",
)

 lines.append(
 f" {host}{suffix}",
)

 lines.extend(
 [
 f" WHERE {primary_key} =",
 f" :{key_host}",
 " END-EXEC.",
 " PERFORM DB2-CHECK-STATUS.",
]
)

 return "\n".join(lines)

def delete_sql(
 self,
 logical_record_name: str,
) -> str:
 physical_record_name = self.physical_record_name(
 logical_record_name,
)

 record = self.schema.records.get(
 physical_record_name,
)

 if not record:
 raise ConversionError(
 f"ERASE references missing record {logical_record_name}."
)

 primary_key = self.resolve_primary_key(
 logical_record_name=logical_record_name,
 physical_record_name=physical_record_name,
)

```

```

)

if not primary_key:
 raise ConversionError(
 f"ERASE record {logical_record_name} has no primary key."
)

key_host = Naming.hv(
 logical_record_name,
 primary_key,
)

return "\n".join(
 [
 " EXEC SQL",
 f" DELETE FROM {physical_record_name}",
 f" WHERE {primary_key} =",
 f" :{key_host}",
 " END-EXEC.",
 " PERFORM DB2-CHECK-STATUS.",
]
)

def commit_sql(
 self,
) -> str:
 return "\n".join(
 [
 " EXEC SQL",
 " COMMIT",
 " END-EXEC.",
 " PERFORM DB2-CHECK-STATUS.",
]
)

def insert_db2_check_status_paragraph(
 self,
 text: str,
) -> str:
 if re.search(
 r"^s*DB2-CHECK-STATUS\.\s*$",
 text,
 flags=re.IGNORECASE | re.MULTILINE,
):
 return text

 paragraph = "\n".join(
 [
 "",
 "DB2-CHECK-STATUS.",
 " IF SQLCODE NOT = 0",
 " DISPLAY 'DB2 SQL ERROR SQLCODE=' SQLCODE",
 " END-IF.",
 "",
]
)

 if re.search(
 r"\n\s*MAIN-LINE\.",
 text,
 flags=re.IGNORECASE,
):
 return re.sub(
 r"(?=\n\s*MAIN-LINE\.)",
 paragraph,
 text,
 count=1,
 flags=re.IGNORECASE,
)

 return text.rstrip() + paragraph

def changed_columns_before_modify(
 self,
 text: str,
 modify_position: int,

```

```

 logical_record_name: str,
) -> list[str]:
 paragraph_text = self.current_paragraph_text(
 text=text,
 position=modify_position,
)

 physical_record_name = self.physical_record_name(
 logical_record_name,
)

 record = self.schema.records.get(
 physical_record_name,
)

 if not record:
 return []

 changed_columns: list[str] = []
 seen: set[str] = set()

 for line in paragraph_text.splitlines():
 match = self.MOVE_TO_TARGET.match(
 line,
)

 if not match:
 continue

 target = match.group(1).upper()

 column_name = self.column_from_move_target(
 logical_record_name=logical_record_name,
 physical_record_name=physical_record_name,
 target=target,
)

 if not column_name:
 continue

 if column_name not in record.fields:
 continue

 if column_name in seen:
 continue

 seen.add(
 column_name,
)

 changed_columns.append(
 column_name,
)

 return changed_columns

 def current_paragraph_text(
 self,
 text: str,
 position: int,
) -> str:
 paragraph_start = 0

 for match in self.PARAGRAPH_HEADER.finditer(
 text,
 0,
 position,
):
 paragraph_start = match.start()

 return text[paragraph_start:position]

 def column_from_move_target(
 self,
 logical_record_name: str,
 physical_record_name: str,

```

```

 target: str,
) -> str | None:
 record = self.schema.records.get(
 physical_record_name,
)

 if not record:
 return None

 target = target.upper().rstrip(".")
 target_as_column = self.normalize_column_token(
 target,
)

 direct = self.find_matching_column(
 record_fields=list(record.fields.keys()),
 candidate=target_as_column,
)

 if direct:
 return direct

 field_map_result = self.column_from_field_map(
 logical_record_name=logical_record_name,
 target=target,
 record_fields=list(record.fields.keys()),
)

 if field_map_result:
 return field_map_result

 host_result = self.column_from_host_variable(
 logical_record_name=logical_record_name,
 target=target,
 record_fields=list(record.fields.keys()),
)

 if host_result:
 return host_result

 return None

def column_from_field_map(
 self,
 logical_record_name: str,
 target: str,
 record_fields: list[str],
) -> str | None:
 field_map = getattr(
 self.schema,
 "field_map",
 {},
)

 meta = field_map.get(
 target.upper(),
)

 if not meta:
 return None

 column = meta.get(
 "column",
)

 if column:
 matched = self.find_matching_column(
 record_fields=record_fields,
 candidate=self.normalize_column_token(str(column)),
)

 if matched:
 return matched

 host = meta.get(
 "host",
)

```

```

)

 if host:
 return self.column_from_host_variable(
 logical_record_name=logical_record_name,
 target=str(host).upper(),
 record_fields=record_fields,
)

 return None

def column_from_host_variable(
 self,
 logical_record_name: str,
 target: str,
 record_fields: list[str],
) -> str | None:
 normalized_target = target.upper().replace("_", "-")
 normalized_record = logical_record_name.upper().replace("_", "-")
 prefix = f"HV-{normalized_record}-"

 if not normalized_target.startswith(prefix):
 return None

 column_part = normalized_target[len(prefix):]
 candidate = self.normalize_column_token(
 column_part,
)

 return self.find_matching_column(
 record_fields=record_fields,
 candidate=candidate,
)

def find_matching_column(
 self,
 record_fields: list[str],
 candidate: str,
) -> str | None:
 candidate = candidate.upper()

 for field_name in record_fields:
 if field_name.upper() == candidate:
 return field_name

 candidate_hyphen = candidate.replace("_", "-")

 for field_name in record_fields:
 if field_name.upper().replace("_", "-") == candidate_hyphen:
 return field_name

 return None

def resolve_primary_key(
 self,
 logical_record_name: str,
 physical_record_name: str,
) -> str | None:
 record = self.schema.records.get(
 physical_record_name,
)

 if not record:
 return None

 record_fields = list(
 record.fields.keys(),
)

 preferred_id = self.preferred_id_column(
 logical_record_name=logical_record_name,
 record_fields=record_fields,
)

 if preferred_id:
 return preferred_id

```

```

 calc_key = self.primary_key_from_calc_key_map(
 logical_record_name=logical_record_name,
 physical_record_name=physical_record_name,
 record_fields=record_fields,
)

 if calc_key:
 return calc_key

 if record.primary_key:
 matched_primary_key = self.find_matching_column(
 record_fields=record_fields,
 candidate=self.normalize_column_token(record.primary_key),
)

 if matched_primary_key:
 return matched_primary_key

 if record_fields:
 return record_fields[0]

 return None

def preferred_id_column(
 self,
 logical_record_name: str,
 record_fields: list[str],
) -> str | None:
 id_columns = [
 field_name
 for field_name in record_fields
 if re.search(
 r"^(^|_)ID(_|$)",
 field_name.upper(),
)
]

 if not id_columns:
 return None

 logical_prefix = logical_record_name.upper().replace("-", "_").split("_")[0]

 for field_name in id_columns:
 first_token = field_name.upper().split("_")[0]

 if first_token.startswith(
 logical_prefix[:3],
):
 return field_name

 return id_columns[0]

def primary_key_from_calc_key_map(
 self,
 logical_record_name: str,
 physical_record_name: str,
 record_fields: list[str],
) -> str | None:
 calc_key_map = getattr(
 self.schema,
 "calc_key_map",
 {},
)

 possible_keys = [
 logical_record_name.upper(),
 logical_record_name.upper().replace("-", "_"),
 physical_record_name.upper(),
 physical_record_name.upper().replace("-", "_"),
]

 for key in possible_keys:
 meta = calc_key_map.get(
 key,
)

```

```

 if not meta:
 continue

 calc_key = (
 meta.get("key")
 or meta.get("primary_key")
 or meta.get("column")
)

 if not calc_key:
 continue

 matched = self.find_matching_column(
 record_fields=record_fields,
 candidate=self.normalize_column_token(str(calc_key)),
)

 if matched:
 return matched

 return None

def physical_record_name(
 self,
 logical_record_name: str,
) -> str:
 logical_record_name = logical_record_name.upper()

 mapped = self.schema.record_table_map.get(
 logical_record_name,
)

 if mapped and mapped in self.schema.records:
 return mapped

 normalized = logical_record_name.replace(
 "-",
 "_",
)

 mapped = self.schema.record_table_map.get(
 normalized,
)

 if mapped and mapped in self.schema.records:
 return mapped

 if logical_record_name in self.schema.records:
 return logical_record_name

 if normalized in self.schema.records:
 return normalized

 return logical_record_name

def host_with_indicator(
 self,
 logical_record_name: str,
 column_name: str,
 nullable: bool,
) -> str:
 host = f":{Naming.hv(logical_record_name, column_name)}"

 if nullable:
 host += f" :{Naming.ni(logical_record_name, column_name)}"

 return host

def normalize_column_token(
 self,
 value: str,
) -> str:
 return (
 value.upper()
 .strip()
)

```

```

 .rstrip(".")
 .replace("-", "_")
 .replace(" ", "_")
)

def sql_list_lines(
 self,
 items: list[str],
 indent: str,
) -> list[str]:
 lines: list[str] = []

 for index, item in enumerate(items):
 suffix = "," if index < len(items) - 1 else ""

 lines.append(
 f"{indent}{item}{suffix}",
)

 return lines

def normalize_blank_lines(
 self,
 text: str,
) -> str:
 text = re.sub(
 r"\n{3,}",
 "\n\n",
 text,
)

 return text

```

```

=====
FILE: src\idms_db2_converter\transformers\field_rewriter.py
ENCODING: utf-8
=====

```

```

import json
import re

from datetime import datetime
from typing import Any

from idms_modernizer.domain.canonical_models import CanonicalSchema
from idms_modernizer.domain.db2_models import DB2Model, DB2Table, DB2Column
from idms_modernizer.domain.schema_models import SchemaMetadata
from idms_modernizer.services.name_normalizer import NameNormalizer

```

```

class Phase2MetadataGenerator:
 """
 Generates Phase 2 metadata JSON from Phase 1 outputs.

```

```

 Supports:
 - Record/table mapping.
 - Field/column host variable mapping.
 - Date part mapping for:
 YEAR / MONTH / DAY
 YR / MO / DY
 Y / M / D
 YY / MM / DD
 YYYY / MM / DD
 DY / DM / DD
 - CALC key mapping.
 - FK/nullability hints.
 - Set relationship payload.
 """

```

```

VERSION = "1.0"

```

```

DATE_PARTS = {
 "YEAR": {
 "substring_start": 3,
 "substring_length": 2,

```



```

 },
 "MONTH": {
 "substring_start": 6,
 "substring_length": 2,
 },
 "DAY": {
 "substring_start": 9,
 "substring_length": 2,
 },
}

YEAR_PARTS = {
 "YEAR",
 "YR",
 "Y",
 "YY",
 "YYYY",
 "DY",
}

MONTH_PARTS = {
 "MONTH",
 "MON",
 "MO",
 "M",
 "MM",
 "DM",
}

DAY_PARTS = {
 "DAY",
 "D",
 "DD",
}

def generate_json(
 self,
 canonical_schema: CanonicalSchema,
 db2_model: DB2Model,
 metadata: SchemaMetadata,
) -> str:
 payload = self.generate(
 canonical_schema=canonical_schema,
 db2_model=db2_model,
 metadata=metadata,
)

 return json.dumps(
 payload,
 indent=2,
)

def generate(
 self,
 canonical_schema: CanonicalSchema,
 db2_model: DB2Model,
 metadata: SchemaMetadata,
) -> dict[str, Any]:
 db2_table_lookup = self.build_db2_table_lookup(
 db2_model=db2_model,
)

 canonical_record_lookup = self.build_canonical_record_lookup(
 canonical_schema=canonical_schema,
)

 record_table_map = self.build_record_table_map(
 canonical_schema=canonical_schema,
 metadata=metadata,
)

 records_payload = self.build_records_payload(
 db2_model=db2_model,
)

 field_map = self.build_field_map(

```

```

 metadata=metadata,
 canonical_schema=canonical_schema,
 db2_table_lookup=db2_table_lookup,
 record_table_map=record_table_map,
)

 calc_key_map = self.build_calc_key_map(
 canonical_schema=canonical_schema,
 metadata=metadata,
 record_table_map=record_table_map,
)

 relationships_payload = self.build_relationships_payload(
 canonical_schema=canonical_schema,
 db2_table_lookup=db2_table_lookup,
)

 set_ordering_map = self.build_set_ordering_map(
 relationships=relationships_payload,
)

 nullable_fk_map = self.build_nullable_fk_map(
 db2_model=db2_model,
)

 date_part_map = self.build_date_part_map(
 metadata=metadata,
 db2_table_lookup=db2_table_lookup,
 record_table_map=record_table_map,
)

 navigation_intent = self.build_navigation_intent(
 relationships=relationships_payload,
)

 output_semantics = self.build_output_semantics()

 validation_messages = self.build_validation_messages(
 canonical_schema=canonical_schema,
 db2_model=db2_model,
 metadata=metadata,
 field_map=field_map,
)

 return {
 "version": self.VERSION,
 "generated_at": datetime.utcnow().isoformat() + "Z",
 "records": records_payload,
 "record_table_map": record_table_map,
 "field_map": field_map,
 "calc_key_map": calc_key_map,
 "relationships": relationships_payload,
 "set_ordering_map": set_ordering_map,
 "nullable_fk_map": nullable_fk_map,
 "date_part_map": date_part_map,
 "navigation_intent": navigation_intent,
 "output_semantics": output_semantics,
 "validation_messages": validation_messages,
 "canonical_record_lookup_count": len(canonical_record_lookup),
 }

def build_db2_table_lookup(
 self,
 db2_model: DB2Model,
) -> dict[str, DB2Table]:
 lookup: dict[str, DB2Table] = {}

 for table in getattr(db2_model, "tables", []) or []:
 table_name = NameNormalizer.normalize(
 getattr(table, "name", ""),
)

 if table_name:
 lookup[table_name] = table

 suffix_removed = self.remove_record_suffix(

```

```

 table_name,
)

 if suffix_removed:
 lookup[suffix_removed] = table

 return lookup

def build_canonical_record_lookup(
 self,
 canonical_schema: CanonicalSchema,
) -> dict[str, Any]:
 lookup: dict[str, Any] = {}

 for record in getattr(canonical_schema, "records", []) or []:
 record_name = NameNormalizer.normalize(
 getattr(record, "name", ""),
)

 if record_name:
 lookup[record_name] = record

 return lookup

def build_record_table_map(
 self,
 canonical_schema: CanonicalSchema,
 metadata: SchemaMetadata,
) -> dict[str, str]:
 record_table_map: dict[str, str] = {}

 for record in getattr(canonical_schema, "records", []) or []:
 canonical_name = NameNormalizer.normalize(
 getattr(record, "name", ""),
)

 if canonical_name:
 record_table_map[canonical_name] = canonical_name

 for record in getattr(metadata, "records", []) or []:
 metadata_name = NameNormalizer.normalize(
 getattr(record, "name", ""),
)

 if metadata_name and metadata_name not in record_table_map:
 record_table_map[metadata_name] = metadata_name

 return record_table_map

def build_records_payload(
 self,
 db2_model: DB2Model,
) -> list[dict[str, Any]]:
 records_payload: list[dict[str, Any]] = []

 for table in getattr(db2_model, "tables", []) or []:
 fields_payload: list[dict[str, Any]] = []

 for column in getattr(table, "columns", []) or []:
 datatype, length, scale = self.parse_db2_datatype(
 getattr(column, "datatype", ""),
)

 fields_payload.append(
 {
 "name": getattr(column, "name", ""),
 "column": getattr(column, "name", ""),
 "datatype": datatype,
 "length": length,
 "scale": scale,
 "nullable": getattr(column, "nullable", True),
 "primary_key": getattr(column, "primary_key", False),
 }
)

 records_payload.append(

```

```

 {
 "name": getattr(table, "name", ""),
 "table": getattr(table, "name", ""),
 "primary_key": getattr(table, "primary_key", None),
 "fields": fields_payload,
 }
)

 return records_payload

def build_field_map(
 self,
 metadata: SchemaMetadata,
 canonical_schema: CanonicalSchema,
 db2_table_lookup: dict[str, DB2Table],
 record_table_map: dict[str, str],
) -> dict[str, dict[str, Any]]:
 field_map: dict[str, dict[str, Any]] = {}

 for record in getattr(metadata, "records", []) or []:
 idms_record_name = NameNormalizer.normalize(
 getattr(record, "name", ""),
)

 if not idms_record_name:
 continue

 table_name = record_table_map.get(
 idms_record_name,
 idms_record_name,
)

 table = db2_table_lookup.get(
 table_name,
)

 if table is None:
 continue

 db2_columns = {
 NameNormalizer.normalize(getattr(column, "name", "")): column
 for column in getattr(table, "columns", []) or []
 }

 source_fields = (
 getattr(record, "mapping_fields", None)
 or getattr(record, "fields", [])
 or []
)

 for field in source_fields:
 legacy_field_name = NameNormalizer.normalize(
 getattr(field, "name", ""),
)

 if not legacy_field_name:
 continue

 physical_column_name = self.find_matching_column(
 legacy_field_name=legacy_field_name,
 db2_columns=db2_columns,
)

 if not physical_column_name:
 continue

 host = self.host_variable(
 record_name=idms_record_name,
 column_name=physical_column_name,
 remove_suffix=True,
)

 field_map[legacy_field_name] = {
 "host": host,
 "record": idms_record_name,
 "table": table.name,
 }

```

```

 "column": physical_column_name,
 "legacy_field": legacy_field_name,
 }

 suffix_removed_legacy = self.remove_record_suffix(
 legacy_field_name,
)

 if suffix_removed_legacy and suffix_removed_legacy not in field_map:
 field_map[suffix_removed_legacy] = {
 "host": host,
 "record": idms_record_name,
 "table": table.name,
 "column": physical_column_name,
 "legacy_field": legacy_field_name,
 }

 return field_map

def build_calc_key_map(
 self,
 canonical_schema: CanonicalSchema,
 metadata: SchemaMetadata,
 record_table_map: dict[str, str],
) -> dict[str, dict[str, Any]]:
 calc_key_map: dict[str, dict[str, Any]] = {}

 for record in getattr(metadata, "records", []) or []:
 primary_key = getattr(record, "primary_key", None)

 if not primary_key:
 continue

 idms_record_name = NameNormalizer.normalize(
 getattr(record, "name", ""),
)

 table_name = record_table_map.get(
 idms_record_name,
 idms_record_name,
)

 normalized_primary_key = NameNormalizer.normalize(
 primary_key,
)

 calc_key_map[idms_record_name] = {
 "record": idms_record_name,
 "table": table_name,
 "key": normalized_primary_key,
 "primary_key": normalized_primary_key,
 "column": normalized_primary_key,
 "host": self.host_variable(
 record_name=idms_record_name,
 column_name=normalized_primary_key,
 remove_suffix=True,
),
 }

 for record in getattr(canonical_schema, "records", []) or []:
 primary_key = getattr(record, "primary_key", None)

 if not primary_key:
 continue

 record_name = NameNormalizer.normalize(
 getattr(record, "name", ""),
)

 normalized_primary_key = NameNormalizer.normalize(
 primary_key,
)

 if record_name not in calc_key_map:
 calc_key_map[record_name] = {
 "record": record_name,

```

```

 "table": record_name,
 "key": normalized_primary_key,
 "primary_key": normalized_primary_key,
 "column": normalized_primary_key,
 "host": self.host_variable(
 record_name=record_name,
 column_name=normalized_primary_key,
 remove_suffix=True,
),
 }

 return calc_key_map

def build_relationships_payload(
 self,
 canonical_schema: CanonicalSchema,
 db2_table_lookup: dict[str, DB2Table],
) -> list[dict[str, Any]]:
 relationships_payload: list[dict[str, Any]] = []

 for relationship in getattr(canonical_schema, "relationships", []) or []:
 parent_record = NameNormalizer.normalize(
 getattr(relationship, "parent_record", ""),
)

 child_record = NameNormalizer.normalize(
 getattr(relationship, "child_record", ""),
)

 set_name = NameNormalizer.normalize(
 getattr(relationship, "set_name", ""),
)

 parent_table = db2_table_lookup.get(
 parent_record,
)

 child_table = db2_table_lookup.get(
 child_record,
)

 parent_key = (
 getattr(parent_table, "primary_key", None)
 if parent_table is not None
 else None
)

 child_fk = None
 order_by: list[str] = []

 if child_table is not None:
 for foreign_key in getattr(child_table, "foreign_keys", []) or []:
 if (
 parent_table is not None
 and NameNormalizer.normalize(getattr(foreign_key, "reference_table", ""))
 == NameNormalizer.normalize(getattr(parent_table, "name", ""))
):
 child_fk = getattr(foreign_key, "column_name", None)
 order_by = [child_fk] if child_fk else []
 break

 relationships_payload.append(
 {
 "set_name": set_name,
 "parent_record": parent_record,
 "child_record": child_record,
 "parent_key": parent_key,
 "child_fk": child_fk,
 "cardinality": getattr(relationship, "cardinality", "1:N") or "1:N",
 "order_by": order_by,
 }
)

 return relationships_payload

def build_set_ordering_map(

```

```

self,
relationships: list[dict[str, Any]],
) -> dict[str, dict[str, Any]]:
 set_ordering_map: dict[str, dict[str, Any]] = {}

 for relationship in relationships:
 set_name = relationship.get(
 "set_name",
)

 if not set_name:
 continue

 set_ordering_map[set_name] = {
 "order_by": relationship.get("order_by") or [],
 }

 return set_ordering_map

def build_nullable_fk_map(
 self,
 db2_model: DB2Model,
) -> dict[str, bool]:
 nullable_fk_map: dict[str, bool] = {}

 for table in getattr(db2_model, "tables", []) or []:
 column_lookup = {
 getattr(column, "name", ""): column
 for column in getattr(table, "columns", []) or []
 }

 for foreign_key in getattr(table, "foreign_keys", []) or []:
 fk_column_name = getattr(foreign_key, "column_name", "")
 fk_column = column_lookup.get(fk_column_name)

 nullable_fk_map[f"{table.name}.{fk_column_name}"] = (
 getattr(fk_column, "nullable", True)
 if fk_column is not None
 else True
)

 return nullable_fk_map

def build_date_part_map(
 self,
 metadata: SchemaMetadata,
 db2_table_lookup: dict[str, DB2Table],
 record_table_map: dict[str, str],
) -> dict[str, dict[str, Any]]:
 date_part_map: dict[str, dict[str, Any]] = {}

 for record in getattr(metadata, "records", []) or []:
 idms_record_name = NameNormalizer.normalize(
 getattr(record, "name", "")
)

 if not idms_record_name:
 continue

 table_name = record_table_map.get(
 idms_record_name,
 idms_record_name,
)

 table = db2_table_lookup.get(
 table_name,
)

 if table is None:
 continue

 date_columns = {
 NameNormalizer.normalize(getattr(column, "name", "")): column
 for column in getattr(table, "columns", []) or []
 if str(getattr(column, "datatype", "")).upper() == "DATE"
 }

```

```

source_fields = (
 getattr(record, "mapping_fields", None)
 or getattr(record, "fields", [])
 or []
)

for field in source_fields:
 legacy_field_name = NameNormalizer.normalize(
 getattr(field, "name", ""),
)

 parsed = self.parse_date_part(
 field_name=legacy_field_name,
)

 if parsed is None:
 continue

 part = parsed["part"]
 candidate_columns = parsed["candidate_columns"]

 physical_date_column = self.find_first_existing_column(
 candidates=candidate_columns,
 columns=date_columns,
)

 if physical_date_column is None:
 continue

 date_part_meta = self.DATE_PARTS[part]

 date_part_map[legacy_field_name] = {
 "host": self.host_variable(
 record_name=idms_record_name,
 column_name=physical_date_column,
 remove_suffix=True,
),
 "record": idms_record_name,
 "table": table.name,
 "column": physical_date_column,
 "date_part": part,
 "substring_start": date_part_meta["substring_start"],
 "substring_length": date_part_meta["substring_length"],
 }

return date_part_map

def build_navigation_intent(
 self,
 relationships: list[dict[str, Any]],
) -> dict[str, dict[str, Any]]:
 navigation_intent: dict[str, dict[str, Any]] = {}

 for relationship in relationships:
 set_name = relationship.get(
 "set_name",
)

 if not set_name:
 continue

 navigation_intent[set_name] = {
 "access_pattern": "SET_NAVIGATION",
 "parent_record": relationship.get("parent_record"),
 "child_record": relationship.get("child_record"),
 "parent_key": relationship.get("parent_key"),
 "child_fk": relationship.get("child_fk"),
 "order_by": relationship.get("order_by") or [],
 }

 return navigation_intent

def build_output_semantics(
 self,
) -> dict[str, Any]:

```



```

 return {
 "generated_by": "idms-db2-modernizer-phase1",
 "usage": "IDMS retrieval COBOL to DB2 embedded SQL conversion",
 "physical_types_source": "DB2_DDL",
 "logical_mapping_source": "PHASE1_CANONICAL_METADATA",
 }

def build_validation_messages(
 self,
 canonical_schema: CanonicalSchema,
 db2_model: DB2Model,
 metadata: SchemaMetadata,
 field_map: dict[str, dict[str, Any]],
) -> list[str]:
 messages: list[str] = []

 if not getattr(canonical_schema, "records", []):
 messages.append("No canonical records found.")

 if not getattr(db2_model, "tables", []):
 messages.append("No DB2 tables found.")

 if not getattr(metadata, "records", []):
 messages.append("No IDMS metadata records found.")

 if not field_map:
 messages.append("No field map entries generated.")

 for table in getattr(db2_model, "tables", []) or []:
 primary_key = getattr(table, "primary_key", None)

 if not primary_key:
 continue

 column_names = {
 NameNormalizer.normalize(getattr(column, "name", ""))
 for column in getattr(table, "columns", []) or []
 }

 if NameNormalizer.normalize(primary_key) not in column_names:
 messages.append(
 f"Table {table.name} primary key {primary_key} is not present as a DB2 column."
)

 return messages

def find_matching_column(
 self,
 legacy_field_name: str,
 db2_columns: dict[str, DB2Column],
) -> str | None:
 normalized = NameNormalizer.normalize(
 legacy_field_name,
)

 if normalized in db2_columns:
 return normalized

 suffix_removed = self.remove_record_suffix(
 normalized,
)

 for column_name in db2_columns:
 if self.remove_record_suffix(column_name) == suffix_removed:
 return column_name

 return None

def parse_date_part(
 self,
 field_name: str,
) -> dict[str, Any] | None:
 tokens = self.split_tokens(
 value=field_name,
)

```

```

if len(tokens) < 2:
 return None

for index, token in enumerate(tokens):
 part = self.date_part_type(
 token=token,
 tokens=tokens,
)

 if part is None:
 continue

 base_tokens = tokens[:index] + tokens[index + 1 :]
 date_tokens = tokens.copy()
 date_tokens[index] = "DATE"

 base_name = " ".join(base_tokens)
 date_name = " ".join(date_tokens)

 return {
 "part": part,
 "candidate_columns": self.unique_values(
 [
 date_name,
 base_name,
]
),
 }

return None

def date_part_type(
 self,
 token: str,
 tokens: list[str],
) -> str | None:
 token = token.upper()

 has_dy_dm_dd = (
 "DY" in tokens
 and "DM" in tokens
 and "DD" in tokens
)

 if token in {"YEAR", "YR", "Y", "YY", "YYYY"}:
 return "YEAR"

 if token in {"MONTH", "MON", "MO", "M", "MM", "DM"}:
 return "MONTH"

 if token in {"DAY", "D", "DD"}:
 return "DAY"

 if token == "DY":
 if has_dy_dm_dd:
 return "YEAR"

 return "DAY"

 return None

def find_first_existing_column(
 self,
 candidates: list[str],
 columns: dict[str, DB2Column],
) -> str | None:
 for candidate in candidates:
 normalized_candidate = NameNormalizer.normalize(
 candidate,
)

 if normalized_candidate in columns:
 return normalized_candidate

 suffix_removed_candidate = self.remove_record_suffix(
 normalized_candidate,
)

```

```

)

 for column_name in columns:
 if self.remove_record_suffix(column_name) == suffix_removed_candidate:
 return column_name

 return None

def host_variable(
 self,
 record_name: str,
 column_name: str,
 remove_suffix: bool = True,
) -> str:
 record = NameNormalizer.normalize(
 record_name,
).replace(
 " ",
 "-",
)

 column = NameNormalizer.normalize(
 column_name,
)

 if remove_suffix:
 column = self.remove_record_suffix(
 column,
)

 column = column.replace(
 " ",
 "-",
)

 return f"HV-{{record}}-{{column}}"

def parse_db2_datatype(
 self,
 datatype: str,
) -> tuple[str, int | None, int | None]:
 value = (
 datatype
 or "VARCHAR(255)"
).strip().upper()

 decimal_match = re.match(
 r"^(DECIMAL|NUMERIC)$($(\d+),\s*(\d+)$)",
 value,
)

 if decimal_match:
 return (
 "DECIMAL",
 int(decimal_match.group(2)),
 int(decimal_match.group(3)),
)

 varchar_match = re.match(
 r"^(VARCHAR|CHAR)$($(\d+)$)",
 value,
)

 if varchar_match:
 return (
 varchar_match.group(1),
 int(varchar_match.group(2)),
 None,
)

 if value in {"INTEGER", "INT"}:
 return "INTEGER", 9, 0

 if value == "BIGINT":
 return "BIGINT", 18, 0

```

```

 if value == "SMALLINT":
 return "INTEGER", 9, 0

 if value == "DATE":
 return "DATE", None, None

 if value == "TIMESTAMP":
 return "TIMESTAMP", None, None

 return value, None, None

def remove_record_suffix(
 self,
 field_name: str,
) -> str:
 normalized = NameNormalizer.normalize(
 field_name,
)

 parts = normalized.split()

 if (
 len(parts) > 1
 and parts[-1].isdigit()
 and len(parts[-1]) == 4
):
 return " ".join(
 parts[:-1],
)

 return normalized

def split_tokens(
 self,
 value: str,
) -> list[str]:
 normalized = NameNormalizer.normalize(
 value,
)

 return [
 token.upper()
 for token in re.split(
 r"[\s_-]+",
 normalized,
)
 if token
]

def unique_values(
 self,
 values: list[str],
) -> list[str]:
 result: list[str] = []
 seen: set[str] = set()

 for value in values:
 normalized = NameNormalizer.normalize(
 value,
)

 if not normalized:
 continue

 if normalized in seen:
 continue

 seen.add(
 normalized,
)

 result.append(
 normalized,
)

 return result

```

```
=====
FILE: src\idms_db2_converter\transformers\metadata_helpers.py
ENCODING: utf-8
=====
```

```
from idms_db2_converter.generators.cobol_builder import Move
from idms_db2_converter.models import SchemaModel
```

```
class MetadataHelpers:
 def __init__(self, schema: SchemaModel):
 self.schema = schema

 def lookup_by_name(self, name: str) -> dict | None:
 for item in self.schema.output_semantics.get("lookups", []):
 if item.get("name", "").upper() == name.upper():
 return item

 return None

 def lookup_by_owner_set(self, owner_set: str) -> dict | None:
 for item in self.schema.output_semantics.get("lookups", []):
 if item.get("owner_set", "").upper() == owner_set.upper():
 return item

 return None

 def lookup_by_first_member_set(self, first_member_set: str) -> dict | None:
 for item in self.schema.output_semantics.get("lookups", []):
 if item.get("first_member_set", "").upper() == first_member_set.upper():
 return item

 return None

 def moves_to_nodes(self, moves: list[dict]) -> list[Move]:
 nodes = []

 for move in moves:
 source = self.map_source(move["from"])
 target = move["to"]
 nodes.append(Move(source=source, target=target))

 return nodes

 def map_source(self, source: str) -> str:
 source_upper = source.upper()

 if source_upper in self.schema.date_part_map:
 meta = self.schema.date_part_map[source_upper]
 return f"{meta['host']}({meta['substring_start']}:{meta['substring_length']})"

 if source_upper in self.schema.field_map:
 return self.schema.field_map[source_upper].get("host", source)

 return source
```

```
=====
FILE: src\idms_db2_converter\transformers\operation_graph_transformer.py
ENCODING: utf-8
=====
```

```
import re

from idms_db2_converter.generators.cobol_builder import (
 Continue,
 ExecSql,
 IfBlock,
 Move,
 Perform,
 PerformUntil,
 PreRenderedBlock,
 ReadAtEndMove,
 Write,
```

```

 render_nodes,
 render_paragraph,
)
from idms_db2_converter.generators.fetch_paragraphs import FetchParagraphGenerator
from idms_db2_converter.generators.naming import Naming
from idms_db2_converter.generators.sql_snippets import SqlSnippets
from idms_db2_converter.models import SchemaModel
from idms_db2_converter.transformers.metadata_helpers import MetadataHelpers

class OperationGraphTransformer:
 def __init__(self, schema: SchemaModel):
 self.schema = schema
 self.sql = SqlSnippets(schema)
 self.meta = MetadataHelpers(schema)
 self.fetch_generator = FetchParagraphGenerator(schema)
 self.used_cursor_sets: set[str] = set()

 def has_graph(self) -> bool:
 return bool(self.schema.paragraph_operation_graph)

 def transform(self, text: str) -> str:
 for paragraph_name, operations in self.schema.paragraph_operation_graph.items():
 rendered = self._render_paragraph(paragraph_name, operations)
 text = self._replace_paragraph(text, paragraph_name, rendered)

 return text

 def _replace_paragraph(self, text: str, paragraph_name: str, replacement: str) -> str:
 pattern = re.compile(
 rf"^\s*{re.escape(paragraph_name)}\.\s*\n.*?(?=\s*[A-Z0-9-]+\.\s*$)",
 re.IGNORECASE | re.MULTILINE | re.DOTALL,
)

 if pattern.search(text):
 return pattern.sub(replacement + "\n", text, count=1)

 return text + "\n" + replacement + "\n"

 def _render_paragraph(self, paragraph_name: str, operations: list[dict]) -> str:
 nodes = self._render_operations(operations)
 return render_paragraph(paragraph_name, nodes)

 def _render_operations(self, operations: list[dict]) -> list:
 nodes = []

 for operation in operations:
 op_type = operation.get("type", "").upper()

 if op_type == "MOVE":
 nodes.append(
 Move(
 source=self.meta.map_source(operation["from"]),
 target=operation["to"],
)
)

 elif op_type == "MOVE_DATE_PART":
 nodes.append(
 Move(
 source=self.meta.map_source(operation["from"]),
 target=operation["to"],
)
)

 elif op_type == "PERFORM":
 nodes.append(Perform(paragraph=operation["paragraph"]))

 elif op_type == "WRITE":
 nodes.append(
 Write(
 record=operation["record"],
 source=operation.get("source"),
)
)

```

```

 elif op_type == "READ_NEXT_INPUT":
 at_end_move = operation.get("at_end_move", {})
 nodes.append(
 ReadAtEndMove(
 file_name=operation["file"],
 source=at_end_move.get("from", "Y"),
 target=at_end_move.get("to", "EOF-SW"),
)
)

 elif op_type == "CONTINUE":
 nodes.append(Continue())

 elif op_type == "OBTAIN_CALC":
 nodes.append(self._node_obtain_calc(operation))

 elif op_type == "CURSOR_LOOP":
 nodes.append(self._node_cursor_loop(operation))

 elif op_type == "FIRST_MEMBER_TO_OWNER_LOOKUP":
 nodes.extend(self._nodes_first_member_to_owner_lookup(operation))

 elif op_type == "OWNER_LOOKUP":
 nodes.extend(self._nodes_owner_lookup(operation))

 return nodes

def _node_obtain_calc(self, operation: dict):
 record = operation["record"].upper()
 select_sql = self.sql.select_for_record_by_pk(record)

 not_found_nodes = self._render_operations(operation.get("not_found", []))
 success_nodes = self._render_operations(operation.get("success", []))

 lines = []
 lines.extend(ExecSql(select_sql).render(indent=7))
 lines.append("")
 lines.extend(
 IfBlock(
 condition="SQLCODE = 100",
 then_body=not_found_nodes,
 else_body=[
 IfBlock(
 condition="SQLCODE NOT = 0",
 then_body=[Perform("SQL-ERROR")],
 else_body=success_nodes,
)
],
).render(indent=7, final=True)
)

 return PreRenderedBlock(lines)

def _node_cursor_loop(self, operation: dict):
 set_name = operation["set"].upper()
 self.used_cursor_sets.add(set_name)

 cursor_name = Naming.cursor(set_name)
 fetch_paragraph = self.fetch_generator.paragraph_name(set_name)

 process_paragraph = operation["process_paragraph"]
 exit_paragraph = operation.get("exit_paragraph")
 empty_nodes = self._render_operations(operation.get("empty", []))
 before_loop_nodes = self._render_operations(operation.get("before_loop", []))

 perform_target = process_paragraph
 if exit_paragraph:
 perform_target = f"{{process_paragraph}} THRU {{exit_paragraph}}"

 cursor_open = ExecSql(
 "\n".join(
 [
 "EXEC SQL",
 f" OPEN {cursor_name}",
 "END-EXEC.",
]
)
)

```

```

)
)

cursor_close = ExecSql(
 "\n".join(
 [
 "EXEC SQL",
 f" CLOSE {cursor_name}",
 "END-EXEC.",
]
)
)

loop_nodes = before_loop_nodes + [
 PerformUntil(
 condition="SQLCODE = 100",
 body=[
 Perform(perform_target),
 Perform(fetch_paragraph),
],
)
]

return IfBlock(
 condition="SQLCODE NOT = 0",
 then_body=[Perform("SQL-ERROR")],
 else_body=[
 Perform(fetch_paragraph),
 IfBlock(
 condition="SQLCODE = 100",
 then_body=empty_nodes,
 else_body=loop_nodes,
),
 cursor_close,
],
).with_prefix(cursor_open)

def _nodes_first_member_to_owner_lookup(self, operation: dict) -> list:
 lookup_name = operation.get("name")
 first_member_set = operation["first_member_set"].upper()
 owner_set = operation["owner_set"].upper()

 lookup = self.meta.lookup_by_name(lookup_name) if lookup_name else None
 if not lookup:
 lookup = self.meta.lookup_by_first_member_set(first_member_set)

 not_found_moves = lookup.get("not_found_moves", []) if lookup else []
 success_moves = lookup.get("success_moves", []) if lookup else []

 first_select = ExecSql(self.sql.select_first_child_for_set(first_member_set))
 owner_select = ExecSql(self.sql.select_for_owner(owner_set))

 not_found_nodes = self.meta.moves_to_nodes(not_found_moves)
 owner_not_found_nodes = self.meta.moves_to_nodes(not_found_moves)
 success_nodes = self.meta.moves_to_nodes(success_moves) or [Continue()]

 return [
 first_select,
 IfBlock(
 condition="SQLCODE = 100",
 then_body=not_found_nodes,
 else_body=[
 IfBlock(
 condition="SQLCODE NOT = 0",
 then_body=[Perform("SQL-ERROR")],
 else_body=[
 owner_select,
 IfBlock(
 condition="SQLCODE = 100",
 then_body=owner_not_found_nodes,
 else_body=[
 IfBlock(
 condition="SQLCODE NOT = 0",
 then_body=[Perform("SQL-ERROR")],
 else_body=success_nodes,
)
]
)
]
)
]
)
]

```



```

],
),
],
)
],
),
]

def _nodes_owner_lookup(self, operation: dict) -> list:
 lookup_name = operation.get("name")
 owner_set = operation["owner_set"].upper()

 lookup = self.meta.lookup_by_name(lookup_name) if lookup_name else None
 if not lookup:
 lookup = self.meta.lookup_by_owner_set(owner_set)

 not_found_moves = lookup.get("not_found_moves", []) if lookup else []
 success_moves = lookup.get("success_moves", []) if lookup else []

 not_found_nodes = self.meta.moves_to_nodes(not_found_moves)
 success_nodes = self.meta.moves_to_nodes(success_moves) or [Continue()]
 owner_select = ExecSql(self.sql.select_for_owner(owner_set))

 nullable_meta = self.schema.nullable_fk_map.get(owner_set)
 null_indicator = nullable_meta.get("null_indicator") if nullable_meta else None

 if null_indicator:
 return [
 IfBlock(
 condition=f"{null_indicator} < 0",
 then_body=not_found_nodes,
 else_body=[
 owner_select,
 IfBlock(
 condition="SQLCODE = 0",
 then_body=success_nodes,
 else_body=[
 IfBlock(
 condition="SQLCODE = 100",
 then_body=not_found_nodes,
 else_body=[Perform("SQL-ERROR")],
)
],
),
],
),
],
),
]

return [
 owner_select,
 IfBlock(
 condition="SQLCODE = 0",
 then_body=success_nodes,
 else_body=[
 IfBlock(
 condition="SQLCODE = 100",
 then_body=not_found_nodes,
 else_body=[Perform("SQL-ERROR")],
)
],
),
],
)
]

```

```

=====
FILE: src\idms_db2_converter\transformers\paragraph_rewriter.py
ENCODING: utf-8
=====

```

```

import re

from idms_db2_converter.generators.fetch_paragraphs import FetchParagraphGenerator
from idms_db2_converter.generators.naming import Naming
from idms_db2_converter.generators.sql_snippets import SqlSnippets
from idms_db2_converter.models import SchemaModel
from idms_db2_converter.transformers.structured_blocks import StructuredBlocks

```

```

class ParagraphRewriter:
 def __init__(self, schema: SchemaModel):
 self.schema = schema
 self.sql = SqlSnippets(schema)
 self.fetch_generator = FetchParagraphGenerator(schema)
 self.controlled_loop_sets: set[str] = set()

 def rewrite(self, text: str) -> str:
 text = self._rewrite_cursor_loop_blocks(text)
 text = self._rewrite_find_first_owner_chain_blocks(text)
 text = self._rewrite_empty_else_obtain_owner_blocks(text)
 text = self._rewrite_empty_else_find_first_blocks(text)
 text = self._rewrite_obtain_calc_if_blocks(text)
 text = self._rewrite_remaining_obtain_calc(text)
 text = self._rewrite_remaining_obtain_next(text)
 text = self._rewrite_remaining_find_first(text)
 text = self._rewrite_remaining_obtain_owner(text)
 text = self._rewrite_status_tokens(text)
 return text

 def _rewrite_cursor_loop_blocks(self, text: str) -> str:
 for set_name in self.schema.relationships:
 text = self._rewrite_cursor_loop_for_set(text, set_name)

 return text

 def _rewrite_cursor_loop_for_set(self, text: str, set_name: str) -> str:
 pattern = re.compile(
 rf"""
 IF\s+{re.escape(set_name)}\s+IS\s+NOT\s+EMPTY\s+THEN
 (?P<before_loop>.*?)
 PERFORM\s+(?P<walk>[A-Z0-9-]+\s+THRU\s+(?P<exit>[A-Z0-9-]+\s+
 \s+UNTIL\s+DB-END-OF-SET
 \s+ELSE
 (?P<empty_body>.*?)
 (?=\.\s*READ|\.\s*[A-Z0-9-]+\.)
 """,
 re.IGNORECASE | re.DOTALL | re.VERBOSE,
)

 def replace(match: re.Match) -> str:
 self.controlled_loop_sets.add(set_name.upper())

 return StructuredBlocks.cursor_loop_block(
 cursor_name=Naming.cursor(set_name),
 fetch_paragraph=self.fetch_generator.paragraph_name(set_name),
 empty_body=self._clean_block(match.group("empty_body")),
 before_loop_body=self._clean_block(match.group("before_loop")),
 walk_paragraph=match.group("walk").upper(),
 walk_exit=match.group("exit").upper(),
 indent=7,
)

 return pattern.sub(replace, text)

 def _rewrite_find_first_owner_chain_blocks(self, text: str) -> str:
 for first_set in self.schema.relationships:
 for owner_set in self.schema.relationships:
 text = self._rewrite_one_find_first_owner_chain(
 text=text,
 first_set=first_set,
 owner_set=owner_set,
)

 return text

 def _rewrite_one_find_first_owner_chain(
 self,
 text: str,
 first_set: str,
 owner_set: str,
) -> str:
 pattern = re.compile(
 rf"""

```

```

IF\s+{re.escape(first_set)}\s+IS\s+EMPTY
(?P<first_empty>.*?)
ELSE\s+
FIND\s+FIRST\s+WITHIN\s+{re.escape(first_set)}\s+\.?
(?P<after_find>.*?)
IF\s+NOT\s+{re.escape(owner_set)}\s+MEMBER
(?P<owner_missing>.*?)
ELSE\s+
OBTAIN\s+OWNER\s+WITHIN\s+{re.escape(owner_set)}\s+\.?
(?P<success>.*?)
(?:=
 \n\s*IF\s+[A-Z0-9-]+\s+IS\s+EMPTY
 |
 \n\s*MOVE\s+EMP-DETAIL-LINE
 |
 \n\s*PERFORM\s+
 |
 \n\s*[A-Z0-9-]+-EXIT\
)
""",
re.IGNORECASE | re.DOTALL | re.VERBOSE,
)

def replace(match: re.Match) -> str:
 first_empty = self._remove_idms_status_lines(
 self._clean_block(match.group("first_empty"))
)
 owner_missing = self._remove_idms_status_lines(
 self._clean_block(match.group("owner_missing"))
)
 success = self._remove_idms_status_lines(
 self._clean_block(match.group("success"))
)

 if not success:
 success = "CONTINUE"

 return StructuredBlocks.select_first_then_owner_chain(
 first_select_sql=self.sql.select_first_child_for_set(first_set),
 owner_select_sql=self.sql.select_for_owner(owner_set),
 first_not_found_body=first_empty,
 owner_not_found_body=owner_missing,
 success_body=success,
 indent=7,
)

return pattern.sub(replace, text)

def _rewrite_empty_else_obtain_owner_blocks(self, text: str) -> str:
 for set_name in self.schema.relationships:
 pattern = re.compile(
 rf"""
 IF\s+{re.escape(set_name)}\s+IS\s+EMPTY
 (?P<empty_body>.*?)
 ELSE\s+
 OBTAIN\s+OWNER\s+WITHIN\s+{re.escape(set_name)}\s+\.?
 (?P<success_body>.*?)
 (?:=
 \n\s*MOVE\s+EMP-DETAIL-LINE
 |
 \n\s*PERFORM\s+
 |
 \n\s*[A-Z0-9-]+-EXIT\
)
 """,
 re.IGNORECASE | re.DOTALL | re.VERBOSE,
)

 def replace(match: re.Match, set_name=set_name) -> str:
 empty_body = self._remove_idms_status_lines(
 self._clean_block(match.group("empty_body"))
)
 success_body = self._remove_idms_status_lines(
 self._clean_block(match.group("success_body"))
)

```

```

 if not success_body:
 success_body = "CONTINUE"

 indicator = self.sql.nullable_fk_indicator_for_set(set_name)

 if indicator:
 return StructuredBlocks.nullable_owner_block(
 null_indicator=indicator,
 null_body=empty_body,
 owner_select_sql=self.sql.select_for_owner(set_name),
 success_body=success_body,
 fallback_body=empty_body,
 indent=7,
)

 return StructuredBlocks.owner_select_block(
 owner_select_sql=self.sql.select_for_owner(set_name),
 success_body=success_body,
 fallback_body=empty_body,
 indent=7,
)

 text = pattern.sub(replace, text)

 return text

def _rewrite_empty_else_find_first_blocks(self, text: str) -> str:
 for set_name in self.schema.relationships:
 pattern = re.compile(
 rf"""
 IF\s+{re.escape(set_name)}\s+IS\s+EMPTY
 (?P<empty_body>.*?)
 ELSE\s+
 FIND\s+FIRST\s+WITHIN\s+{re.escape(set_name)}\s+\.?
 (?P<success_body>.*?)
 (?=
 \n\s*IF\s+[A-Z0-9-]+\s+IS\s+EMPTY
 |
 \n\s*MOVE\s+EMP-DETAIL-LINE
 |
 \n\s*PERFORM\s+
 |
 \n\s*[A-Z0-9-]+\s+-EXIT\
)
 """,
 re.IGNORECASE | re.DOTALL | re.VERBOSE,
)

 def replace(match: re.Match, set_name=set_name) -> str:
 empty_body = self._remove_idms_status_lines(
 self._clean_block(match.group("empty_body"))
)
 success_body = self._remove_idms_status_lines(
 self._clean_block(match.group("success_body"))
)

 if not success_body:
 success_body = "CONTINUE"

 return StructuredBlocks.sqlcode_select_block(
 sql=self.sql.select_first_child_for_set(set_name),
 not_found_body=empty_body,
 success_body=success_body,
 indent=7,
)

 text = pattern.sub(replace, text)

 return text

def _rewrite_obtain_calc_if_blocks(self, text: str) -> str:
 pattern = re.compile(
 rf"""
 OBTAIN\s+CALC\s+(?P<record>[A-Z0-9-]+\s+)\.?
 \s+
 IF\s+DB-REC-NOT-FOUND\s+THEN
 """
)

```

```

 (?P<not_found>.*?)
 ELSE
 (?P<success>.*?)
 (?=\n\s*READ\s+)
 """,
 re.IGNORECASE | re.DOTALL | re.VERBOSE,
)

def replace(match: re.Match) -> str:
 record = match.group("record").upper()
 not_found = self._remove_idms_status_lines(
 self._clean_block(match.group("not_found"))
)
 success = self._remove_idms_status_lines(
 self._clean_block(match.group("success"))
)

 return StructuredBlocks.sqlcode_select_block(
 sql=self.sql.select_for_record_by_pk(record),
 not_found_body=not_found,
 success_body=success,
 indent=7,
)

return pattern.sub(replace, text)

def _rewrite_remaining_obtain_calc(self, text: str) -> str:
 pattern = re.compile(
 r"^\s*OBTAIN\s+CALC\s+([A-Z0-9-]+)\.?\s*$",
 re.IGNORECASE | re.MULTILINE,
)

 return pattern.sub(
 lambda m: self.sql.select_for_record_by_pk(m.group(1).upper()),
 text,
)

def _rewrite_remaining_obtain_next(self, text: str) -> str:
 pattern = re.compile(
 r"^\s*OBTAIN\s+NEXT\s+([A-Z0-9-]+)\s+WITHIN\s+([A-Z0-9-]+)\.?\s*$",
 re.IGNORECASE | re.MULTILINE,
)

 def replace(match: re.Match) -> str:
 set_name = match.group(2).upper()

 if set_name in self.controlled_loop_sets:
 return "CONTINUE."

 return f"PERFORM {self.fetch_generator.paragraph_name(set_name)}"

 return pattern.sub(replace, text)

def _rewrite_remaining_find_first(self, text: str) -> str:
 pattern = re.compile(
 r"^\s*FIND\s+FIRST\s+WITHIN\s+([A-Z0-9-]+)\.?\s*$",
 re.IGNORECASE | re.MULTILINE,
)

 return pattern.sub(
 lambda m: self.sql.select_first_child_for_set(m.group(1).upper()),
 text,
)

def _rewrite_remaining_obtain_owner(self, text: str) -> str:
 pattern = re.compile(
 r"^\s*OBTAIN\s+OWNER\s+WITHIN\s+([A-Z0-9-]+)\.?\s*$",
 re.IGNORECASE | re.MULTILINE,
)

 return pattern.sub(
 lambda m: self.sql.select_for_owner(m.group(1).upper()),
 text,
)

def _rewrite_status_tokens(self, text: str) -> str:

```

```

 text = re.sub(
 r"\bDB-REC-NOT-FOUND\b",
 "SQLCODE = 100",
 text,
 flags=re.IGNORECASE,
)

 text = re.sub(
 r"\bDB-END-OF-SET\b",
 "SQLCODE = 100",
 text,
 flags=re.IGNORECASE,
)

 text = re.sub(
 r"IF\s+NOT\s+[A-Z0-9-]+\s+MEMBER",
 "IF SQLCODE = 100",
 text,
 flags=re.IGNORECASE,
)

 return text

def _remove_idms_status_lines(self, text: str) -> str:
 text = re.sub(
 r"^\s*PERFORM\s+IDMS-STATUS\.\?\s*$",
 "",
 text,
 flags=re.IGNORECASE | re.MULTILINE,
)

 text = re.sub(
 r"^\s*IF SQLCODE NOT = 0 AND SQLCODE NOT = 100\s*"
 r"\n\s*PERFORM SQL-ERROR\s*"
 r"\n\s*END-IF\.\?\s*$",
 "",
 text,
 flags=re.IGNORECASE | re.MULTILINE,
)

 return text.strip()

def _clean_block(self, value: str) -> str:
 value = value.strip()

 if value.endswith("."):
 value = value[:-1].rstrip()

 return value

```

```

=====
FILE: src\idms_db2_converter\transformers\retrieval_transformer.py
ENCODING: utf-8
=====

```

```

import re

from idms_db2_converter.generators.cursors import CursorGenerator
from idms_db2_converter.generators.fetch_paragraphs import FetchParagraphGenerator
from idms_db2_converter.generators.host_variables import HostVariableGenerator
from idms_db2_converter.models import CobolAnalysis, SchemaModel
from idms_db2_converter.transformers.cobol_cleanup import CobolCleanup
from idms_db2_converter.transformers.dml_transformer import DmlTransformer
from idms_db2_converter.transformers.field_rewriter import FieldRewriter
from idms_db2_converter.transformers.operation_graph_transformer import (
 OperationGraphTransformer,
)
from idms_db2_converter.transformers.paragraph_rewriter import ParagraphRewriter

class RetrievalTransformer:
 """
 Transforms IDMS retrieval/update COBOL into DB2 embedded SQL COBOL.

 Retrieval behavior:

```

- OBTAIN CALC becomes SELECT.
- OBTAIN NEXT set navigation becomes cursor processing.
- FIND FIRST lookup sets do not become declared cursors.
- OBTAIN OWNER becomes keyed SELECT.
- Existing generated DB2 blocks are removed before regeneration.
- Existing incomplete FETCH paragraphs are removed and regenerated.
- INIT-BIND-READY is renamed to INIT-DB2-SETUP.
- PERFORM IDMS-STATUS lines are removed.
- FINISH executable lines are removed unless already converted by DML logic.

Update behavior:

- STORE, MODIFY, ERASE are delegated to DmlTransformer.
- DmlTransformer is called only when update DML exists.

Host-variable optimization:

- Does not add every schema relationship record.
- Adds only records actually used by COBOL DML, set navigation, or field references.

"""

```

PROCEDURE_DIVISION = re.compile(
 r"^\s*PROCEDURE\s+DIVISION\.",
 re.IGNORECASE | re.MULTILINE,
)

def __init__(
 self,
 schema: SchemaModel,
 analysis: CobolAnalysis,
) -> None:
 self.schema = schema
 self.analysis = analysis

def transform(
 self,
 cobol: str,
 target_program: str | None = None,
) -> str:
 text = cobol

 if target_program and self.analysis.program_id:
 text = self._rename_program(
 text=text,
 source=self.analysis.program_id,
 target=target_program,
)

 text = self._remove_existing_generated_db2_block(text)
 text = self._remove_idms_control_section(text)
 text = self._remove_schema_section(text)
 text = self._remove_idms_copybooks(text)

 operation_graph_transformer = OperationGraphTransformer(
 self.schema,
)

 if operation_graph_transformer.has_graph():
 text = operation_graph_transformer.transform(text)

 used_cursor_sets = sorted(
 operation_graph_transformer.used_cursor_sets,
)
 else:
 paragraph_rewriter = ParagraphRewriter(
 self.schema,
)

 text = paragraph_rewriter.rewrite(text)

 used_cursor_sets = sorted(
 paragraph_rewriter.controlled_loop_sets,
)

 used_cursor_sets = self._ensure_cursor_sets(
 used_cursor_sets,

```

```

)

 dml_transformer = DmlTransformer(
 schema=self.schema,
 analysis=self.analysis,
)

 if dml_transformer.has_update_dml():
 text = dml_transformer.transform(text)

 text = self._remove_existing_fetch_paragraphs(
 text=text,
 used_cursor_sets=used_cursor_sets,
)

 text = self._insert_sql_declarations(
 text=text,
 used_cursor_sets=used_cursor_sets,
)

 text = self._insert_fetch_paragraphs(
 text=text,
 used_cursor_sets=used_cursor_sets,
)

 text = FieldRewriter(
 self.schema,
).rewrite(text)

 text = self._replace_init_bind_ready(text)
 text = self._remove_idms_status_perform(text)
 text = self._replace_finish(text)
 text = self._remove_bind_ready_lines(text)
 text = self._clean_end_processing(text)
 text = self._remove_idms_abort_paragraphs(text)
 text = self._remove_obsolete_set_walk_guard(text)
 text = self._cleanup_orphan_sqlcode_blocks(text)
 text = self._fix_paragraph_header_concatenation(text)
 text = self._normalize_formatting(text)

 text = CobolCleanup().clean(text)

 text = self._add_sql_error_paragraph(text)

 text = CobolCleanup().clean(text)

 return text

def _rename_program(
 self,
 text: str,
 source: str,
 target: str,
) -> str:
 return re.sub(
 rf"(PROGRAM-ID\.\\s*){re.escape(source)}(\\.)?",
 rf"\\1{target}.",
 text,
 flags=re.IGNORECASE,
)

def _remove_existing_generated_db2_block(
 self,
 text: str,
) -> str:
 pattern = re.compile(
 r"""
 \n\s*
 (?::EJECT\s*)?
 \s
 \n\s**\s*DB2\s+SQLCA, \s+HOST\s+VARIABLES, \s+AND\s+Cursors\s*
 .*?
 (?=\n\s*PROCEDURE\s+DIVISION\.)
 """,
 re.IGNORECASE | re.DOTALL | re.VERBOSE,
)

```



```

 return pattern.sub(
 "\n",
 text,
)

def _remove_idms_control_section(
 self,
 text: str,
) -> str:
 return re.sub(
 r"\n\s*IDMS-CONTROL\s+SECTION\..*?(?=\n\s*DATA\s+DIVISION\.)",
 "\n",
 text,
 flags=re.IGNORECASE | re.DOTALL,
)

def _remove_schema_section(
 self,
 text: str,
) -> str:
 return re.sub(
 r"\n\s*SCHEMA\s+SECTION\..*?(?=\n\s*FILE\s+SECTION\.)",
 "\n",
 text,
 flags=re.IGNORECASE | re.DOTALL,
)

def _remove_idms_copybooks(
 self,
 text: str,
) -> str:
 return re.sub(
 r"^\s*(?:01\s+)?COPY\s+IDMS\s+.*?\.\s*$",
 "",
 text,
 flags=re.IGNORECASE | re.MULTILINE,
)

def _ensure_cursor_sets(
 self,
 used_cursor_sets: list[str],
) -> list[str]:
 result = set(
 item.upper()
 for item in used_cursor_sets
 if item
)

 for _, set_name in getattr(self.analysis, "obtain_next", []):
 if set_name:
 result.add(
 set_name.upper(),
)

 return sorted(result)

def _insert_sql_declarations(
 self,
 text: str,
 used_cursor_sets: list[str],
) -> str:
 used_records = self._used_records(
 used_cursor_sets=used_cursor_sets,
)

 host_variables = HostVariableGenerator().generate(
 self.schema,
 used_records,
)

 cursors = CursorGenerator().generate(
 self.schema,
 used_cursor_sets,
)

```

```

block = "\n".join(
 [
 "",
 "*****",
 " * DB2 SQLCA, HOST VARIABLES, AND CURSORS",
 "*****",
 host_variables,
 cursors,
 "",
]
)

return re.sub(
 r"(?=\n\s*PROCEDURE\s+DIVISION\.)",
 block,
 text,
 count=1,
 flags=re.IGNORECASE,
)

def _insert_fetch_paragraphs(
 self,
 text: str,
 used_cursor_sets: list[str],
) -> str:
 if not used_cursor_sets:
 return text

 fetch_paragraphs = FetchParagraphGenerator(
 self.schema,
).generate(
 used_cursor_sets,
)

 if not fetch_paragraphs.strip():
 return text

 return re.sub(
 r"(?=\n\s*MAIN-LINE\.)",
 "\n" + fetch_paragraphs + "\n",
 text,
 count=1,
 flags=re.IGNORECASE,
)

def _remove_existing_fetch_paragraphs(
 self,
 text: str,
 used_cursor_sets: list[str],
) -> str:
 if not used_cursor_sets:
 return text

 for set_name in used_cursor_sets:
 fetch_name = f"FETCH-{set_name}".upper()

 pattern = re.compile(
 rf"""
 ^\s*{re.escape(fetch_name)}\.\s*
 .*?
 (?=
 ^\s*MAIN-LINE\.\s*$
 |
 ^\s*[A-Z0-9-]+\.\s*$
 |
 \Z
)
 """,
 re.IGNORECASE | re.MULTILINE | re.DOTALL | re.VERBOSE,
)

 text = pattern.sub(
 "",
 text,
)

```

```

return text

def _replace_init_bind_ready(
 self,
 text: str,
) -> str:
 text = re.sub(
 r"\bPERFORM\s+INIT-BIND-READY\b",
 "PERFORM INIT-DB2-SETUP",
 text,
 flags=re.IGNORECASE,
)

 pattern = re.compile(
 r"""
 ^\s*INIT-BIND-READY\.\s*
 .*?
 (?=
 ^\s*INIT-FILES\.\s*$
 |
 \Z
)
 """,
 re.IGNORECASE | re.MULTILINE | re.DOTALL | re.VERBOSE,
)

 replacement = (
 "\n"
 "INIT-DB2-SETUP.\n"
 " CONTINUE.\n"
)

 return pattern.sub(
 replacement,
 text,
 count=1,
)

def _remove_idms_status_perform(
 self,
 text: str,
) -> str:
 return re.sub(
 r"^\s*PERFORM\s+IDMS-STATUS\.\?\s*$",
 "",
 text,
 flags=re.IGNORECASE | re.MULTILINE,
)

def _replace_finish(
 self,
 text: str,
) -> str:
 return re.sub(
 r"^\s*FINISH\.\?\s*$",
 "",
 text,
 flags=re.IGNORECASE | re.MULTILINE,
)

def _remove_bind_ready_lines(
 self,
 text: str,
) -> str:
 text = re.sub(
 r"^\s*BIND\s+[A-Z0-9-]+\.\?\s*$",
 "",
 text,
 flags=re.IGNORECASE | re.MULTILINE,
)

 text = re.sub(
 r"^\s*READY\.\?\s*$",
 "",
 text,
 flags=re.IGNORECASE | re.MULTILINE,
)

```

```

)

 return text

def _clean_end_processing(
 self,
 text: str,
) -> str:
 text = re.sub(
 r"(\n\s*END-PROCESSING\.\s*)\n\s*CONTINUE\.\s*",
 r"\1",
 text,
 flags=re.IGNORECASE,
)

 return text

def _remove_idms_abort_paragraphs(
 self,
 text: str,
) -> str:
 return re.sub(
 r"\n\s*IDMS-ABORT\.\s*(?:\n\s*EXIT\.\s*)?\n\s*IDMS-ABORT-EXIT\.\s*(?:\n\s*EXIT\.\s*)?",
 "\n",
 text,
 flags=re.IGNORECASE | re.DOTALL,
)

def _remove_obsolete_set_walk_guard(
 self,
 text: str,
) -> str:
 pattern = re.compile(
 r"""
 \n\s*CONTINUE\.\s*
 \n\s*IF\s+SQLCODE\s*=\s*100\s*
 \n\s*GO\s+TO\s+[A-Z0-9-]+\s+-EXIT\s*
 \n\s*ELSE\s*
 """,
 re.IGNORECASE | re.VERBOSE,
)

 return pattern.sub(
 "\n CONTINUE.\n",
 text,
)

def _cleanup_orphan_sqlcode_blocks(
 self,
 text: str,
) -> str:
 text = re.sub(
 r"""
 (\n\s*CONTINUE\.\s*)
 \n\s*IF\s+SQLCODE\s+NOT\s*=\s*0\s+AND\s+SQLCODE\s+NOT\s*=\s*100\s*
 \n\s*PERFORM\s+SQL-ERROR\s*
 \n\s*END-IF\.?
 """,
 r"\1",
 text,
 flags=re.IGNORECASE | re.VERBOSE,
)

 text = re.sub(
 r"""
 (\n\s*END-PROCESSING\.\s*)
 \s*IF\s+SQLCODE\s+NOT\s*=\s*0\s+AND\s+SQLCODE\s+NOT\s*=\s*100\s*
 \n\s*PERFORM\s+SQL-ERROR\s*
 \n\s*END-IF\.?
 """,
 r"\1",
 text,
 flags=re.IGNORECASE | re.VERBOSE,
)

 return text

```

```

def _fix_paragraph_header_concatenation(
 self,
 text: str,
) -> str:
 text = re.sub(
 r"(\b[A-Z0-9-]+\.)\s*(IF\s+SQLCODE)",
 r"\1\n \2",
 text,
 flags=re.IGNORECASE,
)

 text = re.sub(
 r"(\b[A-Z0-9-]+\.)\s*(EXEC\s+SQL)",
 r"\1\n \2",
 text,
 flags=re.IGNORECASE,
)

 return text

def _normalize_formatting(
 self,
 text: str,
) -> str:
 text = re.sub(
 r"\n{3,}",
 "\n\n",
 text,
)

 text = re.sub(
 r"[\t]+\$",
 "",
 text,
 flags=re.MULTILINE,
)

 return text

def _add_sql_error_paragraph(
 self,
 text: str,
) -> str:
 if re.search(
 r"^\s*SQL-ERROR\.",
 text,
 flags=re.IGNORECASE | re.MULTILINE,
):
 return text

 return text.rstrip() + """

SQL-ERROR.
MOVE SPACES TO ERR-LINE.
MOVE 'SQL ERROR' TO ERR-MESS-OUT.
MOVE ERR-DETAIL-LINE TO ERR-LINE.
PERFORM U200-WRITE-ERR-LINE.

SQL-ERROR-EXIT.
EXIT.
"""

def _used_records(
 self,
 used_cursor_sets: list[str] | None = None,
) -> list[str]:
 records: set[str] = set()

 for record in getattr(self.analysis, "idms_records", []):
 self._add_record(
 records=records,
 record_name=record,
)

 for record in getattr(self.analysis, "obtain_calc_records", []):

```

```

 self._add_record(
 records=records,
 record_name=record,
)

 for record, _ in getattr(self.analysis, "obtain_next", []):
 self._add_record(
 records=records,
 record_name=record,
)

 for record in getattr(self.analysis, "store_records", []):
 self._add_record(
 records=records,
 record_name=record,
)

 for record in getattr(self.analysis, "modify_records", []):
 self._add_record(
 records=records,
 record_name=record,
)

 for record in getattr(self.analysis, "erase_records", []):
 self._add_record(
 records=records,
 record_name=record,
)

 self._add_relationship_records_for_used_sets(
 records=records,
 used_cursor_sets=used_cursor_sets or [],
)

 self._add_field_reference_records(
 records=records,
)

 return sorted(records)

def _add_record(
 self,
 records: set[str],
 record_name: str | None,
) -> None:
 if not record_name:
 return

 value = str(record_name).strip().upper()

 if not value:
 return

 records.add(
 value,
)

def _used_set_names(
 self,
 used_cursor_sets: list[str],
) -> set[str]:
 set_names: set[str] = set()

 for set_name in used_cursor_sets:
 if set_name:
 set_names.add(
 set_name.upper(),
)

 for _, set_name in getattr(self.analysis, "obtain_next", []):
 if set_name:
 set_names.add(
 set_name.upper(),
)

 for set_name in getattr(self.analysis, "obtain_owner_sets", []):

```

```

 if set_name:
 set_names.add(
 set_name.upper(),
)

 for set_name in getattr(self.analysis, "find_first_sets", []):
 if set_name:
 set_names.add(
 set_name.upper(),
)

 return set_names

def _add_relationship_records_for_used_sets(
 self,
 records: set[str],
 used_cursor_sets: list[str],
) -> None:
 used_set_names = self._used_set_names(
 used_cursor_sets=used_cursor_sets,
)

 if not used_set_names:
 return

 for set_name in used_set_names:
 relationship = self.schema.relationships.get(
 set_name,
)

 if not relationship:
 continue

 self._add_record(
 records=records,
 record_name=relationship.parent_record,
)

 self._add_record(
 records=records,
 record_name=relationship.child_record,
)

def _add_field_reference_records(
 self,
 records: set[str],
) -> None:
 field_references = (
 getattr(self.analysis, "field_references", [])
 or getattr(self.analysis, "idms_fields", [])
 or []
)

 for field_name in field_references:
 for record_name in self._record_names_from_field_reference(
 field_name=field_name,
):
 self._add_record(
 records=records,
 record_name=record_name,
)

def _record_names_from_field_reference(
 self,
 field_name: str,
) -> list[str]:
 result: list[str] = []

 if not field_name:
 return result

 field_map = getattr(
 self.schema,
 "field_map",
 {},
)

```

```

meta = field_map.get(
 field_name.upper(),
)

if not meta:
 return result

record = (
 meta.get("record")
 or meta.get("table")
 or meta.get("record_name")
 or meta.get("table_name")
)

if record:
 result.append(
 str(record).upper(),
)

host = meta.get(
 "host",
)

if host:
 host_record = self._record_name_from_host(
 str(host),
)

 if host_record:
 result.append(
 host_record,
)

column_record = meta.get(
 "logical_record",
)

if column_record:
 result.append(
 str(column_record).upper(),
)

return result

def _record_name_from_host(
 self,
 host: str,
) -> str | None:
 normalized_host = self._normalize_name(
 host,
)

 if not normalized_host.startswith("HV-"):
 return None

 candidates: list[str] = []

 candidates.extend(
 list(getattr(self.schema, "record_table_map", {}).keys()),
)

 candidates.extend(
 list(getattr(self.schema, "records", {}).keys()),
)

 candidates = sorted(
 set(
 str(candidate).upper()
 for candidate in candidates
 if candidate
),
 key=len,
 reverse=True,
)

```



```

 for candidate in candidates:
 normalized_candidate = self._normalize_name(
 candidate,
)

 prefix = f"HV-{normalized_candidate}-"

 if normalized_host.startswith(prefix):
 return candidate.upper()

 return None

def _normalize_name(
 self,
 value: str,
) -> str:
 return (
 str(value)
 .strip()
 .upper()
 .replace("_", "-")
 .replace(" ", "-")
)

```

```

=====
FILE: src\idms_db2_converter\transformers\structured_blocks.py
ENCODING: utf-8
=====

```

```

class StructuredBlocks:
 @staticmethod
 def indent(block: str, spaces: int) -> str:
 pad = " " * spaces
 lines = []

 for line in block.splitlines():
 stripped = line.strip()
 if stripped:
 lines.append(pad + stripped)
 else:
 lines.append("")

 return "\n".join(lines)

 @staticmethod
 def sqlcode_select_block(
 sql: str,
 not_found_body: str,
 success_body: str,
 indent: int = 7,
) -> str:
 pad = " " * indent
 inner = " " * (indent + 3)
 inner2 = " " * (indent + 6)

 return "\n".join(
 [
 StructuredBlocks.indent(sql, indent),
 "",
 f"{pad}IF SQLCODE = 100",
 StructuredBlocks.indent(not_found_body, indent + 3),
 f"{pad}ELSE",
 f"{inner}IF SQLCODE NOT = 0",
 f"{inner2}PERFORM SQL-ERROR",
 f"{inner}ELSE",
 StructuredBlocks.indent(success_body, indent + 6),
 f"{inner}END-IF",
 f"{pad}END-IF.",
]
)

 @staticmethod
 def select_first_then_owner_chain(
 first_select_sql: str,
 owner_select_sql: str,
)

```

```

first_not_found_body: str,
owner_not_found_body: str,
success_body: str,
indent: int = 7,
) -> str:
 pad = " " * indent
 inner = " " * (indent + 3)
 inner2 = " " * (indent + 6)
 inner3 = " " * (indent + 9)

 return "\n".join(
 [
 StructuredBlocks.indent(first_select_sql, indent),
 "",
 f"{pad}IF SQLCODE = 100",
 StructuredBlocks.indent(first_not_found_body, indent + 3),
 f"{pad}ELSE",
 f"{inner}IF SQLCODE NOT = 0",
 f"{inner2}PERFORM SQL-ERROR",
 f"{inner}ELSE",
 StructuredBlocks.indent(owner_select_sql, indent + 6),
 "",
 f"{inner2}IF SQLCODE = 100",
 StructuredBlocks.indent(owner_not_found_body, indent + 9),
 f"{inner2}ELSE",
 f"{inner3}IF SQLCODE NOT = 0",
 f"{inner3} PERFORM SQL-ERROR",
 f"{inner3}ELSE",
 StructuredBlocks.indent(success_body, indent + 12),
 f"{inner3}END-IF",
 f"{inner2}END-IF",
 f"{inner}END-IF",
 f"{pad}END-IF.",
]
)

```

```

@staticmethod
def nullable_owner_block(
 null_indicator: str,
 null_body: str,
 owner_select_sql: str,
 success_body: str,
 fallback_body: str,
 indent: int = 7,
) -> str:
 pad = " " * indent
 inner = " " * (indent + 3)

 return "\n".join(
 [
 f"{pad}IF {null_indicator} < 0",
 StructuredBlocks.indent(null_body, indent + 3),
 f"{pad}ELSE",
 StructuredBlocks.indent(owner_select_sql, indent + 3),
 "",
 f"{inner}IF SQLCODE = 0",
 StructuredBlocks.indent(success_body, indent + 6),
 f"{inner}ELSE",
 StructuredBlocks.indent(fallback_body, indent + 6),
 f"{inner}END-IF",
 f"{pad}END-IF.",
]
)

```

```

@staticmethod
def owner_select_block(
 owner_select_sql: str,
 success_body: str,
 fallback_body: str,
 indent: int = 7,
) -> str:
 pad = " " * indent
 inner = " " * (indent + 3)

 return "\n".join(
 [

```

```

 StructuredBlocks.indent(owner_select_sql, indent),
 """
 f"{pad}IF SQLCODE = 0",
 StructuredBlocks.indent(success_body, indent + 3),
 f"{pad}ELSE",
 StructuredBlocks.indent(fallback_body, indent + 3),
 f"{pad}END-IF.",
]
)

@staticmethod
def cursor_loop_block(
 cursor_name: str,
 fetch_paragraph: str,
 empty_body: str,
 before_loop_body: str,
 walk_paragraph: str,
 walk_exit: str,
 indent: int = 7,
) -> str:
 pad = " " * indent
 inner = " " * (indent + 3)
 inner2 = " " * (indent + 6)

 return "\n".join(
 [
 f"{pad}EXEC SQL",
 f"{pad} OPEN {cursor_name}",
 f"{pad}END-EXEC.",
 """
 f"{pad}IF SQLCODE NOT = 0",
 f"{inner}PERFORM SQL-ERROR",
 f"{pad}ELSE",
 f"{inner}PERFORM {fetch_paragraph}",
 """
 f"{inner}IF SQLCODE = 100",
 StructuredBlocks.indent(empty_body, indent + 6),
 f"{inner}ELSE",
 StructuredBlocks.indent(before_loop_body, indent + 6),
 """
 f"{inner2}PERFORM UNTIL SQLCODE = 100",
 f"{inner2} PERFORM {walk_paragraph} THRU {walk_exit}",
 f"{inner2} PERFORM {fetch_paragraph}",
 f"{inner2}END-PERFORM",
 f"{inner}END-IF",
 """
 f"{inner}EXEC SQL",
 f"{inner} CLOSE {cursor_name}",
 f"{inner}END-EXEC",
 f"{pad}END-IF",
]
)

```

```

=====
FILE: src\idms_db2_converter\validators__init__.py
ENCODING: utf-8
=====

```

[Empty file]

```

=====
FILE: src\idms_db2_converter\validators\output_validator.py
ENCODING: utf-8
=====

```

```
import re
```

```

class OutputValidator:
 """
 Validates generated DB2 COBOL output.

 This validator is generic:
 - No application record names are hard-coded.

```

- No demo set names are hard-coded.
- Paragraph names like READY-AREA are not treated as IDMS READY commands.
- Multiline SQL column lists are not falsely flagged as empty parentheses.

```

FORBIDDEN_EXECUTABLE_PATTERNS = [
 r"^\\s*OBTAIN\\b",
 r"^\\s*FIND\\b",
 r"^\\s*READY(?:\\s|\\.|\\$)",
 r"^\\s*BIND(?:\\s|\\.|\\$)",
 r"^\\s*FINISH\\.?\\s*$",
 r"^\\s*KEEP\\b",
 r"^\\s*STORE\\b",
 r"^\\s*MODIFY\\b",
 r"^\\s*ERASE\\b",
 r"^\\s*CONNECT\\b",
 r"^\\s*DISCONNECT\\b",
 r"^\\s*GET\\b",
 r"^\\s*IF\\s+DB-[A-Z0-9-]+\\b",
 r"^\\s*PERFORM\\s+IDMS-STATUS\\.?\\s*$",
 r"^\\s*USAGE-MODE\\s+IS\\s+UPDATE\\.?\\s*$",
]

REQUIRED = [
 "EXEC SQL",
 "SQLCA",
 "END-EXEC",
]

EXEC_SQL_START = re.compile(
 r"^\\s*EXEC\\s+SQL\\b",
 re.IGNORECASE,
)

EXEC_SQL_END = re.compile(
 r"^\\s*END-EXEC\\.?\\s*$",
 re.IGNORECASE,
)

COMMENT_LINE = re.compile(
 r"^\\s**",
)

PARAGRAPH_HEADER_PATTERN = re.compile(
 r"^\\s*[A-Z0-9-]+\\.\\s*$",
 re.IGNORECASE,
)

UNCONVERTED_IDMS_FIELD_PATTERN = re.compile(
 r"\\b[A-Z][A-Z0-9]*(?:-[A-Z0-9]+)*-\\d{4}\\b",
 re.IGNORECASE,
)

HOST_VARIABLE_PATTERN = re.compile(
 r"\\b(?:HV|NI)-[A-Z0-9-]+(?:\\$\\d+:\\d+\\$)?\\b",
 re.IGNORECASE,
)

def validate(
 self,
 text: str,
) -> list[str]:
 errors: list[str] = []

 executable_text = self.executable_text(
 text,
)

 upper_executable = executable_text.upper()
 upper_all = text.upper()

 self.validate_forbidden_idms_patterns(
 upper=upper_executable,
 errors=errors,
)

```

```

self.validate_required_db2_tokens(
 upper=upper_all,
 errors=errors,
)

self.validate_no_nested_host_variables(
 upper=upper_all,
 errors=errors,
)

self.validate_no_rewritten_report_fields(
 upper=upper_all,
 errors=errors,
)

self.validate_no_unconverted_idms_schema_fields(
 text=executable_text,
 errors=errors,
)

self.validate_sql_blocks_closed(
 text=text,
 errors=errors,
)

self.validate_sql_punctuation(
 text=text,
 errors=errors,
)

return errors

def executable_text(
 self,
 text: str,
) -> str:
 lines: list[str] = []
 in_exec_sql = False
 in_data_division = False
 in_procedure_division = False

 for line in text.splitlines():
 stripped = line.strip()
 upper = stripped.upper()

 if not stripped:
 continue

 if self.COMMENT_LINE.match(line):
 continue

 if upper.startswith("DATA DIVISION"):
 in_data_division = True
 in_procedure_division = False
 continue

 if upper.startswith("PROCEDURE DIVISION"):
 in_data_division = False
 in_procedure_division = True
 lines.append(line)
 continue

 if self.EXEC_SQL_START.match(line):
 in_exec_sql = True
 lines.append(line)

 if self.EXEC_SQL_END.match(line):
 in_exec_sql = False

 continue

 if in_exec_sql:
 lines.append(line)

 if self.EXEC_SQL_END.match(line):
 in_exec_sql = False

```

```

 continue

 if in_data_division:
 continue

 if not in_procedure_division:
 continue

 lines.append(line)

 return "\n".join(lines)

def validate_forbidden_idms_patterns(
 self,
 upper: str,
 errors: list[str],
) -> None:
 for pattern in self.FORBIDDEN_EXECUTABLE_PATTERNS:
 if re.search(
 pattern,
 upper,
 flags=re.IGNORECASE | re.MULTILINE,
):
 errors.append(
 f"Forbidden IDMS executable pattern remains: {pattern}"
)

def validate_required_db2_tokens(
 self,
 upper: str,
 errors: list[str],
) -> None:
 for token in self.REQUIRED:
 if token not in upper:
 errors.append(
 f"Required DB2 token missing: {token}"
)

def validate_no_nested_host_variables(
 self,
 upper: str,
 errors: list[str],
) -> None:
 if re.search(
 r"\bHV-[A-Z0-9-]+-HV-[A-Z0-9-]+\b",
 upper,
):
 errors.append(
 "Converted output contains nested host variables like HV-...-HV-...."
)

 if re.search(
 r"\bNI-[A-Z0-9-]+-NI-[A-Z0-9-]+\b",
 upper,
):
 errors.append(
 "Converted output contains nested null indicators like NI-...-NI-...."
)

def validate_no_rewritten_report_fields(
 self,
 upper: str,
 errors: list[str],
) -> None:
 bad_patterns = [
 r"\bHV-[A-Z0-9-]+-IN\b",
 r"\bHV-[A-Z0-9-]+-OUT\b",
 r"\bNI-[A-Z0-9-]+-IN\b",
 r"\bNI-[A-Z0-9-]+-OUT\b",
]

 for pattern in bad_patterns:
 if re.search(
 pattern,
 upper,

```

```

):
 errors.append(
 "Converted output appears to have rewritten input/output report fields."
)
 return

def validate_no_unconverted_idms_schema_fields(
 self,
 text: str,
 errors: list[str],
) -> None:
 lines = text.splitlines()
 in_exec_sql = False

 for line in lines:
 if self.EXEC_SQL_START.match(line):
 in_exec_sql = True

 if self.EXEC_SQL_END.match(line):
 in_exec_sql = False

 continue

 if in_exec_sql:
 if self.EXEC_SQL_END.match(line):
 in_exec_sql = False

 continue

 if self.COMMENT_LINE.match(line):
 continue

 if self.PARAGRAPH_HEADER_PATTERN.match(line):
 continue

 scrubbed = self.remove_host_variables(
 line,
)

 matches = self.UNCONVERTED_IDMS_FIELD_PATTERN.findall(
 scrubbed,
)

 for match in matches:
 upper_match = match.upper()

 if upper_match.startswith("HV-"):
 continue

 if upper_match.startswith("NI-"):
 continue

 errors.append(
 f"Unconverted IDMS schema field remains in procedure logic: {match}"
)

def remove_host_variables(
 self,
 line: str,
) -> str:
 return self.HOST_VARIABLE_PATTERN.sub(
 "",
 line,
)

def validate_sql_blocks_closed(
 self,
 text: str,
 errors: list[str],
) -> None:
 start_count = 0
 end_count = 0

 for line in text.splitlines():
 if self.EXEC_SQL_START.match(line):
 start_count += 1

```

```

 if self.EXEC_SQL_END.match(line):
 end_count += 1

 if start_count != end_count:
 errors.append(
 f"EXEC SQL / END-EXEC block mismatch: EXEC SQL={start_count}, END-EXEC={end_count}"
)

def validate_sql_punctuation(
 self,
 text: str,
 errors: list[str],
) -> None:
 sql_blocks = self.extract_sql_blocks(
 text,
)

 for block in sql_blocks:
 self.validate_sql_commas(
 block=block,
 errors=errors,
)

def extract_sql_blocks(
 self,
 text: str,
) -> list[str]:
 blocks: list[str] = []
 current: list[str] = []
 in_exec_sql = False

 for line in text.splitlines():
 if self.EXEC_SQL_START.match(line):
 in_exec_sql = True
 current = [
 line,
]

 if self.EXEC_SQL_END.match(line):
 blocks.append(
 "\n".join(current),
)

 current = []
 in_exec_sql = False

 continue

 if in_exec_sql:
 current.append(
 line,
)

 if self.EXEC_SQL_END.match(line):
 blocks.append(
 "\n".join(current),
)

 current = []
 in_exec_sql = False

 return blocks

def validate_sql_commas(
 self,
 block: str,
 errors: list[str],
) -> None:
 if re.search(
 r",\s*",
 block,
):
 errors.append(
 "SQL block contains duplicate commas."
)

```



```

if re.search(
 r",\s*(FROM|WHERE|END-EXEC)",
 block,
 flags=re.IGNORECASE,
):
 errors.append(
 "SQL block contains trailing comma before FROM, WHERE, or END-EXEC."
)

```

```

=====
FILE: src\idms_db2_converter\validators\schema_validator.py
ENCODING: utf-8
=====

```

```

import re
from idms_db2_converter.models import CobolAnalysis, Column, Relationship, SchemaModel

```

```

class SchemaValidator:

```

```

 """

```

```

 Validates and enriches schema references used by COBOL.

```

```

 This validator intentionally performs generic inference:

```

- Infers missing primary keys from field names.
- Infers missing set relationships from set-name tokens and COBOL usage.
- Does not hard-code application-specific record or set names.

```

 """

```

```

def validate(self, schema: SchemaModel, analysis: CobolAnalysis) -> list[str]:
 errors = []

```

```

 self._ensure_primary_keys(schema)

```

```

 for record in analysis.idms_records:

```

```

 if record not in schema.records:

```

```

 errors.append(
 f"COBOL references record {record}, but schema does not define it."
)

```

```

 for record in analysis.obtain_calc_records:

```

```

 if record not in schema.records:

```

```

 errors.append(f"OBTAIN CALC references missing record {record}.")
 continue

```

```

 if not schema.records[record].primary_key:

```

```

 self._infer_primary_key_for_record(schema, record)

```

```

 if not schema.records[record].primary_key:

```

```

 errors.append(f"OBTAIN CALC record {record} has no primary key.")

```

```

 for record_name, set_name in analysis.obtain_next:

```

```

 self._validate_set(

```

```

 schema=schema,
 set_name=set_name,
 errors=errors,
 expected_child_record=record_name,
)

```

```

 for set_name in analysis.obtain_owner_sets:

```

```

 self._validate_set(

```

```

 schema=schema,
 set_name=set_name,
 errors=errors,
 expected_child_record=None,
)

```

```

 for set_name in analysis.find_first_sets:

```

```

 self._validate_set(

```

```

 schema=schema,
 set_name=set_name,
 errors=errors,
 expected_child_record=None,
)

```

```

return errors

def _ensure_primary_keys(self, schema: SchemaModel) -> None:
 for record_name in list(schema.records.keys()):
 self._infer_primary_key_for_record(schema, record_name)

def _infer_primary_key_for_record(
 self,
 schema: SchemaModel,
 record_name: str,
) -> None:
 if record_name not in schema.records:
 return

 record = schema.records[record_name]

 if record.primary_key:
 if record.primary_key in record.fields:
 record.fields[record.primary_key].nullable = False
 return

 candidate = self._find_primary_key_candidate(
 record_name=record_name,
 fields=set(record.fields.keys()),
)

 if candidate:
 record.primary_key = candidate
 record.fields[candidate].nullable = False
 return

 if record.fields:
 first_field = next(iter(record.fields.keys()))
 record.primary_key = first_field
 record.fields[first_field].nullable = False

def _find_primary_key_candidate(
 self,
 record_name: str,
 fields: set[str],
) -> str | None:
 normalized_record = self._normalize(record_name)
 compact_record = self._compact(normalized_record)

 direct_candidates = [
 f"{normalized_record}_ID",
 f"{normalized_record}_CODE",
]

 for candidate in direct_candidates:
 if candidate in fields:
 return candidate

 for field in fields:
 normalized_field = self._normalize(field)
 compact_field = self._compact(normalized_field)

 if normalized_field.endswith("_ID") and compact_record in compact_field:
 return field

 if normalized_field.endswith("_CODE") and compact_record in compact_field:
 return field

 id_fields = [
 field
 for field in fields
 if self._normalize(field).endswith("_ID")
]

 if len(id_fields) == 1:
 return id_fields[0]

 code_fields = [
 field
 for field in fields
 if self._normalize(field).endswith("_CODE")
]

```

```

]

if len(code_fields) == 1:
 return code_fields[0]

return None

def _validate_set(
 self,
 schema: SchemaModel,
 set_name: str,
 errors: list[str],
 expected_child_record: str | None,
) -> None:
 if set_name not in schema.relationships:
 inferred = self._infer_relationship(
 schema=schema,
 set_name=set_name,
 expected_child_record=expected_child_record,
)

 if inferred:
 schema.relationships[set_name] = inferred
 else:
 errors.append(
 f"COBOL references set {set_name}, but schema relationships do not define it."
)
 return

 rel = schema.relationships[set_name]

 if rel.parent_record not in schema.records:
 errors.append(
 f"Set {set_name} parent record {rel.parent_record} is missing."
)
 return

 if rel.child_record not in schema.records:
 errors.append(
 f"Set {set_name} child record {rel.child_record} is missing."
)
 return

 if not rel.parent_key:
 self._infer_primary_key_for_record(schema, rel.parent_record)
 rel.parent_key = schema.records[rel.parent_record].primary_key

 if not rel.child_fk:
 rel.child_fk = self._infer_child_fk(
 schema=schema,
 parent_record=rel.parent_record,
 child_record=rel.child_record,
 parent_key=rel.parent_key,
)

 if not rel.parent_key:
 errors.append(f"Set {set_name} has no parent_key.")

 if not rel.child_fk:
 errors.append(f"Set {set_name} has no child_fk.")

 if rel.parent_key and rel.parent_key not in schema.records[rel.parent_record].fields:
 self._add_field_like_parent_key(
 schema=schema,
 target_record=rel.parent_record,
 source_record=rel.parent_record,
 source_key=rel.parent_key,
 target_field=rel.parent_key,
 nullable=False,
)

 if rel.child_fk and rel.child_fk not in schema.records[rel.child_record].fields:
 self._add_field_like_parent_key(
 schema=schema,
 target_record=rel.child_record,
 source_record=rel.parent_record,

```

```

 source_key=rel.parent_key,
 target_field=rel.child_fk,
 nullable=True,
)

def _infer_relationship(
 self,
 schema: SchemaModel,
 set_name: str,
 expected_child_record: str | None,
) -> Relationship | None:
 child_record = self._infer_child_record(
 schema=schema,
 set_name=set_name,
 expected_child_record=expected_child_record,
)

 if not child_record:
 return None

 parent_record = self._infer_parent_record(
 schema=schema,
 set_name=set_name,
 child_record=child_record,
)

 if not parent_record:
 return None

 self._infer_primary_key_for_record(schema, parent_record)

 parent_key = schema.records[parent_record].primary_key

 if not parent_key:
 return None

 child_fk = self._infer_child_fk(
 schema=schema,
 parent_record=parent_record,
 child_record=child_record,
 parent_key=parent_key,
)

 if not child_fk:
 child_fk = parent_key

 if child_fk not in schema.records[child_record].fields:
 self._add_field_like_parent_key(
 schema=schema,
 target_record=child_record,
 source_record=parent_record,
 source_key=parent_key,
 target_field=child_fk,
 nullable=True,
)

 return Relationship(
 set_name=set_name,
 parent_record=parent_record,
 child_record=child_record,
 cardinality="1:N",
 parent_key=parent_key,
 child_fk=child_fk,
 order_by=[child_fk],
)

def _infer_child_record(
 self,
 schema: SchemaModel,
 set_name: str,
 expected_child_record: str | None,
) -> str | None:
 if expected_child_record and expected_child_record in schema.records:
 return expected_child_record

 set_tokens = self._tokens(set_name)

```

```

best_score = 0
best_record = None

for record_name in schema.records:
 score = self._score_record_against_tokens(record_name, set_tokens)

 if score > best_score:
 best_score = score
 best_record = record_name

return best_record if best_score > 0 else None

def _infer_parent_record(
 self,
 schema: SchemaModel,
 set_name: str,
 child_record: str,
) -> str | None:
 set_tokens = self._tokens(set_name)

 best_score = 0
 best_record = None

 for record_name in schema.records:
 if record_name == child_record:
 continue

 score = self._score_record_against_tokens(record_name, set_tokens)

 if score > best_score:
 best_score = score
 best_record = record_name

 return best_record if best_score > 0 else None

def _infer_child_fk(
 self,
 schema: SchemaModel,
 parent_record: str,
 child_record: str,
 parent_key: str | None,
) -> str | None:
 if not parent_key:
 return None

 child = schema.records[child_record]
 parent_key_norm = self._normalize(parent_key)

 if parent_key in child.fields:
 return parent_key

 if parent_key_norm in child.fields:
 return parent_key_norm

 parent_tokens = self._tokens(parent_record)
 key_suffixes = ["_ID", "_CODE"]

 for field_name in child.fields:
 normalized_field = self._normalize(field_name)

 if normalized_field == parent_key_norm:
 return field_name

 for token in parent_tokens:
 if normalized_field.startswith(token + "_"):
 for suffix in key_suffixes:
 if normalized_field.endswith(suffix):
 return field_name

 parent_compact = self._compact(parent_record)

 for field_name in child.fields:
 compact_field = self._compact(field_name)

 if parent_compact and parent_compact in compact_field:

```

```

 return field_name

 return None

def _add_field_like_parent_key(
 self,
 schema: SchemaModel,
 target_record: str,
 source_record: str,
 source_key: str | None,
 target_field: str,
 nullable: bool,
) -> None:
 if not source_key:
 return

 if source_record not in schema.records:
 return

 source = schema.records[source_record]
 target = schema.records[target_record]

 source_column = source.fields.get(source_key)

 if source_column:
 target.fields[target_field] = Column(
 name=target_field,
 datatype=source_column.datatype,
 length=source_column.length,
 scale=source_column.scale,
 nullable=nullable,
)
 else:
 target.fields[target_field] = Column(
 name=target_field,
 datatype="CHAR",
 length=12,
 scale=None,
 nullable=nullable,
)

def _score_record_against_tokens(
 self,
 record_name: str,
 tokens: list[str],
) -> int:
 normalized_record = self._normalize(record_name)
 compact_record = self._compact(record_name)

 score = 0

 for token in tokens:
 normalized_token = self._normalize(token)
 compact_token = self._compact(token)

 if normalized_token == normalized_record:
 score += 20
 continue

 if normalized_record.startswith(normalized_token):
 score += 10
 continue

 if normalized_token.startswith(normalized_record):
 score += 10
 continue

 if compact_token and compact_record.startswith(compact_token):
 score += 6
 continue

 if compact_token and compact_token in compact_record:
 score += 4
 continue

 if normalized_token[:3] and normalized_record.startswith(normalized_token[:3]):

```

```

 score += 2

 return score

def _tokens(self, value: str) -> list[str]:
 normalized = self._normalize(value)

 return [
 token
 for token in normalized.split("_")
 if token
]

def _normalize(self, value: str) -> str:
 return value.upper().replace("-", "_")

def _compact(self, value: str) -> str:
 return re.sub(r"^[A-Z0-9]", "", self._normalize(value))

=====
FILE: src\idms_modernizer__init__.py
ENCODING: utf-8
=====

[Empty file]

=====
FILE: src\idms_modernizer\app.py
ENCODING: utf-8
=====

from pathlib import Path
from time import perf_counter

import streamlit as st

from idms_modernizer.core.config import settings
from idms_modernizer.core.utils import ensure_directory
from idms_modernizer.core.constants import (
 ER_DIAGRAM_FILE,
 PHASE2_METADATA_FILE,
)
from idms_modernizer.parsers.cobol_pdf_extractor import CobolPdfExtractor
from idms_modernizer.services.metadata_service import MetadataService
from idms_modernizer.services.canonical_schema_builder import (
 CanonicalSchemaBuilder,
)
from idms_modernizer.services.canonical_reconciler import (
 CanonicalReconciler,
)
from idms_modernizer.services.db2_model_builder import DB2ModelBuilder
from idms_modernizer.services.phase2_metadata_generator import (
 Phase2MetadataGenerator,
)
from idms_modernizer.services.phase2_conversion_bridge import (
 Phase2ConversionBridge,
)
from idms_modernizer.services.er_diagram_generator import (
 generate_er_diagram,
)
from idms_modernizer.services.excel_sheet_mapping_service import (
 ExcelSheetMappingService,
)
from idms_modernizer.generators.ddl_generator import DDLGenerator

def initialize_directories() -> None:
 ensure_directory(
 settings.input_dir,
)

 ensure_directory(
 settings.output_dir,
)

```

```

def initialize_session_state() -> None:
 defaults = {
 "generated": False,
 "schema_path": "",
 "cobol_pdf_path": "",
 "metadata": None,
 "canonical_schema": None,
 "db2_model": None,
 "ddl_text": "",
 "canonical_json": "",
 "phase2_metadata_json": "",
 "cobol_text": "",
 "converted_cobol": "",
 "relationships": [],
 "all_sets": [],
 "record_count": 0,
 "set_count": 0,
 "relationship_count": 0,
 "validation_messages": [],
 "generation_warnings": [],
 "generation_timings": [],
 "er_png_path": "",
 "er_image_bytes": None,
 "output_files": {},
 "excel_mapping_rows": [],
 }

 for key, value in defaults.items():
 if key not in st.session_state:
 st.session_state[key] = value

def reset_outputs() -> None:
 st.session_state.generated = False
 st.session_state.schema_path = ""
 st.session_state.cobol_pdf_path = ""
 st.session_state.metadata = None
 st.session_state.canonical_schema = None
 st.session_state.db2_model = None
 st.session_state.ddl_text = ""
 st.session_state.canonical_json = ""
 st.session_state.phase2_metadata_json = ""
 st.session_state.cobol_text = ""
 st.session_state.converted_cobol = ""
 st.session_state.relationships = []
 st.session_state.all_sets = []
 st.session_state.record_count = 0
 st.session_state.set_count = 0
 st.session_state.relationship_count = 0
 st.session_state.validation_messages = []
 st.session_state.generation_warnings = []
 st.session_state.generation_timings = []
 st.session_state.er_png_path = ""
 st.session_state.er_image_bytes = None
 st.session_state.output_files = {}
 st.session_state.excel_mapping_rows = []

def save_uploaded_file(
 uploaded_file,
 target_folder: str,
) -> str:
 target_dir = Path(
 target_folder,
)

 target_dir.mkdir(
 parents=True,
 exist_ok=True,
)

 target_path = target_dir / uploaded_file.name

 with open(

```



```

 target_path,
 "wb",
) as output_file:
 output_file.write(
 uploaded_file.getbuffer(),
)

 return str(
 target_path,
)

def write_output_file(
 output_dir: Path,
 file_name: str,
 content: str,
 encoding: str = "utf-8",
) -> Path:
 output_dir.mkdir(
 parents=True,
 exist_ok=True,
)

 path = output_dir / file_name

 path.write_text(
 content,
 encoding=encoding,
)

 return path

def log_timing(
 timings: list[str],
 label: str,
 step_start: float,
) -> float:
 elapsed = perf_counter() - step_start

 timings.append(
 f"{label}: {elapsed:.2f} seconds",
)

 return perf_counter()

def build_sets_summary(
 metadata,
) -> list[str]:
 all_sets = set()

 for record in metadata.records:
 for membership in record.set_memberships:
 set_name = getattr(
 membership,
 "set_name",
 "",
)

 if set_name:
 all_sets.add(
 set_name,
)

 return sorted(
 all_sets,
)

def build_relationship_rows(
 relationships,
) -> list[dict[str, str]]:
 rows = []

 for relationship in relationships:

```

```

rows.append(
 {
 "Owner Record": getattr(
 relationship,
 "owner_record",
 "",
),
 "Member Record": getattr(
 relationship,
 "member_record",
 "",
),
 "Set Name": getattr(
 relationship,
 "set_name",
 "",
),
 }
)

return rows

def build_mapping_row_count_by_table(
 rows: list[dict],
 include_total: bool = True,
) -> list[dict[str, int | str]]:
 """
 Builds table-level counts from the actual Excel Sheet Mapping rows.

 This count matches the detailed mapping table because it counts the
 generated mapping rows, not only DB2 physical columns.

 Output column order:
 - Column Field Count
 - Table Name
 """
 table_counts: dict[str, int] = {}

 for row in rows or []:
 table_name = (
 row.get("New DB2 Record")
 or row.get("Cobol Record IDMS")
 or ""
)

 table_name = str(
 table_name,
).strip()

 if not table_name:
 continue

 table_counts[table_name] = table_counts.get(
 table_name,
 0,
) + 1

 output_rows: list[dict[str, int | str]] = []

 total_count = 0

 for table_name in sorted(table_counts):
 count = table_counts[table_name]

 output_rows.append(
 {
 "Column Field Count": count,
 "Table Name": table_name,
 }
)

 total_count += count

 if include_total:
 output_rows.append(

```

```

 {
 "Column Field Count": total_count,
 "Table Name": "TOTAL",
 }
)

 return output_rows

def build_db2_physical_column_count_rows(
 db2_model,
 include_total: bool = True,
) -> list[dict[str, int | str]]:
 """
 Builds table-level physical DB2 column counts.

 This is separate from mapping row counts because COBOL YEAR, MONTH,
 and DAY fields can map to one DB2 DATE column.
 """
 table_rows: list[dict[str, int | str]] = []

 if db2_model is None:
 return table_rows

 total_count = 0

 for table in getattr(
 db2_model,
 "tables",
 [],
) or []:
 table_name = getattr(
 table,
 "name",
 "",
)

 columns = getattr(
 table,
 "columns",
 [],
) or []

 count = len(
 columns,
)

 table_rows.append(
 {
 "Column Field Count": count,
 "Table Name": table_name,
 }
)

 total_count += count

 if include_total:
 table_rows.append(
 {
 "Column Field Count": total_count,
 "Table Name": "TOTAL",
 }
)

 return table_rows

def generate_outputs(
 schema_pdf,
 cobol_pdf,
) -> None:
 total_start = perf_counter()
 step_start = perf_counter()
 timings: list[str] = []

 reset_outputs()

```

```

warnings = []

schema_path = save_uploaded_file(
 schema_pdf,
 settings.input_dir,
)

cobol_pdf_path = save_uploaded_file(
 cobol_pdf,
 settings.input_dir,
)

step_start = log_timing(
 timings,
 "Save uploaded files",
 step_start,
)

metadata_service = MetadataService()

metadata = metadata_service.build_metadata(
 schema_path,
)

step_start = log_timing(
 timings,
 "Build metadata from schema PDF",
 step_start,
)

canonical_builder = CanonicalSchemaBuilder()

canonical_schema = canonical_builder.build(
 metadata=metadata,
)

step_start = log_timing(
 timings,
 "Build canonical schema",
 step_start,
)

canonical_reconciler = CanonicalReconciler()

canonical_schema = canonical_reconciler.reconcile(
 canonical_schema=canonical_schema,
 metadata=metadata,
)

step_start = log_timing(
 timings,
 "Reconcile canonical schema",
 step_start,
)

db2_builder = DB2ModelBuilder()

db2_model = db2_builder.build(
 canonical_schema,
)

step_start = log_timing(
 timings,
 "Build DB2 model",
 step_start,
)

ddl_generator = DDLGenerator()

ddl_text = ddl_generator.generate(
 db2_model,
)

step_start = log_timing(
 timings,

```

```

 "Generate DB2 DDL",
 step_start,
)

 excel_mapping_service = ExcelSheetMappingService()

 excel_mapping_rows = excel_mapping_service.build(
 metadata=metadata,
 db2_model=db2_model,
)

 step_start = log_timing(
 timings,
 "Generate Excel Sheet Mapping rows",
 step_start,
)

 phase2_metadata_generator = Phase2MetadataGenerator()

 phase2_metadata_json = phase2_metadata_generator.generate_json(
 canonical_schema=canonical_schema,
 db2_model=db2_model,
 metadata=metadata,
)

 step_start = log_timing(
 timings,
 "Generate Phase 2 metadata JSON",
 step_start,
)

 canonical_json = canonical_schema.model_dump_json(
 indent=2,
)

 step_start = log_timing(
 timings,
 "Generate canonical JSON",
 step_start,
)

 cobol_extractor = CobolPdfExtractor()

 cobol_text = cobol_extractor.extract_text(
 cobol_pdf_path,
)

 step_start = log_timing(
 timings,
 "Extract COBOL PDF text",
 step_start,
)

 converted_cobol = ""
 validation_messages = []

 try:
 phase2_bridge = Phase2ConversionBridge()

 converted_cobol, validation_messages = phase2_bridge.convert(
 cobol_text=cobol_text,
 canonical_json=canonical_json,
 phase2_metadata_json=phase2_metadata_json,
 ddl_text=ddl_text,
 idms_schema_text=None,
 relationship_overrides_json=None,
 target_program=None,
 use_ddl=True,
 use_idms_schema=False,
 use_overrides=False,
)

 except Exception as exc:
 converted_cobol = ""
 validation_messages = [
 f"Phase 2 COBOL conversion failed: {exc}",

```

```

]

 step_start = log_timing(
 timings,
 "Phase 2 COBOL conversion",
 step_start,
)

 relationships = metadata.relationships

 all_sets = build_sets_summary(
 metadata,
)

 step_start = log_timing(
 timings,
 "Build relationship and set summaries",
 step_start,
)

 output_dir = Path(
 settings.output_dir,
)

 output_files = {}

 output_files["ddl"] = write_output_file(
 output_dir=output_dir,
 file_name="db2_ddl.sql",
 content=ddl_text,
)

 output_files["canonical"] = write_output_file(
 output_dir=output_dir,
 file_name="canonical_model.json",
 content=canonical_json,
)

 output_files["phase2_metadata"] = write_output_file(
 output_dir=output_dir,
 file_name=PHASE2_METADATA_FILE,
 content=phase2_metadata_json,
)

 output_files["converted_cobol"] = write_output_file(
 output_dir=output_dir,
 file_name="converted_db2_cobol.cbl",
 content=converted_cobol,
)

 step_start = log_timing(
 timings,
 "Write output files",
 step_start,
)

 er_png_path = ""
 er_image_bytes = None

 try:
 er_path = output_dir / ER_DIAGRAM_FILE

 er_png_path = generate_er_diagram(
 metadata,
 str(
 er_path,
),
)

 with open(
 er_png_path,
 "rb",
) as image_file:
 er_image_bytes = image_file.read()

 output_files["er_diagram"] = Path(

```

```

 er_png_path,
)

except Exception as exc:
 warnings.append(
 "ER diagram was not generated. "
 "Graphviz may not be installed or configured. "
 f"Details: {exc}"
)

step_start = log_timing(
 timings,
 "ER diagram generation",
 step_start,
)

st.session_state.generated = True
st.session_state.schema_path = schema_path
st.session_state.cobol_pdf_path = cobol_pdf_path
st.session_state.metadata = metadata
st.session_state.canonical_schema = canonical_schema
st.session_state.db2_model = db2_model
st.session_state.ddl_text = ddl_text
st.session_state.canonical_json = canonical_json
st.session_state.phase2_metadata_json = phase2_metadata_json
st.session_state.cobol_text = cobol_text
st.session_state.converted_cobol = converted_cobol
st.session_state.relationships = relationships
st.session_state.all_sets = all_sets
st.session_state.record_count = len(
 metadata.records,
)
st.session_state.set_count = len(
 all_sets,
)
st.session_state.relationship_count = len(
 relationships,
)
st.session_state.validation_messages = validation_messages
st.session_state.generation_warnings = warnings
st.session_state.er_png_path = er_png_path
st.session_state.er_image_bytes = er_image_bytes
st.session_state.output_files = output_files
st.session_state.excel_mapping_rows = excel_mapping_rows

total_elapsed = perf_counter() - total_start

timings.append(
 f"TOTAL: {total_elapsed:.2f} seconds",
)

st.session_state.generation_timings = timings

def render_download_button(
 label: str,
 path,
 file_name: str,
 mime: str,
) -> None:
 if not path:
 st.button(
 label,
 disabled=True,
 use_container_width=True,
)
 return

with open(
 path,
 "rb",
) as file:
 st.download_button(
 label=label,
 data=file,
 file_name=file_name,

```

```

 mime=mime,
 use_container_width=True,
)

def render_download_buttons() -> None:
 if not st.session_state.generated:
 return

 st.markdown("### Download Outputs")

 output_files = st.session_state.output_files

 col1, col2, col3, col4, col5 = st.columns(
 5,
)

 with col1:
 render_download_button(
 label="DB2 DDL",
 path=output_files.get(
 "ddl",
),
 file_name="db2_ddl.sql",
 mime="text/sql",
)

 with col2:
 render_download_button(
 label="Phase Metadata",
 path=output_files.get(
 "phase2_metadata",
),
 file_name=PHASE2_METADATA_FILE,
 mime="application/json",
)

 with col3:
 render_download_button(
 label="Canonical JSON",
 path=output_files.get(
 "canonical",
),
 file_name="canonical_model.json",
 mime="application/json",
)

 with col4:
 if st.session_state.er_image_bytes:
 st.download_button(
 label="ER Diagram",
 data=st.session_state.er_image_bytes,
 file_name=ER_DIAGRAM_FILE,
 mime="image/png",
 use_container_width=True,
)
 else:
 st.button(
 "ER Diagram",
 disabled=True,
 use_container_width=True,
)

 with col5:
 render_download_button(
 label="DB2 COBOL",
 path=output_files.get(
 "converted_cobol",
),
 file_name="converted_db2_cobol.cbl",
 mime="text/plain",
)

def total_timing_only() -> str:
 for timing in st.session_state.generation_timings:

```



```

 if timing.startswith(
 "TOTAL:",
):
 return timing

 return ""

def get_total_generation_time() -> str:
 total_timing = total_timing_only()

 if not total_timing:
 return ""

 return total_timing.replace(
 "TOTAL:",
 "",
).strip()

def render_status_panel() -> None:
 if not st.session_state.generated:
 return

 total_time = get_total_generation_time()

 if total_time:
 st.success(
 f"Generation completed in {total_time}",
)

 if st.session_state.generation_warnings:
 with st.expander(
 "Generation Warnings",
 expanded=False,
):
 for warning in st.session_state.generation_warnings:
 st.warning(
 warning,
)

 if not st.session_state.validation_messages:
 st.success(
 "COBOL conversion validation passed.",
)
 else:
 st.warning(
 "COBOL conversion completed with validation messages. "
 "Open the Validation tab for details."
)

def render_main_tab() -> None:
 st.markdown("### Generate Modernization Outputs")

 st.info(
 "Upload the Schema Listing PDF and COBOL Code PDF to generate DB2 "
 "DDL, metadata, ER diagram, converted DB2 COBOL, and sheet mapping."
)

 col1, col2 = st.columns(
 2,
)

 with col1:
 schema_pdf = st.file_uploader(
 "Schema Listing PDF",
 type=["pdf"],
 key="schema_listing_pdf",
)

 with col2:
 cobol_pdf = st.file_uploader(
 "COBOL Code PDF",
 type=["pdf"],
 key="cobol_code_pdf",

```

```

)

generate_clicked = st.button(
 "Generate Outputs",
 type="primary",
 use_container_width=True,
)

if generate_clicked:
 if schema_pdf is None:
 st.error(
 "Please upload the Schema Listing PDF.",
)
 st.stop()

 if cobol_pdf is None:
 st.error(
 "Please upload the COBOL Code PDF.",
)
 st.stop()

 with st.spinner(
 "Processing schema, generating DB2 artifacts, and converting COBOL..."
):
 try:
 generate_outputs(
 schema_pdf=schema_pdf,
 cobol_pdf=cobol_pdf,
)

 st.success(
 "Generation completed successfully.",
)

 except Exception as exc:
 st.error(
 "Generation failed.",
)
 st.exception(
 exc,
)
 st.stop()

if st.session_state.generated:
 st.markdown("### Output Status")

 col_a, col_b = st.columns(
 2,
)

 with col_a:
 st.write(
 f"Schema PDF: `{st.session_state.schema_path}`",
)

 with col_b:
 st.write(
 f"COBOL PDF: `{st.session_state.cobol_pdf_path}`",
)

 render_status_panel()
 render_download_buttons()

def render_metadata_overview_tab() -> None:
 if not st.session_state.generated:
 st.info(
 "Generate outputs from the Main tab first.",
)
 return

 st.markdown("## Metadata Overview")

 st.markdown("### Summary")

 col1, col2, col3, col4 = st.columns(

```

```

 4,
)

with col1:
 st.metric(
 "Records",
 st.session_state.record_count,
)

with col2:
 st.metric(
 "Sets",
 st.session_state.set_count,
)

with col3:
 st.metric(
 "Relationships",
 st.session_state.relationship_count,
)

with col4:
 st.metric(
 "Sheet Mapping Rows",
 len(
 st.session_state.excel_mapping_rows,
),
)

st.divider()

st.markdown("### Detected Sets")

st.json(
 st.session_state.all_sets,
)

st.divider()

st.markdown("### Detected Relationships")

relationship_rows = build_relationship_rows(
 st.session_state.relationships,
)

if relationship_rows:
 st.dataframe(
 relationship_rows,
 use_container_width=True,
 hide_index=True,
)
else:
 st.info(
 "No relationships detected.",
)

st.divider()

st.markdown("### Table List and Mapping Row Counts")

mapping_count_rows = build_mapping_row_count_by_table(
 rows=st.session_state.excel_mapping_rows,
 include_total=True,
)

if mapping_count_rows:
 st.dataframe(
 mapping_count_rows,
 use_container_width=True,
 hide_index=True,
)
else:
 st.info(
 "No table mapping row counts available.",
)

```

```

st.caption(
 "This count is based on actual Excel Sheet Mapping rows. "
 "The TOTAL matches the detailed mapping table."
)

st.divider()

st.markdown("### DB2 Physical Column Counts")

physical_count_rows = build_db2_physical_column_count_rows(
 db2_model=st.session_state.db2_model,
 include_total=True,
)

if physical_count_rows:
 st.dataframe(
 physical_count_rows,
 use_container_width=True,
 hide_index=True,
)
else:
 st.info(
 "No DB2 physical column counts available.",
)

st.caption(
 "This count is based on DB2 physical columns. It can differ from "
 "mapping row count when COBOL YEAR, MONTH, and DAY fields map to "
 "one DB2 DATE column."
)

def render_ddl_tab() -> None:
 if not st.session_state.generated:
 st.info(
 "Generate outputs from the Main tab first.",
)
 return

 st.markdown("### DB2 DDL Preview")

 st.code(
 st.session_state.ddl_text,
 language="sql",
)

def render_phase2_metadata_tab() -> None:
 if not st.session_state.generated:
 st.info(
 "Generate outputs from the Main tab first.",
)
 return

 st.markdown("### Phase 2 Metadata Preview")

 st.code(
 st.session_state.phase2_metadata_json,
 language="json",
)

def render_excel_sheet_mapping_tab() -> None:
 if not st.session_state.generated:
 st.info(
 "Generate outputs from the Main tab first.",
)
 return

 st.markdown("### Excel Sheet Mapping")

 rows = st.session_state.excel_mapping_rows

 if not rows:
 st.info(
 "No mapping rows generated.",

```

```

)
 return

st.markdown("### Sheet Map Abstract")

abstract_rows = build_mapping_row_count_by_table(
 rows=rows,
 include_total=True,
)

if abstract_rows:
 st.dataframe(
 abstract_rows,
 use_container_width=True,
 hide_index=True,
)
else:
 st.info(
 "No table abstract rows available.",
)

st.caption(
 "The TOTAL row matches the number of detailed mapping rows below."
)

st.markdown("### Sheet Mapping Details")

st.dataframe(
 rows,
 use_container_width=True,
 hide_index=True,
)

def render_er_diagram_tab() -> None:
 if not st.session_state.generated:
 st.info(
 "Generate outputs from the Main tab first.",
)
 return

 st.markdown("## ER Diagram")

 if st.session_state.er_image_bytes:
 st.image(
 st.session_state.er_image_bytes,
)
 else:
 st.warning(
 "ER diagram was not generated. Graphviz may not be installed "
 "or configured."
)

def render_converted_cobol_tab() -> None:
 if not st.session_state.generated:
 st.info(
 "Generate outputs from the Main tab first.",
)
 return

 st.markdown("## Converted DB2 COBOL")

 if not st.session_state.converted_cobol:
 st.warning(
 "Converted COBOL output is empty or conversion failed.",
)

 st.text_area(
 "Final DB2 COBOL Code",
 value=st.session_state.converted_cobol,
 height=750,
)

def render_validation_tab() -> None:

```

```

if not st.session_state.generated:
 st.info(
 "Generate outputs from the Main tab first.",
)
 return

st.markdown("## Validation")

if st.session_state.generation_timings:
 st.markdown("### Generation Timings")

 st.code(
 "\n".join(
 st.session_state.generation_timings,
)
)

if st.session_state.validation_messages:
 st.markdown("### Validation Messages")

 for message in st.session_state.validation_messages:
 st.warning(
 message,
)
else:
 st.success(
 "No warnings or validation messages.",
)

def main() -> None:
 st.set_page_config(
 page_title="IDMS DB2 Modernizer",
 layout="wide",
)

 initialize_directories()
 initialize_session_state()

 st.title(
 "IDMS > DB2 Modernizer",
)

 st.caption(
 "Generate DB2 DDL, Phase 2 metadata, canonical JSON, ER diagram, "
 "converted DB2 COBOL, and Excel-style sheet mapping from uploaded PDFs."
)

 tabs = st.tabs(
 [
 "Main",
 "Metadata Overview",
 "DB2 DDL",
 "Phase 2 Metadata",
 "Excel Sheet Mapping",
 "ER Diagram",
 "Converted DB2 COBOL",
 "Validation",
]
)

 with tabs[0]:
 render_main_tab()

 with tabs[1]:
 render_metadata_overview_tab()

 with tabs[2]:
 render_ddl_tab()

 with tabs[3]:
 render_phase2_metadata_tab()

 with tabs[4]:
 render_excel_sheet_mapping_tab()

```

```

with tabs[5]:
 render_er_diagram_tab()

with tabs[6]:
 render_converted_cobol_tab()

with tabs[7]:
 render_validation_tab()

if __name__ == "__main__":
 main()

```

```

=====
FILE: src\idms_modernizer\core__init__.py
ENCODING: utf-8
=====

```

[Empty file]

```

=====
FILE: src\idms_modernizer\core\config.py
ENCODING: utf-8
=====

```

```

from pathlib import Path

from pydantic_settings import BaseSettings

```

```

class Settings(BaseSettings):

 APP_NAME: str = (
 "IDMS DB2 Modernizer"
)

 BASE_DIR: Path = Path.cwd()

 INPUT_DIR: str = "data/input"

 OUTPUT_DIR: str = "data/output"

 TEMP_DIR: str = "data/temp"

 DEBUG: bool = True

 @property
 def input_dir(self) -> str:
 return self.INPUT_DIR

 @property
 def output_dir(self) -> str:
 return self.OUTPUT_DIR

 @property
 def temp_dir(self) -> str:
 return self.TEMP_DIR

 class Config:
 env_file = ".env"

```

```

settings = Settings()

```

```

=====
FILE: src\idms_modernizer\core\constants.py
ENCODING: utf-8
=====

```

```

SUPPORTED_FILE_TYPES = [
 "pdf"
]

```

```

MAX_UPLOAD_SIZE_MB = 100

DB2_DDL_FILE = (
 "db2_ddl.sql"
)

ER_DIAGRAM_FILE = (
 "er_diagram.png"
)

EXCEL_MODEL_FILE = (
 "db2_model.xlsx"
)

REPORT_FILE = (
 "migration_report.pdf"
)

SUPPORTED_FILE_TYPES = [
 "pdf"
]

MAX_UPLOAD_SIZE_MB = 100

DB2_DDL_FILE = (
 "db2_ddl.sql"
)

ER_DIAGRAM_FILE = (
 "er_diagram.png"
)

EXCEL_MODEL_FILE = (
 "db2_model.xlsx"
)

REPORT_FILE = (
 "migration_report.pdf"
)

CANONICAL_MODEL_FILE = (
 "canonical_model.json"
)

PHASE2_METADATA_FILE = (
 "phase2_metadata.json"
)

```

```

=====
FILE: src\idms_modernizer\core\exceptions.py
ENCODING: utf-8
=====

```

```

class ModernizerException(
 Exception
):
 pass

class PdfExtractionException(
 ModernizerException
):
 pass

class SchemaParsingException(
 ModernizerException
):
 pass

class ValidationException(
 ModernizerException
):
 pass

```



```
=====
FILE: src\idms_modernizer\core\logger.py
ENCODING: utf-8
=====
```

```
import logging

def get_logger(
 logger_name: str
) -> logging.Logger:

 logger = logging.getLogger(
 logger_name
)

 logger.setLevel(
 logging.INFO
)

 if not logger.handlers:

 handler = (
 logging.StreamHandler()
)

 formatter = (
 logging.Formatter(
 "%(asctime)s | %(levelname)s | %(message)s"
)
)

 handler.setFormatter(
 formatter
)

 logger.addHandler(
 handler
)

 return logger
```

```
=====
FILE: src\idms_modernizer\core\utils.py
ENCODING: utf-8
=====
```

```
from pathlib import Path
```

```
def ensure_directory(
 directory: str
) -> None:

 Path(
 directory
).mkdir(
 parents=True,
 exist_ok=True
)
```

```
def normalize_text(
 text: str
) -> str:

 return " ".join(
 text.split()
)
```

```
=====
FILE: src\idms_modernizer\domain__init__.py
ENCODING: utf-8
=====
```

[Empty file]

```
=====
FILE: src\idms_modernizer\domain\canonical_models.py
ENCODING: utf-8
=====
```

```
from pydantic import BaseModel, Field
```

```
class CanonicalField(BaseModel):
 name: str
 datatype: str | None = None
 length: int | None = None
 scale: int | None = None
 occurs: bool = False
 occurs_max: int | None = None
```

```
class CanonicalRecord(BaseModel):
 name: str

 # Backward-compatible single PK.
 primary_key: str | None = None

 # Composite PK support.
 # When CALC points to a group, physical child fields are stored here.
 primary_keys: list[str] = Field(default_factory=list)

 record_id: str | None = None
 location_mode: str | None = None
 fields: list[CanonicalField] = Field(default_factory=list)
```

```
class CanonicalSet(BaseModel):
 name: str
 owner_record: str | None = None
 member_record: str | None = None
 order_mode: str | None = None
```

```
class CanonicalRelationship(BaseModel):
 set_name: str
 parent_record: str
 child_record: str
 cardinality: str = "1:N"
```

```
class CanonicalSchema(BaseModel):
 records: list[CanonicalRecord] = Field(default_factory=list)
 sets: list[CanonicalSet] = Field(default_factory=list)
 relationships: list[CanonicalRelationship] = Field(default_factory=list)
```

```
=====
FILE: src\idms_modernizer\domain\db2_models.py
ENCODING: utf-8
=====
```

```
from dataclasses import dataclass, field
```

```
@dataclass
class DB2Column:
 name: str
 datatype: str
 nullable: bool = True
 primary_key: bool = False
 generated: bool = False
 source_kind: str = ""
```

```

@dataclass
class DB2ForeignKey:
 column_name: str
 reference_table: str
 reference_column: str
 set_name: str = ""

@dataclass
class DB2Table:
 name: str
 columns: list[DB2Column] = field(default_factory=list)
 foreign_keys: list[DB2ForeignKey] = field(default_factory=list)
 primary_key: str | None = None
 primary_keys: list[str] = field(default_factory=list)

```

```

@dataclass
class DB2Model:
 tables: list[DB2Table] = field(default_factory=list)

```

```

=====
FILE: src\idms_modernizer\domain\document_models.py
ENCODING: utf-8
=====

```

```

from pydantic import BaseModel, Field

```

```

class DocumentLine(BaseModel):
 line_number: int
 text: str

```

```

class DocumentPage(BaseModel):
 page_number: int
 lines: list[DocumentLine] = Field(
 default_factory=list
)

```

```

class DocumentModel(BaseModel):
 pages: list[DocumentPage] = Field(
 default_factory=list
)

```

```

=====
FILE: src\idms_modernizer\domain\models.py
ENCODING: utf-8
=====

```

```

from pydantic import BaseModel

```

```

from idms_modernizer.domain.db2_models import Table
from idms_modernizer.domain.relationship_models import (
 Relationship
)
from idms_modernizer.domain.schema_models import (
 SchemaMetadata
)

```

```

class ConversionContext(
 BaseModel
):

 schema_metadata: (
 SchemaMetadata | None
) = None

 relationships: (
 list[Relationship]
)

```

```
) = []
```

```
db2_tables: (
 list[Table]
) = []
```

```
=====
```

FILE: src\idms\_modernizer\domain\relationship\_models.py

ENCODING: utf-8

```
=====
```

```
from pydantic import BaseModel
```

```
class SetMembership(BaseModel):
```

```
 set_name: str
```

```
 role: str
```

```
class Relationship(BaseModel):
```

```
 set_name: str
```

```
 owner_record: str
```

```
 member_record: str
```

```
 cardinality: str = "1:N"
```

```
=====
```

FILE: src\idms\_modernizer\domain\schema\_models.py

ENCODING: utf-8

```
=====
```

```
from dataclasses import dataclass, field
```

```
from pydantic import BaseModel, Field
```

```
from idms_modernizer.domain.relationship_models import (
 Relationship,
 SetMembership,
)
```

```
class DataField(BaseModel):
```

```
 name: str
```

```
 level: int | None = None
```

```
 datatype: str | None = None
```

```
 length: int | None = None
```

```
 scale: int | None = None
```

```
 picture: str | None = None
```

```
 start_position: int | None = None
```

```
 end_position: int | None = None
```

```
 basetype: str | None = None
```

```
 has_child: bool = False
```

```
 is_group: bool = False
```

```
 occurs: bool = False
```

```
 occurs_min: int | None = None
```

```
 occurs_max: int | None = None
```

```
 raw_line: str | None = None
```

```
 rest: str | None = None
```

```
@dataclass
```

```
class Record:
```

```
 name: str
```

```

Physical / DDL-safe fields.
Used by canonical schema, DB2 model, DDL, Phase 2 metadata, and COBOL conversion.
fields: list[DataField] = field(
 default_factory=list,
)

Excel-only complete field list.
Includes group fields, leaf fields, outer date groups, key groups, attributes, OCCURS groups.
mapping_fields: list[DataField] = field(
 default_factory=list,
)

set_memberships: list[SetMembership] = field(
 default_factory=list,
)

primary_key: str | None = None
cobol_zone: str | None = None

```

```

class SetDefinition(BaseModel):
 name: str
 owner_record: str | None = None
 member_record: str | None = None

```

```

class SchemaMetadata(BaseModel):
 records: list[Record] = Field(
 default_factory=list,
)

 sets: list[SetDefinition] = Field(
 default_factory=list,
)

 relationships: list[Relationship] = Field(
 default_factory=list,
)

```

```

=====
FILE: src\idms_modernizer\domain\section_models.py
ENCODING: utf-8
=====

```

```

from dataclasses import dataclass, field

```

```

@dataclass
class RecordSection:
 record_name: str
 lines: list[str] = field(
 default_factory=list
)

```

```

=====
FILE: src\idms_modernizer\extractors\cobol_zone_extractor.py
ENCODING: utf-8
=====

```

```

import re

```

```

class CobolZoneExtractor:
 """
 Extracts the IDMS region / zone from a schema record section.

 Examples:
 WITHIN INS-DEMO-REGION OFFSET 5 PGS FOR 20 PGS
 WITHIN
 EMP-DEMO-REGION OFFSET 5 PGS FOR 45 PGS

 Output:
 INS-DEMO-REGION
 EMP-DEMO-REGION
 """

```

```
"""
```

```
DIRECT_WITHIN_PATTERN = re.compile(
 r"\bWITHIN\s+([A-Z][A-Z0-9-]*REGION)\b",
 re.IGNORECASE,
)
```

```
REGION_PATTERN = re.compile(
 r"\b([A-Z][A-Z0-9-]*REGION)\b",
 re.IGNORECASE,
)
```

```
def extract(
 self,
 lines: list[str],
) -> str | None:
 cleaned_lines = [
 self.clean_line(line)
 for line in lines
 if line and self.clean_line(line)
]

 if not cleaned_lines:
 return None

 joined_text = " ".join(cleaned_lines)

 direct_match = self.DIRECT_WITHIN_PATTERN.search(
 joined_text,
)

 if direct_match:
 return direct_match.group(1).upper()

 for index, line in enumerate(cleaned_lines):
 upper_line = line.upper()

 if upper_line == "WITHIN":
 region = self.find_region_after_within(
 lines=cleaned_lines,
 start_index=index + 1,
)

 if region:
 return region

 if "WITHIN" in upper_line:
 region = self.find_region_in_line(
 line=line,
)

 if region:
 return region

 region = self.find_region_after_within(
 lines=cleaned_lines,
 start_index=index + 1,
)

 if region:
 return region

 return None

def find_region_after_within(
 self,
 lines: list[str],
 start_index: int,
) -> str | None:
 for line in lines[start_index : start_index + 5]:
 region = self.find_region_in_line(
 line=line,
)

 if region:
 return region
```

```

 return None

 def find_region_in_line(
 self,
 line: str,
) -> str | None:
 match = self.REGION_PATTERN.search(
 line,
)

 if not match:
 return None

 return match.group(1).upper()

 def clean_line(
 self,
 line: str,
) -> str:
 if line is None:
 return ""

 cleaned = line.strip()
 cleaned = cleaned.replace("\u00a0", " ")
 cleaned = re.sub(r"\s+", " ", cleaned)

 return cleaned

```

```

=====
FILE: src\idms_modernizer\extractors\field_extractor.py
ENCODING: utf-8
=====

```

```

import re

from dataclasses import dataclass
from typing import List

from idms_modernizer.domain.schema_models import DataField

@dataclass
class FieldCandidate:
 level: int
 name: str
 rest: str
 original_line: str
 has_child: bool = False
 is_group: bool = False
 occurs: bool = False
 occurs_min: int | None = None
 occurs_max: int | None = None

class FieldExtractor:
 """
 Extracts IDMS schema fields.

 Generic behavior only:
 - No business field names are hardcoded.
 - No record names are hardcoded.
 - Physical extraction and Sheet Mapping extraction are separated.

 extract():
 - Used for physical / DDL-safe fields.
 - Returns only leaf fields.
 - Excludes FILLER by default because FILLER should not become a DB2 column.

 extract_all():
 - Used for Excel Sheet Mapping.
 - Returns all fields:
 groups, subgroups, leaves, date groups, date parts, OCCURS groups, and FILLER.
 - Includes FILLER by default so Sheet Mapping can show FILLER rows.
 """

```

```

FIELD_NAME_PATTERN = re.compile(
 r"^\s*(?P<level>0[1-9]|[1-4][0-9]|88)\s+"
 r"(?P<name>[A-Z][A-Z0-9-]*|FILLER)\b"
 r"(?P<rest>.*)$",
 re.IGNORECASE,
)

OCCURS_PATTERN = re.compile(
 r"\bOCCURS\s+"
 r"(?P<min>[0-9]+)"
 r"(?:\s+TO\s+(?P<max>[0-9]+))?",
 re.IGNORECASE,
)

def __init__(
 self,
 include_filler: bool = False,
 auto_number_filler: bool = False,
) -> None:
 self.include_filler = include_filler
 self.auto_number_filler = auto_number_filler

def extract(
 self,
 lines: List[str],
) -> List[DataField]:
 """
 Physical / DDL-safe extraction.

 FILLER is excluded here because physical DB2 columns should not be created
 from COBOL FILLER.
 """

 print("USING FIELD EXTRACTOR VERSION LEAF-ONLY-WITH-LEVEL")

 candidates = self.discover_candidates(
 lines=lines,
 include_filler=False,
)

 leaf_candidates = self.mark_and_filter_leaf_fields(
 candidates=candidates,
)

 return self.candidates_to_fields(
 candidates=leaf_candidates,
)

def extract_all(
 self,
 lines: List[str],
 include_filler: bool = True,
) -> List[DataField]:
 """
 Excel Sheet Mapping extraction.

 FILLER is included here so Sheet Mapping can show FILLER rows.
 """

 print("USING FIELD EXTRACTOR VERSION ALL-FIELDS-FOR-MAPPING")

 candidates = self.discover_candidates(
 lines=lines,
 include_filler=include_filler,
)

 self.mark_group_fields(
 candidates=candidates,
)

 return self.candidates_to_fields(
 candidates=candidates,
)

def discover_candidates(

```



```

self,
lines: List[str],
include_filler: bool | None = None,
) -> List[FieldCandidate]:
 candidates: List[FieldCandidate] = []

 if include_filler is None:
 include_filler = self.include_filler

 filler_index = 0

 for line in lines:
 cleaned_line = self.clean_line(
 line=line,
)

 if not cleaned_line:
 continue

 match = self.FIELD_NAME_PATTERN.match(
 cleaned_line,
)

 if not match:
 continue

 level = int(
 match.group("level"),
)

 name = match.group("name").upper()
 rest = match.group("rest").strip()

 if level == 88:
 continue

 if name == "FILLER":
 if not include_filler:
 continue

 filler_index += 1

 candidate_name = name

 if self.auto_number_filler:
 candidate_name = f"FILLER_{filler_index}"
 else:
 candidate_name = name

 occurs_info = self.parse_occurs(
 text=rest,
)

 candidate = FieldCandidate(
 level=level,
 name=candidate_name,
 rest=rest,
 original_line=cleaned_line,
 occurs=occurs_info["occurs"],
 occurs_min=occurs_info["occurs_min"],
 occurs_max=occurs_info["occurs_max"],
)

 candidates.append(candidate)

 return candidates

def mark_group_fields(
 self,
 candidates: List[FieldCandidate],
) -> None:
 for index, candidate in enumerate(candidates):
 candidate.has_child = False
 candidate.is_group = False

 for later_candidate in candidates[index + 1:]:

```

```

 if later_candidate.level <= candidate.level:
 break

 if later_candidate.level > candidate.level:
 candidate.has_child = True
 candidate.is_group = True
 break

def mark_and_filter_leaf_fields(
 self,
 candidates: List[FieldCandidate],
) -> List[FieldCandidate]:
 self.mark_group_fields(
 candidates=candidates,
)

 leaf_candidates: List[FieldCandidate] = []

 for candidate in candidates:
 if candidate.has_child:
 continue

 leaf_candidates.append(candidate)

 return leaf_candidates

def candidates_to_fields(
 self,
 candidates: List[FieldCandidate],
) -> List[DataField]:
 fields: List[DataField] = []

 for candidate in candidates:
 display_name = candidate.name

 if display_name.startswith("FILLER_"):
 display_name = "FILLER"

 field = DataField(
 name=display_name,
 level=candidate.level,
 rest=candidate.rest,
 raw_line=candidate.original_line,
 has_child=candidate.has_child,
 is_group=candidate.is_group,
 occurs=candidate.occurs,
 occurs_min=candidate.occurs_min,
 occurs_max=candidate.occurs_max,
)

 fields.append(field)

 return fields

def parse_occurs(
 self,
 text: str,
) -> dict:
 match = self.OCCURS_PATTERN.search(
 text or "",
)

 if not match:
 return {
 "occurs": False,
 "occurs_min": None,
 "occurs_max": None,
 }

 occurs_min = self.safe_int(
 value=match.group("min"),
)

 occurs_max_raw = match.group("max")

 occurs_max = (

```

```

 self.safe_int(
 value=occurs_max_raw,
)
 if occurs_max_raw is not None
 else occurs_min
)

 return {
 "occurs": True,
 "occurs_min": occurs_min,
 "occurs_max": occurs_max,
 }

def clean_line(
 self,
 line: str,
) -> str:
 value = str(line or "").strip()

 if not value:
 return ""

 value = value.replace("\u00a0", " ")
 value = re.sub(r"\s+", " ", value)

 return value.strip()

def safe_int(
 self,
 value,
) -> int | None:
 try:
 if value is None:
 return None

 return int(value)
 except Exception:
 return None

```

```

=====
FILE: src\idms_modernizer\extractors\owner_member_extractor.py
ENCODING: utf-8
=====

```

```

import re

from idms_modernizer.domain.relationship_models import (
 SetMembership
)

class OwnerMemberExtractor:

 SAME_LINE_PATTERN = re.compile(
 r"^\\s*([A-Z0-9\\-]+)\\s+(?:INDEX\\s+)?(OWNER|MEMBER)\\b",
 re.IGNORECASE
)

 SET_NAME_PATTERN = re.compile(
 r"^\\s*([A-Z][A-Z0-9\\-]+)\\s*$",
 re.IGNORECASE
)

 ROLE_PATTERN = re.compile(
 r"^\\s*(OWNER|MEMBER)\\b",
 re.IGNORECASE
)

 IGNORED_SET_NAMES = {
 "CALC"
 }

 HEADER_WORDS = {
 "SET",
 "TYPE",
 }

```

```

 "NEXT",
 "PRIOR",
 "OWNER",
 "MEMBER"
 }

def extract(
 self,
 record_name: str,
 lines: list[str]
) -> list[SetMembership]:

 memberships = []
 seen = set()

 in_dbkey_block = False
 pending_set_name = None

 for raw_line in lines:

 line = raw_line.strip().upper()

 if not line:
 continue

 if "DBKEY POSITIONS" in line:
 in_dbkey_block = True
 pending_set_name = None
 continue

 if in_dbkey_block and line.startswith("DATA ITEM"):
 break

 if not in_dbkey_block:
 continue

 same_line_match = self.SAME_LINE_PATTERN.search(
 line
)

 if same_line_match:

 set_name = same_line_match.group(1).upper()
 role = same_line_match.group(2).upper()

 pending_set_name = None

 if set_name in self.IGNORED_SET_NAMES:
 continue

 key = (
 set_name,
 role
)

 if key not in seen:
 seen.add(key)

 memberships.append(
 SetMembership(
 set_name=set_name,
 role=role
)
)

 continue

 role_match = self.ROLE_PATTERN.search(
 line
)

 if role_match and pending_set_name:

 set_name = pending_set_name
 role = role_match.group(1).upper()

```

```

 pending_set_name = None

 if set_name in self.IGNORED_SET_NAMES:
 continue

 key = (
 set_name,
 role
)

 if key not in seen:
 seen.add(key)

 memberships.append(
 SetMembership(
 set_name=set_name,
 role=role
)
)

 continue

 set_name_match = self.SET_NAME_PATTERN.search(
 line
)

 if set_name_match:

 candidate = set_name_match.group(1).upper()

 if candidate in self.HEADER_WORDS:
 continue

 if candidate in self.IGNORED_SET_NAMES:
 pending_set_name = None
 continue

 pending_set_name = candidate

 print(
 f"{record_name}: "
 f"{len(memberships)} memberships"
)

 for membership in memberships:
 print(
 f"{record_name} -> "
 f"{membership.set_name} "
 f"{membership.role}"
)

 return memberships

```

```

=====
FILE: src\idms_modernizer\extractors\primary_key_extractor.py
ENCODING: utf-8
=====

```

```
import re
```

```
from idms_modernizer.services.name_normalizer import NameNormalizer
```

```
class PrimaryKeyExtractor:
```

```
 """
```

```
 Extracts IDMS CALC primary key metadata.
```

```
 Generic behavior only:
```

- No hardcoded record names.
- No hardcoded key names.
- Handles listing formats with dots, spaces, and split lines.

```
 Supported examples:
```

- LOCATION MODE CALC USING EMP-ID-0415
- LOCATION MODE..... CALC USING KY-VMBFC DUPLICATES NOT ALLOWED

```

- CALC USING KY-VMBFC
- SET CONTROL ITEM FOR CALC <start> <length>
"""

CALC_PATTERN = re.compile(
 r"\bCALC\s+USING\s+([A-Z0-9-])\b",
 re.IGNORECASE,
)

CONTROL_ITEM_PATTERN = re.compile(
 r"\bSET\s+CONTROL\s+ITEM\s+FOR\s+CALC"
 r"(?:\s+(?P<start>[0-9]+)\s+(?P<length>[0-9]+))?",
 re.IGNORECASE,
)

CONTROL_ITEM_FOLLOWING_CALC_PATTERN = re.compile(
 r"\bCALC\s+(?P<start>[0-9]+)\s+(?P<length>[0-9]+)\b",
 re.IGNORECASE,
)

def extract(
 self,
 lines: list[str],
) -> str | None:
 cleaned_lines = [
 self.clean_line(line=line)
 for line in lines or []
]

 joined_text = " ".join(
 line
 for line in cleaned_lines
 if line
)

 match = self.CALC_PATTERN.search(joined_text)

 if match:
 return NameNormalizer.normalize(
 match.group(1),
)

 for line in cleaned_lines:
 match = self.CALC_PATTERN.search(line)

 if match:
 return NameNormalizer.normalize(
 match.group(1),
)

 return None

def extract_control_item(
 self,
 lines: list[str],
) -> dict[str, int] | None:
 cleaned_lines = [
 self.clean_line(line=line)
 for line in lines or []
 if self.clean_line(line=line)
]

 joined_text = " ".join(cleaned_lines)

 match = self.CONTROL_ITEM_PATTERN.search(joined_text)

 if match:
 start = match.group("start")
 length = match.group("length")

 if start and length:
 return {
 "start": int(start),
 "length": int(length),
 }

```

```

match = self.CONTROL_ITEM_FOLLOWING_CALC_PATTERN.search(joined_text)

if match:
 return {
 "start": int(match.group("start")),
 "length": int(match.group("length")),
 }

return None

def clean_line(
 self,
 line: str,
) -> str:
 value = str(line or "").upper()

 value = value.replace(".", " ")
 value = value.replace("_", " ")
 value = value.replace(":", " ")
 value = value.replace("\u00a0", " ")

 value = re.sub(
 r"\s+",
 " ",
 value,
)

 return value.strip()

```

```

=====
FILE: src\idms_modernizer\generators\ddl_generator.py
ENCODING: utf-8
=====

```

```

class DDLGenerator:
 """
 Generates DB2 DDL.

 Supports:
 - Single primary key
 - Composite primary key through table.primary_keys
 - Multiple FK columns
 - FK constraints emitted after CREATE TABLE
 """

 def generate(
 self,
 db2_model,
) -> str:
 ddl: list[str] = []

 for table in getattr(db2_model, "tables", []) or []:
 ddl.extend(
 self.generate_create_table(
 table=table,
)
)

 foreign_key_statements = self.generate_foreign_key_statements(
 db2_model=db2_model,
)

 if foreign_key_statements:
 ddl.append("")
 ddl.extend(foreign_key_statements)

 return "\n".join(ddl)

 def generate_create_table(
 self,
 table,
) -> list[str]:
 lines: list[str] = []

 table_name = getattr(table, "name", "")

```

```

lines.append(f"CREATE TABLE {table_name}")
lines.append("(")

definitions: list[str] = []
added_columns: set[str] = set()

for column in getattr(table, "columns", []) or []:
 column_name = getattr(column, "name", "")

 if not column_name:
 continue

 if column_name in added_columns:
 continue

 datatype = getattr(column, "datatype", "")

 definition = f" {column_name} {datatype}"

 if not getattr(column, "nullable", True):
 definition += " NOT NULL"

 definitions.append(definition)
 added_columns.add(column_name)

primary_keys = self.primary_key_columns(
 table=table,
)

if primary_keys:
 definitions.append(
 f" PRIMARY KEY ({', '.join(primary_keys)})"
)

lines.append(",\n".join(definitions))
lines.append(");")
lines.append("")

return lines

def primary_key_columns(
 self,
 table,
) -> list[str]:
 primary_keys = list(getattr(table, "primary_keys", []) or [])

 if not primary_keys:
 single_primary_key = getattr(table, "primary_key", None)

 if single_primary_key:
 primary_keys = [single_primary_key]

 if not primary_keys:
 primary_keys = [
 getattr(column, "name", "")
 for column in getattr(table, "columns", []) or []
 if getattr(column, "primary_key", False)
]

 cleaned_primary_keys = []

 for primary_key in primary_keys:
 if not primary_key:
 continue

 if primary_key in cleaned_primary_keys:
 continue

 cleaned_primary_keys.append(primary_key)

 return cleaned_primary_keys

def generate_foreign_key_statements(
 self,
 db2_model,

```



```

) -> list[str]:
 statements: list[str] = []
 added_foreign_keys: set[tuple[str, str, str, str]] = set()

 for table in getattr(db2_model, "tables", []) or []:
 table_name = getattr(table, "name", "")

 if not table_name:
 continue

 for foreign_key in getattr(table, "foreign_keys", []) or []:
 child_column = self.get_foreign_key_column_name(
 foreign_key=foreign_key,
)

 parent_table = self.get_foreign_key_reference_table(
 foreign_key=foreign_key,
)

 parent_column = self.get_foreign_key_reference_column(
 foreign_key=foreign_key,
)

 if not child_column or not parent_table or not parent_column:
 continue

 fk_key = (
 table_name,
 child_column,
 parent_table,
 parent_column,
)

 if fk_key in added_foreign_keys:
 continue

 added_foreign_keys.add(fk_key)

 constraint_name = self.constraint_name(
 table_name=table_name,
 column_name=child_column,
)

 statements.append(
 f"ALTER TABLE {table_name} "
 f"ADD CONSTRAINT {constraint_name} "
 f"FOREIGN KEY ({child_column}) "
 f"REFERENCES {parent_table} ({parent_column});"
)

 return statements

def get_foreign_key_column_name(
 self,
 foreign_key,
) -> str:
 return (
 getattr(foreign_key, "column_name", None)
 or getattr(foreign_key, "child_column", None)
 or getattr(foreign_key, "child_fk", None)
 or getattr(foreign_key, "foreign_key", None)
 or ""
)

def get_foreign_key_reference_table(
 self,
 foreign_key,
) -> str:
 return (
 getattr(foreign_key, "reference_table", None)
 or getattr(foreign_key, "parent_table", None)
 or getattr(foreign_key, "referenced_table", None)
 or ""
)

def get_foreign_key_reference_column(

```

```

 self,
 foreign_key,
) -> str:
 return (
 getattr(foreign_key, "reference_column", None)
 or getattr(foreign_key, "parent_column", None)
 or getattr(foreign_key, "referenced_column", None)
 or getattr(foreign_key, "parent_key", None)
 or ""
)

 def constraint_name(
 self,
 table_name: str,
 column_name: str,
) -> str:
 raw_name = f"FK_{table_name}_{column_name}"

 cleaned = (
 raw_name
 .replace("-", "_")
 .replace(" ", "_")
 .replace(".", "_")
 .upper()
)

 return cleaned[:128]

```

```

=====
FILE: src\idms_modernizer\graph\relationship_resolver.py
ENCODING: utf-8
=====

```

```

from collections import defaultdict

from idms_modernizer.domain.relationship_models import (
 Relationship
)

```

```

class RelationshipResolver:

 def resolve(
 self,
 metadata
) -> list[Relationship]:

 owner_map = defaultdict(list)

 member_map = defaultdict(list)

 for record in metadata.records:

 for membership in record.set_memberships:

 if membership.role == "OWNER":

 owner_map[
 membership.set_name
].append(
 record.name
)

 elif membership.role == "MEMBER":

 member_map[
 membership.set_name
].append(
 record.name
)

 relationships = []

 all_sets = (
 set(owner_map.keys())

```

```

 | set(member_map.keys())
)

 for set_name in all_sets:

 owners = owner_map.get(
 set_name,
 []
)

 members = member_map.get(
 set_name,
 []
)

 for owner in owners:

 for member in members:

 relationships.append(
 Relationship(
 set_name=set_name,
 owner_record=owner,
 member_record=member
)
)

 return relationships

```

```

=====
FILE: src\idms_modernizer\graph\schema_graph.py
ENCODING: utf-8
=====

```

```
import networkx as nx
```

```
class SchemaGraph:
```

```

 def __init__(self):

 self.graph = nx.DiGraph()

 def add_record(
 self,
 record_name: str
):

 self.graph.add_node(
 record_name,
 node_type="record"
)

 def add_relationship(
 self,
 owner: str,
 member: str,
 set_name: str
):

 self.graph.add_edge(
 owner,
 member,
 set_name=set_name
)

```

```

=====
FILE: src\idms_modernizer\parsers__init__.py
ENCODING: utf-8
=====

```

```
[Empty file]
```

```
=====
FILE: src\idms_modernizer\parsers\cobol_pdf_extractor.py
ENCODING: utf-8
=====
```

```
import re
import pdfplumber

class CobolPdfExtractor:
 """
 Extracts COBOL text from PDF.

 Supports:
 - COBOL pasted as text in PDF
 - line-preserving extraction
 - fallback to empty string if extraction fails
 """

 def extract_text(
 self,
 pdf_path: str
) -> str:

 lines: list[str] = []

 with pdfplumber.open(pdf_path) as pdf:
 for page in pdf.pages:
 page_text = (
 page.extract_text()
 or ""
)

 for raw_line in page_text.splitlines():
 cleaned_line = self._clean_line(
 raw_line
)

 lines.append(
 cleaned_line
)

 return "\n".join(lines).strip()

 def _clean_line(
 self,
 line: str | None
) -> str:

 if line is None:
 return ""

 cleaned = str(line).rstrip()

 cleaned = cleaned.replace(
 "\t",
 " "
)

 cleaned = re.sub(
 r"[\u00A0]+",
 " ",
 cleaned
)

 return cleaned
```

```
=====
FILE: src\idms_modernizer\parsers\text_extractor.py
ENCODING: utf-8
=====
```

```
import re
import pdfplumber
```

```

from idms_modernizer.domain.document_models import (
 DocumentLine,
 DocumentModel,
 DocumentPage
)

class TextExtractor:
 """
 Plain text PDF extractor.

 Important:
 - Uses only page.extract_text().
 - Does not use extract_tables().
 - Does not use extract_words().
 - This keeps the useful rows seen in your debug, such as:
 03 EMP-FIRST-NAME-0415 DISPLAY X(10) 5 10
 """

 def extract_document(
 self,
 pdf_path: str
) -> DocumentModel:

 pages: list[DocumentPage] = []

 with pdfplumber.open(pdf_path) as pdf:
 for page_index, page in enumerate(pdf.pages):
 text = (
 page.extract_text()
 or ""
)

 lines: list[DocumentLine] = []

 for line_index, raw_line in enumerate(
 text.splitlines()
):
 cleaned_line = self._clean_line(
 raw_line
)

 if not cleaned_line:
 continue

 lines.append(
 DocumentLine(
 line_number=line_index,
 text=cleaned_line
)
)

 pages.append(
 DocumentPage(
 page_number=page_index,
 lines=lines
)
)

 return DocumentModel(
 pages=pages
)

 def _clean_line(
 self,
 line: str | None
) -> str:

 if not line:
 return ""

 cleaned = str(line).strip()

 cleaned = re.sub(
 r"<[^>]+>",
 " ",

```

```

 cleaned
)

 cleaned = cleaned.replace(
 " ",
 " "
)

 cleaned = cleaned.replace(
 "\t",
 " "
)

 cleaned = cleaned.replace(
 "|",
 " "
)

 cleaned = re.sub(
 r"\s+",
 " ",
 cleaned
)

 return cleaned.strip()

```

```

=====
FILE: src\idms_modernizer\services__init__.py
ENCODING: utf-8
=====

```

[Empty file]

```

=====
FILE: src\idms_modernizer\services\business_datatype_inference.py
ENCODING: utf-8
=====

```

```

class BusinessDatatypeInference:
 """
 Generic datatype inference.

 This class intentionally does not inspect field names.

 Reason:
 Field-name based rules such as PHONE, ZIP, SSN, CODE, ACCOUNT,
 POLICY, or LICENSE are business/domain assumptions and should not be
 hardcoded.

 Datatype should be decided upstream from:
 - IDMS PIC clause
 - USAGE
 - length
 - scale
 """

 @staticmethod
 def infer(
 field_name: str,
 current_type: str,
) -> str:
 if current_type:
 return current_type.upper()

 return "VARCHAR"

```

```

=====
FILE: src\idms_modernizer\services\canonical_reconciler.py
ENCODING: utf-8
=====

```

```

from idms_modernizer.domain.canonical_models import (
 CanonicalSchema,

```

```

 CanonicalField
)
from idms_modernizer.domain.schema_models import SchemaMetadata
from idms_modernizer.services.name_normalizer import NameNormalizer

class CanonicalReconciler:
 """
 Reconciles canonical schema with IDMS schema metadata.

 IDMS schema is authoritative for:
 - datatype
 - length
 - scale
 - picture

 Canonical schema is authoritative for:
 - normalized record names
 - primary keys
 - relationships
 """

 def reconcile(
 self,
 canonical_schema: CanonicalSchema,
 metadata: SchemaMetadata
) -> CanonicalSchema:

 idms_field_lookup = self._build_idms_field_lookup(
 metadata
)

 for record in canonical_schema.records:
 normalized_record_name = NameNormalizer.normalize(
 record.name
)

 reconciled_fields: list[CanonicalField] = []

 for field in record.fields:
 normalized_field_name = NameNormalizer.normalize(
 field.name
)

 idms_field = idms_field_lookup.get(
 (
 normalized_record_name,
 normalized_field_name
)
)

 if idms_field is None:
 idms_field = idms_field_lookup.get(
 (
 normalized_record_name,
 self._remove_record_suffix(
 normalized_field_name
)
)
)

 if idms_field is None:
 reconciled_fields.append(field)
 continue

 reconciled_fields.append(
 CanonicalField(
 name=field.name,
 datatype=idms_field.datatype,
 length=idms_field.length,
 scale=idms_field.scale,
 occurs=field.occurs,
 occurs_max=field.occurs_max
)
)
)

```

```

 record.fields = reconciled_fields

 return canonical_schema

def _build_idms_field_lookup(
 self,
 metadata: SchemaMetadata
) -> dict[tuple[str, str], object]:

 lookup: dict[tuple[str, str], object] = {}

 for record in metadata.records:
 record_name = NameNormalizer.normalize(
 record.name
)

 for field in record.fields:
 field_name = NameNormalizer.normalize(
 field.name
)

 lookup[
 (
 record_name,
 field_name
)
] = field

 lookup[
 (
 record_name,
 self._remove_record_suffix(field_name)
)
] = field

 return lookup

def _remove_record_suffix(
 self,
 field_name: str
) -> str:

 parts = field_name.split("_")

 if (
 len(parts) > 1
 and parts[-1].isdigit()
 and len(parts[-1]) == 4
):
 return "_".join(parts[:-1])

 return field_name

```

```

=====
FILE: src\idms_modernizer\services\canonical_schema_builder.py
ENCODING: utf-8
=====

```

```

import re

from idms_modernizer.domain.canonical_models import (
 CanonicalSchema,
 CanonicalRecord,
 CanonicalField,
 CanonicalSet,
 CanonicalRelationship,
)
from idms_modernizer.services.name_normalizer import NameNormalizer
from idms_modernizer.services.date_field_consolidator import DateFieldConsolidator

class CanonicalSchemaBuilder:
 """
 Builds canonical schema from IDMS metadata.

```



Generic behavior only:

- No hardcoded record names.
- No hardcoded column names.
- No hardcoded SET names.

Rules:

- Physical DB2 columns come from record.fields, after date consolidation.
  - Group detection uses mapping\_fields level hierarchy.
  - CALC outer group is never a physical DB2 PK column.
  - CALC intermediate groups are not physical DB2 columns.
  - CALC physical non-date leaf children become actual composite PK columns.
  - Date group/date parts are never physical PK.
  - FILLER is never physical PK.
  - If no CALC exists, DB2MappingService creates ID\_RECORD\_<record\_name> CHAR(20).
- """

```
def build(self, metadata) -> CanonicalSchema:
 schema = CanonicalSchema()

 for record in getattr(metadata, "records", []) or []:
 record_name = NameNormalizer.normalize(getattr(record, "name", "") or "")

 primary_key = (
 NameNormalizer.normalize(getattr(record, "primary_key", "") or "")
 if getattr(record, "primary_key", None)
 else None
)

 canonical_record = CanonicalRecord(
 name=record_name,
 primary_key=primary_key,
 primary_keys=[],
)

 mapping_fields = (
 getattr(record, "mapping_fields", None)
 or getattr(record, "fields", None)
 or []
)

 group_names = self.build_group_name_set(fields=mapping_fields)
 date_names = self.build_date_name_set(fields=mapping_fields)

 physical_fields = getattr(record, "fields", []) or []

 normalized_fields = DateFieldConsolidator consolidate(
 physical_fields,
)

 added_fields: set[str] = set()

 for field in normalized_fields:
 field_name = NameNormalizer.normalize(getattr(field, "name", "") or "")

 if not field_name:
 continue

 if self.is_date_part_name(field_name):
 continue

 if field_name in added_fields:
 continue

 if field_name in group_names and field_name not in date_names:
 continue

 if self.is_non_physical_group_field(field=field):
 continue

 adjusted_field = self.adjust_occurs_field(field=field)

 canonical_record.fields.append(
 CanonicalField(
 name=field_name,
 datatype=getattr(adjusted_field, "datatype", None),
 length=getattr(adjusted_field, "length", None),
)
)
```

```

 scale=getattr(adjusted_field, "scale", None),
 occurs=getattr(adjusted_field, "occurs", False),
 occurs_max=getattr(adjusted_field, "occurs_max", None),
)
)

added_fields.add(field_name)

self.apply_primary_key_rules(
 canonical_record=canonical_record,
 record=record,
 added_fields=added_fields,
 group_names=group_names,
 date_names=date_names,
)

schema.records.append(canonical_record)

self.add_sets_and_relationships(
 schema=schema,
 metadata=metadata,
)

return schema

def apply_primary_key_rules(
 self,
 canonical_record: CanonicalRecord,
 record,
 added_fields: set[str],
 group_names: set[str],
 date_names: set[str],
) -> None:
 primary_key = canonical_record.primary_key

 if not primary_key:
 canonical_record.primary_keys = []
 return

 primary_key_fields = self.resolve_primary_key_fields(
 record=record,
 primary_key=primary_key,
 group_names=group_names,
 date_names=date_names,
)

 if not primary_key_fields:
 canonical_record.primary_keys = []
 canonical_record.primary_key = None
 return

 canonical_primary_keys: list[str] = []

 for key_field in primary_key_fields:
 key_name = NameNormalizer.normalize(getattr(key_field, "name", "") or "")

 if not key_name:
 continue

 if key_name in canonical_primary_keys:
 continue

 if key_name in date_names:
 continue

 if key_name in group_names:
 continue

 if self.is_date_part_name(key_name):
 continue

 if self.is_date_field(key_field):
 continue

 if self.is_filler_field(key_field):
 continue

```

```

 if not self.has_physical_definition(key_field):
 continue

 canonical_primary_keys.append(key_name)

 if key_name in added_fields:
 continue

 canonical_record.fields.append(
 CanonicalField(
 name=key_name,
 datatype=self.datatype_for_key_field(key_field),
 length=self.length_for_key_field(key_field),
 scale=getattr(key_field, "scale", None),
 occurs=False,
 occurs_max=None,
)
)

 added_fields.add(key_name)

 canonical_record.primary_keys = canonical_primary_keys

 if canonical_primary_keys:
 canonical_record.primary_key = canonical_primary_keys[0]
 else:
 canonical_record.primary_key = None

def resolve_primary_key_fields(
 self,
 record,
 primary_key: str,
 group_names: set[str],
 date_names: set[str],
) -> list:
 mapping_fields = (
 getattr(record, "mapping_fields", None)
 or getattr(record, "fields", None)
 or []
)

 key_field = self.find_field_for_primary_key(
 record=record,
 primary_key=primary_key,
)

 if key_field is None:
 return []

 key_name = NameNormalizer.normalize(getattr(key_field, "name", "") or "")

 if key_name in group_names:
 return self.child_physical_fields_for_group(
 fields=mapping_fields,
 group_field=key_field,
 group_names=group_names,
 date_names=date_names,
)

 if key_name in date_names:
 return []

 if self.is_date_field(key_field):
 return []

 if self.is_date_part_name(key_name):
 return []

 if self.is_filler_field(key_field):
 return []

 return [key_field]

def child_physical_fields_for_group(
 self,

```

```

 fields,
 group_field,
 group_names: set[str],
 date_names: set[str],
) -> list:
 field_list = list(fields or [])

 if not field_list:
 return []

 group_name = NameNormalizer.normalize(getattr(group_field, "name", "") or "")
 group_level = getattr(group_field, "level", None)

 if group_level is None:
 return []

 try:
 group_level_int = int(group_level)
 except Exception:
 return []

 collecting = False
 children = []

 for field in field_list:
 field_name = NameNormalizer.normalize(getattr(field, "name", "") or "")
 field_level = getattr(field, "level", None)

 if field_level is None:
 continue

 try:
 field_level_int = int(field_level)
 except Exception:
 continue

 if not collecting:
 if field_name == group_name:
 collecting = True
 continue

 if field_level_int <= group_level_int:
 break

 if not field_name:
 continue

 if field_name in group_names:
 continue

 if field_name in date_names:
 continue

 if self.is_date_part_name(field_name):
 continue

 if self.is_date_field(field):
 continue

 if self.is_filler_field(field):
 continue

 if not self.has_physical_definition(field):
 continue

 children.append(field)

 return children

 def build_group_name_set(self, fields) -> set[str]:
 result: set[str] = set()
 field_list = list(fields or [])

 for index, field in enumerate(field_list):
 field_name = NameNormalizer.normalize(getattr(field, "name", "") or "")
 field_level = getattr(field, "level", None)

```

```

 if not field_name or field_level is None:
 continue

 try:
 field_level_int = int(field_level)
 except Exception:
 continue

 for next_field in field_list[index + 1:]:
 next_level = getattr(next_field, "level", None)

 if next_level is None:
 continue

 try:
 next_level_int = int(next_level)
 except Exception:
 continue

 if next_level_int > field_level_int:
 result.add(field_name)
 break

 if next_level_int <= field_level_int:
 break

 return result

def build_date_name_set(self, fields) -> set[str]:
 result: set[str] = set()
 field_list = list(fields or [])

 for index, field in enumerate(field_list):
 field_name = NameNormalizer.normalize(getattr(field, "name", "") or "")
 field_level = getattr(field, "level", None)

 if not field_name:
 continue

 if self.is_date_part_name(field_name):
 result.add(field_name)
 continue

 if self.is_date_field(field):
 result.add(field_name)
 continue

 if field_level is None:
 continue

 try:
 field_level_int = int(field_level)
 except Exception:
 continue

 descendants = []

 for next_field in field_list[index + 1:]:
 next_level = getattr(next_field, "level", None)

 if next_level is None:
 continue

 try:
 next_level_int = int(next_level)
 except Exception:
 continue

 if next_level_int <= field_level_int:
 break

 descendants.append(next_field)

 parts_found = set()

```

```

 for descendant in descendants:
 descendant_name = NameNormalizer.normalize(
 getattr(descendant, "name", "") or ""
)

 part = self.date_part_type_from_name(descendant_name)

 if part:
 parts_found.add(part)

 if {"YEAR", "MONTH", "DAY"}.issubset(parts_found):
 result.add(field_name)

 for descendant in descendants:
 descendant_name = NameNormalizer.normalize(
 getattr(descendant, "name", "") or ""
)

 if self.date_part_type_from_name(descendant_name):
 result.add(descendant_name)

 return result

def date_part_type_from_name(self, field_name: str) -> str | None:
 parsed = DateFieldConsolidator.parse_date_part(field_name=field_name)

 if parsed is None:
 return None

 return parsed.get("part")

def find_field_for_primary_key(self, record, primary_key: str):
 fields = []
 fields.extend(getattr(record, "fields", []) or [])
 fields.extend(getattr(record, "mapping_fields", []) or [])

 normalized_primary_key = NameNormalizer.normalize(primary_key)
 suffix_removed_primary_key = self.remove_record_suffix(normalized_primary_key)

 for field in fields:
 field_name = NameNormalizer.normalize(getattr(field, "name", "") or "")

 if field_name == normalized_primary_key:
 return field

 if self.remove_record_suffix(field_name) == suffix_removed_primary_key:
 return field

 return None

def datatype_for_key_field(self, key_field) -> str:
 datatype = getattr(key_field, "datatype", None)

 if datatype:
 return datatype

 picture = str(getattr(key_field, "picture", "") or "").upper()

 if "X" in picture:
 return "CHAR"

 if "9" in picture:
 return "DECIMAL"

 return "CHAR"

def length_for_key_field(self, key_field) -> int | None:
 length = getattr(key_field, "length", None)

 if length:
 try:
 return int(length)
 except Exception:
 pass

 return 20

```

```

def adjust_occurs_field(self, field):
 occurs = getattr(field, "occurs", False)
 occurs_max = getattr(field, "occurs_max", None)

 if not occurs or not occurs_max:
 return field

 length = getattr(field, "length", None)

 if length is None:
 return field

 try:
 adjusted_length = int(length) * int(occurs_max)
 except Exception:
 return field

 try:
 return field.model_copy(update={"length": adjusted_length})
 except Exception:
 try:
 field.length = adjusted_length
 except Exception:
 pass

 return field

def is_non_physical_group_field(self, field) -> bool:
 if self.is_date_field(field):
 return False

 if getattr(field, "is_group", False):
 return True

 if getattr(field, "has_child", False):
 return True

 return False

def has_physical_definition(self, field) -> bool:
 if getattr(field, "picture", None):
 return True

 if getattr(field, "datatype", None):
 return True

 if getattr(field, "length", None):
 return True

 return False

def is_date_field(self, field) -> bool:
 datatype = str(getattr(field, "datatype", "") or "").upper()
 basetype = str(getattr(field, "basetype", "") or "").upper()

 field_name = NameNormalizer.normalize(getattr(field, "name", "") or "")
 normalized_name = field_name.replace(" ", "_")

 return (
 datatype == "DATE"
 or basetype == "DATE"
 or normalized_name.endswith("_DATE")
 or normalized_name == "DATE"
 or "_DATE_" in normalized_name
)

def is_filler_field(self, field) -> bool:
 return str(getattr(field, "name", "") or "").upper().startswith("FILLER")

def is_date_part_name(self, field_name: str) -> bool:
 return DateFieldConsolidator.parse_date_part(field_name=field_name) is not None

def remove_record_suffix(self, field_name: str) -> str:
 normalized = NameNormalizer.normalize(field_name)
 normalized = normalized.replace(" ", "_")

```

```

 return re.sub(r"_[0-9]{4}$", "", normalized)

def add_sets_and_relationships(self, schema: CanonicalSchema, metadata) -> None:
 added_relationships = set()

 for rel in getattr(metadata, "relationships", []) or []:
 set_name = getattr(rel, "set_name", None)
 owner_record = getattr(rel, "owner_record", None)
 member_record = getattr(rel, "member_record", None)

 if not set_name or not owner_record or not member_record:
 continue

 normalized_set_name = NameNormalizer.normalize(set_name)
 normalized_owner = NameNormalizer.normalize(owner_record)
 normalized_member = NameNormalizer.normalize(member_record)

 key = (
 normalized_owner,
 normalized_member,
 normalized_set_name,
)

 if key in added_relationships:
 continue

 added_relationships.add(key)

 schema.sets.append(
 CanonicalSet(
 name=normalized_set_name,
 owner_record=normalized_owner,
 member_record=normalized_member,
)
)

 schema.relationships.append(
 CanonicalRelationship(
 set_name=normalized_set_name,
 parent_record=normalized_owner,
 child_record=normalized_member,
 cardinality="1:N",
)
)

```

```

=====
FILE: src\idms_modernizer\services\date_field_consolidator.py
ENCODING: utf-8
=====

```

```

import re

from idms_modernizer.domain.schema_models import DataField
from idms_modernizer.services.name_normalizer import NameNormalizer

```

```

class DateFieldConsolidator:
 """
 Consolidates legacy date child fields into one DATE field.

 Supports:
 - YEAR / MONTH / DAY
 - YR / MO / DY
 - Y / M / D
 - YY / MM / DD
 - YYYY / MM / DD
 - DY / DM / DD
 """

 YEAR_PARTS = {
 "YEAR",
 "YR",
 "Y",
 "YY",
 }

```



```

 "YYYY",
 "DY",
 }

MONTH_PARTS = {
 "MONTH",
 "MON",
 "MO",
 "M",
 "MM",
 "DM",
}

DAY_PARTS = {
 "DAY",
 "D",
 "DD",
}

@staticmethod
def consolidate(
 fields: list[DataField],
) -> list[DataField]:
 result: list[DataField] = []
 consumed: set[str] = set()
 added_dates: set[str] = set()

 date_groups = DateFieldConsolidator.collect_date_groups(
 fields=fields,
)

 for date_name, parts in date_groups.items():
 if not DateFieldConsolidator.has_complete_date_group(
 parts=parts,
):
 continue

 normalized_date_name = NameNormalizer.normalize(
 date_name,
)

 if normalized_date_name in added_dates:
 continue

 template = (
 parts.get("YEAR")
 or parts.get("MONTH")
 or parts.get("DAY")
)

 result.append(
 DataField(
 name=date_name,
 level=DateFieldConsolidator.parent_level(
 field=template,
),
 datatype="DATE",
 length=None,
 scale=None,
 picture=None,
 start_position=DateFieldConsolidator.min_start_position(
 parts=parts,
),
 end_position=DateFieldConsolidator.max_end_position(
 parts=parts,
),
 basetype="DATE",
 has_child=True,
 is_group=True,
)
)

 added_dates.add(
 normalized_date_name,
)

```

```

 for part_field in parts.values():
 consumed.add(
 NameNormalizer.normalize(
 part_field.name,
)
)

 for field in fields:
 if not field or not field.name:
 continue

 normalized_name = NameNormalizer.normalize(
 field.name,
)

 if normalized_name in consumed:
 continue

 if normalized_name in added_dates:
 continue

 result.append(
 field,
)

 return result

@staticmethod
def collect_date_groups(
 fields: list[DataField],
) -> dict[str, dict[str, DataField]]:
 groups: dict[str, dict[str, DataField]] = {}

 for field in fields:
 parsed = DateFieldConsolidator.parse_date_part(
 field_name=field.name,
)

 if parsed is None:
 continue

 date_name = parsed["date_name"]
 part = parsed["part"]

 if date_name not in groups:
 groups[date_name] = {}

 groups[date_name][part] = field

 return groups

@staticmethod
def parse_date_part(
 field_name: str,
) -> dict[str, str] | None:
 tokens = DateFieldConsolidator.split_tokens(
 value=field_name,
)

 if len(tokens) < 2:
 return None

 for index, token in enumerate(tokens):
 part = DateFieldConsolidator.date_part_type(
 token=token,
 tokens=tokens,
)

 if part is None:
 continue

 date_tokens = tokens.copy()
 date_tokens[index] = "DATE"

 return {
 "date_name": " ".join(date_tokens),
 }

```

```

 "part": part,
 }

 return None

@staticmethod
def date_part_type(
 token: str,
 tokens: list[str],
) -> str | None:
 token = token.upper()

 has_dy_dm_dd = (
 "DY" in tokens
 and "DM" in tokens
 and "DD" in tokens
)

 if token in DateFieldConsolidator.YEAR_PARTS:
 if token == "DY" and not has_dy_dm_dd:
 return "DAY"

 return "YEAR"

 if token in DateFieldConsolidator.MONTH_PARTS:
 return "MONTH"

 if token in DateFieldConsolidator.DAY_PARTS:
 return "DAY"

 return None

@staticmethod
def has_complete_date_group(
 parts: dict[str, DataField],
) -> bool:
 return (
 "YEAR" in parts
 and "MONTH" in parts
 and "DAY" in parts
)

@staticmethod
def parent_level(
 field: DataField | None,
) -> int | None:
 if field is None:
 return None

 level = getattr(
 field,
 "level",
 None,
)

 if level is None:
 return None

 try:
 return max(
 int(level) - 1,
 1,
)

 except Exception:
 return level

@staticmethod
def min_start_position(
 parts: dict[str, DataField],
) -> int | None:
 values: list[int] = []

 for field in parts.values():
 value = getattr(
 field,

```

```

 "start_position",
 None,
)

 if value is not None:
 values.append(
 int(value),
)

 if not values:
 return None

 return min(values)

@staticmethod
def max_end_position(
 parts: dict[str, DataField],
) -> int | None:
 values: list[int] = []

 for field in parts.values():
 value = getattr(
 field,
 "end_position",
 None,
)

 if value is not None:
 values.append(
 int(value),
)

 if not values:
 return None

 return max(values)

@staticmethod
def split_tokens(
 value: str,
) -> list[str]:
 normalized = NameNormalizer.normalize(
 value,
)

 return [
 token.upper()
 for token in re.split(
 r"[\s_-]+",
 normalized,
)
 if token
]

```

```

=====
FILE: src\idms_modernizer\services\db2_datatype_mapper.py
ENCODING: utf-8
=====

```

```
import re
```

```
print("LOADED DB2DatatypeMapper VERSION DEBUG-PIC-PARENS-V-COMP3-FIX-2026-07-30-2")
```

```

class DB2DatatypeMapper:
 DEFAULT_CHAR_LENGTH = 1
 DEFAULT_DECIMAL_PRECISION = 18
 DEFAULT_DECIMAL_SCALE = 0
 DEBUG = True

 @staticmethod
 def map(field) -> str:
 datatype = (
 getattr(field, "datatype", None)
 or getattr(field, "data_type", None)

```

```

 or getattr(field, "type", None)
 or ""
)

datatype = str(datatype or "").strip().upper()

picture = (
 getattr(field, "picture", None)
 or getattr(field, "pic", None)
 or getattr(field, "pic_clause", None)
 or ""
)

picture = str(picture or "").strip()

length = (
 getattr(field, "length", None)
 or getattr(field, "precision", None)
 or getattr(field, "storage_length", None)
 or getattr(field, "physical_length", None)
 or getattr(field, "byte_length", None)
)

scale = getattr(field, "scale", None)

if DB2DatatypeMapper.DEBUG:
 print(
 "DB2_MAP_DEBUG_INPUT",
 f"datatype={datatype}",
 f"picture={repr(picture)}",
 f"length={length}",
 f"scale={scale}",
)

if datatype == "DATE":
 return "DATE"

if datatype in {"TIMESTAMP", "DATETIME"}:
 return "TIMESTAMP"

if picture:
 result = DB2DatatypeMapper.map_picture(
 picture=picture,
 fallback_length=length,
 fallback_scale=scale,
)

 if DB2DatatypeMapper.DEBUG:
 print(
 "DB2_MAP_DEBUG_RESULT",
 f"picture={repr(picture)}",
 f"result={result}",
)

 return result

if datatype in {"DECIMAL", "NUMERIC", "COMP", "COMP-3"}:
 precision = DB2DatatypeMapper.safe_int(
 value=length,
 default=DB2DatatypeMapper.DEFAULT_DECIMAL_PRECISION,
)

 actual_scale = DB2DatatypeMapper.safe_int(
 value=scale,
 default=DB2DatatypeMapper.DEFAULT_DECIMAL_SCALE,
)

 return DB2DatatypeMapper.format_decimal(
 precision=precision,
 scale=actual_scale,
 force_scale=actual_scale > 0,
)

if datatype in {"CHAR", "VARCHAR", "DISPLAY", "TEXT", "ALPHANUMERIC"}:
 actual_length = DB2DatatypeMapper.safe_int(
 value=length,

```

```

 default=DB2DatatypeMapper.DEFAULT_CHAR_LENGTH,
)

 return f"CHAR({actual_length})"

 return f"CHAR({DB2DatatypeMapper.DEFAULT_CHAR_LENGTH})"

@staticmethod
def map_datatype(field) -> str:
 return DB2DatatypeMapper.map(
 field=field,
)

@staticmethod
def map_picture(
 picture: str,
 fallback_length=None,
 fallback_scale=None,
) -> str:
 clean = DB2DatatypeMapper.clean_picture(
 picture=picture,
)

 if not clean:
 return f"CHAR({DB2DatatypeMapper.DEFAULT_CHAR_LENGTH})"

 clean_upper = clean.upper()

 has_comp3 = "COMP-3" in clean_upper
 has_comp = bool(re.search(r"\bCOMP\b", clean_upper)) and not has_comp3

 core = DB2DatatypeMapper.picture_core(
 picture=clean,
)

 if DB2DatatypeMapper.DEBUG:
 print(
 "DB2_MAP_PICTURE_DEBUG_INPUT",
 f"picture={repr(picture)}",
 f"clean={repr(clean)}",
 f"core={repr(core)}",
 f"has_comp3={has_comp3}",
 f"has_comp={has_comp}",
 f"fallback_length={fallback_length}",
 f"fallback_scale={fallback_scale}",
)

 if DB2DatatypeMapper.picture_is_char(core):
 length = DB2DatatypeMapper.char_length(
 picture=core,
 fallback_length=fallback_length,
)

 result = f"CHAR({length})"

 if DB2DatatypeMapper.DEBUG:
 print(
 "DB2_MAP_PICTURE_DEBUG_RESULT",
 f"core={repr(core)}",
 f"result={result}",
)

 return result

 if DB2DatatypeMapper.picture_is_decimal(core):
 precision, scale = DB2DatatypeMapper.decimal_precision_scale(
 picture=core,
)

 result = DB2DatatypeMapper.format_decimal(
 precision=precision,
 scale=scale,
 force_scale=True,
)

 if DB2DatatypeMapper.DEBUG:

```

```

 print(
 "DB2_MAP_PICTURE_DEBUG_RESULT",
 f"core={repr(core)}",
 f"precision={precision}",
 f"scale={scale}",
 f"result={result}",
)

 return result

if DB2DatatypeMapper.picture_is_numeric(core):
 precision = DB2DatatypeMapper.numeric_precision(
 picture=core,
 fallback_length=fallback_length,
)

 if has_comp3 or has_comp:
 result = DB2DatatypeMapper.format_decimal(
 precision=precision,
 scale=0,
 force_scale=True,
)
 else:
 result = DB2DatatypeMapper.format_decimal(
 precision=precision,
 scale=0,
 force_scale=False,
)

 if DB2DatatypeMapper.DEBUG:
 print(
 "DB2_MAP_PICTURE_DEBUG_RESULT",
 f"core={repr(core)}",
 f"precision={precision}",
 "scale=0",
 f"result={result}",
)

 return result

precision = DB2DatatypeMapper.safe_int(
 value=fallback_length,
 default=DB2DatatypeMapper.DEFAULT_DECIMAL_PRECISION,
)

scale = DB2DatatypeMapper.safe_int(
 value=fallback_scale,
 default=DB2DatatypeMapper.DEFAULT_DECIMAL_SCALE,
)

if has_comp3 or has_comp:
 result = DB2DatatypeMapper.format_decimal(
 precision=precision,
 scale=scale,
 force_scale=True,
)
else:
 result = f"CHAR({DB2DatatypeMapper.DEFAULT_CHAR_LENGTH})"

if DB2DatatypeMapper.DEBUG:
 print(
 "DB2_MAP_PICTURE_DEBUG_FALLBACK",
 f"picture={repr(picture)}",
 f"core={repr(core)}",
 f"result={result}",
)

return result

@staticmethod
def clean_picture(
 picture: str,
) -> str:
 text = str(picture or "").strip()
 text = text.replace("\u00a0", " ")
 text = text.replace(".", "")

```

```

 text = re.sub(r"\s+", " ", text)

 return text.strip()

@staticmethod
def picture_core(
 picture: str,
) -> str:
 text = str(picture or "").upper()
 text = text.replace("PICTURE", "")
 text = text.replace("PIC", "")
 text = text.replace("COMP-3", "")
 text = re.sub(r"\bCOMP\b", "", text)
 text = text.replace("DISPLAY", "")
 text = text.replace("USAGE", "")
 text = text.replace("IS", "")
 text = text.replace(".", "")
 text = re.sub(r"\s+", "", text)

 return text.strip()

@staticmethod
def picture_is_char(
 picture: str,
) -> bool:
 text = str(picture or "").upper()

 if re.fullmatch(r"X([0-9]+)", text):
 return True

 if re.fullmatch(r"X+", text):
 return True

 return False

@staticmethod
def picture_is_numeric(
 picture: str,
) -> bool:
 text = str(picture or "").upper()

 if re.fullmatch(r"S?9([0-9]+)", text):
 return True

 if re.fullmatch(r"S?9+", text):
 return True

 return False

@staticmethod
def picture_is_decimal(
 picture: str,
) -> bool:
 text = str(picture or "").upper()

 if "V" not in text:
 return False

 if re.fullmatch(r"S?9([0-9]+)V9([0-9]+)", text):
 return True

 if re.fullmatch(r"S?9([0-9]+)V9+", text):
 return True

 if re.fullmatch(r"S?9+V9([0-9]+)", text):
 return True

 if re.fullmatch(r"S?9+V9+", text):
 return True

 return False

@staticmethod
def char_length(
 picture: str,
 fallback_length=None,

```



```

) -> int:
 text = str(picture or "").upper()

 match = re.fullmatch(r"X([0-9]+)", text)

 if match:
 return int(match.group(1))

 if re.fullmatch(r"X+", text):
 return len(text)

 return DB2DatatypeMapper.safe_int(
 value=fallback_length,
 default=DB2DatatypeMapper.DEFAULT_CHAR_LENGTH,
)

@staticmethod
def numeric_precision(
 picture: str,
 fallback_length=None,
) -> int:
 text = str(picture or "").upper()

 if text.startswith("S"):
 text = text[1:]

 if "V" in text:
 precision, _scale = DB2DatatypeMapper.decimal_precision_scale(
 picture=picture,
)

 return precision

 match = re.fullmatch(r"9([0-9]+)", text)

 if match:
 return int(match.group(1))

 if re.fullmatch(r"9+", text):
 return len(text)

 precision = DB2DatatypeMapper.count_numeric_digits(
 value=text,
)

 if precision > 0:
 return precision

 return DB2DatatypeMapper.safe_int(
 value=fallback_length,
 default=DB2DatatypeMapper.DEFAULT_DECIMAL_PRECISION,
)

@staticmethod
def decimal_precision_scale(
 picture: str,
) -> tuple[int, int]:
 value = str(picture or "").strip().upper()

 if value.startswith("S"):
 value = value[1:]

 if "V" not in value:
 precision = DB2DatatypeMapper.numeric_precision(
 picture=value,
 fallback_length=DB2DatatypeMapper.DEFAULT_DECIMAL_PRECISION,
)

 return precision, 0

 before_v, after_v = value.split("V", 1)

 integer_digits = DB2DatatypeMapper.count_numeric_digits(
 value=before_v,
)

```

```

decimal_digits = DB2DatatypeMapper.count_numeric_digits(
 value=after_v,
)

precision = integer_digits + decimal_digits
scale = decimal_digits

return precision, scale

@staticmethod
def count_numeric_digits(
 value: str,
) -> int:
 text = str(value or "").strip().upper()

 if text.startswith("S"):
 text = text[1:]

 total = 0
 index = 0

 while index < len(text):
 current_character = text[index]

 if current_character not in {"9", "0"}:
 index += 1
 continue

 if index + 1 < len(text) and text[index + 1] == "(":
 close_index = text.find(")", index + 2)

 if close_index != -1:
 number_text = text[index + 2:close_index].strip()

 if number_text.isdigit():
 total += int(number_text)
 index = close_index + 1
 continue

 total += 1
 index += 1

 return total

@staticmethod
def count_9_digits(
 value: str,
) -> int:
 return DB2DatatypeMapper.count_numeric_digits(
 value=value,
)

@staticmethod
def format_decimal(
 precision: int,
 scale: int,
 force_scale: bool = False,
) -> str:
 actual_precision = DB2DatatypeMapper.safe_int(
 value=precision,
 default=DB2DatatypeMapper.DEFAULT_DECIMAL_PRECISION,
)

 actual_scale = DB2DatatypeMapper.safe_int(
 value=scale,
 default=DB2DatatypeMapper.DEFAULT_DECIMAL_SCALE,
)

 if force_scale or actual_scale > 0:
 return f"DECIMAL({actual_precision},{actual_scale})"

 return f"DECIMAL({actual_precision})"

@staticmethod
def safe_int(
 value,

```

```

 default: int,
) -> int:
 try:
 if value is None:
 return default

 text = str(value).strip()

 if not text:
 return default

 return int(text)
 except Exception:
 return default

```

```

=====
FILE: src\idms_modernizer\services\db2_generation_service.py
ENCODING: utf-8
=====

```

```

from idms_modernizer.generators.ddl_generator import (
 DDLGenerator
)

from idms_modernizer.services.db2_mapping_service import (
 DB2MappingService
)

```

```

class DB2GenerationService:

 def __init__(self):

 self.mapper = (
 DB2MappingService()
)

 self.ddl_generator = (
 DDLGenerator()
)

 def generate(
 self,
 canonical_schema
):

 db2_model = (
 self.mapper.build_db2_model(
 canonical_schema
)
)

 ddl = (
 self.ddl_generator.generate(
 db2_model
)
)

 return db2_model, ddl

```

```

=====
FILE: src\idms_modernizer\services\db2_mapping_service.py
ENCODING: utf-8
=====

```

```

import re

from idms_modernizer.domain.canonical_models import CanonicalSchema
from idms_modernizer.domain.db2_models import (
 DB2Column,
 DB2ForeignKey,
 DB2Model,
 DB2Table,
)

```

```
from idms_modernizer.services.db2_datatype_mapper import DB2DatatypeMapper
```

```
print("LOADED DB2MappingService VERSION NAMING-FK-DATE-FIX-2026-07-29")
```

```
class DB2MappingService:
```

```
 """
```

```
 Builds DB2 model from canonical schema.
```

```
 Naming rules implemented:
```

```
 1. Normal COBOL business field:
```

- Start from COBOL business field.
- Normalize separators to underscore.
- Apply project abbreviations.
- Remove generic trailing qualifiers where applicable.
- Append \_479<record-code>.

```
 Example:
```

```
 NR-CIO-FORM-AS in VMBSIC -> NR_CIOFMAS_479BSIC
```

```
 CT-RK-TGDSV in VMBFORM -> CT_RKTGDSV_479FORM
```

```
 NR-ID-STOCK in VMBCOUP -> NR_IDSTOCK_479COUP
```

```
 2. Date field:
```

- Outer COBOL date field becomes one DB2 DATE column.
- DB2 date name keeps DA prefix.
- Append \_479<record-code>.

```
 Example:
```

```
 DA-CPTA-GDIFC -> DA_CPTA_479MBFC
```

```
 DA-UB-GDIFR -> DA_UBDATE_479MBFR
```

```
 3. Foreign key:
```

- FK column reuses exact referenced/master DB2 column name.
- No SET prefix is added to FK column names.
- Relationship/set name is metadata only.

```
 Example:
```

```
 Master PK: NR_CIOFMAS_479BSIC
```

```
 Child FK : NR_CIOFMAS_479BSIC
```

```
 4. Missing PK:
```

- If no primary key exists, create generated technical key:  
 ID\_RECORD\_<record-code>
- Type: CHAR(20)

```
 """
```

```
 TECHNICAL_KEY_DATATYPE = "CHAR(20)"
```

```
 GENERIC_TRAILING_TOKENS = {
```

```
 "SIC",
 "FC",
 "GDIFC",
 "GDIFR",
 "GDIFAR",
 "GDIF",
 "GDI",
 "REC",
 "RECORD",
```

```
 }
```

```
 PROJECT_ABBREVIATIONS = {
```

```
 "FORM": "FM",
 "EVPRCP": "ERCP",
```

```
 }
```

```
 DATE_TOKENS = {
```

```
 "DATE",
 "DT",
 "DTE",
 "DA",
 "YYMMDD",
 "YYYYMMDD",
 "YMD",
```

```
 }
```

```

YEAR_PARTS = {
 "YEAR",
 "YR",
 "Y",
 "YY",
 "YYYY",
 "DY",
}

MONTH_PARTS = {
 "MONTH",
 "MON",
 "MO",
 "M",
 "MM",
 "DM",
}

DAY_PARTS = {
 "DAY",
 "D",
 "DD",
}

def build_db2_model(
 self,
 schema: CanonicalSchema,
) -> DB2Model:
 print("USING DB2MappingService.build_db2_model VERSION NAMING-FK-DATE-FIX-2026-07-29")

 tables: list[DB2Table] = []

 for record in getattr(schema, "records", []) or []:
 record_name = getattr(record, "name", "") or ""
 table_name = self.normalize_table_name(record_name)

 table = DB2Table(
 name=table_name,
 columns=[],
 foreign_keys=[],
 primary_key=None,
 primary_keys=[],
)

 declared_primary_keys = self.get_record_primary_keys(
 record=record,
)

 normalized_primary_keys = []

 for primary_key in declared_primary_keys:
 normalized_primary_key = self.normalize_column_name(
 value=primary_key,
 record_name=record_name,
 field=None,
)

 if normalized_primary_key and normalized_primary_key not in normalized_primary_keys:
 normalized_primary_keys.append(normalized_primary_key)

 table.primary_keys = normalized_primary_keys

 if table.primary_keys:
 table.primary_key = table.primary_keys[0]

 added_columns: set[str] = set()

 for field in getattr(record, "fields", []) or []:
 raw_field_name = getattr(field, "name", "") or ""

 column_name = self.normalize_column_name(
 value=raw_field_name,
 record_name=record_name,
 field=field,
)

```

```

 if not column_name:
 continue

 if column_name in added_columns:
 continue

 is_primary_key = column_name in table.primary_keys

 column = DB2Column(
 name=column_name,
 datatype=DB2DatatypeMapper.map(field),
 nullable=not is_primary_key,
 primary_key=is_primary_key,
 generated=False,
 source_kind="COBOL",
)

 table.columns.append(column)
 added_columns.add(column_name)

 self.ensure_record_primary_key(
 table=table,
 record_name=record_name,
)

 tables.append(table)

model = DB2Model(
 tables=tables,
)

self.apply_relationship_foreign_keys(
 schema=schema,
 model=model,
)

return model

def apply_relationship_foreign_keys(
 self,
 schema: CanonicalSchema,
 model: DB2Model,
) -> None:
 table_lookup = self.build_table_lookup(
 model=model,
)

 for relationship in getattr(schema, "relationships", []) or []:
 set_name = self.get_relationship_set_name(
 relationship=relationship,
)

 owner_record = self.get_relationship_owner_record(
 relationship=relationship,
)

 member_record = self.get_relationship_member_record(
 relationship=relationship,
)

 if not owner_record or not member_record:
 continue

 owner_table = self.find_table_for_record(
 record_name=owner_record,
 table_lookup=table_lookup,
)

 member_table = self.find_table_for_record(
 record_name=member_record,
 table_lookup=table_lookup,
)

 if owner_table is None or member_table is None:
 continue

```

```

 owner_pk_columns = self.get_primary_key_columns(
 table=owner_table,
)

 if not owner_pk_columns:
 owner_pk_columns = self.ensure_record_primary_key(
 table=owner_table,
 record_name=owner_record,
)

 for owner_pk_column in owner_pk_columns:
 fk_column = self.ensure_fk_column_reusing_parent_name(
 child_table=member_table,
 parent_pk_column=owner_pk_column,
)

 self.add_foreign_key_if_missing(
 child_table=member_table,
 child_column=fk_column.name,
 parent_table=owner_table,
 parent_column=owner_pk_column.name,
 set_name=set_name,
)

def ensure_fk_column_reusing_parent_name(
 self,
 child_table: DB2Table,
 parent_pk_column: DB2Column,
) -> DB2Column:
 column_name = getattr(parent_pk_column, "name", "") or ""

 existing_column = self.find_column(
 table=child_table,
 column_name=column_name,
)

 if existing_column is not None:
 existing_column.nullable = True
 existing_column.generated = True
 existing_column.primary_key = False
 existing_column.source_kind = "SET_FK"

 if not getattr(existing_column, "datatype", None):
 existing_column.datatype = getattr(parent_pk_column, "datatype", "") or ""

 return existing_column

 new_column = DB2Column(
 name=column_name,
 datatype=getattr(parent_pk_column, "datatype", "") or self.TECHNICAL_KEY_DATATYPE,
 nullable=True,
 primary_key=False,
 generated=True,
 source_kind="SET_FK",
)

 child_table.columns.append(new_column)

 return new_column

def add_foreign_key_if_missing(
 self,
 child_table: DB2Table,
 child_column: str,
 parent_table: DB2Table,
 parent_column: str,
 set_name: str = "",
) -> None:
 if self.foreign_key_exists(
 child_table=child_table,
 child_column=child_column,
 parent_table=parent_table,
 parent_column=parent_column,
):
 return

```

```

 child_table.foreign_keys.append(
 DB2ForeignKey(
 column_name=child_column,
 reference_table=parent_table.name,
 reference_column=parent_column,
 set_name=self.normalize_name(set_name),
)
)
)

def foreign_key_exists(
 self,
 child_table: DB2Table,
 child_column: str,
 parent_table: DB2Table,
 parent_column: str,
) -> bool:
 normalized_child_column = self.normalize_name(child_column)
 normalized_parent_table = self.normalize_name(parent_table.name)
 normalized_parent_column = self.normalize_name(parent_column)

 for foreign_key in getattr(child_table, "foreign_keys", []) or []:
 existing_child_column = self.normalize_name(
 getattr(foreign_key, "column_name", "") or ""
)
 existing_parent_table = self.normalize_name(
 getattr(foreign_key, "reference_table", "") or ""
)
 existing_parent_column = self.normalize_name(
 getattr(foreign_key, "reference_column", "") or ""
)

 if (
 existing_child_column == normalized_child_column
 and existing_parent_table == normalized_parent_table
 and existing_parent_column == normalized_parent_column
):
 return True

 return False

def ensure_record_primary_key(
 self,
 table: DB2Table,
 record_name: str,
) -> list[DB2Column]:
 primary_key_columns: list[DB2Column] = []

 for primary_key_name in list(getattr(table, "primary_keys", []) or []):
 column = self.find_column(
 table=table,
 column_name=primary_key_name,
)

 if column is None:
 continue

 column.nullable = False
 column.primary_key = True

 if not getattr(column, "source_kind", ""):
 column.source_kind = "COBOL"

 primary_key_columns.append(column)

 if primary_key_columns:
 table.primary_keys = [
 column.name
 for column in primary_key_columns
]
 table.primary_key = table.primary_keys[0]

 return primary_key_columns

generated_pk_name = self.generated_primary_key_name(
 record_name=record_name,

```



```

)

existing_generated = self.find_column(
 table=table,
 column_name=generated_pk_name,
)

if existing_generated is not None:
 existing_generated.nullable = False
 existing_generated.primary_key = True
 existing_generated.generated = True
 existing_generated.source_kind = "GENERATED PK"

 table.primary_keys = [existing_generated.name]
 table.primary_key = existing_generated.name

 return [existing_generated]

generated_column = DB2Column(
 name=generated_pk_name,
 datatype=self.TECHNICAL_KEY_DATATYPE,
 nullable=False,
 primary_key=True,
 generated=True,
 source_kind="GENERATED PK",
)

table.columns.insert(0, generated_column)
table.primary_keys = [generated_column.name]
table.primary_key = generated_column.name

return [generated_column]

def generated_primary_key_name(
 self,
 record_name: str,
) -> str:
 record_code = self.record_code(record_name)

 if record_code:
 return f"ID_RECORD_{record_code}"

 table_name = self.normalize_table_name(record_name)

 if table_name:
 return f"ID_RECORD_{table_name}"

 return "ID_RECORD"

def get_primary_key_columns(
 self,
 table: DB2Table,
) -> list[DB2Column]:
 primary_key_names = list(getattr(table, "primary_keys", []) or [])

 if not primary_key_names and getattr(table, "primary_key", None):
 primary_key_names = [table.primary_key]

 if not primary_key_names:
 primary_key_names = [
 getattr(column, "name", "") or ""
 for column in getattr(table, "columns", []) or []
 if getattr(column, "primary_key", False)
]

 result: list[DB2Column] = []

 for primary_key_name in primary_key_names:
 column = self.find_column(
 table=table,
 column_name=primary_key_name,
)

 if column is not None:
 result.append(column)

```

```

 return result

def find_column(
 self,
 table: DB2Table,
 column_name: str,
) -> DB2Column | None:
 normalized_column_name = self.normalize_name(column_name)

 if not normalized_column_name:
 return None

 for column in getattr(table, "columns", []) or []:
 current_name = self.normalize_name(
 getattr(column, "name", "") or ""
)

 if current_name == normalized_column_name:
 return column

 return None

def build_table_lookup(
 self,
 model: DB2Model,
) -> dict[str, DB2Table]:
 lookup: dict[str, DB2Table] = {}

 for table in getattr(model, "tables", []) or []:
 table_name = getattr(table, "name", "") or ""
 normalized_table_name = self.normalize_name(table_name)

 if normalized_table_name:
 lookup[normalized_table_name] = table

 suffix_removed = self.remove_record_suffix(
 normalized_table_name,
)

 if suffix_removed:
 lookup[suffix_removed] = table

 return lookup

def find_table_for_record(
 self,
 record_name: str,
 table_lookup: dict[str, DB2Table],
) -> DB2Table | None:
 normalized_record_name = self.normalize_table_name(record_name)

 if normalized_record_name in table_lookup:
 return table_lookup[normalized_record_name]

 suffix_removed = self.remove_record_suffix(
 normalized_record_name,
)

 if suffix_removed in table_lookup:
 return table_lookup[suffix_removed]

 for table_key, table in table_lookup.items():
 if self.remove_record_suffix(table_key) == suffix_removed:
 return table

 return None

def normalize_table_name(
 self,
 value: str | None,
) -> str:
 return self.to_db2_name(value or "")

def normalize_column_name(
 self,
 value: str | None,

```

```

 record_name: str | None,
 field=None,
) -> str:
 raw_value = str(value or "").strip()

 if not raw_value:
 return ""

 if field is not None and self.is_date_field(field=field):
 return self.date_column_name(
 field_name=raw_value,
 record_name=record_name,
)

 return self.normal_business_column_name(
 field_name=raw_value,
 record_name=record_name,
)

 def normal_business_column_name(
 self,
 field_name: str,
 record_name: str | None,
) -> str:
 base = self.business_field_base_name(
 field_name=field_name,
)

 record_code = self.record_code(record_name)

 if record_code:
 return f"{base}_479{record_code}"

 return base

 def date_column_name(
 self,
 field_name: str,
 record_name: str | None,
) -> str:
 base = self.date_field_base_name(
 field_name=field_name,
)

 record_code = self.record_code(record_name)

 if record_code:
 return f"{base}_479{record_code}"

 return base

 def business_field_base_name(
 self,
 field_name: str,
) -> str:
 normalized = self.to_db2_name(field_name)

 normalized = self.remove_record_suffix(normalized)

 parts = [
 part
 for part in normalized.split("_")
 if part
]

 if not parts:
 return normalized

 parts = self.remove_generic_trailing_tokens(
 parts=parts,
)

 parts = [
 self.PROJECT_ABBREVIATIONS.get(part, part)
 for part in parts
]

```

```

 if len(parts) == 1:
 return parts[0]

 first = parts[0]
 rest = "".join(parts[1:])

 if rest:
 return f"{first}_{rest}"

 return first

def date_field_base_name(
 self,
 field_name: str,
) -> str:
 normalized = self.to_db2_name(field_name)

 normalized = self.remove_record_suffix(normalized)

 parts = [
 part
 for part in normalized.split("_")
 if part
]

 if not parts:
 return normalized

 if parts[0] == "DA":
 main_parts = parts[1:]
 else:
 main_parts = parts

 if not main_parts:
 return "DA"

 if main_parts[0] in {"UB", "UE"}:
 return f"DA_{main_parts[0]}DATE"

 main_parts = self.apply_date_project_abbreviations(
 parts=main_parts,
)

 main_parts = self.remove_generic_trailing_tokens(
 parts=main_parts,
)

 if not main_parts:
 return "DA"

 if len(main_parts) == 1:
 main = main_parts[0]
 else:
 main = "".join(main_parts)

 return f"DA_{main}"

def apply_date_project_abbreviations(
 self,
 parts: list[str],
) -> list[str]:
 output: list[str] = []

 for part in parts:
 if part == "EVPRCP":
 output.append("ERCP")
 continue

 if part == "GDIFAR":
 output.append("GD")
 continue

 if part in {"GDIFC", "GDIFR"}:
 continue

```

```

 output.append(
 self.PROJECT_ABBREVIATIONS.get(part, part)
)

 return output

def remove_generic_trailing_tokens(
 self,
 parts: list[str],
) -> list[str]:
 output = list(parts or [])

 while output and output[-1] in self.GENERIC_TRAILING_TOKENS:
 output.pop()

 return output

def record_code(
 self,
 record_name: str | None,
) -> str:
 normalized = self.to_db2_name(record_name or "")
 compact = re.sub(r"^[A-Z0-9]", "", normalized)

 if not compact:
 return ""

 if len(compact) <= 4:
 return compact

 return compact[-4:]

def is_date_field(
 self,
 field,
) -> bool:
 datatype = str(
 getattr(field, "datatype", None)
 or getattr(field, "data_type", None)
 or getattr(field, "type", None)
 or "",
).strip().upper()

 basetype = str(
 getattr(field, "basetype", None)
 or getattr(field, "base_type", None)
 or "",
).strip().upper()

 if datatype == "DATE" or basetype == "DATE":
 return True

 field_name = getattr(field, "name", "") or ""

 if self.is_date_like_name(field_name):
 picture = str(
 getattr(field, "picture", None)
 or getattr(field, "pic", None)
 or getattr(field, "pic_clause", None)
 or "",
).strip()

 if self.is_yyyymmdd_picture(picture):
 return True

 return False

def is_yyyymmdd_picture(
 self,
 picture: str,
) -> bool:
 if not picture:
 return False

 clean = DB2DatatypeMapper.clean_picture(
 picture=picture,

```

```

)
 core = DB2DatatypeMapper.picture_core(
 picture=clean,
)

 return core in {
 "9(8)",
 "S9(8)",
 "99999999",
 "S99999999",
 }

def is_date_like_name(
 self,
 value: str,
) -> bool:
 parts = self.name_parts(value)

 if not parts:
 return False

 if parts[0] == "DA":
 return True

 if any(part in self.DATE_TOKENS for part in parts):
 return True

 compact = "".join(parts)

 return any(token in compact for token in self.DATE_TOKENS)

def is_date_part_name(
 self,
 value: str,
) -> bool:
 parts = self.name_parts(value)

 for part in parts:
 if part in self.YEAR_PARTS:
 return True

 if part in self.MONTH_PARTS:
 return True

 if part in self.DAY_PARTS:
 return True

 return False

def get_record_primary_keys(
 self,
 record,
) -> list[str]:
 primary_keys: list[str] = []

 explicit_primary_keys = getattr(record, "primary_keys", None)

 if explicit_primary_keys:
 if isinstance(explicit_primary_keys, list):
 primary_keys.extend(explicit_primary_keys)
 else:
 primary_keys.append(explicit_primary_keys)

 primary_key = getattr(record, "primary_key", None)

 if primary_key:
 primary_keys.append(primary_key)

 cleaned: list[str] = []

 for primary_key_value in primary_keys:
 normalized = self.normalize_name(
 primary_key_value,
)

 if not normalized:

```

```

 continue

 if normalized in cleaned:
 continue

 cleaned.append(normalized)

return cleaned

def get_relationship_set_name(
 self,
 relationship,
) -> str:
 if isinstance(relationship, dict):
 return str(
 relationship.get("set_name")
 or relationship.get("set")
 or relationship.get("name")
 or "",
)

 return str(
 getattr(relationship, "set_name", None)
 or getattr(relationship, "set", None)
 or getattr(relationship, "name", None)
 or "",
)

def get_relationship_owner_record(
 self,
 relationship,
) -> str:
 if isinstance(relationship, dict):
 return str(
 relationship.get("owner_record")
 or relationship.get("parent_record")
 or relationship.get("owner")
 or relationship.get("parent")
 or "",
)

 return str(
 getattr(relationship, "owner_record", None)
 or getattr(relationship, "parent_record", None)
 or getattr(relationship, "owner", None)
 or getattr(relationship, "parent", None)
 or "",
)

def get_relationship_member_record(
 self,
 relationship,
) -> str:
 if isinstance(relationship, dict):
 return str(
 relationship.get("member_record")
 or relationship.get("child_record")
 or relationship.get("member")
 or relationship.get("child")
 or "",
)

 return str(
 getattr(relationship, "member_record", None)
 or getattr(relationship, "child_record", None)
 or getattr(relationship, "member", None)
 or getattr(relationship, "child", None)
 or "",
)

def normalize_name(
 self,
 value: str | None,
) -> str:
 return self.to_db2_name(value or "")

```

```

def to_db2_name(
 self,
 value: str | None,
) -> str:
 text = str(value or "").strip().upper()

 text = text.replace("\u00a0", " ")
 text = text.replace("\t", " ")

 text = re.sub(r"^[A-Z0-9]+", "_", text)
 text = re.sub(r"_"+, "_", text)
 text = text.strip("_")

 return text

def name_parts(
 self,
 value: str | None,
) -> list[str]:
 normalized = self.to_db2_name(value or "")

 return [
 part
 for part in normalized.split("_")
 if part
]

def remove_record_suffix(
 self,
 name: str | None,
) -> str:
 value = str(name or "").strip().upper()

 value = re.sub(r"[_-\s]+[0-9]{4}$", "", value)
 value = re.sub(r"[0-9]{4}$", "", value)
 value = re.sub(r"[_-\s]+$", "", value)

 return value

```

```

=====
FILE: src\idms_modernizer\services\db2_model_builder.py
ENCODING: utf-8
=====

```

```

from idms_modernizer.domain.canonical_models import CanonicalSchema
from idms_modernizer.domain.db2_models import DB2Model
from idms_modernizer.services.db2_mapping_service import DB2MappingService

```

```

class DB2ModelBuilder:

 def __init__(self):
 self.mapping_service = DB2MappingService()

 def build(
 self,
 schema: CanonicalSchema
) -> DB2Model:

 return self.mapping_service.build_db2_model(
 schema
)

```

```

=====
FILE: src\idms_modernizer\services\db2_model_service.py
ENCODING: utf-8
=====

```

```

from idms_modernizer.domain.db2_models import (
 DB2Column,
 DB2Model,
 DB2Table
)

```



```
class DB2ModelService:
```

```
 def build(
 self,
 metadata
) -> DB2Model:

 tables = []

 for record in metadata.records:

 columns = []

 for field in record.fields:

 columns.append(
 DB2Column(
 name=field.name,
 datatype="VARCHAR(255)"
)
)

 tables.append(
 DB2Table(
 name=record.name,
 columns=columns,
 foreign_keys=[]
)
)

 return DB2Model(
 tables=tables
)
```

```
=====
FILE: src\idms_modernizer\services\db2_name_normalizer.py
ENCODING: utf-8
=====
```

```
from idms_modernizer.services.name_normalizer import NameNormalizer
```

```
class DB2NameNormalizer:
```

```
 REMOVE_RECORD_SUFFIX = False
```

```
 @staticmethod
```

```
 def normalize_record_name(
```

```
 name: str | None
```

```
) -> str:
```

```
 return NameNormalizer.normalize(name)
```

```
 @staticmethod
```

```
 def normalize_column_name(
```

```
 name: str | None
```

```
) -> str:
```

```
 normalized = NameNormalizer.normalize(name)
```

```
 if not DB2NameNormalizer.REMOVE_RECORD_SUFFIX:
```

```
 return normalized
```

```
 parts = normalized.split("_")
```

```
 if (
```

```
 len(parts) > 1
```

```
 and parts[-1].isdigit()
```

```
 and len(parts[-1]) == 4
```

```
):
```

```
 return "_".join(parts[:-1])
```

```
 return normalized
```

```
=====
FILE: src\idms_modernizer\services\document_segmenter.py
ENCODING: utf-8
=====
```

```
import re

from idms_modernizer.domain.section_models import (
 RecordSection
)

class DocumentSegmenter:

 RECORD_PATTERN = re.compile(
 r"RECORD\s+NAME.*?([A-Z0-9\-]+)",
 re.IGNORECASE
)

 def segment(
 self,
 document
) -> list[RecordSection]:

 sections = []

 current_section = None

 for page in document.pages:

 for line in page.lines:

 text = line.text.strip()

 record_match = (
 self.RECORD_PATTERN.search(
 text
)
)

 if record_match:

 if current_section:

 sections.append(
 current_section
)

 current_section = (
 RecordSection(
 record_name=record_match.group(1),
 lines=[]
)
)

 elif current_section:

 current_section.lines.append(
 text
)

 if current_section:

 sections.append(
 current_section
)

 return sections
```

```
=====
FILE: src\idms_modernizer\services\er_diagram_generator.py
ENCODING: utf-8
=====
```

```
import os
from pathlib import Path
from graphviz import Digraph

from idms_modernizer.domain.schema_models import (
 SchemaMetadata
)

def generate_er_diagram(
 metadata: SchemaMetadata,
 output_path: str
) -> str:
 """Generate a simple ER diagram PNG from the canonical metadata.

 Nodes are records and edges are relationships (labeled with set name
 and cardinality if present).
 Returns the path to the generated PNG file.
 """

 out = Path(output_path)
 out.parent.mkdir(parents=True, exist_ok=True)
 os.environ["PATH"] += (
 os.pathsep +
 r"C:\Program Files\Graphviz\bin"
)

 dot = Digraph("er", format="png")
 dot.attr(rankdir="LR")
 dot.attr("node", shape="box")

 # Add record nodes
 for record in metadata.records:
 # simple label: record name
 dot.node(record.name, label=record.name)

 # Add relationships
 for rel in metadata.relationships:
 owner = rel.owner_record
 member = rel.member_record
 label = rel.set_name
 if getattr(rel, "cardinality", None):
 label = f"{label}\n{rel.cardinality}"

 dot.edge(owner, member, label=label)

 # Render to the requested path (without extension)
 filename_no_ext = str(out.with_suffix(""))

 try:
 dot.render(
 filename=filename_no_ext,
 cleanup=True
)
 except Exception as ex:
 raise RuntimeError(
 "Graphviz not installed. "
 "Install Graphviz and add "
 "'C:\\Program Files\\Graphviz\\bin' "
 "to PATH."
) from ex

 # Graphviz writes the .png next to filename_no_ext
 png_path = filename_no_ext + ".png"

 return png_path
```

```
=====
FILE: src\idms_modernizer\services\excel_sheet_mapping_service.py
ENCODING: utf-8
=====
```

```
import re

from idms_modernizer.domain.db2_models import (
 DB2Model,
 DB2Table,
 DB2Column,
)
from idms_modernizer.domain.schema_models import SchemaMetadata
from idms_modernizer.services.name_normalizer import NameNormalizer
from idms_modernizer.services.db2_datatype_mapper import DB2DatatypeMapper

print("LOADED ExcelSheetMappingService VERSION FULL-LATEST-CALC-PIC-DATE-FK-NAMING-2026-07-29")

class ExcelSheetMappingService:
 """
 Builds Excel Sheet Mapping rows.

 Rules:
 - Always add level 01 record row if missing.
 - Include all outer/group rows from mapping_fields.
 - Group rows do not create DB2 physical field names.
 - Outer CALC group does not show CALC.
 - Inner groups under CALC also do not show CALC or PK.
 - Only elementary non-date descendants of CALC show CALC and PK.
 - Date groups and date parts inside CALC show neither CALC nor PK.
 - FILLER rows are COBOL-only.
 - Outer date group shows DB2 record and DATE datatype.
 - Date parts remain visible but DB2 mapping stays blank.
 - Sheet Mapping DB2 datatype is calculated directly from IDMS PIC Clause.
 - Field end position = STRT + LGTH - 1.
 - SET/FK rows reuse referenced/master DB2 column names.
 - DB2 field names use project naming rules and _479<record-code>.
 """

 COLUMNS = [
 "Cobol Record IDMS",
 "Cobol Zone",
 "IDMS Key",
 "IDMS PIC Clause",
 "Length of Field Bytes",
 "Field end position",
 "DB2 Key",
 "New DB2 Record",
 "New DB2 Field name",
 "New DB2 Data Type",
 "Hopex Expression TypeRemark",
 "Relation",
 "Reference Field Name (CopyBook) ",
 "Reference Field PIC Clause",
 "Cross Application DB2 Field Name",
 "Cross Appln DB2 Data Type",
 "Basetype",
]

 YEAR_PARTS = {
 "YEAR",
 "YR",
 "Y",
 "YY",
 "YYYY",
 "DY",
 }

 MONTH_PARTS = {
 "MONTH",
 "MON",
 "MO",
 "M",
 "MM",
 }
```

```

 "DM",
}

DAY_PARTS = {
 "DAY",
 "D",
 "DD",
}

DATE_TOKENS = {
 "DATE",
 "DT",
 "DTE",
 "DA",
 "YYMMDD",
 "YYYYMMDD",
 "YMD",
}

DATE_CHILD_TOKENS = YEAR_PARTS | MONTH_PARTS | DAY_PARTS

PROJECT_ABBREVIATIONS = {
 "FORM": "FM",
 "EVPRCP": "ERCP",
}

GENERIC_TRAILING_TOKENS = {
 "SIC",
 "FC",
 "GDIFC",
 "GDIFR",
 "GDIFAR",
 "GDIF",
 "GDI",
 "REC",
 "RECORD",
}

DATE_TRAILING_TOKENS = {
 "SIC",
 "FC",
 "GDIFC",
 "GDIFR",
 "GDIF",
 "GDI",
}

def build(
 self,
 metadata: SchemaMetadata,
 db2_model: DB2Model,
) -> list[dict[str, str]]:
 print("USING ExcelSheetMappingService.build VERSION FULL-LATEST-CALC-PIC-DATE-FK-NAMING-2026-07-29")

 rows: list[dict[str, str]] = []

 table_lookup = self.build_table_lookup(
 db2_model=db2_model,
)

 relationship_lookup = self.build_relationship_lookup(
 metadata=metadata,
)

 for record in getattr(metadata, "records", []) or []:
 mapping_fields = (
 getattr(record, "mapping_fields", None)
 or getattr(record, "fields", None)
 or []
)

 if not self.has_level_01_row(
 record=record,
 mapping_fields=mapping_fields,
):
 rows.append(

```

```

 self.build_record_level_01_row(
 record=record,
)
)

 table = self.find_table_for_record(
 record_name=getattr(record, "name", "") or "",
 table_lookup=table_lookup,
)

 rows.extend(
 self.build_record_mapping_rows(
 record=record,
 table=table,
 relationship_lookup=relationship_lookup,
)
)

 rows.extend(
 self.build_generated_pk_rows(
 record=record,
 table=table,
)
)

 rows.extend(
 self.build_audit_rows(
 record=record,
 table=table,
)
)

 rows.extend(
 self.build_set_fk_rows_for_record(
 metadata=metadata,
 record=record,
 table=table,
 table_lookup=table_lookup,
)
)

 rows = self.force_pic_based_datatypes(
 rows=rows,
)

 return rows

def build_record_mapping_rows(
 self,
 record,
 table: DB2Table | None,
 relationship_lookup: dict[str, str],
) -> list[dict[str, str]]:
 rows: list[dict[str, str]] = []

 mapping_fields = (
 getattr(record, "mapping_fields", None)
 or getattr(record, "fields", None)
 or []
)

 column_lookup = (
 self.build_column_lookup(table=table)
 if table is not None
 else {}
)

 date_scope = self.build_date_scope(
 fields=mapping_fields,
)

 date_group_info = self.collect_date_group_info(
 fields=mapping_fields,
)

 calc_scope = self.build_calc_scope(

```

```

 record=record,
 fields=mapping_fields,
)

 for field in mapping_fields:
 if self.is_filler_field(field=field):
 rows.append(
 self.build_filler_row(
 record=record,
 field=field,
)
)
 continue

 is_group = self.is_group_field(
 field=field,
)

 is_outer_date = self.is_outer_date_group(
 field=field,
 date_group_info=date_group_info,
)

 is_date_child = self.is_date_child(
 field=field,
 date_scope=date_scope,
)

 is_direct_date = self.is_direct_date_field(
 field=field,
)

 is_date = (
 is_outer_date
 or is_date_child
 or is_direct_date
)

 calc_status = self.calc_status_for_field(
 field=field,
 calc_scope=calc_scope,
)

 db2_column = self.find_column_for_field(
 record=record,
 field=field,
 column_lookup=column_lookup,
)

 db2_key = self.db2_key_label(
 table=table,
 column=db2_column,
)

 if calc_status == "ROOT":
 db2_key = ""

 if is_group:
 db2_key = ""

 if calc_status == "DESCENDANT" and not is_date and not is_group:
 db2_key = self.add_pk_to_db2_key(
 db2_key=db2_key,
)

 if is_date:
 db2_key = ""

 row = self.empty_row()

 row["Cobol Record IDMS"] = getattr(record, "name", "") or ""
 row["Cobol Zone"] = self.format_cobol_zone(field=field)
 row["IDMS Key"] = self.idms_key_label(
 calc_status=calc_status,
 is_date=is_date,
 is_group=is_group,

```

```

 db2_key=db2_key,
)
 row["IDMS PIC Clause"] = self.get_field_picture(field=field)
 row["Length of Field Bytes"] = self.to_string(
 self.get_field_length(field=field)
)
 row["Field end position"] = self.to_string(
 self.get_field_end_position(field=field)
)
 row["DB2 Key"] = db2_key

 if is_outer_date:
 row["New DB2 Record"] = self.db2_record_name(
 record=record,
 table=table,
)
 row["New DB2 Field name"] = self.convert_date_field_to_db2_field_name(
 record=record,
 field=field,
)
 row["New DB2 Data Type"] = "DATE"
 row["DB2 Key"] = ""

 elif is_date_child:
 row["New DB2 Record"] = ""
 row["New DB2 Field name"] = ""
 row["New DB2 Data Type"] = ""
 row["DB2 Key"] = ""

 elif is_direct_date:
 row["New DB2 Record"] = self.db2_record_name(
 record=record,
 table=table,
)
 row["New DB2 Field name"] = self.convert_date_field_to_db2_field_name(
 record=record,
 field=field,
)
 row["New DB2 Data Type"] = "DATE"
 row["DB2 Key"] = ""

 elif calc_status == "ROOT":
 row["New DB2 Record"] = ""
 row["New DB2 Field name"] = ""
 row["New DB2 Data Type"] = ""
 row["DB2 Key"] = ""

 elif is_group:
 row["New DB2 Record"] = ""
 row["New DB2 Field name"] = ""
 row["New DB2 Data Type"] = ""
 row["DB2 Key"] = ""

 elif self.should_emit_db2_field(field=field):
 row["New DB2 Record"] = self.db2_record_name(
 record=record,
 table=table,
)

 if db2_column is not None and getattr(db2_column, "name", None):
 row["New DB2 Field name"] = getattr(db2_column, "name", "") or ""
 else:
 row["New DB2 Field name"] = self.convert_cobol_zone_to_db2_field_name(
 record=record,
 field=field,
)

 row["New DB2 Data Type"] = self.infer_db2_datatype_from_field(
 field=field,
)

 row["Hopex Expression TypeRemark"] = self.hopex_remark(
 field=field,
)
 row["Relation"] = relationship_lookup.get(
 NameNormalizer.normalize(getattr(record, "name", "") or ""),

```



```

 "",
)
 row["Basetype"] = self.get_field_basetype(
 field=field,
)

 rows.append(row)

return rows

def build_calc_scope(
 self,
 record,
 fields,
) -> dict[str, str]:
 scope: dict[str, str] = {}

 primary_key = getattr(record, "primary_key", None)

 if not primary_key:
 return scope

 normalized_primary_key = NameNormalizer.normalize(primary_key)
 suffix_removed_primary_key = self.remove_record_suffix(
 normalized_primary_key,
)

 mapping_fields = list(fields or [])

 key_field = None
 key_index = None

 for index, field in enumerate(mapping_fields):
 field_name = NameNormalizer.normalize(
 getattr(field, "name", "") or ""
)

 if not field_name:
 continue

 if field_name == normalized_primary_key:
 key_field = field
 key_index = index
 break

 if self.remove_record_suffix(field_name) == suffix_removed_primary_key:
 key_field = field
 key_index = index
 break

 if key_field is None or key_index is None:
 if normalized_primary_key:
 scope[normalized_primary_key] = "DESCENDANT"
 return scope

 key_name = NameNormalizer.normalize(
 getattr(key_field, "name", "") or ""
)

 if not key_name:
 return scope

 key_is_group = self.is_group_field(
 field=key_field,
)

 key_level = getattr(key_field, "level", None)

 if not key_is_group:
 scope[key_name] = "DESCENDANT"
 return scope

 scope[key_name] = "ROOT"

 if key_level is None:
 return scope

```

```

try:
 key_level_int = int(key_level)
except Exception:
 return scope

for child_field in mapping_fields[key_index + 1:]:
 child_name = NameNormalizer.normalize(
 getattr(child_field, "name", "") or ""
)
 child_level = getattr(child_field, "level", None)

 if child_level is None:
 continue

 try:
 child_level_int = int(child_level)
 except Exception:
 continue

 if child_level_int <= key_level_int:
 break

 if child_name:
 scope[child_name] = "DESCENDANT"

return scope

def calc_status_for_field(
 self,
 field,
 calc_scope: dict[str, str],
) -> str:
 field_name = NameNormalizer.normalize(
 getattr(field, "name", "") or ""
)

 if not field_name:
 return ""

 if field_name in calc_scope:
 return calc_scope[field_name]

 suffix_removed = self.remove_record_suffix(field_name)

 for key, value in calc_scope.items():
 if self.remove_record_suffix(key) == suffix_removed:
 return value

 return ""

def idms_key_label(
 self,
 calc_status: str,
 is_date: bool,
 is_group: bool,
 db2_key: str,
) -> str:
 if is_date:
 return ""

 if is_group:
 return ""

 labels: list[str] = []

 if calc_status == "DESCENDANT":
 labels.append("CALC")

 db2_key_parts = [
 part.strip().upper()
 for part in str(db2_key or "").split("/")
 if part.strip()
]

 if "FK" in db2_key_parts:

```

```

 labels.append("SET")

 output: list[str] = []

 for label in labels:
 if label not in output:
 output.append(label)

 return "; ".join(output)

def add_pk_to_db2_key(
 self,
 db2_key: str,
) -> str:
 parts = [
 part.strip().upper()
 for part in str(db2_key or "").split("/")
 if part.strip()
]

 if "PK" not in parts:
 parts.insert(0, "PK")

 ordered_parts: list[str] = []

 if "PK" in parts:
 ordered_parts.append("PK")

 if "FK" in parts:
 ordered_parts.append("FK")

 return "/".join(ordered_parts)

def force_pic_based_datatypes(
 self,
 rows: list[dict[str, str]],
) -> list[dict[str, str]]:
 corrected_rows: list[dict[str, str]] = []

 for row in rows or []:
 pic_clause = str(row.get("IDMS PIC Clause", "") or "").strip()
 db2_record = str(row.get("New DB2 Record", "") or "").strip()
 db2_field = str(row.get("New DB2 Field name", "") or "").strip()
 current_type = str(row.get("New DB2 Data Type", "") or "").strip().upper()

 if current_type == "DATE":
 corrected_rows.append(row)
 continue

 if pic_clause and db2_record and db2_field:
 row["New DB2 Data Type"] = DB2DatatypeMapper.map_picture(
 picture=pic_clause,
 fallback_length=None,
 fallback_scale=None,
)

 corrected_rows.append(row)

 return corrected_rows

def build_table_lookup(
 self,
 db2_model: DB2Model,
) -> dict[str, DB2Table]:
 lookup: dict[str, DB2Table] = {}

 if db2_model is None:
 return lookup

 for table in getattr(db2_model, "tables", []) or []:
 table_name = getattr(table, "name", "") or ""

 for key in self.name_lookup_keys(table_name):
 lookup[key] = table

 return lookup

```

```

def build_column_lookup(
 self,
 table: DB2Table,
) -> dict[str, DB2Column]:
 lookup: dict[str, DB2Column] = {}

 for column in getattr(table, "columns", []) or []:
 column_name = getattr(column, "name", "") or ""

 for key in self.name_lookup_keys(column_name):
 lookup[key] = column

 return lookup

def build_relationship_lookup(
 self,
 metadata: SchemaMetadata,
) -> dict[str, str]:
 lookup: dict[str, str] = {}

 for relationship in getattr(metadata, "relationships", []) or []:
 owner_record = self.get_relationship_owner_record(relationship=relationship)
 member_record = self.get_relationship_member_record(relationship=relationship)
 set_name = self.get_relationship_set_name(relationship=relationship)

 for record_name in [owner_record, member_record]:
 normalized_record = NameNormalizer.normalize(record_name)

 if not normalized_record:
 continue

 existing = lookup.get(normalized_record, "")

 if existing:
 if set_name and set_name not in existing:
 lookup[normalized_record] = f"{existing}; {set_name}"
 else:
 lookup[normalized_record] = set_name

 return lookup

def build_date_scope(
 self,
 fields,
) -> dict[int, bool]:
 scope: dict[int, bool] = {}
 active_date_levels: list[int] = []

 for field in fields or []:
 level = self.safe_int(getattr(field, "level", None), default=0)

 active_date_levels = [
 current_level
 for current_level in active_date_levels
 if current_level < level
]

 if active_date_levels:
 scope[id(field)] = True

 if self.is_potential_outer_date(field=field):
 active_date_levels.append(level)

 return scope

def collect_date_group_info(
 self,
 fields,
) -> dict[str, dict]:
 info: dict[str, dict] = {}

 for index, field in enumerate(fields or []):
 if not self.is_group_field(field=field):
 continue

```

```

 if not self.is_potential_outer_date(field=field):
 continue

 if not self.group_has_ymd_children(
 field=field,
 fields=fields,
 start_index=index,
):
 continue

 field_name = NameNormalizer.normalize(getattr(field, "name", "") or "")

 if field_name:
 info[field_name] = {"field": field}

 return info

def group_has_ymd_children(
 self,
 field,
 fields,
 start_index: int,
) -> bool:
 parent_level = self.safe_int(getattr(field, "level", None), default=0)

 found_year = False
 found_month = False
 found_day = False

 for child in list(fields or [])[start_index + 1:]:
 child_level = self.safe_int(getattr(child, "level", None), default=0)

 if child_level <= parent_level:
 break

 child_name = getattr(child, "name", "") or ""
 parts = self.name_parts(child_name)

 if any(part in self.YEAR_PARTS for part in parts):
 found_year = True

 if any(part in self.MONTH_PARTS for part in parts):
 found_month = True

 if any(part in self.DAY_PARTS for part in parts):
 found_day = True

 return found_year and found_month and found_day

def is_outer_date_group(
 self,
 field,
 date_group_info: dict[str, dict],
) -> bool:
 if not self.is_group_field(field=field):
 return False

 field_name = NameNormalizer.normalize(getattr(field, "name", "") or "")

 return field_name in date_group_info

def is_date_child(
 self,
 field,
 date_scope: dict[int, bool],
) -> bool:
 if id(field) not in date_scope:
 return False

 return self.is_date_part_name(field_name=getattr(field, "name", "") or "")

def is_direct_date_field(
 self,
 field,
) -> bool:
 if self.is_group_field(field=field):

```

```

 return False

 datatype = str(
 getattr(field, "datatype", None)
 or getattr(field, "data_type", None)
 or getattr(field, "type", None)
 or "",
).strip().upper()

 basetype = str(
 getattr(field, "basetype", None)
 or getattr(field, "base_type", None)
 or "",
).strip().upper()

 if datatype == "DATE" or basetype == "DATE":
 return not self.is_date_part_name(field_name=getattr(field, "name", "") or "")

 pic_clause = self.get_field_picture(field=field)

 if self.is_date_like_name(getattr(field, "name", "") or "") and self.is_yyyymmdd_picture(pic_clause):
 return True

 return False

def is_potential_outer_date(
 self,
 field,
) -> bool:
 field_name = getattr(field, "name", "") or ""

 if self.is_date_like_name(field_name):
 return True

 datatype = str(
 getattr(field, "datatype", None)
 or getattr(field, "data_type", None)
 or getattr(field, "type", None)
 or "",
).strip().upper()

 basetype = str(
 getattr(field, "basetype", None)
 or getattr(field, "base_type", None)
 or "",
).strip().upper()

 return datatype == "DATE" or basetype == "DATE"

def is_date_part_name(
 self,
 field_name: str,
) -> bool:
 parts = self.name_parts(field_name or "")

 return any(part in self.DATE_CHILD_TOKENS for part in parts)

def is_yyyymmdd_picture(
 self,
 pic_clause: str,
) -> bool:
 clean = DB2DatatypeMapper.clean_picture(pic_clause)
 core = DB2DatatypeMapper.picture_core(clean)

 return core in {"9(8)", "S9(8)", "99999999", "S99999999"}

def is_date_like_name(
 self,
 value: str,
) -> bool:
 parts = self.name_parts(value or "")

 if any(part in self.DATE_TOKENS for part in parts):
 return True

 if parts and parts[0] == "DA":

```

```

 return True

compact = "".join(parts)

return any(token in compact for token in self.DATE_TOKENS)

def find_table_for_record(
 self,
 record_name: str,
 table_lookup: dict[str, DB2Table],
) -> DB2Table | None:
 for key in self.name_lookup_keys(record_name):
 if key in table_lookup:
 return table_lookup[key]

 return None

def find_column_for_field(
 self,
 record,
 field,
 column_lookup: dict[str, DB2Column],
) -> DB2Column | None:
 field_name = getattr(field, "name", "") or ""

 if not field_name:
 return None

 possible_names = [
 field_name,
 self.remove_record_suffix(field_name),
 self.cobol_field_base_name(field_name=field_name),
 self.date_field_base_name(field_name=field_name),
 self.convert_cobol_zone_to_db2_field_name(record=record, field=field),
 self.convert_date_field_to_db2_field_name(record=record, field=field),
]

 for name in possible_names:
 column = self.find_matching_column(
 normalized_column_name=name,
 column_lookup=column_lookup,
)

 if column is not None:
 return column

 return None

def find_matching_column(
 self,
 normalized_column_name: str,
 column_lookup: dict[str, DB2Column],
) -> DB2Column | None:
 for key in self.name_lookup_keys(normalized_column_name):
 if key in column_lookup:
 return column_lookup[key]

 suffix_removed = self.remove_record_suffix(normalized_column_name)

 for key in self.name_lookup_keys(suffix_removed):
 if key in column_lookup:
 return column_lookup[key]

 target_suffix_removed = self.remove_record_suffix(
 self.to_db2_name(normalized_column_name)
)

 for current_name, column in column_lookup.items():
 if self.remove_record_suffix(current_name) == target_suffix_removed:
 return column

 return None

def build_filler_row(
 self,
 record,

```

```

 field,
) -> dict[str, str]:
 row = self.empty_row()

 row["Cobol Record IDMS"] = getattr(record, "name", "") or ""
 row["Cobol Zone"] = self.format_cobol_zone(field=field)
 row["IDMS PIC Clause"] = self.get_field_picture(field=field)
 row["Length of Field Bytes"] = self.to_string(self.get_field_length(field=field))
 row["Field end position"] = self.to_string(self.get_field_end_position(field=field))

 return row

def build_generated_pk_rows(
 self,
 record,
 table: DB2Table | None,
) -> list[dict[str, str]]:
 if table is None:
 return []

 rows: list[dict[str, str]] = []

 for column in getattr(table, "columns", []) or []:
 if getattr(column, "source_kind", "") != "GENERATED PK":
 continue

 row = self.empty_row()
 row["Cobol Record IDMS"] = getattr(record, "name", "") or ""
 row["DB2 Key"] = "PK"
 row["New DB2 Record"] = getattr(table, "name", "") or ""
 row["New DB2 Field name"] = getattr(column, "name", "") or ""
 row["New DB2 Data Type"] = self.get_db2_datatype(db2_column=column)
 rows.append(row)

 return rows

def build_audit_rows(
 self,
 record,
 table: DB2Table | None,
) -> list[dict[str, str]]:
 if table is None:
 return []

 rows: list[dict[str, str]] = []
 record_name = getattr(record, "name", "") or ""
 normalized_record_name = self.to_db2_name(record_name)

 audit_fields = [
 (f"TS_CREATE_{normalized_record_name}", "TIMESTAMP"),
 (f"TS_UPDATE_{normalized_record_name}", "TIMESTAMP"),
 (f"ID_USERID_{normalized_record_name}", "CHAR(8)"),
]

 for field_name, datatype in audit_fields:
 row = self.empty_row()
 row["Cobol Record IDMS"] = record_name
 row["New DB2 Record"] = getattr(table, "name", "") or ""
 row["New DB2 Field name"] = field_name
 row["New DB2 Data Type"] = datatype
 rows.append(row)

 return rows

def build_set_fk_rows_for_record(
 self,
 metadata: SchemaMetadata,
 record,
 table: DB2Table | None,
 table_lookup: dict[str, DB2Table],
) -> list[dict[str, str]]:
 if table is None:
 return []

 rows: list[dict[str, str]] = []
 emitted: set[tuple[str, str, str]] = set()

```



```

rows.extend(
 self.build_set_fk_rows_from_db2_foreign_keys(
 record=record,
 table=table,
 emitted=emitted,
)
)

rows.extend(
 self.build_set_fk_rows_from_metadata_relationships(
 metadata=metadata,
 record=record,
 member_table=table,
 table_lookup=table_lookup,
 emitted=emitted,
)
)

return rows

def build_set_fk_rows_from_db2_foreign_keys(
 self,
 record,
 table: DB2Table,
 emitted: set[tuple[str, str, str, str]],
) -> list[dict[str, str]]:
 rows: list[dict[str, str]] = []
 cobol_record_name = getattr(record, "name", "") or ""

 column_lookup = self.build_column_lookup(table=table)

 for foreign_key in getattr(table, "foreign_keys", []) or []:
 fk_column_name = self.get_foreign_key_column_name(foreign_key=foreign_key)

 if not fk_column_name:
 continue

 fk_column = self.find_matching_column(
 normalized_column_name=fk_column_name,
 column_lookup=column_lookup,
)

 if fk_column is None:
 continue

 fk_datatype = self.get_db2_datatype(db2_column=fk_column)
 set_name = getattr(foreign_key, "set_name", "") or ""

 key = (
 NameNormalizer.normalize(cobol_record_name),
 NameNormalizer.normalize(getattr(table, "name", "") or ""),
 NameNormalizer.normalize(getattr(fk_column, "name", "") or ""),
 fk_datatype,
)

 if key in emitted:
 continue

 emitted.add(key)

 row = self.empty_row()
 row["Cobol Record IDMS"] = cobol_record_name
 row["IDMS Key"] = "SET"
 row["DB2 Key"] = "FK"
 row["New DB2 Record"] = getattr(table, "name", "") or ""
 row["New DB2 Field name"] = getattr(fk_column, "name", "") or ""
 row["New DB2 Data Type"] = fk_datatype
 row["Relation"] = set_name
 rows.append(row)

 return rows

def build_set_fk_rows_from_metadata_relationships(
 self,
 metadata: SchemaMetadata,

```

```

record,
member_table: DB2Table,
table_lookup: dict[str, DB2Table],
emitted: set[tuple[str, str, str, str]],
) -> list[dict[str, str]]:
 rows: list[dict[str, str]] = []

 cobol_record_name = getattr(record, "name", "") or ""
 normalized_current_record = NameNormalizer.normalize(cobol_record_name)
 normalized_current_table = NameNormalizer.normalize(getattr(member_table, "name", "") or "")

 for relationship in getattr(metadata, "relationships", []) or []:
 set_name = self.get_relationship_set_name(relationship=relationship)
 owner_record_name = self.get_relationship_owner_record(relationship=relationship)
 member_record_name = self.get_relationship_member_record(relationship=relationship)

 if not set_name:
 continue

 normalized_member_record = NameNormalizer.normalize(member_record_name)

 if normalized_member_record not in {normalized_current_record, normalized_current_table}:
 continue

 owner_table = self.find_table_for_record(
 record_name=owner_record_name,
 table_lookup=table_lookup,
)

 owner_pk_column = self.find_primary_key_column(table=owner_table)

 if owner_pk_column is None:
 continue

 fk_column_name = getattr(owner_pk_column, "name", "") or ""
 fk_datatype = self.get_db2_datatype(db2_column=owner_pk_column)

 key = (
 NameNormalizer.normalize(cobol_record_name),
 NameNormalizer.normalize(getattr(member_table, "name", "") or ""),
 NameNormalizer.normalize(fk_column_name),
 fk_datatype,
)

 if key in emitted:
 continue

 emitted.add(key)

 row = self.empty_row()
 row["Cobol Record IDMS"] = cobol_record_name
 row["IDMS Key"] = "SET"
 row["DB2 Key"] = "FK"
 row["New DB2 Record"] = getattr(member_table, "name", "") or ""
 row["New DB2 Field name"] = fk_column_name
 row["New DB2 Data Type"] = fk_datatype
 row["Relation"] = set_name
 rows.append(row)

 return rows

def find_primary_key_column(
 self,
 table: DB2Table | None,
) -> DB2Column | None:
 if table is None:
 return None

 primary_key_names = list(getattr(table, "primary_keys", []) or [])

 if not primary_key_names and getattr(table, "primary_key", None):
 primary_key_names = [table.primary_key]

 normalized_primary_keys = {
 NameNormalizer.normalize(primary_key)
 for primary_key in primary_key_names
 }

```

```

 if primary_key
 }

 for column in getattr(table, "columns", []) or []:
 column_name = NameNormalizer.normalize(getattr(column, "name", "") or "")

 if column_name in normalized_primary_keys:
 return column

 if getattr(column, "primary_key", False):
 return column

 columns = list(getattr(table, "columns", []) or [])

 return columns[0] if columns else None

def get_foreign_key_column_name(
 self,
 foreign_key,
) -> str:
 if isinstance(foreign_key, dict):
 return str(
 foreign_key.get("column_name")
 or foreign_key.get("column")
 or foreign_key.get("fk_column")
 or foreign_key.get("foreign_key_column")
 or "",
)

 return str(
 getattr(foreign_key, "column_name", None)
 or getattr(foreign_key, "column", None)
 or getattr(foreign_key, "fk_column", None)
 or getattr(foreign_key, "foreign_key_column", None)
 or "",
)

def get_relationship_set_name(
 self,
 relationship,
) -> str:
 if isinstance(relationship, dict):
 return str(
 relationship.get("set_name")
 or relationship.get("set")
 or relationship.get("name")
 or "",
)

 return str(
 getattr(relationship, "set_name", None)
 or getattr(relationship, "set", None)
 or getattr(relationship, "name", None)
 or "",
)

def get_relationship_owner_record(
 self,
 relationship,
) -> str:
 if isinstance(relationship, dict):
 return str(
 relationship.get("owner_record")
 or relationship.get("parent_record")
 or relationship.get("owner")
 or relationship.get("parent")
 or "",
)

 return str(
 getattr(relationship, "owner_record", None)
 or getattr(relationship, "parent_record", None)
 or getattr(relationship, "owner", None)
 or getattr(relationship, "parent", None)
 or "",
)

```

```

def get_relationship_member_record(
 self,
 relationship,
) -> str:
 if isinstance(relationship, dict):
 return str(
 relationship.get("member_record")
 or relationship.get("child_record")
 or relationship.get("member")
 or relationship.get("child")
 or "",
)

 return str(
 getattr(relationship, "member_record", None)
 or getattr(relationship, "child_record", None)
 or getattr(relationship, "member", None)
 or getattr(relationship, "child", None)
 or "",
)

def get_db2_datatype(
 self,
 db2_column: DB2Column | None,
) -> str:
 if db2_column is None:
 return ""

 return str(
 getattr(db2_column, "datatype", None)
 or getattr(db2_column, "data_type", None)
 or getattr(db2_column, "type", None)
 or "",
).strip().upper()

def db2_key_label(
 self,
 table: DB2Table | None,
 column: DB2Column | None,
) -> str:
 if table is None or column is None:
 return ""

 labels: list[str] = []

 if self.is_primary_key_column(table=table, column=column):
 labels.append("PK")

 if self.is_foreign_key_column(table=table, column=column):
 labels.append("FK")

 return "/".join(labels)

def is_primary_key_column(
 self,
 table: DB2Table,
 column: DB2Column,
) -> bool:
 if getattr(column, "primary_key", False):
 return True

 column_name = NameNormalizer.normalize(getattr(column, "name", "") or "")
 primary_keys = list(getattr(table, "primary_keys", []) or [])

 if not primary_keys and getattr(table, "primary_key", None):
 primary_keys = [table.primary_key]

 normalized_primary_keys = {
 NameNormalizer.normalize(primary_key)
 for primary_key in primary_keys
 if primary_key
 }

 return column_name in normalized_primary_keys

```

```

def is_foreign_key_column(
 self,
 table: DB2Table,
 column: DB2Column,
) -> bool:
 column_name = NameNormalizer.normalize(getattr(column, "name", "") or "")

 for foreign_key in getattr(table, "foreign_keys", []) or []:
 fk_column_name = NameNormalizer.normalize(self.get_foreign_key_column_name(foreign_key))

 if fk_column_name == column_name:
 return True

 source_kind = str(getattr(column, "source_kind", "") or "").upper()

 return source_kind in {"SET_FK", "FK", "FOREIGN KEY"}

def should_emit_db2_field(
 self,
 field,
) -> bool:
 if self.is_filler_field(field=field):
 return False

 if self.is_group_field(field=field):
 return False

 if self.is_date_part_name(field_name=getattr(field, "name", "") or ""):
 return False

 picture = self.get_field_picture(field=field)

 if picture:
 return True

 datatype = str(getattr(field, "datatype", "") or "").upper()

 return datatype in {"CHAR", "VARCHAR", "DECIMAL", "NUMERIC", "DATE"}

def is_filler_field(
 self,
 field,
) -> bool:
 return NameNormalizer.normalize(getattr(field, "name", "") or "") == "FILLER"

def is_group_field(
 self,
 field,
) -> bool:
 return bool(getattr(field, "has_child", False) or getattr(field, "is_group", False))

def db2_record_name(
 self,
 record,
 table: DB2Table | None,
) -> str:
 if table is not None and getattr(table, "name", None):
 return getattr(table, "name", "") or ""

 return self.to_db2_name(getattr(record, "name", "") or "")

def convert_cobol_zone_to_db2_field_name(
 self,
 record,
 field,
) -> str:
 field_name = getattr(field, "name", "") or ""
 base = self.cobol_field_base_name(field_name=field_name)
 record_code = self.record_code(record_name=getattr(record, "name", "") or "")

 if record_code:
 return f"{base}_479{record_code}"

 return base

def convert_date_field_to_db2_field_name(

```

```

 self,
 record,
 field,
) -> str:
 field_name = getattr(field, "name", "") or ""
 base = self.date_field_base_name(field_name=field_name)
 record_code = self.record_code(record_name=getattr(record, "name", "") or "")

 if record_code:
 return f"{base}_479{record_code}"

 return base

def cobol_field_base_name(
 self,
 field_name: str,
) -> str:
 normalized = self.to_db2_name(field_name)
 normalized = self.remove_record_suffix(normalized)

 parts = [
 part
 for part in normalized.split("_")
 if part
]

 if not parts:
 return normalized

 parts = self.remove_generic_trailing_tokens(parts=parts)

 parts = [
 self.PROJECT_ABBREVIATIONS.get(part, part)
 for part in parts
]

 if len(parts) == 1:
 return parts[0]

 first = parts[0]
 rest = "".join(parts[1:])

 if rest:
 return f"{first}_{rest}"

 return first

def date_field_base_name(
 self,
 field_name: str,
) -> str:
 normalized = self.to_db2_name(field_name)
 normalized = self.remove_record_suffix(normalized)

 parts = [
 part
 for part in normalized.split("_")
 if part
]

 if not parts:
 return normalized

 if parts[0] == "DA":
 main_parts = parts[1:]
 else:
 main_parts = parts

 if not main_parts:
 return "DA"

 if main_parts[0] in {"UB", "UE"}:
 return f"DA_{main_parts[0]}DATE"

 main_parts = self.apply_date_project_abbreviations(
 parts=main_parts,

```

```

)

 main_parts = self.remove_generic_trailing_tokens(
 parts=main_parts,
)

 if not main_parts:
 return "DA"

 if len(main_parts) == 1:
 main = main_parts[0]
 else:
 main = "".join(main_parts)

 return f"DA_{main}"

def apply_date_project_abbreviations(
 self,
 parts: list[str],
) -> list[str]:
 output: list[str] = []

 for part in parts:
 if part == "EVPRCP":
 output.append("ERCP")
 continue

 if part == "GDIFAR":
 output.append("GD")
 continue

 if part in {"GDIFC", "GDIFR"}:
 continue

 output.append(
 self.PROJECT_ABBREVIATIONS.get(part, part)
)

 return output

def remove_generic_trailing_tokens(
 self,
 parts: list[str],
) -> list[str]:
 output = list(parts or [])

 while output and output[-1] in self.GENERIC_TRAILING_TOKENS:
 output.pop()

 return output

def record_code(
 self,
 record_name: str,
) -> str:
 normalized = self.to_db2_name(record_name)
 compact = re.sub(r"^[A-Z0-9]", "", normalized)

 if len(compact) <= 4:
 return compact

 return compact[-4:]

def get_field_picture(
 self,
 field,
) -> str:
 if self.is_group_field(field=field):
 return ""

 text = str(
 getattr(field, "picture", None)
 or getattr(field, "pic", None)
 or getattr(field, "pic_clause", None)
 or "",
).strip()

```

```

 if not text:
 return ""

 if text.upper().startswith("PIC "):
 return text

 if text.upper().startswith("PICTURE "):
 return "PIC " + text[8:].strip()

 return f"PIC {text}"

def get_field_length(
 self,
 field,
):
 return (
 getattr(field, "length", None)
 or getattr(field, "storage_length", None)
 or getattr(field, "physical_length", None)
 or getattr(field, "byte_length", None)
 or getattr(field, "bytes", None)
)

def get_field_end_position(
 self,
 field,
):
 start = (
 getattr(field, "start_position", None)
 or getattr(field, "start", None)
)

 length = self.get_field_length(field=field)

 try:
 if start is not None and length not in ("", None):
 return int(start) + int(length) - 1
 except Exception:
 pass

 end_position = (
 getattr(field, "end_position", None)
 or getattr(field, "field_end_position", None)
 or getattr(field, "end", None)
)

 if end_position is not None:
 return end_position

 return ""

def infer_db2_datatype_from_field(
 self,
 field,
) -> str:
 pic_clause = self.get_field_picture(field=field)

 if pic_clause:
 return DB2DatatypeMapper.map_picture(
 picture=pic_clause,
 fallback_length=None,
 fallback_scale=getattr(field, "scale", None),
)

 datatype = str(getattr(field, "datatype", "") or "").upper()

 if datatype == "DATE":
 return "DATE"

 if datatype in {"TIMESTAMP", "DATETIME"}:
 return "TIMESTAMP"

 length = self.get_field_length(field=field) or 1

 if datatype in {"CHAR", "VARCHAR", "DISPLAY", "TEXT"}:

```



```

 return f"CHAR({int(length)})"

 if datatype in {"DECIMAL", "NUMERIC"}:
 scale = getattr(field, "scale", None)

 if scale is not None and int(scale) > 0:
 return f"DECIMAL({int(length)},{int(scale)})"

 return f"DECIMAL({int(length)})"

 return ""

def get_field_basetype(
 self,
 field,
) -> str:
 return str(
 getattr(field, "basetype", None)
 or getattr(field, "base_type", None)
 or getattr(field, "datatype", None)
 or "",
)

def hopex_remark(
 self,
 field,
) -> str:
 if getattr(field, "occurs", False):
 occurs_min = getattr(field, "occurs_min", None)
 occurs_max = getattr(field, "occurs_max", None)

 if occurs_min is not None and occurs_max is not None:
 if occurs_min == occurs_max:
 return f"OCCURS {occurs_max}"

 return f"OCCURS {occurs_min} TO {occurs_max}"

 return ""

def has_level_01_row(
 self,
 record,
 mapping_fields,
) -> bool:
 record_name = NameNormalizer.normalize(getattr(record, "name", "") or "")

 for field in mapping_fields or []:
 level = getattr(field, "level", None)

 try:
 if int(level) != 1:
 continue
 except Exception:
 continue

 field_name = NameNormalizer.normalize(getattr(field, "name", "") or "")

 if field_name == record_name:
 return True

 if self.remove_record_suffix(field_name) == self.remove_record_suffix(record_name):
 return True

 return False

def build_record_level_01_row(
 self,
 record,
) -> dict[str, str]:
 row = self.empty_row()

 record_name = getattr(record, "name", "") or ""

 row["Cobol Record IDMS"] = record_name
 row["Cobol Zone"] = self.format_cobol_level_and_name(level=1, name=record_name)

```

```

 return row

def name_lookup_keys(
 self,
 value: str,
) -> list[str]:
 keys: list[str] = []

 candidates = [
 value,
 NameNormalizer.normalize(value or ""),
 self.to_db2_name(value or ""),
 self.remove_record_suffix(value or ""),
 self.remove_record_suffix(NameNormalizer.normalize(value or "")),
 self.remove_record_suffix(self.to_db2_name(value or "")),
]

 for candidate in candidates:
 candidate_text = str(candidate or "").strip()

 if not candidate_text:
 continue

 normalized_name = NameNormalizer.normalize(candidate_text)
 db2_name = self.to_db2_name(candidate_text)

 for key in [candidate_text, normalized_name, db2_name]:
 key = str(key or "").strip()

 if key and key not in keys:
 keys.append(key)

 return keys

def format_cobol_zone(
 self,
 field,
) -> str:
 level = getattr(field, "level", None)
 name = getattr(field, "name", "") or ""

 return self.format_cobol_level_and_name(level=level, name=name)

def format_cobol_level_and_name(
 self,
 level,
 name: str,
) -> str:
 level_text = self.to_string(level)

 if level_text:
 try:
 level_text = f"{int(level_text):02d}"
 except Exception:
 pass

 if level_text and name:
 return f"{level_text} {name}"

 if name:
 return str(name)

 return level_text

def remove_record_suffix(
 self,
 name: str,
) -> str:
 value = str(name or "").strip().upper()
 value = re.sub(r"[_\-\s]{4}$", "", value)
 value = re.sub(r"[0-9]{4}$", "", value)
 value = re.sub(r"[_\-\s]+$", "", value)

 return value

def to_db2_name(

```

```

 self,
 value: str,
) -> str:
 normalized = str(value or "").upper().strip()
 normalized = re.sub(r"^[A-Z0-9]+", "_", normalized)
 normalized = re.sub(r"_+", "_", normalized)
 normalized = normalized.strip("_")

 return normalized

 def name_parts(
 self,
 value: str,
) -> list[str]:
 normalized = self.to_db2_name(value or "")

 return [part for part in normalized.split("_") if part]

 def empty_row(
 self,
) -> dict[str, str]:
 return {column: "" for column in self.COLUMNS}

 def to_string(
 self,
 value,
) -> str:
 if value is None:
 return ""

 return str(value)

 def safe_int(
 self,
 value,
 default: int = 0,
) -> int:
 try:
 if value is None:
 return default

 text = str(value).strip()

 if not text:
 return default

 return int(text)
 except Exception:
 return default

```

```

=====
FILE: src\idms_modernizer\services\metadata_builder.py
ENCODING: utf-8
=====

```

```

import re

from idms_modernizer.domain.document_models import (
 DocumentModel
)

from idms_modernizer.domain.schema_models import (
 DataField,
 Record,
 SchemaMetadata,
)

class MetadataBuilder:

 RECORD_PATTERN = re.compile(
 r"RECORD\s+NAME.*?([A-Z][A-Z0-9\-\-]+)",
 re.IGNORECASE
)

```

```

FIELD_PATTERN = re.compile(
 r"^\d{2}\s+([A-Z][A-Z0-9-]+)",
 re.IGNORECASE
)

def build(
 self,
 document: DocumentModel
) -> SchemaMetadata:

 metadata = SchemaMetadata()

 current_record = None

 seen_records = set()

 for page in document.pages:

 for line in page.lines:

 text = line.text.strip()

 if not text:
 continue

 #
 # RECORD DETECTION
 #

 record_match = (
 self.RECORD_PATTERN.search(
 text
)
)

 if record_match:

 record_name = (
 record_match.group(1)
 .strip()
 .upper()
)

 if (
 record_name
 not in seen_records
):

 current_record = Record(
 name=record_name
)

 metadata.records.append(
 current_record
)

 seen_records.add(
 record_name
)

 continue

 #
 # FIELD DETECTION
 #

 if current_record:

 field_match = (
 self.FIELD_PATTERN.match(
 text
)
)

 if field_match:

```

```

 field_name = (
 field_match.group(1)
 .strip()
 .upper()
)

 current_record.fields.append(
 DataField(
 name=field_name
)
)

#
DEBUG OUTPUT
#

print(
 "\n===== RECORDS ====="
)

for record in metadata.records:

 print(
 f"{record.name} -> "
 f"{len(record.fields)} fields"
)

print(
 "=====\n"
)

return metadata

```

```

=====
FILE: src\idms_modernizer\services\metadata_service.py
ENCODING: utf-8
=====

```

```
import re
```

```

from idms_modernizer.parsers.text_extractor import TextExtractor
from idms_modernizer.services.document_segmenter import DocumentSegmenter
from idms_modernizer.extractors.owner_member_extractor import OwnerMemberExtractor
from idms_modernizer.extractors.field_extractor import FieldExtractor
from idms_modernizer.extractors.cobol_zone_extractor import CobolZoneExtractor
from idms_modernizer.services.schema_picture_enricher import SchemaPictureEnricher
from idms_modernizer.services.relationship_resolver import RelationshipResolver
from idms_modernizer.domain.schema_models import SchemaMetadata, Record
from idms_modernizer.extractors.primary_key_extractor import PrimaryKeyExtractor

```

```
print("LOADED MetadataService VERSION GENERIC-DEBUG-NO-FIELD-HARDCODE-2026-07-30")
```

```
class MetadataService:
```

```
 """
```

```
 Builds SchemaMetadata from the schema PDF.
```

```
 Critical rule:
```

- record.fields is used for physical DB2 / DDL / canonical schema.
- record.mapping\_fields is used for Excel Sheet Mapping.
- BOTH must be enriched with:
  - PIC clause
  - datatype
  - length
  - scale
  - start\_position
  - end\_position
  - basetype

```
 Generic behavior:
```

- No hardcoded record names.
- No hardcoded field names.
- No hardcoded business/application field names.
- Debug logging is pattern-based, not field-name based.

Notes:

- Date identification should remain token/pattern based in downstream services.
  - Date tokens such as YEAR, MONTH, DAY, YY, MM, DD, DA, DATE are generic schema concepts, not application-specific field hardcoding.
- """

DEBUG = True

```
FIELD_LINE_PATTERN = re.compile(
 r"^\s*(0[1-9]|[1-4][0-9]|88)\s+([A-Z][A-Z0-9-]*|FILLER)\b",
 re.IGNORECASE,
)
```

```
PIC_OR_USAGE_PATTERN = re.compile(
 r"\b(PIC|PICTURE|DISPLAY|COMP-3|COMP)\b",
 re.IGNORECASE,
)
```

```
def __init__(self):
 self.extractor = TextExtractor()
 self.segmenter = DocumentSegmenter()
 self.field_extractor = FieldExtractor()
 self.picture_enricher = SchemaPictureEnricher()
 self.membership_extractor = OwnerMemberExtractor()
 self.zone_extractor = CobolZoneExtractor()
 self.relationship_resolver = RelationshipResolver()
 self.primary_key_extractor = PrimaryKeyExtractor()
```

```
def build_metadata(
 self,
 pdf_path: str,
) -> SchemaMetadata:
 print("USING MetadataService.build_metadata VERSION GENERIC-DEBUG-NO-FIELD-HARDCODE-2026-07-30")
```

```
 document = self.extractor.extract_document(
 pdf_path,
)
```

```
 sections = self.segmenter.segment(
 document,
)
```

```
 if self.DEBUG:
 print(
 "METADATA_DOCUMENT_DEBUG",
 f"sections_count={len(sections or [])}",
)
```

```
 metadata = SchemaMetadata()
```

```
 for section in sections:
 record = Record(
 name=section.record_name,
)

 record.cobol_zone = self.zone_extractor.extract(
 section.lines,
)
```

```
 physical_fields = self.field_extractor.extract(
 section.lines,
)
```

```
 mapping_fields = self.field_extractor.extract_all(
 section.lines,
 include_filler=True,
)
```

```
 if self.DEBUG:
 print("=" * 100)
 print(f"METADATA DEBUG RECORD: {record.name}")
 print("=" * 100)
 print(f"RAW SECTION LINE COUNT: {len(section.lines or [])}")
 print(f"PHYSICAL FIELD COUNT BEFORE ENRICH: {len(physical_fields or [])}")
 print(f"MAPPING FIELD COUNT BEFORE ENRICH: {len(mapping_fields or [])}")
```

```

 self.print_generic_raw_schema_lines(
 record_name=record.name,
 lines=section.lines,
)

 record.fields = self.picture_enricher.enrich(
 fields=physical_fields,
 lines=section.lines,
 debug_label=f"{record.name} PHYSICAL",
)

 record.mapping_fields = self.picture_enricher.enrich(
 fields=mapping_fields,
 lines=section.lines,
 debug_label=f"{record.name} MAPPING",
)

 record.set_memberships = self.membership_extractor.extract(
 section.record_name,
 section.lines,
)

 record.primary_key = self.primary_key_extractor.extract(
 section.lines,
)

 if self.DEBUG:
 print("=" * 100)
 print(f"FIELDS EXTRACTED FOR {record.name} - PHYSICAL")
 print("=" * 100)

 for field in record.fields or []:
 self.print_field_debug(
 label="PHYSICAL_FIELD_DEBUG",
 field=field,
)

 print("=" * 100)
 print(f"FIELDS EXTRACTED FOR {record.name} - MAPPING")
 print("=" * 100)

 for field in record.mapping_fields or []:
 self.print_field_debug(
 label="MAPPING_FIELD_DEBUG",
 field=field,
)

 print(
 f"MetadataService: {record.name} "
 f"PK={record.primary_key} "
 f"ZONE={record.cobol_zone} "
 f"PHYSICAL_FIELDS={len(record.fields or [])} "
 f"MAPPING_FIELDS={len(record.mapping_fields or [])}"
)

 metadata.records.append(record)

 metadata.relationships = self.relationship_resolver.resolve(
 metadata,
)

 if self.DEBUG:
 print(
 f"Relationships Found: {len(metadata.relationships)}"
)

 return metadata

def print_generic_raw_schema_lines(
 self,
 record_name: str,
 lines,
) -> None:
 """
 Generic raw-line debug.

```

This replaces hardcoded target\_tokens.

Prints:

- COBOL/IDMS data item lines such as 02 FIELD-NAME, 04 FIELD-NAME, etc.
- Lines containing PIC / PICTURE / DISPLAY / COMP / COMP-3.

This is generic and works for any schema listing.

"""

```
print("=" * 100)
print(f"RAW GENERIC SCHEMA LINES FOR {record_name}")
print("=" * 100)

for index, line in enumerate(lines or []):
 value = getattr(line, "text", None)

 if value is None:
 value = str(line)

 text = str(value or "").strip()

 if not text:
 continue

 is_field_line = self.FIELD_LINE_PATTERN.search(text) is not None
 is_pic_or_usage_line = self.PIC_OR_USAGE_PATTERN.search(text) is not None

 if is_field_line or is_pic_or_usage_line:
 print(
 "METADATA_RAW_SCHEMA_LINE",
 f"record={record_name}",
 f"index={index}",
 f"line={repr(text)}",
)

def print_field_debug(
 self,
 label: str,
 field,
) -> None:
 print(
 label,
 "name=", getattr(field, "name", None),
 "level=", getattr(field, "level", None),
 "datatype=", getattr(field, "datatype", None),
 "length=", getattr(field, "length", None),
 "scale=", getattr(field, "scale", None),
 "picture=", getattr(field, "picture", None),
 "start=", getattr(field, "start_position", None),
 "end=", getattr(field, "end_position", None),
 "basetype=", getattr(field, "basetype", None),
 "group=", getattr(field, "is_group", None),
 "has_child=", getattr(field, "has_child", None),
)
```

```
=====
FILE: src\idms_modernizer\services\name_normalizer.py
ENCODING: utf-8
=====
```

```
import re
```

```
class NameNormalizer:
```

```
 @staticmethod
 def normalize(
 name: str | None
) -> str:

 if not name:
 return ""

 normalized = name.strip().upper()
```



```

normalized = normalized.replace("-", "_")
normalized = re.sub(
 r"^[A-Z0-9_]",
 "-",
 normalized
)
normalized = re.sub(
 r"_{+}",
 "_",
 normalized
)

return normalized.strip("_")

```

```

=====
FILE: src\idms_modernizer\services\phase2_conversion_bridge.py
ENCODING: utf-8
=====

```

```

class Phase2ConversionBridge:
 """
 Bridge from Phase 1 outputs to the Phase 2 converter.

 Import is intentionally lazy so Phase 1 UI can still load even if
 Phase 2 package has a missing or broken module.
 """

 def convert(
 self,
 cobol_text: str,
 canonical_json: str,
 phase2_metadata_json: str,
 ddl_text: str,
 idms_schema_text: str | None = None,
 relationship_overrides_json: str | None = None,
 target_program: str | None = None,
 use_ddl: bool = True,
 use_idms_schema: bool = False,
 use_overrides: bool = False
) -> tuple[str, list[str]]:

 if not cobol_text or not cobol_text.strip():
 raise ValueError(
 "COBOL code is required for Phase 2 conversion."
)

 try:
 from idms_db2_converter.services.conversion_service import (
 ConversionService
)

 except Exception as exc:
 raise RuntimeError(
 "Phase 2 converter package could not be loaded. "
 "Check src/idms_db2_converter files. "
 f"Details: {exc}"
) from exc

 if not canonical_json or not canonical_json.strip():
 canonical_json = '{"records": [], "sets": [], "relationships": []}'

 if not phase2_metadata_json:
 phase2_metadata_json = ""

 if not ddl_text:
 ddl_text = ""

 if not idms_schema_text:
 idms_schema_text = ""

 if not relationship_overrides_json:
 relationship_overrides_json = ""

 service = ConversionService()

```

```

converted, validation_messages = service.convert_retrieval(
 cobol_text=cobol_text,
 canonical_json=canonical_json,
 phase2_metadata_json=phase2_metadata_json,
 ddl_text=ddl_text if use_ddl else None,
 idms_schema_text=(
 idms_schema_text
 if use_idms_schema
 else None
),
 relationship_overrides_json=(
 relationship_overrides_json
 if use_overrides and relationship_overrides_json.strip()
 else None
),
 target_program=(
 target_program.strip()
 if target_program and target_program.strip()
 else None
)
)

return converted, validation_messages

```

```

=====
FILE: src\idms_modernizer\services\phase2_metadata_generator.py
ENCODING: utf-8
=====

```

```

import json
import re

from datetime import datetime
from typing import Any

from idms_modernizer.domain.canonical_models import CanonicalSchema
from idms_modernizer.domain.db2_models import DB2Model, DB2Table, DB2Column
from idms_modernizer.domain.schema_models import SchemaMetadata
from idms_modernizer.services.name_normalizer import NameNormalizer

```

```

class Phase2MetadataGenerator:
 VERSION = "1.0"

 DATE_PARTS = {
 "YEAR": {
 "substring_start": 3,
 "substring_length": 2,
 },
 "MONTH": {
 "substring_start": 6,
 "substring_length": 2,
 },
 "DAY": {
 "substring_start": 9,
 "substring_length": 2,
 },
 }

 YEAR_PARTS = {
 "YEAR",
 "YR",
 "Y",
 "YY",
 "YYYY",
 "DY",
 }

 MONTH_PARTS = {
 "MONTH",
 "MON",
 "MO",
 "M",
 "MM",
 "DM",
 }

```

```

}

DAY_PARTS = {
 "DAY",
 "D",
 "DD",
}

def generate_json(
 self,
 canonical_schema: CanonicalSchema,
 db2_model: DB2Model,
 metadata: SchemaMetadata,
) -> str:
 payload = self.generate_payload(
 canonical_schema=canonical_schema,
 db2_model=db2_model,
 metadata=metadata,
)

 return json.dumps(
 payload,
 indent=2,
)

def generate_payload(
 self,
 canonical_schema: CanonicalSchema,
 db2_model: DB2Model,
 metadata: SchemaMetadata,
) -> dict[str, Any]:
 db2_table_lookup = self.build_db2_table_lookup(
 db2_model=db2_model,
)

 canonical_record_lookup = self.build_canonical_record_lookup(
 canonical_schema=canonical_schema,
)

 records_payload = self.build_records_payload(
 db2_model=db2_model,
)

 record_table_map = self.build_record_table_map(
 metadata=metadata,
 db2_table_lookup=db2_table_lookup,
)

 field_map = self.build_field_map(
 metadata=metadata,
 db2_table_lookup=db2_table_lookup,
 record_table_map=record_table_map,
)

 calc_key_map = self.build_calc_key_map(
 canonical_schema=canonical_schema,
 metadata=metadata,
 record_table_map=record_table_map,
)

 relationships_payload = self.build_relationships_payload(
 canonical_schema=canonical_schema,
 db2_table_lookup=db2_table_lookup,
)

 set_ordering_map = self.build_set_ordering_map(
 relationships=relationships_payload,
)

 nullable_fk_map = self.build_nullable_fk_map(
 db2_model=db2_model,
)

 table_key_map = self.build_table_key_map(
 db2_model=db2_model,
)

```

```

date_part_map = self.build_date_part_map(
 metadata=metadata,
 db2_table_lookup=db2_table_lookup,
 record_table_map=record_table_map,
)

navigation_intent = self.build_navigation_intent(
 relationships=relationships_payload,
)

output_semantics = self.build_output_semantics()

validation_messages = self.build_validation_messages(
 canonical_schema=canonical_schema,
 db2_model=db2_model,
 metadata=metadata,
 field_map=field_map,
)

return {
 "version": self.VERSION,
 "generated_at": datetime.utcnow().isoformat() + "Z",
 "records": records_payload,
 "record_table_map": record_table_map,
 "field_map": field_map,
 "calc_key_map": calc_key_map,
 "relationships": relationships_payload,
 "set_ordering_map": set_ordering_map,
 "nullable_fk_map": nullable_fk_map,
 "table_key_map": table_key_map,
 "date_part_map": date_part_map,
 "navigation_intent": navigation_intent,
 "output_semantics": output_semantics,
 "validation_messages": validation_messages,
 "canonical_record_lookup_count": len(canonical_record_lookup),
}

def build_records_payload(
 self,
 db2_model: DB2Model,
) -> list[dict[str, Any]]:
 records_payload: list[dict[str, Any]] = []

 for table in getattr(db2_model, "tables", []) or []:
 fields_payload: list[dict[str, Any]] = []

 for column in getattr(table, "columns", []) or []:
 datatype, length, scale = self.parse_db2_datatype(
 getattr(column, "datatype", ""),
)

 fields_payload.append(
 {
 "name": getattr(column, "name", ""),
 "column": getattr(column, "name", ""),
 "datatype": datatype,
 "length": length,
 "scale": scale,
 "nullable": getattr(column, "nullable", True),
 "primary_key": getattr(column, "primary_key", False),
 "generated": getattr(column, "generated", False),
 "source_kind": getattr(column, "source_kind", ""),
 }
)

 primary_keys = list(getattr(table, "primary_keys", []) or [])

 if not primary_keys and getattr(table, "primary_key", None):
 primary_keys = [table.primary_key]

 records_payload.append(
 {
 "name": getattr(table, "name", ""),
 "table": getattr(table, "name", ""),
 "primary_key": primary_keys[0] if primary_keys else None,
 }
)

```

```

 "primary_keys": primary_keys,
 "fields": fields_payload,
 }
)

return records_payload

def build_table_key_map(
 self,
 db2_model: DB2Model,
) -> dict[str, Any]:
 table_key_map: dict[str, Any] = {}

 for table in getattr(db2_model, "tables", []) or []:
 table_name = NameNormalizer.normalize(getattr(table, "name", "") or "")

 primary_keys = list(getattr(table, "primary_keys", []) or [])

 if not primary_keys and getattr(table, "primary_key", None):
 primary_keys = [table.primary_key]

 foreign_keys = []

 for foreign_key in getattr(table, "foreign_keys", []) or []:
 foreign_keys.append(
 {
 "column_name": getattr(foreign_key, "column_name", "") or "",
 "reference_table": getattr(foreign_key, "reference_table", "") or "",
 "reference_column": getattr(foreign_key, "reference_column", "") or "",
 "set_name": getattr(foreign_key, "set_name", "") or "",
 }
)

 if table_name:
 table_key_map[table_name] = {
 "primary_keys": primary_keys,
 "foreign_keys": foreign_keys,
 }

 return table_key_map

def build_db2_table_lookup(
 self,
 db2_model: DB2Model,
) -> dict[str, DB2Table]:
 lookup: dict[str, DB2Table] = {}

 for table in getattr(db2_model, "tables", []) or []:
 table_name = NameNormalizer.normalize(
 getattr(table, "name", "") or ""
)

 if table_name:
 lookup[table_name] = table

 suffix_removed = self.remove_record_suffix(table_name)

 if suffix_removed:
 lookup[suffix_removed] = table

 return lookup

def build_canonical_record_lookup(
 self,
 canonical_schema: CanonicalSchema,
) -> dict[str, Any]:
 lookup: dict[str, Any] = {}

 for record in getattr(canonical_schema, "records", []) or []:
 record_name = NameNormalizer.normalize(
 getattr(record, "name", "") or ""
)

 if record_name:
 lookup[record_name] = record

```

```

 suffix_removed = self.remove_record_suffix(record_name)

 if suffix_removed:
 lookup[suffix_removed] = record

 return lookup

def build_record_table_map(
 self,
 metadata: SchemaMetadata,
 db2_table_lookup: dict[str, DB2Table],
) -> dict[str, str]:
 record_table_map: dict[str, str] = {}

 for record in getattr(metadata, "records", []) or []:
 record_name = NameNormalizer.normalize(
 getattr(record, "name", "") or "",
)

 if not record_name:
 continue

 table = db2_table_lookup.get(record_name)

 if table is None:
 suffix_removed = self.remove_record_suffix(record_name)
 table = db2_table_lookup.get(suffix_removed)

 record_table_map[record_name] = (
 getattr(table, "name", "") if table is not None else record_name
)

 return record_table_map

def build_field_map(
 self,
 metadata: SchemaMetadata,
 db2_table_lookup: dict[str, DB2Table],
 record_table_map: dict[str, str],
) -> dict[str, dict[str, Any]]:
 field_map: dict[str, dict[str, Any]] = {}

 for record in getattr(metadata, "records", []) or []:
 idms_record_name = NameNormalizer.normalize(
 getattr(record, "name", "") or "",
)

 if not idms_record_name:
 continue

 table_name = record_table_map.get(
 idms_record_name,
 idms_record_name,
)

 table = db2_table_lookup.get(
 NameNormalizer.normalize(table_name),
)

 if table is None:
 continue

 column_lookup = self.build_column_lookup(
 table=table,
)

 source_fields = (
 getattr(record, "mapping_fields", None)
 or getattr(record, "fields", None)
 or []
)

 for field in source_fields:
 legacy_field_name = NameNormalizer.normalize(
 getattr(field, "name", "") or "",
)

```

```

 if not legacy_field_name:
 continue

 column = column_lookup.get(legacy_field_name)

 if column is None:
 suffix_removed = self.remove_record_suffix(legacy_field_name)
 column = column_lookup.get(suffix_removed)

 if column is None:
 continue

 field_map[legacy_field_name] = {
 "record": idms_record_name,
 "table": getattr(table, "name", ""),
 "column": getattr(column, "name", ""),
 "host": self.host_variable_name(
 record=idms_record_name,
 column=getattr(column, "name", ""),
),
 }

 return field_map

def build_column_lookup(
 self,
 table: DB2Table,
) -> dict[str, DB2Column]:
 lookup: dict[str, DB2Column] = {}

 for column in getattr(table, "columns", []) or []:
 column_name = NameNormalizer.normalize(
 getattr(column, "name", "") or "",
)

 if column_name:
 lookup[column_name] = column

 suffix_removed = self.remove_record_suffix(column_name)

 if suffix_removed:
 lookup[suffix_removed] = column

 return lookup

def build_calc_key_map(
 self,
 canonical_schema: CanonicalSchema,
 metadata: SchemaMetadata,
 record_table_map: dict[str, str],
) -> dict[str, dict[str, Any]]:
 calc_key_map: dict[str, dict[str, Any]] = {}

 for record in getattr(metadata, "records", []) or []:
 record_name = NameNormalizer.normalize(
 getattr(record, "name", "") or "",
)

 primary_keys = []

 explicit_primary_keys = getattr(record, "primary_keys", None)

 if explicit_primary_keys:
 if isinstance(explicit_primary_keys, list):
 primary_keys.extend(explicit_primary_keys)
 else:
 primary_keys.append(explicit_primary_keys)

 primary_key = getattr(record, "primary_key", None)

 if primary_key:
 primary_keys.append(primary_key)

 cleaned_primary_keys = []

```

```

 for primary_key_value in primary_keys:
 normalized_primary_key = NameNormalizer.normalize(
 primary_key_value,
)

 if not normalized_primary_key:
 continue

 if normalized_primary_key in cleaned_primary_keys:
 continue

 cleaned_primary_keys.append(normalized_primary_key)

 if not cleaned_primary_keys:
 continue

 calc_key_map[record_name] = {
 "record": record_name,
 "table": record_table_map.get(record_name, record_name),
 "primary_key": cleaned_primary_keys[0],
 "primary_keys": cleaned_primary_keys,
 }

 return calc_key_map

def build_relationships_payload(
 self,
 canonical_schema: CanonicalSchema,
 db2_table_lookup: dict[str, DB2Table],
) -> list[dict[str, Any]]:
 relationships_payload: list[dict[str, Any]] = []

 for relationship in getattr(canonical_schema, "relationships", []) or []:
 parent_record = NameNormalizer.normalize(
 getattr(relationship, "parent_record", None)
 or getattr(relationship, "owner_record", None)
 or "",
)

 child_record = NameNormalizer.normalize(
 getattr(relationship, "child_record", None)
 or getattr(relationship, "member_record", None)
 or "",
)

 set_name = NameNormalizer.normalize(
 getattr(relationship, "set_name", None)
 or getattr(relationship, "name", None)
 or "",
)

 parent_table = db2_table_lookup.get(parent_record)
 child_table = db2_table_lookup.get(child_record)

 parent_keys = []
 child_fks = []

 if parent_table is not None:
 parent_keys = list(getattr(parent_table, "primary_keys", []) or [])

 if not parent_keys and getattr(parent_table, "primary_key", None):
 parent_keys = [parent_table.primary_key]

 if child_table is not None:
 for foreign_key in getattr(child_table, "foreign_keys", []) or []:
 fk_set_name = NameNormalizer.normalize(
 getattr(foreign_key, "set_name", "") or "",
)

 if set_name and fk_set_name and fk_set_name != set_name:
 continue

 child_fks.append(
 getattr(foreign_key, "column_name", "") or "",
)

```



```

 relationships_payload.append(
 {
 "set_name": set_name,
 "parent_record": parent_record,
 "child_record": child_record,
 "owner_record": parent_record,
 "member_record": child_record,
 "parent_table": getattr(parent_table, "name", "") if parent_table else "",
 "child_table": getattr(child_table, "name", "") if child_table else "",
 "parent_key": parent_keys[0] if parent_keys else None,
 "parent_keys": parent_keys,
 "child_fk": child_fks[0] if child_fks else None,
 "child_fks": child_fks,
 "order_by": getattr(relationship, "order_by", []) or [],
 }
)
)

 return relationships_payload

def build_set_ordering_map(
 self,
 relationships: list[dict[str, Any]],
) -> dict[str, dict[str, Any]]:
 set_ordering_map: dict[str, dict[str, Any]] = {}

 for relationship in relationships:
 set_name = relationship.get("set_name") or ""

 if not set_name:
 continue

 set_ordering_map[set_name] = {
 "parent_record": relationship.get("parent_record") or "",
 "child_record": relationship.get("child_record") or "",
 "parent_key": relationship.get("parent_key"),
 "parent_keys": relationship.get("parent_keys") or [],
 "child_fk": relationship.get("child_fk"),
 "child_fks": relationship.get("child_fks") or [],
 "order_by": relationship.get("order_by") or [],
 }

 return set_ordering_map

def build_nullable_fk_map(
 self,
 db2_model: DB2Model,
) -> dict[str, Any]:
 nullable_fk_map: dict[str, Any] = {}

 for table in getattr(db2_model, "tables", []) or []:
 column_lookup = {
 getattr(column, "name", ""): column
 for column in getattr(table, "columns", []) or []
 }

 for foreign_key in getattr(table, "foreign_keys", []) or []:
 fk_column_name = getattr(foreign_key, "column_name", "")
 fk_column = column_lookup.get(fk_column_name)

 key = f"{getattr(table, 'name', '')}.{fk_column_name}"

 nullable_fk_map[key] = {
 "nullable": (
 getattr(fk_column, "nullable", True)
 if fk_column is not None
 else True
),
 "set_name": getattr(foreign_key, "set_name", "") or "",
 "reference_table": getattr(foreign_key, "reference_table", "") or "",
 "reference_column": getattr(foreign_key, "reference_column", "") or "",
 }

 return nullable_fk_map

def build_date_part_map(
 self,

```

```

metadata: SchemaMetadata,
db2_table_lookup: dict[str, DB2Table],
record_table_map: dict[str, str],
) -> dict[str, dict[str, Any]]:
 date_part_map: dict[str, dict[str, Any]] = {}

 for record in getattr(metadata, "records", []) or []:
 idms_record_name = NameNormalizer.normalize(
 getattr(record, "name", "") or "",
)

 if not idms_record_name:
 continue

 table_name = record_table_map.get(
 idms_record_name,
 idms_record_name,
)

 table = db2_table_lookup.get(
 NameNormalizer.normalize(table_name),
)

 if table is None:
 continue

 date_columns = {
 NameNormalizer.normalize(getattr(column, "name", "") or ""): column
 for column in getattr(table, "columns", []) or []
 if str(getattr(column, "datatype", "")).upper() == "DATE"
 }

 source_fields = (
 getattr(record, "mapping_fields", None)
 or getattr(record, "fields", None)
 or []
)

 for field in source_fields:
 legacy_field_name = NameNormalizer.normalize(
 getattr(field, "name", "") or "",
)

 parsed = self.parse_date_part(
 field_name=legacy_field_name,
)

 if parsed is None:
 continue

 part = parsed["part"]
 date_key = parsed["date_key"]

 date_column = date_columns.get(date_key)

 if date_column is None:
 suffix_removed = self.remove_record_suffix(date_key)
 date_column = date_columns.get(suffix_removed)

 if date_column is None:
 continue

 date_part_map[legacy_field_name] = {
 "record": idms_record_name,
 "table": getattr(table, "name", ""),
 "column": getattr(date_column, "name", ""),
 "host": self.host_variable_name(
 record=idms_record_name,
 column=getattr(date_column, "name", ""),
),
 "substring_start": self.DATE_PARTS[part]["substring_start"],
 "substring_length": self.DATE_PARTS[part]["substring_length"],
 "part": part,
 }

 return date_part_map

```

```

def parse_date_part(
 self,
 field_name: str,
) -> dict[str, Any] | None:
 candidates = self.parse_date_part_candidates(
 field_name=field_name,
)

 if not candidates:
 return None

 return candidates[0]

def parse_date_part_candidates(
 self,
 field_name: str,
) -> list[dict[str, Any]]:
 normalized = NameNormalizer.normalize(field_name or "")

 if not normalized:
 return []

 tokens = [
 token
 for token in re.split(r"[\s_]+", normalized)
 if token
]

 candidates = []

 for index, token in enumerate(tokens):
 part = self.date_part_type(
 token=token,
 tokens=tokens,
)

 if part is None:
 continue

 date_tokens = tokens.copy()
 date_tokens[index] = "DATE"

 date_key = "_".join(date_tokens)

 candidates.append(
 {
 "date_key": date_key,
 "part": part,
 "tokens": date_tokens,
 }
)

 return candidates

def date_part_type(
 self,
 token: str,
 tokens: list[str],
) -> str | None:
 token = token.upper()

 has_dy_dm_dd = (
 "DY" in tokens
 and "DM" in tokens
 and "DD" in tokens
)

 if token in {"YEAR", "YR", "Y", "YY", "YYYY"}:
 return "YEAR"

 if token in {"MONTH", "MON", "MO", "M", "MM", "DM"}:
 return "MONTH"

 if token in {"DAY", "D", "DD"}:
 return "DAY"

```

```

 if token == "DY":
 if has_dy_dm_dd:
 return "YEAR"

 return "DAY"

 return None

def build_navigation_intent(
 self,
 relationships: list[dict[str, Any]],
) -> dict[str, Any]:
 navigation_intent: dict[str, Any] = {}

 for relationship in relationships:
 set_name = relationship.get("set_name") or ""

 if not set_name:
 continue

 navigation_intent[set_name] = {
 "access_pattern": "SET_NAVIGATION",
 "parent_record": relationship.get("parent_record"),
 "child_record": relationship.get("child_record"),
 "parent_key": relationship.get("parent_key"),
 "parent_keys": relationship.get("parent_keys") or [],
 "child_fk": relationship.get("child_fk"),
 "child_fks": relationship.get("child_fks") or [],
 "order_by": relationship.get("order_by") or [],
 }

 return navigation_intent

def build_output_semantics(
 self,
) -> dict[str, Any]:
 return {
 "generated_by": "idms-db2-modernizer-phase1",
 "usage": "IDMS retrieval COBOL to DB2 embedded SQL conversion",
 "physical_types_source": "DB2_DDL",
 "logical_mapping_source": "PHASE1_CANONICAL_METADATA",
 "db2_key_values": ["PK", "FK", "PK/FK"],
 "generated_primary_key_rule": "ID_RECORD_<record_name>",
 "generated_primary_key_datatype": "CHAR(20)",
 "foreign_key_rule": "Use SET relationship and owner primary key columns only.",
 "character_rule": "CHAR by default; VARCHAR only when length equals 100.",
 "numeric_rule": "Numeric COBOL PIC maps to DECIMAL.",
 "date_rule": "Date part recognition remains generic for YEAR, YR, Y, YY, YYYY, DY, MONTH, MON, MO, M, MM, D
M, DAY, D, DD.",
 }

def build_validation_messages(
 self,
 canonical_schema: CanonicalSchema,
 db2_model: DB2Model,
 metadata: SchemaMetadata,
 field_map: dict[str, dict[str, Any]],
) -> list[str]:
 messages: list[str] = []

 if not getattr(canonical_schema, "records", []) or []:
 messages.append("No canonical records found.")

 if not getattr(db2_model, "tables", []) or []:
 messages.append("No DB2 tables found.")

 if not getattr(metadata, "records", []) or []:
 messages.append("No IDMS metadata records found.")

 if not field_map:
 messages.append("No field map entries generated.")

 for table in getattr(db2_model, "tables", []) or []:
 primary_keys = list(getattr(table, "primary_keys", []) or [])

```

```

 if not primary_keys and getattr(table, "primary_key", None):
 primary_keys = [table.primary_key]

 if not primary_keys:
 messages.append(f"Table {table.name} has no primary key.")
 continue

 column_names = {
 NameNormalizer.normalize(getattr(column, "name", "") or "")
 for column in getattr(table, "columns", []) or []
 }

 for primary_key in primary_keys:
 if NameNormalizer.normalize(primary_key) not in column_names:
 messages.append(
 f"Table {table.name} primary key {primary_key} is not present as a DB2 column."
)

 return messages

def parse_db2_datatype(
 self,
 datatype: str,
) -> tuple[str, int | None, int | None]:
 value = (datatype or "").strip().upper()

 decimal_match = re.match(
 r"^(DECIMAL|NUMERIC)$((\d+)(?:, \d*(\d+))?)?$",
 value,
)

 if decimal_match:
 return (
 "DECIMAL",
 int(decimal_match.group(2)),
 int(decimal_match.group(3) or 0),
)

 char_match = re.match(
 r"^(VARCHAR|CHAR|CHARACTER)$((\d+))$",
 value,
)

 if char_match:
 return (
 "VARCHAR" if char_match.group(1) == "VARCHAR" else "CHAR",
 int(char_match.group(2)),
 None,
)

 if value == "DATE":
 return "DATE", None, None

 if value == "TIMESTAMP":
 return "TIMESTAMP", None, None

 return value or "CHAR", None, None

def host_variable_name(
 self,
 record: str,
 column: str,
) -> str:
 record_name = NameNormalizer.normalize(record or "")
 column_name = NameNormalizer.normalize(column or "")
 return f"HV-{{record_name}}-{{column_name}}"

def remove_record_suffix(
 self,
 value: str,
) -> str:
 text = NameNormalizer.normalize(value or "")

 if not text:
 return ""

```

```
text = text.replace(" ", "_")
```

```
return re.sub(
 r"_[0-9]{4}$",
 "",
 text,
)
```

```
=====
FILE: src\idms_modernizer\services\relationship_resolver.py
ENCODING: utf-8
=====
```

```
from collections import defaultdict
```

```
from idms_modernizer.domain.relationship_models import (
 Relationship,
)
```

```
class RelationshipResolver:
```

```
 """
 Resolves IDMS SET owner/member relationships from record set memberships.
```

```
 Generic behavior only:
```

- No hardcoded SET names.
- No hardcoded record names.
- OWNER and MEMBER are read from schema listing memberships.

```
 """
```

```
 def resolve(
 self,
 metadata,
) -> list[Relationship]:
 owner_map: dict[str, list[str]] = defaultdict(list)
 member_map: dict[str, list[str]] = defaultdict(list)

 for record in getattr(metadata, "records", []) or []:
 record_name = getattr(record, "name", "") or ""

 if not record_name:
 continue

 for membership in getattr(record, "set_memberships", []) or []:
 set_name = (
 getattr(membership, "set_name", None)
 or getattr(membership, "name", None)
 or ""
)

 role = (
 getattr(membership, "role", None)
 or getattr(membership, "relation_type", None)
 or getattr(membership, "type", None)
 or ""
)

 set_name = str(set_name or "").strip().upper()
 role = str(role or "").strip().upper()

 if not set_name:
 continue

 if not role:
 continue

 if set_name == "CALC":
 continue

 if role == "OWNER":
 if record_name not in owner_map[set_name]:
 owner_map[set_name].append(record_name)

 elif role == "MEMBER":
 if record_name not in member_map[set_name]:
```

```

 member_map[set_name].append(record_name)

relationships: list[Relationship] = []

all_sets = set(owner_map.keys()) | set(member_map.keys())

for set_name in sorted(all_sets):
 owners = owner_map.get(set_name, [])
 members = member_map.get(set_name, [])

 if not owners:
 continue

 if not members:
 continue

 for owner in owners:
 for member in members:
 if not owner or not member:
 continue

 if owner == member:
 continue

 relationships.append(
 Relationship(
 set_name=set_name,
 owner_record=owner,
 member_record=member,
 cardinality="1:N",
)
)

metadata.relationships = relationships

return relationships

```

```

=====
FILE: src\idms_modernizer\services\schema_picture_enricher.py
ENCODING: utf-8
=====

```

```

import re

from idms_modernizer.domain.schema_models import DataField
from idms_modernizer.services.name_normalizer import NameNormalizer

print("LOADED SchemaPictureEnricher VERSION GENERIC-PIC-PARENS-V-COMP3-FIX-2026-07-30")

class SchemaPictureEnricher:
 """
 Enriches DataField objects using schema listing lines.

 Critical rules:
 - IDMS PIC Clause must come from schema PICTURE, not byte length.
 - PIC S9(13)V9(2) must remain PIC S9(13)V9(2).
 - PIC S9(13)V9(2) COMP-3 must remain PIC S9(13)V9(2) COMP-3.
 - Do not convert PIC S9(13)V9(2) to PIC S9(8).
 - Do not convert PIC 9(8) COMP-3 to PIC 9(5) COMP-3.
 - Storage length remains byte length.
 - Numeric logical precision comes from PIC.

 Generic behavior:
 - No hardcoded record names.
 - No hardcoded field names.
 - No hardcoded application-specific debug target list.
 - Debug is controlled by DEBUG / DEBUG_VERBOSE only.
 """

 DEBUG = True
 DEBUG_VERBOSE = False

 FIELD_START_PATTERN = re.compile(
 r"^\s*(?P<level>0[1-9]|[1-4][0-9]|88)\s+"
)

```

```

r"(?P<name>[A-Z][A-Z0-9-]*|FILLER)\b"
r"(?P<rest>.*)$",
re.IGNORECASE,
)

USAGE_PATTERN = re.compile(
r"\b(?:USAGE\s+IS\s+)?(?:P<usage>DISPLAY|COMP-3|COMP)\b",
re.IGNORECASE,
)

START_LENGTH_PATTERN = re.compile(
r"\b(?:P<start>[0-9]+\s+(?:P<length>[0-9]+\s*)$",
re.IGNORECASE,
)

COMPACT_PIC_PATTERNS = [
re.compile(r"S?9[()][0-9]+[()V9[()][0-9]+[()]", re.IGNORECASE),
re.compile(r"S?9[()][0-9]+[()V90]+", re.IGNORECASE),
re.compile(r"S?[90]+V9[()][0-9]+[()]", re.IGNORECASE),
re.compile(r"S?[90]+V[90]+", re.IGNORECASE),
re.compile(r"S?9[()][0-9]+[()]", re.IGNORECASE),
re.compile(r"S?[90]+", re.IGNORECASE),
re.compile(r"X[()][0-9]+[()]", re.IGNORECASE),
re.compile(r"X+", re.IGNORECASE),
]

DATE_NAME_TOKENS = {
"DA",
"DATE",
"DT",
"DTE",
"YYMMDD",
"YYYYMMDD",
"YMD",
}

YEAR_PARTS = {
"YEAR",
"YR",
"Y",
"YY",
"YYYY",
"DY",
}

MONTH_PARTS = {
"MONTH",
"MON",
"MO",
"M",
"MM",
"DM",
}

DAY_PARTS = {
"DAY",
"D",
"DD",
}

def enrich(
self,
fields: list[DataField],
lines: list[str],
debug_label: str = "",
) -> list[DataField]:
if self.DEBUG:
print(
"USING SchemaPictureEnricher.enrich VERSION GENERIC-PIC-PARENS-V-COMP3-FIX-2026-07-30",
f"debug_label={debug_label}",
)

normalized_lines = self.normalize_lines(
lines=lines,
)

```



```

if self.DEBUG:
 print(
 "SCHEMA_ENRICH_DEBUG_LINES",
 f"debug_label={debug_label}",
 f"line_count={len(normalized_lines)}",
)

field_blocks = self.build_field_blocks(
 normalized_lines=normalized_lines,
 debug_label=debug_label,
)

enriched_fields: list[DataField] = []

for field in fields or []:
 field_name = getattr(field, "name", "") or ""

 block = self.find_block_for_field(
 field_name=field_name,
 field_blocks=field_blocks,
)

 if not block:
 if self.DEBUG:
 print(
 "SCHEMA_ENRICH_NO_BLOCK",
 f"debug_label={debug_label}",
 f"field={repr(field_name)}",
)

 enriched_fields.append(
 self.copy_field_with_defaults(
 field=field,
)
)
 continue

 enriched_fields.append(
 self.enrich_field(
 field=field,
 block=block,
 debug_label=debug_label,
)
)

enriched_fields = self.enrich_group_positions_from_children(
 fields=enriched_fields,
 debug_label=debug_label,
)

return enriched_fields

def normalize_lines(
 self,
 lines: list[str],
) -> list[str]:
 result: list[str] = []

 for line in lines or []:
 if line is None:
 continue

 value = getattr(line, "text", None)

 if value is None:
 value = str(line)

 value = str(value)
 value = value.replace("\t", " ")
 value = value.replace("\u00a0", " ")
 value = value.replace("PICTURE .", "PICTURE")
 value = value.replace("PIC .", "PIC")
 value = re.sub(r"<[^\>]+>", " ", value)
 value = re.sub(r"\s+", " ", value).strip()

 if value:

```

```

 result.append(value)

 return result

def build_field_blocks(
 self,
 normalized_lines: list[str],
 debug_label: str = "",
) -> dict[str, str]:
 starts: list[tuple[int, str]] = []

 for index, line in enumerate(normalized_lines or []):
 match = self.FIELD_START_PATTERN.match(line)

 if not match:
 continue

 field_name = match.group("name") or ""

 starts.append(
 (
 index,
 field_name.upper(),
)
)

 if self.DEBUG:
 print(
 "SCHEMA_BLOCK_STARTS_DEBUG",
 f"debug_label={debug_label}",
 f"starts_count={len(starts)}",
 f"starts={starts[:80]}",
)

 blocks: dict[str, str] = {}

 for index, item in enumerate(starts):
 start_index, field_name = item

 if index + 1 < len(starts):
 end_index = starts[index + 1][0]
 else:
 end_index = len(normalized_lines)

 block = " ".join(
 normalized_lines[start_index:end_index],
)

 normalized_field_name = NameNormalizer.normalize(
 field_name,
)

 if normalized_field_name:
 blocks[normalized_field_name] = block

 suffix_removed = self.remove_record_suffix(
 value=normalized_field_name,
)

 if suffix_removed:
 blocks.setdefault(
 suffix_removed,
 block,
)

 if self.DEBUG_VERBOSE:
 print(
 "SCHEMA_BLOCK_DEBUG",
 f"debug_label={debug_label}",
 f"field={repr(normalized_field_name)}",
 f"block={repr(block)}",
)

 return blocks

def find_block_for_field(

```

```

 self,
 field_name: str,
 field_blocks: dict[str, str],
) -> str:
 normalized_name = NameNormalizer.normalize(
 field_name or "",
)

 if not normalized_name:
 return ""

 if normalized_name in field_blocks:
 return field_blocks[normalized_name]

 suffix_removed = self.remove_record_suffix(
 value=normalized_name,
)

 if suffix_removed in field_blocks:
 return field_blocks[suffix_removed]

 for block_name, block in field_blocks.items():
 if self.remove_record_suffix(block_name) == suffix_removed:
 return block

 return ""

def enrich_field(
 self,
 field: DataField,
 block: str,
 debug_label: str = "",
) -> DataField:
 field_name = getattr(field, "name", "") or ""

 if not block:
 return self.copy_field_with_defaults(
 field=field,
)

 parsed_line = self.parse_schema_block(
 block=block,
 field_name=field_name,
 debug_label=debug_label,
)

 usage = parsed_line["usage"]
 start_position = parsed_line["start_position"]
 storage_length = parsed_line["storage_length"]
 picture_core = parsed_line["picture_core"]

 is_group = bool(
 getattr(field, "has_child", False)
 or getattr(field, "is_group", False)
)

 if is_group:
 return self.make_field(
 source=field,
 datatype=getattr(field, "datatype", None),
 length=storage_length or getattr(field, "length", None),
 scale=getattr(field, "scale", None),
 picture=None,
 start_position=start_position or getattr(field, "start_position", None),
 end_position=self.calculate_end_position(
 start_position=start_position,
 storage_length=storage_length,
 fallback=getattr(field, "end_position", None),
),
 basetype=getattr(field, "basetype", None),
)

 rendered_picture = self.render_cobol_pic_clause(
 picture=picture_core,
 usage=usage,
 storage_length=storage_length,

```

```

)

datatype, logical_length, scale = self.derive_type_from_picture(
 picture=rendered_picture,
 usage=usage,
 storage_length=storage_length,
 fallback_datatype=getattr(field, "datatype", None),
)

if self.is_date_field(
 field=field,
 picture=rendered_picture,
 storage_length=storage_length,
 datatype=datatype,
):
 datatype = "DATE"
 scale = None

end_position = self.calculate_end_position(
 start_position=start_position,
 storage_length=storage_length,
 fallback=getattr(field, "end_position", None),
)

actual_length = storage_length

if actual_length is None:
 actual_length = logical_length

if self.DEBUG_VERBOSE:
 print(
 "SCHEMA_ENRICH_RESULT",
 f"debug_label={debug_label}",
 f"field={repr(field_name)}",
 f"block={repr(block)}",
 f"usage={repr(usage)}",
 f"picture_core={repr(picture_core)}",
 f"rendered_picture={repr(rendered_picture)}",
 f"datatype={repr(datatype)}",
 f"logical_length={logical_length}",
 f"storage_length={storage_length}",
 f"actual_length={actual_length}",
 f"scale={scale}",
 f"start={start_position}",
 f"end={end_position}",
)

return self.make_field(
 source=field,
 datatype=datatype,
 length=actual_length,
 scale=scale,
 picture=rendered_picture,
 start_position=start_position,
 end_position=end_position,
 basetype=self.basetype_for_datatype(
 datatype=datatype,
),
)

def parse_schema_block(
 self,
 block: str,
 field_name: str,
 debug_label: str = "",
) -> dict:
 text = str(block or "").strip()

 usage = self.extract_usage(
 block=text,
)

 start_position, storage_length = self.extract_start_and_length(
 block=text,
)

```

```

body_without_positions = self.remove_trailing_start_and_length(
 value=text,
)

rest = self.extract_rest_after_level_and_name(
 block=body_without_positions,
)

picture_area = self.remove_usage_words(
 value=rest,
)

picture_area = self.remove_schema_noise(
 value=picture_area,
)

picture_core = self.extract_picture_core(
 value=picture_area,
 field_name=field_name,
 debug_label=debug_label,
)

if self.DEBUG_VERBOSE:
 print(
 "SCHEMA_PARSE_DEBUG",
 f"debug_label={debug_label}",
 f"field={repr(field_name)}",
 f"block={repr(block)}",
 f"usage={repr(usage)}",
 f"start={start_position}",
 f"length={storage_length}",
 f"rest={repr(rest)}",
 f"picture_area={repr(picture_area)}",
 f"picture_core={repr(picture_core)}",
)

return {
 "usage": usage,
 "start_position": start_position,
 "storage_length": storage_length,
 "picture_core": picture_core,
}

def extract_rest_after_level_and_name(
 self,
 block: str,
) -> str:
 match = self.FIELD_START_PATTERN.match(
 block or ""
)

 if not match:
 return str(block or "")

 return str(match.group("rest") or "").strip()

def extract_usage(
 self,
 block: str,
) -> str:
 upper = str(block or "").upper()

 if "COMP-3" in upper:
 return "COMP-3"

 if re.search(r"\bCOMP\b", upper):
 return "COMP"

 usage_match = self.USAGE_PATTERN.search(
 block or ""
)

 if usage_match:
 return usage_match.group("usage").upper()

 return "DISPLAY"

```

```

def extract_start_and_length(
 self,
 block: str,
) -> tuple[int | None, int | None]:
 match = self.START_LENGTH_PATTERN.search(
 block or ""
)

 if not match:
 return None, None

 return int(match.group("start")), int(match.group("length"))

def remove_trailing_start_and_length(
 self,
 value: str,
) -> str:
 return re.sub(
 r"\b[0-9]+\s+[0-9]+\s*$",
 "",
 str(value or ""),
).strip()

def remove_usage_words(
 self,
 value: str,
) -> str:
 text = str(value or "")

 text = re.sub(r"\bUSAGE\s+IS\s+COMP-3\b", " ", text, flags=re.IGNORECASE)
 text = re.sub(r"\bUSAGE\s+IS\s+COMP\b", " ", text, flags=re.IGNORECASE)
 text = re.sub(r"\bUSAGE\s+IS\s+DISPLAY\b", " ", text, flags=re.IGNORECASE)
 text = re.sub(r"\bCOMP-3\b", " ", text, flags=re.IGNORECASE)
 text = re.sub(r"\bCOMP\b", " ", text, flags=re.IGNORECASE)
 text = re.sub(r"\bDISPLAY\b", " ", text, flags=re.IGNORECASE)

 return re.sub(r"\s+", " ", text).strip()

def remove_schema_noise(
 self,
 value: str,
) -> str:
 text = str(value or "")

 text = re.sub(r"\bOCCURS\b.*$", " ", text, flags=re.IGNORECASE)
 text = re.sub(r"\bREDEFINES\b.*$", " ", text, flags=re.IGNORECASE)
 text = text.replace(".", " ")
 text = text.replace("\u00a0", " ")
 text = text.replace("\t", " ")

 return re.sub(r"\s+", " ", text).strip()

def extract_picture_core(
 self,
 value: str,
 field_name: str = "",
 debug_label: str = "",
) -> str | None:
 original = str(value or "").upper()

 compact = re.sub(r"\s+", "", original)
 compact = compact.replace("PICTURE", "")
 compact = compact.replace("PIC", "")
 compact = compact.replace(".", "")

 candidates: list[tuple[int, int, str]] = []

 for pattern in self.COMPACT_PIC_PATTERNS:
 for match in pattern.finditer(compact):
 raw = match.group(0)

 core = self.clean_picture_core(
 value=raw,
)

```

```

 if not core:
 continue

 score = self.picture_score(
 core=core,
)

 candidates.append(
 (
 score,
 match.start(),
 core,
)
)

 if self.DEBUG_VERBOSE:
 print(
 "PIC_EXTRACT_DEBUG_INPUT",
 f"debug_label={debug_label}",
 f"field={repr(field_name)}",
 f"value={repr(value)}",
 f"compact={repr(compact)}",
 f"patterns=[[pattern.pattern for pattern in self.COMPACT_PIC_PATTERNS]]",
 f"candidates_before_sort={candidates}",
)

 if not candidates:
 return None

 candidates.sort(
 key=lambda item: (item[0], item[1]),
)

 selected = candidates[-1][2]

 if self.DEBUG_VERBOSE:
 print(
 "PIC_EXTRACT_DEBUG_RESULT",
 f"debug_label={debug_label}",
 f"field={repr(field_name)}",
 f"candidates_after_sort={candidates}",
 f"selected={repr(selected)}",
)

 return selected

def picture_score(
 self,
 core: str,
) -> int:
 text = str(core or "").upper()

 score = 0

 if "V" in text:
 score += 1000

 if "(" in text and ")" in text:
 score += 100

 if text.startswith("S"):
 score += 10

 if text.startswith("X"):
 score += 5

 score += len(text)

 return score

def clean_picture_core(
 self,
 value: str | None,
) -> str | None:
 if value is None:
 return None

```

```

text = str(value).upper()
text = text.replace("PICTURE", "")
text = text.replace("PIC", "")
text = text.replace(".", "")
text = text.replace("\u00a0", " ")
text = text.replace("\t", " ")
text = re.sub(r"\s+", "", text)

return text.strip() or None

def render_cobol_pic_clause(
 self,
 picture: str | None,
 usage: str,
 storage_length: int | None,
) -> str | None:
 if not picture:
 return None

 normalized_picture = self.normalize_picture_preserving_v(
 picture=picture,
 storage_length=storage_length,
)

 if not normalized_picture:
 return None

 usage_upper = str(usage or "DISPLAY").upper()

 if usage_upper in {"COMP", "COMP-3"}:
 if usage_upper not in normalized_picture.upper():
 normalized_picture = f"{normalized_picture} {usage_upper}"

 if normalized_picture.upper().startswith("PIC "):
 return normalized_picture

 return f"PIC {normalized_picture}"

def normalize_picture_preserving_v(
 self,
 picture: str | None,
 storage_length: int | None = None,
) -> str | None:
 if not picture:
 return None

 core = self.picture_core(
 picture,
)

 if not core:
 return None

 if "V" in core:
 before_v, after_v = core.split("V", 1)

 before_v_normalized = self.normalize_9_part(
 part=before_v,
 storage_length=None,
)

 after_v_normalized = self.normalize_9_part(
 part=after_v,
 storage_length=None,
)

 return f"{before_v_normalized}V{after_v_normalized}"

 if core.startswith("X"):
 return self.normalize_x_part(
 part=core,
 storage_length=storage_length,
)

 return self.normalize_9_part(

```



```

 part=core,
 storage_length=storage_length,
)

def normalize_x_part(
 self,
 part: str,
 storage_length: int | None = None,
) -> str:
 text = str(part or "").upper()

 if text.startswith("X(") and text.endswith(")"):
 return text

 if text and set(text) == {"X"}:
 if len(text) == 1 and storage_length and int(storage_length) > 1:
 return f"X({int(storage_length)})"

 if len(text) == 1:
 return "X"

 return f"X({len(text)})"

 return text

def normalize_9_part(
 self,
 part: str,
 storage_length: int | None = None,
) -> str:
 text = str(part or "").upper()
 signed = False

 if text.startswith("S"):
 signed = True
 text = text[1:]

 if text.startswith("9(") and text.endswith(")"):
 return f"{'S' if signed else ''}{text}"

 count = self.count_9_digits(
 value=text,
)

 if count <= 0:
 return f"{'S' if signed else ''}{text}"

 if count == 1 and storage_length and int(storage_length) > 1:
 return f"{'S' if signed else ''}9({int(storage_length)})"

 if count == 1:
 return f"{'S' if signed else ''}9"

 return f"{'S' if signed else ''}9({count})"

def derive_type_from_picture(
 self,
 picture: str | None,
 usage: str,
 storage_length: int | None,
 fallback_datatype: str | None = None,
) -> tuple[str | None, int | None, int | None]:
 if not picture:
 return fallback_datatype, storage_length, None

 core = self.picture_core(
 picture=picture,
)

 if not core:
 return fallback_datatype, storage_length, None

 if self.picture_is_character(core):
 length = self.character_length(
 picture=core,
)

```

```

 return "CHAR", length, None

 if self.picture_is_decimal(core):
 precision, scale = self.decimal_precision_scale(
 picture=core,
)

 return "DECIMAL", precision, scale

 if self.picture_is_numeric(core):
 precision = self.numeric_precision(
 picture=core,
)

 return "DECIMAL", precision, 0

 return fallback_datatype, storage_length, None

def picture_core(
 self,
 picture: str | None,
) -> str:
 text = str(picture or "").upper()
 text = text.replace("PICTURE", "")
 text = text.replace("PIC", "")
 text = text.replace("COMP-3", "")
 text = re.sub(r"\bCOMP\b", "", text)
 text = text.replace("DISPLAY", "")
 text = text.replace("USAGE", "")
 text = text.replace("IS", "")
 text = text.replace(".", "")
 text = re.sub(r"\s+", "", text)

 return text.strip()

def picture_is_character(
 self,
 picture: str,
) -> bool:
 text = str(picture or "").upper()

 if text.startswith("X(") and text.endswith(")"):
 return self.extract_parenthesized_int(text) is not None

 return bool(text) and set(text) == {"X"}

def character_length(
 self,
 picture: str,
) -> int:
 text = str(picture or "").upper()

 if text.startswith("X(") and text.endswith(")"):
 parsed = self.extract_parenthesized_int(text)

 if parsed is not None:
 return parsed

 return text.count("X")

def picture_is_numeric(
 self,
 picture: str,
) -> bool:
 text = str(picture or "").upper()

 if text.startswith("S"):
 text = text[1:]

 return "9" in text and "V" not in text

def picture_is_decimal(
 self,
 picture: str,
) -> bool:

```

```

text = str(picture or "").upper()

if text.startswith("S"):
 text = text[1:]

return "V" in text and "9" in text

def decimal_precision_scale(
 self,
 picture: str,
) -> tuple[int, int]:
 text = str(picture or "").upper()

 if text.startswith("S"):
 text = text[1:]

 before_v, after_v = text.split("V", 1)

 integer_digits = self.count_9_digits(
 value=before_v,
)

 decimal_digits = self.count_9_digits(
 value=after_v,
)

 return integer_digits + decimal_digits, decimal_digits

def numeric_precision(
 self,
 picture: str,
) -> int:
 text = str(picture or "").upper()

 if text.startswith("S"):
 text = text[1:]

 return self.count_9_digits(
 value=text,
)

def count_9_digits(
 self,
 value: str,
) -> int:
 text = str(value or "").upper()

 if text.startswith("S"):
 text = text[1:]

 total = 0
 index = 0

 while index < len(text):
 if text[index] not in {"9", "0"}:
 index += 1
 continue

 if index + 1 < len(text) and text[index + 1] == "(":
 close_index = text.find(")", index + 2)

 if close_index != -1:
 number_text = text[index + 2:close_index]

 if number_text.isdigit():
 total += int(number_text)
 index = close_index + 1
 continue

 total += 1
 index += 1

 return total

def extract_parenthesized_int(
 self,

```

```

 value: str,
) -> int | None:
 text = str(value or "")
 open_index = text.find("(")

 if open_index == -1:
 return None

 close_index = text.find(")", open_index + 1)

 if close_index == -1:
 return None

 number_text = text[open_index + 1:close_index].strip()

 if not number_text.isdigit():
 return None

 return int(number_text)

def calculate_end_position(
 self,
 start_position: int | None,
 storage_length: int | None,
 fallback=None,
) -> int | None:
 try:
 if start_position is not None and storage_length is not None:
 return int(start_position) + int(storage_length) - 1
 except Exception:
 pass

 try:
 if fallback is not None:
 return int(fallback)
 except Exception:
 pass

 return None

def is_date_field(
 self,
 field: DataField,
 picture: str | None,
 storage_length: int | None,
 datatype: str | None,
) -> bool:
 datatype_upper = str(datatype or "").upper()

 if datatype_upper == "DATE":
 return True

 field_name = NameNormalizer.normalize(
 getattr(field, "name", "") or "",
)

 parts = [
 part
 for part in field_name.replace("-", " ").replace("_", " ").split()
 if part
]

 if "DATE" in parts or "DA" in parts:
 if storage_length == 8:
 return True

 core = self.picture_core(
 picture=picture,
)

 if core in {"9(8)", "S9(8)", "99999999", "S99999999"}:
 if field_name.startswith("DA ") or " DATE" in field_name:
 return True

 return False

```

```

def basetype_for_datatype(
 self,
 datatype: str | None,
) -> str | None:
 datatype_upper = str(datatype or "").upper()

 if datatype_upper == "DATE":
 return "DATE"

 if datatype_upper in {"DECIMAL", "NUMERIC", "INTEGER"}:
 return "NUMERIC"

 if datatype_upper in {"CHAR", "VARCHAR"}:
 return "CHAR"

 return datatype

def enrich_group_positions_from_children(
 self,
 fields: list[DataField],
 debug_label: str = "",
) -> list[DataField]:
 output = list(fields or [])

 for index, field in enumerate(output):
 is_group = bool(
 getattr(field, "has_child", False)
 or getattr(field, "is_group", False)
)

 if not is_group:
 continue

 level = getattr(field, "level", None)

 try:
 parent_level = int(level)
 except Exception:
 continue

 child_starts: list[int] = []
 child_ends: list[int] = []

 for child in output[index + 1:]:
 child_level = getattr(child, "level", None)

 try:
 current_level = int(child_level)
 except Exception:
 continue

 if current_level <= parent_level:
 break

 start = getattr(child, "start_position", None)
 end = getattr(child, "end_position", None)

 if start is not None:
 try:
 child_starts.append(int(start))
 except Exception:
 pass

 if end is not None:
 try:
 child_ends.append(int(end))
 except Exception:
 pass

 if not child_starts and not child_ends:
 continue

 group_start = min(child_starts) if child_starts else getattr(field, "start_position", None)
 group_end = max(child_ends) if child_ends else getattr(field, "end_position", None)

 group_length = getattr(field, "length", None)

```

```

try:
 if group_start is not None and group_end is not None:
 group_length = int(group_end) - int(group_start) + 1
except Exception:
 pass

output[index] = self.make_field(
 source=field,
 datatype=getattr(field, "datatype", None),
 length=group_length,
 scale=getattr(field, "scale", None),
 picture=None,
 start_position=group_start,
 end_position=group_end,
 basetype=getattr(field, "basetype", None),
)

return output

def copy_field_with_defaults(
 self,
 field: DataField,
) -> DataField:
 return self.make_field(
 source=field,
 datatype=getattr(field, "datatype", None),
 length=getattr(field, "length", None),
 scale=getattr(field, "scale", None),
 picture=getattr(field, "picture", None),
 start_position=getattr(field, "start_position", None),
 end_position=getattr(field, "end_position", None),
 basetype=getattr(field, "basetype", None),
)

def make_field(
 self,
 source: DataField,
 datatype: str | None,
 length: int | None,
 scale: int | None,
 picture: str | None,
 start_position: int | None,
 end_position: int | None,
 basetype: str | None,
) -> DataField:
 data = source.model_dump()

 data.update(
 {
 "datatype": datatype,
 "length": length,
 "scale": scale,
 "picture": picture,
 "start_position": start_position,
 "end_position": end_position,
 "basetype": basetype,
 }
)

 return DataField(**data)

def remove_record_suffix(
 self,
 value: str,
) -> str:
 text = str(value or "").strip().upper()
 text = re.sub(r"[\s_-]+[0-9]{4}$", "", text)
 text = re.sub(r"[0-9]{4}$", "", text)
 text = re.sub(r"[\s_-]+$", "", text)

 return text

```

```
=====
FILE: src\idms_modernizer\services\validation_service.py
ENCODING: utf-8
=====
```

```
class ValidationService:

 def validate_metadata(
 self,
 metadata
) -> list[str]:

 errors = []

 record_names = {
 record.name
 for record in metadata.records
 }

 for rel in metadata.relationships:

 if rel.owner_record not in record_names:

 errors.append(
 f"Missing Owner Record: {rel.owner_record}"
)

 if rel.member_record not in record_names:

 errors.append(
 f"Missing Member Record: {rel.member_record}"
)

 return errors
```

```
=====
FILE: src\idms_modernizer\tests__init__.py
ENCODING: utf-8
=====
```

[Empty file]

```
=====
FILE: src\idms_modernizer\tests\test_date_field_consolidator.py
ENCODING: utf-8
=====
```

```
from idms_modernizer.services.date_field_consolidator import (
 DateFieldConsolidator
)
```

```
from idms_modernizer.domain.schema_models import (
 DataField
)
```

```
def test_consolidate_year_month_day():
 fields = [
 DataField(name="START_YEAR"),
 DataField(name="START_MONTH"),
 DataField(name="START_DAY")
]

 out = DateFieldConsolidator.consolidate(fields)

 assert len(out) == 1
 assert out[0].name == "START_DATE"
 assert out[0].datatype == "DATE"
```

```
def test_consolidate_variants():
 fields = [
 DataField(name="FINISH_YR"),
 DataField(name="FINISH_MO"),
```

```

 DataField(name="FINISH_DY")
]

 out = DateFieldConsolidator.consolidate(fields)

 assert len(out) == 1
 assert out[0].name == "FINISH_DATE"
 assert out[0].datatype == "DATE"

def test_preserve_existing_full_date():
 fields = [
 DataField(name="BIRTH_DATE", datatype="DATE"),
 DataField(name="BIRTH_YEAR"),
 DataField(name="BIRTH_MONTH")
]

 out = DateFieldConsolidator.consolidate(fields)

 # Should keep the existing BIRTH_DATE and not create duplicate
 names = [f.name for f in out]
 assert "BIRTH_DATE" in names
 assert all(n.startswith("BIRTH_") for n in names)

def test_keep_year_only():
 fields = [
 DataField(name="CLAIM_YEAR")
]

 out = DateFieldConsolidator.consolidate(fields)

 assert len(out) == 1
 assert out[0].name == "CLAIM_YEAR"

```

```

=====
FILE: src\idms_modernizer\tests\test_diagram_parser.py
ENCODING: utf-8
=====

```

```

from idms_modernizer.parsers.pdf_diagram_parser import (
 PdfDiagramParser
)

```

```

def test_diagram_parser():

 parser = (
 PdfDiagramParser()
)

 relationships = (
 parser.parse(
 """
 DEPARTMENT
 EMPLOYEE
 """
)
)

 assert (
 len(relationships)
 == 1
)

 assert (
 relationships[0].owner
 == "DEPARTMENT"
)

```



```
=====
FILE: src\idms_modernizer\tests\test_field_extractor.py
ENCODING: utf-8
=====
```

```
import re
import sys
from dataclasses import dataclass, asdict
from typing import List, Optional, Set
```

```
----- PDF READER -----
```

```
def read_pdf_lines(pdf_path: str) -> List[str]:
 """
 Extract text lines from a PDF file using pdfminer.six.
 Returns a list of lines.
 """
 try:
 from pdfminer.high_level import extract_text
 except ImportError as e:
 raise RuntimeError(
 "pdfminer.six is required. Install it with:\n\n"
 " pip install pdfminer.six\n"
) from e

 text = extract_text(pdf_path) or ""
 # Split into lines while preserving basic line structure
 lines = text.splitlines()
 # Trim trailing spaces for consistency
 return [ln.rstrip("\r\n") for ln in lines]
```

```
----- DATA TYPES -----
```

```
@dataclass(frozen=True)
class DataField:
 name: str
 datatype: str
 length: Optional[int]
 scale: Optional[int]
 picture: str
```

```
----- EXTRACTOR -----
```

```
class FieldExtractor:
 """
 Robust parser for IDMS-like listing lines.

 - Extracts PICTURE regardless of position and with/without PIC/PICTURE keyword
 - Recognizes DISPLAY, COMP, COMP-3 in any order relative to PICTURE
 - Skips FILLER items by default (configurable)
 - Removes duplicate names
 - Maps:
 * X -> CHAR(1)
 * X(n) -> VARCHAR(n)
 * DISPLAY + 9/S9[/ (n)] -> INTEGER(length = digits)
 * COMP/COMP-3 + 9/S9[/ (n)] -> DECIMAL(precision = digits)
 * S9(n)V9(m)/9(n)V9(m) -> DECIMAL(precision = n+m, scale = m)
 """

 def __init__(
 self,
 require_explicit_length: bool = False,
 include_filler: bool = False,
 auto_number_filler: bool = True,
):
 self.require_explicit_length = require_explicit_length
 self.include_filler = include_filler
 self.auto_number_filler = auto_number_filler

 # Start: <level> <name>
 _R_START = re.compile(r"^\s*(\d{2})\s+([A-Z0-9\-\+])\b", re.IGNORECASE)

 # USAGE anywhere (allow "USAGE IS ...")
 _R_USAGE = re.compile(r"\b(?:USAGE\s+IS\s+)?(DISPLAY|COMP-3|COMP)\b", re.IGNORECASE)

 # PICTURE anywhere; optional PIC/PICTURE keyword; tolerate spaces; no trailing \b
```

```

_R_PIC_ANYWHERE = re.compile(
 r"""
 (?:\b(?:PIC|PICTURE)\s*)?
 (
 S\s*9\s*$\s*\d+\s*$\s*V\s*9\s*$\s*\d+\s*$ | # S9(n)V9(m) / 9(n)V9(m)
 S\s*9\s*$\s*\d+\s*$ | # S9(n)
 9\s*$\s*\d+\s*$ | # 9(n)
 S\s*9 | # S9
 9 | # 9
 X\s*$\s*\d+\s*$ | # X(n)
 X | # X
)
 """,
 re.IGNORECASE | re.VERBOSE,
)

Helpers (operate on normalized picture like X(30), 9(7), S9(7)V9(2))
_R_CHAR = re.compile(r"^X$(\d+)$", re.IGNORECASE) # X(n)
_R_INT = re.compile(r"^S?9(?:$(\d+)$)?$", re.IGNORECASE) # 9 / 9(n) / S9 / S9(n)
_R_DEC = re.compile(r"^S?9$(\d+)$V9$(\d+)$", re.IGNORECASE) # S9(n)V9(m) / 9(n)V9(m)

def extract(self, lines: List[str]) -> List[DataField]:
 seen: Set[str] = set()
 out: List[DataField] = []
 filler_idx = 0

 for raw in lines:
 line = raw.strip()
 if not line:
 continue

 m_start = self._R_START.match(line)
 if not m_start:
 continue

 _, name = m_start.groups()
 name_up = name.upper()

 # Handle FILLER items
 if name_up.startswith("FILLER"):
 if not self.include_filler:
 continue
 if self.auto_number_filler:
 filler_idx += 1
 name_up = f"FILLER_{filler_idx}"

 if name_up in seen:
 continue

 # USAGE default to DISPLAY if absent
 m_usage = self._R_USAGE.search(line)
 usage = m_usage.group(1).upper() if m_usage else "DISPLAY"

 # PICTURE capture
 m_pic = self._R_PIC_ANYWHERE.search(line)
 if not m_pic:
 continue

 # Normalize: remove spaces inside the picture and uppercase
 pic = re.sub(r"\s+", "", m_pic.group(1).upper())

 # Optional filter: require explicit length (skip X, 9, S9)
 if self.require_explicit_length and pic in {"X", "9", "S9"}:
 continue

 dtype: str = "VARCHAR"
 length: Optional[int] = None
 scale: Optional[int] = None

 # Character
 if pic == "X":
 dtype, length = "CHAR", 1
 elif self._R_CHAR.fullmatch(pic):
 length = int(self._R_CHAR.fullmatch(pic).group(1))
 dtype = "VARCHAR"

```

```

Decimal with V
elif self._R_DEC.fullmatch(pic):
 int_len, frac_len = map(int, self._R_DEC.fullmatch(pic).groups())
 length = int_len + frac_len
 scale = frac_len
 dtype = "DECIMAL"

Integer-like 9/S9 with optional (n)
elif self._R_INT.fullmatch(pic):
 digits_str = self._R_INT.fullmatch(pic).group(1)
 digits = int(digits_str) if digits_str else 1
 length = digits
 dtype = "INTEGER" if usage == "DISPLAY" else "DECIMAL"
else:
 # Unrecognized picture; skip
 continue

seen.add(name_up)
out.append(
 DataField(
 name=name_up,
 datatype=dtype,
 length=length,
 scale=scale,
 picture=pic,
)
)

return out

----- DEMO (PDF PATH) -----
if __name__ == "__main__":
 # Option A: Provide the PDF file path here (edit this string)
 pdf_path = r"C:\VSCode\idms-db2-modernizer-master\idms-db2-modernizer-master\src\idms_modernizer\data\IDMS_Schema_Listing.pdf"

 # Option B: Or pass the path as first CLI argument
 if len(sys.argv) > 1:
 pdf_path = sys.argv[1]

 # Read lines from PDF
 lines = read_pdf_lines(pdf_path)

 # Configure extractor as needed
 extractor = FieldExtractor(
 require_explicit_length=False, # set True to skip X / 9 / S9 without (n)
 include_filler=False, # set True to include FILLER items
 auto_number_filler=True
)

 fields = extractor.extract(lines)
 for f in fields:
 print(asdict(f))

=====
FILE: src\idms_modernizer\tests\test_normalization_mapping.py
ENCODING: utf-8
=====

from idms_modernizer.domain.schema_models import DataField
from idms_modernizer.services.name_normalizer import NameNormalizer
from idms_modernizer.services.date_field_consolidator import DateFieldConsolidator
from idms_modernizer.services.db2_mapping_service import DB2MappingService

def test_name_normalizer_removes_suffix_and_normalizes():
 assert (
 NameNormalizer.normalize(
 "CLAIM-YEAR-0405"
)
 == "CLAIM_YEAR"
)
 assert (
 NameNormalizer.normalize(

```

```

 "EMP-ID 0415"
)
 == "EMP_ID"
)
assert (
 NameNormalizer.normalize(
 " CLAIM--MONTH-0405 "
)
 == "CLAIM_MONTH"
)

def test_date_field_consolidator_consolidates_suffixed_date_fields():
 fields = [
 DataField(name="CLAIM-YEAR-0405"),
 DataField(name="CLAIM-MONTH-0405"),
 DataField(name="CLAIM-DAY-0405"),
 DataField(name="OTHER-FIELD-0405"),
]

 consolidated = DateFieldConsolidator.consolidate(
 fields
)

 assert any(
 field.name == "CLAIM_DATE"
 and field.datatype == "DATE"
 for field in consolidated
)
 assert any(
 field.name == "OTHER-FIELD-0405"
 and field.datatype is None
 for field in consolidated
)
 assert len(consolidated) == 2

def test_db2_mapping_service_preserves_date_and_varchar_length():
 mapper = DB2MappingService()

 date_column = DataField(
 name="CLAIM_DATE",
 datatype="DATE"
)
 assert mapper.map_datatype(date_column) == "DATE"

 timestamp_column = DataField(
 name="EVENT_TS",
 datatype="TIMESTAMP"
)
 assert mapper.map_datatype(timestamp_column) == "TIMESTAMP"

 string_column = DataField(
 name="NAME",
 datatype="DISPLAY",
 length=40,
)
 assert mapper.map_datatype(string_column) == "VARCHAR(40)"

```

```

=====
FILE: src\idms_modernizer\tests\test_schema_parser.py
ENCODING: utf-8
=====

```

```

from idms_modernizer.parsers.pdf_schema_parser import (
 PdfSchemaParser
)

```

```

def test_schema_parser():

 sample_text = """

 RECORD NAME..... EMPLOYEE

```

EMP-ID-0415

EMP-FIRST-NAME-0415

EMP-LAST-NAME-0415

RECORD NAME..... DEPARTMENT

DEPT-ID-0416

DEPT-NAME-0416

"""

```
parser = (
 PdfSchemaParser()
)
```

```
metadata = (
 parser.parse(
 sample_text
)
)
```

```
assert (
 len(metadata.records)
 == 2
)
```

```
assert (
 metadata.records[0].name
 == "EMPLOYEE"
)
```

```
assert (
 len(
 metadata.records[0].fields
)
 == 3
)
```

```
=====
```

FILE: src\idms\_modernizer\ui\\_\_init\_\_.py  
ENCODING: utf-8

```
=====
```

[Empty file]

```
=====
```

FILE: src\idms\_modernizer\ui\metadata\_page.py  
ENCODING: utf-8

```
=====
```

```
import streamlit as st
```

```
def render_metadata(
 metadata
):
```

```
 st.subheader(
 "Detected Records"
)
```

```
 for record in metadata.records:
```

```
 st.markdown(
 f"### {record.name}"
)
```

```
 st.write(
 f"Fields: {len(record.fields)}"
)
```

```

 field_names = [
 field.name
 for field in record.fields
]

 st.dataframe(
 field_names
)

```

```

=====
FILE: src\idms_modernizer\ui\phase2_converter_panel.py
ENCODING: utf-8
=====

```

```

import json
from pathlib import Path
from typing import Any

import streamlit as st

from idms_modernizer.parsers.cobol_pdf_extractor import CobolPdfExtractor
from idms_modernizer.services.phase2_conversion_bridge import (
 Phase2ConversionBridge
)

try:
 from idms_db2_converter.exceptions import ConversionError
except Exception:
 class ConversionError(Exception):
 pass

class Phase2ConverterPanel:
 """
 Streamlit panel for running Phase 2 conversion inside Phase 1 app.

 Inputs:
 - COBOL text, COBOL PDF, or COBOL text file
 - Canonical JSON generated by Phase 1
 - Phase 2 metadata JSON generated by Phase 1
 - DB2 DDL generated by Phase 1
 - Optional IDMS schema text
 - Optional relationship overrides

 Important:
 - No hardcoded relationship overrides.
 - Relationship override JSON is dynamically generated from Phase 2 metadata
 when the user chooses to use overrides.
 """

 def render(
 self,
 canonical_json: str,
 phase2_metadata_json: str,
 ddl_text: str,
 idms_schema_text: str | None = None
) -> None:

 st.header(
 "Phase 2 - IDMS Retrieval COBOL to DB2 COBOL"
)

 st.markdown(
 """
 Use this section to convert an IDMS retrieval COBOL program into DB2 embedded SQL COBOL using the Phase 1 outputs generated above.
 """
)

 with st.expander(
 "Phase 1 Inputs Passed to Phase 2",
 expanded=False
):
 st.subheader(
 "Canonical JSON"
)

```

```

)

 st.code(
 canonical_json or "",
 language="json"
)

 st.subheader(
 "Phase 2 Metadata JSON"
)

 st.code(
 phase2_metadata_json or "",
 language="json"
)

 st.subheader(
 "DB2 DDL"
)

 st.code(
 ddl_text or "",
 language="sql"
)

 st.subheader(
 "COBOL Input"
)

 cobol_text = self._render_cobol_input()

 st.subheader(
 "Conversion Settings"
)

 target_program = st.text_input(
 "Target PROGRAM-ID",
 value="",
 placeholder="Example: DEPTDB2"
)

 col1, col2, col3 = st.columns(3)

 with col1:
 use_ddl = st.checkbox(
 "Use DB2 DDL",
 value=True,
 help="Recommended. DDL should be the physical source of truth."
)

 with col2:
 use_phase2_metadata = st.checkbox(
 "Use Phase 2 Metadata",
 value=True,
 help="Recommended. Uses Phase 1 generated mapping metadata."
)

 with col3:
 use_idms_schema = st.checkbox(
 "Use IDMS Schema Text",
 value=False,
 help="Optional. Usually not required if canonical, DDL, and Phase 2 metadata are provided."
)

 use_overrides = st.checkbox(
 "Use relationship key overrides",
 value=False,
 help="Optional. Dynamically generated from Phase 2 metadata when enabled."
)

 relationship_overrides_json = ""

 if use_overrides:
 relationship_overrides_json = self._render_relationship_overrides(
 phase2_metadata_json=phase2_metadata_json
)

```

```

phase2_idms_schema_text = ""

if use_idms_schema:
 phase2_idms_schema_text = st.text_area(
 "Paste IDMS schema/subschema listing text",
 height=300,
 value=idms_schema_text or ""
)

convert_clicked = st.button(
 "Convert to DB2 COBOL",
 type="primary"
)

if convert_clicked:
 self._run_conversion(
 cobol_text=cobol_text,
 canonical_json=canonical_json,
 phase2_metadata_json=(
 phase2_metadata_json
 if use_phase2_metadata
 else ""
),
 ddl_text=(
 ddl_text
 if use_ddl
 else ""
),
 idms_schema_text=(
 phase2_idms_schema_text
 if use_idms_schema
 else None
),
 relationship_overrides_json=(
 relationship_overrides_json
 if use_overrides
 else None
),
 target_program=target_program,
 use_ddl=use_ddl,
 use_idms_schema=use_idms_schema,
 use_overrides=use_overrides
)

def _render_cobol_input(
 self
) -> str:

 input_mode = st.radio(
 "Choose COBOL input method",
 [
 "Paste COBOL",
 "Upload COBOL PDF",
 "Upload COBOL Text File"
],
 horizontal=True
)

 cobol_text = ""

 if input_mode == "Paste COBOL":
 cobol_text = st.text_area(
 "Paste IDMS COBOL retrieval program",
 height=420,
 placeholder="Paste DEPTRPT or another IDMS retrieval program here..."
)

 elif input_mode == "Upload COBOL PDF":
 cobol_text = self._load_cobol_from_pdf()

 elif input_mode == "Upload COBOL Text File":
 cobol_text = self._load_cobol_from_text_file()

 return cobol_text

```



```

def _load_cobol_from_pdf(
 self
) -> str:

 cobol_text = ""

 cobol_pdf = st.file_uploader(
 "Upload COBOL PDF",
 type=[
 "pdf"
],
 key="phase2_cobol_pdf"
)

 if cobol_pdf is None:
 return cobol_text

 temp_path = self._save_uploaded_file(
 uploaded_file=cobol_pdf,
 folder="data/temp"
)

 extractor = CobolPdfExtractor()

 try:
 cobol_text = extractor.extract_text(
 temp_path
)

 st.success(
 "COBOL PDF extracted successfully."
)

 cobol_text = st.text_area(
 "Extracted COBOL text",
 value=cobol_text,
 height=420
)

 except Exception as ex:
 st.error(
 f"Failed to extract COBOL PDF: {ex}"
)

 return cobol_text

def _load_cobol_from_text_file(
 self
) -> str:

 cobol_text = ""

 cobol_file = st.file_uploader(
 "Upload COBOL source file",
 type=[
 "cbl",
 "cob",
 "txt"
],
 key="phase2_cobol_text"
)

 if cobol_file is None:
 return cobol_text

 try:
 cobol_text = cobol_file.read().decode(
 "utf-8",
 errors="ignore"
)

 st.success(
 "COBOL text file loaded successfully."
)

 cobol_text = st.text_area(

```

```

 "Loaded COBOL text",
 value=cobol_text,
 height=420
)

except Exception as ex:
 st.error(
 f"Failed to read COBOL file: {ex}"
)

return cobol_text

def _render_relationship_overrides(
 self,
 phase2_metadata_json: str
) -> str:

 st.markdown(
 """
Relationship overrides are generated from the current Phase 2 metadata.
You can edit them before conversion if needed.
"""
)

 generated_overrides = self._build_overrides_from_phase2_metadata(
 phase2_metadata_json
)

 if not generated_overrides:
 st.info(
 "No complete relationship overrides could be generated from Phase 2 metadata."
)

 generated_overrides = {
 "relationships": []
 }

 return st.text_area(
 "Relationship key overrides JSON",
 height=300,
 value=json.dumps(
 generated_overrides,
 indent=2
)
)

def _build_overrides_from_phase2_metadata(
 self,
 phase2_metadata_json: str
) -> dict[str, Any]:

 if not phase2_metadata_json or not phase2_metadata_json.strip():
 return {
 "relationships": []
 }

 try:
 payload = json.loads(
 phase2_metadata_json
)

 except json.JSONDecodeError:
 return {
 "relationships": []
 }

 relationships = payload.get(
 "relationships",
 []
)

 override_relationships = []

 for relationship in relationships:
 set_name = self._get_first_non_empty(
 relationship,

```

```

 [
 "set_name",
 "name",
 "relationship"
]
)

 parent_record = self._get_first_non_empty(
 relationship,
 [
 "parent_record",
 "parent_table"
]
)

 child_record = self._get_first_non_empty(
 relationship,
 [
 "child_record",
 "child_table"
]
)

 parent_key = self._get_first_non_empty(
 relationship,
 [
 "parent_key",
 "parent_pk"
]
)

 child_fk = self._get_first_non_empty(
 relationship,
 [
 "child_fk",
 "foreign_key"
]
)

 order_by = relationship.get(
 "order_by",
 []
)

 if not set_name:
 continue

 if not parent_record:
 continue

 if not child_record:
 continue

 item = {
 "set_name": self._to_idms_name(set_name),
 "parent_record": self._normalize_name(parent_record),
 "child_record": self._normalize_name(child_record)
 }

 if parent_key:
 item[
 "parent_key"
] = self._normalize_name(parent_key)

 if child_fk:
 item[
 "child_fk"
] = self._normalize_name(child_fk)

 if order_by:
 item[
 "order_by"
] = [
 self._normalize_name(value)
 for value in order_by
 if value

```

```

]

 override_relationships.append(
 item
)

 return {
 "relationships": override_relationships
 }

def _run_conversion(
 self,
 cobol_text: str,
 canonical_json: str,
 phase2_metadata_json: str,
 ddl_text: str,
 idms_schema_text: str | None,
 relationship_overrides_json: str | None,
 target_program: str | None,
 use_ddl: bool,
 use_idms_schema: bool,
 use_overrides: bool
) -> None:

 if not cobol_text or not cobol_text.strip():
 st.error(
 "COBOL code is required."
)
 st.stop()

 bridge = Phase2ConversionBridge()

 try:
 converted, validation_messages = bridge.convert(
 cobol_text=cobol_text,
 canonical_json=canonical_json,
 phase2_metadata_json=phase2_metadata_json,
 ddl_text=ddl_text,
 idms_schema_text=idms_schema_text,
 relationship_overrides_json=relationship_overrides_json,
 target_program=target_program,
 use_ddl=use_ddl,
 use_idms_schema=use_idms_schema,
 use_overrides=use_overrides
)

 st.success(
 "Phase 2 conversion completed."
)

 if validation_messages:
 st.warning(
 "Conversion completed with validation messages."
)

 for message in validation_messages:
 st.write(
 f"- {message}"
)

 else:
 st.info(
 "Validation passed."
)

 st.subheader(
 "Final DB2 COBOL"
)

 st.text_area(
 "Copy converted DB2 COBOL",
 value=converted,
 height=700
)

 except ConversionError as exc:

```

```

 st.error(
 "Phase 2 conversion failed."
)

 st.code(
 str(exc),
 language="text"
)

except Exception as exc:
 st.error(
 "Unexpected Phase 2 conversion error."
)

 st.code(
 str(exc),
 language="text"
)

def _save_uploaded_file(
 self,
 uploaded_file,
 folder: str
) -> str:

 target_folder = Path(
 folder
)

 target_folder.mkdir(
 parents=True,
 exist_ok=True
)

 target_path = (
 target_folder
 / uploaded_file.name
)

 with open(
 target_path,
 "wb"
) as file:
 file.write(
 uploaded_file.getbuffer()
)

 return str(
 target_path
)

def _get_first_non_empty(
 self,
 source: dict[str, Any],
 keys: list[str]
) -> str | None:

 for key in keys:
 value = source.get(
 key
)

 if value is None:
 continue

 value = str(
 value
).strip()

 if value:
 return value

 return None

def _normalize_name(
 self,

```

```

 value: str | None
) -> str:

 if value is None:
 return ""

 return str(
 value
).strip().upper().replace(
 "_",
 "-",
)

```

```

def _to_idms_name(
 self,
 value: str | None
) -> str:

 if value is None:
 return ""

 return str(
 value
).strip().upper().replace(
 "_",
 "-",
)

```

```

=====
FILE: src\idms_modernizer\ui\schema_listing_only_app.py
ENCODING: utf-8
=====

```

```

from pathlib import Path
from tempfile import NamedTemporaryFile

```

```

import streamlit as st

```

```

from idms_modernizer.core.config import settings
from idms_modernizer.core.utils import ensure_directory
from idms_modernizer.services.metadata_service import MetadataService
from idms_modernizer.services.canonical_schema_builder import (
 CanonicalSchemaBuilder,
)
from idms_modernizer.services.canonical_reconciler import (
 CanonicalReconciler,
)
from idms_modernizer.services.db2_model_builder import DB2ModelBuilder
from idms_modernizer.generators.ddl_generator import DDLGenerator
from idms_modernizer.services.excel_sheet_mapping_service import (
 ExcelSheetMappingService,
)

```

```

def initialize_directories() -> None:
 ensure_directory(
 settings.output_dir,
)

```

```

def initialize_session_state() -> None:
 defaults = {
 "schema_only_generated": False,
 "schema_only_error": "",
 "schema_only_schema_path": "",
 "schema_only_metadata": None,
 "schema_only_canonical_schema": None,
 "schema_only_db2_model": None,
 "schema_only_ddl_text": "",
 "schema_only_excel_mapping_rows": [],
 }

```

```

 for key, value in defaults.items():
 if key not in st.session_state:
 st.session_state[key] = value

```

```

def reset_schema_only_outputs() -> None:
 st.session_state.schema_only_generated = False
 st.session_state.schema_only_error = ""
 st.session_state.schema_only_schema_path = ""
 st.session_state.schema_only_metadata = None
 st.session_state.schema_only_canonical_schema = None
 st.session_state.schema_only_db2_model = None
 st.session_state.schema_only_ddl_text = ""
 st.session_state.schema_only_excel_mapping_rows = []

def save_uploaded_schema_file(
 uploaded_file,
) -> str:
 suffix = Path(
 uploaded_file.name,
).suffix or ".pdf"

 with NamedTemporaryFile(
 delete=False,
 suffix=suffix,
) as temp_file:
 temp_file.write(
 uploaded_file.getbuffer(),
)

 return temp_file.name

def generate_schema_outputs(
 schema_pdf,
) -> None:
 reset_schema_only_outputs()

 try:
 schema_path = save_uploaded_schema_file(
 uploaded_file=schema_pdf,
)

 metadata_service = MetadataService()

 metadata = metadata_service.build_metadata(
 pdf_path=schema_path,
)

 canonical_builder = CanonicalSchemaBuilder()

 canonical_schema = canonical_builder.build(
 metadata=metadata,
)

 canonical_reconciler = CanonicalReconciler()

 canonical_schema = canonical_reconciler.reconcile(
 canonical_schema=canonical_schema,
 metadata=metadata,
)

 db2_builder = DB2ModelBuilder()

 db2_model = db2_builder.build(
 canonical_schema,
)

 ddl_generator = DDLGenerator()

 ddl_text = ddl_generator.generate(
 db2_model,
)

 excel_mapping_service = ExcelSheetMappingService()

 excel_mapping_rows = excel_mapping_service.build(
 metadata=metadata,

```

```

 db2_model=db2_model,
)

 st.session_state.schema_only_schema_path = schema_path
 st.session_state.schema_only_metadata = metadata
 st.session_state.schema_only_canonical_schema = canonical_schema
 st.session_state.schema_only_db2_model = db2_model
 st.session_state.schema_only_ddl_text = ddl_text
 st.session_state.schema_only_excel_mapping_rows = excel_mapping_rows
 st.session_state.schema_only_generated = True

except Exception as exc:
 st.session_state.schema_only_generated = False
 st.session_state.schema_only_error = str(
 exc,
)
)

def build_mapping_row_count_by_table(
 rows: list[dict],
 include_total: bool = True,
) -> list[dict[str, int | str]]:
 """
 Builds table-level counts from the actual Excel Sheet Mapping rows.

 This count matches the detailed mapping table because it counts the
 generated mapping rows, not only DB2 physical columns.

 Output column order:
 - Column Field Count
 - Table Name
 """
 table_counts: dict[str, int] = {}

 for row in rows or []:
 table_name = (
 row.get("New DB2 Record")
 or row.get("Cobol Record IDMS")
 or ""
)

 table_name = str(
 table_name,
).strip()

 if not table_name:
 continue

 table_counts[table_name] = table_counts.get(
 table_name,
 0,
) + 1

 output_rows: list[dict[str, int | str]] = []

 total_count = 0

 for table_name in sorted(table_counts):
 count = table_counts[table_name]

 output_rows.append(
 {
 "Column Field Count": count,
 "Table Name": table_name,
 }
)

 total_count += count

 if include_total:
 output_rows.append(
 {
 "Column Field Count": total_count,
 "Table Name": "TOTAL",
 }
)
)

```



```

return output_rows

def build_db2_physical_column_count_rows(
 db2_model,
 include_total: bool = True,
) -> list[dict[str, int | str]]:
 """
 Builds table-level physical DB2 column counts.

 This is separate from the mapping row count because DATE child fields
 can create multiple mapping rows but only one DB2 physical DATE column.
 """
 table_rows: list[dict[str, int | str]] = []

 if db2_model is None:
 return table_rows

 total_count = 0

 for table in getattr(
 db2_model,
 "tables",
 [],
) or []:
 table_name = getattr(
 table,
 "name",
 "",
)

 columns = getattr(
 table,
 "columns",
 [],
) or []

 count = len(
 columns,
)

 table_rows.append(
 {
 "Column Field Count": count,
 "Table Name": table_name,
 }
)

 total_count += count

 if include_total:
 table_rows.append(
 {
 "Column Field Count": total_count,
 "Table Name": "TOTAL",
 }
)

 return table_rows

def render_main_tab() -> None:
 st.markdown("## Schema Listing Only")

 st.info(
 "Upload only the Schema Listing PDF to generate Metadata Overview, "
 "DB2 DDL, and Excel Sheet Mapping."
)

 schema_pdf = st.file_uploader(
 "Schema Listing PDF",
 type=["pdf"],
 key="schema_only_schema_listing_pdf",
)

```

```

generate_clicked = st.button(
 "Generate Schema Outputs",
 type="primary",
 use_container_width=True,
)

if generate_clicked:
 if schema_pdf is None:
 st.error(
 "Please upload a Schema Listing PDF."
)
 return

 with st.spinner(
 "Processing schema listing and generating outputs..."
):
 generate_schema_outputs(
 schema_pdf=schema_pdf,
)

 if st.session_state.schema_only_generated:
 st.success(
 "Schema outputs generated successfully."
)
 else:
 st.error(
 "Schema output generation failed."
)

 if st.session_state.schema_only_error:
 st.error(
 st.session_state.schema_only_error,
)

if st.session_state.schema_only_generated:
 st.markdown("### Output Status")

 metadata = st.session_state.schema_only_metadata
 db2_model = st.session_state.schema_only_db2_model
 mapping_rows = st.session_state.schema_only_excel_mapping_rows

 col1, col2, col3, col4 = st.columns(
 4,
)

 with col1:
 st.metric(
 "Records",
 len(
 metadata.records,
)
 if metadata is not None
 else 0,
)

 with col2:
 st.metric(
 "Relationships",
 len(
 metadata.relationships,
)
 if metadata is not None
 else 0,
)

 with col3:
 st.metric(
 "DB2 Tables",
 len(
 db2_model.tables,
)
 if db2_model is not None
 else 0,
)

 with col4:

```

```

 st.metric(
 "Sheet Mapping Rows",
 len(
 mapping_rows,
)
 if mapping_rows is not None
 else 0,
)

def render_metadata_overview_tab() -> None:
 if not st.session_state.schema_only_generated:
 st.info(
 "Generate outputs from the Main tab first."
)
 return

 metadata = st.session_state.schema_only_metadata
 db2_model = st.session_state.schema_only_db2_model
 mapping_rows = st.session_state.schema_only_excel_mapping_rows

 if metadata is None:
 st.info(
 "No metadata available."
)
 return

 st.markdown("## Metadata Overview")

 st.markdown("### Records")

 record_rows = []

 for record in metadata.records:
 record_rows.append(
 {
 "Record": record.name,
 "Cobol Zone": record.cobol_zone or "",
 "Primary Key": record.primary_key or "",
 "Field Count": len(
 record.fields,
),
 "Set Membership Count": len(
 record.set_memberships,
),
 }
)

 st.dataframe(
 record_rows,
 use_container_width=True,
 hide_index=True,
)

 st.divider()

 st.markdown("### Table List and Mapping Row Counts")

 mapping_count_rows = build_mapping_row_count_by_table(
 rows=mapping_rows,
 include_total=True,
)

 if mapping_count_rows:
 st.dataframe(
 mapping_count_rows,
 use_container_width=True,
 hide_index=True,
)
 else:
 st.info(
 "No table mapping row counts available."
)

 st.caption(
 "This count is based on the actual Excel Sheet Mapping rows, "

```

```

 "so the TOTAL matches the detailed mapping table."
)

st.divider()

st.markdown("### DB2 Physical Column Counts")

physical_column_count_rows = build_db2_physical_column_count_rows(
 db2_model=db2_model,
 include_total=True,
)

if physical_column_count_rows:
 st.dataframe(
 physical_column_count_rows,
 use_container_width=True,
 hide_index=True,
)
else:
 st.info(
 "No DB2 physical column counts available."
)

st.caption(
 "This count is based on DB2 physical columns. It can be lower than "
 "the mapping row count when COBOL YEAR, MONTH, and DAY fields map "
 "to one DB2 DATE column."
)

st.divider()

st.markdown("### Records and Fields")

record_names = [
 record.name
 for record in metadata.records
]

if not record_names:
 st.info(
 "No records found."
)
 return

selected_record = st.selectbox(
 "Select a record",
 options=record_names,
)

selected_record_obj = None

for record in metadata.records:
 if record.name == selected_record:
 selected_record_obj = record
 break

if selected_record_obj is not None:
 st.write(
 f"Fields found: `{len(selected_record_obj.fields)}`"
)

 field_rows = []

 for field in selected_record_obj.fields:
 field_rows.append(
 {
 "Field": field.name,
 "Level": field.level,
 "Datatype": field.datatype,
 "Length": field.length,
 "Scale": field.scale,
 "Picture": field.picture,
 "Start Position": field.start_position,
 "End Position": field.end_position,
 "Basetype": field.basetype,
 }
)

```

```

)

 st.dataframe(
 field_rows,
 use_container_width=True,
 hide_index=True,
)

with st.expander(
 "View all records and fields as JSON",
 expanded=False,
):
 st.json(
 [
 {
 "record": record.name,
 "cobol_zone": record.cobol_zone,
 "primary_key": record.primary_key,
 "fields": [
 field.model_dump()
 for field in record.fields
],
 "set_memberships": [
 {
 "set_name": getattr(
 membership,
 "set_name",
 "",
),
 "relation_type": getattr(
 membership,
 "relation_type",
 "",
),
 "owner_record": getattr(
 membership,
 "owner_record",
 "",
),
 "member_record": getattr(
 membership,
 "member_record",
 "",
),
 }
 for membership in record.set_memberships
],
 }
 for record in metadata.records
]
)

def render_ddl_tab() -> None:
 if not st.session_state.schema_only_generated:
 st.info(
 "Generate outputs from the Main tab first."
)
 return

 st.markdown("## DB2 DDL")

 ddl_text = st.session_state.schema_only_ddl_text

 if not ddl_text:
 st.info(
 "No DDL generated."
)
 return

 st.code(
 ddl_text,
 language="sql",
)

```

```

def render_excel_sheet_mapping_tab() -> None:
 if not st.session_state.schema_only_generated:
 st.info(
 "Generate outputs from the Main tab first."
)
 return

 st.markdown("## Excel Sheet Mapping")

 rows = st.session_state.schema_only_excel_mapping_rows

 if not rows:
 st.info(
 "No mapping rows generated."
)
 return

 st.markdown("### Sheet Map Abstract")

 abstract_rows = build_mapping_row_count_by_table(
 rows=rows,
 include_total=True,
)

 if abstract_rows:
 st.dataframe(
 abstract_rows,
 use_container_width=True,
 hide_index=True,
)
 else:
 st.info(
 "No table abstract rows available."
)

 st.caption(
 "The TOTAL row matches the number of detailed mapping rows below."
)

 st.markdown("### Sheet Mapping Details")

 st.dataframe(
 rows,
 use_container_width=True,
 hide_index=True,
)

def main() -> None:
 st.set_page_config(
 page_title="Schema Listing Mapping",
 layout="wide",
)

 initialize_directories()
 initialize_session_state()

 st.title(
 "Schema Listing Mapping"
)

 st.caption(
 "Upload Schema Listing PDF only and generate DB2 DDL plus "
 "Excel-style mapping."
)

 tabs = st.tabs(
 [
 "Main",
 "Metadata Overview",
 "DB2 DDL",
 "Excel Sheet Mapping",
]
)

 with tabs[0]:

```

```

 render_main_tab()

 with tabs[1]:
 render_metadata_overview_tab()

 with tabs[2]:
 render_ddl_tab()

 with tabs[3]:
 render_excel_sheet_mapping_tab()

if __name__ == "__main__":
 main()

=====
FILE: src\idms_modernizer\ui\upload_page.py
ENCODING: utf-8
=====

from pathlib import Path

import streamlit as st

from idms_modernizer.core.config import (
 settings
)

def render_upload_page():

 st.subheader(
 "Upload IDMS Schema PDF"
)

 uploaded_file = (
 st.file_uploader(
 "Schema PDF",
 type=["pdf"]
)
)

 if uploaded_file:

 save_path = (
 Path(
 settings.input_dir
)
 / uploaded_file.name
)

 with open(
 save_path,
 "wb"
) as file:

 file.write(
 uploaded_file.read()
)

 st.success(
 f"Saved: {save_path}"
)

 return str(save_path)

 return None

=====
FILE: src\tools\audit_hardcoding.py
ENCODING: utf-8
=====

import re

```

```
from pathlib import Path
```

```
SEARCH_TERMS = [
 "0400",
 "0405",
 "0410",
 "0415",
 "0420",
 "0425",
 "0430",
 "0435",
 "0440",
 "0445",
 "0450",
 "0455",
 "0460",
 "DEPARTMENT",
 "EMPLOYEE",
 "EMPOSITION",
 "JOB",
 "OFFICE",
 "COVERAGE",
 "EXPERTISE",
 "NON-HOSP",
 "SKILL",
 "STRUCTURE",
 "DEPT-EMPLOYEE",
 "EMP-EMPOSITION",
 "JOB-EMPOSITION",
 "OFFICE-EMPLOYEE",
 "NEW-DEPT-STORE-DEPARTMENT",
 "OLD-DEPT-ERASE-DEPARTMENT",
 "OLD-LASTNAME-MODIFY-EMPLOYEE",
]
```

```
SKIP_DIRS = {
 ".git",
 ".venv",
 "__pycache__",
 "data",
 "output",
 "temp",
 "logs",
 "tests",
}
```

```
SKIP_FILES = {
 "audit_hardcoding.py",
 "installed.txt",
}
```

```
INCLUDE_SUFFIXES = {
 ".py",
}
```

```
FALSE_POSITIVE_SUBSTRINGS = {
 "STRUCTUREDBLOCKS",
 "CLASS STRUCTUREDBLOCKS",
 "FROM IDMS_DB2_CONVERTER.TRANSFORMERS.STRUCTURED_BLOCKS",
 "IDMS_DB2_CONVERTER.TRANSFORMERS.STRUCTURED_BLOCKS",
}
```

```
def should_skip(
 path: Path,
) -> bool:
 if path.name in SKIP_FILES:
 return True

 parts = set(
 part.lower()
```



```

 for part in path.parts
)

 if parts.intersection(SKIP_DIRS):
 return True

 if path.suffix.lower() not in INCLUDE_SUFFIXES:
 return True

 return False

def strip_docstrings(
 text: str,
) -> str:
 text = re.sub(
 r'(""".*?""")',
 "",
 text,
 flags=re.DOTALL,
)

 text = re.sub(
 r'(\''.*?\')',
 "",
 text,
 flags=re.DOTALL,
)

 return text

def is_likely_comment_line(
 line: str,
) -> bool:
 stripped = line.strip()

 if not stripped:
 return True

 return stripped.startswith(
 (
 "#",
 "*",
 "- ",
)
)

def contains_false_positive(
 line: str,
) -> bool:
 upper_line = line.upper()

 for value in FALSE_POSITIVE_SUBSTRINGS:
 if value in upper_line:
 return True

 return False

def term_pattern(
 term: str,
) -> re.Pattern:
 escaped = re.escape(
 term,
)

 if re.fullmatch(
 r"\d+",
 term,
):
 return re.compile(
 rf"(?!\\d){escaped}(?!\\d)",
 re.IGNORECASE,
)

```

```

return re.compile(
 rf"(?![A-Z0-9_-]){escaped}(?![A-Z0-9_-])",
 re.IGNORECASE,
)

def main() -> None:
 root = Path.cwd()

 findings: list[str] = []

 compiled_terms = [
 (
 term,
 term_pattern(term),
)
 for term in SEARCH_TERMS
]

 for path in root.rglob("*"):
 if not path.is_file():
 continue

 if should_skip(path):
 continue

 try:
 text = path.read_text(
 encoding="utf-8",
 errors="ignore",
)
 except Exception:
 continue

 text_without_docstrings = strip_docstrings(
 text,
)

 for line_number, line in enumerate(
 text_without_docstrings.splitlines(),
 start=1,
):
 if is_likely_comment_line(
 line,
):
 continue

 if contains_false_positive(
 line,
):
 continue

 for term, pattern in compiled_terms:
 if pattern.search(line):
 findings.append(
 f"{path}:{line_number}: {line.strip()}"
)

 if not findings:
 print(
 "No hardcoded demo terms found in scanned Python logic."
)
 return

 print(
 "Potential hardcoded demo terms found in Python logic:"
)

 print()

 for item in findings:
 print(
 item,
)

```

```
if __name__ == "__main__":
 main()
```

```
=====
FILE: test
ENCODING: utf-8
=====
```

```
digraph G { A -> B }
```

```
=====
FILE: uv.lock
ENCODING: utf-8
=====
```

```
version = 1
revision = 3
requires-python = ">=3.12"
resolution-markers = [
 "python_full_version >= '3.15' and sys_platform == 'win32'",
 "python_full_version == '3.14.*' and sys_platform == 'win32'",
 "python_full_version >= '3.15' and sys_platform == 'emscripten'",
 "python_full_version == '3.14.*' and sys_platform == 'emscripten'",
 "python_full_version >= '3.15' and sys_platform == 'darwin'",
 "python_full_version >= '3.15' and platform_machine == 'aarch64' and sys_platform == 'linux'",
 "(python_full_version >= '3.15' and platform_machine != 'aarch64' and sys_platform == 'linux') or (python_full_vers
ion >= '3.15' and sys_platform != 'darwin' and sys_platform != 'emscripten' and sys_platform != 'linux' and sys_platfor
m != 'win32')",
 "python_full_version == '3.14.*' and sys_platform == 'darwin'",
 "python_full_version == '3.14.*' and platform_machine == 'aarch64' and sys_platform == 'linux'",
 "(python_full_version == '3.14.*' and platform_machine != 'aarch64' and sys_platform == 'linux') or (python_full_ve
rsion == '3.14.*' and sys_platform != 'darwin' and sys_platform != 'emscripten' and sys_platform != 'linux' and sys_pla
tform != 'win32')",
 "python_full_version < '3.14' and sys_platform == 'win32'",
 "python_full_version < '3.14' and sys_platform == 'emscripten'",
 "python_full_version < '3.14' and sys_platform == 'darwin'",
 "python_full_version < '3.14' and platform_machine == 'aarch64' and sys_platform == 'linux'",
 "(python_full_version < '3.14' and platform_machine != 'aarch64' and sys_platform == 'linux') or (python_full_versi
on < '3.14' and sys_platform != 'darwin' and sys_platform != 'emscripten' and sys_platform != 'linux' and sys_platform
!= 'win32')",
]
```

```
[[package]]
name = "altair"
version = "6.2.1"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "jinja2" },
 { name = "jsonschema" },
 { name = "narwhals" },
 { name = "packaging" },
 { name = "typing-extensions", marker = "python_full_version < '3.15'" },
]
sdist = { url = "https://files.pythonhosted.org/packages/86/97/9a0dc61efd4f2dee29cb6d8edbbacdb789ce48cbffd98efa2b3ab145
b297/altair-6.2.1.tar.gz", hash = "sha256:ca0298fa20b1a4fae22eff8847b95f74912bd90544013ad36af192119883ea64", size = 766
468, upload-time = "2026-06-05T16:23:36.57Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/dc/78/b556548d92b9e29ae68a86e7b416888820900809e189e39caf308c7d44a3
/altair-6.2.1-py3-none-any.whl", hash = "sha256:bf2fee3733c3a31a588e45b857a2495a88d506970deb87f74e1613f0247446b1", size
= 797498, upload-time = "2026-06-05T16:23:34.799Z" },
]
```

```
[[package]]
name = "annotated-types"
version = "0.7.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/ee/67/531ea369ba64dcff5ec9c3402f9f51bf748cec26dde048a2f973a4ee
a7f5/annotated_types-0.7.0.tar.gz", hash = "sha256:aff07c09a53a08bc8cfcc9c85b05f1aa9a2a6f23728d790723543408344ce89", s
ize = 16081, upload-time = "2024-05-20T21:33:25.928Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/78/b6/6307fbef88d9b5ee7421e68d78a9f162e0da4900bc5f5793f6d3d0e34fb8
/annotated_types-0.7.0-py3-none-any.whl", hash = "sha256:1f02e8b43a8fbbc3f3e0d4f0f4bfc8131bcb4eebe8849b8e5c773f3a1c582a
53", size = 13643, upload-time = "2024-05-20T21:33:24.1Z" },
]
```

```

]

[[package]]
name = "anyio"
version = "4.14.0"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "idna" },
 { name = "typing-extensions", marker = "python_full_version < '3.13'" },
]
sdist = { url = "https://files.pythonhosted.org/packages/1c/b5/001890774a9552aff22502b8da382593109ce0c95314abaebbb116567545/anyio-4.14.0.tar.gz", hash = "sha256:b47c1f9ccf73e67021df785332508f99379c68fa7d0684e8e3492cb1d4b23f89", size = 253586, upload-time = "2026-06-15T22:00:49.021Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/ba/16/9826f089383c593cdfc4a6e5aca94d9e91ae1692c57af82c3b2aa5e810f7/anyio-4.14.0-py3-none-any.whl", hash = "sha256:dd9b7a2a9799ed6552fde617b2c5df02b7fdd7d88392fc48101e51bae46164d9", size = 123506, upload-time = "2026-06-15T22:00:47.595Z" },
]

[[package]]
name = "attrs"
version = "26.1.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/9a/8e/82a0fe20a541c03148528be8cac2408564a6c9a0cc7e9171802bc1d26985/attrs-26.1.0.tar.gz", hash = "sha256:d03ceb89cb322a8fd706d4fb91940737b6642aa36998fe130a9bc96c985eff32", size = 952055, upload-time = "2026-03-19T14:22:25.026Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/64/b4/17d4b0b2a2dc85a6df63d1157e028ed19f90d4cd97c36717afef2bc2f395/attrs-26.1.0-py3-none-any.whl", hash = "sha256:c647aa4a12dfbad9333ca4e71fe62ddc36f4e63b2d260a37a8b83d2f043ac309", size = 67548, upload-time = "2026-03-19T14:22:23.645Z" },
]

[[package]]
name = "blinker"
version = "1.9.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/21/28/9b3f50ce0e048515135495f198351908d99540d69bfdc8c1d15b73dc55ce/blinker-1.9.0.tar.gz", hash = "sha256:b4c2265a7abece45e7cc896e98dbebe6cead56bcf805a3d23136d145f5445bf", size = 22460, upload-time = "2024-11-08T17:25:47.436Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/10/cb/f2ad4230dc2eb1a74edf38f1a38b9b52277f75bef262d8908e60d957e13c/blinker-1.9.0-py3-none-any.whl", hash = "sha256:ba0efaa9080b619ff2f3459d1d500c57bddea4a6b424b60a91141db6fd2f08bc", size = 8458, upload-time = "2024-11-08T17:25:46.184Z" },
]

[[package]]
name = "cachetools"
version = "7.1.4"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/f4/8b/0d3945a13955303b81272f759a0331e54c5c793da455e6f5706b89d2639c/cachetools-7.1.4.tar.gz", hash = "sha256:437f55a4e0c1b01a4f3077cc470e6991d47430970e36fbc77e2be0df4fc1cd6", size = 40085, upload-time = "2026-05-21T22:40:43.376Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/8c/7b/1fc1c09cc0756cf25861a3be10565915953876da48bb228fb9a672b20a42/cachetools-7.1.4-py3-none-any.whl", hash = "sha256:323dc4127934744db5b54eb4924482d7edafbf9554e820d1531c2e08c0e4ef54", size = 16761, upload-time = "2026-05-21T22:40:41.845Z" },
]

[[package]]
name = "certifi"
version = "2026.6.17"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/c9/c7/424b75da314c1045981bd9777432fad05a9e0c69daa4ed7e308bbaffe405/certifi-2026.6.17.tar.gz", hash = "sha256:024c88eeec92ca068db80f02b8b07c9cef7b9fe261d1d535abfd5abd6f6af432", size = 134594, upload-time = "2026-06-17T10:31:07.894Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/ef/2f/c5464532e965badff2f4c4c1a3a83f5697f0d7c407ed0cda44aaa99bb451/certifi-2026.6.17-py3-none-any.whl", hash = "sha256:2227dcbaf0d2f59279d1762dddc37783ed4354594f194ffc31d20f41fc3db", size = 133289, upload-time = "2026-06-17T10:31:06.348Z" },
]

[[package]]
name = "cffi"
version = "2.0.0"
source = { registry = "https://pypi.org/simple" }
dependencies = [

```

```
{ name = "pycparser", marker = "implementation_name != 'PyPy'" },
]
sdist = { url = "https://files.pythonhosted.org/packages/eb/56/b1ba7935a17738ae8453301356628e8147c79dbb825bcb73dc7401f
9846/cffi-2.0.0.tar.gz", hash = "sha256:44d1b590921139fe36001ae048dbdde8214afa20200eda0f64c068cac5d5529", size = 52358
8, upload-time = "2025-09-08T23:24:04.541Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/ea/47/4f61023ea636104d4f16ab488e268b93008c3d0bb76893b1b31db1f96802
/cffi-2.0.0-cp312-cp312-macosx_10_13_x86_64.whl", hash = "sha256:6d02d6655b0e54f54c4ef0b94eb6be0607b70853c45ce98bd278dc
7de718be5d", size = 185271, upload-time = "2025-09-08T23:22:44.795Z" },
 { url = "https://files.pythonhosted.org/packages/df/a2/781b623f57358e360d62cdd7a8c681f074a71d445418a776eef0aadb4ab4
/cffi-2.0.0-cp312-cp312-macosx_11_0_arm64.whl", hash = "sha256:8eca2a813c1cb7ad4fb74d368c2ffbbb4789d377ee5bb8df98373c2c
c0dee76c", size = 181048, upload-time = "2025-09-08T23:22:45.938Z" },
 { url = "https://files.pythonhosted.org/packages/ff/df/a4f0fbd47331ceeba3d37c2e51e9dfc9722498becbeec2bd8bc856c9538a
/cffi-2.0.0-cp312-cp312-manylinux1_i686.manylinux2014_i686.manylinux_2_17_i686.manylinux_2_5_i686.whl", hash = "sha256:
21d1152871b019407d8ac3985f6775c079416c282e431a4da6afe7aefd2bccbe", size = 212529, upload-time = "2025-09-08T23:22:47.34
92Z" },
 { url = "https://files.pythonhosted.org/packages/d5/72/12b5f8d3865bf0f87cf1404d8c374e7487dcf097a1c91c436e72e6badd83
/cffi-2.0.0-cp312-cp312-manylinux2014_aarch64.manylinux_2_17_aarch64.whl", hash = "sha256:b21e08af67b8a103c71a250401c78
d5e0893beff75e28c53c98f4de42f774062", size = 220097, upload-time = "2025-09-08T23:22:48.677Z" },
 { url = "https://files.pythonhosted.org/packages/c2/95/7a135d52a50dfa7c882ab0ac17e8dc11cec9d55d2c18dda414c051c5e69e
/cffi-2.0.0-cp312-cp312-manylinux2014_ppc64le.manylinux_2_17_ppc64le.whl", hash = "sha256:1e3a615586f05fc4065a8b22b8152
f0c1b00cdbc60596d187c2a74f9e3036e4e", size = 207983, upload-time = "2025-09-08T23:22:50.06Z" },
 { url = "https://files.pythonhosted.org/packages/3a/c8/15cb9ada8895957ea171c62dc78ff3e99159ee7adb13c0123c001a2546c1
/cffi-2.0.0-cp312-cp312-manylinux2014_s390x.manylinux_2_17_s390x.whl", hash = "sha256:81afed14892743bbe14dacb9e36d9e0e5
04cd204e0b165062c488942b9718037", size = 206519, upload-time = "2025-09-08T23:22:51.364Z" },
 { url = "https://files.pythonhosted.org/packages/78/2d/7fa73dfa841b5ac06c7b8855cfc18622132e365f5b81d02230333ff26e9e
/cffi-2.0.0-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.whl", hash = "sha256:3e17ed538242334bf70832644a32a7a
ae3d83b57567f9fd60a26257e992b79ba", size = 219572, upload-time = "2025-09-08T23:22:52.902Z" },
 { url = "https://files.pythonhosted.org/packages/07/e0/267e57e387b4ca276b90f0434ff88b2c2241ad72b16d31836adddfd6031b
/cffi-2.0.0-cp312-cp312-musllinux_1_2_aarch64.whl", hash = "sha256:3925dd22fa2b7699ed2617149842d2e6adde22b262fcbfada50e
3d195e4b3a94", size = 222963, upload-time = "2025-09-08T23:22:54.518Z" },
 { url = "https://files.pythonhosted.org/packages/b6/75/1f2747525e06f53efbd878f4d03bac5b859cbc11c633d0fb81432d98a795
/cffi-2.0.0-cp312-cp312-musllinux_1_2_x86_64.whl", hash = "sha256:2c8f814d84194c9ea681642fd164267891702542f028a15fc97d4
674b6206187", size = 221361, upload-time = "2025-09-08T23:22:55.867Z" },
 { url = "https://files.pythonhosted.org/packages/7b/2b/2b6435f76bfef6bbf055596976da087377ede68df465419d192acff00c437
/cffi-2.0.0-cp312-cp312-win32.whl", hash = "sha256:da902562c3e9c550df360bfa53c035b2f241fed6d9aef119048073680ace4a18", s
ize = 172932, upload-time = "2025-09-08T23:22:57.188Z" },
 { url = "https://files.pythonhosted.org/packages/f8/ed/13bd4418627013bec4ed6e54283b1959cf6db888048c7cf4b4c3b5b36002
/cffi-2.0.0-cp312-cp312-win_amd64.whl", hash = "sha256:da68248800ad6320861f129cd9c1bf96ca849a2771a59e0344e88681905916f5
", size = 183557, upload-time = "2025-09-08T23:22:58.351Z" },
 { url = "https://files.pythonhosted.org/packages/95/31/9f7f93ad2f8eff1dbc1c3656d7ca5b5fd8f5b2c9d786b4dcf19b2d02217fa
/cffi-2.0.0-cp312-cp312-win_arm64.whl", hash = "sha256:4671d9dd5ec934cb9a73e7ee9676f9362aba54f7f34910956b84d727b0d73fb6
", size = 177762, upload-time = "2025-09-08T23:22:59.668Z" },
 { url = "https://files.pythonhosted.org/packages/4b/8d/a0a47a0c9e413a658623d014e91e74a50cdd2c423f7ccfd44086ef767f90
/cffi-2.0.0-cp313-cp313-macosx_10_13_x86_64.whl", hash = "sha256:00bdf7acc5f795150faa6957054fbbca2439db2f775ce831222b66
f192f03beb", size = 185230, upload-time = "2025-09-08T23:23:00.879Z" },
 { url = "https://files.pythonhosted.org/packages/4a/d2/a6c0296814556c68ee32009d9c2ad4f85f2707cdecfd7727951ec228005d
/cffi-2.0.0-cp313-cp313-macosx_11_0_arm64.whl", hash = "sha256:45d5e886156860dc35862657e1494b9bae8dfa63bf56796f2fb56e16
79fc0bca", size = 181043, upload-time = "2025-09-08T23:23:02.231Z" },
 { url = "https://files.pythonhosted.org/packages/b0/1e/d22cc63332bd59b06481ceaac49d6c507598642e2230f201649058a7e704
/cffi-2.0.0-cp313-cp313-manylinux1_i686.manylinux2014_i686.manylinux_2_17_i686.manylinux_2_5_i686.whl", hash = "sha256:
07b271772c100085dd28b74fa0cd81c8fb1a3ba18b21e03d7c27f3436a10606b", size = 212446, upload-time = "2025-09-08T23:23:03.47
2Z" },
 { url = "https://files.pythonhosted.org/packages/a9/f5/a2c23eb03b61a0b8747f211eb716446c826ad66818ddc7810cc2cc19b3f2
/cffi-2.0.0-cp313-cp313-manylinux2014_aarch64.manylinux_2_17_aarch64.whl", hash = "sha256:d48a880098c96020b02d5a1f7d925
1308510ce8858940e6fa9ece33f610838b", size = 220101, upload-time = "2025-09-08T23:23:04.792Z" },
 { url = "https://files.pythonhosted.org/packages/f2/7f/e6647792f2c5850d634695bc0e6ab4111ae88e89981d35ac269956605feba
/cffi-2.0.0-cp313-cp313-manylinux2014_ppc64le.manylinux_2_17_ppc64le.whl", hash = "sha256:f93fd8e5c80a4aa1f424d6173f14
a892044054871c771f8566e4008eaa359d2", size = 207948, upload-time = "2025-09-08T23:23:06.127Z" },
 { url = "https://files.pythonhosted.org/packages/cb/1e/a5a1bd6f1fb30f22573f76533de12a00bf274abdc55c8edab639078abb6
/cffi-2.0.0-cp313-cp313-manylinux2014_s390x.manylinux_2_17_s390x.whl", hash = "sha256:dd4f05f54a52fb558f1ba9f5282280669
54fee3ebe629fc1660d874d040ae5a3", size = 206422, upload-time = "2025-09-08T23:23:07.753Z" },
 { url = "https://files.pythonhosted.org/packages/98/df/0a1755e750013a2081e863e7cd37e0cdd02664372c754e5560099eb7aa44
/cffi-2.0.0-cp313-cp313-manylinux2014_x86_64.manylinux_2_17_x86_64.whl", hash = "sha256:c8d3b5532fc71b7a77c09192b4a5a20
0ea992702734a2e9279a37f2478236f26", size = 219499, upload-time = "2025-09-08T23:23:09.648Z" },
 { url = "https://files.pythonhosted.org/packages/50/e1/a969e687fcf9ea58e6e2a928ad5e2dd88cc12f6f0ab477e9971f2309b57c
/cffi-2.0.0-cp313-cp313-musllinux_1_2_aarch64.whl", hash = "sha256:d9b29c1f0ae438d5ee9acb31cadee00a58c46cc9c0b2f9038c6b
0b3470877a8c", size = 222928, upload-time = "2025-09-08T23:23:10.928Z" },
 { url = "https://files.pythonhosted.org/packages/36/54/0362578dd2c9e557a28ac77698ed67323ed5b9775ca9d3fe73fe191bb5d8
/cffi-2.0.0-cp313-cp313-musllinux_1_2_x86_64.whl", hash = "sha256:6d50360be4546678fc1b79ffe7a66265e28667840010348dd69a3
14145807a1b", size = 221302, upload-time = "2025-09-08T23:23:12.42Z" },
 { url = "https://files.pythonhosted.org/packages/eb/6d/bf9bda840d5f1dfdbf0feca87fbbdb64a918a69bca42cfa0ba7b137c48cb8
/cffi-2.0.0-cp313-cp313-win32.whl", hash = "sha256:74a03b9698e198d47562765773b4a8309919089150a0bb17d829ad7b44b60d27", s
ize = 172909, upload-time = "2025-09-08T23:23:14.32Z" },
 { url = "https://files.pythonhosted.org/packages/37/18/6519e1ee6f5a1e579e04b9ddb6f1676c17368a7aba48299c3759bbc3c8b3
/cffi-2.0.0-cp313-cp313-win_amd64.whl", hash = "sha256:19f705ada2530c1167abacb171925dd886168931e0a7b78f5bffcfae5c6b5be75
```

```
", size = 183402, upload-time = "2025-09-08T23:23:15.535Z" },
 { url = "https://files.pythonhosted.org/packages/cb/0e/02ceec9a7d6ee63bb596121c2c8e9b3a9e150936f4fbef6ca1943e6137c/cffi-2.0.0-cp313-cp313-win_arm64.whl", hash = "sha256:256f80b80ca3853f90c21b23ee78cd008713787b1b1e93eae9f3d6a7134abd91", size = 177780, upload-time = "2025-09-08T23:23:16.761Z" },
 { url = "https://files.pythonhosted.org/packages/92/c4/3ce07396253a83250ee98564f8d7e9789fab8e58858f35d07a9a2c78de9f/cffi-2.0.0-cp314-cp314-macosx_10_13_x86_64.whl", hash = "sha256:fc33c5141b55ed366cfaad382df24fe7dcdb686de5be719b207bb248e3053dc5", size = 185320, upload-time = "2025-09-08T23:23:18.087Z" },
 { url = "https://files.pythonhosted.org/packages/59/dd/27e9fa567a23931c838c6b02d0764611c62290062a6d4e8ff7863daf9730/cffi-2.0.0-cp314-cp314-macosx_11_0_arm64.whl", hash = "sha256:c654de545946e0db659b3400168c9ad31b5d29593291482c43e3564effbce13", size = 181487, upload-time = "2025-09-08T23:23:19.622Z" },
 { url = "https://files.pythonhosted.org/packages/d6/43/0e822876f87ea8a4ef95442c3d766a06a51fc5298823f884ef87aaad168c/cffi-2.0.0-cp314-cp314-manylinux2014_aarch64.manylinux_2_17_aarch64.whl", hash = "sha256:24b6f81f1983e6df8db3adc38562c83f7d4a0c36162885ec7f7b77c7dbec97b", size = 220049, upload-time = "2025-09-08T23:23:20.853Z" },
 { url = "https://files.pythonhosted.org/packages/b4/89/76799151d9c2d2d1ead63c2429da9ea9d7aac304603de0c6e8764e6e8e70/cffi-2.0.0-cp314-cp314-manylinux2014_ppc64le.manylinux_2_17_ppc64le.whl", hash = "sha256:12873ca6cb9b0f0d3a0da705d6086fe911591737a59f28b7936bdfed27c0d47c", size = 207793, upload-time = "2025-09-08T23:23:22.08Z" },
 { url = "https://files.pythonhosted.org/packages/bb/dd/3465b14bb9e24ee24cb88c9e3730f6de63111fffe513492bf8c808a3547e/cffi-2.0.0-cp314-cp314-manylinux2014_s390x.manylinux_2_17_s390x.whl", hash = "sha256:d9b97165e8aed9272a6bb17c01e3cc5871a594a446ebdc996e2397a1c1ea8ef", size = 206300, upload-time = "2025-09-08T23:23:23.314Z" },
 { url = "https://files.pythonhosted.org/packages/47/d9/d83e293854571c877a92da46fdec39158f8d7e68da75bf73581225d28e90/cffi-2.0.0-cp314-cp314-manylinux2014_x86_64.manylinux_2_17_x86_64.whl", hash = "sha256:afb8db5439b81cf9c9d0c80404b60c3cc9c3add93e114dcae767f1477cb53775", size = 219244, upload-time = "2025-09-08T23:23:24.541Z" },
 { url = "https://files.pythonhosted.org/packages/2b/0f/1f177e3683aeadd2bb00f7679a16451d302c436b5cbf2505f0ea8146ef59e/cffi-2.0.0-cp314-cp314-musllinux_1_2_aarch64.whl", hash = "sha256:737fe7d37e1a1bffe70bd5754ea763a62a066dc5913ca57e957824b72a85e205", size = 222828, upload-time = "2025-09-08T23:23:26.143Z" },
 { url = "https://files.pythonhosted.org/packages/c6/0f/cafacebd4b040e3119dcb32fed8bdef8dfe94da653155f9d0b9dc660166e/cffi-2.0.0-cp314-cp314-musllinux_1_2_x86_64.whl", hash = "sha256:38100abb9d1b1435bc4cc340bb4489635dc2f0da7456590877030c9b3d40b0c1", size = 220926, upload-time = "2025-09-08T23:23:27.873Z" },
 { url = "https://files.pythonhosted.org/packages/3e/aa/df335faa45b395396fcbcb03de2dfcab242cd61a9900e914fe682a59170b1/cffi-2.0.0-cp314-cp314-win32.whl", hash = "sha256:087067fa8953339c723661eda6b54bc98c5625757ea62e95eb4898ad5e776e9f", size = 175328, upload-time = "2025-09-08T23:23:44.61Z" },
 { url = "https://files.pythonhosted.org/packages/bb/92/882c2d30831744296ce713f0feb4c1cd30f346ef747b530b5318715cc367/cffi-2.0.0-cp314-cp314-win_amd64.whl", hash = "sha256:203a48d1fb583fc7d78a4c6655692963b860a417c0528492a6bc21f1aaefab25", size = 185650, upload-time = "2025-09-08T23:23:45.848Z" },
 { url = "https://files.pythonhosted.org/packages/9f/2c/98ece204b9d35a7366b5b2c6539c350313ca13932143e79dc133ba757104/cffi-2.0.0-cp314-cp314-win_arm64.whl", hash = "sha256:dbd5c7a25a7cb98f5ca55d258b103a2054f859a46ae11aaf23134f9cc0d356ad", size = 180687, upload-time = "2025-09-08T23:23:47.105Z" },
 { url = "https://files.pythonhosted.org/packages/3e/61/c768e4d548bfa607abcbda77423448df8c471f25dbe64fb2ef6d555eae006/cffi-2.0.0-cp314-cp314t-macosx_10_13_x86_64.whl", hash = "sha256:9a67fc9e8eb39039280526379fb3a70023d77caec1852002b4da7e8b270c4dd9", size = 188773, upload-time = "2025-09-08T23:23:29.347Z" },
 { url = "https://files.pythonhosted.org/packages/2c/ea/5f76bce7cf6fcd0ab1a1058b5af899bfbe198bea4d5686da88471ea0336/cffi-2.0.0-cp314-cp314t-macosx_11_0_arm64.whl", hash = "sha256:7a66c7204d8869299919db4d5069a82f1561581af12b11b3c9f48c584eb8743d", size = 185013, upload-time = "2025-09-08T23:23:30.63Z" },
 { url = "https://files.pythonhosted.org/packages/be/b4/c56878d0d1755cf9caa54ba71e5d049479c52f9e4afc230f06822162ab2f/cffi-2.0.0-cp314-cp314t-manylinux2014_aarch64.manylinux_2_17_aarch64.whl", hash = "sha256:7cc09976e8b56f8cebd752f7113ad07752461f48a58cbb44139015ac24954c", size = 221593, upload-time = "2025-09-08T23:23:31.91Z" },
 { url = "https://files.pythonhosted.org/packages/e0/0d/eb704606dfe8033e7128df5e90fee946bbcb64a04fcdad97321309004000/cffi-2.0.0-cp314-cp314t-manylinux2014_ppc64le.manylinux_2_17_ppc64le.whl", hash = "sha256:92b68146a71df78564e4ef48af17551a5ddd142e5190cdf2c5624d0c3ff5b2e8", size = 209354, upload-time = "2025-09-08T23:23:33.214Z" },
 { url = "https://files.pythonhosted.org/packages/d8/19/3c435d727b368ca475fb8742ab97c9cb13a0de600ce86f62eab7fa3eeaa60/cffi-2.0.0-cp314-cp314t-manylinux2014_s390x.manylinux_2_17_s390x.whl", hash = "sha256:b1e74d11748e7e98e2f426ab176d4ed720a64412b6a15054378afdb71e0f37dc", size = 208480, upload-time = "2025-09-08T23:23:34.495Z" },
 { url = "https://files.pythonhosted.org/packages/d0/44/681604464ed9541673e486521497406fadcc15b5217c3e326b061696899a/cffi-2.0.0-cp314-cp314t-manylinux2014_x86_64.manylinux_2_17_x86_64.whl", hash = "sha256:28a3a209b96630bca57cce802da70c266eb08c6e97e5afd61a75611ee6c64592", size = 221584, upload-time = "2025-09-08T23:23:36.096Z" },
 { url = "https://files.pythonhosted.org/packages/25/8e/342a504ff018a2825d395d44d63a767dd8ebc927ebda557fecda3ac33a/cffi-2.0.0-cp314-cp314t-musllinux_1_2_aarch64.whl", hash = "sha256:7553fb2090d71822f02c629afe6042c299edf91ba1bf94951165613553984512", size = 224443, upload-time = "2025-09-08T23:23:37.328Z" },
 { url = "https://files.pythonhosted.org/packages/e1/5e/b666bacbbcb0fbf415ba9988324a132c9a7a0448a9a8f125074671c0f2c3/cffi-2.0.0-cp314-cp314t-musllinux_1_2_x86_64.whl", hash = "sha256:6c6c373cfc5c83a975506110d17457138c8c63016b563cc9ed6e056a82f13ce4", size = 223437, upload-time = "2025-09-08T23:23:38.945Z" },
 { url = "https://files.pythonhosted.org/packages/a0/1d/ec1a60bd1a10daa292d3cd6bb0b359a81607154fb8165f3ec95fe003b85c/cffi-2.0.0-cp314-cp314t-win32.whl", hash = "sha256:1fc9ea04857caf665289b7a75923f2c6ed559b8298a1b8c49e59f7dd95c8481e", size = 180487, upload-time = "2025-09-08T23:23:40.423Z" },
 { url = "https://files.pythonhosted.org/packages/bf/41/4c1168c74fac325c0c8156f04b749c8b6a8f405bbf91413ba088359f60d/cffi-2.0.0-cp314-cp314t-win_amd64.whl", hash = "sha256:d68b6cef7827e8641e8ef16f4494edda8b36104d79773a334beaa1e3521430f6", size = 191726, upload-time = "2025-09-08T23:23:41.742Z" },
 { url = "https://files.pythonhosted.org/packages/ae/3a/dbcec9d1ee0844c679f6bb5d6ad4e9f198b1224f4e7a32825f47f6192b0c/cffi-2.0.0-cp314-cp314t-win_arm64.whl", hash = "sha256:0a1527a803f0a659de1af2e1fd700213caba79377e27e4693648c2923da066f9", size = 184195, upload-time = "2025-09-08T23:23:43.004Z" },
]
```

```
[[package]]
name = "charset-normalizer"
version = "3.4.7"
source = { registry = "https://pypi.org/simple" }
```

```
sdist = { url = "https://files.pythonhosted.org/packages/e7/a1/67fe25fac3c7642725500a3f6cfe5821ad557c3abb11c9d20d12c700
8d3e/charset_normalizer-3.4.7.tar.gz", hash = "sha256:ae89db9e5f98a11a4bf50407d4363e7b09b31e55bc117b4f7d80aab97ba009e5"
, size = 144271, upload-time = "2026-04-02T09:28:39.342Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/0c/eb/4fc8d0a7110eb5fc9cc161723a34a8a6c200ce3b4fbf681bc86feee22308
/charset_normalizer-3.4.7-cp312-cp312-macosx_10_13_universal2.whl", hash = "sha256:eca9705049ad3c7345d574e3510665cb2cf8
44c2f2dcfe675332677f081cbd46", size = 311328, upload-time = "2026-04-02T09:26:24.331Z" },
 { url = "https://files.pythonhosted.org/packages/f8/e3/0fad706008ac9d7b9b5be6dc767c05f9d3e5df51744ce4cc9605de7b9f4
/charset_normalizer-3.4.7-cp312-cp312-manylinux2014_aarch64.manylinux_2_17_aarch64.manylinux_2_28_aarch64.whl", hash =
"sha256:6178f72c5508bfc5fd446a5905e698c6212932f25bcd4b47a757a50605a90e2", size = 208061, upload-time = "2026-04-02T09:
26:25.568Z" },
 { url = "https://files.pythonhosted.org/packages/42/f0/3dd1045c47f4a4604df85ec18ad093912ae1344ac706993aff91d38773a2
/charset_normalizer-3.4.7-cp312-cp312-manylinux2014_ppc64le.manylinux_2_17_ppc64le.manylinux_2_28_ppc64le.whl", hash =
"sha256:e1421b502d83040e6d7fb2fb18dff63957f720da3d77b2fbd3187ceb63755d7b", size = 229031, upload-time = "2026-04-02T09:
26:26.865Z" },
 { url = "https://files.pythonhosted.org/packages/dc/67/675a46eb016118a2fbde5a277a5d15f4f69d5f3f5f338e5ee2f8948fcf43
/charset_normalizer-3.4.7-cp312-cp312-manylinux2014_s390x.manylinux_2_17_s390x.manylinux_2_28_s390x.whl", hash = "sha25
6:edac0f1ab77644605be2cbb5a25e6b7f630731fc42b34cb0f634be1a6eface56a", size = 225239, upload-time = "2026-04-02T09:26:28.
044Z" },
 { url = "https://files.pythonhosted.org/packages/4b/f8/d0118a2f5f23b02cd166fa385c60f9b0d4f9194f574e2b31cef350ad7223
/charset_normalizer-3.4.7-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl", hash = "sh
a256:5649fd1c7bade02f320a462fdefdb4bd3ce036065836d4f42e0de958038e116", size = 216589, upload-time = "2026-04-02T09:26:
29.239Z" },
 { url = "https://files.pythonhosted.org/packages/b1/f1/6d2b0b261b6c4ceef0fcb0d17a01cc5bc53586c2d4796fa04b5c540bc13d
/charset_normalizer-3.4.7-cp312-cp312-manylinux_2_31_armv7l.whl", hash = "sha256:203104ed3e428044fd943bc4bf45fa73c07303
91f9621e37fe39ecf477b128cb", size = 202733, upload-time = "2026-04-02T09:26:30.5Z" },
 { url = "https://files.pythonhosted.org/packages/6f/c0/7b1f943f7e87cc3db9626ba17807d042c38645f0a1d4415c7a14afb5591f
/charset_normalizer-3.4.7-cp312-cp312-manylinux_2_31_riscv64.manylinux_2_39_riscv64.whl", hash = "sha256:298930cec56029
e05497a76988377cbd7457ba864beee92ad7e844fe74cd1f1", size = 212652, upload-time = "2026-04-02T09:26:31.709Z" },
 { url = "https://files.pythonhosted.org/packages/38/dd/5a9ab159fe45c6e72079398f277b7d2b523e7f716acc489726115a910097
/charset_normalizer-3.4.7-cp312-cp312-musllinux_1_2_aarch64.whl", hash = "sha256:708838739abf24b2ceb208d0e22403dd018fae
ef86ddac04319a62ae884c4f15", size = 211229, upload-time = "2026-04-02T09:26:33.282Z" },
 { url = "https://files.pythonhosted.org/packages/d5/ff/531a1cad5ca85d1c1a8b69cb71abfd6d85c0291580146fda7c82857caa1
/charset_normalizer-3.4.7-cp312-cp312-musllinux_1_2_armv7l.whl", hash = "sha256:0f7eb884681e3938906ed0434f20c63046eacd0
111c4ba96f27b76084cd679f5", size = 203552, upload-time = "2026-04-02T09:26:34.845Z" },
 { url = "https://files.pythonhosted.org/packages/c1/4c/a5fb52d528a8ca41f7598cb619409ece30a169fbdf9cdce592e53b46c3a6
/charset_normalizer-3.4.7-cp312-cp312-musllinux_1_2_ppc64le.whl", hash = "sha256:4dc1e73c36828f982bfe79fadf5919923f8a6f
4df2860804db9a98c48824ce8d", size = 230806, upload-time = "2026-04-02T09:26:36.152Z" },
 { url = "https://files.pythonhosted.org/packages/59/7a/071feed8124111a32b316b33ae4de83d36923039ef8cf48120266844285b
/charset_normalizer-3.4.7-cp312-cp312-musllinux_1_2_riscv64.whl", hash = "sha256:aed52fea0513bac0ccde438c188c8a471c4e0f
457c2dd20cdbf6ea7a50046c7", size = 212316, upload-time = "2026-04-02T09:26:37.672Z" },
 { url = "https://files.pythonhosted.org/packages/fd/35/f7dba3994312d7ba508e041eaac39a36b120f32d4c8662b8814dab876431
/charset_normalizer-3.4.7-cp312-cp312-musllinux_1_2_s390x.whl", hash = "sha256:fea24543955a6a729c45a73fe90e08c743f0b333
4bbf3201e6c4bc1b0c7fa464", size = 227274, upload-time = "2026-04-02T09:26:38.93Z" },
 { url = "https://files.pythonhosted.org/packages/8a/2d/a572df5c9204ab7688ec1edc895a73ebdd3b023bb07364710b05dd1c9be
/charset_normalizer-3.4.7-cp312-cp312-musllinux_1_2_x86_64.whl", hash = "sha256:bb6d88045545b26da47aa879dd4a89a71d1dce0
f0e549b1abcb31dfe4a8eac49", size = 218468, upload-time = "2026-04-02T09:26:40.17Z" },
 { url = "https://files.pythonhosted.org/packages/86/eb/890922a8b03a568ca2f336c36585a4713c55d4d67bf0f0c78924be6315ca
/charset_normalizer-3.4.7-cp312-cp312-win32.whl", hash = "sha256:2257141f39fe65a3fdf38aeccae4b953e5f3b3324f4ff0daf9f15b
8518666a2c", size = 148460, upload-time = "2026-04-02T09:26:41.416Z" },
 { url = "https://files.pythonhosted.org/packages/35/d9/0e7dff06c5ab081f75b1b786f0aefc88365825dfcd0ac544bdb7b2b6853
/charset_normalizer-3.4.7-cp312-cp312-win_amd64.whl", hash = "sha256:5ed6ab538499c8644b8a3e18debabacd7ce684f3fa91cf86752
1a7a0279cab2d6", size = 159330, upload-time = "2026-04-02T09:26:42.554Z" },
 { url = "https://files.pythonhosted.org/packages/9e/5d/481bcc2a7c88ea6b0878c299547843b2521ccbc40980cb406267088bc701
/charset_normalizer-3.4.7-cp312-cp312-win_arm64.whl", hash = "sha256:56be790f86bfb2c98fb742ce566dfb4816e5a83384616ab59c
49e0604d49c51d", size = 147828, upload-time = "2026-04-02T09:26:44.075Z" },
 { url = "https://files.pythonhosted.org/packages/c1/3b/66777e39d38a1ddc77ee606be4ec6d8cbd4c801f65e5a1b6f2b11b8346dd
/charset_normalizer-3.4.7-cp313-cp313-macosx_10_13_universal2.whl", hash = "sha256:f496c9c3cc02230093d8330875c4c3cdfc3b
73612a5fd921c65d39cbcef08063", size = 309627, upload-time = "2026-04-02T09:26:45.198Z" },
 { url = "https://files.pythonhosted.org/packages/2e/4e/b7f84e617b4854ade48a1b7915c8ccfadeba444d2a18c291f696e37f0d3b
/charset_normalizer-3.4.7-cp313-cp313-manylinux2014_aarch64.manylinux_2_17_aarch64.manylinux_2_28_aarch64.whl", hash =
"sha256:0ea948db76d31190bf08bd371623927ee1339d5f2a0b4b1b4a4439a65298703c", size = 207008, upload-time = "2026-04-02T09:
26:46.824Z" },
 { url = "https://files.pythonhosted.org/packages/c4/bb/ec73c0257c9e11b268f018f068f5d00aa0ef8c8b09f7753ebd5f2880e248
/charset_normalizer-3.4.7-cp313-cp313-manylinux2014_ppc64le.manylinux_2_17_ppc64le.manylinux_2_28_ppc64le.whl", hash =
"sha256:a277ab8928b9f299723bc1a2dabb1265911b1a76341f90a510368ca44ad9ab66", size = 228303, upload-time = "2026-04-02T09:
26:48.397Z" },
 { url = "https://files.pythonhosted.org/packages/85/fb/32d1f5033484494619f701e719429c69b766bfc4dbc61aa9e9c8c166528b
/charset_normalizer-3.4.7-cp313-cp313-manylinux2014_s390x.manylinux_2_17_s390x.manylinux_2_28_s390x.whl", hash = "sha25
6:3bec022aec2c514d9cf199522a802bd007cd588ab17ab2525f20f9c34d067c18", size = 224282, upload-time = "2026-04-02T09:26:49.
684Z" },
 { url = "https://files.pythonhosted.org/packages/fa/07/330e3a0dda4c404d6da83b327270906e9654a24f6c546dc886a0eb0fffb23
/charset_normalizer-3.4.7-cp313-cp313-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl", hash = "sh
a256:e044c39e41b92c845bc815e5ae4230804e8e7bc29e399b0437d64222d92809dd", size = 215595, upload-time = "2026-04-02T09:26:
50.915Z" },
 { url = "https://files.pythonhosted.org/packages/e3/7c/fc890655786e423f02556e0216d4b8c6bcb6bdfa890160dc66bf52dee468
```

/charset\_normalizer-3.4.7-cp313-cp313-manylinux\_2\_31\_armv7l.whl", hash = "sha256:f495a1652cf3fbab2eb0639776dad966c2fb874d79d87ca07f9d5f059b8bd215", size = 201986, upload-time = "2026-04-02T09:26:52.197Z" },  
 { url = "https://files.pythonhosted.org/packages/d8/97/bfb18b3db2aed3b90cf54dc292ad79fdd5ad65c4eae54099475cbeadd0d/charset\_normalizer-3.4.7-cp313-cp313-manylinux\_2\_31\_riscv64.manylinux\_2\_39\_riscv64.whl", hash = "sha256:e712b419df8ba5e42b226c510472b37bd57b38e897d3eca5e8cfd410a29fa859", size = 211711, upload-time = "2026-04-02T09:26:53.49Z" },  
 { url = "https://files.pythonhosted.org/packages/6f/a5/a581c13798546a7fd557c82614a5c65a13df2157e9ad6373166d2a3e645d/charset\_normalizer-3.4.7-cp313-cp313-musllinux\_1\_2\_aarch64.whl", hash = "sha256:7804338df6fcc08105c7745f1502ba68d900f45fd770d5bdd5288ddcc8a42d8", size = 210036, upload-time = "2026-04-02T09:26:54.975Z" },  
 { url = "https://files.pythonhosted.org/packages/8c/bf/b3ba5bcb478e4193d517644b0fb2bf5497fbceaa7a1bc0f4d5b50953861/charset\_normalizer-3.4.7-cp313-cp313-musllinux\_1\_2\_armv7l.whl", hash = "sha256:481551899c856c704d58119b5025793fa6730ad3571971af568f66d2424bb5", size = 202998, upload-time = "2026-04-02T09:26:56.303Z" },  
 { url = "https://files.pythonhosted.org/packages/e7/4e/23efd79b65d314fa320ec6017b4b5834d5c12a58ba4610aa353af2e2f577/charset\_normalizer-3.4.7-cp313-cp313-musllinux\_1\_2\_ppc64le.whl", hash = "sha256:f59099f9b66f0d7145115e6f80dd8b1d847176df89b234a5a6b3f00437aa0832", size = 230056, upload-time = "2026-04-02T09:26:57.554Z" },  
 { url = "https://files.pythonhosted.org/packages/b9/9f/1e1941bc3f0e01df116e68dc37a55c4d249df5e6fa77f008841aef68264f/charset\_normalizer-3.4.7-cp313-cp313-musllinux\_1\_2\_riscv64.whl", hash = "sha256:f59ad4c0e8f6bba240a9bb85504faa1ab438237199d4cce5f622761507b8f6a6", size = 211537, upload-time = "2026-04-02T09:26:58.843Z" },  
 { url = "https://files.pythonhosted.org/packages/80/0f/088cbb3020d44428964a6c97fedfb1b9550396bf6d278330281e8b709c/charset\_normalizer-3.4.7-cp313-cp313-musllinux\_1\_2\_s390x.whl", hash = "sha256:3dedcc22d73ec993f42055eff4fcfed9318d1eeb9a6606c55892a26964964e48", size = 226176, upload-time = "2026-04-02T09:27:00.437Z" },  
 { url = "https://files.pythonhosted.org/packages/6a/9f/130394f9bbe06f4f63e22641d32fc9b202b7e251c9aef4db044324dac493/charset\_normalizer-3.4.7-cp313-cp313-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:64f02c6841d7d83f832cd97ccf8eb8a906d06eb95d5276069175c696b024b60a", size = 217723, upload-time = "2026-04-02T09:27:02.021Z" },  
 { url = "https://files.pythonhosted.org/packages/73/55/c469897448a06e49f8fa03f6caae97074fde823f432a98f979cc42b90e69/charset\_normalizer-3.4.7-cp313-cp313-win32.whl", hash = "sha256:4042d5c8f957e15221d423ba781e85d553722fc4113f523f2feb7b188cc34c5e", size = 148085, upload-time = "2026-04-02T09:27:03.192Z" },  
 { url = "https://files.pythonhosted.org/packages/5d/78/1b74c5bb3f99b77a1715c91b3e0b5bdb6fe302d95ace4f5b1bec37b0167/charset\_normalizer-3.4.7-cp313-cp313-win\_amd64.whl", hash = "sha256:3946fa46a0cf3e4c8b1cc52f56bb536310d34f25f01ca9b6c16afa767dab110", size = 158819, upload-time = "2026-04-02T09:27:04.454Z" },  
 { url = "https://files.pythonhosted.org/packages/68/86/46bd42279d323deb8687c4a5a811fd548cb7d1de10cf6535d099877a9a9f/charset\_normalizer-3.4.7-cp313-cp313-win\_arm64.whl", hash = "sha256:80d04837f55fc81da168b98de4f4b797ef007fc8a79ab71c6ec9bc4dd662b15b", size = 147915, upload-time = "2026-04-02T09:27:05.971Z" },  
 { url = "https://files.pythonhosted.org/packages/97/c8/c67bc8c70e19ef1960b97b22ed2a1567711de46c4ddf19799923adc836c2/charset\_normalizer-3.4.7-cp314-cp314-macosx\_10\_15\_universal2.whl", hash = "sha256:c36c333c39be2dbca264d780333c896ab8fa7d4d6f0ab7edb7dfd7aea6e98c0", size = 309234, upload-time = "2026-04-02T09:27:07.194Z" },  
 { url = "https://files.pythonhosted.org/packages/99/85/c091fdee33f20de70d6c8b522743b6f831a2f1cd3ff86de4c6a827c48a76/charset\_normalizer-3.4.7-cp314-cp314-manylinux2014\_aarch64.manylinux\_2\_17\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:1c2aed2e5e41f24ea8ef1590b8e848a79b56f3a5564a65ceec43c9d692dc7d8a", size = 208042, upload-time = "2026-04-02T09:27:08.749Z" },  
 { url = "https://files.pythonhosted.org/packages/87/1c/ab2ce611b984d2fd5d86a5a8a19c1ae26acac6bad967da4967562c75114d/charset\_normalizer-3.4.7-cp314-cp314-manylinux2014\_ppc64le.manylinux\_2\_17\_ppc64le.manylinux\_2\_28\_ppc64le.whl", hash = "sha256:54523e136b894806c0fa0bc7b1b50c32c186f2fcee897a495406bb6e311d2b", size = 228706, upload-time = "2026-04-02T09:27:09.951Z" },  
 { url = "https://files.pythonhosted.org/packages/a8/29/2b1d2cb00bf085f59d29eb773ce58ec2d325430f8c216804a0a5cd83bca/charset\_normalizer-3.4.7-cp314-cp314-manylinux2014\_s390x.manylinux\_2\_17\_s390x.manylinux\_2\_28\_s390x.whl", hash = "sha256:715479b9a2802ecac752a3b0efa2b0b60285cf962ee38414211abdfccc233b41", size = 224727, upload-time = "2026-04-02T09:27:11.175Z" },  
 { url = "https://files.pythonhosted.org/packages/47/5c/032c2d5a07fe4d4855fea851209cca2b6f03eb6bd4e3afdb3358386a684/charset\_normalizer-3.4.7-cp314-cp314-manylinux2014\_x86\_64.manylinux\_2\_17\_x86\_64.manylinux\_2\_28\_x86\_64.whl", hash = "sha256:bd6c2a1c7573c64738d716488d2cdd3c00e340e4835707d8fdb8dc1a66ef164e", size = 215882, upload-time = "2026-04-02T09:27:12.446Z" },  
 { url = "https://files.pythonhosted.org/packages/2c/c2/356065d5a8b78ed04499cae5f339f091946a6a74f91e03476c33f0ab7100/charset\_normalizer-3.4.7-cp314-cp314-manylinux\_2\_31\_armv7l.whl", hash = "sha256:c45e9440fb78f8ddabc7f14b68f936737a121355bf59f3907f4e17721b9d1aae", size = 200860, upload-time = "2026-04-02T09:27:13.721Z" },  
 { url = "https://files.pythonhosted.org/packages/0c/cd/a32a84217ced5039f53b29f460962abb2d4420def55afabe45b1c3c7483d/charset\_normalizer-3.4.7-cp314-cp314-manylinux\_2\_31\_riscv64.manylinux\_2\_39\_riscv64.whl", hash = "sha256:3534e7dcdbcf757da6b85a0bbfb5b6868786d5982dd959b065e65481644817a18", size = 211564, upload-time = "2026-04-02T09:27:15.272Z" },  
 { url = "https://files.pythonhosted.org/packages/44/86/58e6f13ce26cc3b8f4a36b94a0f22ae2f00a72534520f4ae6857c4b81f89/charset\_normalizer-3.4.7-cp314-cp314-musllinux\_1\_2\_aarch64.whl", hash = "sha256:e8ac484bf18ce6975760921bb6148041faa8fe0547200386ea0b52b5d27bf7b", size = 211276, upload-time = "2026-04-02T09:27:16.834Z" },  
 { url = "https://files.pythonhosted.org/packages/8f/fe/d17c32dc72e17e155e06883efa84514ca375f8a528ba2546bee73fc4df81/charset\_normalizer-3.4.7-cp314-cp314-musllinux\_1\_2\_armv7l.whl", hash = "sha256:a5fe03b42827c13cdcc0d8e6c0247b6a6d4b5e3cdc53fd1749f5896adcdc2356", size = 201238, upload-time = "2026-04-02T09:27:18.229Z" },  
 { url = "https://files.pythonhosted.org/packages/6a/29/f33daa50b06525a237451cbb6c69da366c381a3dadcd833fa5676bc468b3/charset\_normalizer-3.4.7-cp314-cp314-musllinux\_1\_2\_ppc64le.whl", hash = "sha256:2d6eb928e13016cea4f1f21d1e10c1cebd5a421bc57ddfb5b1142ae3f86824fab", size = 230189, upload-time = "2026-04-02T09:27:19.445Z" },  
 { url = "https://files.pythonhosted.org/packages/b6/6e/52c84015394a6a0bdcd435210a7e944c5f94ea1055f5cc5d56c5fe368e7b/charset\_normalizer-3.4.7-cp314-cp314-musllinux\_1\_2\_riscv64.whl", hash = "sha256:e74327fb75de8986940def6e8dee4f127cc9752bee7355bb323cc5b2659b6d46", size = 211352, upload-time = "2026-04-02T09:27:20.79Z" },  
 { url = "https://files.pythonhosted.org/packages/8c/d7/4353be581b373033fb9198bf1da3cf8f09c1082561e8e922aa7b39bf9fe8/charset\_normalizer-3.4.7-cp314-cp314-musllinux\_1\_2\_s390x.whl", hash = "sha256:d6038d37043bcd98a66e68d3aa2b6a35505dc01328cd65217cefe82f25def44", size = 227024, upload-time = "2026-04-02T09:27:22.063Z" },  
 { url = "https://files.pythonhosted.org/packages/30/45/99d18aa925bd1740098ccd3060e238e21115ffbfdbcf8f3ece837d0ace6c/charset\_normalizer-3.4.7-cp314-cp314-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:7579e913a5339fb8fa133f6bbcf8e6749696206cf05acd8dca71a1b436d8e72", size = 217869, upload-time = "2026-04-02T09:27:23.486Z" },  
 { url = "https://files.pythonhosted.org/packages/5c/05/5ee478aa53f4bb7996482153d4bfe1b89e0f087f0ab6b294fcf92d595873



```

/charset_normalizer-3.4.7-cp314-cp314-win32.whl", hash = "sha256:5b77459df20e08151cd6f8b9ef8ef1f961ef73d85c21a555c7eed5
b79410ec10", size = 148541, upload-time = "2026-04-02T09:27:25.146Z" },
 { url = "https://files.pythonhosted.org/packages/48/77/72dcb0921b2ce86420b2d79d454c7022bf5be40202a2a07906b9f2a35c97
/charset_normalizer-3.4.7-cp314-cp314-win_amd64.whl", hash = "sha256:92a0a01ead5e668468e952e4238cccd7c537364eb7d851ab14
4ab6627dbbe12f", size = 159634, upload-time = "2026-04-02T09:27:26.642Z" },
 { url = "https://files.pythonhosted.org/packages/c6/a3/c2369911cd72f02386e4e340770f6e158c7980267da16af8f668217abaa0
/charset_normalizer-3.4.7-cp314-cp314-win_arm64.whl", hash = "sha256:67f6279d125ca0046a7fd386d01b311c6363844deac3e5b069
b514ba3e63c246", size = 148384, upload-time = "2026-04-02T09:27:28.271Z" },
 { url = "https://files.pythonhosted.org/packages/94/09/7e8a7f73d24dba1f0035fbbf014d2c36828fc1bf9c88f84093e57d315935
/charset_normalizer-3.4.7-cp314-cp314t-macosx_10_15_universal2.whl", hash = "sha256:effc3f449787117233702311a1b7d8f59cb
a9ced946ba727bdc329ec69028e24", size = 330133, upload-time = "2026-04-02T09:27:29.474Z" },
 { url = "https://files.pythonhosted.org/packages/8d/da/96975ddb11f8e977f706f45cddd8540fd8242f71ecdb5d18a80723dcf62c
/charset_normalizer-3.4.7-cp314-cp314t-manylinux2014_aarch64.manylinux_2_17_aarch64.manylinux_2_28_aarch64.whl", hash =
"sha256:fbccdc05410c9ee21bbf16a35f4c1d16123dcdeb8a1d38f33654fa21d0234f79", size = 216257, upload-time = "2026-04-02T09
:27:30.793Z" },
 { url = "https://files.pythonhosted.org/packages/e5/e8/1d63bf8ef2d388e95c64b2098f45f84758f6d102a087552da1485912637b
/charset_normalizer-3.4.7-cp314-cp314t-manylinux2014_ppc64le.manylinux_2_17_ppc64le.manylinux_2_28_ppc64le.whl", hash =
"sha256:733784b6d6def852c814bce5f318d25da2ee65dd4839a0718641c696e09a2960", size = 234851, upload-time = "2026-04-02T09
:27:32.44Z" },
 { url = "https://files.pythonhosted.org/packages/9b/40/e5ff04233e70da2681fa43969ad6f66ca5611d7e669be0246c4c7aaf6dc8
/charset_normalizer-3.4.7-cp314-cp314t-manylinux2014_s390x.manylinux_2_17_s390x.manylinux_2_28_s390x.whl", hash = "sha2
56:a89c23ef8d2c6b27fd200a42aa4ac72786e7c60d40efdc76e6011260b6e949c4", size = 233393, upload-time = "2026-04-02T09:27:34
.03Z" },
 { url = "https://files.pythonhosted.org/packages/be/c1/06c6c49d5a5450f76899992f1ee40b41d076aee9279b49cf9974d2f313d5
/charset_normalizer-3.4.7-cp314-cp314t-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl", hash = "s
ha256:6c114670c45346afedc0d947faf3c7f701051d2518b943679c8ff88befe14f8e", size = 223251, upload-time = "2026-04-02T09:27
:35.369Z" },
 { url = "https://files.pythonhosted.org/packages/2b/9f/f2ff16fb050946169e3e1f82134d107e5d4ae72647ec8a1b1446c148480f
/charset_normalizer-3.4.7-cp314-cp314t-manylinux_2_31_armv7l.whl", hash = "sha256:a180c5e59792af262bf263b21a3c49353f259
45d8d9f70628e73de370d55e1e1", size = 206609, upload-time = "2026-04-02T09:27:36.661Z" },
 { url = "https://files.pythonhosted.org/packages/69/d5/a527c0cd8d64d2eab7459784fb4169a0ac76e5a6fc5237337982fd61347e
/charset_normalizer-3.4.7-cp314-cp314t-manylinux_2_31_riscv64.manylinux_2_39_riscv64.whl", hash = "sha256:3c9a494bc5ec7
7d43cea229c4f6db1e4d8fe7e1bbffa8b6f0f0032430ff8ab44", size = 220014, upload-time = "2026-04-02T09:27:38.019Z" },
 { url = "https://files.pythonhosted.org/packages/7e/80/8a7b8104a3e203074dc9aa2c613d4b726c0e136bad1cc734594b02867972
/charset_normalizer-3.4.7-cp314-cp314t-musllinux_1_2_aarch64.whl", hash = "sha256:8d828b6667a32a728a1ad1d93957cdf37489c
57b97ae6c4de2860fa749b8fc1e", size = 218979, upload-time = "2026-04-02T09:27:39.37Z" },
 { url = "https://files.pythonhosted.org/packages/02/9a/b759b503d507f375b2b5c153e4d2ee0a75aa215b7f2489cf314f4541f2c0
/charset_normalizer-3.4.7-cp314-cp314t-musllinux_1_2_armv7l.whl", hash = "sha256:cf1493cd8607bec4d8a7b9b004e699cf8f910
3a9284cc94962cb73d20f9d4a3", size = 209238, upload-time = "2026-04-02T09:27:40.722Z" },
 { url = "https://files.pythonhosted.org/packages/c2/4e/0f3f5d47b86bdb79256e7290b26ac847a2832d9a4033f7eb2cd4bcf4bb5b
/charset_normalizer-3.4.7-cp314-cp314t-musllinux_1_2_ppc64le.whl", hash = "sha256:0c96c3b819b5c3e9e165495db84d41914d689
4d55181d2d108cc1a69bfc9cce0", size = 236110, upload-time = "2026-04-02T09:27:42.33Z" },
 { url = "https://files.pythonhosted.org/packages/96/23/bce28734eb3ed2c91dcf93abeb8a5cfc393a7b2749725030bb630e554fdd8
/charset_normalizer-3.4.7-cp314-cp314t-musllinux_1_2_riscv64.whl", hash = "sha256:752a45dc4a6934060b3b0dab47e04edc33265
75f82be64bc4fc293914566503e", size = 219824, upload-time = "2026-04-02T09:27:43.924Z" },
 { url = "https://files.pythonhosted.org/packages/2c/6f/6e897c6984cc4d41af319b077f2f600fc8214eb2fe2d6bcb79141b882400
/charset_normalizer-3.4.7-cp314-cp314t-musllinux_1_2_s390x.whl", hash = "sha256:8778f0c7a52e56f75d12dae53ae320fae900a8b
9b4164b981b9c5ce059cd1fcb", size = 233103, upload-time = "2026-04-02T09:27:45.348Z" },
 { url = "https://files.pythonhosted.org/packages/76/22/ef7bd0fe480a0ae9b656189ec00744b60933f68b4f42a7bb06589f6f576a
/charset_normalizer-3.4.7-cp314-cp314t-musllinux_1_2_x86_64.whl", hash = "sha256:ce3412f1e31eb81ea42f4169ed94861c56e6
43189e1e75f0041f3fe7020abe", size = 225194, upload-time = "2026-04-02T09:27:46.706Z" },
 { url = "https://files.pythonhosted.org/packages/c5/a7/0e0ab3e0b5bc1219bd80a6a0d4d72ca74d9250cb2382b7c699c147e06017
/charset_normalizer-3.4.7-cp314-cp314t-win32.whl", hash = "sha256:c03a41a8784091e67a39648f70c5f97b5b6a37f216896d44d2cdc
b82615339a0", size = 159827, upload-time = "2026-04-02T09:27:48.053Z" },
 { url = "https://files.pythonhosted.org/packages/7a/1d/29d32e0fb40864b1f878c7f5a0b343ae676c6e2b271a2d55cc3a152391da
/charset_normalizer-3.4.7-cp314-cp314t-win_amd64.whl", hash = "sha256:03853ed82eeebbce3c2abfdbc98c96dc205f32a79627688ac
9a27370ea61a49c", size = 174168, upload-time = "2026-04-02T09:27:49.795Z" },
 { url = "https://files.pythonhosted.org/packages/de/32/d92444ad05c7a6e41fb2036749777c163baf7a0301a040cb672d6b2b1ae9
/charset_normalizer-3.4.7-cp314-cp314t-win_arm64.whl", hash = "sha256:c35abb8bfff0185efac5878da64c45dafd2b37fb0383add1b
e155a763c1f083d", size = 153018, upload-time = "2026-04-02T09:27:51.116Z" },
 { url = "https://files.pythonhosted.org/packages/db/8f/61959034484a4a7c527811f4721e75d02d653a35afb0b6054474d8185d4c
/charset_normalizer-3.4.7-py3-none-any.whl", hash = "sha256:3dce51d0f5e7951f8bb4900c257dad282f49190fdbbecc4ba99bcc41fe
f404d", size = 61958, upload-time = "2026-04-02T09:28:37.794Z" },
]

[[package]]
name = "click"
version = "8.4.1"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "colorama", marker = "sys_platform == 'win32'" },
]
sdist = { url = "https://files.pythonhosted.org/packages/9b/98/518d8e508100768423226f475082b30087d0f585e8457db08729825
9f49/click-8.4.1.tar.gz", hash = "sha256:918db5633eddf6b41c32d4f454bf0de810065c74e3f7dbf8ee5452f8be88d3e96", size = 3530
07, upload-time = "2026-05-22T04:08:37.769Z" }
wheels = [

```

```

{ url = "https://files.pythonhosted.org/packages/c7/0d/67e5b4109ea4a837e80daa87c2c696711955e40449a97e8926672534def2
/click-8.4.1-py3-none-any.whl", hash = "sha256:482be17c6991b8c19c5429a1e995d9b0efdbb63172824c41f99965dc0ade8ec2", size
= 116639, upload-time = "2026-05-22T04:08:35.262" },
]

[[package]]
name = "colorama"
version = "0.4.6"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/d8/53/6f443c9a4a8358a93a6792e2acffbb9d9d5cb0a5cfd8802644b7b1c9a
02e4/colorama-0.4.6.tar.gz", hash = "sha256:08695f5cb7ed6e0531a20572697297273c47b8cae5a63ffc6d6ed5c201be6e44", size = 2
7697, upload-time = "2022-10-25T02:36:22.414Z" }
wheels = [
{ url = "https://files.pythonhosted.org/packages/d1/d6/3965ed04c63042e047cb6a3e6ed1a63a35087b6a609aa3a15ed8ac56c221
/colorama-0.4.6-py2.py3-none-any.whl", hash = "sha256:4f1d9991f5acc0ca119f9d443620b77f9d6b33703e51011c16baf57afb285fc6"
, size = 25335, upload-time = "2022-10-25T02:36:20.889Z" },
]

[[package]]
name = "cryptography"
version = "49.0.0"
source = { registry = "https://pypi.org/simple" }
dependencies = [
{ name = "cffi", marker = "platform_python_implementation != 'PyPy'" },
]
sdist = { url = "https://files.pythonhosted.org/packages/1f/99/d1c90d6041656cc6ee229dc99cd67fd0cd5aec3c5f7d72fffc27cc75
0054/cryptography-49.0.0.tar.gz", hash = "sha256:f89660a348f4f78a92366240a61404e337586ef7f5909a2fef59ca88ef505493", siz
e = 854345, upload-time = "2026-06-12T20:02:30.512Z" }
wheels = [
{ url = "https://files.pythonhosted.org/packages/9b/22/adf66990e63584a68dfb50c24f48a125c07b1699899381c8151e63ed458c
/cryptography-49.0.0-cp311-abi3-macosx_11_0_arm64.whl", hash = "sha256:966fe0e9c67490071f14c0d2b1cb2dfb3023c5ce39457343
931415f08382f2db", size = 4032100, upload-time = "2026-06-12T20:02:32.143Z" },
{ url = "https://files.pythonhosted.org/packages/09/41/3797cfaf69cae04a13ee78ebd83f0678d9c02b4779d21ce24445326f1a69
/cryptography-49.0.0-cp311-abi3-manylinux2014_aarch64.manylinux_2_17_aarch64.whl", hash = "sha256:36d1709f992593689b45b
da411498d62c6e365f2ca00b84657d4dadd24de16db", size = 4692978, upload-time = "2026-06-12T20:01:21.305Z" },
{ url = "https://files.pythonhosted.org/packages/e6/8b/43011f7ebe515a8aa20d61f290a326cd890c2e738e16e59eaff8d9c3a412
/cryptography-49.0.0-cp311-abi3-manylinux2014_x86_64.manylinux_2_17_x86_64.whl", hash = "sha256:0e959b578856a3924bc0cbb
710fc12c387b9412a951389f3ca61704a9e25f325", size = 4716422, upload-time = "2026-06-12T20:01:48.566Z" },
{ url = "https://files.pythonhosted.org/packages/4a/91/01ce7303a4579e6d3a6abef01bd322848e9ea7a219adcbabc5048b9033571
/cryptography-49.0.0-cp311-abi3-manylinux_2_28_aarch64.whl", hash = "sha256:53ecce2e23f7169b6117e99fc8a944e5e50f79e6975
8a83b52a00cb98ab2b2d2", size = 4700503, upload-time = "2026-06-12T20:02:47.091Z" },
{ url = "https://files.pythonhosted.org/packages/62/99/a2c95cf8293f07491e9e27c20cc4dcd18176d944e674679adeb1d0173fd6
/cryptography-49.0.0-cp311-abi3-manylinux_2_28_ppc64le.whl", hash = "sha256:2eda353d8a27bcbcaa4cbcd18994a74ab4d19a2ca89
7db188ea269ab9b71419b", size = 5309779, upload-time = "2026-06-12T20:02:08.987Z" },
{ url = "https://files.pythonhosted.org/packages/20/2c/0622f20ff02b2ef32558733443805dc82fd4c275be01b2d19d14676f3a1b
/cryptography-49.0.0-cp311-abi3-manylinux_2_28_x86_64.whl", hash = "sha256:2afe9051da7ae7bd5905da5a949280c7d2bb75682e18
8f650a9d0f2756b834c6", size = 4749683, upload-time = "2026-06-12T20:02:03.335Z" },
{ url = "https://files.pythonhosted.org/packages/a3/5b/c5246635d5fd3b64e0d45ae10e99fd32fe9676a79915ccffe5a61ba9af1a5
/cryptography-49.0.0-cp311-abi3-manylinux_2_31_armv7l.whl", hash = "sha256:0b82e28ee398a386f0807bba7884d30f25218855690f
45115831bcc5d90822c", size = 4337874, upload-time = "2026-06-12T20:02:54.323Z" },
{ url = "https://files.pythonhosted.org/packages/6d/88/05563c7fe2e914e87d1a536d06fe83e66b4e1d95cb593e05aea375531da8
/cryptography-49.0.0-cp311-abi3-manylinux_2_34_aarch64.whl", hash = "sha256:ccac2bfefbc306b862133e3bb71f3f6ee8bb52524008
9b2d952e4144b3a6d5da7", size = 4700283, upload-time = "2026-06-12T20:01:34.822Z" },
{ url = "https://files.pythonhosted.org/packages/c4/b6/d7696e4e890d6ae1469935164c9e5215c557671cb78d6e3f458ccceaa632
/cryptography-49.0.0-cp311-abi3-manylinux_2_34_ppc64le.whl", hash = "sha256:d0527ce944105f257f605a827d6bead966c752038b
6e8656abb9c5edeef6c68", size = 5265844, upload-time = "2026-06-12T20:01:24.092Z" },
{ url = "https://files.pythonhosted.org/packages/a9/3c/f3ad17eecc1a57b0ba236dc01f90e783c51f4a2f35f64777cc4f47a184b2
/cryptography-49.0.0-cp311-abi3-manylinux_2_34_x86_64.whl", hash = "sha256:cbc77da8c523d5abd028635ba850a6966fcee2c82e2b
f65a41d1d8afe0f98be9", size = 4749290, upload-time = "2026-06-12T20:01:30.848Z" },
{ url = "https://files.pythonhosted.org/packages/4f/01/339573cf1023163a400b0b5d16f6d507de413b9f60be6fd1b77feeaf6737
/cryptography-49.0.0-cp311-abi3-musllinux_1_2_aarch64.whl", hash = "sha256:b87e65d263b3e5d3bb92a57e2a6638e2f31110fa7aa8
90c7b2dbba42248d0a3f", size = 4834612, upload-time = "2026-06-12T20:01:29.246Z" },
{ url = "https://files.pythonhosted.org/packages/71/fd/577302e213a1be9468f92d1afef66fc1ef83d516819d9992ca547f592bd
/cryptography-49.0.0-cp311-abi3-musllinux_1_2_x86_64.whl", hash = "sha256:66ec79c3904820572d7e987abd304281f141d37ad9a4
89b8e97066e7b9b6459", size = 4980804, upload-time = "2026-06-12T20:01:42.853Z" },
{ url = "https://files.pythonhosted.org/packages/1f/09/f42b1d190c5ba75f72062a387f8030d1d75f6ab035788f1d9c4b01de6525
/cryptography-49.0.0-cp311-abi3-win_amd64.whl", hash = "sha256:e5dfc1e64de5677cec922ffa8da89c546d0415bf6efdf081842e5d44
c84e1f0e", size = 3810026, upload-time = "2026-06-12T20:02:39.262Z" },
{ url = "https://files.pythonhosted.org/packages/ec/9e/db72b3ae7fc9cfad53e630e56c6ae83b9b6ff0bf3718ffbb8012d20b3aabf
/cryptography-49.0.0-cp314-cp314t-macosx_11_0_arm64.whl", hash = "sha256:73a205dce83953d131a4aa1e0fd917a2fd1c5b1eef251e
9d7152efefcbf5caf7", size = 4013892, upload-time = "2026-06-12T20:02:10.735Z" },
{ url = "https://files.pythonhosted.org/packages/86/12/c48a424f38db03027be9f7ed5c7dc5de9933dbee992865f98b13727a009d
/cryptography-49.0.0-cp314-cp314t-manylinux2014_aarch64.manylinux_2_17_aarch64.whl", hash = "sha256:196ecd6a36e4e9aa102
70393bb98d8df88fccceebf1e5128b91ae4eb4375896d", size = 4678835, upload-time = "2026-06-12T20:02:48.743Z" },
{ url = "https://files.pythonhosted.org/packages/68/28/8a3ad4653662c93fc44dc4e5d8fd374c25c42e07b34bbfbad49cf57a5a8
/cryptography-49.0.0-cp314-cp314t-manylinux2014_x86_64.manylinux_2_17_x86_64.whl", hash = "sha256:7abcee80084cda3f7691f

```

```
3eb1ce480d8df49cec637b429aa35986c1de71738aa", size = 4697239, upload-time = "2026-06-12T20:02:56.03Z" },
 { url = "https://files.pythonhosted.org/packages/a8/b2/2193fc74f81aee4f9b62733133b73b5176718932ed8f2e4b03fa040480a6/cryptography-49.0.0-cp314-cp314t-manylinux_2_28_aarch64.whl", hash = "sha256:4ae387c9cb68ea569ca17e490d66d8142b81c3cc814bf179974b7d146e490bbb", size = 4685593, upload-time = "2026-06-12T20:02:50.666Z" },
 { url = "https://files.pythonhosted.org/packages/47/f1/1d3eaa243bfc5de4a187b22aa8c048b3e4980bfbe830ac46e6bac2e66947/cryptography-49.0.0-cp314-cp314t-manylinux_2_28_ppc64le.whl", hash = "sha256:f37d847238971164fdb6c8ade6f6574aacc9c0af714190e2083429ff68f4ce9d", size = 5289961, upload-time = "2026-06-12T20:01:46.468Z" },
 { url = "https://files.pythonhosted.org/packages/58/39/2d51306721330c486495853eda1c567880ff036de15a14c4b74f399934af/cryptography-49.0.0-cp314-cp314t-manylinux_2_28_x86_64.whl", hash = "sha256:c2bc30226390d60ea19d9f82b19db005fe0452154a23c1c410c12ea801e43561", size = 4731145, upload-time = "2026-06-12T20:02:16.832Z" },
 { url = "https://files.pythonhosted.org/packages/17/50/983e838c7fd0d87fd8c969bccdd328edaf5f756e38df5281637424c155873/cryptography-49.0.0-cp314-cp314t-manylinux_2_31_armv7l.whl", hash = "sha256:07cab27cc7b7e0fd28e5e26bb9eeedde5c135c868b46de4a27845abe94af6122", size = 4321719, upload-time = "2026-06-12T20:02:52.611Z" },
 { url = "https://files.pythonhosted.org/packages/a7/f5/8f571d7e27c55bce9f76f026143bcb1e040a4233149ecca0bea5fa5dd5f7/cryptography-49.0.0-cp314-cp314t-manylinux_2_34_aarch64.whl", hash = "sha256:b20133d204d2bb56ba047642199603876c872026ca53e79c35b83772ab2cc505", size = 4685209, upload-time = "2026-06-12T20:02:07.282Z" },
 { url = "https://files.pythonhosted.org/packages/e7/84/0e27016afc5a0886f797018b26aa42f40c09a82332bfff77822a451deaaa/cryptography-49.0.0-cp314-cp314t-manylinux_2_34_ppc64le.whl", hash = "sha256:b970c6da94d5bb18629db453d14f2a1300f6bf59b61e9b82377931ef95504866", size = 5246285, upload-time = "2026-06-12T20:01:32.439Z" },
 { url = "https://files.pythonhosted.org/packages/11/2d/5e1fb307cb5931881516b464c98774b3f2c36b5d4bb9a2830253cf553cad/cryptography-49.0.0-cp314-cp314t-manylinux_2_34_x86_64.whl", hash = "sha256:d8ecde755e2e91bf773fc94e8c9d730cd7f2007004cb492263a794ec3899a1c8", size = 4730441, upload-time = "2026-06-12T20:02:01.469Z" },
 { url = "https://files.pythonhosted.org/packages/e4/c0/bff5a02ee731d207d6a1ed51732549d8c53d2bcb8da1d10ec6f2844201d68/cryptography-49.0.0-cp314-cp314t-musllinux_1_2_aarch64.whl", hash = "sha256:e3fb64c420688e5319ae25113a354015abbdb8dffbfbc41781a1ea66fc7622ac3", size = 4815869, upload-time = "2026-06-12T20:01:36.574Z" },
 { url = "https://files.pythonhosted.org/packages/b9/26/814681d14248d95d73d5c3eea0c39a94eb8302df966f670a2c60de90974b/cryptography-49.0.0-cp314-cp314t-musllinux_1_2_x86_64.whl", hash = "sha256:32703d93296f5c1f4b53349ad3a250c2cae0fdec3a3dd5d47e616d8d616af27", size = 4960948, upload-time = "2026-06-12T20:02:18.688Z" },
 { url = "https://files.pythonhosted.org/packages/4c/fe/93ecac273d3738939d023612ad12cca9a3740a5345d69fda04134c43fd96/cryptography-49.0.0-cp314-cp314t-win_amd64.whl", hash = "sha256:33cd0565932807badb67b96dbee92f2c374b5c89dee09fd74709aeb8c8dba61", size = 3799153, upload-time = "2026-06-12T20:01:39.059Z" },
 { url = "https://files.pythonhosted.org/packages/19/2a/5bb823f5bedcf80718cea7fbc95ec5515cca3769633c4b01a32be7f30e7c/cryptography-49.0.0-cp39-abi3-macosx_11_0_arm64.whl", hash = "sha256:ec5e529fb80935c94fe7b729f9972b50e351a0e6b50aa294fd5cabb109fcc29a", size = 4025947, upload-time = "2026-06-12T20:01:25.745Z" },
 { url = "https://files.pythonhosted.org/packages/3d/df/40577043ca124e17012f408dddaeb213b856336ac82ddb3bc915f39e29f/cryptography-49.0.0-cp39-abi3-manylinux2014_aarch64.whl", hash = "sha256:f78ff2c9ed8dc2d036b0bf4d640e22522213d047c1b14e61205a7e55c80a494d4", size = 4692429, upload-time = "2026-06-12T20:01:53.628Z" },
 { url = "https://files.pythonhosted.org/packages/2c/99/2d13299eb3dd27b02dcfaafcc91d6b5cb3329f7cbd6d8f51921acd566c1a/cryptography-49.0.0-cp39-abi3-manylinux2014_x86_64.whl", hash = "sha256:35b151772baff2c74cba7fa290ceaff4c3b11c0c881eb93eb5dbc05a7cfbba18", size = 4700968, upload-time = "2026-06-12T20:02:45.383Z" },
 { url = "https://files.pythonhosted.org/packages/a5/4d/9c0cd02f95e2602dd5e563da149ee0830abef3537be8b34dc56281ebe27a/cryptography-49.0.0-cp39-abi3-manylinux_2_28_aarch64.whl", hash = "sha256:0f21641cf4b30fca7aee061ced0ec7ad7b073518088b7c9969a297c0ae796c69", size = 4697758, upload-time = "2026-06-12T20:01:41.13Z" },
 { url = "https://files.pythonhosted.org/packages/24/01/186c825898477d7e2324d5360fefe622ff1d8d1963ec0554e2cada8ec77/cryptography-49.0.0-cp39-abi3-manylinux_2_28_ppc64le.whl", hash = "sha256:9e82dcc8e56052715fb18b2429e3bca4823b1629136a2084fc45a9a5cecb9b64", size = 5298863, upload-time = "2026-06-12T20:02:24.579Z" },
 { url = "https://files.pythonhosted.org/packages/b8/7b/62cbbab75d0659865bf0273790031544a0b16c8072d258f9428dcd8190dc/cryptography-49.0.0-cp39-abi3-manylinux_2_28_x86_64.whl", hash = "sha256:6f2debedf9ca60cf1d5bd466475638af5130f89965605cd818484d19987d3a21", size = 4735983, upload-time = "2026-06-12T20:01:50.14Z" },
 { url = "https://files.pythonhosted.org/packages/6c/72/3e798c064bc39e471008075d0f9bc9daf77a80879c092e4a8e170c585ed4/cryptography-49.0.0-cp39-abi3-manylinux_2_31_armv7l.whl", hash = "sha256:8c25ceb16df5b9435f3f6a9829204985b0e0cbee3b48aacd432c7d2c850b44d9", size = 4334173, upload-time = "2026-06-12T20:01:44.743Z" },
 { url = "https://files.pythonhosted.org/packages/f0/ee/6fca21d1ac73e06f8bef71940abfd4d2f6472b4bca284d770f32bd4086f6/cryptography-49.0.0-cp39-abi3-manylinux_2_34_aarch64.whl", hash = "sha256:28d8b15e6275f12c8a207dc309dfa957903c927d08d0cc937ee3f63f200693cc", size = 4697298, upload-time = "2026-06-12T20:02:20.918Z" },
 { url = "https://files.pythonhosted.org/packages/d0/a5/fcd3515f0bae49a7b6d0413cc1bdccdc1fc0047037a0d480642cdc5d6/cryptography-49.0.0-cp39-abi3-manylinux_2_34_ppc64le.whl", hash = "sha256:6fc361c34fb6aac015ce19435876635e5c6d21db31998b0920f675f131e043b8", size = 5254338, upload-time = "2026-06-12T20:02:22.737Z" },
 { url = "https://files.pythonhosted.org/packages/a0/84/84fe36f19caf857d61cb7fc9c63035a47ffabd84ea12d1d393148efa3615/cryptography-49.0.0-cp39-abi3-manylinux_2_34_x86_64.whl", hash = "sha256:2400ef9c9e2299a25614eb1dea3db54a69b1349efd043bfac9c67630d136df36", size = 4735650, upload-time = "2026-06-12T20:02:41.389Z" },
 { url = "https://files.pythonhosted.org/packages/6c/a0/db537264e234f7273a73ec020873d6d6b39dfd8a53db78b550ca8320440e/cryptography-49.0.0-cp39-abi3-musllinux_1_2_aarch64.whl", hash = "sha256:67e1d20ad9ef3a563c59ef22e7a8a0b8210bd26604369ea4a30a7c66ae504e", size = 4834820, upload-time = "2026-06-12T20:01:51.847Z" },
 { url = "https://files.pythonhosted.org/packages/93/77/8df9eb486495979bccccecd1062e2eaf435250e84437040295b57d09048b0b/cryptography-49.0.0-cp39-abi3-musllinux_1_2_x86_64.whl", hash = "sha256:42b0684e0e40cf26122427802486f6d93aea593612603a94fbf260c7eb1e9c1b", size = 4967968, upload-time = "2026-06-12T20:02:12.524Z" },
 { url = "https://files.pythonhosted.org/packages/c2/e6/f60198ea8d9dfa15fff9ed4ca02ce362f6eadd9ba757dcc50634c4257b63/cryptography-49.0.0-cp39-abi3-win_amd64.whl", hash = "sha256:026ac7423e6fa66872d3bf889be5974507da3944f866f704fa200eada00001", size = 3785547, upload-time = "2026-06-12T20:02:26.847Z" },
]
```

```
[[package]]
name = "gitdb"
version = "4.0.12"
source = { registry = "https://pypi.org/simple" }
```

```

dependencies = [
 { name = "smmap" },
]
sdist = { url = "https://files.pythonhosted.org/packages/72/94/63b0fc47eb32792c7ba1fe1b694daec9a63620db1e313033d18140c2320a/gitdb-4.0.12.tar.gz", hash = "sha256:5ef71f855d191a3326fcfbc0d5da835f26b13fbcba60c32c21091c349ffdb571", size = 394684, upload-time = "2025-01-02T07:20:46.413Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/a0/61/5c78b91c3143ed5c14207f463aecfc8f9dbb5092fb2869baf37c273b2705/gitdb-4.0.12-py3-none-any.whl", hash = "sha256:67073e15955400952c6565cc3e707c554a4eea2e428946f7a4c162fab9bd9bcf", size = 62794, upload-time = "2025-01-02T07:20:43.624Z" },
]

[[package]]
name = "gitpython"
version = "3.1.50"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "gitdb" },
]
sdist = { url = "https://files.pythonhosted.org/packages/33/f6/354ae6491228b5eb40e10d89c4d13c651fe1cf7556e35ebddd50cff57ce/gitpython-3.1.50.tar.gz", hash = "sha256:80da2d12504d52e1f998772dc5baf6e553f8d2fcfe1fcc226c9d9a2ee3372dcc", size = 219798, upload-time = "2026-05-06T04:01:26.571Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/20/7a/1c6e3562dfd8950adbb11ffbc65d21e7c89d01a6e4f137fa981056de25c5/gitpython-3.1.50-py3-none-any.whl", hash = "sha256:d352abe2908d07355014abdd21ddf798c2a961469239afec4962e9da884858f9", size = 212507, upload-time = "2026-05-06T04:01:23.799Z" },
]

[[package]]
name = "graphviz"
version = "0.21"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/f8/b3/3ac91e9be6b761a4b30d66ff165e54439dcd48b83f4e20d644867215f6ca/graphviz-0.21.tar.gz", hash = "sha256:20743e7183be82aaaa8ad6c93f8893c923bd6658a04c32ee115edb3c8a835f78", size = 200434, upload-time = "2025-06-15T09:35:05.824Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/91/4c/e0ce1ef95d4000ebc1c11801f9b944fa5910ecc15b5e351865763d8657f8/graphviz-0.21-py3-none-any.whl", hash = "sha256:54f33de9f4f911d7e84e4191749cac8cc5653f815b06738c54db9a15ab8b1e42", size = 47300, upload-time = "2025-06-15T09:35:04.433Z" },
]

[[package]]
name = "h11"
version = "0.16.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/01/ee/02a2c011bdab74c6fb3c75474d40b3052059d95df7e73351460c8588d963/h11-0.16.0.tar.gz", hash = "sha256:4e35b956cf45792e4caa5885e69fba00bdbbcffafbfaf020300e549b208ee5fff1", size = 101250, upload-time = "2025-04-24T03:35:25.427Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/04/4b/29cac41a4d98d144bf5f6d33995617b185d14b22401f75ca86f384e87ff1/h11-0.16.0-py3-none-any.whl", hash = "sha256:63cf8bbe7522de3bf65932fda1d9c2772064fffb3dae62d55932da54b31cb6c86", size = 37515, upload-time = "2025-04-24T03:35:24.344Z" },
]

[[package]]
name = "httptools"
version = "0.8.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/43/e5/d471fcb0e14523fe1c3f4ba58ca52480e7bd70ad7109a3846bc75892f7fb/httptools-0.8.0.tar.gz", hash = "sha256:6b2a32f18d97e16e90827d7a819ffa8dbd8cc245fc4e1fa9d1095b54ef4bd999", size = 271342, upload-time = "2026-05-25T22:17:48.841Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/14/88/1d21a36da8f5cb0fa49eafd4b169eba5608d57e75bbcf61845cb6243216/httptools-0.8.0-cp312-cp312-macosx_10_13_universal2.whl", hash = "sha256:880490234c10f70a9830743097e8958d6e4b9f5a0ffc24515023afeef984054d", size = 208247, upload-time = "2026-05-25T22:17:07.843Z" },
 { url = "https://files.pythonhosted.org/packages/a5/42/cc4feea2945cb3051038f090c9b36bd5b8a9d7f5a894a506a8983e33fd1c/httptools-0.8.0-cp312-cp312-macosx_11_0_arm64.whl", hash = "sha256:5931891fb7b441b8a3853cf1b85c82c903defce084dd5f6771ca46e31bf862c5", size = 113064, upload-time = "2026-05-25T22:17:09.136Z" },
 { url = "https://files.pythonhosted.org/packages/e3/a6/febbb8b8db0f58b38e44ad6cb946e6a255ae49b55f2e8543408fb7501ccd/httptools-0.8.0-cp312-cp312-manylinux1_x86_64.manylinux_2_28_x86_64.manylinux_2_5_x86_64.whl", hash = "sha256:b15fc622b0f869d19207c4089a501d9bcc63ca5e071ffdd2f03f922df882dcb2", size = 523851, upload-time = "2026-05-25T22:17:10.106Z" },
 { url = "https://files.pythonhosted.org/packages/b7/e4/f90a0df0b83beff265b7e3b65f2a4cefd95792d4be0ac3e16049f2acd3c2/httptools-0.8.0-cp312-cp312-manylinux2014_aarch64.manylinux_2_17_aarch64.manylinux_2_28_aarch64.whl", hash = "sha256:425f83884fd6343828d8c565f046cb72b6d19063f6924093e11bcd8e1548cd09", size = 518842, upload-time = "2026-05-25T22:17:11.218Z" },
 { url = "https://files.pythonhosted.org/packages/9e/2d/0c9ac76dd2c893841fbf6498d6accec4f2442e1b7067f6e3e316a80e494e8

```

```
/httptools-0.8.0-cp312-cp312-musllinux_1_2_aarch64.whl", hash = "sha256:ef7c3c97f4311c7be57e2986629df89d49cb434dbff78ea
fcd48c2bff986b15a", size = 501238, upload-time = "2026-05-25T22:17:12.728Z" },
{ url = "https://files.pythonhosted.org/packages/ca/42/906adc91ae3a5fa9c59c0a2f21c139725bd7e5b41ae6acd485cd14123ebf
/httptools-0.8.0-cp312-cp312-musllinux_1_2_x86_64.whl", hash = "sha256:a1afd7c9fbff0d9f5d489c4ce2768bd09c84a46ddefc7161
e6aa82ae35c85745", size = 509567, upload-time = "2026-05-25T22:17:13.842Z" },
{ url = "https://files.pythonhosted.org/packages/05/0b/4240efeb672751ee5b9b380cb0e3fdc050bc05f68adc7a8aefc4fcd9a69a
/httptools-0.8.0-cp312-cp312-win_amd64.whl", hash = "sha256:cd96f29b4bab1d42fa6e3d008711c75e0f79e94e06827330160e3a30422
7f150", size = 90918, upload-time = "2026-05-25T22:17:15.155Z" },
{ url = "https://files.pythonhosted.org/packages/5e/e5/8fcabec5546e8022f168be28bcdad128a240a0befdd03b59d558b4f18bd6
/httptools-0.8.0-cp313-cp313-macosx_10_13_universal2.whl", hash = "sha256:614ceea8ea606848bece2338ac03b3ce5324bcb4be8dc
7d377ed708012fa4db8", size = 205148, upload-time = "2026-05-25T22:17:16.333Z" },
{ url = "https://files.pythonhosted.org/packages/2a/0e/0fb14848c19a686c8062ff9067c1a48793e3224b47bc5b201535b6036fce
/httptools-0.8.0-cp313-cp313-macosx_11_0_arm64.whl", hash = "sha256:2d689918c15a013c65ef52d9fd495d766893ab831a2c8d89f2a
c5940a5df847c", size = 111368, upload-time = "2026-05-25T22:17:17.586Z" },
{ url = "https://files.pythonhosted.org/packages/2e/1b/46f1cec9f06b9bbde8e4b8c88034ac7908989e5ff7a3a388ef38392949c1f
/httptools-0.8.0-cp313-cp313-manylinux1_x86_64.manylinux_2_28_x86_64.manylinux_2_5_x86_64.whl", hash = "sha256:eb3028cc
a2fc0a6d720e52ef61d8ebb62fcbfeb1de56874546d858d3f25a26b7", size = 486447, upload-time = "2026-05-25T22:17:18.564Z" },
{ url = "https://files.pythonhosted.org/packages/77/00/258bfc0837221f81d9725c45f9b948a6a6b2994a147a4fb66e85100c668f
/httptools-0.8.0-cp313-cp313-manylinux2014_aarch64.manylinux_2_17_aarch64.manylinux_2_28_aarch64.whl", hash = "sha256:8
8bdd940f2b5d487b4d032c6afa5489a7dc4694410d43de3c38c4fb3af0dc45d", size = 482448, upload-time = "2026-05-25T22:17:19.912
Z" },
{ url = "https://files.pythonhosted.org/packages/04/ab/d1cef3b5523f4d272a70f42a776c3169a2dddf3a54de4b2ce4a36341528
/httptools-0.8.0-cp313-cp313-musllinux_1_2_aarch64.whl", hash = "sha256:6a43c9dd399758ccc0531ac0a3c4a6c299ee893ee9400e
9c893b7bdcfae0681", size = 464460, upload-time = "2026-05-25T22:17:20.882Z" },
{ url = "https://files.pythonhosted.org/packages/ce/48/5d1d072442277bb2b3434e0e60690b8e8c23840ef7de8b6ea54040a536d3
/httptools-0.8.0-cp313-cp313-musllinux_1_2_x86_64.whl", hash = "sha256:070728beb05094c809b98e814eddf5f5ef69d26ad7d21185
f2f6d5884a0ba683", size = 471312, upload-time = "2026-05-25T22:17:22.085Z" },
{ url = "https://files.pythonhosted.org/packages/0d/66/b96623b27e51a68199ef4efdda0613cced9233fe3062ac74e50749c5ad37
/httptools-0.8.0-cp313-cp313-win_amd64.whl", hash = "sha256:7685df791fad561384bfb139e77fde27a1ff93134e016f95a0db424fffb
f77b1", size = 90117, upload-time = "2026-05-25T22:17:23.074Z" },
{ url = "https://files.pythonhosted.org/packages/1a/12/fa3fbf5f9517b273edea2dc982aa82a8c634091e67c590792b729017bc6f
/httptools-0.8.0-cp314-cp314-macosx_10_13_universal2.whl", hash = "sha256:de242a49b5d18e0a8776e654e9f6bf6d89f3875a5c35b
425a0e7ce940feb3fd6", size = 206183, upload-time = "2026-05-25T22:17:24.004Z" },
{ url = "https://files.pythonhosted.org/packages/30/fc/5e7c4cb443370f2090a3aba0453a07384d29ff66b7435bb90e77e1037599
/httptools-0.8.0-cp314-cp314-macosx_11_0_arm64.whl", hash = "sha256:159e9ab5f701ccd42e555a12f1ad8ff69702910fc1c996cf2bb
66e5fcb7a231b", size = 112079, upload-time = "2026-05-25T22:17:25.216Z" },
{ url = "https://files.pythonhosted.org/packages/ba/53/771bd891eb0f236f32145d6a1775777ec85745f3cc983a1f23d1a3b8ddfe
/httptools-0.8.0-cp314-cp314-manylinux1_x86_64.manylinux_2_28_x86_64.manylinux_2_5_x86_64.whl", hash = "sha256:c4a9f170
7e4823d54dfec6c33fa3697d302aed536ed352a7eb5a061ddb869d0", size = 481596, upload-time = "2026-05-25T22:17:26.186Z" },
{ url = "https://files.pythonhosted.org/packages/62/42/94e15bc68ce3d423243c45d7f1b0c7561f13844f97dc52ae23182fb65628
/httptools-0.8.0-cp314-cp314-manylinux2014_aarch64.manylinux_2_17_aarch64.manylinux_2_28_aarch64.whl", hash = "sha256:d
76ad7b951387e3632c8716a9bb03ac5b45c5f16119aa409db0459520887944e", size = 480865, upload-time = "2026-05-25T22:17:27.542
Z" },
{ url = "https://files.pythonhosted.org/packages/1c/7c/fe2980fc03723272e30f135b62360b075f513dfe7cc73aef36c7f04012bd
/httptools-0.8.0-cp314-cp314-musllinux_1_2_aarch64.whl", hash = "sha256:a3b7387147361c3fd47a0bde763c5c91b5b4cd4dc9989b8
ece84ff436c99843b", size = 463189, upload-time = "2026-05-25T22:17:28.546Z" },
{ url = "https://files.pythonhosted.org/packages/15/1b/47fc5fff68acd1bfa20b4734059c9a06cadb88119dcd5258b5b0d21d91c8
/httptools-0.8.0-cp314-cp314-musllinux_1_2_x86_64.whl", hash = "sha256:f256d6ce930c52ca1cb2a960b7da03548c454e7d28b06059
ad41bfe789036ce0", size = 466610, upload-time = "2026-05-25T22:17:29.816Z" },
{ url = "https://files.pythonhosted.org/packages/60/bd/07b13c93ff9b9bc9546e0d43f8e19378dd696dbd278511406bc07371ef1f
/httptools-0.8.0-cp314-cp314-win_amd64.whl", hash = "sha256:19d1ee275bb59ba2643ba9a3a1e51cc0c788caf2b8df506368e03f56fdd
08527", size = 92705, upload-time = "2026-05-25T22:17:31.133Z" },
{ url = "https://files.pythonhosted.org/packages/fd/c4/121648f68ce066d7bd762d6b6d97e620847642d38d54f3d90ff11d947629
/httptools-0.8.0-cp314-cp314t-macosx_10_13_universal2.whl", hash = "sha256:de1ed58a974e75d56560acc7e7fed01a454994429456
f65209789992e41f2568", size = 215023, upload-time = "2026-05-25T22:17:32.401Z" },
{ url = "https://files.pythonhosted.org/packages/b9/b0/312a062ae741ae3e8baa8c8bf20be81b2e67337b259ab4349bebc7b6142e
/httptools-0.8.0-cp314-cp314t-macosx_11_0_arm64.whl", hash = "sha256:e93c227b595c6926c1acee96891dd9da4be338cfbe82e5cd3b
b9d8dd7dc4ac0b", size = 117405, upload-time = "2026-05-25T22:17:33.742Z" },
{ url = "https://files.pythonhosted.org/packages/fc/37/fccd705f795386bb05bf413012fecff2a33e5aa8c2f069096de3e9fd8702
/httptools-0.8.0-cp314-cp314t-manylinux1_x86_64.manylinux_2_28_x86_64.manylinux_2_5_x86_64.whl", hash = "sha256:2a021c3
a8e65cc125390d72f59b968afca3bdcaff25bd67965e0a055a14946ca", size = 558497, upload-time = "2026-05-25T22:17:34.732Z" },
{ url = "https://files.pythonhosted.org/packages/bd/39/f172e8003576de35f5ba77ff417cf0e34429d35dc014deef15afa337a72c
/httptools-0.8.0-cp314-cp314t-manylinux2014_aarch64.manylinux_2_17_aarch64.manylinux_2_28_aarch64.whl", hash = "sha256:4
8774d39cbb70e2b1f71f88852a3087ae1d3a1eb80482bb48c13067ab080c14f", size = 571585, upload-time = "2026-05-25T22:17:35.81
3Z" },
{ url = "https://files.pythonhosted.org/packages/3e/b9/f5564760af99f3dbbf3f9104dc00e5da27e96cf433c6bdcf77617f70bf3f
/httptools-0.8.0-cp314-cp314t-musllinux_1_2_aarch64.whl", hash = "sha256:88eed8ec8680a9f146c655bc88445a325bd7921cfd819
4c7337e9467282427d", size = 543297, upload-time = "2026-05-25T22:17:37.08Z" },
{ url = "https://files.pythonhosted.org/packages/99/67/8d9f2c313618e161b82f3873188e7196126da1d6e29688df40eb3997c77a
/httptools-0.8.0-cp314-cp314t-musllinux_1_2_x86_64.whl", hash = "sha256:2c032fa028f46871ec7e1fc59fc15e8023eab3e6bbe6ece
786a1611719a5d081", size = 539535, upload-time = "2026-05-25T22:17:38.032Z" },
{ url = "https://files.pythonhosted.org/packages/48/63/b906c01e53f50d432c0defe43ce52764a111dc1bdd028bafbeb54dcfd008
/httptools-0.8.0-cp314-cp314t-win_amd64.whl", hash = "sha256:384c17174464c8e873398b7af24f0b1f44d992c820328413951a625323
155d77", size = 108209, upload-time = "2026-05-25T22:17:39.473Z" },
]
```

```

[[package]]
name = "idms-db2-modernizer"
version = "0.1.0"
source = { virtual = "." }
dependencies = [
 { name = "graphviz" },
 { name = "networkx" },
 { name = "pdfplumber" },
 { name = "pydantic" },
 { name = "pydantic-settings" },
 { name = "streamlit" },
]

[package.dev-dependencies]
dev = [
 { name = "pdfminer-six" },
 { name = "pytest" },
]

[package.metadata]
requires-dist = [
 { name = "graphviz", specifier = ">=0.21" },
 { name = "networkx", specifier = ">=3.6.1" },
 { name = "pdfplumber", specifier = ">=0.11.10" },
 { name = "pydantic", specifier = ">=2.13.4" },
 { name = "pydantic-settings", specifier = ">=2.14.1" },
 { name = "streamlit", specifier = ">=1.58.0" },
]

[package.metadata.requires-dev]
dev = [
 { name = "pdfminer-six", specifier = ">=20250506" },
 { name = "pytest", specifier = ">=9.1.0" },
]

[[package]]
name = "idna"
version = "3.18"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/cd/63/9496c57188a2ee585e0f1db071d75089a11e98aa86eb99d9d7618fc1edce/idna-3.18.tar.gz", hash = "sha256:ffb385a7e039654cef1ab9ef32c6fafe283c0c0467bba1d9029738ce4a1a848", size = 196711, upload-time = "2026-06-02T14:34:07.794Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/1e/5e/d4e9f1a599fb8e573b7b87160658329fbf28d19eac2718f51fc3def3aa5a/idna-3.18-py3-none-any.whl", hash = "sha256:7f952cbe720b688055e3f87de14f5c3e5fdaa8bc3928985c4077ca689de849a2", size = 65455, upload-time = "2026-06-02T14:34:06.319Z" },
]

[[package]]
name = "iniconfig"
version = "2.3.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/72/34/14ca021ce8e5dfedc35312d08ba8bf51fdd999c576889fc2c24cb97f4f10/iniconfig-2.3.0.tar.gz", hash = "sha256:c76315c77db068650d49c5b56314774a7804df16fee4402c1f19d6d15d8c4730", size = 20503, upload-time = "2025-10-18T21:55:43.219Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/cb/b1/3846dd7f199d53cb17f49cba7e651e9ce294d8497c8c150530ed11865bb8/iniconfig-2.3.0-py3-none-any.whl", hash = "sha256:f631c04d2c48c52b84d0d0549c99ff3859c98df65b3101406327ecc7d53fbf12", size = 7484, upload-time = "2025-10-18T21:55:41.639Z" },
]

[[package]]
name = "itsdangerous"
version = "2.2.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/9c/cb/8ac0172223afbcb63986cc25049b154ecfb5e85932587206f42317be31d/itsdangerous-2.2.0.tar.gz", hash = "sha256:e0050c0b7da1eea53ffa149c0cfbb5c6e2e2b69c4bef22c81fa6eb73e5f6173", size = 54410, upload-time = "2024-04-16T21:28:15.614Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/04/96/92447566d16df59b2a776c0fb82dbc4d9e07cd95062562af01e408583fc4/itsdangerous-2.2.0-py3-none-any.whl", hash = "sha256:c6242fc49e35958c8b15141343aa660db5fc54d4f13a1db01a3f5891b98700ef", size = 16234, upload-time = "2024-04-16T21:28:14.499Z" },
]

[[package]]
name = "jinja2"

```

```

version = "3.1.6"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "markupsafe" },
]
sdist = { url = "https://files.pythonhosted.org/packages/df/bf/f7da0350254c0ed7c72f3e33cef02e048281fec7ecec5f032d4aac52226b/jinja2-3.1.6.tar.gz", hash = "sha256:0137fb05990d35f1275a587e9aee6d56da821fc83491a0fb838183be43f66d6d", size = 245115, upload-time = "2025-03-05T20:05:02.478Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/62/a1/3d680cbdf5f4b8f15abc1d571870c5fc3e594bb582bc3b64ea099db13e56/jinja2-3.1.6-py3-none-any.whl", hash = "sha256:85ece4451f492d0c13c5dd7c13a64681a86afae63a5f347908daf103ce6d2f67", size = 134899, upload-time = "2025-03-05T20:05:00.369Z" },
]

[[package]]
name = "jsonschema"
version = "4.26.0"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "attrs" },
 { name = "jsonschema-specifications" },
 { name = "referencing" },
 { name = "rpds-py" },
]
sdist = { url = "https://files.pythonhosted.org/packages/b3/fc/e067678238fa451312d4c62bf6e6cf5ec56375422aee02f9cb5f909b3047/jsonschema-4.26.0.tar.gz", hash = "sha256:0c26707e2efad8aa1bfc5b7ce170f3fcc2e4918ff85989ba9ffa9facb2be326", size = 366583, upload-time = "2026-01-07T13:41:07.246Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/69/90/f63fb5873511e014207a475e2bb4e8b2e570d655b00ac19a9a0ca0a385ee/jsonschema-4.26.0-py3-none-any.whl", hash = "sha256:d489f15263b8d200f8387e64b4c3a75f06629559fb73deb8fdfb525f2dab50ce", size = 90630, upload-time = "2026-01-07T13:41:05.306Z" },
]

[[package]]
name = "jsonschema-specifications"
version = "2025.9.1"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "referencing" },
]
sdist = { url = "https://files.pythonhosted.org/packages/19/74/a633ee74eb36c44aa6d1095e7cc5569bebf04342ee146178e2d36600708b/jsonschema_specifications-2025.9.1.tar.gz", hash = "sha256:b540987f239e745613c7a9176f3edb72b832a4ac465cf02712288397832b5e8d", size = 32855, upload-time = "2025-09-08T01:34:59.186Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/41/45/1a4ed80516f02155c51f51e8cedb3c1902296743db0bb66608a0db2814f/jsonschema_specifications-2025.9.1-py3-none-any.whl", hash = "sha256:98802fee3a11ee76ecaca44429fda8a41bfff98b00a0f2838151b113f210cc6fe", size = 18437, upload-time = "2025-09-08T01:34:57.871Z" },
]

[[package]]
name = "markupsafe"
version = "3.0.3"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/7e/99/7690b6d4034fffd95959cbe0c02de8deb3098cc577c67bb6a24fe5d7caa7/markupsafe-3.0.3.tar.gz", hash = "sha256:722695808f4b6457b320fdc131280796bdceb04ab50fe1795cd540799ebe1698", size = 80313, upload-time = "2025-09-27T18:37:40.426Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/5a/72/147da192e38635ada20e0a2e1a51cf8823d2119ce8883f7053879c2199b5/markupsafe-3.0.3-cp312-cp312-macosx_10_13_x86_64.whl", hash = "sha256:d53197da72cc091b024dd97249dfc7794d6a56530370992a5e1a08983ad9230e", size = 11615, upload-time = "2025-09-27T18:36:30.854Z" },
 { url = "https://files.pythonhosted.org/packages/9a/81/7e4e08678a1f98521201c3079f77db69fb552acd56067661f8c2f534a718/markupsafe-3.0.3-cp312-cp312-macosx_11_0_arm64.whl", hash = "sha256:1872df69a4de6aeadd3491198eaf13810b565bdbec3ae2dc8780f14458ec73ce", size = 12020, upload-time = "2025-09-27T18:36:31.971Z" },
 { url = "https://files.pythonhosted.org/packages/1e/2c/799f4742efc39633a1b54a92eec4082e4f815314869865d876824c257c1e/markupsafe-3.0.3-cp312-cp312-manylinux2014_aarch64.manylinux_2_17_aarch64.manylinux_2_28_aarch64.whl", hash = "sha256:3a7e8ae81ae39e62a41ec302f972ba6ae23a5c5396c8e60113e9066ef893da0d", size = 24332, upload-time = "2025-09-27T18:36:32.813Z" },
 { url = "https://files.pythonhosted.org/packages/3c/2e/8d0c2ab90a8c1d9a24f0399058ab8519a3279d1bd4289511d74e909f060e/markupsafe-3.0.3-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.manylinux_2_28_x86_64.whl", hash = "sha256:d6d0be5b5b189d31db7cda48b91d7e0a9795f31430b7f271219ab30f1d3ac9d", size = 22947, upload-time = "2025-09-27T18:36:33.86Z" },
 { url = "https://files.pythonhosted.org/packages/2c/54/887f3092a85238093a0b2154bd629c89444f395618842e8b0c41783898ea/markupsafe-3.0.3-cp312-cp312-manylinux_2_31_riscv64.manylinux_2_39_riscv64.whl", hash = "sha256:94c6f0bb423f739146aec64595853541634bde58b2135f27f61c1ffd1cd4d16a", size = 21962, upload-time = "2025-09-27T18:36:35.099Z" },
 { url = "https://files.pythonhosted.org/packages/c9/2f/336b8c7b6f4a4d95e91119dc8521402461b74a485558d8f238a68312f11c/markupsafe-3.0.3-cp312-cp312-musllinux_1_2_aarch64.whl", hash = "sha256:be8813b57049a7dc738189df53d69395eba14fb99345e0"

```

a5994914a3864c8a4b", size = 23760, upload-time = "2025-09-27T18:36:36.001Z" },  
 { url = "https://files.pythonhosted.org/packages/32/43/67935f2b7e4982ffb50a4d169b724d74b62a3964bc1a9a527f5ac4f1ee2b/markupsafe-3.0.3-cp312-cp312-musllinux\_1\_2\_riscv64.whl", hash = "sha256:83891d0e9fb81a825d9a6d61e3f07550ca70a076484292a70fde82c4b807286f", size = 21529, upload-time = "2025-09-27T18:36:36.906Z" },  
 { url = "https://files.pythonhosted.org/packages/89/e0/4486f11e51bbba8b0c041098859e869e304d1c261e59244baa3d295d47b7/markupsafe-3.0.3-cp312-cp312-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:77f0643abe7495da77fb436f50f8dab76dbbc6e5fd25d39589a0f1fe6548bfa2b", size = 23015, upload-time = "2025-09-27T18:36:37.868Z" },  
 { url = "https://files.pythonhosted.org/packages/2f/e1/78ee7a023dac597a5825441ebd17170785a9dab23de95d2c7508ade94e0e/markupsafe-3.0.3-cp312-cp312-win32.whl", hash = "sha256:d88b440e37a16e651bda4c7c2b930eb586fd15ca7406cb39e211fcff3bf3017d", size = 14540, upload-time = "2025-09-27T18:36:38.761Z" },  
 { url = "https://files.pythonhosted.org/packages/aa/5b/bec5aa9bbbbb2c946ca2733ef9c4ca91c91b6a24580193e891b5f7dbe8e1e/markupsafe-3.0.3-cp312-cp312-win\_amd64.whl", hash = "sha256:26a5784ded40c9e318cfc2bdb30fe164bdb8665ded9cd64d500a34fb42067b1c", size = 15105, upload-time = "2025-09-27T18:36:39.701Z" },  
 { url = "https://files.pythonhosted.org/packages/e5/f1/216fc1bbfd74011693a4fd837e7026152e89c4bcf3e77b6692fba9923123/markupsafe-3.0.3-cp312-cp312-win\_arm64.whl", hash = "sha256:35add3b638a5d900e807944a078b51922212fb3dedb01633a8defc4b01a3c85f", size = 13906, upload-time = "2025-09-27T18:36:40.689Z" },  
 { url = "https://files.pythonhosted.org/packages/38/2f/907b9c7bbba283e68f20259574b13d005c121a0fa4c175f9bed27c4597ff/markupsafe-3.0.3-cp313-cp313-macosx\_10\_13\_x86\_64.whl", hash = "sha256:e1cf1972137e83c5d4c136c43ced9ac51d0e124706ee1c8a8532c1287fa8795", size = 11622, upload-time = "2025-09-27T18:36:41.777Z" },  
 { url = "https://files.pythonhosted.org/packages/9c/d9/5f7756922cdd676869eca1c4e3c0cd0df60ed30199ffd775e319089cb3ed/markupsafe-3.0.3-cp313-cp313-macosx\_11\_0\_arm64.whl", hash = "sha256:116bb52f642a37c115f517494ea5feb03889e04df47eeff5b130b1808ce7c219", size = 12029, upload-time = "2025-09-27T18:36:43.257Z" },  
 { url = "https://files.pythonhosted.org/packages/00/07/575a68c754943058c78f30db02ee03a64b3c638586fba6a6dd56830b30a3/markupsafe-3.0.3-cp313-cp313-manylinux2014\_aarch64.manylinux\_2\_17\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:133a43e73a802c5562be9bbcd03d090aa5a1fe899db609c29e8c8d815c5f6de6", size = 24374, upload-time = "2025-09-27T18:36:44.508Z" },  
 { url = "https://files.pythonhosted.org/packages/a9/21/9b05698b46f218fc0e118e1f8168395c65c8a2c750ae2bab54fc4bd4e0e8/markupsafe-3.0.3-cp313-cp313-manylinux2014\_x86\_64.manylinux\_2\_17\_x86\_64.manylinux\_2\_28\_x86\_64.whl", hash = "sha256:ccfcd093f13f0f0b7fdd0f198b90053bf7b2f02a3927a30e63f3ccc9df56b676", size = 22980, upload-time = "2025-09-27T18:36:45.385Z" },  
 { url = "https://files.pythonhosted.org/packages/7f/71/544260864f893f18b6827315b988c146b559391e6e7e8f7252839b1b846a/markupsafe-3.0.3-cp313-cp313-manylinux\_2\_31\_riscv64.manylinux\_2\_39\_riscv64.whl", hash = "sha256:509fa21c6deb7a7a273d629cf5ec029bc209d1a51178615dd7f18f5918992ab9", size = 21990, upload-time = "2025-09-27T18:36:46.916Z" },  
 { url = "https://files.pythonhosted.org/packages/c2/28/b50fc2f74d1ad761af2f5dcce7492648b983d00a65b8c0e0cb457c82ebbe/markupsafe-3.0.3-cp313-cp313-musllinux\_1\_2\_aarch64.whl", hash = "sha256:a4afe79fb3de0b7097d81da19090f4df4f8d3a2b3adaa8764138aac2e44f3af1", size = 23784, upload-time = "2025-09-27T18:36:47.884Z" },  
 { url = "https://files.pythonhosted.org/packages/ed/76/104b2aa106a208da8b17a2fb72e033a5a9d7073c68f7e508b94916ed47a9/markupsafe-3.0.3-cp313-cp313-musllinux\_1\_2\_riscv64.whl", hash = "sha256:795e7751525cae078558e679d646ae45574b47ed6e7771863fcc079a6171a0fc", size = 21588, upload-time = "2025-09-27T18:36:48.82Z" },  
 { url = "https://files.pythonhosted.org/packages/b5/99/16a5eb2d140087ebd97180d95249b00a03aa87e29cc224056274f2e45fd6/markupsafe-3.0.3-cp313-cp313-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:8485f406a96febb5140bfeca44a73e3ce5116b2501ac54fe953e488fb1d03b12", size = 23041, upload-time = "2025-09-27T18:36:49.797Z" },  
 { url = "https://files.pythonhosted.org/packages/19/bc/e7140ed90c5d61d77cea142eed9f9c303f4c4806f60a1044c13e3f1471d0/markupsafe-3.0.3-cp313-cp313-win32.whl", hash = "sha256:bdd37121970bfdb8be76c5fb069c7751683bdf373db1ed6c010162b2a130248ed", size = 14543, upload-time = "2025-09-27T18:36:51.584Z" },  
 { url = "https://files.pythonhosted.org/packages/05/73/c4abe620b841b6b791f2edc248f556900667a5a1cf023a6646967ae98335/markupsafe-3.0.3-cp313-cp313-win\_amd64.whl", hash = "sha256:9a1abfcd021a164803f4d485104931fb8f8c1efd55bc6b748d2f5774e78b62c5", size = 15113, upload-time = "2025-09-27T18:36:52.537Z" },  
 { url = "https://files.pythonhosted.org/packages/f0/3a/fa34a0f7cfef23cf9500d68cb7c32dd64ffd58a12b09225fb03dd37d5b80/markupsafe-3.0.3-cp313-cp313-win\_arm64.whl", hash = "sha256:7e68f88e5b8799aa49c85cd116c932a1ac15caaa3f5db09087854d218359e485", size = 13911, upload-time = "2025-09-27T18:36:53.513Z" },  
 { url = "https://files.pythonhosted.org/packages/e4/d7/e05cd7efe43a88a17a37b3ae96e79a19e846f3f456fe79c57ca61356ef01/markupsafe-3.0.3-cp313-cp313t-macosx\_10\_13\_x86\_64.whl", hash = "sha256:218551f6df4868a8d527e3062d0fb968682fe92054e89978594c28e642c43a73", size = 11658, upload-time = "2025-09-27T18:36:54.819Z" },  
 { url = "https://files.pythonhosted.org/packages/99/9e/e412117548182ce2148bdeacdda3bb494260c0b0184360fe0d56389b523b/markupsafe-3.0.3-cp313-cp313t-macosx\_11\_0\_arm64.whl", hash = "sha256:7e68f88e5b8799aa49c85cd116c932a1ac15caaa3f5db09087854d21830ba09f2ceb29d37", size = 12066, upload-time = "2025-09-27T18:36:55.714Z" },  
 { url = "https://files.pythonhosted.org/packages/bc/e6/fa0ffcd717ef64a5108eaa7b4f5ed28d56122c9a6d70ab8b72f9f715c80/markupsafe-3.0.3-cp313-cp313t-manylinux2014\_aarch64.manylinux\_2\_17\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:4e885a3d1efa2eadc93c894a21770e4bc67899e3543680313b09f139e149ab19", size = 25639, upload-time = "2025-09-27T18:36:56.908Z" },  
 { url = "https://files.pythonhosted.org/packages/96/ec/2102e881fe9d25fc16cb4b25d5f5cde50970967ffa5ddda9db771237062d/markupsafe-3.0.3-cp313-cp313t-manylinux2014\_x86\_64.manylinux\_2\_17\_x86\_64.manylinux\_2\_28\_x86\_64.whl", hash = "sha256:8709b08f4a89aa7586de0aad8da56180242ee0ada3999749b183aa23df95025", size = 23569, upload-time = "2025-09-27T18:36:57.913Z" },  
 { url = "https://files.pythonhosted.org/packages/4b/30/6f2fce1f1f205fc9323255b216ca8a235b15860c34b6798f810f05828e32/markupsafe-3.0.3-cp313-cp313t-manylinux\_2\_31\_riscv64.manylinux\_2\_39\_riscv64.whl", hash = "sha256:b8512a91625c9b3da6f127803b166b629725e68af71f8184ae7e7d54686a56d6", size = 23284, upload-time = "2025-09-27T18:36:58.833Z" },  
 { url = "https://files.pythonhosted.org/packages/58/47/4a0ccea4ab9f5dcb6f79c0236d954ac382202721e704223a8aafa38b5c8/markupsafe-3.0.3-cp313-cp313t-musllinux\_1\_2\_aarch64.whl", hash = "sha256:9b79b7a16f7fedff2495d684f2b59b0457c3b493778c9eed3111be64d58279f", size = 24801, upload-time = "2025-09-27T18:36:59.739Z" },  
 { url = "https://files.pythonhosted.org/packages/6a/70/3780e9b72180b6fecb83a4814d84c3bf4b4ae4bf0b19c27196104149734c/markupsafe-3.0.3-cp313-cp313t-musllinux\_1\_2\_riscv64.whl", hash = "sha256:12c63dfb4a98206f045aa9563db46507995f7ef6d83b2f68eda65c307c6829eb", size = 22769, upload-time = "2025-09-27T18:37:00.719Z" },  
 { url = "https://files.pythonhosted.org/packages/98/c5/c03c7f4125180fc215220c035beac6b9cb684bc7a067c84fc69414d315f5/markupsafe-3.0.3-cp313-cp313t-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:8f71bc33915be5186016f675cd83a1e08523649b0e33ef



db898db577ef5bb009", size = 23642, upload-time = "2025-09-27T18:37:01.673Z" },

{ url = "https://files.pythonhosted.org/packages/80/d6/2d1b89f6ca4bfff1036499b1e29a1d02d282259f3681540e16563f27ebc23/markupsafe-3.0.3-cp313-cp313t-win32.whl", hash = "sha256:69c0b73548bc525c8cb9a251cdddf1931d1db4d2258e9599c28c07ef3580ef354", size = 14612, upload-time = "2025-09-27T18:37:02.639Z" },

{ url = "https://files.pythonhosted.org/packages/2b/98/e48a4bfba0a0ffcf9925fe2d69240bfaa19c6f7507b8cd09c70684a53c1e/markupsafe-3.0.3-cp313-cp313t-win\_amd64.whl", hash = "sha256:1b4b79e8ebf6b55351f0d91fe80f893b4743f104bfff22e90697db1590e47a218", size = 15200, upload-time = "2025-09-27T18:37:03.582Z" },

{ url = "https://files.pythonhosted.org/packages/0e/72/e3cc540f351f316e9ed0f092757459afbc595824ca724cbc5a5d4263713f/markupsafe-3.0.3-cp313-cp313t-win\_arm64.whl", hash = "sha256:ad2cf8aa28b8c020ab2fc8287b0f823d0a7d8630784c31e9ee5edea20f406287", size = 13973, upload-time = "2025-09-27T18:37:04.929Z" },

{ url = "https://files.pythonhosted.org/packages/33/8a/8e42d4838cd89b7d7de187011e97fe6c3af66d8c044997d2183fbd6d31352/markupsafe-3.0.3-cp314-cp314-macosx\_10\_13\_x86\_64.whl", hash = "sha256:eea9599de571d72e2daf60164784109f19978b327a3910d3e9de8c97b5b70cfe", size = 11619, upload-time = "2025-09-27T18:37:06.342Z" },

{ url = "https://files.pythonhosted.org/packages/b5/64/7660f8a4a8e53c924d0fa05dc3a55c9cee10bbd82b11c5afb27d44b096ce/markupsafe-3.0.3-cp314-cp314-macosx\_11\_0\_arm64.whl", hash = "sha256:c47a551199eb8eb2121d4f0f15ae0f923d31350ab9280078d1e5f12b249e0026", size = 12029, upload-time = "2025-09-27T18:37:07.213Z" },

{ url = "https://files.pythonhosted.org/packages/da/ef/e648bfd021127bef5fa12e1720ffed0c6cbb8310c8d9bea7266337ff06de/markupsafe-3.0.3-cp314-cp314-manylinux2014\_aarch64.manylinux\_2\_17\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:f34c41761022dd093b4b6896d4810782fffbabe30f2d443ff5f083e0cbb8c737", size = 24408, upload-time = "2025-09-27T18:37:09.572Z" },

{ url = "https://files.pythonhosted.org/packages/41/3c/a36c2450754618e62008bf7435ccb0f88053e07592e6028a34776213d877/markupsafe-3.0.3-cp314-cp314-manylinux2014\_x86\_64.manylinux\_2\_17\_x86\_64.manylinux\_2\_28\_x86\_64.whl", hash = "sha256:457a69a9577064c05a97c41f4e65148652db078a3a509039e64d3467b9e7ef97", size = 23005, upload-time = "2025-09-27T18:37:10.582Z" },

{ url = "https://files.pythonhosted.org/packages/bc/20/b7fd89a8456b099837cd1dc21974632a02a999ec9bf7ca3e490aacd98e7/markupsafe-3.0.3-cp314-cp314-manylinux\_2\_31\_riscv64.manylinux\_2\_39\_riscv64.whl", hash = "sha256:e8afc3f2ccfa24215f8cb28dcf43f0113ac3c7c2f0f0806d8c70e4228c5cf4d", size = 22048, upload-time = "2025-09-27T18:37:11.547Z" },

{ url = "https://files.pythonhosted.org/packages/9a/a7/591f592afdc734f47db08a75793a55d7fbcc6902a723ae4cfbab61010cc5/markupsafe-3.0.3-cp314-cp314-musllinux\_1\_2\_aarch64.whl", hash = "sha256:ec15a59cf5af7be74194f7ab02d0f59a62bdcf1a537677ce67a2537c9b87fcd", size = 23821, upload-time = "2025-09-27T18:37:12.48Z" },

{ url = "https://files.pythonhosted.org/packages/7d/33/45b24e4f44195b26521bc6f1a82197118f74df348556594bd2262bda1038/markupsafe-3.0.3-cp314-cp314-musllinux\_1\_2\_riscv64.whl", hash = "sha256:0eb9ff8191e8498cca014656ae6b8d61f39da5f95b488805da4bb029ccbfabaf", size = 21606, upload-time = "2025-09-27T18:37:13.485Z" },

{ url = "https://files.pythonhosted.org/packages/ff/0e/53dfaca23a69fbfbfbf17a4b64072090e70717344c52eaaaa9c5ddff1e5f0/markupsafe-3.0.3-cp314-cp314-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:2713baf880df847f2bece4230d4d094280f4e67b1e813eec43b4c0e144a34ffe", size = 23043, upload-time = "2025-09-27T18:37:14.408Z" },

{ url = "https://files.pythonhosted.org/packages/46/11/f333a06fc16236d5238bfe74daccbca41459dcd8d1fa952e8fbd5dccb70/markupsafe-3.0.3-cp314-cp314-win32.whl", hash = "sha256:729586769a26dbceff69f7a7dbbf59ab6572b99d94576a5592625d5b411576b9", size = 14747, upload-time = "2025-09-27T18:37:15.36Z" },

{ url = "https://files.pythonhosted.org/packages/28/52/182836104b33b444e400b14f797212f720cbc9ed6ba34c800639d154e821/markupsafe-3.0.3-cp314-cp314-win\_amd64.whl", hash = "sha256:bdc919ead48f234740ad807933cdf545180bfbe9342c2bb451556db2ed958581", size = 15341, upload-time = "2025-09-27T18:37:16.496Z" },

{ url = "https://files.pythonhosted.org/packages/6f/18/acf23e91bd94fd7b3031558b1f013adfa21a8e407a3fdb32745538730382/markupsafe-3.0.3-cp314-cp314-win\_arm64.whl", hash = "sha256:5a7d5dc5140555cf21a6fefbdbf8723f06fcd2f63ef108f2854de715e4422cb4", size = 14073, upload-time = "2025-09-27T18:37:17.476Z" },

{ url = "https://files.pythonhosted.org/packages/3c/f0/57689aa4076e1b43b15fdfa646b04653969d50cf30c32a102762be2485da/markupsafe-3.0.3-cp314-cp314t-macosx\_10\_13\_x86\_64.whl", hash = "sha256:1353ef0c1b138e1907ae78e2f6c63ff67501122006b0f9abad68fda5f4ffcf6ab", size = 11661, upload-time = "2025-09-27T18:37:18.453Z" },

{ url = "https://files.pythonhosted.org/packages/89/c3/2e67a7ca217c6912985ec766c6393b636fb0c2344443ff9d91404dc4c79f/markupsafe-3.0.3-cp314-cp314t-macosx\_11\_0\_arm64.whl", hash = "sha256:1085e7fbddd3be5f89cc898938f42c0b3c711fdcb37d75221de2666af647c175", size = 12069, upload-time = "2025-09-27T18:37:19.332Z" },

{ url = "https://files.pythonhosted.org/packages/f0/00/be561dce4e6ca66b15276e184ce4b8a6c61fe83662cce2f7d72bd3249d28/markupsafe-3.0.3-cp314-cp314t-manylinux2014\_aarch64.manylinux\_2\_17\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:1b52b4fb9d94eb9ae465f8d0c228a00624de2334f216f178a995ccdcf82c4634", size = 25670, upload-time = "2025-09-27T18:37:20.245Z" },

{ url = "https://files.pythonhosted.org/packages/50/09/c419f6f5a92e5fadde27efd190eca90f05e1261b10dbd8cbb39cd8ea1dc/markupsafe-3.0.3-cp314-cp314t-manylinux2014\_x86\_64.manylinux\_2\_17\_x86\_64.manylinux\_2\_28\_x86\_64.whl", hash = "sha256:fe51ac40f757d41b7c48425901843666a6677e3e8eb0abccff09e4ba6e664f50", size = 23598, upload-time = "2025-09-27T18:37:21.177Z" },

{ url = "https://files.pythonhosted.org/packages/22/44/a0681611106e0b2921b3033fc19bc53323e0b50bc70cfffdd19f7d679bb66/markupsafe-3.0.3-cp314-cp314t-manylinux\_2\_31\_riscv64.manylinux\_2\_39\_riscv64.whl", hash = "sha256:f190daf01f13c72eac4efd5c430a8de82489d9cfff23c364c3ea822545032993e", size = 23261, upload-time = "2025-09-27T18:37:22.167Z" },

{ url = "https://files.pythonhosted.org/packages/5f/57/1b0b3f100259dc9fffe780cfb60d4be71375510e435efec3d116b6436d43/markupsafe-3.0.3-cp314-cp314t-musllinux\_1\_2\_aarch64.whl", hash = "sha256:e56b7d45a839a697b5eb268c82a71bd8c7f6c94d6fd50c3d577fa39a9f1409f5", size = 24835, upload-time = "2025-09-27T18:37:23.296Z" },

{ url = "https://files.pythonhosted.org/packages/26/6a/4bf6d0c97c4920f1597cc14dd720705eca0bf7c787aebc6bb4d1bead5388/markupsafe-3.0.3-cp314-cp314t-musllinux\_1\_2\_riscv64.whl", hash = "sha256:f3e98bb3798ead92273dc0e5fd0f31ade220f59a266ffd8a4f6065e0a3ce0523", size = 22733, upload-time = "2025-09-27T18:37:24.237Z" },

{ url = "https://files.pythonhosted.org/packages/14/c7/ca723101509b518797fedc2fdf79ba57f886b4aca8a7d31857ba3ee8281f/markupsafe-3.0.3-cp314-cp314t-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:5678211cb9333a6468fb8d8be0305520aa073f50d17f089b5b4b477ea6e67fdc", size = 23672, upload-time = "2025-09-27T18:37:25.271Z" },

{ url = "https://files.pythonhosted.org/packages/fb/df/5bd7a48c256faecd1d36edc13133e51397e41b73bb77e1a69deab746ebac/markupsafe-3.0.3-cp314-cp314t-win32.whl", hash = "sha256:915c04ba3851909ce68ccc2b8e2cd691618c4dc4c4232fb7982bca3f41fd8c3d", size = 14819, upload-time = "2025-09-27T18:37:26.285Z" },

{ url = "https://files.pythonhosted.org/packages/1a/8a/0402ba61a2f16038b48b39bccca271134be00c5c9f0f623208399333c448/markupsafe-3.0.3-cp314-cp314t-win\_amd64.whl", hash = "sha256:4faffd047e07c38848ce017e8725090413cd80cbc23d86e55c587bf97

```

9e579c9", size = 15426, upload-time = "2025-09-27T18:37:27.316Z" },
 { url = "https://files.pythonhosted.org/packages/70/bc/6f1c2f612465f5fa89b95bead1f44dcb607670fd42891d8fdcd5d039f4f4
/markupsafe-3.0.3-cp314-cp314t-win_arm64.whl", hash = "sha256:32001d6a8fc98c8cb5c947787c5d08b0a50663d139f1305bac5885d98
d9b40fa", size = 14146, upload-time = "2025-09-27T18:37:28.327Z" },
]

[[package]]
name = "narwhals"
version = "2.22.1"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/62/3c/c4ef2164a71c1a63d7f1ae411c4082c5fa872405106db60a4b711498
9ad7/narwhals-2.22.1.tar.gz", hash = "sha256:d62920805a0a43b7ff8b54b0c0d3142d796f8a9301836ada37e573d6a33cbcd9", size =
647493, upload-time = "2026-06-05T12:34:34.051Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/48/ca/36339329c4604adbcc99c899b7eb1ce1a555c499b6a6860757dc9bfed36d
/narwhals-2.22.1-py3-none-any.whl", hash = "sha256:60567d774edf77db53906f89d9fbd164e66e56d66d388e1e6990f17ac33cfb53", s
ize = 454815, upload-time = "2026-06-05T12:34:32.289Z" },
]

[[package]]
name = "networkx"
version = "3.6.1"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/6a/51/63fe664f3908c97be9d2e4f1158eb63317598cfa6e1fc14af5383f1
7512/networkx-3.6.1.tar.gz", hash = "sha256:26b7c357accc0c8cde558ad486283728b65b6a95d85ee1cd66bafab4c8168509", size = 2
517025, upload-time = "2025-12-08T17:02:39.908Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/9e/c9/b2622292ea83fbb4ec318f5b9ab867d0a28ab43c5717bb85b0a5f6b3b0a4
/networkx-3.6.1-py3-none-any.whl", hash = "sha256:d47fbf302e7d9cbbb9e2555a0d267983d2aa476bac30e90dfbe5669bd57f3762", si
ze = 2068504, upload-time = "2025-12-08T17:02:38.159Z" },
]

[[package]]
name = "numpy"
version = "2.4.6"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/d0/ad/fed0499ce6a338d2a03ebae59cd15093910c8875328855781952abf6
c2fe/numpy-2.4.6.tar.gz", hash = "sha256:f3a3570c4a2a16746ac2c31a7c7c7b0c186b95ce902e33db6f28094ed7387dda", size = 2073
5807, upload-time = "2026-05-18T23:37:14.07Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/95/2a/3d7b5ac8aac24feaf9ad7ed58f45b0bbc06d37e4338ae84c9f2298b570f9
/numpy-2.4.6-cp312-cp312-macosx_10_13_x86_64.whl", hash = "sha256:001fbb8e08d942dd57599e781f2472269ee7f2755fae407b4f67b
2f0b17da3f1", size = 16689119, upload-time = "2026-05-18T23:33:54.065Z" },
 { url = "https://files.pythonhosted.org/packages/ea/12/92c4c131527599e8288d6918e888d88726f84d805d784b771f32408aaeaf
/numpy-2.4.6-cp312-cp312-macosx_11_0_arm64.whl", hash = "sha256:ebfb099f8dcf083deef3ac1ca4c1503f387cf76296fcb3816b66f5e
cb5f54fdb", size = 14699246, upload-time = "2026-05-18T23:33:57.621Z" },
 { url = "https://files.pythonhosted.org/packages/ad/fe/c0a6b7b2ca128a8fb228575147073b660656734b8ebe4d76c8fd748dcc79
/numpy-2.4.6-cp312-cp312-macosx_14_0_arm64.whl", hash = "sha256:3213d622a0283a39a93d188f3cf72b26862df52fbb4ca3697f51705
016523d41", size = 5204410, upload-time = "2026-05-18T23:34:00.302Z" },
 { url = "https://files.pythonhosted.org/packages/f3/d4/9770d14ba719432bb90a421bfd443872ed0f707f7264b64bec12ea363d5fd
/numpy-2.4.6-cp312-cp312-macosx_14_0_x86_64.whl", hash = "sha256:357cc07a6d7b0b182ff02249616a03742827ebb1277546b5c7cd7f
7620a45698", size = 6551240, upload-time = "2026-05-18T23:34:02.852Z" },
 { url = "https://files.pythonhosted.org/packages/c9/c6/50a46a6205feba2343f1d6d17438107c5dc491ed1c736e6ea68689fd906b
/numpy-2.4.6-cp312-cp312-manylinux_2_27_aarch64.manylinux_2_28_aarch64.whl", hash = "sha256:5f9fb9157b4ce2971008323afe4
6053787b526ef624fea915b261468a8421a0f", size = 15671012, upload-time = "2026-05-18T23:34:05.485Z" },
 { url = "https://files.pythonhosted.org/packages/99/60/14115e6364fa676c5397c2ad3004e527e9aa487abf5d0706ec81bbd08529
/numpy-2.4.6-cp312-cp312-manylinux_2_27_x86_64.manylinux_2_28_x86_64.whl", hash = "sha256:90f9849678c75fe7afa2d348ac842
c168b0a4d3d61919687216dfc547976d853", size = 16645538, upload-time = "2026-05-18T23:34:09.265Z" },
 { url = "https://files.pythonhosted.org/packages/ae/c5/693cbe59e57db94d2231fa519ca3978dc9e19da5a8f088588f5c6e947ff2
/numpy-2.4.6-cp312-cp312-musllinux_1_2_aarch64.whl", hash = "sha256:c1a2af6c6ef86344a6b0db6b97834208bf598db514f2b155042
439b62605601a", size = 17020706, upload-time = "2026-05-18T23:34:13.053Z" },
 { url = "https://files.pythonhosted.org/packages/ef/fc/85b7c4eff9b4966ade25c2273cf7e7012e92366c032058653934b37de044
/numpy-2.4.6-cp312-cp312-musllinux_1_2_x86_64.whl", hash = "sha256:e5805d5a22fd19c8ccff10a9561f9d9f4436b0545619ea579db2
d3c35294bce2", size = 18368541, upload-time = "2026-05-18T23:34:17.024Z" },
 { url = "https://files.pythonhosted.org/packages/f6/81/e1b27545deedce7f4a0b348618c6b62d74e36a4dc9ccd42f3eb2f85eee32
/numpy-2.4.6-cp312-cp312-win32.whl", hash = "sha256:e3eeb0aabd6bd5ce64faae67e9935203a6991b4bc2a485a767fbaf2c5125f45",
size = 5962825, upload-time = "2026-05-18T23:34:20.3Z" },
 { url = "https://files.pythonhosted.org/packages/ab/ca/feab00bd44aa5fe1ad2c18f08b4d3bb92e26484b0b1d1443897809ed528c
/numpy-2.4.6-cp312-cp312-win_amd64.whl", hash = "sha256:d8e8286dd7cea7895157318d1b91cdacac64c479f3cbc8dce54833172848475
1", size = 12321687, upload-time = "2026-05-18T23:34:23.095Z" },
 { url = "https://files.pythonhosted.org/packages/63/cf/5a6d34850a39d1093558564f77ee8e8e0bee5061151b8f05a55711001ec7
/numpy-2.4.6-cp312-cp312-win_arm64.whl", hash = "sha256:4081eb135ac24158bd51cdfbef16f1c64df7063b1143f24731387137c092bec
8", size = 10221482, upload-time = "2026-05-18T23:34:25.876Z" },
 { url = "https://files.pythonhosted.org/packages/fb/82/bdab26d7438c6791ca31b7c024ca37c1eab8b726ba236129005cd4a06e45
/numpy-2.4.6-cp313-cp313-macosx_10_13_x86_64.whl", hash = "sha256:511dbaf848decaaf4b4ca48032619fb3138710c4bf7da7617765
edad1ef96b0", size = 16684648, upload-time = "2026-05-18T23:34:29.41Z" },
]

```

{ url = "https://files.pythonhosted.org/packages/1b/30/a80189bcc7f5e4258b3fbc3968d909d1756f54d023299ecc39ad6fdb9ef8/numpy-2.4.6-cp313-cp313-macosx\_11\_0\_arm64.whl", hash = "sha256:bf162abab1c1a736333192707cef898e735a5ca00f38f27eedf44b39d9e85eb", size = 14693902, upload-time = "2026-05-18T23:34:33.013Z" },

{ url = "https://files.pythonhosted.org/packages/97/12/70b5d0d7c15e1ebb8a6a84a8caa1d19e181d84f58bb6d70aca29099dec1/numpy-2.4.6-cp313-cp313-macosx\_14\_0\_arm64.whl", hash = "sha256:043191bfa8eab18c776647b62723ac9dddece59743b13f49b2016094129c2b3f", size = 5198992, upload-time = "2026-05-18T23:34:36.132Z" },

{ url = "https://files.pythonhosted.org/packages/ba/8c/ebd2a8f8a83541f8d38cc5667e8c2b69cecf30da6e45693e8158857d44b/numpy-2.4.6-cp313-cp313-macosx\_14\_0\_x86\_64.whl", hash = "sha256:6180d8b35af935aed8ece3a85e0a43f87393ae0ac87c8d2c8bd2c993f7270ef3", size = 6546944, upload-time = "2026-05-18T23:34:38.484Z" },

{ url = "https://files.pythonhosted.org/packages/bb/c5/7b863a97a91671a0338f4253bd3b5a3d3852f0692dae91711c9f4a10e787/numpy-2.4.6-cp313-cp313-manylinux\_2\_27\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:72fbe16c6fac95aedf5937fa873445cec2110be35d8a4e9433d7501fd98dae6b", size = 15669392, upload-time = "2026-05-18T23:34:41.257Z" },

{ url = "https://files.pythonhosted.org/packages/a5/9d/3584b9984ca4c047aea75214ce1a4c4c73d849bd71b604264b7f5653f8a8/numpy-2.4.6-cp313-cp313-manylinux\_2\_27\_x86\_64.manylinux\_2\_28\_x86\_64.whl", hash = "sha256:a7830bab239b79cda9c08c2da014761caf48da6150e1da17ac06283f43b6089", size = 16633220, upload-time = "2026-05-18T23:34:45.075Z" },

{ url = "https://files.pythonhosted.org/packages/05/ae/7c67fba23bd98caec7c99261f3a16072ade14813486b0282cb29846de832/numpy-2.4.6-cp313-cp313-musllinux\_1\_2\_aarch64.whl", hash = "sha256:ef4aea96ce4d3b074422cb4f2f64e216bf9e213004bb58ecfdf50ea02ea8eb9a", size = 17020800, upload-time = "2026-05-18T23:34:49.065Z" },

{ url = "https://files.pythonhosted.org/packages/d9/5d/3b6725cb31d983c5e66916f5d36f6d7e5521129e4c4404d64f918292a5b6/numpy-2.4.6-cp313-cp313-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:dfa20cc6ca228e6b155b11da03825975ce66aea520985dbbdddff0f2a5a495c605", size = 18357600, upload-time = "2026-05-18T23:34:52.709Z" },

{ url = "https://files.pythonhosted.org/packages/f7/da/2ccc6c2fe8898dee01d90c75c5f5f914a23daf99e3e0ff59516a08760c8b5/numpy-2.4.6-cp313-cp313-win32.whl", hash = "sha256:56b39e5e0622a09a25bf5baf62f4bcf0cb8a41ae6e2819cf49bcb5a74c083f91", size = 5961134, upload-time = "2026-05-18T23:34:55.618Z" },

{ url = "https://files.pythonhosted.org/packages/b5/cd/9cc4dc876fb065d5c220aae4d5e14826b2715331bb7618ce1fb07a679d99/numpy-2.4.6-cp313-cp313-win\_amd64.whl", hash = "sha256:c4fc99836233ea196540b17ab0983aff60ed07941751930f5f4d05bc3b3b7359", size = 12318598, upload-time = "2026-05-18T23:34:58.928Z" },

{ url = "https://files.pythonhosted.org/packages/39/1e/c0bcbaf18694116485fe28fd1be698c278fcd4a141c5b0e53a2aed8b12a8/numpy-2.4.6-cp313-cp313-win\_arm64.whl", hash = "sha256:a7c711e21628b52034bb5ab8d1bce291f752fcc5e92accc615778acee1ff4778", size = 10222272, upload-time = "2026-05-18T23:35:02.167Z" },

{ url = "https://files.pythonhosted.org/packages/63/6d/cc5619247c8f4204e507f5883528372e4ac4bb189e579fb859a12e480b1f/numpy-2.4.6-cp313-cp313t-macosx\_11\_0\_arm64.whl", hash = "sha256:112b06a867b235ef466ed3508ddf0238050df9c727caf65301ac385b899189a1", size = 14821197, upload-time = "2026-05-18T23:35:05.468Z" },

{ url = "https://files.pythonhosted.org/packages/00/58/f1c39161c87d9e9bed660f1ed4bafcf0e403d5ec9650b6dd77aead07d489b/numpy-2.4.6-cp313-cp313t-macosx\_14\_0\_arm64.whl", hash = "sha256:eaf7fa2de5c0be8ae6ff8e9bea2ccd725e980541244521d8d4b5f3354a27babe", size = 5326287, upload-time = "2026-05-18T23:35:08.693Z" },

{ url = "https://files.pythonhosted.org/packages/af/57/3917ab0fd97f271a8694513581b8a36c655f11c446852c302f04ccdb6fc/numpy-2.4.6-cp313-cp313t-macosx\_14\_0\_x86\_64.whl", hash = "sha256:7265a2f3d436e54ef9f2b52b5c937e6be778781bd97a590319d7348f1c1ca997", size = 6646763, upload-time = "2026-05-18T23:35:11.459Z" },

{ url = "https://files.pythonhosted.org/packages/eb/0f/037e64c494b67581ae18193d770adeff354c41f3f2c8ebf865602d949bf8f/numpy-2.4.6-cp313-cp313t-manylinux\_2\_27\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:f74a575920ab21fe304421a3fc28793d82e299cae9ecbc37084e9cf7f3617c20", size = 15728070, upload-time = "2026-05-18T23:35:14.79Z" },

{ url = "https://files.pythonhosted.org/packages/21/a6/5d2bae9c9542eb4df16dc9c46dc79c186e9bad53805dfa5399a6023c6db0/numpy-2.4.6-cp313-cp313t-manylinux\_2\_27\_x86\_64.manylinux\_2\_28\_x86\_64.whl", hash = "sha256:ede83e07a75dd06bc501566c1eca2afc0d61677c1472ac9ad93fdeee6638a48d", size = 16681752, upload-time = "2026-05-18T23:35:18.836Z" },

{ url = "https://files.pythonhosted.org/packages/92/14/23d1dfb410ae362cd59ce53e936b1513d545eb40db3949ced632e19a459e/numpy-2.4.6-cp313-cp313t-musllinux\_1\_2\_aarch64.whl", hash = "sha256:68bb27509ac1b9a3443094260f6326150663b06abe40b73a2f81160623da5b67", size = 17086024, upload-time = "2026-05-18T23:35:22.52Z" },

{ url = "https://files.pythonhosted.org/packages/4b/6e/23595a2c642cdf3bc567877064bdd7f91c8b0038a4453cf2daf7248eafe9/numpy-2.4.6-cp313-cp313t-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:a0df0043bdb289bde1f62da130d20df23d58b45429f752bc7a8fc5325a225ecd", size = 18403398, upload-time = "2026-05-18T23:35:26.398Z" },

{ url = "https://files.pythonhosted.org/packages/8a/90/0ac3bc947217e66dec77e7cbc6a1979d1af70b6461b82f620d3bccd5e4c8/numpy-2.4.6-cp313-cp313t-win32.whl", hash = "sha256:29a287e0cf63ff528da061de6b9f64a4618da591ca1046aaafc54062e40ca7eab", size = 6084971, upload-time = "2026-05-18T23:35:29.387Z" },

{ url = "https://files.pythonhosted.org/packages/77/71/5673e351671a1d2bd6063b91b44f70c0affea7d1516fa7a6572941ba4aa1/numpy-2.4.6-cp313-cp313t-win\_amd64.whl", hash = "sha256:25c692919ac5a01f170a3bfc6d2745b24fd095c353d50812637d6fcab442e75", size = 12458532, upload-time = "2026-05-18T23:35:32.175Z" },

{ url = "https://files.pythonhosted.org/packages/3f/88/19d3503c5046e688f049274b27a3ef3d771152fa80d3ba3d01a3dff61abe/numpy-2.4.6-cp313-cp313t-win\_arm64.whl", hash = "sha256:1e978ec1e8bd0e0e4de6bb75de9d30cbb74db6b6a2bb727618613703ca0167dd", size = 10291881, upload-time = "2026-05-18T23:35:35.465Z" },

{ url = "https://files.pythonhosted.org/packages/f8/91/3ab2044d05fd16d343c5ac2e69b127f1b2854040dd20b193257c78028bd3/numpy-2.4.6-cp314-cp314-macosx\_10\_15\_x86\_64.whl", hash = "sha256:06ca2f61ec4385a07a6977c55ba998a4466c123642b4a32694d3128fce18c079", size = 16683458, upload-time = "2026-05-18T23:35:38.353Z" },

{ url = "https://files.pythonhosted.org/packages/8e/62/764ce66fa4147ae6d73071a3abf804ffe606f174618697c571acdf26a7c9/numpy-2.4.6-cp314-cp314-macosx\_11\_0\_arm64.whl", hash = "sha256:38efbc8de75c7a0fc1ac190162d892787f3f47b57cc291231aafec36b80982b7", size = 14704559, upload-time = "2026-05-18T23:35:42.14Z" },

{ url = "https://files.pythonhosted.org/packages/60/61/23f27c172f022e04025b7dc2367f4d63c1a398120607ec896228649a6f48/numpy-2.4.6-cp314-cp314-macosx\_14\_0\_arm64.whl", hash = "sha256:d581b735e177fdcdce6fed8e7e8880a3fb6ee4e3653a3ac6af01c6f4c03effc5", size = 5209716, upload-time = "2026-05-18T23:35:45.377Z" },

{ url = "https://files.pythonhosted.org/packages/03/71/21cf70dc6ea3e3ac95fc53a265b2fc248b981f0194ceb5b475271b8809d/numpy-2.4.6-cp314-cp314-macosx\_14\_0\_x86\_64.whl", hash = "sha256:0a041d3d761dc3c35cc56ce0351506a02bcbcc25f7b169f652435141a17db9096", size = 6543947, upload-time = "2026-05-18T23:35:47.926Z" },

{ url = "https://files.pythonhosted.org/packages/d5/91/64288395e1799bd2e0b04a305dce966da90c961e1f3fe982a05ee1c036/numpy-2.4.6-cp314-cp314-manylinux\_2\_27\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:40fdc1ae7125e518ea98e53e69a4ebc27e1fd50510c47b7ea130cf21e5e1d42b", size = 15685197, upload-time = "2026-05-18T23:35:50.863Z" },

{ url = "https://files.pythonhosted.org/packages/f3/eb/ebffaa97dc55502df69584a8f0dcf07f69a3e0b3e2323670a2722db9aa39

```

/numpy-2.4.6-cp314-cp314-manylinux_2_27_x86_64.manylinux_2_28_x86_64.whl", hash = "sha256:a2c306dea656c12c68f51f4cea133cbe78ca7435eb28c735eac1d3ebe73be6e8", size = 16638245, upload-time = "2026-05-18T23:35:54.752Z" },
 { url = "https://files.pythonhosted.org/packages/b8/0b/54f9da33128d7e350fab89c7455902eeae70349ee52bddd448dc4a576f45/numpy-2.4.6-cp314-cp314-musllinux_1_2_aarch64.whl", hash = "sha256:33111801a01c12a8a1e3721f0a9232f8cfc8ae2c6b7098167e6f623c6073f402", size = 17036587, upload-time = "2026-05-18T23:35:58.355Z" },
 { url = "https://files.pythonhosted.org/packages/b6/f0/fdebc1052db1cc37c64beb22072d67cd6d1c71adca1299f53dec2b5e20d3/numpy-2.4.6-cp314-cp314-musllinux_1_2_x86_64.whl", hash = "sha256:ae506e6902902557576a26ff33eda8695e7ecb3cb36c3b573a0765dee114ebdb", size = 18363226, upload-time = "2026-05-18T23:36:02.845Z" },
 { url = "https://files.pythonhosted.org/packages/aa/b4/298628d98c72b57e57f7165ae6a481a1deaf6f3c28262a6e4c739c275930/numpy-2.4.6-cp314-cp314-win32.whl", hash = "sha256:aaf159caa35993cb1f56fb9b8e4610d35758e7ca005412eb1daa856a78c9c4b1", size = 6010196, upload-time = "2026-05-18T23:36:05.92Z" },
 { url = "https://files.pythonhosted.org/packages/df/ac/46de6dda46478f7942f839e094970be2d4a861e005c4b3bf07c92e291a09/numpy-2.4.6-cp314-cp314-win_amd64.whl", hash = "sha256:b507f5c4c1d508876d1819b6bf9a49d365b96320b5d4993426b33a23ca4b8261", size = 12450334, upload-time = "2026-05-18T23:36:09.107Z" },
 { url = "https://files.pythonhosted.org/packages/78/92/b8b798ac784102c0da830d2257d59358e3d3d90d1e2b3f2575dad976c5cf/numpy-2.4.6-cp314-cp314-win_arm64.whl", hash = "sha256:6f41ae150c4e32db4f3310cdf64b1593a03dbabe29e9c77fc9b50fe64061df6", size = 10495678, upload-time = "2026-05-18T23:36:12.766Z" },
 { url = "https://files.pythonhosted.org/packages/30/34/ec28d1aa8115971537c01469ab2011ee96827930f0a124de1000cc2a7ed7/numpy-2.4.6-cp314-cp314t-macosx_11_0_arm64.whl", hash = "sha256:ece3d2cfe132e7d51f44a832b303895e6f2d499c5e74dfbdb06ee246147a304a", size = 14823672, upload-time = "2026-05-18T23:36:16.473Z" },
 { url = "https://files.pythonhosted.org/packages/16/bd/f6d1fede4e54e8042a7ff97bb495510f3c220f94bcd9e8b228e87c92cc0d/numpy-2.4.6-cp314-cp314t-macosx_14_0_arm64.whl", hash = "sha256:e3e5193ef5a3dc73bcee50f7fdc2c90dbb76c42df8d8fae3d1067a583df579e", size = 5328731, upload-time = "2026-05-18T23:36:19.767Z" },
 { url = "https://files.pythonhosted.org/packages/f4/f0/e105b9e2fd728a9910103884decdd6951d9dd73896b914a98d9a231de02ee/numpy-2.4.6-cp314-cp314t-macosx_14_0_x86_64.whl", hash = "sha256:17f9ade344e7d9b464a084d69bcf18fc691cb1db67c62ed80820bf4926d78f0e", size = 6649805, upload-time = "2026-05-18T23:36:22.266Z" },
 { url = "https://files.pythonhosted.org/packages/82/dd/1206a7ca6ab15e3f02069707ca96222e202af681bb73756da7527f3cb837/numpy-2.4.6-cp314-cp314t-manylinux_2_27_aarch64.manylinux_2_28_aarch64.whl", hash = "sha256:9cd5ffdd25db4e7ba6a375693b3fc0fc1791ec636c17db3720da19bde7180ec43", size = 15730496, upload-time = "2026-05-18T23:36:25.713Z" },
 { url = "https://files.pythonhosted.org/packages/51/e7/38d3ea825dcab85a591734decbb2f6c67caa7c8367d374df1a1c3842f9b07/numpy-2.4.6-cp314-cp314t-manylinux_2_27_x86_64.manylinux_2_28_x86_64.whl", hash = "sha256:7d92c3819208a60205a12a245c91ad70cb0a85336659b19b834205573ac8456e", size = 16679616, upload-time = "2026-05-18T23:36:29.652Z" },
 { url = "https://files.pythonhosted.org/packages/93/b7/caabfd53edf663e0b4eb74d7d405d83baef09eb5e83bcd32d601d72b93e/numpy-2.4.6-cp314-cp314t-musllinux_1_2_aarch64.whl", hash = "sha256:e85b752a1e912b70eaad4fafbd4d1238007ab221de2009b9a2f5ae7461239895", size = 17085145, upload-time = "2026-05-18T23:36:33.449Z" },
 { url = "https://files.pythonhosted.org/packages/f9/45/68d7c33a6bcf3e5aa3bdbc57a367e6f615286dfd6482f97e8ffeb734306e/numpy-2.4.6-cp314-cp314t-musllinux_1_2_x86_64.whl", hash = "sha256:29cb7f67d10b479ff07c17d33e39f78c07f71c40ef30d63c153d340e96cd3fb4", size = 18403813, upload-time = "2026-05-18T23:36:37.369Z" },
 { url = "https://files.pythonhosted.org/packages/9c/50/0753655aa844c99cd9e018aacf76f130f1bd81d881bb74bc0aef57d3a8ba/numpy-2.4.6-cp314-cp314t-win32.whl", hash = "sha256:260a5d70215b61ab4fadf5c7baacd64821842975eea312125ed3c39a6391b063", size = 6156982, upload-time = "2026-05-18T23:36:40.817Z" },
 { url = "https://files.pythonhosted.org/packages/b2/d4/7c67becf668f973cb490cec3e98dfd799d866f9c989a54d355672cfa0db6/numpy-2.4.6-cp314-cp314t-win_amd64.whl", hash = "sha256:81a1cca95ed5bb92aa8b10dd2cdc9a0d3853a50fad926c28b5d7e8ea54389627", size = 12638908, upload-time = "2026-05-18T23:36:43.996Z" },
 { url = "https://files.pythonhosted.org/packages/43/bb/e1c71a4295b1b1d1393d50dbb4f2a36283c6859d9d3892e84f00ec5a91d5/numpy-2.4.6-cp314-cp314t-win_arm64.whl", hash = "sha256:0c9136e14ed34a9e343a31c533d78a9813a69a3148332bce5e9821cb2f996e66", size = 10565867, upload-time = "2026-05-18T23:36:47.114Z" },
]

[[package]]
name = "packaging"
version = "26.2"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/d7/f1/e7a6dd94a8d4a5626c03e4e99c87f241ba9e350cd9e6d75123f992427270/packaging-26.2.tar.gz", hash = "sha256:ff452ff5a3e828ce110190feff1178bb1f2ea2281fa2075aadb987c2fb221661", size = 228134, upload-time = "2026-04-24T20:15:23.917Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/df/b2/87e62e8c3e2f4b32e5fe99e0b86d576da1312593b39f47d8ceef365e95ed/packaging-26.2-py3-none-any.whl", hash = "sha256:5fc45236b9446107ff2415ce77c807cee2862cb6fac22b8a73826d0693b0980e", size = 100195, upload-time = "2026-04-24T20:15:22.081Z" },
]

[[package]]
name = "pandas"
version = "3.0.3"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "numpy" },
 { name = "python-dateutil" },
 { name = "tzdata", marker = "sys_platform == 'emscripten' or sys_platform == 'win32'" },
]
sdist = { url = "https://files.pythonhosted.org/packages/f8/87/4341c6252d1c47b08768c3d25ac487362bf403f0313ddae4a2a26c9b1b4c/pandas-3.0.3.tar.gz", hash = "sha256:696a4a00a2a2a35d4e5deb3fc946641b96c944f02230e4f76137fe35d806c4fc", size = 4651414, upload-time = "2026-05-11T18:54:29.212Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/24/f1/392f8c5bfc16f66a0d2d41561c01627c228fe7ed2a0d056ef11315042570

```

/pandas-3.0.3-cp312-cp312-macosx\_10\_13\_x86\_64.whl", hash = "sha256:fed2ff7fd9779120e388e285fc029bd5cf9490cdd2e4166a9ee22c0e49a9ab09", size = 10357846, upload-time = "2026-05-11T18:52:36.143Z" },  
 { url = "https://files.pythonhosted.org/packages/cf/3d/b16412745651e855f357e5e66930248688378853a6e2698a214e331fba1f/pandas-3.0.3-cp312-cp312-macosx\_11\_0\_arm64.whl", hash = "sha256:b168fc218fd80a6cbdbdbbc1a97ddc7889ed057d7eb45f50d866cea5b5f39904c4", size = 9899550, upload-time = "2026-05-11T18:52:38.976Z" },  
 { url = "https://files.pythonhosted.org/packages/31/a8/fa2535168fffcdf67f4f6de28d2dd903a747ca7c8ea6989451aeb3a92f/pandas-3.0.3-cp312-cp312-manylinux\_2\_24\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:0383c72c75cdcca61a9e116e61143902dbfd08bfff356829c2f6d1cf40a9ca8c", size = 10412965, upload-time = "2026-05-11T18:52:41.915Z" },  
 { url = "https://files.pythonhosted.org/packages/65/b6/09b01cdbc15224e2850365192d17b7bdebb8b8dbd8780ed221fcd0d9a515/pandas-3.0.3-cp312-cp312-manylinux\_2\_24\_x86\_64.manylinux\_2\_28\_x86\_64.whl", hash = "sha256:6dc0b3fd2169c9157deed50b4d519553a3655c8c6a96027136d654592be973a9", size = 10894600, upload-time = "2026-05-11T18:52:45.022Z" },  
 { url = "https://files.pythonhosted.org/packages/c9/a4/2eb28f2fcb4ced4a2c79ab2a5dee9ade1ebf44922ebad6fea158c9f95d4/pandas-3.0.3-cp312-cp312-musllinux\_1\_2\_aarch64.whl", hash = "sha256:7e65d5407dc0b394f509699650e4a2ec01c0514f21850f453fa60f3be79a5dbf", size = 11422824, upload-time = "2026-05-11T18:52:48.058Z" },  
 { url = "https://files.pythonhosted.org/packages/f8/45/830bb57f533a10f165e435e07edcb8ea18cf88b5f94e5fca92f27052d7c597/pandas-3.0.3-cp312-cp312-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:f8894dc474d648fe7b6ff0ca9b0bd73950d19952bc1a6534540762c5d79d305c", size = 11950889, upload-time = "2026-05-11T18:52:50.905Z" },  
 { url = "https://files.pythonhosted.org/packages/b9/c5/fc1b368f303087d20e8c9bf3d6ceb186263cfac0ade735cd938538bea839/pandas-3.0.3-cp312-cp312-win\_amd64.whl", hash = "sha256:c7be265b62cef88e253a941e4698604973736dcfe242fdb5198f0f7bc473cdcc", size = 9755463, upload-time = "2026-05-11T18:52:53.386Z" },  
 { url = "https://files.pythonhosted.org/packages/86/bd/fda8f9705b1b09c6ebe14bfc0fa0e4ec8584d54ea673628f157ff55131af/pandas-3.0.3-cp312-cp312-win\_arm64.whl", hash = "sha256:557409bc4178e70ee8d9ddb494798e51ebf6ea59330f6be22c51bab2a7db6c49", size = 9066158, upload-time = "2026-05-11T18:52:56.038Z" },  
 { url = "https://files.pythonhosted.org/packages/c5/90/62d8302883c44308c477e222c3daf7c813a34c8e96985882fbd53d964352/pandas-3.0.3-cp313-cp313-macosx\_10\_13\_x86\_64.whl", hash = "sha256:67b3b64c11910cfa29f4e94a14d3bfff9ee693b6fc76055e7cad549cee0aec5fa", size = 10331071, upload-time = "2026-05-11T18:52:58.838Z" },  
 { url = "https://files.pythonhosted.org/packages/7f/ae/6a649b3c783a101f165e4356953ba3c74d6f77f0042fa7d53da9dfbb640c/pandas-3.0.3-cp313-cp313-macosx\_11\_0\_arm64.whl", hash = "sha256:39436b377d56d2a2e52d0395bdbbee171f01068e99af5250509aceeb929f765c7", size = 9875690, upload-time = "2026-05-11T18:53:01.431Z" },  
 { url = "https://files.pythonhosted.org/packages/62/7c/5df8e9f56c69a2769f9e9382a5ef8f2658c007e376434e1e2cbb57ad895f/pandas-3.0.3-cp313-cp313-manylinux\_2\_24\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:d4be06d68f9ddcfc645b87534911da79a8bfbfc7573c80e0edcf42a5020624d8", size = 10381634, upload-time = "2026-05-11T18:53:04.393Z" },  
 { url = "https://files.pythonhosted.org/packages/99/68/1237369725aa617bb358263d535803e3053fdbc593513ec5ed9c9896b5b6/pandas-3.0.3-cp313-cp313-manylinux\_2\_24\_x86\_64.manylinux\_2\_28\_x86\_64.whl", hash = "sha256:a4eeb6830daf35a71cc09649bd823e2b542dac246cdee9614c6e4bd65028cd6a", size = 10891243, upload-time = "2026-05-11T18:53:07.643Z" },  
 { url = "https://files.pythonhosted.org/packages/25/93/77d108e8af7222b4a503ebde0e30215b1c2e4f8e53a526431890f22d5586/pandas-3.0.3-cp313-cp313-musllinux\_1\_2\_aarch64.whl", hash = "sha256:1928e07221f82db493cd4af1e23c1bfca524a19a4699887975bff68f49a72bfb", size = 11388659, upload-time = "2026-05-11T18:53:10.634Z" },  
 { url = "https://files.pythonhosted.org/packages/d0/bd/eff5b4399f332ac386c853f6cd2bd3fa2ca0061b9f36ecd9c4d7c4265649/pandas-3.0.3-cp313-cp313-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:51b1fe551acb77dac643c6fda86084d8d446c10fe64b06a9cc29c4cc8540e7f2", size = 11942880, upload-time = "2026-05-11T18:53:13.536Z" },  
 { url = "https://files.pythonhosted.org/packages/2c/20/559ace4200982c3887d0b86bfd0d856a2143ef8ddab63cc07934951a964c/pandas-3.0.3-cp313-cp313-win\_amd64.whl", hash = "sha256:a82d532a3351d435432cd913edbcacf8b8e01d4dd0e5ced5a8d2e8ecd94c7e44", size = 9757091, upload-time = "2026-05-11T18:53:16.306Z" },  
 { url = "https://files.pythonhosted.org/packages/3a/66/69055a09fe200f29f922a3eeec4804611900b95f52d932ece3393c3c0c19/pandas-3.0.3-cp313-cp313-win\_arm64.whl", hash = "sha256:275c14e0fce14a2ec20eee474aec305478ea3c1e6f6a9d8fe219a165542717e", size = 9057282, upload-time = "2026-05-11T18:53:18.768Z" },  
 { url = "https://files.pythonhosted.org/packages/57/0e/efe801b0e6811e8e650cd21b7f2608e30f08a7067e2bf6e8752b0d56ee3c/pandas-3.0.3-cp313-cp313t-macosx\_10\_13\_x86\_64.whl", hash = "sha256:46997386d528eb40376ecd6b033cf4a8a1e5282580f68f43de875b78cba2199d", size = 10767016, upload-time = "2026-05-11T18:53:21.272Z" },  
 { url = "https://files.pythonhosted.org/packages/ea/dc/eb55135a1d5f09519f28da1f609a206d2cad1f9c35c32d51e38dd7261ae/pandas-3.0.3-cp313-cp313t-macosx\_11\_0\_arm64.whl", hash = "sha256:261e308dfb22448384b7580cf719d2f998fe2966c92893c3e77d14008af1f066", size = 10420210, upload-time = "2026-05-11T18:53:23.982Z" },  
 { url = "https://files.pythonhosted.org/packages/c6/3e/b1d5d955ce33ffecb407465a60bc32769d74fcf68224b7ae67ae11d4dea4/pandas-3.0.3-cp313-cp313t-manylinux\_2\_24\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:dd1a5d1def6a46002e964510bd6c67c368aa0951df5d1d9f8365336f5a1f490cd", size = 10336126, upload-time = "2026-05-11T18:53:27.731Z" },  
 { url = "https://files.pythonhosted.org/packages/f5/76/a01261711ab60a22d71b862f0de20e4c504bf80457270ad8cb42110f6abc/pandas-3.0.3-cp313-cp313t-manylinux\_2\_24\_x86\_64.manylinux\_2\_28\_x86\_64.whl", hash = "sha256:d72828c20c6d6e83e1e22a6a3b47b326b71664112fa9705dcbccfd7a39b62085", size = 10728051, upload-time = "2026-05-11T18:53:29.125Z" },  
 { url = "https://files.pythonhosted.org/packages/e9/21/ea191195e587b18cf682e97f433f81b2d0fbc341380e80a3e0d6e4403c8e/pandas-3.0.3-cp313-cp313t-musllinux\_1\_2\_aarch64.whl", hash = "sha256:d26cbe1fcfc12e8fd900e2454163e466b2d3af84f7c75481df7683ffcf073d870", size = 11350796, upload-time = "2026-05-11T18:53:32.056Z" },  
 { url = "https://files.pythonhosted.org/packages/64/69/f0eaa5f4939f0e8c6768fd06be9af2cef9b36048b96dfb9e1b2c685a807e/pandas-3.0.3-cp313-cp313t-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:3e91cec1879ada0624fc3dc9953c5cbd60208e59c0db28f540c5d6d47502422f", size = 11799741, upload-time = "2026-05-11T18:53:34.985Z" },  
 { url = "https://files.pythonhosted.org/packages/45/a4/865e0e510cae5fc2194de4db28be638952de942571ba9125934fd9c01d47/pandas-3.0.3-cp313-cp313t-win\_amd64.whl", hash = "sha256:08d789b41f87e0905880e293cedf6197ce71fe67cc081358b1e148a491b9bd13", size = 10499958, upload-time = "2026-05-11T18:53:37.857Z" },  
 { url = "https://files.pythonhosted.org/packages/86/54/effdccc30ff7a08037889200e148ebe94c16c4f653be078c7b3675955df1/pandas-3.0.3-cp314-cp314-macosx\_10\_15\_x86\_64.whl", hash = "sha256:3650109c0f22879df8bd6179ab9ee3d7f1d1d4e7e0094a3f0032d9f51e2e64ac", size = 10336065, upload-time = "2026-05-11T18:53:41.099Z" },  
 { url = "https://files.pythonhosted.org/packages/68/10/bf2d6738d72748b961a3751ab89522d58c54efc36a8e1a12161216cd45cf/pandas-3.0.3-cp314-cp314-macosx\_11\_0\_arm64.whl", hash = "sha256:bab900348131a7db1f69a7309ef141fd5680f1487094193bcbbbb61791573bf8f", size = 9926101, upload-time = "2026-05-11T18:53:43.515Z" },  
 { url = "https://files.pythonhosted.org/packages/ae/e9/e35cf11c8a136e757b956f5f0efdcaa50aecde85ea055f1898dfc68262f3/pandas-3.0.3-cp314-cp314-manylinux\_2\_24\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:ba7e08b9ac1d54569cd1e256e3

```

668975ed624d6826f7b68df0342b012007bddb", size = 10457553, upload-time = "2026-05-11T18:53:46.394Z" },
 { url = "https://files.pythonhosted.org/packages/58/3b/1cdec6772bdbaf7b25dab360c59f03cadf05492dd724c6540af905389b07
/pandas-3.0.3-cp314-cp314-manylinux_2_24_x86_64.manylinux_2_28_x86_64.whl", hash = "sha256:9d71c63ae4ebdbf70209742096f1
fc46a83a0613c99d4b23766cccd9ff8cd62a", size = 10914065, upload-time = "2026-05-11T18:53:49.134Z" },
 { url = "https://files.pythonhosted.org/packages/c4/c2/1ef644445fcd72e3627bceec77e3560636f87ddce4ed841afe76b83b5bf9
/pandas-3.0.3-cp314-cp314-musllinux_1_2_aarch64.whl", hash = "sha256:e3a2ec42c98ffa2565a67e08e218d06d72576d758d90facb7c
00805194d8f360", size = 11459188, upload-time = "2026-05-11T18:53:52.527Z" },
 { url = "https://files.pythonhosted.org/packages/7e/49/4d8d4f42cbc9c4adc7a1870f269c02cbd6cd40d059622c06fb298addcbad
/pandas-3.0.3-cp314-cp314-musllinux_1_2_x86_64.whl", hash = "sha256:335f62418ed562cfc3c49e9e196375c28b729dcef8543abf4f9
438e381bf3c76", size = 11982966, upload-time = "2026-05-11T18:53:55.043Z" },
 { url = "https://files.pythonhosted.org/packages/38/55/792619469bab9882d8bbd5865d45a72f6478762d04a9af4bf0d08c503e95
/pandas-3.0.3-cp314-cp314-win_amd64.whl", hash = "sha256:3c20a521bbb85902f79f7270c80a59e1b5452d96d170c034f207181870f97a
c5", size = 9876755, upload-time = "2026-05-11T18:53:58.067Z" },
 { url = "https://files.pythonhosted.org/packages/2a/af/33c469653b0ba03b50c3a98192d4c07f0c75c66b263ceb097fce0ee97d31
/pandas-3.0.3-cp314-cp314-win_arm64.whl", hash = "sha256:a2d2dff8a04f3917b55ab3910c32990f8dddf7ecea114947838cefa976a689
77", size = 9198658, upload-time = "2026-05-11T18:54:00.733Z" },
 { url = "https://files.pythonhosted.org/packages/a2/fa/b8c257bd76b8bd060c3a9151c1fca05e9b9c5e3af5d0f549c0356f6d143d
/pandas-3.0.3-cp314-cp314t-macosx_10_15_x86_64.whl", hash = "sha256:0d589105b3c14645af1738ff279b2995102d8f7a03b0a66dc8d
95550eb513e04", size = 10787242, upload-time = "2026-05-11T18:54:03.564Z" },
 { url = "https://files.pythonhosted.org/packages/54/eb/f19206fffb0bf1919002969aa448b4702c6594845156a6f8050674855aac3
/pandas-3.0.3-cp314-cp314t-macosx_11_0_arm64.whl", hash = "sha256:a2d2dff8a04f3917b55ab3910c32990f8dddf7ecea114947838cefa976a689
77", size = 10436369, upload-time = "2026-05-11T18:54:06.311Z" },
 { url = "https://files.pythonhosted.org/packages/fd/24/c7c39fb4fe22b71a0c2d78bf0c585c600092d85f94f086d2b3b2f6ca27e2
/pandas-3.0.3-cp314-cp314t-manylinux_2_24_aarch64.manylinux_2_28_aarch64.whl", hash = "sha256:819959dab7bbd0049c15623fb
ac4e29a191b9528160a61fb1032242d8ced2d9c", size = 10358306, upload-time = "2026-05-11T18:54:09.085Z" },
 { url = "https://files.pythonhosted.org/packages/16/ec/dd2a9eb7fa1204df88c0864164e35b228ac581062ac612ba0a67fd812e4c
/pandas-3.0.3-cp314-cp314t-manylinux_2_24_x86_64.manylinux_2_28_x86_64.whl", hash = "sha256:60ae316d3fd75d1858d450d0db0
103ea2be3e7d4a95ec2f064f7e2ae63f7b028", size = 10758394, upload-time = "2026-05-11T18:54:11.956Z" },
 { url = "https://files.pythonhosted.org/packages/95/6e/00c61ea8e85b4f6d8d35e11852a1a4998fc7fafc91c6a602d1cc9c972d64
/pandas-3.0.3-cp314-cp314t-musllinux_1_2_aarch64.whl", hash = "sha256:bd3a518890b400d32f9023722dc9a9a5c969f00b415419a3c
06c043f09bb5d7d", size = 11375717, upload-time = "2026-05-11T18:54:14.539Z" },
 { url = "https://files.pythonhosted.org/packages/31/89/8fcl268969fac43688d65fd92e67df24bd128d53cb4d2eeee534cd307399
/pandas-3.0.3-cp314-cp314t-musllinux_1_2_x86_64.whl", hash = "sha256:13fc1e853d9e04743d11ba75a985ccbc2a317fe07d8af61e445a6
7d6c5802cf976a", size = 11828897, upload-time = "2026-05-11T18:54:17.146Z" },
 { url = "https://files.pythonhosted.org/packages/56/3b/e7d20dea247a3e6dc0bd8a6953854afbedc03951def4e7371e05e7263e25
/pandas-3.0.3-cp314-cp314t-win_amd64.whl", hash = "sha256:4db8c527972a821cf5286b40ccc57642a39bc62e62022b42f99f8a67fca8c
3a1", size = 10900855, upload-time = "2026-05-11T18:54:19.72Z" },
 { url = "https://files.pythonhosted.org/packages/0f/54/68a0978d1ef8502b8492099beaa6e7a0c1b32e3b5d4f677f5810cb08711c
/pandas-3.0.3-cp314-cp314t-win_arm64.whl", hash = "sha256:b2c95f8bfc1ee412bf482605d7bfd30c12d1d26bd59fdd91efeef1d4718de
cb1", size = 9466464, upload-time = "2026-05-11T18:54:22.754Z" },
]

[[package]]
name = "pdfminer-six"
version = "20260107"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "charset-normalizer" },
 { name = "cryptography" },
]

sdist = { url = "https://files.pythonhosted.org/packages/34/a4/5cec1112009f0439a5ca6afa8ace321f0ab2f48da3255b7a1c895301
4670/pdfminer-six-20260107.tar.gz", hash = "sha256:96bfd431e3577a55a0efd25676968ca4ce8fd5b53f14565f85716ff363889602", s
ize = 8512094, upload-time = "2026-01-07T13:29:12.937Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/20/8b/28c4eaec9d6b036a52cb44720408f26b1a143ca9bce76cc19e8f5de00ab4
/pdfminer-six-20260107-py3-none-any.whl", hash = "sha256:366585ba97e80dffaf8f00cebe303d2f381884d8637af4ce422f1df3ef38111
a9", size = 6592252, upload-time = "2026-01-07T13:29:10.742Z" },
]

[[package]]
name = "pdfplumber"
version = "0.11.10"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "pdfminer-six" },
 { name = "pillow" },
 { name = "pypdfium2" },
]

sdist = { url = "https://files.pythonhosted.org/packages/05/56/6f450312ba05a27d7713b73857c1a25100dbda04fbc1331b13fb227a
607d/pdfplumber-0.11.10.tar.gz", hash = "sha256:b95b2d28c66efb0a794a83b88c6c6aea5987532a445d20a1c9bfa657022e6e57", size
= 102892, upload-time = "2026-06-15T03:31:31.035Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/a2/9a/07d658e1e7fad860f1c541ab941348125dbdab773be3a0afaf32361866c7
/pdfplumber-0.11.10-py3-none-any.whl", hash = "sha256:7741ea81bf165b474b153e6789d10d18e06b6ddcf3ec84289c3ef2fed6802580"
, size = 60047, upload-time = "2026-06-15T03:31:29.702Z" },
]

```

```
[[package]]
name = "pillow"
version = "12.2.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/8c/21/c2bcd5906101a30244eaffc1b6e6ce71a31bd0742a01eb89e660ebf
ac2d/pillow-12.2.0.tar.gz", hash = "sha256:a830b1a40919539d07806aa58e1b114df53ddd43213d9c8b75847eee6c0182b5", size = 46
987819, upload-time = "2026-04-01T14:46:17.687Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/58/be/7482c8a5ebbbbc6470b3eb791812fff7d5e0216c2be3827b30b8bb6603ed
/pillow-12.2.0-cp312-cp312-macosx_10_13_x86_64.whl", hash = "sha256:2d192a155bbcec180f8564f693e6fd9bcccff5a7af9b32e24bf
8c9c69dbad6b5", size = 5308279, upload-time = "2026-04-01T14:43:13.246Z" },
 { url = "https://files.pythonhosted.org/packages/d8/95/0a351b9289c2b5cbde0bacd4a83ebc44023e835490a727b2a3bd60ddc0f4
/pillow-12.2.0-cp312-cp312-macosx_11_0_arm64.whl", hash = "sha256:f3f40b3c5a968281fd507d519e444c35f0ff171237f4fdde090dd
60699458421", size = 4695490, upload-time = "2026-04-01T14:43:15.584Z" },
 { url = "https://files.pythonhosted.org/packages/de/af/4e8e6869cbcd569d43c416fad3dc4ecb944cb5d9492defaed89ddd6fe871
/pillow-12.2.0-cp312-cp312-manylinux2014_aarch64.manylinux_2_17_aarch64.whl", hash = "sha256:03e7e372d5240cc23e9f07deca
4d775c0817bffc641b01e9c3af208dbd300987", size = 6284462, upload-time = "2026-04-01T14:43:18.268Z" },
 { url = "https://files.pythonhosted.org/packages/e9/9e/c05e19657fd57841e476be1ab46c4d501bffbabadbafdc31a6d665f8b737b6
/pillow-12.2.0-cp312-cp312-manylinux2014_x86_64.manylinux_2_17_x86_64.whl", hash = "sha256:b86024e52a1b269467a802258c25
521e6d742349d760728092e1bc2d135b4d76", size = 8094744, upload-time = "2026-04-01T14:43:20.716Z" },
 { url = "https://files.pythonhosted.org/packages/2b/54/1789c455ed10176066b6e7e6da1b01e50e36f94ba584dc68d9eebf9156d
/pillow-12.2.0-cp312-cp312-manylinux_2_27_aarch64.manylinux_2_28_aarch64.whl", hash = "sha256:7371b48c4fa448d20d2714c9a
1f775a81155050d383333e0a6c15b1123dda005", size = 6398371, upload-time = "2026-04-01T14:43:23.443Z" },
 { url = "https://files.pythonhosted.org/packages/43/e3/fdc657359e919462369869f1c9f0e973f353f9a9ee295a39b1fea8ee1a77
/pillow-12.2.0-cp312-cp312-manylinux_2_27_x86_64.manylinux_2_28_x86_64.whl", hash = "sha256:62f5409336adb0663b7caa0da5c
7d9e7bdbaae9ce761d34669420c2a801b2780", size = 7087215, upload-time = "2026-04-01T14:43:26.758Z" },
 { url = "https://files.pythonhosted.org/packages/8b/f8/2f6825e441d5b1959d2ca5adec984210f1ec086435b0ed5f52c19b3b8a6e
/pillow-12.2.0-cp312-cp312-musllinux_1_2_aarch64.whl", hash = "sha256:01afa7c6f7f74f09523699b4e88c73fb55c13346d212a59a2
db1f86b0a63e8c5", size = 6509783, upload-time = "2026-04-01T14:43:29.56Z" },
 { url = "https://files.pythonhosted.org/packages/67/f9/029a27095ad20f854f9dba026b3ea6428548316e057e6fc3545409e86651
/pillow-12.2.0-cp312-cp312-musllinux_1_2_x86_64.whl", hash = "sha256:fc3d34d4a8fbec3e88a79b92e5465e0f9b842b628675850d86
0b8bd300b159f5", size = 721212, upload-time = "2026-04-01T14:43:32.091Z" },
 { url = "https://files.pythonhosted.org/packages/be/42/025cfe05d1be22dbfdb4f264fe9de1ccda83f66e4fc3aac94748e784af04
/pillow-12.2.0-cp312-cp312-win32.whl", hash = "sha256:58f62cc0f00fd29e64b29f4fd923ffdb3859c9f9e6105bfc37ba1d08994e8940"
, size = 6378489, upload-time = "2026-04-01T14:43:34.601Z" },
 { url = "https://files.pythonhosted.org/packages/5d/7b/25a221d2c761c6a8ae21bfa3874988ff2583e19cf8a27bf2fee358df7942
/pillow-12.2.0-cp312-cp312-win_amd64.whl", hash = "sha256:7f84204dee22a783350679a0333981df803dac21a0190d706a50475e361c9
3f5", size = 7084129, upload-time = "2026-04-01T14:43:37.213Z" },
 { url = "https://files.pythonhosted.org/packages/10/e1/542a474affab20fd4a0f1836cb234e8493519da6b76899e30bcc5d990b8b
/pillow-12.2.0-cp312-cp312-win_arm64.whl", hash = "sha256:af73337013e0b3b46f175e79492d96845b16126ddf79c438d7ea7ff27783a
414", size = 2463612, upload-time = "2026-04-01T14:43:39.421Z" },
 { url = "https://files.pythonhosted.org/packages/4a/01/53d10cf0dbad820a8db274d259a37ba50b88b24768ddccce07355382d5ad
/pillow-12.2.0-cp313-cp313-ios_13_0_arm64_iphoneos.whl", hash = "sha256:8297651f5b5679c19968abefdb6b84d95fe30ef712eb1b2
d9b2d31ca61267f4c", size = 4100837, upload-time = "2026-04-01T14:43:41.506Z" },
 { url = "https://files.pythonhosted.org/packages/0f/98/f3a6657ecb698c937f6c76ee564882945f29b79bad496abcba0e84659ec5
/pillow-12.2.0-cp313-cp313-ios_13_0_arm64_iphonesimulator.whl", hash = "sha256:50d8520da2a6ce0af445fa6d648c4273c3eeefbc
32d7ce049f22e8b5c3daecc2", size = 4176528, upload-time = "2026-04-01T14:43:43.773Z" },
 { url = "https://files.pythonhosted.org/packages/69/bc/8986948f05e3ea490b8442ea1c1d4d990b24a7e43d8a51b2c7d8b1dced36
/pillow-12.2.0-cp313-cp313-ios_13_0_x86_64_iphonesimulator.whl", hash = "sha256:766cef22385fa1091258ad7e6216792b156dc16
d8d3fa607e7545b2b72061f1c", size = 3640401, upload-time = "2026-04-01T14:43:45.87Z" },
 { url = "https://files.pythonhosted.org/packages/34/46/6c717baadcd62bc8ed51d238d521ab651eaa74838291bda1f86fe1f864c9
/pillow-12.2.0-cp313-cp313-macosx_10_13_x86_64.whl", hash = "sha256:5d2fd0fa6b5d9d1de415060363433f28da8b1526c1c12902043
5e186794b3795", size = 5308094, upload-time = "2026-04-01T14:43:48.438Z" },
 { url = "https://files.pythonhosted.org/packages/71/43/905a14a8b17fdb1ccb58d282454490662d2cb89a6bfec26af6d3520da5ec
/pillow-12.2.0-cp313-cp313-macosx_11_0_arm64.whl", hash = "sha256:56b25336f502b6ed02e889f4ece894a72612fe885889a6e8c4c80
239ff6e5f5f", size = 4695402, upload-time = "2026-04-01T14:43:51.292Z" },
 { url = "https://files.pythonhosted.org/packages/73/dd/42107efcb777b16fa0393317eac58f5b5cf30e8392e266e76e51cff28c3d
/pillow-12.2.0-cp313-cp313-manylinux2014_aarch64.manylinux_2_17_aarch64.whl", hash = "sha256:f1c943e96e85df3d3478f7b691
f229887e143f81fedab9b20205349ab04d73ed", size = 6280005, upload-time = "2026-04-01T14:43:54.242Z" },
 { url = "https://files.pythonhosted.org/packages/a8/68/b93e09e5e8549019e61acf49f65b1a8530765a7f812c77a7461bca7e4494
/pillow-12.2.0-cp313-cp313-manylinux2014_x86_64.manylinux_2_17_x86_64.whl", hash = "sha256:03f6fab9219220f041c74aeaa293
9ff0062bd5c364ba9ce037197f4c6d498cd9", size = 8090669, upload-time = "2026-04-01T14:43:57.335Z" },
 { url = "https://files.pythonhosted.org/packages/4b/6e/3ccb54ce8ec4ddd1accd2d89004308b7b0b21c4ac3d20fa70af4760a4330
/pillow-12.2.0-cp313-cp313-manylinux_2_27_aarch64.manylinux_2_28_aarch64.whl", hash = "sha256:5cdfeb7d75ec52bf5bb4e35d9
c64b40826bc5b40a13df7c3cda20a2c03a0f5ed", size = 6395194, upload-time = "2026-04-01T14:43:59.864Z" },
 { url = "https://files.pythonhosted.org/packages/67/ee/21d4e8536afd1a328f01b359b4d3997b291ffdf35a237c877b331c1c3b71c
/pillow-12.2.0-cp313-cp313-manylinux_2_27_x86_64.manylinux_2_28_x86_64.whl", hash = "sha256:1e1757442ed87f4912397c6d35a0db6a7b52592156014706f1
7658ff58bbf795", size = 7208580, upload-time = "2026-04-01T14:44:08.39Z" },
 { url = "https://files.pythonhosted.org/packages/23/c4/7349421080b12fb35414607b8871e9534546c128a11965fd4a7002ccfbfee
```



/pillow-12.2.0-cp313-cp313-win32.whl", hash = "sha256:144748b3af2d1b358d41286056d0003f47cb339b8c43a9ea42f5fea4d8c66b6e", size = 6375896, upload-time = "2026-04-01T14:44:11.197Z" },

{ url = "https://files.pythonhosted.org/packages/3f/82/8a3739a5e470b3c6cbb1d21d315800d8e16bfff503d1f16b03a4ec3212786/pillow-12.2.0-cp313-cp313-win\_amd64.whl", hash = "sha256:390ede346628ccc626e5730107cde16c42d3836b89662a115a921f28440e6a3b", size = 7081266, upload-time = "2026-04-01T14:44:13.947Z" },

{ url = "https://files.pythonhosted.org/packages/c3/25/f968f618a062574294592f668218f8af564830ccebddd1fa6200f598e65c5/pillow-12.2.0-cp313-cp313-win\_arm64.whl", hash = "sha256:8023abc91fba39036dbce14a7d6535632f99c0b857807cbbbf21ecc9f4717f06", size = 2463508, upload-time = "2026-04-01T14:44:16.312Z" },

{ url = "https://files.pythonhosted.org/packages/4d/a4/b342930964e3cb4dce5038ae34b0eab4653334995336cd486c5a8c25a00c/pillow-12.2.0-cp313-cp313t-macosx\_10\_13\_x86\_64.whl", hash = "sha256:042db20a421b9bafec4b84a8b6e444686bd9d836c7fd24542db3e7df7baad9b", size = 5309927, upload-time = "2026-04-01T14:44:18.89Z" },

{ url = "https://files.pythonhosted.org/packages/9f/de/23198e0a65a9cf06123f5435a5d95cea62a635697f8f03d134d3f3a96151/pillow-12.2.0-cp313-cp313t-macosx\_11\_0\_arm64.whl", hash = "sha256:dd025009355c926a84a612fecf58bb315a3f6814b17ead51a8e48d3823d9087f", size = 4698624, upload-time = "2026-04-01T14:44:21.115Z" },

{ url = "https://files.pythonhosted.org/packages/01/a6/1265e977f17d93ea37aa28aa81bad4fa597933879fac2520d24e021c8da3/pillow-12.2.0-cp313-cp313t-manylinux2014\_aarch64.manylinux\_2\_17\_aarch64.whl", hash = "sha256:88ddbc66737e277852913bd1e07c150cc7bb124539f94c4e2df5344494e0a612", size = 6321252, upload-time = "2026-04-01T14:44:23.663Z" },

{ url = "https://files.pythonhosted.org/packages/3c/83/5982eb4a285967baa70340320be9f88e57665a387e3a53a7f0db8231a0cd/pillow-12.2.0-cp313-cp313t-manylinux2014\_x86\_64.manylinux\_2\_17\_x86\_64.whl", hash = "sha256:d362d1878f00c142b7e1a16e6e5e780f02be8195123f164edf7eddd911ee7c", size = 8126550, upload-time = "2026-04-01T14:44:26.772Z" },

{ url = "https://files.pythonhosted.org/packages/4e/48/6ffc514adce69f60500753b1a18fd920fcec8ac87620d5a31231b04bfc5/pillow-12.2.0-cp313-cp313t-manylinux\_2\_27\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:2c727a6d53cb0018aadd8018c2b938376af27914a68a492f59dfcaca650d5eea", size = 6433114, upload-time = "2026-04-01T14:44:29.615Z" },

{ url = "https://files.pythonhosted.org/packages/36/a3/f9a77144231fb8d40ee27107b4463e205fa4677e2ca2548e14da5cf18dce/pillow-12.2.0-cp313-cp313t-manylinux\_2\_27\_x86\_64.manylinux\_2\_28\_x86\_64.whl", hash = "sha256:efd8c21c98c5cc60653bcb311bef2ce0401642b7ce9d09e03a7da87c878289d4", size = 7115667, upload-time = "2026-04-01T14:44:32.773Z" },

{ url = "https://files.pythonhosted.org/packages/c1/fc/ac4ee3041e7d5a565e1c4fd72a113f03b6394cc72ab7089d27608f8aacbb/pillow-12.2.0-cp313-cp313t-musllinux\_1\_2\_aarch64.whl", hash = "sha256:9f08483a632889536b8139663db60f6724bfc443c96f1b18855860d7d5c0fd4", size = 6538966, upload-time = "2026-04-01T14:44:35.252Z" },

{ url = "https://files.pythonhosted.org/packages/c0/a8/27fb307055087f3668f6d0a8ccb636e7431d56ed0750e07a60547b1e083e/pillow-12.2.0-cp313-cp313t-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:dac8d77255a37e81a2efcbdf1fc05f1c15ee82200e6c240d7e127e25e365c39ea", size = 7238241, upload-time = "2026-04-01T14:44:37.875Z" },

{ url = "https://files.pythonhosted.org/packages/ad/4b/926ab182c07fcca9fcb120043464e1ff1564775ec8864f21a0ebce6ac25/pillow-12.2.0-cp313-cp313t-win32.whl", hash = "sha256:ee3120ae9dff32f121610bb08e4313be87e03efeadfc6c0d18f89127e24d0c24", size = 6379592, upload-time = "2026-04-01T14:44:40.336Z" },

{ url = "https://files.pythonhosted.org/packages/c2/c4/f9e476451a098181b30050cc4c9a3556b64c02cf6497ea421ac047e89e4b/pillow-12.2.0-cp313-cp313t-win\_amd64.whl", hash = "sha256:325ca0528c6788d2a6c3d40e3568639398137346c3d6e66bb1db96b96511c98", size = 7085542, upload-time = "2026-04-01T14:44:43.251Z" },

{ url = "https://files.pythonhosted.org/packages/00/a4/285f12aeacbe2d6dc36c407dfbbe9e96d4a80b0fb710a337f6d2ad978c75/pillow-12.2.0-cp313-cp313t-win\_arm64.whl", hash = "sha256:2e5a76d03a6c6dcef67edabda7a52494afa4035021a79c8558e14af25313d453", size = 2465765, upload-time = "2026-04-01T14:44:45.996Z" },

{ url = "https://files.pythonhosted.org/packages/bf/98/4595daa2365416a86cb0d495248a393dfc84e96d62ad080c8546256cb9c0/pillow-12.2.0-cp314-cp314-ios\_13\_0\_arm64\_iphoneos.whl", hash = "sha256:3adc9215e8be0448ed6e814966ecf3d9952f0ea40eb14e89a102b87f450660d8", size = 4100848, upload-time = "2026-04-01T14:44:48.482Z" },

{ url = "https://files.pythonhosted.org/packages/0b/79/40184d464cf89f6663e18dfcf7ca21aae2491fff1a16127681bf1fa9b8cf/pillow-12.2.0-cp314-cp314-ios\_13\_0\_arm64\_iphonesimulator.whl", hash = "sha256:6a9adfc6d24b10f89588096364cc726174118c62130c817c2837c60cf08a392b", size = 4176515, upload-time = "2026-04-01T14:44:51.353Z" },

{ url = "https://files.pythonhosted.org/packages/b0/63/703f86fd4c422a9cf722833670f4f71418fb116b2853ff7da722ea43f184/pillow-12.2.0-cp314-cp314-ios\_13\_0\_x86\_64\_iphonesimulator.whl", hash = "sha256:6a6e67ea2e6feda684ed370f9a1c52e7a243631c025ba42149a2cc5934dec295", size = 3640159, upload-time = "2026-04-01T14:44:53.588Z" },

{ url = "https://files.pythonhosted.org/packages/71/e0/fb22f797187d0be2270f83500aab851536101b254bfa1eae10795709d283/pillow-12.2.0-cp314-cp314-macosx\_10\_15\_x86\_64.whl", hash = "sha256:2bb4a8d594eacdfc59d9e5ad972aa8afdd48d584ffdf5f13a937a664c3e7db0ed", size = 5312185, upload-time = "2026-04-01T14:44:56.039Z" },

{ url = "https://files.pythonhosted.org/packages/ba/8c/1a9e46228571de18f8e28f16fabdfc20212a5d019f3e3303452b3f0a580d/pillow-12.2.0-cp314-cp314-macosx\_11\_0\_arm64.whl", hash = "sha256:80b2da48193b2f33ed0c32c38140f9d3186583ce7d516526d462645fd98660ae", size = 4695386, upload-time = "2026-04-01T14:44:58.663Z" },

{ url = "https://files.pythonhosted.org/packages/70/62/98f6b7f0c88b9add0e87c217ded307b36be024d4ff8869a812b241d1345/pillow-12.2.0-cp314-cp314-manylinux2014\_aarch64.manylinux\_2\_17\_aarch64.whl", hash = "sha256:22db17c68434de69d8ecfc2fe821569195c0c373b25ccc9cbdacf2c6e53c601", size = 6280384, upload-time = "2026-04-01T14:45:01.5Z" },

{ url = "https://files.pythonhosted.org/packages/5e/03/688747d2e91cfbe0e64f316cd2e8005698f76ada3130d0194664174fa5de/pillow-12.2.0-cp314-cp314-manylinux2014\_x86\_64.manylinux\_2\_17\_x86\_64.whl", hash = "sha256:7b14cc0106cd9aecd6a15dd6903840a058b4700fcb817687d0ee4fc8b6e389be", size = 8091599, upload-time = "2026-04-01T14:45:04.5Z" },

{ url = "https://files.pythonhosted.org/packages/f6/35/577e22b936fcd66537329b33af0b4ccfefaebad8aec04b266528cddb33c/pillow-12.2.0-cp314-cp314-manylinux\_2\_27\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:8cbeb542b2ebc6fcdacabf8ac8c1a97c9b3ad3927d46b8723f9d4f033288a0f", size = 6396021, upload-time = "2026-04-01T14:45:07.117Z" },

{ url = "https://files.pythonhosted.org/packages/11/8d/d2532ad2a603ca2b93ad9f5135732124e57811d0168155852f37fbce2458/pillow-12.2.0-cp314-cp314-manylinux\_2\_27\_x86\_64.manylinux\_2\_28\_x86\_64.whl", hash = "sha256:4bfd07bc812fbd20395212969e41931001fd59eb55a0658b0e5710872e95286", size = 7083360, upload-time = "2026-04-01T14:45:09.763Z" },

{ url = "https://files.pythonhosted.org/packages/5e/26/d325f9f56c7e039034897e7380e9cc202b1e368bfd04d4cbe6a441f02885/pillow-12.2.0-cp314-cp314-musllinux\_1\_2\_aarch64.whl", hash = "sha256:9aba9a17b623ef750a4d11b742cbafffeb48a869821252b30ee21b5e91392c50", size = 6507628, upload-time = "2026-04-01T14:45:12.378Z" },

{ url = "https://files.pythonhosted.org/packages/5f/f7/769d5632ffb0988f1c5e7660b3e731e30f7f8ec4318e94d0a5d674eb65a4/pillow-12.2.0-cp314-cp314-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:deede7c263feb25dba4e82ea23058a235dcc2fe1f6021025dc71f2b618e26104", size = 7209321, upload-time = "2026-04-01T14:45:15.122Z" },

{ url = "https://files.pythonhosted.org/packages/6a/7a/c253e3c645cd47f1aceea6a8bacdba9991bf45bb7dfe927f7c893e89c93c/pillow-12.2.0-cp314-cp314-win32.whl", hash = "sha256:632ff19b2778e43162304d50da0181ce24ac5bb8180122cbe1bf4673428328c7"



```
, size = 6479723, upload-time = "2026-04-01T14:45:17.797Z" },
 { url = "https://files.pythonhosted.org/packages/cd/8b/601e6566b957ca50e28725cb6c355c59c2c8609751efbecd980db44e0349
/pillow-12.2.0-cp314-cp314-win_amd64.whl", hash = "sha256:4e6c62e9d237e9b65fac06857d511e90d8461a32adcc1b9065ea0c0fa3a28
150", size = 7217400, upload-time = "2026-04-01T14:45:20.529Z" },
 { url = "https://files.pythonhosted.org/packages/d6/94/220e46c73065c3e2951bb91c11a1fb636c8c9ad427ac3ce7d7f3359b9b2f
/pillow-12.2.0-cp314-cp314-win_arm64.whl", hash = "sha256:b1c1fbd8a5a1af3412a0810d060a78b5136ec0836c8a4ef9aa11807f2a22f
4e1", size = 2554835, upload-time = "2026-04-01T14:45:23.162Z" },
 { url = "https://files.pythonhosted.org/packages/b6/ab/1b426a3974cb0e7da5c29ccff4807871d48110933a57207b5a676cccc155
/pillow-12.2.0-cp314-cp314t-macosx_10_15_x86_64.whl", hash = "sha256:57850958fe9c751670e49b2cec6f6294acc99e562531f4bd317
fa5dde2068463", size = 5314225, upload-time = "2026-04-01T14:45:25.637Z" },
 { url = "https://files.pythonhosted.org/packages/19/1e/dce46f371be2438eef2a1960ee2a243bbe5e961890146d2dee1ff0f12
/pillow-12.2.0-cp314-cp314t-macosx_11_0_arm64.whl", hash = "sha256:d5d38f1411c0ed9f97bcb49b7bd59b6b7c314e0e27420e34d99d
844b9ce3b6f3", size = 4698541, upload-time = "2026-04-01T14:45:28.355Z" },
 { url = "https://files.pythonhosted.org/packages/55/c3/7fbecf70adb3a0c33b77a300dc52e424dc22ad8cdc06557a2e49523b703d
/pillow-12.2.0-cp314-cp314t-manylinux2014_aarch64.manylinux_2_17_aarch64.whl", hash = "sha256:5c0a9f29ca8e79f09de89293f
82f9b0270bb4af1d58bc98f540cc4aedf03166", size = 6322251, upload-time = "2026-04-01T14:45:30.924Z" },
 { url = "https://files.pythonhosted.org/packages/1c/3c/7fbc17cfb7e4fe0ef1642e0abc17fc6c94c9f7a16be41498e12e2ba60408
/pillow-12.2.0-cp314-cp314t-manylinux2014_x86_64.manylinux_2_17_x86_64.whl", hash = "sha256:1610dd6c61621ae1cf811bef44d
77e149ce3f7b95afe66a4512f8c59f25d9ebe", size = 8127807, upload-time = "2026-04-01T14:45:33.908Z" },
 { url = "https://files.pythonhosted.org/packages/ff/c3/a8ae14d6defd2e448493ff512fae903b1e9bd40b72efb6ec55ce0048c8ce
/pillow-12.2.0-cp314-cp314t-manylinux_2_27_aarch64.manylinux_2_28_aarch64.whl", hash = "sha256:0a34329707af4f73cf1782a3
6cd2289c0368880654a2c11f027bcee9052d35dd", size = 6433935, upload-time = "2026-04-01T14:45:36.623Z" },
 { url = "https://files.pythonhosted.org/packages/6e/32/2880fb3a074847ac159d8f902cb43278a61e85f681661e7419e6596803ed
/pillow-12.2.0-cp314-cp314t-manylinux_2_27_x86_64.manylinux_2_28_x86_64.whl", hash = "sha256:8e9c4f5b3c546fa3458a29ab22
646c1c6c787ea8f5ef51300e5a60300736905e", size = 7116720, upload-time = "2026-04-01T14:45:39.258Z" },
 { url = "https://files.pythonhosted.org/packages/46/87/495cc9c30e0129501643f24d320076f4cc54f718341df18cc70ec94c44e1
/pillow-12.2.0-cp314-cp314t-musllinux_1_2_aarch64.whl", hash = "sha256:fb043ee2f06b41473269765c2feae53fc2e2fbf96e5e22ca
94fb5ad677856f06", size = 6540498, upload-time = "2026-04-01T14:45:41.879Z" },
 { url = "https://files.pythonhosted.org/packages/18/53/773f5edca692009d883a72211b60fdaf8871cbef075eaa9d577f0a2f989e
/pillow-12.2.0-cp314-cp314t-musllinux_1_2_x86_64.whl", hash = "sha256:f278f034eb75b4e8a13a54a876cc4a5ab39173d2cdd93a638
e1b467fc545ac43", size = 7239413, upload-time = "2026-04-01T14:45:44.705Z" },
 { url = "https://files.pythonhosted.org/packages/c9/e4/4b64a97d71b2a83158134abbb2f5bd3f8a2ea691361282f010998f339ec7
/pillow-12.2.0-cp314-cp314t-win32.whl", hash = "sha256:6bb77b2dcb0b620f9f4b4a8454caa581cd4dd0643a08bacf821216a16d9c8354
", size = 6482084, upload-time = "2026-04-01T14:45:47.568Z" },
 { url = "https://files.pythonhosted.org/packages/ba/13/306d275efd3a3453f72114b7431c877d10b1154014c1ebbedd067770d629
/pillow-12.2.0-cp314-cp314t-win_amd64.whl", hash = "sha256:6562ace0d3fb5f20ed7290f1f929cae41b25ae29528f2af1722966a0a02e
2aa1", size = 7225152, upload-time = "2026-04-01T14:45:50.032Z" },
 { url = "https://files.pythonhosted.org/packages/ff/6e/cf826fae916b8658848d7b9f38d88da6396895c67e8086fc0988073aaf8
/pillow-12.2.0-cp314-cp314t-win_arm64.whl", hash = "sha256:aa88ccfe4e32d362816319ed727a004423aab09c5cea43c01a4b435643fa
34eb", size = 2556579, upload-time = "2026-04-01T14:45:52.529Z" },
]
```

```
[[package]]
name = "pluggy"
version = "1.6.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/f9/e2/3e91f31a7d2b083fe6ef3fa267035b518369d9511ffab804f839851d
2779/pluggy-1.6.0.tar.gz", hash = "sha256:7dccc130b76258d33b90f61b658791dede3486c3e6bfb003ee5c9bfb396dd22f3", size = 694
12, upload-time = "2025-05-15T12:30:07.975Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/54/20/4d324d65cc6d9205fabledc306948156824eb9f0ee1633355a8f7ec5c66bf
/pluggy-1.6.0-py3-none-any.whl", hash = "sha256:e920276dd6813095e9377c0bc5566d94c932c33b27a3e3945d8389c374dd4746", size
= 20538, upload-time = "2025-05-15T12:30:06.134Z" },
]
```

```
[[package]]
name = "protobuf"
version = "7.35.1"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/da/01/9ef0afd7999eb9badb3a768b4aedd78c86d4c65cfaf1958ab276199e
76b4/protobuf-7.35.1.tar.gz", hash = "sha256:ce115a26fe0c39a2c29973d914d327e516a6455464489fe3cd1e51a1b354f81a", size =
458717, upload-time = "2026-06-11T21:55:40.257Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/10/03/8aeeb7458d22546bf64b5250ca1daeb5ff757d900e8e4a7476c6f0db843e
/protobuf-7.35.1-cp310-abi3-macosx_10_9_universal2.whl", hash = "sha256:24f857477359a85c0c235261b8ba905fd51b2562f4a64ca
1df5473f29850cbf6", size = 433226, upload-time = "2026-06-11T21:55:31.719Z" },
 { url = "https://files.pythonhosted.org/packages/37/4b/dfb89eb0e652a1ff073c39a59fb5e3a83cfe9b57a2c83fa6d78270101767
/protobuf-7.35.1-cp310-abi3-manylinux2014_aarch64.whl", hash = "sha256:11d6b0ec246892d85215b0a13ca6e0233cf5284b68f0ac02
646427f4ff88a799", size = 328847, upload-time = "2026-06-11T21:55:34.035Z" },
 { url = "https://files.pythonhosted.org/packages/0f/58/dc12f2cd484951524af6e3382c785869b9b3fb5e52ee95ae23add53ee8f9
/protobuf-7.35.1-cp310-abi3-manylinux2014_s390x.whl", hash = "sha256:b73f9489a4b8b1c9cb1f8ed951c736392592edb24b9d6819f3
6d2e10b171d5b4", size = 344030, upload-time = "2026-06-11T21:55:34.941Z" },
 { url = "https://files.pythonhosted.org/packages/e4/be/5b3cfe508bfab761414ff944e3366eb13be4fd71efcd69450f89ba39f43
/protobuf-7.35.1-cp310-abi3-manylinux2014_x86_64.whl", hash = "sha256:74758715c53d7158fb76caf4f0cfdacc5329a4b1bb994f865
d6cf302d413a1c4", size = 327130, upload-time = "2026-06-11T21:55:35.921Z" },
 { url = "https://files.pythonhosted.org/packages/d8/bc/6d6c7ba8709c85f8f2c390b2b118d6fb08a783676a572271851bf45a7d22
```

```

/protobuf-7.35.1-cp310-abi3-win32.whl", hash = "sha256:353652e4efdbca5b5fc2656abf8307ef351f0cf938c9eba09f0e09c20a25c30", size = 428945, upload-time = "2026-06-11T21:55:37.034Z" },
 { url = "https://files.pythonhosted.org/packages/0a/19/8d0cb6f20a1ef7b18f1c8986ad5783f22f84cce39c6ce9a6e645ea55192e/protobuf-7.35.1-cp310-abi3-win_amd64.whl", hash = "sha256:230a75ddfc2de4806e56696ce9640c1cdfdb6543b7cfc98d42a4c0a0e7bdb87", size = 439996, upload-time = "2026-06-11T21:55:38.123Z" },
 { url = "https://files.pythonhosted.org/packages/19/c7/5f7c636ec43e0c545e28d1fdb71990108306f7bdc89f069ba97e428e7f/protobuf-7.35.1-py3-none-any.whl", hash = "sha256:4bc97768d8fe4ad6743c8a19403e314511ed9f6d13205b687e52421c023ac1b9", size = 171659, upload-time = "2026-06-11T21:55:39.155Z" },
]

[[package]]
name = "pyarrow"
version = "24.0.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/91/13/13e1069b351bdc3881266e11147ffccf687505dbb0ea74036237f5d454a5/pyarrow-24.0.0.tar.gz", hash = "sha256:85fe721a14dd823aca09127acbb06c3ca723efbd436c004f16bca601b04dcc83", size = 180261, upload-time = "2026-04-21T10:51:25.837Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/b4/a9/9686d9f07837f91f775e8932659192e02c74f9d8920524b480b85212cc68/pyarrow-24.0.0-cp312-cp312-macosx_12_0_arm64.whl", hash = "sha256:6233c9ed9ab9d1db47de57d9753256d9dcffbf42db341576099f0fd9f6bf4810", size = 34981559, upload-time = "2026-04-21T10:47:22.17Z" },
 { url = "https://files.pythonhosted.org/packages/80/b6/0ddfe09b6ead3474ab087ae598c76b031fc45532bf6a63f3a553440fb258/pyarrow-24.0.0-cp312-cp312-macosx_12_0_x86_64.whl", hash = "sha256:f7616236ec1bc2b15bfdec22a71ab38851c86f8f05ff64f379e1278cf20c634a", size = 36663654, upload-time = "2026-04-21T10:47:28.315Z" },
 { url = "https://files.pythonhosted.org/packages/7c/3b/926382efe8ce27ba729071d3566ade6dfb86bdf112f366000196b2f5780a/pyarrow-24.0.0-cp312-cp312-manylinux_2_28_aarch64.whl", hash = "sha256:1617043b99bd33e5318ae18eb2919af09c71322ef1ca46566cdafc6e6712fb66", size = 45679394, upload-time = "2026-04-21T10:47:34.821Z" },
 { url = "https://files.pythonhosted.org/packages/b3/7a/829f7d9dfd37c207206081d6dad474d81dde29952401f07f2ba507814818/pyarrow-24.0.0-cp312-cp312-manylinux_2_28_x86_64.whl", hash = "sha256:6165461f55ef6314f026de6638d661188e3455d3ec49834556a0ebdbbace18bb", size = 48863122, upload-time = "2026-04-21T10:47:42.056Z" },
 { url = "https://files.pythonhosted.org/packages/5f/e8/f88ce625fe8babaee64e8db2d417c7653adb3019b08aae85c5ed787dc816/pyarrow-24.0.0-cp312-cp312-musllinux_1_2_aarch64.whl", hash = "sha256:3b13dedfe76a0ad2d1d859b0811b53827a4e9d93a0bcb05cf59333ab4980cc7e", size = 49376032, upload-time = "2026-04-21T10:47:48.967Z" },
 { url = "https://files.pythonhosted.org/packages/36/7a/82c363caa145fff88fb475da50d3bf52bb024f61917be5424c3392eaf878/pyarrow-24.0.0-cp312-cp312-musllinux_1_2_x86_64.whl", hash = "sha256:25ea65d868eb04015cd18e6df2f2be98f07e5bda2abefabcb88fce39a947716f6", size = 51929490, upload-time = "2026-04-21T10:47:55.981Z" },
 { url = "https://files.pythonhosted.org/packages/66/1c/e3e72c8014ad2743ca64a701652c733cc5cbcee15c0463a32a8c55518d9e/pyarrow-24.0.0-cp312-cp312-win_amd64.whl", hash = "sha256:295f0af7e2e242dabd513737cf076007dc5b2d59237e3eca37b05c0c6446f3826", size = 27355660, upload-time = "2026-04-21T10:48:01.718Z" },
 { url = "https://files.pythonhosted.org/packages/6f/d3/a1abf004482026ddc17f4503db227787fa3cfe41ec5091ff20e4fea55e57/pyarrow-24.0.0-cp313-cp313-macosx_12_0_arm64.whl", hash = "sha256:02b00b13ed4723caa44f6cd1af2d5c86aa2cf9971dacc2ffa55b21237713dfba", size = 34976759, upload-time = "2026-04-21T10:48:07.258Z" },
 { url = "https://files.pythonhosted.org/packages/4f/4a/34f0a36d28a2dd32225301b79daad44e243dc1a2bb77d43b60749be255c4/pyarrow-24.0.0-cp313-cp313-macosx_12_0_x86_64.whl", hash = "sha256:04920d6a71aabd08a0417709efce97d45ea8e6fb733d9ca9ecfb13c67839f68", size = 36658471, upload-time = "2026-04-21T10:48:13.347Z" },
 { url = "https://files.pythonhosted.org/packages/1f/78/543b94712ae8bb1a6023bcc1ac1fa740fbff8286747c289cd9468fced2a5/pyarrow-24.0.0-cp313-cp313-manylinux_2_28_aarch64.whl", hash = "sha256:a964266397740257f16f7bb2e4f08a0c81454004beab8ff59dd531b73610e9f2", size = 45675981, upload-time = "2026-04-21T10:48:20.201Z" },
 { url = "https://files.pythonhosted.org/packages/84/9f/8fb7c222b100d314137fa40ec050de56cd8c6d957d1cfff685ce72f15b17/pyarrow-24.0.0-cp313-cp313-manylinux_2_28_x86_64.whl", hash = "sha256:6f066b179d68c413374294bc1735f68475457c933258df594443bb9d88ddc2a0", size = 48859172, upload-time = "2026-04-21T10:48:27.541Z" },
 { url = "https://files.pythonhosted.org/packages/a7/d3/1ea72538e6c8b3b475ed78d1049a2c518e655761ea50fe1171fc855fcab7/pyarrow-24.0.0-cp313-cp313-musllinux_1_2_aarch64.whl", hash = "sha256:1183baeb14c5f587b1ec52831e665718ce632caab84b7cd6b85fd44f96114495", size = 49385733, upload-time = "2026-04-21T10:48:34.7Z" },
 { url = "https://files.pythonhosted.org/packages/c3/be/c3d8b06a1ba35f2260f8e1f771abbee7d5e345c0937aab90675706b1690a/pyarrow-24.0.0-cp313-cp313-musllinux_1_2_x86_64.whl", hash = "sha256:806f24b4085453c197a5078218d1ee08783ebba271badd153d1ae22a3ee804f", size = 51934335, upload-time = "2026-04-21T10:48:42.099Z" },
 { url = "https://files.pythonhosted.org/packages/9c/62/89e07a1e7329d2cde3e3c6994ba0839a24977a2beda8be6005ea3d860b99/pyarrow-24.0.0-cp313-cp313-win_amd64.whl", hash = "sha256:e4505fc6583f7b05ab854934896bcac8253b04ac1171a77dfb73efef92076d91", size = 27271748, upload-time = "2026-04-21T10:49:42.532Z" },
 { url = "https://files.pythonhosted.org/packages/17/1a/cff3a59f80b5b1658549d46611b67163f65e0664431c076ad728bf9d5af4/pyarrow-24.0.0-cp313-cp313t-macosx_12_0_arm64.whl", hash = "sha256:1a4e45017efbf115032e4475ee876d525e0e36c742214fbe405332480ecd6275", size = 35238554, upload-time = "2026-04-21T10:48:48.526Z" },
 { url = "https://files.pythonhosted.org/packages/a8/99/cce0f42a327bfef2c420fb6078a3eb834826e5d6697bf3009fe11d2ad051/pyarrow-24.0.0-cp313-cp313t-macosx_12_0_x86_64.whl", hash = "sha256:7986f1fa71cee060ad00758bcc79d3a93bab8559bf978fab9e53472a2e25a17b", size = 36782301, upload-time = "2026-04-21T10:48:55.181Z" },
 { url = "https://files.pythonhosted.org/packages/2a/66/8e560d5ff6793ca29aca213c53eec0dd482dd46cb93b2819e5aab52e4252/pyarrow-24.0.0-cp313-cp313t-manylinux_2_28_aarch64.whl", hash = "sha256:d3e0b61e8efb24ed38898e5cdc5fffa9124be480008d401a1f8071500494ae42", size = 45721929, upload-time = "2026-04-21T10:49:03.676Z" },
 { url = "https://files.pythonhosted.org/packages/27/0c/a26e25505d030716e078d9f16eb74973cbf0b33b672884e9f9da1c83b871/pyarrow-24.0.0-cp313-cp313t-manylinux_2_28_x86_64.whl", hash = "sha256:55a3bc1e3df3b5567b7d27ef551b2283f0c68a5e86f1cd56abc569da4f31335b", size = 48825365, upload-time = "2026-04-21T10:49:11.714Z" },
 { url = "https://files.pythonhosted.org/packages/5f/eb/771f9ecb0c65e73fe9dcccdd1717901b9594f08c4515d000c7c62df573811/pyarrow-24.0.0-cp313-cp313t-musllinux_1_2_aarch64.whl", hash = "sha256:641f795b361874ac9da5294f8f443dfdbee355cf2bd9e3b8d97aaac2306b9b37", size = 49451819, upload-time = "2026-04-21T10:49:21.474Z" },
 { url = "https://files.pythonhosted.org/packages/48/da/61ae89a88732f5a785646f3ec6125dbb640fa98a540eb2b9889caa561403

```

```

/pyarrow-24.0.0-cp313-cp313t-musllinux_1_2_x86_64.whl", hash = "sha256:8adc8e6ce5fccf5dc707046ae4914fd537def529709cc0d2
85d37a7f9cd442ca", size = 51909252, upload-time = "2026-04-21T10:49:31.164Z" },
 { url = "https://files.pythonhosted.org/packages/cb/1a/8dd5cafab7b66573fa91c03d06d213356ad4edd71813aa75e08ce2b3a844
/pyarrow-24.0.0-cp313-cp313t-win_amd64.whl", hash = "sha256:9b18371ad2f44044b81a8d23bc2d8a9b6a6226dca775e8e16cfee640473
d6c5d", size = 27388127, upload-time = "2026-04-21T10:49:37.334Z" },
 { url = "https://files.pythonhosted.org/packages/ad/80/d022a34ff05d2cbedd8ccf841fc1f532ecfa9eb5ed1711b56d0e0ea71fc9
/pyarrow-24.0.0-cp314-cp314-macosx_12_0_arm64.whl", hash = "sha256:1cc9057f0319e26333b357e17f3c2c022f1a83739b48a88b25bf
d5fa2dc18838", size = 35007997, upload-time = "2026-04-21T10:49:48.796Z" },
 { url = "https://files.pythonhosted.org/packages/1a/ff/f01485fda6f4e5d441afb8dd5e7681e4db18826c1e271852f5d3957d6a80
/pyarrow-24.0.0-cp314-cp314-macosx_12_0_x86_64.whl", hash = "sha256:e6f1278ee4785b6db21229374a1c9e54ec7c549de5d1efc9630
b6207de7e170b", size = 36678720, upload-time = "2026-04-21T10:49:55.858Z" },
 { url = "https://files.pythonhosted.org/packages/9e/c2/2d2d5fea814237923f71b36495211f20b43a1576f9a4d6da7e751a64ec6f
/pyarrow-24.0.0-cp314-cp314-manylinux_2_28_aarch64.whl", hash = "sha256:adbbec55506cbdabb830890444fb856bfb060c46c6f80
26c6c2f2cf86ae795", size = 45741852, upload-time = "2026-04-21T10:50:04.624Z" },
 { url = "https://files.pythonhosted.org/packages/8e/3a/28ba9c1c1ebdbb5f1b94dfebb46f207e52e6a554b7fe4132540fde29a3a0
/pyarrow-24.0.0-cp314-cp314-manylinux_2_28_x86_64.whl", hash = "sha256:ae8a1145af31d903fa9bb166824d7abe9b4681a000b0159c
9fb99c11bc11ad26", size = 48889852, upload-time = "2026-04-21T10:50:12.293Z" },
 { url = "https://files.pythonhosted.org/packages/df/51/4a389acfd31dca009f8fb82d7f510bb4130f2b3a8e18cf00194d0687d8ac
/pyarrow-24.0.0-cp314-cp314-musllinux_1_2_aarch64.whl", hash = "sha256:d7027eba1df3b2069e2e8d80f644fa0918b68c46432af3d0
88ddd390d063ecde", size = 49445207, upload-time = "2026-04-21T10:50:20.677Z" },
 { url = "https://files.pythonhosted.org/packages/19/4b/0bab2b23d2ae901b1b9a03c0efd4b2d070256f8ce3fc43f6e58c167b2081
/pyarrow-24.0.0-cp314-cp314-musllinux_1_2_x86_64.whl", hash = "sha256:e56a1ffe9bf7b727432b89104cc0849c21582949dd7bdc34
f17b2001a351a76", size = 51954117, upload-time = "2026-04-21T10:50:29.14Z" },
 { url = "https://files.pythonhosted.org/packages/29/88/f4e9145da0417b3d2c12035a8492b35fff4a3dbc653e614fcb51d9dedb38
/pyarrow-24.0.0-cp314-cp314-win_amd64.whl", hash = "sha256:38be1808cdd068605b787e6ca9119b27eb275a0234e50212c3492331680c
3b1e", size = 28001155, upload-time = "2026-04-21T10:51:22.337Z" },
 { url = "https://files.pythonhosted.org/packages/79/4f/46a49a63f43526da895b1a45bbb51d5baf8e4d77159f8528fc3e5490007f
/pyarrow-24.0.0-cp314-cp314t-macosx_12_0_arm64.whl", hash = "sha256:418e48ce50a45a6a6c73c454677203a9c75c966cb1e92ca3370
959185f197a05", size = 35250387, upload-time = "2026-04-21T10:50:35.552Z" },
 { url = "https://files.pythonhosted.org/packages/a0/da/d5e0cd5ef00796922404806d5f00325cdadc3441ce2c13fe7115f2df9a64
/pyarrow-24.0.0-cp314-cp314t-macosx_12_0_x86_64.whl", hash = "sha256:2f16197705a230a78270cdd4ea8a1d57e86b2fdbc34a1f6ae
bc72e65c986f9a", size = 36797102, upload-time = "2026-04-21T10:50:42.417Z" },
 { url = "https://files.pythonhosted.org/packages/34/c7/5904145b0a593a05236c882933d439b5720f0a145381179063722fbfc123
/pyarrow-24.0.0-cp314-cp314t-manylinux_2_28_aarch64.whl", hash = "sha256:fb24ac194bfc5e86839d7dcd52092ee31e5fe6733fe11f
5e3b06ef0812b20072", size = 45745118, upload-time = "2026-04-21T10:50:49.324Z" },
 { url = "https://files.pythonhosted.org/packages/13/d3/cc42fe166d1c6e4d5b80e530b7949104d10e17508a90ae202dac205ce2a
/pyarrow-24.0.0-cp314-cp314t-manylinux_2_28_x86_64.whl", hash = "sha256:9700ebd9a51f5895ce75ff4ac4b3c47a7d4b42bc618be8e
713e5d56bacf5f931", size = 48844765, upload-time = "2026-04-21T10:50:55.579Z" },
 { url = "https://files.pythonhosted.org/packages/b0/49/942c3b79878ba928324d1e17c274ed84581db8c0a749b24bcf4cbdf15bd3
/pyarrow-24.0.0-cp314-cp314t-musllinux_1_2_aarch64.whl", hash = "sha256:d8dd2768da81d3ee08cfea9b597f4abb4e8e1dc8ae7e20
4b608d23a0d3ab699", size = 49471890, upload-time = "2026-04-21T10:51:02.439Z" },
 { url = "https://files.pythonhosted.org/packages/76/97/ff71431000a75d84135a1ace5ca4ba11726a231a8007bbb320a4c54075d5
/pyarrow-24.0.0-cp314-cp314t-musllinux_1_2_x86_64.whl", hash = "sha256:61a3d7eaa97a14768b542f3d284dc6400dd2470d9f080708
b13cd46b6ae18136", size = 51932250, upload-time = "2026-04-21T10:51:10.576Z" },
 { url = "https://files.pythonhosted.org/packages/51/be/6f79d55816d5c22557cf27533543d5d70dfe692adfbee4b99f2760674f38
/pyarrow-24.0.0-cp314-cp314t-win_amd64.whl", hash = "sha256:c91d00057f23b8d353039520dc3a6c09d8608164c692e9f59a175a42b2a
e0c19", size = 28131282, upload-time = "2026-04-21T10:51:16.815Z" },
]

[[package]]
name = "pycparser"
version = "3.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/1b/7d/92392ff7815c21062bea51aa7b87d45576f649f16458d78b7cf94b9a
b2e6/pycparser-3.0.tar.gz", hash = "sha256:600f49d217304a5902ac3c37e1281c9fe94e4d0489de643a9504c5cdfdfc6b29", size = 10
3492, upload-time = "2026-01-21T14:26:51.89Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/0c/c3/44f3fbbfa403ea2a7c779186dc20772604442dde72947e7d01069cbe98e3
/pycparser-3.0-py3-none-any.whl", hash = "sha256:b727414169a36b7d524c1c3e31839a521725078d7b2ff038656844266160a992", siz
e = 48172, upload-time = "2026-01-21T14:26:50.693Z" },
]

[[package]]
name = "pydantic"
version = "2.13.4"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "annotated-types" },
 { name = "pydantic-core" },
 { name = "typing-extensions" },
 { name = "typing-inspection" },
]
sdist = { url = "https://files.pythonhosted.org/packages/18/a5/b60d21ac674192f8ab0ba4e9fd860690f9b4a6e51ca5df118733b487
d8d6/pydantic-2.13.4.tar.gz", hash = "sha256:c40756b57adaa8b1efeeced5c196f3f3b7c435f90e84ea7f443901bec8099ef6", size =
844775, upload-time = "2026-05-06T13:43:05.343Z" }
wheels = [

```

```

{ url = "https://files.pythonhosted.org/packages/fd/7b/122376b1fd3c62c1ed9dc80c931ace4844b3c55407b6fb2d199377c9736f
/pydantic-2.13.4-py3-none-any.whl", hash = "sha256:45a282cde31d808236fd7ea9d919b128653c8b38b393d1c4ab335c62924d9aba", s
ize = 471464, upload-time = "2026-05-06T13:43:02.641Z" },
]

[[package]]
name = "pydantic-core"
version = "2.46.4"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "typing-extensions" },
]
sdist = { url = "https://files.pythonhosted.org/packages/9d/56/921726b776ace8d8f5db44c4ef961006580d91dc52b803c489fafd1a
a249/pydantic_core-2.46.4.tar.gz", hash = "sha256:62f875393d7f270851f20523dd2e29f082bcc82292d66db2b64ea71f64b6e1c1", si
ze = 471464, upload-time = "2026-05-06T13:37:06.982Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/ce/8c/af022f0af448d7747c5154288d46b5f2bc5f17366eaa0e23e9aa04d59f3b
/pydantic_core-2.46.4-cp312-cp312-macosx_10_12_x86_64.whl", hash = "sha256:3245406455a5d98187ec35530fd772b1d799b2666798
0872c8d4614991e2c4a2", size = 2106158, upload-time = "2026-05-06T13:38:57.215Z" },
 { url = "https://files.pythonhosted.org/packages/19/95/6195171e385007300f0f5574592e467c568becce2d937a0b6804f218bc49
/pydantic_core-2.46.4-cp312-cp312-macosx_11_0_arm64.whl", hash = "sha256:962ccbab7b642487b1d8b7df90ef677e03134cf1fd8880
bf698649b22a69371f", size = 1951724, upload-time = "2026-05-06T13:37:02.697Z" },
 { url = "https://files.pythonhosted.org/packages/8e/bc/f47d1ff9cbb1620e1b5b697eef06010035735f07820180e74178226b27b3
/pydantic_core-2.46.4-cp312-cp312-manylinux_2_17_aarch64.manylinux2014_aarch64.whl", hash = "sha256:8233f2947cf85404441
fd7e0085f53b10c93e0ee78611099b5c7237e36aacbf7", size = 1975742, upload-time = "2026-05-06T13:37:09.448Z" },
 { url = "https://files.pythonhosted.org/packages/5b/11/9b9a5b0306345664a2da6410877af6e8082481b5884b3ddd78d47c6013ce
/pydantic_core-2.46.4-cp312-cp312-manylinux_2_17_armv7l.manylinux2014_armv7l.whl", hash = "sha256:3a233125ac121aa3ffba9
a2b59edfc4a985a76092dc8279586ab4b71390875e7", size = 2052418, upload-time = "2026-05-06T13:37:38.234Z" },
 { url = "https://files.pythonhosted.org/packages/f1/b7/a65fec226f5d78fc39f4a13c4cc0c768c22b113438f60c14adc9d2865038
/pydantic_core-2.46.4-cp312-cp312-manylinux_2_17_ppc64le.manylinux2014_ppc64le.whl", hash = "sha256:5b712b53160b79a5850
310b912a5ef8e57e56947c8ad690c227f5c9d7e561712", size = 2232274, upload-time = "2026-05-06T13:38:27.753Z" },
 { url = "https://files.pythonhosted.org/packages/68/f0/92039db98b907ef49269a8271f67db9cb78ae2fc68062ef7e4e77adb5f61
/pydantic_core-2.46.4-cp312-cp312-manylinux_2_17_s390x.manylinux2014_s390x.whl", hash = "sha256:9401557acd873c3a7f3eb93
83edef8ac4968f9510e340f4808d427e75667e7b4", size = 2309940, upload-time = "2026-05-06T13:38:05.353Z" },
 { url = "https://files.pythonhosted.org/packages/5f/97/2aab507d3d00ca626e8e57c1eac6a79e4e5fbcc63eb99733ff55d1717f65
/pydantic_core-2.46.4-cp312-cp312-manylinux_2_17_x86_64.manylinux2014_x86_64.whl", hash = "sha256:926c9541b14b12b1681dc
a8a0b75feb510b06c6341b70a8e500c2f2dcff837cce", size = 2094516, upload-time = "2026-05-06T13:39:10.577Z" },
 { url = "https://files.pythonhosted.org/packages/22/37/a8aca44d40d737dde2bc05b3c6c07dff0de07ce6f82e9f3167aeaf4d5dea
/pydantic_core-2.46.4-cp312-cp312-manylinux_2_31_riscv64.whl", hash = "sha256:56cb4851bcacf3d117eddcfe4fe66afd750a50274b
0da8e22be256d10e5611987", size = 2136854, upload-time = "2026-05-06T13:40:22.59Z" },
 { url = "https://files.pythonhosted.org/packages/24/99/fcefb1b79238c06a8cbec70819ac722ba76e02bc8ada9b0fd66eba40da01b
/pydantic_core-2.46.4-cp312-cp312-manylinux_2_5_i686.manylinux1_i686.whl", hash = "sha256:c68fcd102d71ea85c5b2dfac3f4f8
476eff42a9e078fd5faefff6d145063536b", size = 2180306, upload-time = "2026-05-06T13:40:10.666Z" },
 { url = "https://files.pythonhosted.org/packages/ae/6c/fc44000918855b42779d007ae63b0532794739027b2f417321cddbc44f6a
/pydantic_core-2.46.4-cp312-cp312-musllinux_1_1_aarch64.whl", hash = "sha256:b2f69dec1725e79a012d920df1707de5caf7ed5e08
f3be4435e25803efc47458", size = 2190044, upload-time = "2026-05-06T13:40:43.231Z" },
 { url = "https://files.pythonhosted.org/packages/6b/65/d9cad9f1920d7a127ad2edba16c1db7916e59719285cd6c94600b0080ba
/pydantic_core-2.46.4-cp312-cp312-musllinux_1_1_armv7l.whl", hash = "sha256:8d0820e8192167f80d88d64038e609c31452eeca865
b4e1d9950a27a4609b00b", size = 2329133, upload-time = "2026-05-06T13:39:57.365Z" },
 { url = "https://files.pythonhosted.org/packages/d0/cf/c873d91679f3a30bcf5e7ac280ce5573483e72295307685120d0d5ad3416
/pydantic_core-2.46.4-cp312-cp312-musllinux_1_1_x86_64.whl", hash = "sha256:fbdb89b3e1c94a30cc5edf477c6e6a5dc4d8f8466
5b455c27582f211a1c72c", size = 2374464, upload-time = "2026-05-06T13:38:06.976Z" },
 { url = "https://files.pythonhosted.org/packages/47/bd/6f2fc8188f31bf10590f1e98e7b306336161fac930a8c514cd7bd828c7dc
/pydantic_core-2.46.4-cp312-cp312-win32.whl", hash = "sha256:9aa768456404a8bf48a4406685ac2bec8e72b62c69313734fa3b73cf33
b3a894", size = 1974823, upload-time = "2026-05-06T13:40:47.985Z" },
 { url = "https://files.pythonhosted.org/packages/40/8c/985c1d41ea1107c2534abd9870e4ed5c8e7669b5c308297835c001e7a1c4
/pydantic_core-2.46.4-cp312-cp312-win_amd64.whl", hash = "sha256:e9c26f834c65f5752f3f06cb08cb86a913ceb7274d0db6e267808a
708b46bc89", size = 2072919, upload-time = "2026-05-06T13:39:21.153Z" },
 { url = "https://files.pythonhosted.org/packages/c4/ba/f463d006e0c47373ca7ec5e1a261c59dc01ef4d62b2657af925fb0deee3a
/pydantic_core-2.46.4-cp312-cp312-win_arm64.whl", hash = "sha256:4fc73cb559bdb54b1134a706a2802a4cddd27a0633f5abb7e53056
268751ac6a", size = 2027604, upload-time = "2026-05-06T13:39:03.753Z" },
 { url = "https://files.pythonhosted.org/packages/51/a2/5d30b469c5267a17b39dec53208222f76a8d351dfac4af661888c5aee77d
/pydantic_core-2.46.4-cp313-cp313-macosx_10_12_x86_64.whl", hash = "sha256:5d5902252db0d3cedf8d4a1bc68f70eeb430f7e4c710
4c8c476753519b423008", size = 2106306, upload-time = "2026-05-06T13:37:48.029Z" },
 { url = "https://files.pythonhosted.org/packages/c1/81/4fa520eaffa8bd7d1525e644cd6d39e7d60b1592bc5b516693c7340b50f1
/pydantic_core-2.46.4-cp313-cp313-macosx_11_0_arm64.whl", hash = "sha256:c94f0688e7b8d0a67abf40e57a7eaaecd17cc9586706a3
1b76c031f63df052b4", size = 1951906, upload-time = "2026-05-06T13:37:17.012Z" },
 { url = "https://files.pythonhosted.org/packages/03/d5/fd02da45b65968b0c5923b17ba3a0100a0a3d5541e3bd8fcc4ecb711309e
/pydantic_core-2.46.4-cp313-cp313-manylinux_2_17_aarch64.manylinux2014_aarch64.whl", hash = "sha256:f027324c56cd5406ca4
9c124b0db10e56c69064fec039acc571c29020cc87c76", size = 1976802, upload-time = "2026-05-06T13:37:35.113Z" },
 { url = "https://files.pythonhosted.org/packages/21/f2/95727e1368be3d3ed485eaab7adbd7dda08f33f7a36e8b48e0144002b91
/pydantic_core-2.46.4-cp313-cp313-manylinux_2_17_armv7l.manylinux2014_armv7l.whl", hash = "sha256:e739fee756ba1010f8bcc
cb534252e85a35fe45ae92c295a06059ce58b74ccd3", size = 2052446, upload-time = "2026-05-06T13:37:12.313Z" },
 { url = "https://files.pythonhosted.org/packages/9c/86/5d99feea3f77c7234b8718075b23db11532773c1a0dbd9b9490215dc2eeb
/pydantic_core-2.46.4-cp313-cp313-manylinux_2_17_ppc64le.manylinux2014_ppc64le.whl", hash = "sha256:9d56801be94b86a9da1
83e5f3766e6310752b99ff647e38b09a9500d88e46e76", size = 2232757, upload-time = "2026-05-06T13:39:01.149Z" },

```

{ url = "https://files.pythonhosted.org/packages/d2/3a/508ac615935ef7588cf6d9e9b91309fdc2da751af865e02a9098de88258c/pydantic\_core-2.46.4-cp313-cp313-manylinux\_2\_17\_s390x.manylinux2014\_s390x.whl", hash = "sha256:2412e734dcb48da14d4e4006b82b46b74f2518b8a26ee7e58c6844a6cd6d03c4", size = 2309275, upload-time = "2026-05-06T13:37:41.406Z" },

{ url = "https://files.pythonhosted.org/packages/07/f8/41db9de19d7987d6b04715a02b3b40aea467000275d9d758ffaa31af7d50/pydantic\_core-2.46.4-cp313-cp313-manylinux\_2\_17\_x86\_64.manylinux2014\_x86\_64.whl", hash = "sha256:9551187363ffcc0de2a00b2e47c25aaeb1020b69b668762966df15fc5659dd5a", size = 2094467, upload-time = "2026-05-06T13:39:18.847Z" },

{ url = "https://files.pythonhosted.org/packages/2c/e2/f35033184cb11d0052daf4416e8e10a502ea2ac006fc4f459aee872727d1/pydantic\_core-2.46.4-cp313-cp313-manylinux\_2\_31\_riscv64.whl", hash = "sha256:0186750b482eefa11d7f435892b09c5c606193ef3375bcf94aa00ae6bf66262", size = 2134417, upload-time = "2026-05-06T13:40:17.944Z" },

{ url = "https://files.pythonhosted.org/packages/7e/7b/6ceeb1cc90e193862f444ebe373d8fd6f13f0a82572dde03fb10734c6c71/pydantic\_core-2.46.4-cp313-cp313-manylinux\_2\_5\_i686.manylinux1\_i686.whl", hash = "sha256:5855698a4856556d86e8e6cd8434bc3ac0314ee8e12089ae0e143f64c6256e4e", size = 2179782, upload-time = "2026-05-06T13:40:32.618Z" },

{ url = "https://files.pythonhosted.org/packages/5a/f2/c8d7773ede6af08036423a00ae0ceffce266c3c52a096c435d68c896083f/pydantic\_core-2.46.4-cp313-cp313-musllinux\_1\_1\_aarch64.whl", hash = "sha256:cbaf13819775b7f769bf4a1f066cb6df7a28d4480081a589828ef190226881cd", size = 2188782, upload-time = "2026-05-06T13:36:51.018Z" },

{ url = "https://files.pythonhosted.org/packages/59/31/0c864784e31f09f05cdd87606f08923b9c9e7f6e51dd27f20f62f975ce9f/pydantic\_core-2.46.4-cp313-cp313-musllinux\_1\_1\_armv7l.whl", hash = "sha256:633147d34cf4550417f12e2b1a0383973bdf5cdfde212cb09e9a581cf10820be", size = 2328334, upload-time = "2026-05-06T13:40:37.764Z" },

{ url = "https://files.pythonhosted.org/packages/c2/eb/4f6c8a41efa30baa755590f4141abf3a8c370fab610915733e74134a7270/pydantic\_core-2.46.4-cp313-cp313-musllinux\_1\_1\_x86\_64.whl", hash = "sha256:82cf5301172168103724d49a1444d3378cb20cdee30b116a1bde6031236298a5d", size = 2372986, upload-time = "2026-05-06T13:39:34.152Z" },

{ url = "https://files.pythonhosted.org/packages/5b/24/b375a480d53113860c299764bfe9f349a3dc9108b3adc0d7f0d786492ebf/pydantic\_core-2.46.4-cp313-cp313-win32.whl", hash = "sha256:9fa8ae11da9e2b3126c6426f147e0fba88d96d65921799bb30c6abd1cb2c97fb", size = 1973693, upload-time = "2026-05-06T13:37:55.072Z" },

{ url = "https://files.pythonhosted.org/packages/7e/e8/cff247591966f2d22ec8c003cd7587e27b7ba7b81ab2fb888e3ab75dc285/pydantic\_core-2.46.4-cp313-cp313-win\_amd64.whl", hash = "sha256:6b3ace8194b0e5204818c92802dcdca7fc6d88aabb799d7c795540d9cd6d292", size = 2071819, upload-time = "2026-05-06T13:38:49.139Z" },

{ url = "https://files.pythonhosted.org/packages/c6/1a/f4aee670d5670e9e148e0c82c7db98d780be566c6e6a97ee8035528ca0b3/pydantic\_core-2.46.4-cp313-cp313-win\_arm64.whl", hash = "sha256:184c081504d17f1c1066e430e117142b2c77d9448a97f7b65c6ac9fd9aee238d", size = 2027411, upload-time = "2026-05-06T13:40:45.796Z" },

{ url = "https://files.pythonhosted.org/packages/8d/74/228a26ddad29c6672b805d9df78e8d251cd04004fa7eed0e622096cd0250/pydantic\_core-2.46.4-cp314-cp314-macosx\_10\_12\_x86\_64.whl", hash = "sha256:428e04521a40150c85216fc8b85e8d39feced235a9cf5e383761238c7fa9b96fb", size = 2102079, upload-time = "2026-05-06T13:38:41.019Z" },

{ url = "https://files.pythonhosted.org/packages/ad/1f/8970b150a4b4365623ae00fc88603491f763c627311ae8031e3111356d6e/pydantic\_core-2.46.4-cp314-cp314-macosx\_11\_0\_arm64.whl", hash = "sha256:23ace664830ee0bfe014a0c7bc248b1f7f25ed7ad103852c317624a1083af462", size = 1952179, upload-time = "2026-05-06T13:36:59.812Z" },

{ url = "https://files.pythonhosted.org/packages/95/30/5211a831ae054928054b2f79731661087a2bc5c01e825c672b3a4a8f1b3e/pydantic\_core-2.46.4-cp314-cp314-manylinux\_2\_17\_aarch64.manylinux2014\_aarch64.whl", hash = "sha256:ce5c1d2a8b27468f433ca974829c44060b8097eedc39933e3c206a90ee49c4a9", size = 1978926, upload-time = "2026-05-06T13:37:39.933Z" },

{ url = "https://files.pythonhosted.org/packages/57/e9/689668733b1eb67adeef047db3c2e8788fc65a7fd9c9e2b46b7744fe245/pydantic\_core-2.46.4-cp314-cp314-manylinux\_2\_17\_armv7l.manylinux2014\_armv7l.whl", hash = "sha256:7283d57845ecf5a163403eb0702dfc220cc4fbdd18919cb5ccea4f95ee1cda4b", size = 2046785, upload-time = "2026-05-06T13:38:01.995Z" },

{ url = "https://files.pythonhosted.org/packages/60/d9/6715260422ff50a2109878fd24d948a6c3446bb2664f34ee78cd972b3acd/pydantic\_core-2.46.4-cp314-cp314-manylinux\_2\_17\_ppc64le.manylinux2014\_ppc64le.whl", hash = "sha256:8daafc69c93ee8a0204506a3b6b30f586ef54028f52aeeeb5c4cfc5184df5914", size = 2228733, upload-time = "2026-05-06T13:40:37.371Z" },

{ url = "https://files.pythonhosted.org/packages/18/ae/fdb2f64316afca925640f8e70bb1a564b0ec2721c1389e25b8eb4bf9a299/pydantic\_core-2.46.4-cp314-cp314-manylinux\_2\_17\_s390x.manylinux2014\_s390x.whl", hash = "sha256:cd2213145bcc2ba85884d0a63d222fece9209678f77b9b4d76f054c561adb28", size = 2307534, upload-time = "2026-05-06T13:37:21.531Z" },

{ url = "https://files.pythonhosted.org/packages/89/1d/8eff589b45bb8190a9d12c49cfad0f176a5cbd1534908a6b5125e2886239/pydantic\_core-2.46.4-cp314-cp314-manylinux\_2\_17\_x86\_64.manylinux2014\_x86\_64.whl", hash = "sha256:1a7dd0b3ee80d90150e3495a3a13a34dbcbfd4f012996a6a1d8900e91b5c0fb", size = 2179141, upload-time = "2026-05-06T13:37:14.046Z" },

{ url = "https://files.pythonhosted.org/packages/06/d5/ee5a3366637fee41dee51a1fc91562dcf12ddbc68fda34e6b253da2324bb/pydantic\_core-2.46.4-cp314-cp314-manylinux\_2\_31\_riscv64.whl", hash = "sha256:c1b3f518abeca3aa13c712fd202306e145abf59a18b094a6bafb2d2bbf59192c", size = 2129627, upload-time = "2026-05-06T13:37:25.033Z" },

{ url = "https://files.pythonhosted.org/packages/94/33/2414be571d2c6a6c4d08be21f9292b6d3fdb08949a97b6dfe985017821db/pydantic\_core-2.46.4-cp314-cp314-manylinux\_2\_5\_i686.manylinux1\_i686.whl", hash = "sha256:1a7dd0b3ee80d90150e3495a3a13a34dbcbfd4f012996a6a1d8900e91b5c0fb", size = 2179141, upload-time = "2026-05-06T13:37:14.046Z" },

{ url = "https://files.pythonhosted.org/packages/7b/79/7daa95be995be0eecc4cf75064cb33f9bbbf3fe0158caf2f0d4a996a5c7/pydantic\_core-2.46.4-cp314-cp314-musllinux\_1\_1\_aarch64.whl", hash = "sha256:3fb702cd90b0446a3a1c5e470bfa0dd23c0233b676a9099ddcc964fa6ca13898", size = 2184325, upload-time = "2026-05-06T13:36:53.615Z" },

{ url = "https://files.pythonhosted.org/packages/9f/cb/d0a382f5c0de8a222dc61c65348e0ce831b1f68e0a018450d31c2cace3a5/pydantic\_core-2.46.4-cp314-cp314-musllinux\_1\_1\_armv7l.whl", hash = "sha256:b8458003118a712e66286df6a707db01c52c0f52f7db8e4a38f0da1d3b94fc4e", size = 2323990, upload-time = "2026-05-06T13:40:29.971Z" },

{ url = "https://files.pythonhosted.org/packages/05/db/d9ba624cc4a5aced1598e88c04fddb8310c8a69b9d38b9a3d39ce3a61ed7/pydantic\_core-2.46.4-cp314-cp314-musllinux\_1\_1\_x86\_64.whl", hash = "sha256:372429a130e469c9cd698925ce5fc50940b7a1336b0d82038e63d5bb4edc519", size = 2369978, upload-time = "2026-05-06T13:37:23.027Z" },

{ url = "https://files.pythonhosted.org/packages/f2/20/d15df15ba918c423461905802bfd2981c3af0bfa0e40d05e13edbf4a8bc3/pydantic\_core-2.46.4-cp314-cp314-win32.whl", hash = "sha256:bfecc22eab3c8cc2ceec0248aec886624116dc079afa027ecc8ad4a7e62010f8a", size = 1966354, upload-time = "2026-05-06T13:38:03.499Z" },

{ url = "https://files.pythonhosted.org/packages/fc/b6/6b8de4c0a7d7ab3004c439c80c5c1e0a3e8d78bbae19379b01960383d9e5/pydantic\_core-2.46.4-cp314-cp314-win\_amd64.whl", hash = "sha256:811ff8e9c313ab425368bcbb36e5c4ebd7108c2bbf4e4089cfbb0b01eff63fac", size = 2072238, upload-time = "2026-05-06T13:39:40.807Z" },

{ url = "https://files.pythonhosted.org/packages/32/36/51eb763beec1f4cf59b1db243a7dcc39cbb41230f050a09b9d69faaf0a48/pydantic\_core-2.46.4-cp314-cp314-win\_arm64.whl", hash = "sha256:bfecc22eab3c8cc2ceec0248aec886624116dc079afa027ecc8ad4a7e62010f8a", size = 2018251, upload-time = "2026-05-06T13:37:26.722Z" },

{ url = "https://files.pythonhosted.org/packages/e8/91/855af51d625b23aa987116a19e231d2aaef9c4a415273ddc189b79a45fee

```

/pydantic_core-2.46.4-cp314-cp314t-macosx_10_12_x86_64.whl", hash = "sha256:af8244b2bef6aaad6d92cda81372de7f8c8d36c9f0c3ea36e827c60e7d9467a0", size = 2099593, upload-time = "2026-05-06T13:39:47.682Z" },
{ url = "https://files.pythonhosted.org/packages/fb/1b/8784a54c65edb5f49f0a14d6977cf1b209bba85a4c77445b255c2de58ab3/pydantic_core-2.46.4-cp314-cp314t-macosx_11_0_arm64.whl", hash = "sha256:5a4330cdcbc57162e4b3aa303f588ba752257694c9c9be3e7ebb11b4aca659b5d", size = 1935226, upload-time = "2026-05-06T13:40:40.428Z" },
{ url = "https://files.pythonhosted.org/packages/e8/e7/1955d28d1afc56dd4b3ad7cc0cf39df1b9852964cf16e5d13912756d6db/pydantic_core-2.46.4-cp314-cp314t-manylinux_2_17_aarch64.manylinux2014_aarch64.whl", hash = "sha256:29c61fc04a3d840155ff08e475a04809278972fe6aef51e2720554e96367e34b", size = 1974605, upload-time = "2026-05-06T13:37:32.029Z" },
{ url = "https://files.pythonhosted.org/packages/93/e2/3fedbf0ba7a22850e6e9fd78117f1c0f10f950182344d8a6c535d468fdd8/pydantic_core-2.46.4-cp314-cp314t-manylinux_2_17_armv7l.manylinux2014_armv7l.whl", hash = "sha256:c50f2528cf200c5eed56faf3f4e22fcd5f38c157a8b78576e6ba3168ec35f000", size = 2030777, upload-time = "2026-05-06T13:38:55.239Z" },
{ url = "https://files.pythonhosted.org/packages/f8/61/46be275fcaaba0b4f5b9669dd852267ce1ff616592dccf7a7845588df091/pydantic_core-2.46.4-cp314-cp314t-manylinux_2_17_ppc64le.manylinux2014_ppc64le.whl", hash = "sha256:0cbe8b01f948de4286c74cdd6c667aceb38f5c1e26f0693b3983d9d74887c65e", size = 2236641, upload-time = "2026-05-06T13:37:08.096Z" },
{ url = "https://files.pythonhosted.org/packages/60/db/12e93e46a8bac9988be3c016860f83293daea8c716c029c9ace279036f2f/pydantic_core-2.46.4-cp314-cp314t-manylinux_2_17_s390x.manylinux2014_s390x.whl", hash = "sha256:617d7e2ca7dcb8c5cf6bcb8c59b8832c94b36196bbf1cbd1bfb56ed341905edd", size = 2286404, upload-time = "2026-05-06T13:40:20.221Z" },
{ url = "https://files.pythonhosted.org/packages/e2/4a/4d8b19008f38d31c53b8219cfedc2e3d5de5fe99d90076b7e767de29274f/pydantic_core-2.46.4-cp314-cp314t-manylinux_2_17_x86_64.manylinux2014_x86_64.whl", hash = "sha256:7027560ee92211647d0d34e3f7cd6f50da56399d26a9c8ad0da286d3869a53f3", size = 2109219, upload-time = "2026-05-06T13:38:12.153Z" },
{ url = "https://files.pythonhosted.org/packages/88/70/3cbc40978fefb7bb09c6708d40d4ad1a5d70fd7213c3d17f971de868ec1f/pydantic_core-2.46.4-cp314-cp314t-manylinux_2_31_riscv64.whl", hash = "sha256:f99626688942fb746e545232e7726926f3be91b5975f8b55327665fafda991c7", size = 2110594, upload-time = "2026-05-06T13:40:02.971Z" },
{ url = "https://files.pythonhosted.org/packages/9d/20/b8d36736216e29491125531685b2f9e61aa5b4b2599893f8268551da3338/pydantic_core-2.46.4-cp314-cp314t-manylinux_2_5_i686.manylinux1_i686.whl", hash = "sha256:fc3e9034a63de20e15e8ade85358bc6efc614008cab72898b4b4952bea0509ff", size = 2159542, upload-time = "2026-05-06T13:39:27.506Z" },
{ url = "https://files.pythonhosted.org/packages/1d/a2/367df868eb584dac6fbf82a389272406d7178e301c4ac82545ab98bc2dd9/pydantic_core-2.46.4-cp314-cp314t-musllinux_1_1_aarch64.whl", hash = "sha256:97e7cf2be5c77b7d1a9713a05605d49460d02c6078d38dbef3cbe323c548424", size = 2168146, upload-time = "2026-05-06T13:38:31.93Z" },
{ url = "https://files.pythonhosted.org/packages/c1/b8/4460f77f7e201893f649a29ab355ddddd3beee8a97bcb1a320db414f9a06e/pydantic_core-2.46.4-cp314-cp314t-musllinux_1_1_armv7l.whl", hash = "sha256:3bf92c5d0e00fefaab325a4d27828fe6b6e2a21848686b5b60d2d9eeb09d76c6", size = 2306309, upload-time = "2026-05-06T13:37:44.717Z" },
{ url = "https://files.pythonhosted.org/packages/64/c4/be2639293acd87dc8dbbceca41a73cee9b2ebf996fe6d892a1a74e88ad3f7/pydantic_core-2.46.4-cp314-cp314t-musllinux_1_1_x86_64.whl", hash = "sha256:3ecbc122d18468d06ca279dc26a8c2e2d5acb10943bb35e36ae92096dc3b5565", size = 2369736, upload-time = "2026-05-06T13:37:05.645Z" },
{ url = "https://files.pythonhosted.org/packages/30/a6/9f9f380dbb301f67023bf8f707aaa75daadf84f7152d95c410fd7e81d994/pydantic_core-2.46.4-cp314-cp314t-win32.whl", hash = "sha256:e846ae7835bf0703ae43f534ab79a867146dadd59dc9ca5c8b53d5c8f7c9ef02", size = 1955575, upload-time = "2026-05-06T13:38:51.116Z" },
{ url = "https://files.pythonhosted.org/packages/40/1f/f1eb9eb350e795d1af8586289746f5c5677d16043040d63710e22abc43c9/pydantic_core-2.46.4-cp314-cp314t-win_amd64.whl", hash = "sha256:2108ba5c1ceca18030634489dc54484414ee36357f2f9f780b93e7ddb44b5", size = 2051624, upload-time = "2026-05-06T13:38:21.672Z" },
{ url = "https://files.pythonhosted.org/packages/f6/d2/42dd53d0a85c27606f316d3aa5d2869c4e8470a5ed6dec30e4a1abe19192/pydantic_core-2.46.4-cp314-cp314t-win_arm64.whl", hash = "sha256:4fcbe087dbc2068af7eda3aa87634eba216dbda64d1ae73c8684b621d33f6596", size = 2017325, upload-time = "2026-05-06T13:40:52.723Z" },
{ url = "https://files.pythonhosted.org/packages/9d/1d/8987ad40f65ae1432753072f214fb5c74fe47ffbd0698b9b9cbbb585664f8/pydantic_core-2.46.4-graalpy312-graalpy250_312_native-macosx_10_12_x86_64.whl", hash = "sha256:1d8ba486450b14f3b1d63bc521d410ec7565e52f887b9fb671791886436a42f7", size = 2095527, upload-time = "2026-05-06T13:39:52.283Z" },
{ url = "https://files.pythonhosted.org/packages/64/d3/84c282a7eee1d3ac4c0377546ef5a1ea436ce26840d9ac3b7ed54a377507/pydantic_core-2.46.4-graalpy312-graalpy250_312_native-macosx_11_0_arm64.whl", hash = "sha256:3009f12e4e90b7f88b4f9adb1b0c4a3d58fe7820f3238c190047209d148026df", size = 1936024, upload-time = "2026-05-06T13:40:15.671Z" },
{ url = "https://files.pythonhosted.org/packages/d7/ca/eac61596cdeb4d7e174d3dc0bd8a6238f14f75f97a24e7b7db4c7e7340a0/pydantic_core-2.46.4-graalpy312-graalpy250_312_native-manylinux_2_17_aarch64.manylinux2014_aarch64.whl", hash = "sha256:6:ad785e92e6dc634c21555edc8db6b64957ab844541bcb96a1366c202951ae526", size = 1990696, upload-time = "2026-05-06T13:38:34.717Z" },
{ url = "https://files.pythonhosted.org/packages/fa/c3/7c8b240552251faf6b3a957db200fcfbcbec36763c050428b601e0c9b83b/pydantic_core-2.46.4-graalpy312-graalpy250_312_native-manylinux_2_17_x86_64.manylinux2014_x86_64.whl", hash = "sha256:00c603d540afdd6b80eb39f078f33ebd46211f02f33e34a32d9f053bba711de0", size = 2147590, upload-time = "2026-05-06T13:39:29.883Z" },
]

```

```

[[package]]
name = "pydantic-settings"
version = "2.14.1"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "pydantic" },
 { name = "python-dotenv" },
 { name = "typing-inspection" },
]
sdist = { url = "https://files.pythonhosted.org/packages/07/60/1d1e59c9c90d54591469ada7d268251f71c24bdb765f1a8a832cee8c6653/pydantic_settings-2.14.1.tar.gz", hash = "sha256:e874d3bec7e787b0c9958277956ed9b4dd5de6a80e162188fdaff7c5e26fd5fa", size = 235551, upload-time = "2026-05-08T13:40:06.542Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/ae/8d/f1af3832f5e6eb13ba94ee809e72b8ecb5eef226d27ee0bef7d963d943c7/pydantic_settings-2.14.1-py3-none-any.whl", hash = "sha256:6e3c7edfd8277687cdc598f56e5cfff0e9bfff0910a3749deaa8d4401c3a2b9de", size = 60964, upload-time = "2026-05-08T13:40:04.958Z" },
]

```

```

]

[[package]]
name = "pydeck"
version = "0.9.2"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "jinja2" },
 { name = "numpy" },
]
sdist = { url = "https://files.pythonhosted.org/packages/eb/df/4e9e7f20f8034a37c6571c93809f6d22388c39978c98d174d656c1a18fd2/pydeck-0.9.2.tar.gz", hash = "sha256:c10d9035e81ead6385264cac8d19402471f6866a15ca1f7df1400f52142bcf87", size = 5849672, upload-time = "2026-04-16T18:30:30.089Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/88/24/b30ee7d723100fd822de1bb4c0adea62f3419884a75a536f35f355d1e7c0/pydeck-0.9.2-py3-none-any.whl", hash = "sha256:8213dfeacc5f6bfe6825f61c8ee34e3850e8a31fc43924379ec98edb34a75b25", size = 11305615, upload-time = "2026-04-16T18:30:28.133Z" },
]

[[package]]
name = "pygments"
version = "2.20.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/c3/b2/bc9c9196916376152d65552fdcebac55e66de6603a76a02bca1b6414f6c/pygments-2.20.0.tar.gz", hash = "sha256:6757cd03768053ff99f3039c1a36d6c0aa0b263438fcab17520b30a303a82b5f", size = 4955991, upload-time = "2026-03-29T13:29:33.898Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/f4/7e/a72dd26f3b0f4f2bf1dd8923c85f7ceb43172af56d63c7383eb62b332364/pygments-2.20.0-py3-none-any.whl", hash = "sha256:81a9e26dd42fd28a23a2d169d86d7ac03b46e2f8b59ed4698fb4785f946d0176", size = 1231151, upload-time = "2026-03-29T13:29:30.038Z" },
]

[[package]]
name = "pypdfium2"
version = "5.10.1"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/1d/78/d9b45abb97a3686643f7c6472a5f7688f2013a373226121dc76b9debacfb/pypdfium2-5.10.1.tar.gz", hash = "sha256:f257d2011eb43c846b7e9f5a802e28646b29732763e4a35dd6ca76f9be580538", size = 272963, upload-time = "2026-06-15T10:09:16.179Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/98/49/0b85fcc0d236582143a25cf275b0b4f5d786f51eb07a89ec9c79d43efe18/pypdfium2-5.10.1-py3-none-android_23_arm64_v8a.whl", hash = "sha256:13abf7a9f5e0ddecb8bbcccea5f13ae5abe8a298ea219e125b0fc24c1d2171b4", size = 3409176, upload-time = "2026-06-15T10:08:36.017Z" },
 { url = "https://files.pythonhosted.org/packages/20/d2/2f522c5b2ad5166edf256bb4dbab97de5d07b2573f8a5630dddfcd1f8d4ee/pypdfium2-5.10.1-py3-none-android_23_armeabi_v7a.whl", hash = "sha256:a0dc52b56631e2f7edcdb22bae3b155aa840bec32c5bd05781e90baaeceee88e7", size = 2866175, upload-time = "2026-06-15T10:08:37.955Z" },
 { url = "https://files.pythonhosted.org/packages/a7/be/477548c026c2badfdbf4afc3358b7135121fb5bec2e2effcb67e3a674d0b/pypdfium2-5.10.1-py3-none-macosx_12_0_arm64.whl", hash = "sha256:ebb9e63f92d15fc41b359fe7a187233dfae37548800e1fa09cb2fc466ac89951", size = 3621427, upload-time = "2026-06-15T10:08:39.969Z" },
 { url = "https://files.pythonhosted.org/packages/8c/9b/0131c7f711b62c6edd6b200e9eb6340be6de4f6dc5baae625e3394d8d5fb/pypdfium2-5.10.1-py3-none-macosx_12_0_x86_64.whl", hash = "sha256:d04f2050b6b32bb18624688b600543342a4ab3aacf64bf66521a5af72bbc7de1", size = 3682825, upload-time = "2026-06-15T10:08:42.181Z" },
 { url = "https://files.pythonhosted.org/packages/9d/3d/bddfceb6e67e54d6dd1ab6c0f1feff796a89596e40f6345a3b4cc6a3d408/pypdfium2-5.10.1-py3-none-manylinux_2_17_aarch64.manylinux2014_aarch64.whl", hash = "sha256:0de53d2710ca9509fc2812340acc57c3f043697609068592d87de654f8cabf44", size = 3682206, upload-time = "2026-06-15T10:08:44.087Z" },
 { url = "https://files.pythonhosted.org/packages/58/08/dedeb25c6645fc8a5eda24f54e0b1d083b7334ababf5f518bb939d729cc0/pypdfium2-5.10.1-py3-none-manylinux_2_17_armv7l.manylinux2014_armv7l.whl", hash = "sha256:10a26ce04795f8ec079e81c707fcb5737061e8a78025bab3d6e36642e9c903a", size = 3413720, upload-time = "2026-06-15T10:08:45.739Z" },
 { url = "https://files.pythonhosted.org/packages/cc/48/69e1fc8b1216005243c6415183bbf6de1cda3f5a06758b3fa4a26a7385c6/pypdfium2-5.10.1-py3-none-manylinux_2_17_i686.manylinux2014_i686.whl", hash = "sha256:be6d2a8d1bcfd777188e7aa55a25c83f34d54e8350ad8810fb32017787d9b0d9", size = 3812913, upload-time = "2026-06-15T10:08:47.452Z" },
 { url = "https://files.pythonhosted.org/packages/72/7f/132455a58ad736d76815c6cd1307532c3f433299d945b9d2f8cc2387c309/pypdfium2-5.10.1-py3-none-manylinux_2_17_ppc64le.manylinux2014_ppc64le.whl", hash = "sha256:cf4d2527f79f31c550490cc74c9f32e19385a944630a3ef4cd4d9b6f961fbf77", size = 4223220, upload-time = "2026-06-15T10:08:49.099Z" },
 { url = "https://files.pythonhosted.org/packages/bf/8c/4d5804eca598bbe894e0a9a510807e221c1623e7276ce6b68fa2660dc933/pypdfium2-5.10.1-py3-none-manylinux_2_17_x86_64.manylinux2014_x86_64.whl", hash = "sha256:3ba127750bc3f4161461538d532d74491cd976f584f1753a6cee9cb821338ec1", size = 3738950, upload-time = "2026-06-15T10:08:50.821Z" },
 { url = "https://files.pythonhosted.org/packages/d1/7f/baac59bf14ff914d97789ee0368c22ae233aa857aa9c0726bcb515dbc4d7/pypdfium2-5.10.1-py3-none-manylinux_2_27_s390x.manylinux_2_28_s390x.whl", hash = "sha256:80f30517ee089dfbbcb6e9de6da365b6e8c0ce8f80c40b7d4025a3b1d3bbd8a70", size = 4029869, upload-time = "2026-06-15T10:08:52.494Z" },
 { url = "https://files.pythonhosted.org/packages/d0/d7/a5d58a0bcb3a1a0e37ed636a76ef3d2d215733f28af61637287d061b0c54/pypdfium2-5.10.1-py3-none-manylinux_2_34_riscv64.manylinux_2_39_riscv64.whl", hash = "sha256:ad5f5de15febb788c6eb3853e58aceda9cd8c5187c92472abaecf9558deb0cf", size = 3990927, upload-time = "2026-06-15T10:08:54.555Z" },
 { url = "https://files.pythonhosted.org/packages/da/1a/98eebd14b36812176297cf765d504ebeebe982f895c8a3a9fbd217797de/pypdfium2-5.10.1-py3-none-musllinux_1_2_aarch64.whl", hash = "sha256:8947fa3cd808da33960bdf8ff9e5247aa94ccd94f0b09bb3402e99498d83bcc9", size = 4989624, upload-time = "2026-06-15T10:08:56.284Z" },
]

```

```

 { url = "https://files.pythonhosted.org/packages/1c/20/f2e124d607b8bb90a9f1ce976afff38c70e215cd7ea86af784cb2e8a19dd
 /pypdfium2-5.10.1-py3-none-musllinux_1_2_armv7l.whl", hash = "sha256:139a6387a3a2652f288e53164268bb03af4fa221d78484ee18
 407053a60082a3", size = 4535124, upload-time = "2026-06-15T10:08:58.214Z" },
 { url = "https://files.pythonhosted.org/packages/59/ef/469ea87f668a32ff3280ea15e522e3a7858d2c80f1eccc320ece1244624c9
 /pypdfium2-5.10.1-py3-none-musllinux_1_2_i686.whl", hash = "sha256:172ff3e10358d66456e27fb0b8b5098e28ec24e51072eb4b5b86
 077d50e21bb", size = 5229373, upload-time = "2026-06-15T10:09:00.702Z" },
 { url = "https://files.pythonhosted.org/packages/c3/48/c7ed3001f0c5e28114c98bf918c8121e422a65ba7323e1e12f3f28e2d278
 /pypdfium2-5.10.1-py3-none-musllinux_1_2_ppc64le.whl", hash = "sha256:09fda0609dc4749c9865a0315c447d6f2583a580693bcabd6
 9980d3fbb22ad51", size = 5140010, upload-time = "2026-06-15T10:09:02.734Z" },
 { url = "https://files.pythonhosted.org/packages/b2/bc/00b731bfc1fdc0f3c7d91108fceb54978ff4f5a92336820e5ed6c12535ff
 /pypdfium2-5.10.1-py3-none-musllinux_1_2_riscv64.whl", hash = "sha256:6b01adcf9aaf7a635a59bed5687fd4fd7b0da292664f050d
 4ebd2bfa5c70584", size = 4643310, upload-time = "2026-06-15T10:09:04.794Z" },
 { url = "https://files.pythonhosted.org/packages/9a/e8/3ad242233f657c19092a8c83684c8154b8d02a826535a6a2591d91aa5dde
 /pypdfium2-5.10.1-py3-none-musllinux_1_2_s390x.whl", hash = "sha256:610e14c37d2090b826dccc0604fc7e7612c0ce591190780ae22
 8abdb9abb971e", size = 5087879, upload-time = "2026-06-15T10:09:06.861Z" },
 { url = "https://files.pythonhosted.org/packages/80/3f/9d0747a02ac3021ed3db7ac27c5187d97e78b0253a4bdfbf386666968474
 /pypdfium2-5.10.1-py3-none-musllinux_1_2_x86_64.whl", hash = "sha256:f2803020952afa57e1e148adc19369b835154e1fa251a1ca85
 008ab6466a710f", size = 5047369, upload-time = "2026-06-15T10:09:08.883Z" },
 { url = "https://files.pythonhosted.org/packages/9e/41/7d5187e9527eae81890a3b13193442112ef788d61ddaa68a6d59ac447bec
 /pypdfium2-5.10.1-py3-none-win32.whl", hash = "sha256:8702bb4f01ddfc8e7757b41b4c2c8392ac17c9f0234476e1e69672ea7c6d6aa0"
 , size = 3680056, upload-time = "2026-06-15T10:09:10.95Z" },
 { url = "https://files.pythonhosted.org/packages/16/1d/c62bd59dd8345cc4b640f942f465633f6b07b859d01ddb648610a7bf5c7c
 /pypdfium2-5.10.1-py3-none-win_amd64.whl", hash = "sha256:58da5b51fb7884c7d21a05062ab13edb011d1a08dfd9694f3d5d685df6279
 6b9", size = 3812105, upload-time = "2026-06-15T10:09:12.684Z" },
 { url = "https://files.pythonhosted.org/packages/10/d5/21bac39125df8a93e99c04583486b58a62b5997d6b3541e3ad0f69053392
 /pypdfium2-5.10.1-py3-none-win_arm64.whl", hash = "sha256:e3301c2f7a66fb8cb57dba857d0c9e90215e178f6602a87c5a306cd98513d
 ab8", size = 3600043, upload-time = "2026-06-15T10:09:14.606Z" },
]

[[package]]
name = "pytest"
version = "9.1.0"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "colorama", marker = "sys_platform == 'win32'" },
 { name = "iniconfig" },
 { name = "packaging" },
 { name = "pluggy" },
 { name = "pygments" },
]
sdist = { url = "https://files.pythonhosted.org/packages/84/0e/b5858858d74958632c49b72cb25a3976ff9f632397626715be71c89d
3971/pytest-9.1.0.tar.gz", hash = "sha256:41dd9148c08072446394cefd3d79701701335a9f4cae69ba92e39f6c7f5c061c", size = 163
4181, upload-time = "2026-06-13T18:52:45.983Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/8b/5a/ba30a81239b909821b3153e303e7def45178bf353da4f72380e6c5e8793b
 /pytest-9.1.0-py3-none-any.whl", hash = "sha256:8ebb0e7888bdf2bdfc602ec51f8f62d50200af37356c74e503c79a94f5c81f32", size
 = 386453, upload-time = "2026-06-13T18:52:44.045Z" },
]

[[package]]
name = "python-dateutil"
version = "2.9.0.post0"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "six" },
]
sdist = { url = "https://files.pythonhosted.org/packages/66/c0/0c8b6ad9f17a802ee498c46e004a0eb49bc148f2fd230864601a86dc
f6db/python-dateutil-2.9.0.post0.tar.gz", hash = "sha256:37dd54208da7e1cd875388217d5e00ebd4179249f90fb72437e91a35459a0a
d3", size = 342432, upload-time = "2024-03-01T18:36:20.211Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/ec/57/56b9bcc3c9c6a792fcbaf139543cee77261f3651ca9da0c93f5c1221264b
 /python_dateutil-2.9.0.post0-py2.py3-none-any.whl", hash = "sha256:a8b2bc7bffa282281c8140a97d3aa9c14da0b136dfe83f850ee
 a9a5f7470427", size = 229892, upload-time = "2024-03-01T18:36:18.57Z" },
]

[[package]]
name = "python-dotenv"
version = "1.2.2"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/82/ed/0301aeec3e5353ef3d94b6ec08bbcabd04a72018415dcb29e588514
bba8/python_dotenv-1.2.2.tar.gz", hash = "sha256:2c371a91fbd7ba082c2c1dc1f8bf89ca22564a087c2c287cd9b662adde799cf3", siz
e = 50135, upload-time = "2026-03-01T16:00:26.196Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/0b/d7/1959b9648791274998a9c3526f6d0ec8fd2233e4d4acce81bbae76b44b2a
 /python_dotenv-1.2.2-py3-none-any.whl", hash = "sha256:1d8214789a24de455a8b8bd8ae6fe3c6b69a5e3d64aa8a8e5d68e694bbcb285a
 ", size = 22101, upload-time = "2026-03-01T16:00:25.09Z" },
]

```



```

]

[[package]]
name = "python-multipart"
version = "0.0.32"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/5b/42/55c32bb9b12693c092ad250a0e82edb5b31ddeda6eb772de5f308b3804ad/python_multipart-0.0.32.tar.gz", hash = "sha256:be54b7f3fa167bb83e4fcd936b887b708f4e57fe75911c02aebf53efaf8d938e", size = 46881, upload-time = "2026-06-04T16:18:58.647Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/e1/04/e8135ebd1ad02c56ec633277529b2602ff99ff634be76cdba5744cf554fd/python_multipart-0.0.32-py3-none-any.whl", hash = "sha256:ff6d3f776f16878c894e52e107296ffc890e913c611b1a4ec6c44e2821fe2e23", size = 30042, upload-time = "2026-06-04T16:18:57.319Z" },
]

[[package]]
name = "referencing"
version = "0.37.0"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "attrs" },
 { name = "rpds-py" },
 { name = "typing-extensions", marker = "python_full_version < '3.13'" },
]
sdist = { url = "https://files.pythonhosted.org/packages/22/f5/df4e9027acead3ecc63e50fe1e36aca1523e1719559c499951bb4b53188f/referencing-0.37.0.tar.gz", hash = "sha256:44aefc3142c5b842538163acb373e24cce6632bd54bdb01b21ad5863489f50d8", size = 78036, upload-time = "2025-10-13T15:30:48.871Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/2c/58/ca301544e1fa93ed4f80d724bf5b194f6e4b945841c5bfd555878eea9fcb/referencing-0.37.0-py3-none-any.whl", hash = "sha256:381329a9f99628c9069361716891d34ad94af76e461dcb0335825aecc7692231", size = 26766, upload-time = "2025-10-13T15:30:47.625Z" },
]

[[package]]
name = "requests"
version = "2.34.2"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "certifi" },
 { name = "charset-normalizer" },
 { name = "idna" },
 { name = "urllib3" },
]
sdist = { url = "https://files.pythonhosted.org/packages/ac/c3/e2a2b89f2d3e2179abd6d00ebd70bfff6273f37fb3e0cc209f48b39d00cbf/requests-2.34.2.tar.gz", hash = "sha256:f288924cae4e29463698d6d60bc6a4da69c89185ad1e0bcc4104f584e960b9ed", size = 142856, upload-time = "2026-05-14T19:25:27.735Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/a0/f4/c67b0b3f1b9245e8d266f0f112c500d50e5b4e83cb6f3b71b6528104182a/requests-2.34.2-py3-none-any.whl", hash = "sha256:2a0d60c172f83ac6ab31e4554906c0f3b3588d37b5cb939b1c061f4907e278e0", size = 73075, upload-time = "2026-05-14T19:25:26.443Z" },
]

[[package]]
name = "rpds-py"
version = "2026.5.1"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/2e/43/25a8dcd3feedd735039a8f0b5b7e3b118232b5eae288c4fd9ab200d41094/rpds_py-2026.5.1.tar.gz", hash = "sha256:07b24fea40541e28570e5b795a4a38fbdc12550c06bd0748005ecc8116ca256", size = 64459, upload-time = "2026-05-28T12:02:13.232Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/d4/e7/a78582dc57caa592dcc7d4fb69b61390561e908eb3d2f5df5928a8e354c0/rpds_py-2026.5.1-cp312-cp312-macosx_10_12_x86_64.whl", hash = "sha256:3abe24a66e57adcfa645d718063a5fa5103ecc71ddb26d78af8f9368018ff1d", size = 353040, upload-time = "2026-05-28T11:59:12.531Z" },
 { url = "https://files.pythonhosted.org/packages/a3/43/35e3f136343aef451e545ce8c38d36c2f93c0ed88703db8b64ba2b205c68/rpds_py-2026.5.1-cp312-cp312-macosx_11_0_arm64.whl", hash = "sha256:58b1d94308ddf0b1982f61f2eb54bf92997c9ece8a8093ef014250f4a517906c", size = 345775, upload-time = "2026-05-28T11:59:13.827Z" },
 { url = "https://files.pythonhosted.org/packages/20/e1/0f2160c5982d3157734d5cb3ed63d8b2d583a73c9864f77b666449f32cf8/rpds_py-2026.5.1-cp312-cp312-manylinux_2_17_aarch64.manylinux2014_aarch64.whl", hash = "sha256:0fa92420128dadce7f54bd73ba1825a273e9268fe9e35dbf7e6362890efa4e08", size = 376329, upload-time = "2026-05-28T11:59:15.271Z" },
 { url = "https://files.pythonhosted.org/packages/d0/11/ee0ba42aff83bf4effdbc576673c6be64c5e173978c3f6d537e94482f77d/rpds_py-2026.5.1-cp312-cp312-manylinux_2_17_armv7l.manylinux2014_armv7l.whl", hash = "sha256:ca653c6546386227cd9800d1bef6a348099acf8db4250341da6d90f663d6dfcb", size = 383539, upload-time = "2026-05-28T11:59:16.665Z" },
 { url = "https://files.pythonhosted.org/packages/11/df/d94aa6a499d4ac40afe2d7620f2c597fd3c0f182e854ad7cf3f596a81cb6/rpds_py-2026.5.1-cp312-cp312-manylinux_2_17_ppc64le.manylinux2014_ppc64le.whl", hash = "sha256:66c93681c4729e4e3ecba31b8179fae083ff3118841672835140338b4b9867c1", size = 494674, upload-time = "2026-05-28T11:59:17.991Z" },
 { url = "https://files.pythonhosted.org/packages/1f/75/33d30f43bb2f458de11979486a591b1bf6e5651765ed1704c6197c2dc773

```

/rpds\_py-2026.5.1-cp312-cp312-manylinux\_2\_17\_s390x.manylinux2014\_s390x.whl", hash = "sha256:40ff257542e04796880e011e15c  
d4dc21c259975df2aa8f2c8495ca574e1a5", size = 389268, upload-time = "2026-05-28T11:59:19.434Z" },  
{ url = "https://files.pythonhosted.org/packages/f4/1e/2c9096fc19d5fd084b0184ca2b651e659aa0a37e6fdbecf6e647f147fe1  
/rpds\_py-2026.5.1-cp312-cp312-manylinux\_2\_17\_x86\_64.manylinux2014\_x86\_64.whl", hash = "sha256:b6825cc329b290e93c5f6a9be  
2393118a763f6ccf6abd83704e0c102ca583644", size = 376280, upload-time = "2026-05-28T11:59:21Z" },  
{ url = "https://files.pythonhosted.org/packages/b9/e5/61ec9f8be8211ea7f48448195549e4aaf02004083475493b0e137702ecb2  
/rpds\_py-2026.5.1-cp312-cp312-manylinux\_2\_31\_riscv64.whl", hash = "sha256:de42116e69cb53b911cc34aee5ab98f36c597b8225450  
45d49e938818b99e5e4", size = 387233, upload-time = "2026-05-28T11:59:22.454Z" },  
{ url = "https://files.pythonhosted.org/packages/0d/ca/bcec1005c4f4a234f92a29078631fee49206c7265ccae966f18fd332e80e  
/rpds\_py-2026.5.1-cp312-cp312-manylinux\_2\_5\_i686.manylinux1\_i686.whl", hash = "sha256:c0f920015df2a504bebab6d4c31ccf3f  
cf942f92655c086da30b671aad19aa6", size = 405009, upload-time = "2026-05-28T11:59:23.845Z" },  
{ url = "https://files.pythonhosted.org/packages/72/e6/4d5718c5cf26c522dc7c9999e238da1e77380b81d0c5d1df11e271ddfeb1  
/rpds\_py-2026.5.1-cp312-cp312-musllinux\_1\_2\_aarch64.whl", hash = "sha256:0408a24e44feb919423cd6d9da677cb5cddb894d2ca9e7  
63967d156d9c60fab4", size = 553113, upload-time = "2026-05-28T11:59:25.184Z" },  
{ url = "https://files.pythonhosted.org/packages/d4/25/2ee807bdb3e1f0b7eddf7782acd5665a8b5205a331a7d7244a52c4812fd9  
/rpds\_py-2026.5.1-cp312-cp312-musllinux\_1\_2\_i686.whl", hash = "sha256:cea68bcd53467561ae2f96a6bdad1544299ba97b5b0ddcd5a  
c3d376e5c781c24", size = 618838, upload-time = "2026-05-28T11:59:26.749Z" },  
{ url = "https://files.pythonhosted.org/packages/6a/c1/7d4c26f167f8c41501cc073d30ee22082b16ce358cf5b00ec97cbc7804ea  
/rpds\_py-2026.5.1-cp312-cp312-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:4be8b1d2a705cc37d08256004e1d07de143fa0075c8e85a  
3df020b776f62b732", size = 582436, upload-time = "2026-05-28T11:59:28.11Z" },  
{ url = "https://files.pythonhosted.org/packages/04/1d/9d12b0a337bab46f4769f8857f4007e3b2d639e14f9a44a0efe157696e64  
/rpds\_py-2026.5.1-cp312-cp312-win32.whl", hash = "sha256:6736718bd4fc49cbcb538ba30516fdbef161522acefb739657d48b97bd864f  
ed", size = 212734, upload-time = "2026-05-28T11:59:29.689Z" },  
{ url = "https://files.pythonhosted.org/packages/c5/93/e4116f2de7f56bc7406a76033dc501811ddeb22b7f056b92d632871ebbb0c  
/rpds\_py-2026.5.1-cp312-cp312-win\_amd64.whl", hash = "sha256:0a7d1eec967df0e9b22614a5e177622e0c89611d03727fa0cb48e45028  
907870", size = 229045, upload-time = "2026-05-28T11:59:31.033Z" },  
{ url = "https://files.pythonhosted.org/packages/cb/53/6c3419d85eb2ec5938a37627c585b42d76a63bb731d6e42ed4b079ebf486  
/rpds\_py-2026.5.1-cp312-cp312-win\_arm64.whl", hash = "sha256:1841d067089e117142d79b98aa0df2f08b52f2ecc1819dd2700636c0db  
74a473", size = 223967, upload-time = "2026-05-28T11:59:32.318Z" },  
{ url = "https://files.pythonhosted.org/packages/6c/32/14c961ad295f490eb0849ada8b79683e93a59b9de3afdd983eaf55fa6867  
/rpds\_py-2026.5.1-cp313-cp313-macosx\_10\_12\_x86\_64.whl", hash = "sha256:efef4ac29c6ff495531eb17ee705b62841ecaa291b7c7077  
e848ea03e237164d", size = 352787, upload-time = "2026-05-28T11:59:33.655Z" },  
{ url = "https://files.pythonhosted.org/packages/ca/bb/d1b85117967c1191441a7274ae616c65d93901d082c588f89a50a8da5ae  
/rpds\_py-2026.5.1-cp313-cp313-macosx\_11\_0\_arm64.whl", hash = "sha256:c39f5b67a8a2e67179ada2a954227d670fe65fa9098457f698  
f56ddf248709b3", size = 345179, upload-time = "2026-05-28T11:59:35Z" },  
{ url = "https://files.pythonhosted.org/packages/7c/46/d84105f062e626a1b233f863907288a4708c2d833b8b4c6fb2764bc080c0  
/rpds\_py-2026.5.1-cp313-cp313-manylinux\_2\_17\_aarch64.manylinux2014\_aarch64.whl", hash = "sha256:b5c30f3f04eef4fbd362226  
a6f31d7c8895ca4fbb6e0b790f6890a98d8da8559", size = 376173, upload-time = "2026-05-28T11:59:36.43Z" },  
{ url = "https://files.pythonhosted.org/packages/e2/ae/469d7959ce5b1201e1de135dc735b86db3b35dd0d1734f6a44246d5f061c  
/rpds\_py-2026.5.1-cp313-cp313-manylinux\_2\_17\_armv7l.manylinux2014\_armv7l.whl", hash = "sha256:277f6c82f0580848796c7ecc8  
a7173aa3bfb928e4ff831261c2f60a81dc270db", size = 383162, upload-time = "2026-05-28T11:59:37.995Z" },  
{ url = "https://files.pythonhosted.org/packages/dc/a2/57853d31a116a561aa072794602ad3f6341e18d70a8523f1bd5b9fc1e5a  
/rpds\_py-2026.5.1-cp313-cp313-manylinux\_2\_17\_ppc64le.manylinux2014\_ppc64le.whl", hash = "sha256:63c2c4c213f1a4e3f3de28e  
cab029dbdee976324e729c0d7a55211be72576b02", size = 495093, upload-time = "2026-05-28T11:59:39.453Z" },  
{ url = "https://files.pythonhosted.org/packages/99/63/3a8eabcad9314b7daf5c65f451d2c33d989235cd8a5762186cf2c3f5a4f8  
/rpds\_py-2026.5.1-cp313-cp313-manylinux\_2\_17\_s390x.manylinux2014\_s390x.whl", hash = "sha256:3350ec808fb538fe71a1f94dfaa  
0e29c598dfad805ce49f0caec5ae3183c652b", size = 389829, upload-time = "2026-05-28T11:59:40.896Z" },  
{ url = "https://files.pythonhosted.org/packages/4b/25/05678d97fc25e2622df14dc530fb82023174ecffff6733991ed0d78f167bd  
/rpds\_py-2026.5.1-cp313-cp313-manylinux\_2\_17\_x86\_64.manylinux2014\_x86\_64.whl", hash = "sha256:b1b964e3ab599e718dc46c018  
d104b1ebc007cbc6567d827c94a687fca56d77e", size = 374786, upload-time = "2026-05-28T11:59:42.626Z" },  
{ url = "https://files.pythonhosted.org/packages/88/d1/8c90b6431e80a3b91b284a5c7c8c0c4f9c006444d90477a740d6e0f9c694  
/rpds\_py-2026.5.1-cp313-cp313-manylinux\_2\_31\_riscv64.whl", hash = "sha256:19cb09fab7b7fc96b2a6e28f2e34b72a3705ff27b37ed  
b77455316e5d3f3dc9b", size = 386920, upload-time = "2026-05-28T11:59:44.124Z" },  
{ url = "https://files.pythonhosted.org/packages/ff/99/4638f672ab356682d633ee0da9255f5b67ce6efd0b85eb94ad3e255e65a5  
/rpds\_py-2026.5.1-cp313-cp313-manylinux\_2\_5\_i686.manylinux1\_i686.whl", hash = "sha256:abe76bcdba31e576cb83eeb8797aa0d88  
2b738fef6dc65d0601fc753806a5b46", size = 405059, upload-time = "2026-05-28T11:59:47.177Z" },  
{ url = "https://files.pythonhosted.org/packages/66/3f/3546524b6eb4cc2e1f363a3d638fa52f6c24faae3500c25fb488b02f1740  
/rpds\_py-2026.5.1-cp313-cp313-musllinux\_1\_2\_aarch64.whl", hash = "sha256:8bff7073db3899158fff55ebf57b113a67030af26f80a1  
8978f9f0aa60250dddf", size = 553030, upload-time = "2026-05-28T11:59:48.603Z" },  
{ url = "https://files.pythonhosted.org/packages/c6/c3/7b3388c796fcf471bd17194242d4dc1a7608567c0fa422bcc1c5e79f9c1e  
/rpds\_py-2026.5.1-cp313-cp313-musllinux\_1\_2\_i686.whl", hash = "sha256:8ba264fa49be666cd9cc56bf34ec7002fb3d27a4aee5bcb4d  
43d0d18feb1bb6f", size = 618975, upload-time = "2026-05-28T11:59:50.314Z" },  
{ url = "https://files.pythonhosted.org/packages/61/1e/a3cb07f2795075d1d88efddae2f541359fde5f08c81ee114c29c2949c90a  
/rpds\_py-2026.5.1-cp313-cp313-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:4860b603ddda0475a8885499b3729e90229d480105b4265  
1962a5397d995fa89", size = 581178, upload-time = "2026-05-28T11:59:51.673Z" },  
{ url = "https://files.pythonhosted.org/packages/a1/74/e758c03a5ef46f04c37f2651a2893db846d569ba8a7bca469d4b58939bcd  
/rpds\_py-2026.5.1-cp313-cp313-win32.whl", hash = "sha256:7944270ae71383f6e2657dd7d5ce4eeb4ac2d0059a6738f0510583d462ab48  
42", size = 212481, upload-time = "2026-05-28T11:59:53.148Z" },  
{ url = "https://files.pythonhosted.org/packages/70/ec/a2aca432db9c7359b40fa393eeaa0d166c2f70175be956e75fa24197c44  
/rpds\_py-2026.5.1-cp313-cp313-win\_amd64.whl", hash = "sha256:88647f43a73c4e01be19b04ceef0c8d3a1958153604d13c773becd8016  
f2a0cf", size = 228519, upload-time = "2026-05-28T11:59:54.505Z" },  
{ url = "https://files.pythonhosted.org/packages/29/60/a73bfd45b096574556acf303bbd9fa9eed36ca8a818b514e2a5d5fe2b9d  
/rpds\_py-2026.5.1-cp313-cp313-win\_arm64.whl", hash = "sha256:453895624ecf7db7063b1004e44037522bbaef9ff6a945e59bc71662d7  
a03abd", size = 223446, upload-time = "2026-05-28T11:59:56.081Z" },  
{ url = "https://files.pythonhosted.org/packages/18/e2/408105fd611823f00882aea810f3989a30d26b1bab8b6beb20f98c724e0e  
/rpds\_py-2026.5.1-cp313-cp313t-macosx\_10\_12\_x86\_64.whl", hash = "sha256:b4e4bc98639ec915f512fde3aa7a95e0041d95d9c3cc86e

ea841fa63cb1e8600", size = 355287, upload-time = "2026-05-28T11:59:57.448Z" },  
 { url = "https://files.pythonhosted.org/packages/8d/58/5c4a43436843c90df6d19f82c200c80e3843ca9fa07b237623327f6d384/rpds\_py-2026.5.1-cp313-cp313t-macosx\_11\_0\_arm64.whl", hash = "sha256:cacedb7a6e167680acba45ad5716e89067d225dc80da0d7040cae8c81d4572fa", size = 347033, upload-time = "2026-05-28T11:59:58.881Z" },  
 { url = "https://files.pythonhosted.org/packages/fb/c2/1a71acdacaf4e259b10278fb87b039ded3cf80041bcd89dd8a3ea702ded6/rpds\_py-2026.5.1-cp313-cp313t-manylinux\_2\_17\_aarch64.manylinux2014\_aarch64.whl", hash = "sha256:68700371c5d7ae1412862dffa719090925c93ecf351c566d66f09d04b136ea00", size = 376891, upload-time = "2026-05-28T12:00:00.516Z" },  
 { url = "https://files.pythonhosted.org/packages/c2/c8/535f3d9b65add8e28aa87b83c6e526799c3717a8823db8ea795beef7a/rpds\_py-2026.5.1-cp313-cp313t-manylinux\_2\_17\_armv7l.manylinux2014\_armv7l.whl", hash = "sha256:296c799becfa849c779c8725494fe9ed94959ed886787df4364b058465bad7f0", size = 385646, upload-time = "2026-05-28T12:00:02.394Z" },  
 { url = "https://files.pythonhosted.org/packages/1c/91/dc033f313345c354ade914dbe73cdb90b615a4409ea02430d5356794f3d8/rpds\_py-2026.5.1-cp313-cp313t-manylinux\_2\_17\_ppc64le.manylinux2014\_ppc64le.whl", hash = "sha256:d3858b908218ee108d0bbfb2095ccc237648053c9bf98affad7cb079acaf1d97", size = 498830, upload-time = "2026-05-28T12:00:04.189Z" },  
 { url = "https://files.pythonhosted.org/packages/27/fc/90fcbca459dbb8ddc18a2e0fd1de9412b48bc84ffff2db771cf714bacfd6/rpds\_py-2026.5.1-cp313-cp313t-manylinux\_2\_17\_s390x.manylinux2014\_s390x.whl", hash = "sha256:b9a6528956191c48c5229a592dbd4a8386d7048bdb21b991738accec96500a75c30f49caf064ce7cef", size = 392830, upload-time = "2026-05-28T12:00:05.797Z" },  
 { url = "https://files.pythonhosted.org/packages/b2/1d/46cd11a228c9750684a798d98f878be6f614aa762438da7378f035e79e35/rpds\_py-2026.5.1-cp313-cp313t-manylinux\_2\_17\_x86\_64.manylinux2014\_x86\_64.whl", hash = "sha256:27b74c10ed6a8f190f4287f53bcfea348b92a84a9c9f70d30183d1e6172d580d", size = 379613, upload-time = "2026-05-28T12:00:07.433Z" },  
 { url = "https://files.pythonhosted.org/packages/24/4a/d9b0c6af3a1de03eb93741bbe8be2bdce84d8fda8224f3005451d86df389/rpds\_py-2026.5.1-cp313-cp313t-manylinux\_2\_31\_riscv64.whl", hash = "sha256:b9a6528956191c48c5229a592dbd4a8386d7048bdb25c0efcb6b966466c6d83", size = 388183, upload-time = "2026-05-28T12:00:09.227Z" },  
 { url = "https://files.pythonhosted.org/packages/c5/b4/db7aaabdda6d020afcf87d981bcc2f57a434c7dec60ecfc2ab3dd50b20351/rpds\_py-2026.5.1-cp313-cp313t-manylinux\_2\_5\_i686.manylinux1\_i686.whl", hash = "sha256:af03e34e860047bc7a352b842856fcf78798fbb81132cc98bd2f907ab4eb9cd2", size = 408578, upload-time = "2026-05-28T12:00:10.779Z" },  
 { url = "https://files.pythonhosted.org/packages/08/d6/070f6a41cbb343e2ac4171859bf3f3623e0ab002f72619d6d505313ec2de/rpds\_py-2026.5.1-cp313-cp313t-musllinux\_1\_2\_aarch64.whl", hash = "sha256:fea6e836d10abbe191d557d33bd58bd5987725fe63aa1eefe557d230209855bd", size = 553573, upload-time = "2026-05-28T12:00:12.443Z" },  
 { url = "https://files.pythonhosted.org/packages/75/ab/1a71ea3589c4345dac0a0518f0e6a031cb42689277851b683c46d27463a5/rpds\_py-2026.5.1-cp313-cp313t-musllinux\_1\_2\_i686.whl", hash = "sha256:fc0c0f878ea770a0a8a462456c5ad36fc9fe6358e6b76fda7c7f17575e0b8bf1", size = 620861, upload-time = "2026-05-28T12:00:14.09Z" },  
 { url = "https://files.pythonhosted.org/packages/8a/22/9bf80a56069c0c443fcfefac639a86a744550a2898817a6dfd3e26654924/rpds\_py-2026.5.1-cp313-cp313t-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:e0b360f316d966b048b085857630b3cc51f3db2f07b06f440eac8f695374d1e3", size = 585633, upload-time = "2026-05-28T12:00:15.66Z" },  
 { url = "https://files.pythonhosted.org/packages/da/68/3b2c0a75c9e04125696f84ebdbbf304acf5a40b58ba4481c98a922c3ba/rpds\_py-2026.5.1-cp313-cp313t-win32.whl", hash = "sha256:a2999883eedf72fdb7520b92c7d4ec2572a71ff40239377aa604cc529eecaafc", size = 210074, upload-time = "2026-05-28T12:00:17.291Z" },  
 { url = "https://files.pythonhosted.org/packages/e7/8b/609157d5a25d37d4f29f92840ba531f416907c34ae5c5739dd21fc2bef98/rpds\_py-2026.5.1-cp313-cp313t-win\_amd64.whl", hash = "sha256:e07be2a9d7122bd6e82dea89814ef8dc893feb1aae97fec1630f3263bb30e55", size = 228635, upload-time = "2026-05-28T12:00:18.73Z" },  
 { url = "https://files.pythonhosted.org/packages/d4/6f/19c1918a4b590d8de87e712e4abe4b3875771eff60216fb6153fc6665c68/rpds\_py-2026.5.1-cp314-cp314-macosx\_10\_12\_x86\_64.whl", hash = "sha256:1f2c391c3059798093b65df23aca2cac150460ae9c630d99dec83d703d9485b9", size = 349756, upload-time = "2026-05-28T12:00:20.217Z" },  
 { url = "https://files.pythonhosted.org/packages/e5/60/a06fe7da34eca79dabcf958a2ba0c6eea85bc2b29de20080bf40f72f66fa/rpds\_py-2026.5.1-cp314-cp314-macosx\_11\_0\_arm64.whl", hash = "sha256:413b424f7c4ee65ab5e5be91f5731be0f8b41a1ee2b12df8e10d716312e95a78", size = 343831, upload-time = "2026-05-28T12:00:21.711Z" },  
 { url = "https://files.pythonhosted.org/packages/bf/ec/b2333b97b90e2a6ef6ca8ad386ee284968e74bfcfe113b3f1a8d9036429a9/rpds\_py-2026.5.1-cp314-cp314-manylinux\_2\_17\_aarch64.manylinux2014\_aarch64.whl", hash = "sha256:2c595a1d9255dce0599e13130d1440ab2506654f2b50294226ee06402f8fef63", size = 375127, upload-time = "2026-05-28T12:00:23.326Z" },  
 { url = "https://files.pythonhosted.org/packages/14/7f/e00aae54067f2b488c4637961d5f58204d40795fc791085fa3f15060d2e/rpds\_py-2026.5.1-cp314-cp314-manylinux\_2\_17\_armv7l.manylinux2014\_armv7l.whl", hash = "sha256:1c27c5f6102eac8c03e7595a00827a53b271ba40a53b59ff8709170e0855ea4a", size = 379034, upload-time = "2026-05-28T12:00:24.89Z" },  
 { url = "https://files.pythonhosted.org/packages/be/cc/423999bbb8ae8dc93c77fcd15e984ade5eb89d237d3bb884ccfa72ae2890/rpds\_py-2026.5.1-cp314-cp314-manylinux\_2\_17\_ppc64le.manylinux2014\_ppc64le.whl", hash = "sha256:6c7f9cf61d44cacecaf3aea542b0e053db77972a4573e7ceda16fb2b399161195", size = 490823, upload-time = "2026-05-28T12:00:26.676Z" },  
 { url = "https://files.pythonhosted.org/packages/0f/aa/c671bf660f12e68d3c52ff86c7066ed1372df5a0f42ff584e419b8207e7/rpds\_py-2026.5.1-cp314-cp314-manylinux\_2\_17\_s390x.manylinux2014\_s390x.whl", hash = "sha256:2c817a189d4ee14290420e5ff051e4dd6baa13f3edf84685071dee07a6d538ee", size = 388144, upload-time = "2026-05-28T12:00:28.577Z" },  
 { url = "https://files.pythonhosted.org/packages/19/c8/d63bb75b68afe77b229e3021c6031bcacf01da5db5b0e69d0d10f9ba679a7/rpds\_py-2026.5.1-cp314-cp314-manylinux\_2\_17\_x86\_64.manylinux2014\_x86\_64.whl", hash = "sha256:21846aac0ed2e0589f38c12dc44e77bb64e494b77leadbcf169cba00566ba7ba", size = 371959, upload-time = "2026-05-28T12:00:30.304Z" },  
 { url = "https://files.pythonhosted.org/packages/82/35/c51122014d8274ff37dc606d60049c3db7d83da02b5b282511e5a906a9a6/rpds\_py-2026.5.1-cp314-cp314-manylinux\_2\_31\_riscv64.whl", hash = "sha256:b317c87a13f769a4e787819bd508aaa5d69aa09b0880de9af6d3a8a54571cdec", size = 383558, upload-time = "2026-05-28T12:00:31.764Z" },  
 { url = "https://files.pythonhosted.org/packages/e3/f9/2790cb99c136a5363acdeacf5c27c56f3de0d4118a1f48fca83404c99c89/rpds\_py-2026.5.1-cp314-cp314-manylinux\_2\_5\_i686.manylinux1\_i686.whl", hash = "sha256:ce87129d9f2c14fa6c4a8601fb80eb4488c80d38a20cd13758ef11123e14995d", size = 402789, upload-time = "2026-05-28T12:00:33.247Z" },  
 { url = "https://files.pythonhosted.org/packages/e5/1b/ef4fb584f8c75d35c38150ff6a332cda949e6f97acba1f4fd123b14ab56fe/rpds\_py-2026.5.1-cp314-cp314-musllinux\_1\_2\_aarch64.whl", hash = "sha256:9cdddb6c1207d284d94fd1530adf57fbd797fe7c4b8704ba85f49414f2557e7d", size = 551405, upload-time = "2026-05-28T12:00:34.819Z" },  
 { url = "https://files.pythonhosted.org/packages/d8/f7/a6731b4216cb3793ea1af5391da240f5683dacc0d13e034fe5fc3503f240/rpds\_py-2026.5.1-cp314-cp314-musllinux\_1\_2\_i686.whl", hash = "sha256:4e237e139f94d3c036fd28eb9f564c99055476ff4ff05cd42be55ce349b5aa02", size = 616975, upload-time = "2026-05-28T12:00:36.268Z" },  
 { url = "https://files.pythonhosted.org/packages/2c/ea/2e051a81d95d8e63f4b35a1c463a87e8766bc3d083c067c5df6bbf220747/rpds\_py-2026.5.1-cp314-cp314-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:ed0954b524873214369184a9c82b0eaa45a3fbb9a798cd95b17e0d98499e7ea0", size = 578701, upload-time = "2026-05-28T12:00:37.82Z" },

{ url = "https://files.pythonhosted.org/packages/65/56/b5f6fdb2083e32bca8a8993d89e70db114b4756c9e2c38421328126689d2/rpds\_py-2026.5.1-cp314-cp314-win32.whl", hash = "sha256:2d88621d6a7d4dfa633d21abe90f280bb205274e16b1d1e61c6ad4640b2453b7", size = 209806, upload-time = "2026-05-28T12:00:39.492Z" },

{ url = "https://files.pythonhosted.org/packages/fb/80/65a5aa96c155e611d1ed844e4e1f57f3e36b021f396d9f8585d756e6b90d/rpds\_py-2026.5.1-cp314-cp314-win\_amd64.whl", hash = "sha256:cef8ac28d26f4dda3533060c20fbf80a325458fa9fd23ea72a73cdfa8e978838", size = 225985, upload-time = "2026-05-28T12:00:40.94Z" },

{ url = "https://files.pythonhosted.org/packages/27/7c/ad185212e87b05f196daef92bc5f3caf07298eb47c295b5585c3dd3093ac/rpds\_py-2026.5.1-cp314-cp314-win\_arm64.whl", hash = "sha256:eaeea962c68cdc68d4a533ba985ab8e9484277910bbfaa2ab3ef7732667bfed8", size = 221219, upload-time = "2026-05-28T12:00:46.14Z" },

{ url = "https://files.pythonhosted.org/packages/23/58/e14ae18759020334646b031e708ab4158d653a938822bf7b95ef2e93aa3/rpds\_py-2026.5.1-cp314-cp314t-macosx\_10\_12\_x86\_64.whl", hash = "sha256:21942f52dbbd5f8758bf021213d28bd45c39e873e65e2407faf5f1846f5761ad", size = 352148, upload-time = "2026-05-28T12:00:44.638Z" },

{ url = "https://files.pythonhosted.org/packages/31/9b/5f4a1e2f960bca3ac5d052b139dd31eed97b259f9d909173821760d542e8/rpds\_py-2026.5.1-cp314t-macosx\_11\_0\_arm64.whl", hash = "sha256:f414556f6e3958300ff941e40c9f97e3dc9774ddd1b3434c475d73dd354bbcd3", size = 345196, upload-time = "2026-05-28T12:00:46.14Z" },

{ url = "https://files.pythonhosted.org/packages/1a/71/1d9574d6a2fa20ab60eaa55c7467f5aa20cbc770f341a05f09c0876f59e2/rpds\_py-2026.5.1-cp314-cp314t-manylinux\_2\_17\_aarch64.manylinux2014\_aarch64.whl", hash = "sha256:ef1013a8625c74043210190b246f5b1551e09757c1f356c6e4160ef96c5bc081", size = 374981, upload-time = "2026-05-28T12:00:47.531Z" },

{ url = "https://files.pythonhosted.org/packages/0c/9a/37e99f4915a80aa71670263c1267f7ae0af95f53a3f61e6c3bdc016d4515/rpds\_py-2026.5.1-cp314-cp314t-manylinux\_2\_17\_armv7l.manylinux2014\_armv7l.whl", hash = "sha256:cc68e231a77a5f0d774ae278a1f8e55c0456501820847c1e4efb3829f3441df6", size = 379961, upload-time = "2026-05-28T12:00:49.216Z" },

{ url = "https://files.pythonhosted.org/packages/a8/ff/6e73f74b89d2e0715e0fc86b7dde893f9a61ae2f9b256ff3bdfc41ac4e94/rpds\_py-2026.5.1-cp314-cp314t-manylinux\_2\_17\_ppc64le.manylinux2014\_ppc64le.whl", hash = "sha256:9baffb505aff33acc69b422a19f77806680f3c8632227d79f48de8a810d1c2c5", size = 495965, upload-time = "2026-05-28T12:00:51.111Z" },

{ url = "https://files.pythonhosted.org/packages/ea/e0/425faba25f59d74d4638b267f7c7a80e8649d2ef4db10a19b0c4a71e6e6f/rpds\_py-2026.5.1-cp314-cp314t-manylinux\_2\_17\_s390x.manylinux2014\_s390x.whl", hash = "sha256:b8d2f912928d426e8cfa396f7f3f8d29a59e6689c86dcca3c420730c1096322b", size = 389526, upload-time = "2026-05-28T12:00:52.77Z" },

{ url = "https://files.pythonhosted.org/packages/c6/76/7a41960e3fddae47fab43a28684d5da981401dff88253de0944148654cb/rpds\_py-2026.5.1-cp314-cp314t-manylinux\_2\_17\_x86\_64.manylinux2014\_x86\_64.whl", hash = "sha256:90f628283be835db980c941767d41c9a27b5239e54ba0a9c1335247e82406964", size = 376190, upload-time = "2026-05-28T12:00:54.215Z" },

{ url = "https://files.pythonhosted.org/packages/27/60/5f38dc70824fc6951b51d35377e577a3a3a4c81a6769cc5a2de25ebe0ad1/rpds\_py-2026.5.1-cp314-cp314t-manylinux\_2\_31\_riscv64.whl", hash = "sha256:1ebb2f0ab7e16132995a72de805170e0203df0c3dd22e1ef1cd1fdd90bd7a131", size = 383921, upload-time = "2026-05-28T12:00:55.673Z" },

{ url = "https://files.pythonhosted.org/packages/60/1a/d60a38caa1505f4b9483c3fbbde12c94e1079154f4f401a6da96f7e77621/rpds\_py-2026.5.1-cp314-cp314t-manylinux\_2\_5\_i686.manylinux1\_i686.whl", hash = "sha256:f3dfd316ded76f1f8c9cdebd0e1ea55fdf4c23b812de189814da7cf229c22a81", size = 404766, upload-time = "2026-05-28T12:00:57.518Z" },

{ url = "https://files.pythonhosted.org/packages/87/ff/602fd3f174d6425f0bce05ad0dfbec0e96b38d0f7d08a79af5aa20083885/rpds\_py-2026.5.1-cp314-cp314t-musllinux\_1\_2\_aarch64.whl", hash = "sha256:9af8905b8f854990e40d5206aa5ac58d9b0fe0b7f351ff2bb086c20f6c8c6a47", size = 551343, upload-time = "2026-05-28T12:00:58.978Z" },

{ url = "https://files.pythonhosted.org/packages/b8/c1/1be13327acdbead3eca1fde03b6a34dbb011f1e864e217f0d32cc1779a7f/rpds\_py-2026.5.1-cp314-cp314t-musllinux\_1\_2\_i686.whl", hash = "sha256:036a36a87fb1cd3b214d11c4b3c4f7d2ddad933625dca1c900b56a057c07740a", size = 618502, upload-time = "2026-05-28T12:01:00.656Z" },

{ url = "https://files.pythonhosted.org/packages/f3/d7/afb49b49d7f2be8b7ba1a9f0977fa5168003437b93086726f066544e8351/rpds\_py-2026.5.1-cp314-cp314t-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:62ae3853454fe9ef283a03c96c2d835d39e84b14643a9d62c82ef0fb87d702ca", size = 581916, upload-time = "2026-05-28T12:01:02.22Z" },

{ url = "https://files.pythonhosted.org/packages/25/d1/dbef8c1f8a10f07beb62b5f054e20099fd9924b3ec001b8f0b6ac7813a85/rpds\_py-2026.5.1-cp314-cp314t-win32.whl", hash = "sha256:6c3d771a46ec18b12af06ce36243a9a80b07a5d0515236332d90863ca8bb326a", size = 207855, upload-time = "2026-05-28T12:01:03.821Z" },

{ url = "https://files.pythonhosted.org/packages/2a/72/bfa4e61ab8e7dc1c8adf397e05e6cbdd4239357bd72b248d3de662f23915/rpds\_py-2026.5.1-cp314-cp314t-win\_amd64.whl", hash = "sha256:c93c629be4636cf54337bd5f06c104d55e42ced54d681f6fe21ae510a65116f6", size = 225422, upload-time = "2026-05-28T12:01:05.194Z" },

{ url = "https://files.pythonhosted.org/packages/27/3a/7b5da92b640f67b6717ccafc83cdd06bfa7ff2395c3685c68922bb54d703/rpds\_py-2026.5.1-cp315-cp315-macosx\_10\_12\_x86\_64.whl", hash = "sha256:3574b55c604b8f75dacb007136508bbcd0b406e626301778096a133327e7f2fb", size = 349576, upload-time = "2026-05-28T12:01:06.722Z" },

{ url = "https://files.pythonhosted.org/packages/d7/8a/2aafd7ad355a1bd48ca76e2262b74b15e6432b5a1efe150efd4d779cd55d/rpds\_py-2026.5.1-cp315-cp315-macosx\_11\_0\_arm64.whl", hash = "sha256:94068eb3ae6d43f5a786b7db96a406a34e6d5c24489feef32fd6e8946ea7b291", size = 343640, upload-time = "2026-05-28T12:01:08.441Z" },

{ url = "https://files.pythonhosted.org/packages/f7/7d/6c9523c1abbe840a1b7fba3c516d48e1d3487cc80fea4366c4071cf56784/rpds\_py-2026.5.1-cp315-cp315-manylinux\_2\_17\_aarch64.manylinux2014\_aarch64.whl", hash = "sha256:f3a5b10e8ce894825f380a8f1b6444cf73c294dfea62afbb2d13e3a9e630cec1", size = 375322, upload-time = "2026-05-28T12:01:09.934Z" },

{ url = "https://files.pythonhosted.org/packages/5a/5d/0b7b03fb1dc509321f01de3149784ab773e34c8573022029af8076afcb9c/rpds\_py-2026.5.1-cp315-cp315-manylinux\_2\_17\_armv7l.manylinux2014\_armv7l.whl", hash = "sha256:fc09f82e63d4bcd58149572f857a431bae851dc747e313c3b5bdf7abb907fda8", size = 379066, upload-time = "2026-05-28T12:01:11.48Z" },

{ url = "https://files.pythonhosted.org/packages/d7/e2/8ef6012999ebf1cb1c22f876d9ce5e63d960fd4631d2af3202d3f480aa25/rpds\_py-2026.5.1-cp315-cp315-manylinux\_2\_17\_ppc64le.manylinux2014\_ppc64le.whl", hash = "sha256:e10464d17df3b582745c25cec695cb9558bca2cb6dd6b31aee1787fc72c767b2", size = 494586, upload-time = "2026-05-28T12:01:13.051Z" },

{ url = "https://files.pythonhosted.org/packages/80/af/1eeb029bec67582c226b7809172207cd005073af4ebd906e65ff494f4983/rpds\_py-2026.5.1-cp315-cp315-manylinux\_2\_17\_s390x.manylinux2014\_s390x.whl", hash = "sha256:ba05adbf15d994c38ec0b7ab32e858e5110c21e9009a00a86545fd220f84e038", size = 388415, upload-time = "2026-05-28T12:01:14.631Z" },

{ url = "https://files.pythonhosted.org/packages/18/23/ffbe10711c4d766c1cab0557d6906c074f795814863c67b351355d29354a/rpds\_py-2026.5.1-cp315-cp315-manylinux\_2\_17\_x86\_64.manylinux2014\_x86\_64.whl", hash = "sha256:77c004fdc7b891967106f78ddfd7b076bfe6813c6139c6fff6aed3bcaa960b26", size = 372427, upload-time = "2026-05-28T12:01:16.153Z" },

{ url = "https://files.pythonhosted.org/packages/bd/3a/30ba4a6ad457e5b070c18d742a33fb77d8d922b565cc881f8a5313d63bfe/rpds\_py-2026.5.1-cp315-cp315-manylinux\_2\_31\_riscv64.whl", hash = "sha256:83bcf894486c9d78dd290d3c0124ff6dd8875d3025e2090a8ec49fcc37c55fdd", size = 383615, upload-time = "2026-05-28T12:01:17.809Z" },

{ url = "https://files.pythonhosted.org/packages/d3/69/62e242b53ce39c0814bd24e1a6e6eba6c92be716277745f317f9540a2e7b

```

/rpds_py-2026.5.1-cp315-cp315-manylinux_2_5_i686.manylinux1_i686.whl", hash = "sha256:c3df104083952a0e0c6f10de33e440eab
e98fb6317d23e1a58c68f6df08d01b9", size = 402786, upload-time = "2026-05-28T12:01:19.419Z" },
 { url = "https://files.pythonhosted.org/packages/38/c1/a770b9c186928a1ed0f7e6d7ae50e7f3950ed23e3f9e366dbc8e38cb55de
/rpds_py-2026.5.1-cp315-cp315-musllinux_1_2_aarch64.whl", hash = "sha256:980450826cf22e133c57e0835070bdd0dd3f73b9b708c3
ce223def2cb9469e14", size = 551583, upload-time = "2026-05-28T12:01:21.013Z" },
 { url = "https://files.pythonhosted.org/packages/21/7c/68e8579b95375b70d2a963103c42e705856cdb98569258bd807f4423891c
/rpds_py-2026.5.1-cp315-cp315-musllinux_1_2_i686.whl", hash = "sha256:205dde846f24332ab0c1188699a043b8d165b79bb84529ce2
72c45048ff6be01", size = 616941, upload-time = "2026-05-28T12:01:22.548Z" },
 { url = "https://files.pythonhosted.org/packages/70/a1/a6135aed5730ff03ab957182259987ac11e55fb392a28dc6f0592048a280
/rpds_py-2026.5.1-cp315-cp315-musllinux_1_2_x86_64.whl", hash = "sha256:3966b82dd563176396df030f3dd52a6e54cb69b718e95e7
8bd555ed3d1e0185d", size = 578349, upload-time = "2026-05-28T12:01:24.118Z" },
 { url = "https://files.pythonhosted.org/packages/09/6e/f24201a76a84e6c49d0bbdfdfcb735210e21701e9b21c5bfc0ba497dd62f6
/rpds_py-2026.5.1-cp315-cp315-win32.whl", hash = "sha256:7818f8d0a415be74d2be3590b0a1c1f463a642f4d0217e7d10602dceef5b79
aa", size = 209922, upload-time = "2026-05-28T12:01:25.522Z" },
 { url = "https://files.pythonhosted.org/packages/9e/e4/966bc240bb0485fc265278f6de44d05834bf0b3618886e0b22e33d54c49a
/rpds_py-2026.5.1-cp315-cp315-win_amd64.whl", hash = "sha256:b3cc20c0d800af78fd0fac68086e28c1856cec51ea528bb81ea851aa40
d39325", size = 226003, upload-time = "2026-05-28T12:01:27.062Z" },
 { url = "https://files.pythonhosted.org/packages/5c/5c/a15a59269cd5e74472734516c73795c15eccfc841b3d4b0228c3f53f19d0
/rpds_py-2026.5.1-cp315-cp315-win_arm64.whl", hash = "sha256:3609e9939a8a76cd904cf98a3f1f13b5dc7e150adeaee89e0ea09652ea
213e16", size = 221245, upload-time = "2026-05-28T12:01:28.51Z" },
 { url = "https://files.pythonhosted.org/packages/e0/22/135ce03804e179a71ceb13be095deda4a279bc88f7a6b8fa161c5ad44e12
/rpds_py-2026.5.1-cp315-cp315t-macosx_10_12_x86_64.whl", hash = "sha256:5d333a7127d4b307601ac37792bee01bb95c867cbfacf21
b6375b804d6bbd723", size = 352015, upload-time = "2026-05-28T12:01:30.214Z" },
 { url = "https://files.pythonhosted.org/packages/3b/5f/f1f6d2652eb9d848f6eb369d8db83a2da6249bb49ad2c2a48f45d54538d3
/rpds_py-2026.5.1-cp315-cp315t-macosx_11_0_arm64.whl", hash = "sha256:b5f077b44a4f7808520f66dae234988d867deb9aed9be5da0
57ce9ba831b2a41", size = 345016, upload-time = "2026-05-28T12:01:31.656Z" },
 { url = "https://files.pythonhosted.org/packages/88/66/b74182775691ea2290c99e52ac8d5db844e56fbec90ce421f107658c8314
/rpds_py-2026.5.1-cp315-cp315t-manylinux_2_17_aarch64.manylinux2014_aarch64.whl", hash = "sha256:55d8f9b7b78c9538fc9e04
e82ec0e888ff0c3cfffad152c77e57cd09351a98a", size = 374775, upload-time = "2026-05-28T12:01:33.136Z" },
 { url = "https://files.pythonhosted.org/packages/ff/8f/15e5a61d9f0a43902d36561d4f07cae6ae9f4716be825159fd72717f33af
/rpds_py-2026.5.1-cp315-cp315t-manylinux_2_17_armv7l.manylinux2014_armv7l.whl", hash = "sha256:e3a8ae58895ac107ed934a6b
f51e5846f95c53b9b940c2c6d310838fd5846358", size = 380270, upload-time = "2026-05-28T12:01:34.574Z" },
 { url = "https://files.pythonhosted.org/packages/02/c3/f859b12763a80540cdf2af0f15b19904cf756a71d7bdd3f82ff3e5b1bbf9
/rpds_py-2026.5.1-cp315-cp315t-manylinux_2_17_ppc64le.manylinux2014_ppc64le.whl", hash = "sha256:0957cf3c2b8632ec7aaebf
febea8005b353cc2a237b6e2ae3c2cac0820704cfb", size = 495285, upload-time = "2026-05-28T12:01:36.127Z" },
 { url = "https://files.pythonhosted.org/packages/1c/c7/ff27c2ac8411d30b03b1829fd88cae8dad1a4d0da48dd25e57c4038042e6
/rpds_py-2026.5.1-cp315-cp315t-manylinux_2_17_s390x.manylinux2014_s390x.whl", hash = "sha256:c396c1304de421050b3681ea70
f371874b54d41b0151e96109758144c231e30b", size = 389581, upload-time = "2026-05-28T12:01:37.635Z" },
 { url = "https://files.pythonhosted.org/packages/6e/67/fe92ee32a6cc05c77228a2f8b1762e7124f386ec20ff83d0757b762d58d0
/rpds_py-2026.5.1-cp315-cp315t-manylinux_2_17_x86_64.manylinux2014_x86_64.whl", hash = "sha256:aad1bfff7f666b9598e573815
affd666aac6a13a585dde336f843e33350c7fadc", size = 376041, upload-time = "2026-05-28T12:01:39.307Z" },
 { url = "https://files.pythonhosted.org/packages/f8/91/b4d6685c27aba55bd82f25b278be8237038117d05f9659a6213ad3408130
/rpds_py-2026.5.1-cp315-cp315t-manylinux_2_31_riscv64.whl", hash = "sha256:656a042550878f12d45752452d47094b7cfe5ad1e9d7
b87b5a22ad3ae5ff8015", size = 383946, upload-time = "2026-05-28T12:01:41.043Z" },
 { url = "https://files.pythonhosted.org/packages/bd/79/2c1d832a53c8e0f8e98fc970ec257b950fecdf62be2ab7182b500a0cbbc8
/rpds_py-2026.5.1-cp315-cp315t-manylinux_2_5_i686.manylinux1_i686.whl", hash = "sha256:73c4bd4f70294737b5206a3e8e30ccad
bf8a60301831c8ea23eec5dbeea1ecfa", size = 405526, upload-time = "2026-05-28T12:01:43.032Z" },
 { url = "https://files.pythonhosted.org/packages/78/c4/c98117b03c6a8581ab2c2dfccfe9a5ad82bd8128a3c28b46a6ad2d97c393
/rpds_py-2026.5.1-cp315-cp315t-musllinux_1_2_aarch64.whl", hash = "sha256:43bca78665423cabae77146f2fe7ce55272b6c8d55d82
cca83effd42c7e13972", size = 551165, upload-time = "2026-05-28T12:01:44.648Z" },
 { url = "https://files.pythonhosted.org/packages/3b/c1/bc479ca069200af730881b1bd525e3114b2b391a351509fcb1b772f28086
/rpds_py-2026.5.1-cp315-cp315t-musllinux_1_2_i686.whl", hash = "sha256:42d0f20e85e549c870749d0e247f0c10d318a45b7e9676d5
75d2dc04a1b2e66", size = 618778, upload-time = "2026-05-28T12:01:46.337Z" },
 { url = "https://files.pythonhosted.org/packages/77/65/38ab2f90df44c2febfb63cc10ced40763d9b4bc94d173e734528663fe7f5
/rpds_py-2026.5.1-cp315-cp315t-musllinux_1_2_x86_64.whl", hash = "sha256:b1be5c35683684d5331b93600c210e8367c254683d8a6d
f6bd21bd2da3a334fb", size = 581839, upload-time = "2026-05-28T12:01:48.109Z" },
 { url = "https://files.pythonhosted.org/packages/15/2d/ce1f605fe036aadd460e5822e578c6c7ec3a860936cca37d6e0f299daa77
/rpds_py-2026.5.1-cp315-cp315t-win32.whl", hash = "sha256:75808f6c38ce7749bb68cc2770161aae5045e6c6f6781a9782e74b9330439
9df", size = 207866, upload-time = "2026-05-28T12:01:49.648Z" },
 { url = "https://files.pythonhosted.org/packages/79/cb/966040123eb102371559746908ef2c9471f4d43e17ec9a645a2258dab64b
/rpds_py-2026.5.1-cp315-cp315t-win_amd64.whl", hash = "sha256:90bd6630002a1c7f09e7843dd79f0d24f3d2897cc25a753480917865d
14f15b3", size = 225441, upload-time = "2026-05-28T12:01:51.408Z" },
]

[[package]]
name = "six"
version = "1.17.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/94/e7/b2c673351809dca68a0e064b6af791aa332cf192da575fd474ed7d6f
16a2/six-1.17.0.tar.gz", hash = "sha256:ff70335d468e7eb6ec65b95b99d3a2836546063f63acc5171de367e834932a81", size = 34031
, upload-time = "2024-12-04T17:35:28.174Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/b7/ce/149a00dd41f10bc29e5921b496af8b574d8413afcd5e30dfa0ed46c2cc5e
/six-1.17.0-py2.py3-none-any.whl", hash = "sha256:4721f391ed90541fddacab5acf947aa0d3dc7d27b2e1e8eda2be8970586c3274", si
ze = 11050, upload-time = "2024-12-04T17:35:26.475Z" },
]

```

```

[[package]]
name = "smmap"
version = "5.0.3"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/1f/ea/49c993d6dfdd7338c9b1000a0f36817ed7ec84577ae2e52f890d1a4ff909/smmap-5.0.3.tar.gz", hash = "sha256:4d9debb8b99007ae47165abc08670bd74cb74b5227dda7f643eccc4e9eb5642c", size = 22506, upload-time = "2026-03-09T03:43:26.1Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/c1/d4/59e74daffcb57a07668852eeeb6035af9f32cbfd7a1d2511f17d2fe6a738/smmap-5.0.3-py3-none-any.whl", hash = "sha256:c106e05d5a61449cf6ba9a1e650227ecfb141590d2a98412103ff35d89fc7b2f", size = 24390, upload-time = "2026-03-09T03:43:24.361Z" },
]

[[package]]
name = "starlette"
version = "1.3.1"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "anyio" },
 { name = "typing-extensions", marker = "python_full_version < '3.13'" },
]
sdist = { url = "https://files.pythonhosted.org/packages/eb/e3/7c1dc7381d9f8ab7d854328ebfa884e62cb3f3d8549ddfd37c7814f42afa/starlette-1.3.1.tar.gz", hash = "sha256:05d0213193f2fbaae60e2ecb593b4add4262ad4e46536b54abe36f11a71724e0", size = 2703240, upload-time = "2026-06-12T09:23:11.602Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/ec/bb/2799cc2ede3ed41131f8975621e7213dfc7ef4acbbadfa440f32500c370/starlette-1.3.1-py3-none-any.whl", hash = "sha256:c7372aae11c3c3f26a42df7bd626cec2f47d03483d261d369516a615a53714c6", size = 73632, upload-time = "2026-06-12T09:23:10.017Z" },
]

[[package]]
name = "streamlit"
version = "1.58.0"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "altair" },
 { name = "anyio" },
 { name = "blinker" },
 { name = "cachetools" },
 { name = "click" },
 { name = "gitpython" },
 { name = "httptools" },
 { name = "itsdangerous" },
 { name = "numpy" },
 { name = "packaging" },
 { name = "pandas" },
 { name = "pillow" },
 { name = "protobuf" },
 { name = "pyarrow" },
 { name = "pydeck" },
 { name = "python-multipart" },
 { name = "requests" },
 { name = "starlette" },
 { name = "tenacity" },
 { name = "toml" },
 { name = "typing-extensions" },
 { name = "uvicorn" },
 { name = "watchdog", marker = "sys_platform != 'darwin'" },
 { name = "websockets" },
]
sdist = { url = "https://files.pythonhosted.org/packages/91/74/20dac6d6200d6ec0e1c230fb8eeb6a1a423645each76e8d802adfc246456/streamlit-1.58.0.tar.gz", hash = "sha256:78a22e7085b053af7ce544442bf4b670771e68c509ba1bdaa056ba0708f49c3d", size = 8721149, upload-time = "2026-05-28T18:02:44.606Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/df/84/14c36a92fb24f8e1cea452f53b0744b5da69d52cdd2fe22e71e6fbf765d5/streamlit-1.58.0-py3-none-any.whl", hash = "sha256:4ca8a7afc5bd16a5f176ccf4be1e34e8121cad0240becd127fb58a103ea3178d", size = 9219185, upload-time = "2026-05-28T18:02:41.993Z" },
]

[[package]]
name = "tenacity"
version = "9.1.4"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/47/c6/ee486fd809e357697ee8a44d3d69222b344920433d3b6666ccd9b374630c/tenacity-9.1.4.tar.gz", hash = "sha256:adb31d4c263f2bd041081ab33b498309a57c77f9acf2db65aadf0898179cf93a", size = 4

```

```

9413, upload-time = "2026-02-07T10:45:33.841Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/d7/c1/eb8f9debc45d3b7918a32ab756658a0904732f75e555402972246b0b8e71
/tenacity-9.1.4-py3-none-any.whl", hash = "sha256:6095a360c919085f28c6527de529e76a06ad89b23659fa881ae0649b867a9d55", si
ze = 28926, upload-time = "2026-02-07T10:45:32.24Z" },
]

[[package]]
name = "toml"
version = "0.10.2"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/be/ba/1f744cdc819428fc6b5084ec34d9b30660f6f9daaf70eead706e3203
ec3c/toml-0.10.2.tar.gz", hash = "sha256:b3bda1d108d5dd99f4a20d24d9c348e91c4db7ab1b749200bde2f839ccbe68f", size = 2225
3, upload-time = "2020-11-01T01:40:22.204Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/44/6f/7120676b6d73228c96e17f1f794d8ab046fc910d781c8d151120c3f1569e
/toml-0.10.2-py2.py3-none-any.whl", hash = "sha256:806143ae5bfb6a3c6e736a764057db0e6a0e05e338b5630894a5f779cabb4f9b", s
ize = 16588, upload-time = "2020-11-01T01:40:20.672Z" },
]

[[package]]
name = "typing-extensions"
version = "4.15.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/72/94/1a15dd82efb362ac84269196e94cf00f187f7ed21c242792a923cdb1
c61f/typing_extensions-4.15.0.tar.gz", hash = "sha256:0cea48d173cc12fa28ecabc3b837ea3cf6f38c6d1136f85cbaaf598984861466"
, size = 109391, upload-time = "2025-08-25T13:49:26.313Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/18/67/36e9267722cc04a6b9f15c7f3441c2363321a3ea07da7ae0c0707beb2a9c
/typing_extensions-4.15.0-py3-none-any.whl", hash = "sha256:f0fa19c6845758ab08074a0cfa8b7aebc71c999ca73d62883bc25cc018c
4e548", size = 44614, upload-time = "2025-08-25T13:49:24.86Z" },
]

[[package]]
name = "typing-inspection"
version = "0.4.2"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "typing-extensions" },
]
sdist = { url = "https://files.pythonhosted.org/packages/55/e3/70399cb7dd41c10ac53367ae42139cf4b1ca5f36bb3dc6c9d33acdb4
3655/typing_inspection-0.4.2.tar.gz", hash = "sha256:ba561c48a67c5958007083d386c3295464928b01faa735ab8547c5692e87f464",
size = 75949, upload-time = "2025-10-01T02:14:41.687Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/dc/9b/47798a6c91d8bdb567fe2698fe81e0c6b7cb7ef4d13da4114b41d239f65d
/typing_inspection-0.4.2-py3-none-any.whl", hash = "sha256:4ed1cacbdc298c220f1bd249ed5287caa16f34d44ef4e9c3d0cbad5b5215
45e7", size = 14611, upload-time = "2025-10-01T02:14:40.154Z" },
]

[[package]]
name = "tzdata"
version = "2026.2"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/ba/19/1b9b0e29f30c6d35cb345486df41110984ea67ae69dddbc0e8a10099
9493/tzdata-2026.2.tar.gz", hash = "sha256:9173fde7d80d9018e02a662e168e5a2d04f87c41ea174b139fbef642eda62d10", size = 19
8254, upload-time = "2026-04-24T15:22:08.651Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/ce/e4/dccd7f47c4b64213ac01ef921a1337ee6e30e8c6466046018326977efd95
/tzdata-2026.2-py2.py3-none-any.whl", hash = "sha256:bbe9af844f658da81a5f95019480da3a89415801f6cc966806612cc7169bffe7",
size = 349321, upload-time = "2026-04-24T15:22:05.876Z" },
]

[[package]]
name = "urllib3"
version = "2.7.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/53/0c/06f8b233b8fd13b9e5ee11424ef85419ba0d8ba0b3138bf360be2ff5
6953/urllib3-2.7.0.tar.gz", hash = "sha256:231e0ec3b63ceb14667c67be60f2f2c40a518cb38b03af60abc813da26505f4c", size = 43
3602, upload-time = "2026-05-07T16:13:18.596Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/7f/3e/5db95bcf282c52709639744ca2a8b149baccf648e39c8cc87553df9eae0c
/urllib3-2.7.0-py3-none-any.whl", hash = "sha256:9fb4c81ebbb1ce9531cce37674bbc6f1360472bc18ca9a553ede278ef7276897", siz
e = 131087, upload-time = "2026-05-07T16:13:17.151Z" },
]

[[package]]

```

```

name = "uvicorn"
version = "0.49.0"
source = { registry = "https://pypi.org/simple" }
dependencies = [
 { name = "click" },
 { name = "h11" },
]
sdist = { url = "https://files.pythonhosted.org/packages/c4/1f/fa18009dea8469069cca78a4e877a008ab78f08b064bfc9ab891579077ff/uvicorn-0.49.0.tar.gz", hash = "sha256:ebf4271aa580d9de97f93192d4595176df6e91f9aae919ca73e4fc07df1e66a3", size = 91284, upload-time = "2026-06-03T22:01:30.448Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/88/fa/e1388bbcf24ef3274f45c0c1c7b501fd14971037c1b6ee23610553307497/uvicorn-0.49.0-py3-none-any.whl", hash = "sha256:ba3d14c3ee7e41c6c654c46c9eb489d33213cdd30aa1696eab1374337c13f68f", size = 71376, upload-time = "2026-06-03T22:01:29.037Z" },
]

[[package]]
name = "watchdog"
version = "6.0.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/db/7d/7f3d619e951c88ed75c6037b246ddcf2d322812ee8ea189be89511721d54/watchdog-6.0.0.tar.gz", hash = "sha256:9dddf7c82fda3ae8e24decda1338ede66e1c99883db93711d8fb941eaa2d8c282", size = 131220, upload-time = "2024-11-01T14:07:13.037Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/a9/c7/ca4bf3e518cb57a686b2feb4f55a1892fd9a3dd13f470fca14e00f80ea36/watchdog-6.0.0-py3-none-manylinux2014_aarch64.whl", hash = "sha256:7607498efa04a3542ae3e05e64da8202e58159aa1fa4acddf7678d34a35d4f13", size = 79079, upload-time = "2024-11-01T14:06:59.472Z" },
 { url = "https://files.pythonhosted.org/packages/5c/51/d46dc9332f9a647593c947b4b88e2381c8dfc0942d15b8edc0310fa4abb1/watchdog-6.0.0-py3-none-manylinux2014_armv7l.whl", hash = "sha256:9041567ee8953024c83343288ccc458fd0a2d811d6a0fd68c4c22609e3490379", size = 79078, upload-time = "2024-11-01T14:07:01.431Z" },
 { url = "https://files.pythonhosted.org/packages/d4/57/04edbf5e169cd318d5f07b4766fee38e825d64b6913ca157ca32d1a42267/watchdog-6.0.0-py3-none-manylinux2014_i686.whl", hash = "sha256:82dc3e3143c7e38ec49d61af98d6558288c415eac98486a5c581726e0737c00e", size = 79076, upload-time = "2024-11-01T14:07:02.568Z" },
 { url = "https://files.pythonhosted.org/packages/ab/cc/da8422b300e13cb187d2203f20b9253e91058aaf7db65b74142013478e66/watchdog-6.0.0-py3-none-manylinux2014_ppc64.whl", hash = "sha256:212ac9b8bf1161dc91bd09c048048a95ca3a4c4f5e5d4a7d1b1a7d5752a7f96f", size = 79077, upload-time = "2024-11-01T14:07:03.893Z" },
 { url = "https://files.pythonhosted.org/packages/2c/3b/b8964e04ae1a025c44ba8e4291f86e97fac443bca31de8bd98d3263d2fcf/watchdog-6.0.0-py3-none-manylinux2014_ppc64le.whl", hash = "sha256:e3df4cbb9a450c6d49318f6d14f4bbc80d763fa587ba46ec86f99f9e6876bb26", size = 79078, upload-time = "2024-11-01T14:07:05.189Z" },
 { url = "https://files.pythonhosted.org/packages/62/ae/a696eb424bedff7407801c257d4b1afda455fe40821a2be430e173660e81/watchdog-6.0.0-py3-none-manylinux2014_s390x.whl", hash = "sha256:2cce7cfc2008eb51feb6aab51251fd79b85d9894e98ba847408f662b3395ca3c", size = 79077, upload-time = "2024-11-01T14:07:06.376Z" },
 { url = "https://files.pythonhosted.org/packages/b5/e8/dbf020b4d98251a9860752a094d09a65e1b436ad181faf929983f697048f/watchdog-6.0.0-py3-none-manylinux2014_x86_64.whl", hash = "sha256:20ffe5b202af80ab4266dcd3e91aae72bf2da48c0d33bdb15c66658e685e94e2", size = 79078, upload-time = "2024-11-01T14:07:07.547Z" },
 { url = "https://files.pythonhosted.org/packages/07/f6/d0e5b343768e8bcb4cda79f0f2f55051bf26177ecd5651f84c07567461cf/watchdog-6.0.0-py3-none-win32.whl", hash = "sha256:07df1fdd701c5d4c8e55ef6cf55b8f0120fe1aef7ef39a1c6fc6bc2e606d517a", size = 79065, upload-time = "2024-11-01T14:07:09.525Z" },
 { url = "https://files.pythonhosted.org/packages/db/d9/c495884c6e548fce18a8f40568ff120bc3a4b7b99813081c8ac0c936fa64/watchdog-6.0.0-py3-none-win_amd64.whl", hash = "sha256:cbafb470cf848d93b5d013e2ecb245d4aa1c8fd0504e863ccefa32445359d680", size = 79070, upload-time = "2024-11-01T14:07:10.686Z" },
 { url = "https://files.pythonhosted.org/packages/33/e8/e40370e6d74ddb47f002a32919d91310d6074130fe4e17dabcafc15cbf1/watchdog-6.0.0-py3-none-win_iarm64.whl", hash = "sha256:a1914259fa9e1454315171103c6a30961236f508b9b623eae470268bbcc6a22f", size = 79067, upload-time = "2024-11-01T14:07:11.845Z" },
]

[[package]]
name = "websockets"
version = "16.0"
source = { registry = "https://pypi.org/simple" }
sdist = { url = "https://files.pythonhosted.org/packages/04/24/4b2031d72e840ce4c1ccb255f693b15c334757fc50023e4db9537080b8c4/websockets-16.0.tar.gz", hash = "sha256:5f6261a5e56e8d5c42a4497b364ea24d94d9563e8fbd44e78ac40879c60179b5", size = 179346, upload-time = "2026-01-10T09:23:47.181Z" }
wheels = [
 { url = "https://files.pythonhosted.org/packages/84/7b/bac442e6b96c9d25092695578dda82403c77936104b5682307bd4deb1ad4/websockets-16.0-cp312-cp312-macosx_10_13_universal2.whl", hash = "sha256:71c989cbf3254fbd5e84d3bfff31e4da39c43f884e64f2551d14bb3c186230f00", size = 177365, upload-time = "2026-01-10T09:22:46.787Z" },
 { url = "https://files.pythonhosted.org/packages/b0/fe/136ccece61bd690d9c1f715baaeefd953bb2360134de73519d5df19d29ca/websockets-16.0-cp312-cp312-macosx_10_13_x86_64.whl", hash = "sha256:8b6e209ffee39ff1b6d0fa7bfe6de950c60dfb91b8fcedad17da4ee539121a79", size = 175038, upload-time = "2026-01-10T09:22:47.999Z" },
 { url = "https://files.pythonhosted.org/packages/40/1e/9771421ac2286eaa95b8575b0cb701ae3663abf8b5e1f64f1fd90d0a673/websockets-16.0-cp312-cp312-macosx_11_0_arm64.whl", hash = "sha256:86890e837d61574c92a97496d590968b23c2ef0aeb8a9bc9421d174cd378ae39", size = 175328, upload-time = "2026-01-10T09:22:49.809Z" },
 { url = "https://files.pythonhosted.org/packages/18/29/71729b4671f21e1eaa5d6573031ab810ad2936c8175f03f97f3ff164c802/websockets-16.0-cp312-cp312-manylinux1_x86_64.manylinux_2_28_x86_64.manylinux_2_5_x86_64.whl", hash = "sha256:9b5aca38b67492ef518a8ab76851862488a478602229112c4b0d58d63a7a4d5c", size = 184915, upload-time = "2026-01-10T09:22:51.071Z" },
]

```



{ url = "https://files.pythonhosted.org/packages/97/bb/21c36b7dbbafc85d2d480cd65df02a1dc93bf76d97147605a8e27ff9409d/websockets-16.0-cp312-cp312-manylinux2014\_aarch64.manylinux\_2\_17\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:e0334872c0a37b606418ac52f6ab9cfd17317ac26365f7f65e2d03e2d0d0359f", size = 186152, upload-time = "2026-01-10T09:22:52.224Z" },

{ url = "https://files.pythonhosted.org/packages/4a/34/9bf8df0cf88fa7bfe36678dc7b02970c9a7d5e065a3099292db87b1be2/websockets-16.0-cp312-cp312-musllinux\_1\_2\_aarch64.whl", hash = "sha256:a0b31e0b424cc6b5a04b8838bbaec1688834b2383256688cf47eb97412531da1", size = 185583, upload-time = "2026-01-10T09:22:53.443Z" },

{ url = "https://files.pythonhosted.org/packages/47/88/4dd516068e1a3d6ab3c7c183288404cd424a9a02d585efbac226cb61ff2d/websockets-16.0-cp312-cp312-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:485c49116d0af10ac698623c513c1cc01c9446c058a4e61e3bf6c19dff7335a2", size = 184880, upload-time = "2026-01-10T09:22:55.033Z" },

{ url = "https://files.pythonhosted.org/packages/91/d6/7d4553ad4bf1c0421e1ebd4b18de5d9098383b5caa1d937b63df8d04b565/websockets-16.0-cp312-cp312-win32.whl", hash = "sha256:eaded469f5e5b7294e2bdca0ab06becb6756ea86894a47806456089298813c89", size = 178261, upload-time = "2026-01-10T09:22:56.251Z" },

{ url = "https://files.pythonhosted.org/packages/c3/f0/f3a17365441ed1c27f850a80b2bc680a0fa9505d733fe152fdf5e98c1c0b/websockets-16.0-cp312-cp312-win\_amd64.whl", hash = "sha256:5569417dc80977fc8c2d43a86f78e0a5a22fee17565d78621b6bb264a115d4ea", size = 178693, upload-time = "2026-01-10T09:22:57.478Z" },

{ url = "https://files.pythonhosted.org/packages/cc/9c/baa8456050d1c1b08dd0ec7346026668c6cf145ab4e314d707bb845bf0d/websockets-16.0-cp313-cp313-macosx\_10\_13\_universal2.whl", hash = "sha256:878b336ac47938b474c8f982ac2f27266a540adc3fa4ad74ae96fea9823a02cc9", size = 177364, upload-time = "2026-01-10T09:22:59.333Z" },

{ url = "https://files.pythonhosted.org/packages/7e/0c/8811fc53e9bcff68fe7de2bcbe75116a8d959ac699a3200f4847a8925210/websockets-16.0-cp313-cp313-macosx\_10\_13\_x86\_64.whl", hash = "sha256:52a0fec0e6c8d9a784c2c78276a48a2bdf099e4ccc2a4cad53b27718dbfd0230", size = 175039, upload-time = "2026-01-10T09:23:01.171Z" },

{ url = "https://files.pythonhosted.org/packages/aa/82/39a5f910cb99ec0b59e482971238c845af9220d3ab9fa76dd9162cda9d62/websockets-16.0-cp313-cp313-macosx\_11\_0\_arm64.whl", hash = "sha256:e6578de5b6981005df1860a5e3617f14a6c307e6a71b4ffff8c48fdc50f3ed2c", size = 175323, upload-time = "2026-01-10T09:23:02.341Z" },

{ url = "https://files.pythonhosted.org/packages/bd/28/0a25ee5342eb5d5f297d992a77e56892ecb65e7854c7898fb7d35e9b33bd/websockets-16.0-cp313-cp313-manylinux1\_x86\_64.manylinux\_2\_28\_x86\_64.manylinux\_2\_5\_x86\_64.whl", hash = "sha256:95724e638f0f9c350bb1c2b0a7ad0e83d9cc0c9259f3ea94e40d7b02a2179ae5", size = 184975, upload-time = "2026-01-10T09:23:03.756Z" },

{ url = "https://files.pythonhosted.org/packages/f9/66/27ea52741752f5107c2e41fda05e8395a682a1e11c4e592a809a90c6a506/websockets-16.0-cp313-cp313-manylinux2014\_aarch64.manylinux\_2\_17\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:c0204dc62a89dc9d50d682412c10b3542d748260d743500a85c13cd1ee4bde82", size = 186203, upload-time = "2026-01-10T09:23:05.01Z" },

{ url = "https://files.pythonhosted.org/packages/37/e5/8e32857371406a757816a2b471939d51c463509be73fa538216ea52b792a/websockets-16.0-cp313-cp313-musllinux\_1\_2\_aarch64.whl", hash = "sha256:52ac480f44d32970d66763115ede932f1c5b1312de36df06d6b219f6741eed8", size = 185653, upload-time = "2026-01-10T09:23:06.301Z" },

{ url = "https://files.pythonhosted.org/packages/9b/67/f926bac29882894669368dc73f4da900fcd47955d0a0185d60103df5737/websockets-16.0-cp313-cp313-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:6e5a82b677f8f6f59e8dfc34ec06ca6b5b48bc4fcd3a46acd093694cc2c24d8f", size = 184920, upload-time = "2026-01-10T09:23:07.492Z" },

{ url = "https://files.pythonhosted.org/packages/3c/a1/3d6ccddc125b0a42a311bcd15a7f705d688f73b2a22d8cf1c0875d35d34a/websockets-16.0-cp313-cp313-win32.whl", hash = "sha256:abf050a199613f64c886ea10f38b47770a65154dc37181bfaff70c160f45315a", size = 178255, upload-time = "2026-01-10T09:23:09.245Z" },

{ url = "https://files.pythonhosted.org/packages/6b/ae/90366304d7c2ce80f9b826096a9e9048b4bb760e44d3b873bb272cba696b/websockets-16.0-cp313-cp313-win\_amd64.whl", hash = "sha256:3425ac5cf448801335d6fdc7ae1eb22072055417a96cc6b31b3861f455fbc156", size = 178689, upload-time = "2026-01-10T09:23:10.483Z" },

{ url = "https://files.pythonhosted.org/packages/f3/1d/e88022630271f5bd349ed82417136281931e558d628dd52c4d8621b4a0b2/websockets-16.0-cp314-cp314-macosx\_10\_15\_universal2.whl", hash = "sha256:8cc451a50f2aee53042ac52d2d053d08bf89bcb31ae799cb4487587661c038a0", size = 177406, upload-time = "2026-01-10T09:23:12.178Z" },

{ url = "https://files.pythonhosted.org/packages/f2/78/e63be1bf0724eeb4616efb1ae1c9044f7c3953b7957799abb5915bffd38e/websockets-16.0-cp314-cp314-macosx\_10\_15\_x86\_64.whl", hash = "sha256:daa3b6ff70a9241cf6c7fc9e949d41232d9d72d6fd3522b1a2db4d62487e9904", size = 175085, upload-time = "2026-01-10T09:23:13.511Z" },

{ url = "https://files.pythonhosted.org/packages/bb/f4/d3c9220d818ee955ae390cf319a7c7a467beceb24f05ee7aaaa2414345ba/websockets-16.0-cp314-cp314-macosx\_11\_0\_arm64.whl", hash = "sha256:fd3cb4adb94a2a6e2b7c0d8d05cb94e6f1c81a0cf9dc2694fb65c7e8d94c42e4", size = 175328, upload-time = "2026-01-10T09:23:14.727Z" },

{ url = "https://files.pythonhosted.org/packages/63/bc/d3e208028de777087e6fb2b122051a6ff7bbcca0d6df9d9c2bf1dd869ae9/websockets-16.0-cp314-cp314-manylinux1\_x86\_64.manylinux\_2\_28\_x86\_64.manylinux\_2\_5\_x86\_64.whl", hash = "sha256:781caf5e8eee67f663126490c2f96f4096594cb86b408a703630f9550a8c3e", size = 185044, upload-time = "2026-01-10T09:23:15.939Z" },

{ url = "https://files.pythonhosted.org/packages/ad/6e/9a0927ac24bd33a0a9af834d89e0abc7cfd8e13bed17a86407a66773cc0e/websockets-16.0-cp314-cp314-manylinux2014\_aarch64.manylinux\_2\_17\_aarch64.manylinux\_2\_28\_aarch64.whl", hash = "sha256:caab51a72c51973ca21fa8a18bd8165e1a0183f1ac7066a182ff27107b71e1a4", size = 186279, upload-time = "2026-01-10T09:23:17.148Z" },

{ url = "https://files.pythonhosted.org/packages/b9/ca/bf1c68440d7a868180e11be653c85959502efd3a709323230314fda6e0b3/websockets-16.0-cp314-cp314-musllinux\_1\_2\_aarch64.whl", hash = "sha256:19c4dc84098e523fd63711e563077d39e90ec6702aff4b5d9e344a60cb3c0cb1", size = 185711, upload-time = "2026-01-10T09:23:18.372Z" },

{ url = "https://files.pythonhosted.org/packages/c4/f8/fdc34643a989561f217bb477cbc47a3a07212cbda91c0e4389c43c296ebf/websockets-16.0-cp314-cp314-musllinux\_1\_2\_x86\_64.whl", hash = "sha256:a5e18a238a2b2249c9a9235466b90e96ae4795672598a58772dd806edc7ac6d3", size = 184982, upload-time = "2026-01-10T09:23:19.652Z" },

{ url = "https://files.pythonhosted.org/packages/dd/d1/574fa27e233764dbac9c52730d63fcf2823b16f0856b3329fc6268d6ae4f/websockets-16.0-cp314-cp314-win32.whl", hash = "sha256:a069d734c4a043182729edd3e9f247c3b2a4035415a9172fd0f1b71658a320a8", size = 177915, upload-time = "2026-01-10T09:23:21.458Z" },

{ url = "https://files.pythonhosted.org/packages/8a/f1/ae6b937bf3126b5134ce1f482365fde31a357c784ac51852978768b5eff4/websockets-16.0-cp314-cp314-win\_amd64.whl", hash = "sha256:c0ee0e63f23914732c6d7e0cce24915c48f3f1512ec1d079ed01fc629da b269d", size = 178381, upload-time = "2026-01-10T09:23:22.715Z" },

{ url = "https://files.pythonhosted.org/packages/06/9b/f791d1db48403ef0a27577a6beb37afae94254a8c6f08be4a23e4930bc0/websockets-16.0-cp314-cp314-macosx\_10\_15\_universal2.whl", hash = "sha256:a35539cacc3febb22b8f4d4a99cc79b104226a756aa7400adc722e83b0d03244", size = 177737, upload-time = "2026-01-10T09:23:24.523Z" },

{ url = "https://files.pythonhosted.org/packages/bd/40/53ad02341fa33b3ce489023f635367a4ac98b73570102ad2cdd770dacc9a

```

/websockets-16.0-cp314-cp314t-macosx_10_15_x86_64.whl", hash = "sha256:b784ca5de850f4ce93ec85d3269d24d4c82f22b7212023c9
74c401d4980ebc5e", size = 175268, upload-time = "2026-01-10T09:23:25.781Z" },
 { url = "https://files.pythonhosted.org/packages/74/9b/6158d4e459b984f949dcbbb0c5d270154c7618e11c01029b9bbdb1bb4c4f9
/websockets-16.0-cp314-cp314t-macosx_11_0_arm64.whl", hash = "sha256:569d01a4e7fba956c5ae4fc988f0d4e187900f5497ce46339c
996dbf24f17641", size = 175486, upload-time = "2026-01-10T09:23:27.033Z" },
 { url = "https://files.pythonhosted.org/packages/e5/2d/7583b30208b639c8090206f95073646c2c9ffdf66f44df967981a64f849ad
/websockets-16.0-cp314-cp314t-manylinux1_x86_64.manylinux_2_28_x86_64.manylinux_2_5_x86_64.whl", hash = "sha256:50f23cd
d8343b984957e4077839841146f67a3d31ab0d00e6b824e74c5b2f6e8", size = 185331, upload-time = "2026-01-10T09:23:28.259Z" },
 { url = "https://files.pythonhosted.org/packages/45/b0/cce3784eb519b7b5ad680d14b9673a31ab8dcb7aad8b64d81709d2430aa8
/websockets-16.0-cp314-cp314t-manylinux2014_aarch64.manylinux_2_17_aarch64.manylinux_2_28_aarch64.whl", hash = "sha256:
152284a83a00c59b759697b7f9e9cddf4e3c7861dd0d964b472b70f78f89e80e", size = 186501, upload-time = "2026-01-10T09:23:29.44
9Z" },
 { url = "https://files.pythonhosted.org/packages/19/60/b8ebe4c7e89fb5f6cdf080623c9d92789a53636950f7abacfc33fe2b3135
/websockets-16.0-cp314-cp314t-musllinux_1_2_aarch64.whl", hash = "sha256:bc59589ab64b0022385f429b94697348a6a234e8ce2254
4e3681b2e9331b5944", size = 186062, upload-time = "2026-01-10T09:23:31.368Z" },
 { url = "https://files.pythonhosted.org/packages/88/a8/a080593f89b0138b6cba1b28f8df5673b5506f72879322288b031337c0b8
/websockets-16.0-cp314-cp314t-musllinux_1_2_x86_64.whl", hash = "sha256:32da954ffa2814258030e5a57bc73a3635463238e797c73
75dc8091327434206", size = 185356, upload-time = "2026-01-10T09:23:32.627Z" },
 { url = "https://files.pythonhosted.org/packages/c2/b6/b9afed2afadddaf5ebb2afa801abf4b0868f42f8539bfe4b071b5266c9fe
/websockets-16.0-cp314-cp314t-win32.whl", hash = "sha256:5a4b4cc550cb665dd8a47f868c8d04c8230f857363ad3c9caf7a0c3bf8c61c
a6", size = 178085, upload-time = "2026-01-10T09:23:33.816Z" },
 { url = "https://files.pythonhosted.org/packages/9f/3e/28135a24e384493fa804216b79a6a6759a38cc4ff59118787b9fb693df93
/websockets-16.0-cp314-cp314t-win_amd64.whl", hash = "sha256:b14dc141ed6d2dde437cddb216004bac6a1df0935d79656387bd41632
ba0bbd", size = 178531, upload-time = "2026-01-10T09:23:35.016Z" },
 { url = "https://files.pythonhosted.org/packages/6f/28/258ebab549c2bf3e64d2b0217b973467394a9cea8c42f70418ca2c5d0d2e
/websockets-16.0-py3-none-any.whl", hash = "sha256:1637db62fad1dc833276dded54215f2c7fa46912301a24bd94d45d46a011ceec", s
ize = 171598, upload-time = "2026-01-10T09:23:45.395Z" },
]

```

#### EXPORT SUMMARY

```

Source folder: C:\VSCode\idms-db2-modernizer-master\idms-db2-modernizer-master
Total files found: 115
Text/code files processed: 104
Files skipped: 11

```

#### SKIPPED FILES

```

C:\VSCode\idms-db2-modernizer-master\idms-db2-modernizer-master\data\input\IDMS_DB2_Code_09_07_2026.pdf - Binary file s
kipped
C:\VSCode\idms-db2-modernizer-master\idms-db2-modernizer-master\data\input\IDMS_Schema_Diagram.pdf - Binary file skippe
d
C:\VSCode\idms-db2-modernizer-master\idms-db2-modernizer-master\data\input\IDMS_Schema_Listing.pdf - Binary file skippe
d
C:\VSCode\idms-db2-modernizer-master\idms-db2-modernizer-master\data\input\Retrieval_COBOL_code.pdf - Binary file skippe
d
C:\VSCode\idms-db2-modernizer-master\idms-db2-modernizer-master\data\input\Schema_Listing.pdf - Binary file skipped
C:\VSCode\idms-db2-modernizer-master\idms-db2-modernizer-master\data\input\Update_COBOL_code.pdf - Binary file skipped
C:\VSCode\idms-db2-modernizer-master\idms-db2-modernizer-master\data\output\er_diagram.png - Binary file skipped
C:\VSCode\idms-db2-modernizer-master\idms-db2-modernizer-master\data\temp\diagram_page_0.png - Binary file skipped
C:\VSCode\idms-db2-modernizer-master\idms-db2-modernizer-master\src\idms_modernizer\data\IDMS Diagram.pdf - Binary file
skipped
C:\VSCode\idms-db2-modernizer-master\idms-db2-modernizer-master\src\idms_modernizer\data\IDMS_Schema_Listing.pdf - Bina
ry file skipped
C:\VSCode\idms-db2-modernizer-master\idms-db2-modernizer-master\src\idms_modernizer\data\Retrieval.pdf - Binary file sk
ipped

```