

# Context Window

[CLS] left\_ctx [MASK] right\_ctx [SEP]

### Paragraph-level surprisal

One paragraph as a long string of text. Moving the context windows from the left to the right at each iteration. Example text: "The cat is on the table. But I don't think [...]"

L1w:R1w

# iter 1: [CLS the cat is SEP]  
# iter 2: [CLS cat is on SEP]  
# iter 3: [CLS is on the SEP]  
# iter 4: [CLS on the table SEP]  
# iter 5: [CLS the table . SEP]  
# iter 6: [CLS table . But SEP] . . .

L1w:R2w

# iter 1: [CLS the cat is on SEP]  
# iter 2: [CLS cat is on the SEP]  
# iter 3: [CLS is on the table SEP]  
# iter 4: [CLS on the table . SEP] . . .

L1w:R0w

# iter 1: [CLS the cat SEP]  
# iter 2: [CLS cat is SEP] . . .

L2w:R1w

# iter 1: [CLS the cat is on SEP] . . .

L2w:R2w

# iter 1: [CLS the cat is on the SEP] . . .

L2w:R0w

# iter 1: [CLS the cat is SEP] . . .

### Sentence-level surprisal

One paragraph composed of multiple sentences, one string each. Incremental left context and symmetrical/asymmetrical right context.

L1S:R1w (1 sentence, 1 word right)

# iter 1: [CLS the cat SEP]  
# iter 2: [CLS the cat is SEP]  
# iter 3: [CLS the cat is on SEP]  
# iter 4: [CLS the cat is on the SEP] . . .

L1S:R2w

# iter 1: [CLS the cat is SEP]

```
# iter 2: [CLS the cat is on SEP]
# iter 3: [CLS the cat is on the SEP]
# iter 4: [CLS the cat is on the table SEP] . . .
```

#### L1S:R0w

```
# iter 1: [CLS the SEP]
# iter 2: [CLS the cat SEP]
# iter 3: [CLS the cat is SEP] . . .
```

#### L1S:R1S

```
# iter 1: [CLS the cat is on the table . SEP]
# iter 2: [CLS the cat is on the table . SEP]
# iter 3: [CLS the cat is on the table . SEP]
# iter 4: [CLS the cat is on the table . SEP]
# iter 5: [CLS the cat is on the table . SEP]
# iter 6: [CLS the cat is on the table . SEP]
# iter 7: [CLS the cat is on the table . SEP]
```