

Antenna Datasheet

Product OC (Antenna Only)**:** YC0017EA
Product OC (Antenna + Rectangular EVB)**:** YC0017EAEVBAA
Version: 3.3
Date: 2025-05-25
Status: Released

Product Name: 4G SMT Mount PCB Chip IFA Embedded Antenna
Key Features:
Frequency band: 698–960 MHz, 1710–2690 MHz, 3300–3800 MHz
Efficiency: Up to 74.6 % (On 140 mm × 36 mm EVB)
Dimensions: 25 mm × 7 mm × 3 mm
RoHS & REACH Compliant

Overview

This Quectel embedded 4G SMD antenna covers main 4G LTE bands and is compatible with 3G/2G/LPWA bands. Featuring high efficiency and gain, it is an ideal antenna for a smooth and stable connection with high-efficiency data transmission even under the influence of the device's internal structure. Ground plane dependent, it's designed to be mounted directly to the device host PCB using a conventional PCB reflow process. Supplied tape and reel for high volume pick and place assembly, this SMD antenna can be tuned specifically for the final device environment with a simple PI matching circuit.

Contents

Overview **1**
Contents **2**

1 Specification **3**
1.1. Electrical 3
1.2. Supported Bands 6
1.3. Mechanical & Environmental 8

2 Drawing **9**
2.1. Antenna 9
2.2. Rectangular EVB 10

3 Detailed Performance **11**
3.1. GND Length Dimensions Overview 11
3.2. S-Parameter Test 12
3.2.1. VSWR 12
3.2.2. Return Loss 14
3.3. Radiation Performance Test 16
3.3.1. Efficiency 16
3.3.2. Average Gain 18
3.3.3. Peak Gain 20
3.3.4. 3D & 2D Radiation Pattern 22

4 Schematic Symbol and Pin Definition **26**

5 Transmission Line **27**

6 Recommended PCB Layout **28**

7 Matching Circuit **29**

8 Soldering Temperature **30**

9 Reflow Profile **31**

10 Packaging **32**

Contact Us **34**
Legal Notices **35**
Revision History **37**

1 Specification

Test Condition: Assembled On EVB

1.1. Electrical

Electrical	
Frequency Range	698–960 MHz, 1710–2690 MHz, 3300-3800 MHz
Impedance	50 Ω
Polarization	Linear
Radiation Pattern	Omni-directional

Electrical – Detail									
Band / SPEC	Band	B71	B12 /B13 /B28	B5 /B8 /B26	B1 /B2 /B3	B40	Wi-Fi 2G	B38 /B41	B42 /B48 /B78
	Freq. (MHz)	600–698	700–810	820–960	1710–2170	2300–2400	2400–2500	2500–2690	3300-3800
Max VSWR	On 140 mm × 36 mm EVB	-	3.6	3.2	2.9	4.1	4.1	3.7	3.8
	On 130 mm × 36 mm EVB	-	3.9	3.5	2.6	3.6	3.7	3.6	3.4
	On 110 mm × 36 mm EVB	-	4.3	4.7	3.2	3.1	3.0	2.8	3.4
	On 90 mm × 36 mm EVB	-	5.1	6.2	3.8	4.0	3.8	3.4	3.7
	On 60 mm × 36 mm EVB	-	5.3	5.7	2.3	3.1	3.3	3.3	3.6
	On 40 mm × 36 mm EVB	-	5.1	4.3	4.0	3.7	3.3	2.8	3.4
Max Return Loss (dB)	On 140 mm × 36 mm EVB	-	-5.0	-5.7	-6.2	-4.4	-4.3	-4.8	-4.6
	On 130 mm × 36 mm EVB	-	-4.6	-5.2	-7.1	-5.0	-4.8	-4.9	-5.2
	On 110 mm × 36 mm EVB	-	-4.1	-3.8	-5.7	-5.7	-5.9	-6.5	-5.3
	On 90 mm × 36 mm EVB	-	-3.4	-2.8	-4.6	-4.4	-4.7	-5.3	-4.8
	On 60 mm × 36 mm EVB	-	-3.3	-3.1	-8.0	-5.8	-5.5	-5.5	-5.0
	On 40 mm × 36 mm EVB	-	-3.5	-4.1	-4.4	-4.8	-5.5	-6.4	-5.2
AVG Eff. (%)	On 140 mm × 36 mm EVB	-	50.7	52.8	62.4	41.4	47.9	56.3	53.3
	On 130 mm × 36 mm EVB	-	44.4	51.7	59.3	46.3	50.0	54.2	52.7
	On 110 mm × 36 mm EVB	-	29.5	40.5	50.6	52.2	60.7	60.0	53.0
	On 90 mm × 36 mm EVB	-	17.7	24.9	55.4	41.9	51.5	58.8	53.1
	On 60 mm × 36 mm EVB	-	13.3	17.6	69.3	54.8	60.7	57.5	54.1
	On 40 mm × 36 mm EVB	-	15.7	20.6	47.0	50.5	62.5	65.2	53.7
AVG.AVG Gain (dB)	On 140 mm × 36 mm EVB	-	-3.2	-2.8	-2.1	-3.8	-3.2	-2.5	-2.8
	On 130 mm × 36 mm EVB	-	-3.8	-2.9	-2.3	-3.3	-3.0	-2.7	-2.8
	On 110 mm × 36 mm EVB	-	-5.6	-4.0	-3.0	-2.8	-2.2	-2.2	-2.8
	On 90 mm × 36 mm EVB	-	-7.8	-6.1	-2.6	-3.8	-2.9	-2.3	-2.8
	On 60 mm × 36 mm EVB	-	-9.0	-7.6	-1.6	-2.6	-2.2	-2.4	-2.7
	On 40 mm × 36 mm EVB	-	-8.2	-6.9	-3.3	-3.0	-2.0	-1.9	-2.7
Max Peak	On 140 mm × 36 mm EVB	-	2.4	3.3	2.8	0.9	1.2	1.5	3.6

Gain (dBi)	**On 130 mm × 36 mm EVB**	-	1.8	3.2	3.1	1.2	1.7	2.0	3.7
	On 110 mm × 36 mm EVB	-	0.4	2.0	4.3	1.9	2.1	2.3	3.7
	On 90 mm × 36 mm EVB	-	-1.6	-0.9	4.8	-0.2	0.1	1.9	3.7
	On 60 mm × 36 mm EVB	-	-2.1	-1.1	2.8	0.4	0.6	1.4	3.3
	On 40 mm × 36 mm EVB	-	-0.9	0.2	3.1	0.4	0.8	2.6	3.9
VSWR		**On 140 mm × 36 mm EVB**	≤ 4.1						
		On 130 mm × 36 mm EVB	≤ 3.9						
		On 110 mm × 36 mm EVB	≤ 4.7						
		On 90 mm × 36 mm EVB	≤ 6.2						
		On 60 mm × 36 mm EVB	≤ 5.7						
		On 40 mm × 36 mm EVB	≤ 5.1						
Return Loss		**On 140 mm × 36 mm EVB**	≤ -4.3 dB						
		On 130 mm × 36 mm EVB	≤ -4.6 dB						
		On 110 mm × 36 mm EVB	≤ -3.8 dB						
		On 90 mm × 36 mm EVB	≤ -2.8 dB						
		On 60 mm × 36 mm EVB	≤ -3.1 dB						
		On 40 mm × 36 mm EVB	≤ -3.5 dB						
Peak Gain		**On 140 mm × 36 mm EVB**	≤ 3.6 dBi						
		On 130 mm × 36 mm EVB	≤ 3.7 dBi						
		On 110 mm × 36 mm EVB	≤ 4.3 dBi						
		On 90 mm × 36 mm EVB	≤ 4.8 dBi						
		On 60 mm × 36 mm EVB	≤ 3.3 dBi						
		On 40 mm × 36 mm EVB	≤ 3.9 dBi						

1.2. Supported Bands

5G NR / LTE / LTE-Advanced / WCDMA / HSPA / HSPA+ / GPRS / GSM / NB-IoT				
Band	**Frequency (MHz)**	**Uplink (MHz)**	**Downlink (MHz)**	**Covered**
1	2100	1920–1980	2110–2170	√
2	1900	1850–1910	1930–1990	√
3	1800	1710–1785	1805–1880	√
4	1700	1710–1755	2110–2155	√
5	850	824–849	869–894	√
7	2600	2500–2570	2620–2690	√
8	900	880–915	925–960	√
9	1800	1749.9-1784.9	1844.9-1879.9	√
11	1500	1427.9–1447.9	1475.9–1495.9	-
12	700	699–716	729–746	√
13	700	777–787	746–756	√
14	700	788–798	758–768	√
17	700	704–716	734–746	√
18	850	815–830	860–875	√
19	850	830–845	875–890	√
20	800	832–862	791–821	√
21	1500	1447.9–1462.9	1495.9–1510.9	-
22	3500	3410–3490	3510–3590	√
23	2100	2000–2020	2180–2200	√
24	1600	1626.5–1660.5	1525–1559	-
25	1900	1850–1915	1930–1995	√
26	850	814–849	859–894	√


28	700	703–748	758–803	√
31	450	452.5–457.5	462.5–467.5	-
34	2100	2010–2025		√
38	2600	2570–2620		√
39	1900	1880–1920		√
40	2300	2300–2400		√
41	2500	2496–2690		√
42	3500	3400–3600		√
48	3500	3550–3700		√
66	1700	1710–1780	2110–2200	√
71	600	663–698	617–652	-
74	1500	1427–1470	1475–1518	-
77	3500	3300–4200		√
78	3500	3300–3800		√
79	4500	4400–5000		-

1.3. Mechanical & Environmental

Mechanical	
Antenna Size	25 mm × 7 mm × 3 mm
Material & Color	FR4 & Black
Antenna Weight	Typ. 1.05 g
Mounting Type	SMD
Recommended EVB Size	140 mm × 36 mm × 0.8 mm
Environmental	
Operation Temperature	-40 °C to +85 °C
Storage Temperature	-40 °C to +85 °C
RoHS & REACH Compliant	Yes

2 Drawing


2.1. Antenna



All dimensions are in mm

Name	Material	Brand	QTY	Model
Antenna	FR4 3.0 t	Quectel	1	YC0017EA
PCB	FR4 0.8 t	Quectel	1	YC0017EAEVB
0 Ω	Ceramics	Murata	1	
10 nH	Ceramics	Murata	1	LQG15HS10NJ02
2.4 pF	Ceramics	Murata	1	GCM1555C1H2R4BA16
1.5 nH	Ceramics	Murata	1	LQG15HS1N5S02
SMA Female Connector	Brass	Quectel	1	-

2.2. Rectangular EVB




All dimensions are in mm.

3 Detailed Performance


3.1. GND Length Dimensions Overview

The performance of the low bands is highly dependent on the ground plane length. The host PCB ground needs to be as long as the device allows. Reducing the GND directly relates to the performance of the low bands. As shown below you can see the effect of the different shapes vs the efficiency.



3.2. S-Parameter Test


3.2.1. VSWR



VSWR

Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
On 140 mm × 36 mm EVB	-	-	3.0	2.7	3.1	2.8	-	1.8	1.7	1.8
On 130 mm × 36 mm EVB	-	-	3.2	3.0	3.4	2.9	-	2.1	1.9	2.1
On 110 mm × 36 mm EVB	-	-	3.6	3.5	4.7	4.0	-	2.3	2.1	2.3
On 90 mm × 36 mm EVB	-	-	4.4	4.4	6.1	5.4	-	1.8	1.6	1.7
On 60 mm × 36 mm EVB	-	-	4.6	4.0	5.5	5.4	-	1.4	1.5	1.8
On 40 mm × 36 mm EVB	-	-	4.4	3.2	4.2	4.1	-	2.2	2.1	2.4
Frequency (MHz)	**1950**	**2140**	**2350**	**2450**	**2600**	**2690**	**3300**	**3800**	**5500**	**6000**
On 140 mm × 36 mm EVB	1.8	2.7	4.0	4.0	2.7	1.7	1.8	3.8	-	-
On 130 mm × 36 mm EVB	2.1	2.4	3.4	3.7	2.9	1.9	1.9	3.4	-	-
On 110 mm × 36 mm EVB	2.7	3.2	3.1	2.9	2.5	2.1	1.9	3.4	-	-
On 90 mm × 36 mm EVB	2.1	3.6	4.0	3.6	2.5	1.6	1.8	3.7	-	-
On 60 mm × 36 mm EVB	1.9	2.2	3.0	3.3	2.9	2.0	1.8	3.6	-	-
On 40 mm × 36 mm EVB	2.8	4.0	3.5	3.1	2.2	1.8	1.8	3.4	-	-

3.2.2. Return Loss




Return Loss (dB)

Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
On 140 mm × 36 mm EVB	-	-	-6.1	-6.9	-5.7	-6.6	-	-10.9	-11.6	-11.1
On 130 mm × 36 mm EVB	-	-	-5.5	-6.1	-5.2	-6.3	-	-9.2	-9.9	-9.0
On 110 mm × 36 mm EVB	-	-	-5.0	-5.2	-3.8	-4.4	-	-8.3	-8.9	-8.1
On 90 mm × 36 mm EVB	-	-	-4.1	-4.0	-2.9	-3.3	-	-11.2	-12.5	-11.6
On 60 mm × 36 mm EVB	-	-	-3.8	-4.5	-3.2	-3.3	-	-15.0	-14.3	-11.0
On 40 mm × 36 mm EVB	-	-	-4.0	-5.6	-4.2	-4.3	-	-8.5	-8.8	-7.6
Frequency (MHz)	**1950**	**2140**	**2350**	**2450**	**2600**	**2690**	**3300**	**3800**	**5500**	**6000**
On 140 mm × 36 mm EVB	-11.1	-6.8	-4.5	-4.4	-6.8	-12.1	-10.9	-4.6	-	-
On 130 mm × 36 mm EVB	-8.8	-7.6	-5.3	-4.8	-6.2	-9.9	-10.2	-5.2	-	-
On 110 mm × 36 mm EVB	-6.7	-5.7	-5.8	-6.2	-7.2	-9.2	-9.8	-5.3	-	-
On 90 mm × 36 mm EVB	-8.9	-4.9	-4.4	-4.9	-7.3	-12.3	-10.8	-4.8	-	-
On 60 mm × 36 mm EVB	-10.3	-8.6	-6.0	-5.5	-6.3	-9.5	-10.8	-5.0	-	-
On 40 mm × 36 mm EVB	-6.4	-4.4	-5.2	-5.8	-8.5	-11.0	-11.0	-5.2	-	-

3.3. Radiation Performance Test


3.3.1. Efficiency



Efficiency (%)

Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
On 140 mm × 36 mm EVB	-	-	29.1	58.5	50.8	52.5	-	66.3	66.5	66.6
On 130 mm × 36 mm EVB	-	-	23.9	53.8	50.6	54.7	-	60.6	60.6	59.7
On 110 mm × 36 mm EVB	-	-	14.6	37.7	39.9	49.2	-	58.9	58.3	51.8
On 90 mm × 36 mm EVB	-	-	8.8	22.7	24.3	31.6	-	68.1	68.2	62.1
On 60 mm × 36 mm EVB	-	-	7.8	16.2	17.2	22.2	-	74.5	75.5	71.4
On 40 mm × 36 mm EVB	-	-	10.0	18.8	20.0	26.3	-	52.3	52.9	46.7
Frequency (MHz)	**1950**	**2140**	**2350**	**2450**	**2600**	**2690**	**3300**	**3800**	**5500**	**6000**
On 140 mm × 36 mm EVB	62.6	54.2	40.9	48.3	55.2	59.5	60.0	43.7	-	-
On 130 mm × 36 mm EVB	56.9	58.9	45.9	50.4	52.5	57.0	61.2	42.3	-	-
On 110 mm × 36 mm EVB	46.1	48.3	52.0	61.8	58.2	58.6	60.5	42.3	-	-
On 90 mm × 36 mm EVB	52.0	43.9	41.4	52.3	58.4	59.4	60.7	44.0	-	-
On 60 mm × 36 mm EVB	65.0	64.5	53.8	62.2	55.5	56.4	60.1	44.7	-	-
On 40 mm × 36 mm EVB	42.4	45.6	49.9	64.0	64.4	62.6	62.1	43.9	-	-


3.3.2. Average Gain



Average Gain (dB)

Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
On 140 mm × 36 mm EVB	-	-	-5.4	-2.3	-2.9	-2.8	-	-1.8	-1.8	-1.8
On 130 mm × 36 mm EVB	-	-	-6.2	-2.7	-3.0	-2.6	-	-2.2	-2.2	-2.2
On 110 mm × 36 mm EVB	-	-	-8.4	-4.2	-4.0	-3.1	-	-2.3	-2.3	-2.9
On 90 mm × 36 mm EVB	-	-	-10.6	-6.4	-6.1	-5.0	-	-1.7	-1.7	-2.1
On 60 mm × 36 mm EVB	-	-	-11.1	-7.9	-7.6	-6.5	-	-1.3	-1.2	-1.5
On 40 mm × 36 mm EVB	-	-	-10.0	-7.3	-7.0	-5.8	-	-2.8	-2.8	-3.3
Frequency (MHz)	**1950**	**2140**	**2350**	**2450**	**2600**	**2690**	**3300**	**3800**	**5500**	**6000**
On 140 mm × 36 mm EVB	-2.0	-2.7	-3.9	-3.2	-2.6	-2.3	-2.2	-3.6	-	-
On 130 mm × 36 mm EVB	-2.5	-2.3	-3.4	-3.0	-2.8	-2.4	-2.1	-3.7	-	-
On 110 mm × 36 mm EVB	-3.4	-3.2	-2.8	-2.1	-2.4	-2.3	-2.2	-3.7	-	-
On 90 mm × 36 mm EVB	-2.8	-3.6	-3.8	-2.8	-2.3	-2.3	-2.2	-3.6	-	-
On 60 mm × 36 mm EVB	-1.9	-1.9	-2.7	-2.1	-2.6	-2.5	-2.2	-3.5	-	-
On 40 mm × 36 mm EVB	-3.7	-3.4	-3.0	-1.9	-1.9	-2.0	-2.1	-3.6	-	-

3.3.3. Peak Gain




Peak Gain (dBi)

















Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
On 140 mm × 36 mm EVB	-	-	-3.8	2.6	2.6	3.3	-	2.1	1.5	2.5
On 130 mm × 36 mm EVB	-	-	-4.6	1.9	2.3	3.2	-	3.1	2.4	2.4
On 110 mm × 36 mm EVB	-	-	-6.7	0.4	0.5	2.0	-	4.3	3.8	1.9
On 90 mm × 36 mm EVB	-	-	-8.9	-1.6	-2.2	-0.9	-	4.8	4.4	3.5
On 60 mm × 36 mm EVB	-	-	-7.4	-2.2	-2.9	-1.1	-	2.8	2.5	2.0
On 40 mm × 36 mm EVB	-	-	-6.0	-1.0	-1.5	0.2	-	3.1	2.8	1.9
Frequency (MHz)	**1950**	**2140**	**2350**	**2450**	**2600**	**2690**	**3300**	**3800**	**5500**	**6000**
On 140 mm × 36 mm EVB	2.3	1.3	0.5	1.2	0.5	1.4	3.4	1.9	-	-
On 130 mm × 36 mm EVB	1.9	1.8	0.5	1.7	0.7	1.8	3.5	2.2	-	-
On 110 mm × 36 mm EVB	1.0	1.1	0.9	2.1	2.1	2.2	3.3	1.9	-	-
On 90 mm × 36 mm EVB	3.2	0.4	-0.9	0.1	1.3	1.6	3.4	1.9	-	-
On 60 mm × 36 mm EVB	2.0	1.3	-0.5	0.5	0.2	1.3	2.7	2.2	-	-
On 40 mm × 36 mm EVB	1.7	0.2	-0.5	0.7	2.3	2.4	3.5	2.1	-	-

















3.3.4. 3D & 2D Radiation Pattern













- Test Status: Assembled On EVB
- Test Chamber: GL-S-1



- **On 140 mm × 36 mm EVB**

710 MHz		830 MHz	
			
			
900 MHz		1740 MHz	
			
			


1880 MHz		1950 MHz	
			
			
2140 MHz		2350 MHz	
			
			

2450 MHz		2600 MHz	
			
			
3600 MHz			
			
			

4 Schematic Symbol and Pin Definition

- The pin assignment for the antenna is as follows.
- The circuit symbol for the antenna is shown below. The antenna has 6 pins, only one of which works. All other pins are for mechanical strength.

Pin	Description
1, 2, 3, 4, 5	Not used (Mechanical only)
6	Feed



5 Transmission Line


The characteristic impedance of all transmission lines shall be designed as 50 Ω.

- The length of the transmission lines should be kept as short as possible.
- Any other part of the RF system, such as transceiver, power amplifiers, etc., shall also be designed with an impedance of 50 Ω.

Once the material for the PCB has been chosen (PCB thickness and dielectric constant), a coplanar transmission line can easily be designed using any of the commercial software packages for transmission line design. For the chosen PCB thickness, copper thickness and substrate dielectric constant, the program will calculate the appropriate transmission line width and gaps on either side of the track so the characteristic impedance of the coplanar transmission is 50 Ω.

6 Recommended PCB Layout


The host PCB must be designed using the PCB footprint shown with the correct clearances. An example of the PCB layout shows the antenna footprint. Please note this clearance area is critical to the performance of the antenna and must be applied through all layers of the PCB.



All dimensions are in mm.

7 Matching Circuit

Demo Board Top View




	S1	P1	S2	S3
Default Matching	0 Ohm	10 nH	2.4 pF	1.5 nH
Tolerance	-	±5 %	±5 %	±5 %



8 Soldering Temperature




Phase	Profile Features	PB-Free Assembly
RAMP-UP	Avg. Ramp-up Rate (Tsmax to Tp)	3 °C / second (Max.)
PREHEAT	Temperature Min (Tsmin) Temperature Max (Tsmax) Time (tsmin to tsmax)	150 °C 190 °C 110 seconds (Max.)
REFLOW	Temperature (TL) Total Time above TL (tl)	220 °C 90 seconds (Max.)
PEAK	Temperature (Tp)	230–250 °C
RAMP-DOWN	Rate	-1 °C / second (Max.)

9 Reflow Profile



10 Packaging

Step	Packaging Picture / 2D Picture	Description
1		Reel
2		(1600 Antenna Products /vacuum bag) Put one packet of desiccant in each roll, and then pack them in vacuum bag.
3		(1600 Antenna Products / inner box) The reel tape is vacuum-sealed within the inner box. Pizza Box Size (mm): 350 (L) × 350 (W) × 70 (H)

4		(4 Inner Boxes / Carton Box) (6400 Antennas / Carton Box) Estimated quantity Products that cannot fill the entire carton box are packed in a suitable size carton box. Carton Size: L × W × H = 370 × 370 × 295 mm
5		**Position for Attaching Labels** ① Carton Label ② Quality Label
6		**Sealing Cartons** H-shaped sealing cartons
Note	The initial packaging method described above is for reference only, and the final actual packaging method shall be subject to the actual shipping packaging.	

Contact Us

At Quectel, our aim is to provide timely and comprehensive services to our customers. If you require any assistance, please contact our headquarters:

Quectel Wireless Solutions Co., Ltd.
No. 8 Waipojing Road, Sijing Town, Songjiang District, Shanghai 201601, China
Tel: +86 21 5108 6236
Email: info@quectel.com

Or our local offices. For more information, please visit:
https://www.quectel.com/contact/.

For technical support, or to report documentation errors, please visit:
https://www.quectel.com/tech-support/.
Or email us at: support@quectel.com.

Legal Notices

We provide this document to support your product design. You are required to design your products based on the specifications and parameters set forth herein. You agree that you are responsible for using independent analysis and evaluation in designing intended products, and we provide reference designs for illustrative purposes only. Before using any hardware, software or service guided by this document, please read this notice carefully. Even though we employ commercially reasonable efforts to provide the best possible experience, you hereby acknowledge and agree that this document and related services hereunder are provided to you on an “as available” basis. You acknowledge and agree that we may add to, amend, or restate this document at any time at our sole discretion without any prior notice to you, and such additions, amendments, or restatements shall be binding upon you.

Use and Disclosure Restrictions

License Agreements

The recipient of any hardware, software, materials, or documentation provided by us shall keep such content confidential, unless expressly authorized by us. The recipient shall not disclose, access, or use any part of the received content for any purpose other than the execution and implementation of the intended project.

Copyright

Our and third-party products hereunder may contain copyrighted materials, including but not limited to protected content, hardware, software, and documentation owned by us or applicable third parties. Unless prior written consent is obtained, you shall not access, use, or disclose any documents or information provided by us, nor shall you copy, reproduce, republish, display, translate, distribute, merge, modify, or create derivative works from any such copyrighted materials. We and the applicable third party retain exclusive rights to all copyrighted materials. No license to any patents, copyrights, trademarks, or service marks shall be granted or transferred. For the avoidance of doubt, no form of purchase shall be construed as granting any license beyond a normal, non-exclusive, royalty-free license to use the product. We reserve the right to pursue legal action against any violation of confidentiality obligations, unauthorized use, or any other unlawful or malicious use of the aforementioned documents and information.

Trademarks

Unless otherwise expressly provided, nothing in this document shall be construed as conferring any rights to use any trademark, trade name, name, abbreviation, or counterfeit thereof owned by us or any third party in advertising, publicity, or any other contexts.

Third-Party Rights

You understand that this document may refer to hardware, software, and/or documentation owned by one or more third parties (“third-party materials”). Use of such third-party materials is subject to all applicable restrictions and obligations set forth herein.

We make no warranty or representation, either express or implied, regarding the third-party materials, including but not limited to any implied or statutory, warranties of merchantability or fitness for a particular purpose, quiet enjoyment, system integration, information accuracy, and non-infringement of any third-party intellectual property rights with regard to the licensed technology or use thereof. Nothing herein constitutes a representation or warranty by us to either develop, enhance, modify, distribute, market, sell, offer for sale, or otherwise maintain production of any our products or any other hardware, software, device, tool, information, or product. We moreover disclaim any and all warranties arising from the course of dealing, course of performance, or usage of trade.

Privacy Policy

To enable product functionality, certain device data may be uploaded to our or third-party servers, including those operated by carriers, chipset suppliers, or servers designated by you. We strictly comply with applicable laws and regulations and will retain, use, disclose, or otherwise process relevant data solely for the purpose of enabling product functionality, or as permitted by applicable laws. Before interacting with any third party regarding data exchange, please be informed of and understand their privacy and data security policies.

Disclaimer

a) We shall not be liable for any damages resulting from failure to comply with applicable operational or design specifications.
b) We shall bear no liability for any inaccuracies or omissions in this document, nor for any damages arising from the use of the information contained herein.
c) While we make every effort to ensure the integrity, accuracy, and timeliness of the features and functions under development, errors or omissions may nevertheless occur. Unless otherwise provided in a valid written agreement, we make no warranties of any kind, express, implied, or statutory, and disclaim all liability for any loss or damage arising from the use of any features or functions under development, to the maximum extent permitted by law, regardless of whether such loss or damage is foreseeable.
d) We assume no legal responsibility for the accessibility, safety, accuracy, availability, legality, or completeness of any information, content, advertising, commercial offers, products, services, or materials on third-party websites or third-party resources.

Copyright © Quectel Wireless Solutions Co., Ltd. 2026. All rights reserved.

Revision History

Version	Date	Author	Note
-	2023-06-12	Ezail Tan/ Lucky Feng/ David Liu Vinnie Liu	Creation of the document
1.0	2023-06-12	Ezail Tan/ Lucky Feng/ David Liu Vinnie Liu	First official release
2.0	2023-09-07	Ezail Tan/ Lucky Feng/ David Liu/ Vinnie Liu	Updated the template and all test data.
3.0	2024-03-29	Jaden Feng/ Vinnie Liu	Numerous changes were made to this document. It should be read in its entirety.
3.1	2025-03-06	Allow Xu	1. Deleted the notes (Chapter 1.2). 2. Updated the packaging (Chapter 10).
3.2	2026-04-13	Mayes Li	Updated the pin description (Chapter 7).
3.3	2026-05-25	Caius Zhang	Updated the packaging (Chapter 10).



www.quectel.com