

Antenna Datasheet

Product OC: YECA002L1AH
Version: 1.2
Date: 2025-04-24
Status: Released

Product Name: 4G Adhesive Mount Whip Monopole External Antenna
Key Features:
Frequency Band: 698–960 MHz, 1710–2690 MHz
Dimensions: Φ 30 mm × 83.2 mm
Efficiency: Up to 64.5 % (MP)
RoHS and REACH Compliant
IP67

Overview

The YECA001L2AH is a 4G external antenna measuring Φ 30 mm × 83.2 mm. This ultra-wide-band 4G antenna provides broad coverage from 698–960 MHz, 1710–2690 MHz whilst offering backward-compatibility to support 3G and 2G networks as well as LTE Cat-M and narrowband IoT (NB-IoT). The antenna is available with connection via cable lengths from 300–5,000 mm, terminated with SMA Male (Center pin) connector. This low profile, adhesive mount omni-directional antenna, ideal for applications where the antenna is required to be discrete, is easy to install with maximum durability assured thanks to its IP67 rated and ASA enclosure. It is compatible with Quectel's 4G Series modules.

It allows constant and reliable transmission and reception due to its omni-directional gain across all frequency bands. The YECA001L2AH is designed as a monopole antenna, which offers high efficiency in all working bands. It is a perfect antenna product for customers that desire highest performance. This high-efficiency, high-gain omni-directional antenna is ideally suited for high-speed video, real-time streaming, high-capacity MIMO networks and public transportation. It is suitable for outdoor and indoor applications due to its robust UV resistant ASA enclosure, which meets UL 746C f1.

- **Typical applications include:**

✓ High speed video
✓ Real-time streaming
✓ High-capacity MIMO networks
✓ Public transportation

Quectel provides comprehensive antenna design support such as simulation, testing and manufacturing for custom antenna solutions to meet your specific application needs. We have regional R & D centers to offer quick response to meet your requirements. Please contact our sales & FAEs if you have any requests.

Contents

Overview **1**
Contents **2**

1 Specification **3**
1.1. Electrical 3
1.2. Supported Bands 5
1.3. Mechanical & Environmental 7

2 Drawing **8**

3 Detailed Performance **9**
3.1. S-Parameter Test 9
3.1.1. VSWR 9
3.1.2. Return Loss 10
3.2. Radiation Performance Test 11
3.2.1. Efficiency 11
3.2.2. Average Gain 12
3.2.3. Peak Gain 13
3.2.4. 3D & 2D Radiation Pattern 14
3.2.4.1. Test Condition: Free Space 14
3.2.4.2. Test Condition: On 300 mm × 300 mm Metal Plane 18

4 Packaging **22**

Contact Us **24**
Legal Notices **25**
Revision History **27**

1 Specification

Test Condition: Free Space & On 300 mm × 300 mm Metal Plane

1.1. Electrical

Electrical	
Frequency Range	698–960 MHz, 1710–2690 MHz
Impedance	50 Ω
Polarization	Linear
Radiation Pattern	Omni-directional

Electrical – Detail												
Band / SPEC	Band	B71	B12 /B13 /B28	B5 /B8 /B26	n74 /n75 /n76	B1 /B2 /B3	B40	Wi-Fi 2G	B38 /B41	B42 /B48 /n77	n79	Wi-Fi 5G
	Freq. (MHz)	600–700	700–810	820–960	1420–1520	1700–2170	2300–2400	2400–2500	2500–2690	3300–4200	4400–5000	5150–5850
Max. VSWR	FS	-	3.7	3.2	-	2.1	2.0	2.0	1.9	-	-	-
	MP	-	3.4	3.8	-	2.1	1.5	1.8	2.4	-	-	-
Max. Return Loss (dB)	FS	-	-4.9	-5.5	-	-9.0	-9.4	-9.6	-9.9	-	-	-
	MP	-	-5.2	-4.6	-	-9.0	-13.4	-10.5	-7.7	-	-	-
AVG Eff. (%)	FS	-	47.3	49.5	-	53.9	50.2	46.6	46.9	-	-	-
	MP	-	44.8	49.8	-	53.6	58.2	52.6	45.6	-	-	-
AVG AVG Gain (dB)	FS	-	-3.3	-3.1	-	-2.7	-3.0	-3.3	-3.3	-	-	-
	MP	-	-3.5	-3.0	-	-2.7	-2.4	-2.8	-3.4	-	-	-
Max. Peak Gain (dBi)	FS	-	1.7	1.3	-	4.3	3.3	3.1	2.4	-	-	-
	MP	-	1.3	2.3	-	3.7	4.4	3.2	1.9	-	-	-
VSWR	FS	≤ 3.7										
	MP	≤ 3.8										
Return Loss	FS	≤ -4.9 dB										
	MP	≤ -4.6 dB										
Peak Gain	FS	≤ 4.3 dBi										
	MP	≤ 4.4 dBi										

- **FS: Free Space**
- **MP: On 300 mm × 300 mm Metal Plane**

1.2. Supported Bands


5G NR/LTE/LTE-Advanced/WCDMA/HSPA/HSPA+/GPRS/GSM/NB-IoT					
Band	**Frequency (MHz)**	**Uplink (MHz)**	**Downlink (MHz)**	**FS**	**MP**
1	2100	1920–1980	2110–2170	√	√
2	1900	1850–1910	1930–1990	√	√
3	1800	1710–1785	1805–1880	√	√
4	1700	1710–1755	2110–2155	√	√
5	850	824–849	869–894	√	√
7	2600	2500–2570	2620–2690	√	√
8	900	880–915	925–960	√	√
9	1800	1749.9–1784.9	1844.9–1879.9	√	√
11	1500	1427.9–1447.9	1475.9–1495.9	-	-
12	700	699–716	729–746	√	√
13	700	777–787	746–756	√	√
14	700	788–798	758–768	√	√
17	700	704–716	734–746	√	√
18	850	815–830	860–875	√	√
19	850	830–845	875–890	√	√
20	800	832–862	791–821	√	√
21	1500	1447.9–1462.9	1495.9–1510.9	-	-
22	3500	3410–3490	3510–3590	-	-
23	2100	2000–2020	2180–2200	√	√
24	1600	1626.5–1660.5	1525–1559	-	-
25	1900	1850–1915	1930–1995	√	√
26	850	814–849	859–894	√	√

5G NR/LTE/LTE-Advanced/WCDMA/HSPA/HSPA+/GPRS/GSM/NB-IoT					
Band	**Frequency (MHz)**	**Uplink (MHz)**	**Downlink (MHz)**	**FS**	**MP**
28	700	703–748	758–803	√	√
31	450	452.5–457.5	462.5–467.5	-	-
34	2100	2010–2025		√	√
38	2600	2570–2620		√	√
39	1900	1880–1920		√	√
40	2300	2300–2400		√	√
41	2500	2496–2690		√	√
42	3500	3400–3600		-	-
48	3500	3550–3700		-	-
66	1700	1710–1780	2110–2200	√	√
71	600	663–698	617–652	-	-
74	1500	1427–1470	1475–1518	-	-
77	3500	3300–4200		-	-
78	3500	3300–3800		-	-
79	4500	4400–5000		-	-

1.3. Mechanical & Environmental

Mechanical		
Antenna Dimensions		Φ 30 mm × 83.2 mm
Material & Color		ASA & Black
Cable Type & Color & Length		RG174LL & Black & 1000 mm
Connector Type		SMA Male (Center pin)
Weight		Typ. 24.8 g
Mounting Type	**YECA002L1AH**	Adhesive
	YECM002L1AH	Magnetic
Environmental		
Operation Temperature		-40 °C to +85 °C
Storage Temperature		-40 °C to +85 °C
Ingress Protection (IP) Rating		IP67
Housing UV Resistant		UL 746C f1
RoHS and REACH Compliant		Yes

2 Drawing




Unit: mm

3 Detailed Performance

3.1. S-Parameter Test


3.1.1. VSWR



VSWR

Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
FS	-	-	3.4	3.2	2.1	2.2	-	1.3	1.1	1.6
MP	-	-	2.6	3.8	2.3	2.5	-	1.3	1.2	2.0
Frequency (MHz)	**1950**	**2140**	**2350**	**2450**	**2600**	**2690**	**4700**	**5000**	**5500**	**6000**
FS	1.7	2.0	2.0	2.0	1.6	1.7	-	-	-	-
MP	2.1	1.9	1.4	1.8	2.0	2.0	-	-	-	-

3.1.2. Return Loss




Return Loss (dB)

Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
FS	-	-	-5.3	-5.6	-9.2	-8.3	-	-17.4	-25.6	-13.2
MP	-	-	-7.2	-4.6	-8.0	-7.5	-	-16.8	-19.2	-9.8
Frequency (MHz)	**1950**	**2140**	**2350**	**2450**	**2600**	**2690**	**4700**	**5000**	**5500**	**6000**
FS	-11.6	-9.3	-9.4	-9.7	-12.7	-11.5	-	-	-	-
MP	-9.2	-10.4	-14.9	-10.8	-9.7	-9.5	-	-	-	-

3.2. Radiation Performance Test


3.2.1. Efficiency



Efficiency (%)

Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
FS	-	-	45.3	47.0	53.3	51.3	-	60.6	61.0	51.7
MP	-	-	47.0	41.3	54.3	60.0	-	62.9	62.6	49.4
Frequency (MHz)	**1950**	**2140**	**2350**	**2450**	**2600**	**2690**	**4700**	**5000**	**5500**	**6000**
FS	50.8	46.5	52.4	45.7	48.5	44.7	-	-	-	-
MP	48.8	51.6	60.1	52.5	45.6	43.8	-	-	-	-


3.2.2. Average Gain



Average Gain (dB)

Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
FS	-	-	-3.4	-3.3	-2.7	-2.9	-	-2.2	-2.1	-2.9
MP	-	-	-3.3	-3.8	-2.7	-2.2	-	-2.0	-2.0	-3.1
Frequency (MHz)	**1950**	**2140**	**2350**	**2450**	**2600**	**2690**	**4700**	**5000**	**5500**	**6000**
FS	-2.9	-3.3	-2.8	-3.4	-3.1	-3.5	-	-	-	-
MP	-3.1	-2.9	-2.2	-2.8	-3.4	-3.6	-	-	-	-

3.2.3. Peak Gain




Peak Gain (dBi)

















Frequency (MHz)	600	630	710	830	900	960	1440	1710	1740	1880
FS	-	-	0.2	0.1	0.2	1.3	-	1.3	2.1	2.0
MP	-	-	1.0	-0.1	0.7	2.3	-	1.5	1.6	1.4
Frequency (MHz)	**1950**	**2140**	**2350**	**2450**	**2600**	**2690**	**4700**	**5000**	**5500**	**6000**
FS	3.2	2.9	3.2	2.4	1.4	1.2	-	-	-	-
MP	2.0	3.2	4.0	2.0	1.0	1.7	-	-	-	-

















3.2.4. 3D & 2D Radiation Pattern









3.2.4.1. Test Condition: Free Space

- Test Chamber: FS-S-1




710 MHz		830 MHz	
			
			
900 MHz		1740 MHz	
			
			

1880 MHz		1950 MHz	
			
			
2140 MHz		2350 MHz	
			
			

















2450 MHz		2600 MHz	
			
			

















3.2.4.2. Test Condition: On 300 mm × 300 mm Metal Plane









- Test Chamber: FS-S-1







On 300 mm × 300 mm Metal Plane


710 MHz		830 MHz	
			
			
900 MHz		1740 MHz	
			
			

1880 MHz		1950 MHz	
			
			
2140 MHz		2350 MHz	
			
			

2450 MHz		2600 MHz	
			
			

4 Packaging

Step	Packaging Picture / 2D Picture	Description
1		1 antenna product in a small PE bag. (1 Antenna / Small PE Bag)
2		40 antenna products in a big PE bag. (40 Antennas / Big PE Bag)
3		(6 Big PE Bags / Carton Box) (240 Antennas / Carton Box) Estimated quantity Products that cannot fill the entire carton box are packed in a suitable size carton box. Carton Size: L × W × H = 370 × 370 × 295 mm
4		**Position for Attaching Labels** ① Carton Label ② Quality Label

5		**Sealing Cartons** H-shaped sealing cartons
Note	The initial packaging method described above is for reference only, and the final actual packaging method shall be subject to the actual shipping packaging.	

Contact Us

At Quectel, our aim is to provide timely and comprehensive services to our customers. If you require any assistance, please contact our headquarters:

Quectel Wireless Solutions Co., Ltd.
No. 8 Waipojing Road, Sijing Town, Songjiang District, Shanghai 201601, China
Tel: +86 21 5108 6236
Email: info@quectel.com

Or our local offices. For more information, please visit:
https://www.quectel.com/contact/.

For technical support, or to report documentation errors, please visit:
https://www.quectel.com/tech-support/.
Or email us at: support@quectel.com.

Legal Notices

We provide this document to support your product design. You are required to design your products based on the specifications and parameters set forth herein. You agree that you are responsible for using independent analysis and evaluation in designing intended products, and we provide reference designs for illustrative purposes only. Before using any hardware, software or service guided by this document, please read this notice carefully. Even though we employ commercially reasonable efforts to provide the best possible experience, you hereby acknowledge and agree that this document and related services hereunder are provided to you on an “as available” basis. You acknowledge and agree that we may add to, amend, or restate this document at any time at our sole discretion without any prior notice to you, and such additions, amendments, or restatements shall be binding upon you.

Use and Disclosure Restrictions

License Agreements

The recipient of any hardware, software, materials, or documentation provided by us shall keep such content confidential, unless expressly authorized by us. The recipient shall not disclose, access, or use any part of the received content for any purpose other than the execution and implementation of the intended project.

Copyright

Our and third-party products hereunder may contain copyrighted materials, including but not limited to protected content, hardware, software, and documentation owned by us or applicable third parties. Unless prior written consent is obtained, you shall not access, use, or disclose any documents or information provided by us, nor shall you copy, reproduce, republish, display, translate, distribute, merge, modify, or create derivative works from any such copyrighted materials. We and the applicable third party retain exclusive rights to all copyrighted materials. No license to any patents, copyrights, trademarks, or service marks shall be granted or transferred. For the avoidance of doubt, no form of purchase shall be construed as granting any license beyond a normal, non-exclusive, royalty-free license to use the product. We reserve the right to pursue legal action against any violation of confidentiality obligations, unauthorized use, or any other unlawful or malicious use of the aforementioned documents and information.

Trademarks

Unless otherwise expressly provided, nothing in this document shall be construed as conferring any rights to use any trademark, trade name, name, abbreviation, or counterfeit thereof owned by us or any third party in advertising, publicity, or any other contexts.

Third-Party Rights

You understand that this document may refer to hardware, software, and/or documentation owned by one or more third parties (“third-party materials”). Use of such third-party materials is subject to all applicable restrictions and obligations set forth herein.

We make no warranty or representation, either express or implied, regarding the third-party materials, including but not limited to any implied or statutory, warranties of merchantability or fitness for a particular purpose, quiet enjoyment, system integration, information accuracy, and non-infringement of any third-party intellectual property rights with regard to the licensed technology or use thereof. Nothing herein constitutes a representation or warranty by us to either develop, enhance, modify, distribute, market, sell, offer for sale, or otherwise maintain production of any our products or any other hardware, software, device, tool, information, or product. We moreover disclaim any and all warranties arising from the course of dealing, course of performance, or usage of trade.

Privacy Policy

To enable product functionality, certain device data may be uploaded to our or third-party servers, including those operated by carriers, chipset suppliers, or servers designated by you. We strictly comply with applicable laws and regulations and will retain, use, disclose, or otherwise process relevant data solely for the purpose of enabling product functionality, or as permitted by applicable laws. Before interacting with any third party regarding data exchange, please be informed of and understand their privacy and data security policies.

Disclaimer

a) We acknowledge no liability for any injury or damage arising from the reliance upon the information.
b) We shall bear no liability resulting from any inaccuracies or omissions, or from the use of the information contained herein.
c) While we have made every effort to ensure that the functions and features under development are free from errors, it is possible that they could contain errors, inaccuracies, and omissions. Unless otherwise provided by valid agreement, we make no warranties of any kind, either implied or express, and exclude all liability for any loss or damage suffered in connection with the use of features and functions under development, to the maximum extent permitted by law, regardless of whether such loss or damage may have been foreseeable.
d) We are not responsible for the accessibility, safety, accuracy, availability, legality, or completeness of information, advertising, commercial offers, products, services, and materials on third-party websites and third-party resources.

Copyright © Quectel Wireless Solutions Co., Ltd. 2025. All rights reserved.

Revision History

Version	Date	Author	Note
-	2024-08-31	Mordecai Liu/ Jason Long/ David Liu/ Rainey Liao	Creation of the document
1.0	2024-08-31	Mordecai Liu/ Jason Long/ David Liu/ Rainey Liao	First official release
1.1	2025-03-11	Rainey Liao	Updated the starting frequency to 698 MHz (Homepage, Overview and Chapter 1.1).
1.2	2025-04-24	Riva Ren/ Rainey Liao/	1. Updated the antenna image (Cover page). 2. Updated the packaging (Chapter 4).



www.quectel.com