

hackeRnews CHEAT SHEET

An R wrapper for the official Hacker News API



Best stories

`get_best_stories(max_items)`

Hacker News best stories

`get_best_stories_ids()`

Hacker News best stories ids

Latest stories

`get_latest_ask_stories(max_items)`

Hacker News latest ask stories

`get_latest_ask_stories_ids()`

Hacker News latest ask stories ids

`get_latest_job_stories(max_items)`

Hacker News latest job stories

`get_latest_job_stories_ids()`

Hacker News latest job stories ids

`get_latest_show_stories(max_items)`

Hacker News latest show stories

`get_latest_show_stories_ids()`

Hacker News latest show stories ids

Profile

`get_updates()`

Hacker News updated profiles

`get_user_by_username(username)`

Get Hacker News user

username

Username of the user, that should be
retrieved

New stories

`get_new_stories(max_items)`

Hacker News newest stories

`get_new_stories_ids()`

Hacker News newest stories ids

Top stories

`get_top_stories(max_items)`

Hacker News top stories

`get_top_stories_ids()`

Hacker News top stories ids

Examples

`%>%`

Example for pipeR

param

Parameter description

`df %>% plot(col = "red")`

Items

`get_item_by_id(id)`

Get Hacker News by Id

id

Id of the item, that should be retrieved

`get_item_by_ids(ids)`

Get Hacker News by ids

ids

List of ids.

`get_max_item_id()`

Hacker News item largest id