

configure

hostname hq-rtr.sirius-exam.org

username net_admin

password P@ssw0rd

privilege 15

exit

domain lookup enable

domain nameserver 192.168.100.2

domain nameserver 77.88.8.7

domain name sirius-exam.org

security passwords default-expired

ip ssh server

ntp enable

ntp broadcast-client enable

interface gigabitethernet 1/0/3

ip firewall disable

ip address 172.16.1.2/28

exit

interface gigabitethernet 1/0/2

ip firewall disable

ip address 192.168.100.1/27

exit

interface gigabitethernet 1/0/1

ip firewall disable

ip address 192.168.200.1/28

exit

key-chain auth_ospf

key 1

key-string ascii-text P@ssw0rd

exit

exit

tunnel gre 1

ttl 64

local address 172.16.1.2

remote address 172.16.2.2

```
ip address 10.10.10.1/30
ip firewall disable
ip ospf instance 1
ip ospf authentication key-chain auth_ospf
ip ospf authentication algorithm md5
ip ospf
enable
exit
```

```
router ospf 1
router-id 1.1.1.1
area 0.0.0.0
network 192.168.100.0/27
network 192.168.200.0/28
enable
exit
enable
```

```
object-group network LOCAL_NET
ip address-range 192.168.100.2-192.168.100.30
ip address-range 192.168.200.2-192.168.200.14
exit
object-group network PUBLIC_POOL
ip address-range 172.16.1.3-172.16.1.7
exit
```

```
interface gigabitethernet 1/0/3
ip nat proxy-arp PUBLIC_POOL
exit
```

```
nat source
pool TRANSLATE_ADDRESS
ip address-range 172.16.1.3-172.16.1.7
exit
ruleset SNAT
to interface gigabitethernet 1/0/3
rule 1
match source-address object-group network LOCAL_NET
action source-nat pool TRANSLATE_ADDRESS
enable
exit
exit
exit
```

```
ip dhcp-server
ip dhcp-server pool CLI_POOL
```

```
network 192.168.200.0/28
domain-name sirius-exam.org
address-range 192.168.200.2-192.168.200.14
default-router 192.168.200.1
dns-server 192.168.100.2
exit
exit

object-group service HTTP_PORT
port-range 8080
exit
object-group service SSH_PORT
port-range 2026
exit

nat destination
pool HQ_WEB_POOL
ip address 192.168.100.2
ip port 80
exit
pool HQ_SSH_POOL
ip address 192.168.100.2
ip port 2026
exit
ruleset DNAT
from default
rule 10
match destination-address address-range 172.16.1.2
match protocol tcp
match destination-port object-group HTTP_PORT
action destination-nat pool HQ_WEB_POOL
enable
exit
rule 20
match destination-address address-range 172.16.1.2
match protocol tcp
match destination-port object-group SSH_PORT
action destination-nat pool HQ_SSH_POOL
enable
exit
exit
exit

ip route 0.0.0.0/0 172.16.1.1 200
```

commit
confirm