

Navigate through complex lesions effortlessly with Siroflex Curve. Offering a range of dimensions to accommodate your diverse patient requirements.

Diameter (mm)	Stent Length (mm)											
	8	12	16	20	24	28	32	36	40	44	48	52
2.00	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
2.25	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
2.50	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
2.75	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
3.00	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
3.50	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
4.00	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
4.50	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

Device Technical Specification

Design	Open Cell Design	
Stent Material	L605 Cobalt Chromium	
Stent Design	Open Cell Design with Valley-to-Valley S Connectors (V2V S)	
Stent Strut Width	WavFlo Struts: 65 ± 10 µm and Valley-to-Valley "S" Connectors: 55 ± 10 µm	
Guide Wire Compatibility (Max)	0.014"(0.36 mm)	
Polymers	Bio-degradable Polymers	
Stent Strut thickness	60 ± 10 µm	
Guiding Catheter (Inner Diameter)	5 Fr Compatible	
Crossing Profile	1mm (≤ 1mm for 3.0 diameter)	
Radial Strength (Force/Axial Length)	1.50 N/mm	
Foreshortening	Nearly Zero	
Flexibility	Excellent	
Drug	Sirolimus	

Over-expansion Limit

Nominal Diameter (mm)	2.00 - 2.25 - 2.50 - 2.75 - 3.00	3.50 - 4.00 - 4.50
Number of Crowns	6	8
Post-Dilatation limit (mm)	4.00	5.50

Flex your Way into
Complex Lesions with
SIROFLEX PLUS⁺
Sirolimus Eluting Coronary Stent System



An Innovative **Sirolimus Stent**

with Extreme Flexibility for Complex Lesions

Proprietary V2V S-connectors

- Valley-to-valley long 'S'Connectors
- For higher Flexibility, Deliverability, Radial Strength (Force/Axial Length) and Conformability
- Lowering stent dislodgement force to minimum 6N in 12 mm stents

Proprietary WavFlo Struts

- DES with thin struts up to 60 μm
- Enhancing trackability, crossability, and radial force, while reducing the risk of restenosis and thrombosis

Perfect drug coating ensures systematic and sustained drug release to the target lesion

- Coated with Sirolimus drug-biodegradable polymers mix using highly automated process

Spacious open cell design

- Helps navigate tortuous and serpentine vessels
- Providing high flexibility
- Providing enhanced side branch access

Enhanced deliverability with 60 μm ultrathin struts

- Preventing stent thrombosis and restenosis
- Reducing deep wall trauma

Perfectly engineered smooth edges

- Preventing artery injury or dissection

