

# Project 1

Due date **19.th of September, 2016 - 23:59**

Øyvind B. Svendsen, Magnus Christopher Bareid  
un: oyvinbsv, magnucb

September 18, 2016

## Abstract

The aim of this project is to get familiar with various vector and matrix operations, from dynamic memory allocation to the usage of programs in the library package of the course.

The student was invited to use either brute force-algorithms to calculate linear algebra, or to use a set of recommended linear algebra packages through Armadillo that simplify the syntax of linear algebra. Additionally, dynamic memory handling is expected.

The students will showcase necessary algebra to perform the tasks given to them, and explain the way said algebra is implemented into algorithms. In essence, we're asked to simplify a linear second-order differential equation from the form of the Poisson equation, seen as

$$\nabla^2 \Phi = -4\pi\rho(\mathbf{r})$$

into a one-dimensional form bounded by Dirichlet boundary conditions.

$$-u''(x) = f(x)$$

so that discretized linear algebra may be committed unto the equation, yielding a number of numerical methods for acquiring the underivated function  $u(x)$ .

---

## Contents

|          |                                |          |
|----------|--------------------------------|----------|
| <b>1</b> | <b>Introduction</b>            | <b>2</b> |
| <b>2</b> | <b>Problem</b>                 | <b>2</b> |
| <b>3</b> | <b>Method</b>                  | <b>2</b> |
| <b>4</b> | <b>Explanation of programs</b> | <b>5</b> |
| 4.1      | main.cpp . . . . .             | 5        |
| <b>5</b> | <b>Appendix - Program list</b> | <b>6</b> |

# 1 Introduction

The production of this document will inevitably familiarize its authors with the programming language C++, and to this end mathematical groundwork must first be elaborated to translate a Poisson equation from continuous calculus form, into a discretized numerical form.

The Poisson equation is rewritten to a simplified form, for which a real solution is given, with which we will compare our numerical approximation to the real solution.

## 2 Problem

## 3 Method

Reviewing the Poisson equation:

$$\begin{aligned} \nabla^2 \Phi &= -4\pi\rho(\mathbf{r}), \text{ which is simplified one-dimensionally by } \Phi(r) = \phi(r)/r \\ \Rightarrow \frac{d^2\phi}{dr^2} &= -4\pi r\rho(r), \text{ which is further simplified by these substitutions:} \\ r &\rightarrow x, \\ \phi &\rightarrow u, \\ 4\pi r\rho(r) &\rightarrow f, \quad \text{which produces the simplified form} \end{aligned}$$

$$\begin{aligned} -u''(x) &= f(x), \quad \text{for which we assume that } f(x) = 100e^{-10x}, \\ \Rightarrow u(x) &= 1 - (1 - e^{-10})x - e^{-10x}, \text{ with bounds: } x \in [0, 1], u(0) = u(1) = 0 \end{aligned} \quad (1)$$

From here on and out, the methods for finding  $u(x)$  numerically will be deduced.

To more easily comprehend the syntax from a programming viewpoint, one may refer to the each discretized representation of  $x$  and  $u$ ; we know the span of  $x$ , and therefore we may divide it up into appropriate chunks. Each of these  $x_i$  will yield a corresponding  $u_i$ .

We may calculate each discrete  $x_i$  by the form  $x_i = ih$  in the interval from  $x_0 = 0$  to  $x_n = 1$  as it is linearly increasing, meaning we use  $n$  points in our approximation, yielding the step length  $h = 1/n$ . Of course, this also yields discretized representation of  $u(x_i) = u_i$ .

Through Euler's teachings on discretized numerical derivation methods, a second derivative may be constructed through the form of

$$\begin{aligned} \left(\frac{\partial u}{\partial x}\right)_{fw} &= \frac{u_{i+1} - u_i}{h} & \left(\frac{\partial u}{\partial x}\right)_{bw} &= \frac{u_i - u_{i-1}}{h} \\ \left(\frac{\partial}{\partial x}\right)^2 [u_i] &= \left(\frac{\partial}{\partial x_{bw}}\right) \left(\frac{\partial}{\partial x}\right)_{fw} [u_i] = \left(\frac{\partial}{\partial x}\right)_{bw} \left(\frac{u_{i+1} - u_i}{h}\right) = \frac{\left(\frac{\partial u_{i+1}}{\partial x}\right)_{bw} - \left(\frac{\partial u_i}{\partial x}\right)_{bw}}{h} \\ &= \frac{\left(\frac{\partial}{\partial x}\right)^2 [u_i]}{h^2} = \frac{u_{i+1} - 2u_i + u_{i-1}}{h^2} \\ -u''(x) &= -\frac{u_{i+1} - 2u_i + u_{i-1}}{h^2} = \frac{-u_{i+1} + 2u_i - u_{i-1}}{h^2} = f_i, \quad \text{for } i = 1, \dots, n \end{aligned} \quad (2)$$

The discretized problem can now be solved as a linear algebraic problem. Looking closer at

the discretized problem:

$$\begin{aligned}
-u''(x_i) &= \frac{-u_{i+1} + 2u_i - u_{i-1}}{h^2} = f_i \\
&\Rightarrow -u_{i+1} + 2u_i - u_{i-1} = h^2 f_i = y_i \\
i = 1 : \quad &-u_2 + 2u_1 - u_0 = y_1 \\
i = 2 : \quad &-u_3 + 2u_2 - u_1 = y_2 \\
i = 3 : \quad &-u_4 + 2u_3 - u_2 = y_3 \\
&\vdots \\
i = n : \quad &-u_{n+1} + 2u_n - u_{n-1} = y_n
\end{aligned}$$

This is very similar to a linear algebra / matrix problem and we will test a system of equations to match.

$$A\vec{u} = \vec{y}$$

$$\begin{bmatrix} 2 & -1 & 0 & \dots \\ -1 & 2 & -1 & \dots \\ 0 & -1 & 2 & \ddots \\ \vdots & \vdots & \ddots & \ddots \end{bmatrix} \begin{bmatrix} u_0 \\ u_1 \\ \vdots \\ u_{n+1} \end{bmatrix} = \begin{bmatrix} y_0 \\ y_1 \\ \vdots \\ y_{n+1} \end{bmatrix}$$

This matrix equation will not be valid for the first and last values of  $\vec{y}$  because they would require elements of  $\vec{u}$  that are not defined;  $u_{-1}$  and  $u_{n+2}$ . Given this constraint we see that the matrix-equation gives the same set of equations that we require.

$$\begin{aligned}
i = 1 : \quad &-u_2 + 2u_1 - u_0 = y_1 \\
i = 2 : \quad &-u_3 + 2u_2 - u_1 = y_2 \\
i = 3 : \quad &-u_4 + 2u_3 - u_2 = y_3 \\
&\vdots \\
i = n : \quad &-u_{n+1} + 2u_n - u_{n-1} = y_n
\end{aligned}$$

The coefficients from each of these terms and their corresponding value of  $u(x)$  may be represented by a tridiagonal matrix multiplication:

$$-\frac{d^2}{dx^2}u(x) = f(x) \quad \Rightarrow \quad \hat{\mathbf{A}}\hat{\mathbf{u}} = h^2\hat{\mathbf{f}} \quad \Rightarrow \quad \begin{pmatrix} 2 & -1 & 0 & \dots & \dots & 0 \\ -1 & 2 & -1 & 0 & & \vdots \\ 0 & -1 & 2 & \ddots & \ddots & \vdots \\ \vdots & 0 & \ddots & \ddots & \ddots & 0 \\ \vdots & & \ddots & \ddots & \ddots & -1 \\ 0 & \dots & \dots & 0 & -1 & 2 \end{pmatrix} \begin{pmatrix} u_0 \\ \vdots \\ \vdots \\ \vdots \\ \vdots \\ u_n \end{pmatrix} = h^2 \begin{pmatrix} f_0 \\ \vdots \\ \vdots \\ \vdots \\ \vdots \\ f_n \end{pmatrix}$$

The double derivation is now reduced to a discretized linear algebra operation by way of matrix multiplication. In our case,  $f(x)$  is known to us, and the only unknowns are the  $u(x)$ 's from  $u_1 \rightarrow u_{n-1}$ , as per the Dirichlet boundary conditions, which allows the use of the algorithm from equation .

The original problem at hand (the Poisson equation) has now been "degraded" to a simpler, linear algebra problem.

Solving a tridiagonal matrix-problem like this is done by gaussian elimination of the tridiagonal matrix A, and thereby solving  $\vec{u}$  for the resulting diagonal-matrix.

Firstly the tridiagonal matrix A is rewritten to a series of three vectors  $\vec{a}$ ,  $\vec{b}$ , and  $\vec{c}$  that will represent a general tridiagonal matrix. This will make it easier to include other problems of a general form later.

The tridiagonal matrix A (with the vector y) now looks like:

$$\begin{bmatrix} b_1 & c_1 & 0 & 0 & \dots & y_1 \\ a_2 & b_2 & c_2 & 0 & & y_2 \\ 0 & a_3 & b_3 & c_3 & & \vdots \\ 0 & 0 & a_4 & b_4 & \ddots & \\ \vdots & & & \ddots & \ddots & c_{n-1} & y_{n-1} \\ & & & a_n & b_n & y_n \end{bmatrix}$$

The gaussian elimination can be split into two parts; a forward substitution where the matrix-elements  $a_i$  are set to zero, and a backward substitution where the vector-elements  $u_i$  are calculated from known values.

starting with row 2, a row-operation is performed to maintain the validity of the system. The goal is to remove element  $a_2$  from the row. This is done by subtracting row 1 (multiplied with some constant 'k' from row 2.

$$\begin{aligned} \tilde{Row}_2 &= Row_2 - k \times Row_1 \\ \begin{bmatrix} b_1 & c_1 & 0 & 0 & \dots & y_1 \\ \tilde{a}_2 & \tilde{b}_2 & \tilde{c}_2 & 0 & & \tilde{y}_2 \\ 0 & a_3 & b_3 & c_3 & & y_3 \\ 0 & 0 & a_4 & b_4 & \ddots & \vdots \\ \vdots & & & \ddots & \ddots & c_{n-1} & y_{n-1} \\ & & & a_n & b_n & y_n \end{bmatrix} \end{aligned} \quad \begin{aligned} \text{where } k \text{ is determined by } \tilde{a}_2 = 0 &\Rightarrow k = \frac{a_2}{b_1} \\ \tilde{b}_2 &= b_2 - \frac{a_2}{b_1} c_1 \\ \tilde{c}_2 &= c_2 - \frac{a_2}{b_1} \times 0 = c_2 \\ \tilde{y}_2 &= y_2 - \frac{a_2}{b_1} y_1 \end{aligned}$$

Moving on to row 3, and performing a similar operation:

$$\begin{aligned} \tilde{Row}_3 &= Row_3 - k \times Row_2 \\ \begin{bmatrix} b_1 & c_1 & 0 & 0 & \dots & y_1 \\ 0 & \tilde{b}_2 & \tilde{c}_2 & 0 & & \tilde{y}_2 \\ 0 & \tilde{a}_3 & \tilde{b}_3 & \tilde{c}_3 & & \tilde{y}_3 \\ 0 & 0 & a_4 & b_4 & \ddots & \vdots \\ \vdots & & & \ddots & \ddots & c_{n-1} & y_{n-1} \\ & & & a_n & b_n & y_n \end{bmatrix} \end{aligned} \quad \begin{aligned} \text{where } k \text{ is determined by } \tilde{a}_3 = 0 &\Rightarrow k = \frac{a_3}{\tilde{b}_2} \\ \tilde{b}_3 &= b_3 - \frac{a_3}{\tilde{b}_2} c_2 \\ \tilde{c}_3 &= c_3 - \frac{a_3}{\tilde{b}_2} \times 0 = c_3 \\ \tilde{y}_3 &= y_3 - \frac{a_3}{\tilde{b}_2} \tilde{y}_2 \end{aligned}$$

By repeating this step a pattern emerges, and an algorithm can be found:

$$\begin{aligned}\tilde{b}_{i+1} &= b_{i+1} - \frac{a_{i+1}}{\tilde{b}_i} c_i \\ \tilde{y}_{i+1} &= y_{i+1} - \frac{a_{i+1}}{\tilde{b}_i} \tilde{y}_i \\ i &= 1, 2, \dots, n-1\end{aligned}$$

After this procedure, the tridiagonal matrix A is transformed into an uppertriangular matrix. This sort of set of equations can be solved for u, since the last equation has one unknown and the other equations has only two unknowns.

$$\begin{bmatrix} b_1 & c_1 & 0 & 0 & \dots & y_1 \\ 0 & \tilde{b}_2 & c_2 & 0 & & \tilde{y}_2 \\ 0 & 0 & \tilde{b}_3 & \tilde{c}_3 & & \tilde{y}_3 \\ 0 & 0 & a_4 & b_4 & \ddots & \vdots \\ \vdots & & & \ddots & \ddots & c_{n-1} & y_{n-1} \\ & & & a_n & b_n & y_n \end{bmatrix}$$

## 4 Explanation of programs

### 4.1 main.cpp

The main-program is a `c++`

---

## 5 Appendix - Program list

This is the code used in this assignment. Anything that was done by hand has been implemented into this pdf, above. `plot_stuff.py`

```
1 import pylab as pyl
2 import os
3 import sys
4
5 curdir = os.getcwd()
6 data_dict = {} #dictionary of files
7 n_range_LU = pyl.logspace(1,3,num=3)
8 n_range_tridiag = pyl.logspace(1, 4,num=7)
9
10 for n in n_range_tridiag:
11     #loop through different n's
12     with open(curdir+"/data/dderiv_u_c+_n%d_tridiag.dat"%(int(n)), 'r') as infile:
13         full_file = infile.read() #read entire file into text
14         lines = full_file.split('\n') #separate by EOL-characters
15         lines = lines[:-1] #remove last line (empty line)
16         keys = lines.pop(0).split(',') #use top line as keys for dictionary
17         dict_of_content = {}
18         for i, key in zip(range(len(keys)), keys): #loop over keys, create approp. arrays
19             dict_of_content[key] = [] #empty list
20             for j in range(len(lines)): #loop through the remaining lines of the data-set
21                 line = lines[j].split(',') #split the line into string-lists
22                 word = line[i] # append the correct value to the correct list with the correct key
23                 try:
24                     word = float(word) #check if value can be float
25                 except ValueError: #word cannot be turned to number
26                     print word
27                     sys.exit("There is something wrong with your data-file \n'%s' cannot be turned to numbers"%word)
28                 dict_of_content[key].append(word)
29             data_dict["n=%d"%n] = dict_of_content #add complete dictionary to dictionary of files
30
31 def u_exact(x):
32     u = 1.0 - (1.0 - pyl.exp(-10.0))*x - pyl.exp(-10.0*x)
33     return u
34
35 def compare_methods(n):
36     """
37     For a specific length 'n' compare both methods
38     with the exact function.
39     """
40     x = pyl.array(data_dict["n=%d"%n]["x"])
41     gen = pyl.array(data_dict["n=%d"%n]["u_gen"])
42     spec = pyl.array(data_dict["n=%d"%n]["u_spec"])
43     exact = u_exact(x)
44     pyl.figure("compare methods")
45     pyl.grid(True)
46     pyl.hold(True)
47     pyl.xlabel("x")
48     pyl.ylabel("u(x)")
49     pyl.title("function u for three different methods (n=%d)"%n)
50
51     pyl.plot(x, exact, 'k-', label="exact")
52     pyl.plot(x, gen, 'b--', label="general tridiagonal")
53     pyl.plot(x, spec, 'g-', label="specific tridiagonal")
54     pyl.legend(loc='best', prop={'size':9})
55     pyl.savefig(curdir+"/img/compare_methods_n%d.png"%n)
```

```

56
57 def compare_approx_n(n_range=[10,100,1000], approx_string="general"):
58     """
59     For all n's available, plot the general approximation and
60     exact solution
61     """
62     if approx_string == "general":
63         approx_key = "u_gen"
64     elif approx_string == "specific":
65         approx_key = "u_spec"
66     else:
67         sys.exit("In function 'compare_approx_n', wrong argument 'approx_string'")
68     pyl.figure("compare %s"%approx_string)
69     pyl.grid(True)
70     pyl.hold(True)
71     pyl.xlabel("x")
72     pyl.ylabel("u(x)")
73     pyl.title("approximation by %s tridiagonal method"%approx_string)
74
75     for n in n_range:
76         n = int(n)
77         x = pyl.array(data_dict["n=%d"%n]["x"])
78         u_approx = pyl.array(data_dict["n=%d"%n][approx_key])
79         pyl.plot(x, u_approx, '--', label="n=%1.1e"%n)
80
81     x = pyl.linspace(0,1,1001)
82     exact = u_exact(x)
83     pyl.plot(x, exact, '-', label="exact")
84     pyl.legend(loc='best', prop={'size':9})
85     pyl.savefig(curdir+"/img/compare_%s_n_n%d.png"%(approx_string,n))
86
87 def epsilon_plots(n_range=[10,100,1000]):
88     eps_max = pyl.zeros(len(n_range))
89     h = pyl.zeros(len(n_range))
90     for i, n in enumerate(n_range):
91         x = pyl.array(data_dict["n=%d"%n]["x"])
92         u = u_exact(x)
93         v = pyl.array(data_dict["n=%d"%n]["u_gen"])
94         #calculate eps_max by finding max of |v_i - u_i|
95         max_diff_uv = 0; jmax = 0;
96         for j in range(n):
97             diff_uv = abs(v[j]-u[j])
98             if diff_uv > max_diff_uv:
99                 max_diff_uv = diff_uv
100                 jmax = j
101         if jmax == 0 or jmax == n-1:
102             sys.exit("There is an error in calculating the max_epsilon")
103         eps_max[i] = pyl.log10(max_diff_uv/float(abs(u[jmax])))
104         h[i] = pyl.log10(1.0/(n+1))
105     pyl.figure("epsilon")
106     pyl.grid(True)
107     pyl.hold(True)
108     pyl.xlabel(r"\log_{10}(h)")
109     pyl.ylabel(r"$\epsilon = \log_{10}(\frac{u_{approx}-e_{exact}}{u_{exact}})$")
110     pyl.title("log-plot of epsilon against step-length h")
111     pyl.plot(h, eps_max, 'ko')
112     pyl.legend(loc='best')
113     pyl.savefig(curdir+"/img/epsilon.png")
114
115 #make plots

```

```
116 compare_methods(n=10)
117 #compare_approx_n(approx_string="general")
118 #compare_approx_n(approx_string="specific")
119 #epsilon_plots()
120 pyl.show()
```