

PC Hardware Details

Resumo

- **Motherboard:** ROG STRIX B760-G GAMING WIFI
- **Sistema:** System Product Name (SKU)
- **CPU:** 13th Gen Intel(R) Core(TM) i5-13500
- **Memória total:** 64 GiB (2 × 32 GiB DIMM, 4800 MHz)
- **Discos:** 256GB KINGSTON SKC6002 (`/dev/sda`), 2TB ST2000DM008-2UB1 (`/dev/sdb`)
- **Rede:** Ethernet `I226-V` (eno1), WiFi `AX211` (wlp0s20f3)
- **GPU (integrada):** AlderLake-S GT1

Detalhes principais

CPU

- Modelo: 13th Gen Intel(R) Core(TM) i5-13500
- CPUs reportados: 20
- Cores por socket: 14
- Threads por core: 2
- Frequência (máx): 4800 MHz, (mín): 800 MHz

Memória

- Total: 64 GiB System Memory
- DIMMs instaladas:
 - 32 GiB DIMM Synchronous 4800 MHz (slot /0/c/1)
 - 32 GiB DIMM Synchronous 4800 MHz (slot /0/c/3)

Armazenamento

- `/dev/sda` – 256GB KINGSTON SKC6002
 - `/dev/sda1` – 511 MiB Windows FAT
 - `/dev/sda2` – 237 GiB EXT4
 - `/dev/sda3` – 976 MiB Linux swap
- `/dev/sdb` – 2TB ST2000DM008-2UB1
 - `/dev/sdb1` – 1074 MiB Windows FAT
 - `/dev/sdb2` – 2 GiB EXT4
 - `/dev/sdb3` – 1859 GiB EFI partition

Rede e Conectividade

- Ethernet: `Intel Ethernet Controller I226-V` (eno1)
- WiFi: `Raptor Lake-S PCH CNVi WiFi` (AX211) – interface `wlp0s20f3`
- USB: Raptor Lake USB 3.2 Gen 2x2 XHCI

Áudio

- Raptor Lake High Definition Audio Controller (card0)

Saída bruta (raw)

O bloco abaixo contém a saída original usada para compilar este resumo.

...

H/W path	Device	Class	Description
=====			
		system	System Product Name (SKU)
/0		bus	ROG STRIX B760-G GAMING WIFI

/0/0		memory	64KiB BIOS
/0/c		memory	64GiB System Memory
/0/c/0		memory	[empty]
/0/c/1		memory	32GiB DIMM Synchronous 4800 MHz (0.2 ns)
/0/c/2		memory	[empty]
/0/c/3		memory	32GiB DIMM Synchronous 4800 MHz (0.2 ns)
/0/1b		memory	288KiB L1 cache
/0/1c		memory	192KiB L1 cache
/0/1d		memory	7680KiB L2 cache
/0/1e		memory	24MiB L3 cache
/0/1f		memory	256KiB L1 cache
/0/20		memory	512KiB L1 cache
/0/21		memory	4MiB L2 cache
/0/22		memory	24MiB L3 cache
/0/23		processor	13th Gen Intel(R) Core(TM) i5-13500
/0/100		bridge	Intel Corporation
/0/100/2	/dev/fb0	display	AlderLake-S GT1
/0/100/a		generic	Platform Monitoring Technology
/0/100/e		storage	Volume Management Device NVMe RAID
Controller			
/0/100/14		bus	Raptor Lake USB 3.2 Gen 2x2 (20 Gb/s) XHCI
Host Controller			
/0/100/14/0	usb1	bus	xHCI Host Controller
/0/100/14/0/2		input	AURA LED Controller
/0/100/14/0/a		bus	ASM107x
/0/100/14/0/b		bus	USB2.0 Hub
/0/100/14/0/e		communication	AX211 Bluetooth
/0/100/14/1	usb2	bus	xHCI Host Controller
/0/100/14/1/9		bus	ASM107x
/0/100/14.2		memory	RAM memory
/0/100/14.3	wlp0s20f3	network	Raptor Lake-S PCH CNVi WiFi
/0/100/15		bus	Raptor Lake Serial IO I2C Host Controller #0
/0/100/15.1		bus	Raptor Lake Serial IO I2C Host Controller #1
/0/100/15.2		bus	Raptor Lake Serial IO I2C Host Controller #2
/0/100/16		communication	Raptor Lake CSME HECI #1
/0/100/17	scsi4	storage	Raptor Lake SATA AHCI Controller
/0/100/17/0	/dev/sda	disk	256GB KINGSTON SKC6002
/0/100/17/0/1	/dev/sda1	volume	511MiB Windows FAT volume
/0/100/17/0/2	/dev/sda2	volume	237GiB EXT4 volume
/0/100/17/0/3	/dev/sda3	volume	976MiB Linux swap volume
/0/100/17/1	/dev/sdb	disk	2TB ST2000DM008-2UB1
/0/100/17/1/1	/dev/sdb1	volume	1074MiB Windows FAT volume
/0/100/17/1/2	/dev/sdb2	volume	2GiB EXT4 volume
/0/100/17/1/3	/dev/sdb3	volume	1859GiB EFI partition
...			(output truncated)
...			

Para ver a saída completa, consulte o ficheiro original `PC\_hardware\_details.txt`.