

MAgPIE Workshop 2025

First steps: Update model settings

Debbora Leip

leip@pik-potsdam.de

June 17th, 2025



Last tutorial...

... you learned how to start a default MAgPIE run


But what are the default settings and how can you change them?

➔ The MAgPIE configuration file (*default.cfg*)


In this tutorial...

- ... you will learn
- where to find the MAgPIE configuration file
 - how the MAgPIE configuration file is structured
 - how to update model settings using the MAgPIE configuration file
 - how to start a model run using the updated settings

Where is the MAgPIE config file?



Main folder of the MAgPIE model



The MAgPIE config folder

First lines of the MAgPIE config file:

```
1 # | (C) 2008-2025 Potsdam Institute for Climate Impact Research (PIK)
2 # | authors, and contributors see CITATION.cff file. This file is part
3 # | of MAgPIE and licensed under AGPL-3.0-or-later. Under Section 7 of
4 # | AGPL-3.0, you are granted additional permissions described in the
5 # | MAgPIE License Exception, version 1.0 (see LICENSE file).
6 # | Contact: magpie@pik-potsdam.de
7
8 #####
9 ##### SETTINGS #####
10 #####
11
12 cfg <- list()
13
14 ##### Main settings #####
15
16 # short description of the actual run
17 cfg$title <- "default"
18
19 # path to the submodel to be used relative to main model folder
20 cfg$model <- "main.gms" #def = "main.gms"
21
22 ##### input settings #####
23
24 # which input data sets should be used?
25 cfg$input <- c(regional = "rev4.118_h12_magpie.tgz",
26               cellular = "rev4.118_h12_1b5c3817_cellularmagpie_c200_MRI-ESM2-0-ssp245_lpjml-8e6c5eb1.tgz",
27               validation = "rev4.118_h12_validation.tgz",
28               additional = "additional_data_rev4.62.tgz",
29               calibration = "calibration_H12_FAO_13Mar25.tgz")
```

Content and structure of the MAgPIE config file

The config file contains all MAgPIE settings that are not fixed in the model

- **metadata settings** (e.g. the title of the model run, *cfg\$title*)
- **technical settings** (e.g. the maximum number of iterations if precision goal is not met, *cfg\$calib_maxiter*)
- **module settings** (e.g. which SSP scenario should be used for population projections, *cfg\$gms\$c09_pop_scenario*)
- **output and model reporting settings** (e.g. which output-scripts should be run, *cfg\$output*)

Core components of the MAgPIE config file

cfg\$title	Model run title X
cfg\$model	Path to the submodel (relative to main model folder)
cfg\$input	Input data source
cfg\$repositories	Repository containing input data
cfg\$force_download	Should data be downloaded even if inputs didn't change?
cfg\$force_replace	Should existing output folder be replaced if a new run with the same name is started?
cfg\$recalibrate	Should yields be recalibrated?
cfg\$calib_cropland	Switch for cropland calibration
cfg\$recalibrate_landconversion_cost	Should land conversion cost be calibrated
cfg\$recalc_npi_ndc	Settings for NPI/NDC recalculation
cfg\$policyregions	National or sub-national mapping

cfg\$gms	List of module settings X
cfg\$magicc_emis_scen	Scenario for coupling with MAGICC for emissions outside the food system
cfg\$sequential	Should runs be made sequentially or in parallel?
cfg\$logoption	Log information
cfg\$output	Output scripts that should be used X
cfg\$results_folder	Results folder name
cfg\$files2export	Files copied to output folder
cfg\$runstatistics	Folder run statistics location
cfg\$model_name	Name of the overall model
cfg\$info	List of additional information characterizing the run
cfg\$developer_mode	Developer mode
cfg\$debug	Debugging mode

Changing the run title

- the title of the run is defined by the setting `cfg$title`, which can be found on line 17 of the default.cfg file

```
15  
16 # short description of the actual run  
17 cfg$title <- "default"  
18
```

- you can change the run title by replacing “default” with a title of your choice, e.g.

```
15  
16 # short description of the actual run  
17 cfg$title <- "magpieWorkshopPIK"  
18
```


Changing the module settings cfg\$gms

- a few settings are relevant to all modules, e.g. which time steps should be used, *cfg\$gms\$c_timesteps*

```
131
132 # Set number of time steps (1-16) or type "less_TS" for remind time steps
133 cfg$gms$c_timesteps <- "coup2100"
134
```

- coup2100 refers to a set defined in the GAMS code, you can find it's definition by opening the file **core/sets.gms** (from the main MAgPIE model folder), and searching for “coup2100”

```
181 set t(t_all) Simulated time periods
182 $If "%c_timesteps%"== "less_TS" /y1995,y2000,y2005,y2010,y2015,y2020,y2025,y2030,y2035,y2040,y2045,y2050,y2055,y2060,y2070,y2080,y2090,y2100,y2110,y2130,y2150/;
183 $If "%c_timesteps%"== "coup2100" /y1995,y2000,y2005,y2010,y2015,y2020,y2025,y2030,y2035,y2040,y2045,y2050,y2055,y2060,y2070,y2080,y2090,y2100/;
184 $If "%c_timesteps%"== "test_TS" /y1995,y2000,y2005,y2010,y2020,y2030,y2040,y2050,y2070,y2090,y2110,y2130,y2150/;
185 $If "%c_timesteps%"== "TS_benni" /y1995,y2000,y2005,y2010,y2020,y2030,y2040,y2050/;
186 $If "%c_timesteps%"== "TS_WB" /y1995,y2000,y2005,y2010,y2020,y2030,y2040,y2050,y2060,y2070,y2080/;
187 $If "%c_timesteps%"== "5year" /y1995,y2000,y2005,y2010,y2015,y2020,y2025,y2030,y2035,y2040,y2045,y2050,y2055,y2060,y2065,y2070,y2075,y2080,y2085,y2090,y2095,y2100/;
188 $If "%c_timesteps%"== "5year2050" /y1995,y2000,y2005,y2010,y2015,y2020,y2025,y2030,y2035,y2040,y2045,y2050/;
189 $If "%c_timesteps%"== "5year2070" /y1995,y2000,y2005,y2010,y2015,y2020,y2025,y2030,y2035,y2040,y2045,y2050,y2055,y2060,y2065,y2070/;
190 $If "%c_timesteps%"== "quicktest" /y1995,y2010,y2025/;
191 $If "%c_timesteps%"== "quicktest2" /y1995,y2020,y2050,y2100/;
192 $If "%c_timesteps%"== "calib" /y1995,y2000,y2005,y2010,y2015/;
```

Changing the module settings `cfg$gms`

- a few settings are relevant to all modules, e.g. which time steps should be used, `cfggmsc_timesteps`
- then, each module has its own section in the config file, where the module realization is chosen, and (if necessary) additional module parameters are set

```
287 # ***----- 13_tc -----
288 # * (endo_jan22): endogenous technological change with full cost accounting and
289 # *                stepwise updated crop and managed pastures area information
290 # * (exo): exogenous technological change (removes non-linearities from the model);
291 # *       requires an existing model run with endo tc for generating the input file
292 # *       f13_tau_scenario.csv
293 cfg$gms$tc <- "endo_jan22"          # def = endo_jan22
294
295 # * tc cost scenario crops: low, medium or high
296 cfg$gms$c13_tccost <- "medium"      # def = medium
297
298 # * ignore historical tau (1) or use it as lower bound (0)
299 cfg$gms$s13_ignore_tau_historical <- 1 # def = 1
300
301 # * Maximum regional tech cost expressed as share of regional GDP
302 # *   A meaningful value would be 0.002. However, this bound causes infeasibilities in some cases.
303 # *   Therefore, this bound is not used in the current model version.
304 cfg$gms$s13_max_gdp_shr <- Inf # def = Inf
```

description of module realizations

realization setting


additional module parameters

Changing which output scripts should be run

- `cfg$output` defines which output script should be run:

```
2226 # Should output.R generate output?
2227 # List of output scripts that should be used
2228 # Available scripts can be found in scripts/output/
2229 cfg$output <- c("output_check", "extra/disaggregation", "rds_report")
```

- available scripts can be found in `scripts/output/`:



- descriptions are included within the output script files, e.g. for `output_check`:

```
1 # | (C) 2008-2025 Potsdam Institute for Climate Impact Research (PIK)
2 # | authors, and contributors see CITATION.cff file. This file is part
3 # | of MAGPIE and licensed under AGPL-3.0-or-later. Under Section 7 of
4 # | AGPL-3.0, you are granted additional permissions described in the
5 # | MAGPIE License Exception, version 1.0 (see LICENSE file).
6 # | Contact: magpie@pik-potsdam.de
7
8 # -----
9 # description: check output for known problems
10 # comparison script: FALSE
11 # position: 1
12 # -----
13
14 library(magpie4, quietly = TRUE)
15
16 ##### BASIC CONFIGURATION #####
17 if(!exists("source_include")) {
18   outputdir <- ""
19   readArgs("outputdir")
20 }
21
22 gdx <- file.path(outputdir, "fulldata.gdx")
23 #####
24
25 magpie4::outputCheck(gdx)
```

Starting a run with updated settings

- in general, all settings in the MAgPIE config file are set to default values, therefore the name *default.cfg*
- settings can easily be changed by editing the configuration file, e.g. changing the title from `cfg$title <- "default"` to `cfg$title <- "magpieWorkshopPIK"` (line 17)
- once the *default.cfg* file is edited, starting the model using the default start script (as done in the last tutorial) will use the updated model settings
 - in the main model folder, execute `Rscript start.R` in a terminal or `source("start.R")` within R
 - type **1** and confirm via **Enter** to choose the *default start script*
 - again, type **1** and confirm via **Enter** to choose *direct execution*

Normally, the *default.cfg* file is not directly edited, but settings are changed using a start script, which will be explained in the next tutorial

Exercises

- 1) By editing the corresponding setting in the default.cfg file, change the title of the model run to contain your affiliation (e.g. "magWorkshop_PIK").
- 2) By editing the corresponding setting in the default.cfg file, change the model time steps to the set "quicktest". Additionally, find out which years are include in this set (without running the model).
- 3) By editing the corresponding setting in the default.cfg file, change the model configuration such that only the output script "output_check" is run.
- 4) Start a MAgPIE run using the updated model settings from exercises 1-3.