



SQL Code Count™

Counting Standard

University of Southern California

Center for Systems and Software Engineering

December , 2016

Revision Sheet

Date	Version	Revision Description	Author
7/6/2016	1.0	Original Release	Matthew Swartz
7/12/2016	1.1	Updated complexity table	Matthew Swartz

Table of Contents

No.	Contents	Page No.
1.0	Definitions	4
1.1	SLOC	4
1.2	Physical SLOC	4
1.3	Logical SLOC	4
1.4	Data declaration line	4
1.5	Compiler directive	4
1.6	Blank line	4
1.7	Comment line	4
1.8	Executable line of code	4
2.0	Checklist for source statement counts	6
3.0	Examples of logical SLOC counting	8
3.1	Executable Lines	8
3.1.1	Data Statements	8
3.1.2	Schema Statements	9
3.1.3	Transactional Statements	9
3.1.4	Conditional Statements	10
3.2	Declaration lines	11
4.0	Complexity	12
5.0	Cyclomatic Complexity	13

1. Definitions

- 1.1. **SLOC** – Source Lines of Code is a unit used to measure the size of software program. SLOC counts the program source code based on a certain set of rules. SLOC is a key input for estimating project effort and is also used to calculate productivity and other measurements.
- 1.2. **Physical SLOC** – One physical SLOC is corresponding to one line starting with the first character and ending by a carriage return or an end-of-file marker of the same line, and which excludes the blank and comment line.
- 1.3. **Logical SLOC** – Lines of code intended to measure “statements”, which normally terminate by a semicolon (C/C++, Java, C#) or a carriage return (VB, Assembly), etc. Logical SLOC are not sensitive to format and style conventions, but they are language-dependent.

Data declaration line or data line – A line that contains declaration of data and used by an assembler or compiler to interpret other elements of the program.

The following table lists the SQL keywords that denote data declaration lines:

UNIQUEIDENTIFIER	SMALLDATETIME	MEDIUMBLOB	MEDIUMTEXT	SMALLMONEY	CHARACTER
TIMESTAMP	VARBINARY	DATETIME	INTERVAL	LONGBLOB	LONGTEXT
SMALLINT	TINYTEXT	BOOLEAN	DECIMAL	INTEGER	NUMERIC
VARCHAR	BIGINT	BINARY	DOUBLE	SINGLE	FLOAT
MONEY	NCHAR	NTEXT	BLOB	BYTE	CHAR
ENUM	LONG	MEMO	REAL	TEXT	TIME
BIT	INT				

Table 1 SQL Data Keywords

- 1.4. **Compiler Directives** – A statement that tells the compiler how to compile a program, but not what to compile. SQL does not contain any compiler directives.
- 1.5. **Blank Line** – A physical line of code, which contains any number of white space characters (spaces, tabs, form feed, carriage return, line feed, or their derivatives).
- 1.6. **Comment Line** – A comment is defined as a string of zero or more characters that follow language-specific comment delimiter. SQL comment delimiters are "/*", "--", or "{.} ". A whole comment line may span one line and does not contain any compilable source code. An embedded comment can co-exist with compilable source code on the same physical line. Banners and empty comments are treated as types of comments.
- 1.7. **Executable Line of code** – A line that contains software instruction executed during runtime and on which a breakpoint can be set in a debugging tool. An instruction can be stated in a simple or compound form.

An executable line of code may not contain the following statements:

- Commands which access the storage memory

- Keywords which perform conditional operations
- Data declaration (data) lines

2. Checklist for source statement counts

<u>PHYSICAL SLOC COUNTING RULES</u>			
MEASUREMENT UNIT	ORDER OF PRECEDENCE	PHYSICAL SLOC	COMMENTS
Executable lines	1	One per line	Defined in 1.8
Non-executable lines			
Declaration (Data) lines	2	One per line	Defined in 1.4
Compiler directives	3	One per line	Defined in 1.5
Comments			Defined in 1.7
On their own lines	4	Not included (NI)	
Embedded	5	NI	
Banners	6	NI	
Empty comments	7	NI	
Blank lines	8	NI	Defined in 1.6

<u>LOGICAL SLOC COUNTING RULES</u>				
NO.	STRUCTURE	ORDER OF PRECEDENCE	LOGICAL SLOC RULES	COMMENTS
R01	Data Statements: SELECT UPDATE INSERT DELETE ALTER TABLE ALTER USER DECLARE FETCH CLOSE	1	Count once	Each statement, including nested queries, is counted once per each occurrence.
R02	Schema Statements: CREATE CREATE TRIGGER CREATE SEQUENCE CREATE INDEX CREATE SYNONYM REPLACE COMMENT TRUNCATE RENAME DROP GRANT REVOKE	2	Count once	

R03	Transactional Statements: COMMIT ROLLBACK	3	Count once	
R04	Conditional Statements: WHERE GROUP BY ORDER BY HAVING LIMIT JOIN UNION	4	Count once	Conditional statements appearing in combination with other keywords are counted once per each occurrence.

3. Examples

EXECUTABLE LINES

DATA Statement

EDS1 – SELECT statement

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
SELECT [ALL DISTINCT] select-list	SELECT city FROM cities	1
SELECT * FROM select-list	WHERE city IN	1
SELECT column FROM select-list	(SELECT city FROM country	1
WHERE column = <criteria>	WHERE id='1')	1

EDS2 – UPDATE statement

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
UPDATE table SET set-list [WHERE predicate]	UPDATE Customers	1
	SET Customer.id ='1'	1
	WHERE Customer.id='2'	1

EDS3 – INSERT statement

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
INSERT INTO table [(column-list)] VALUES (value-list)	INSERT INTO colors (cnum, color) VALUES ('C1', 'green')	1 0
INSERT INTO table [(column-list)] (query-specification)	INSERT INTO location SELECT ct.name, loc.type, 500 FROM ct, loc WHERE ct.name="London" AND loc.type='Europe'	1 1 0 1 0

EDS4 – DELETE statement

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
DELETE FROM table [WHERE predicate]	DELETE * FROM Customers WHERE Id='1'	1 1
DELETE FROM table WHERE column NOT IN (SELECT column FROM table)	DELETE * FROM Customers NOT IN (SELECT Customers FROM Regulars)	1 1

EDS5 – ALTER statement		
GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
ALTER TABLE <TABLE NAME>	ALTER TABLE Customer ADD PRIMARY KEY (SID);	1 0
<u>SCHEMA Statement</u>		
ESS1 – CREATE statement		
GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
CREATE TABLE table-name {column-descr constraint} [, {column-descr constraint}]...)	CREATE TABLE locals (ct VARCHAR(5) NOT NULL PRIMARY KEY, name VARCHAR(16), city VARCHAR(16))	1 0 0 0 0 0
CREATE VIEW view-name [(column-list)] AS query [WITH [CASCADED LOCAL] CHECK OPTION]	CREATE VIEW supplied_parts AS SELECT * FROM parts WHERE pnum IN (SELECT pnum FROM supplier)	1 1 2 0
ESS2 – DROP statement		
GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
DROP TABLE table-name {CASCADE RESTRICT}	DROP TABLE locals	1
DROP VIEW view-name {CASCADE RESTRICT}	DROP VIEW supplied_parts	1
ESS3 – GRANT statement		
GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
GRANT privilege-list ON [TABLE] object-list TO user-list	GRANT SELECT,INSERT,UPDATE(parts) ON p TO mike	1 1
ESS4 – REVOKE statement		
GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
REVOKE	REVOKE privilege-list ON [TABLE] object-list FROM user-list	1 1
<u>TRANSACTIONAL Statement</u>		
ETS1 – COMMIT statement		

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
COMMIT [WORK]	COMMIT	1
ETS2 – ROLLBACK statement		
GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
ROLLBACK [WORK]	ROLLBACK	1
<u>CONDITIONAL</u> Statement		
ECS1 – WHERE statement		
GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
SELECT [FROM table_references] [WHERE where_condition]	SELECT * FROM Table WHERE Table.id='1'	1 1
ECS2 – GROUP BY statement		
GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
SELECT [FROM table_references] [WHERE where_condition] [GROUP BY {col_name expr position} [ASC DESC]]	SELECT * FROM Customers GROUP BY ID	1 0 1
ECS3 – ORDER BY statement		
GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
SELECT * FROM select_list ORDER BY column [ASC DESC]	SELECT * FROM Customers ORDER BY Id ASC	1 0 1
ECS4 – LIMIT statement		
GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
SELECT [FROM table_references] [WHERE where_condition] [LIMIT {[offset,] row_count row_count OFFSET offset}]	SELECT * FROM Customers LIMIT 1	1 0 1
ECS5 – JOIN statement		
GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
table-1 { LEFT RIGHT FULL	SELECT count(*) as totalcount,	1

OUTER JOIN table-2 ON predicate	trsuser.id, trsuser.fname, trsuser.mortgage FROM customers, loanInfo, trsuser LEFT OUTER JOIN leadSupplierCampaign ON leadSupplierCampaign.CampaignID = customers.ReferralORDER BY Id ASC	0 0 0 1 0 0 0 0
ECS6 – UNION statement		
GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
table_query UNION [ALL] table_query [ORDER BY column [ASC DESC] [, ...]]	SELECT customers.name FROM customers WHERE customers.name LIKE 'T%' UNION SELECT public.name FROM public WHERE public.name LIKE 'T%'	1 0 1 1 1 0 1

DECLARATION OR DATA LINES

DDL1 - variable declaration

GENERAL EXAMPLE	SPECIFIC EXAMPLE	SLOC COUNT
<name> <type>	userid int(10), addnewuser enum('1','0'), permission enum('1','0'), assignleadsupplier enum('1','0'), addnewtsr enum('1','0'), assigntsrsls enum('1','0'), leadsquery enum('1','0'), postedleadsall enum('1','0'), postedleadsassigned enum('1','0'), leadpurchasers enum('1','0'), accountexecutives enum('1','0'), lsall enum('1','0'), lsassigned enum('1','0')	1 1 1 1 1 1 1 1 1 1 1 1 1

4. Complexity

Complexity measures the occurrences of different keywords in code baseline. Below table identifies the categories and their respective keywords that are counted as part of the complexity metrics.

Table 2 - Complexity Keywords List

Math Functions	Trig	Log	Calculations	Conditionals	Logic	Pre-processor	Assignment	Pointer
VARIANCE	ACOSH	LOG	+	INTERSECT	LIKE		=	
STDDEV	ASINH	LN	-	GROUP BY	AND			
COUNT	ATAN2		/	ORDER BY	NOT			
FLOOR	ATANH		*	EXCEPT	!=			
POWER	ACOS			HAVING	<>			
ROUND	ASIN			LIMIT	>=			
TRUNC	ATAN			UNION	<=			
CEIL	COSH			WHERE	OR			
SIGN	SINH			JOIN	>			
SQRT	TANH				<			
ABS	COS							
AVG	SIN							
EXP	TAN							
MAX								
MIN								
MOD								
SUM								

5. Cyclomatic Complexity

Cyclomatic complexity measures the number of linearly independent paths through a program. It is measured for each function, procedure, or method according to each specific program language. This metric indicates the risk of program complexity and also determines the number of independent test required to verify program coverage.

The cyclomatic complexity is computed by counting the number of decisions plus one for the linear path. Decisions are determined by the number of conditional statements in a function. A function without any decisions would have a cyclomatic complexity of one. Each decision such as an if condition or a for loop adds one to the cyclomatic complexity.

The cyclomatic complexity metric $v(G)$ was defined by Thomas McCabe. Several variations are commonly used but are not included in the UCC. The modified cyclomatic complexity counts select blocks as a single decision rather than counting each case. The strict or extended cyclomatic complexity includes boolean operators within conditional statements as additional decisions.

Table 3 – Cyclomatic Complexity Risk Evaluation

Cyclomatic Complexity	Risk Evaluation
1 - 10	A simple program, without much risk
11 - 20	More complex, moderate risk
21 - 50	Complex, high risk program
> 50	Untestable program, very high risk

For PL/SQL the following table lists the conditional keywords used to compute cyclomatic complexity.

Table 4 – Cyclomatic Complexity Counts

Statement	CC Count	Rationale
If	+1	if adds a decision
Elsif	+1	else if adds a decision
Else	0	Decision is at the if statement
case when	+1 per when	Each when adds a decision – not

		the case
case default	0	Decision is at the when statements
For	+1	for adds a decision at loop start
while	+1	while adds a decision at loop start or at end of do loop