```sql
/* insert companies data */

INSERT INTO companies (company_id, company_name, city, industry,
no_employees, revenue, training_budget)
VALUES (10, 'USCABLES', 'WASHINGTON', 'MANUFACTURING', 250, 4000000,
50000.00);
INSERT INTO companies (company_id, company_name, city, industry,
no_employees, revenue, training_budget)
VALUES (20, 'KODAK', 'HOUSTON', 'MANUFACTURING', 2500, 10000000,
100000.00);
INSERT INTO companies (company_id, company_name, city, industry,
no_employees, revenue, training_budget)
VALUES (30, 'KLM', 'AMSTERDAM', 'SERVICE', 5000, 11000000, 990000.00);
INSERT INTO companies (company_id, company_name, city, industry,
no_employees, revenue, training_budget)
VALUES (40, 'HAMBRO', 'LONDON', 'SERVICE', 2000, 6000000, 500000.00);
INSERT INTO companies (company_id, company_name, city, industry,
no_employees, revenue, training_budget)
VALUES (50, 'FORD', 'DETROIT', 'MANUFACTURING', 8000, 20000000,
100000.00);
INSERT INTO companies (company_id, company_name, city, industry,
no_employees, revenue, training_budget)
VALUES (60, 'CITYBANK', 'BOSTON', 'FINANCE', 3000, 5000000,
200000.00);
INSERT INTO companies (company_id, company_name, city, industry,
no_employees, revenue, training_budget)
VALUES (70, 'DISNEY', 'ORLANDO', 'ARTS', 2500, 10000000, 300000.00);
```