

Semi-structured Data

8 - XQuery

Outline


- What is XQuery?
- XQuery at First Glance
- FLWOR Expressions
- Element Constructors
- List, Conditional and Quantified Expressions
- Joins
- Aggregating Values

What is XQuery?


- XQuery is a **language for querying XML data**
- XQuery for XML is like SQL for relational databases
- XQuery is built on XPath expressions
- As expected, XQuery is a W3C standard

XQuery vs. XPath

- XPath is essentially a **subset** of XQuery
- XQuery has a number of features not supported by XPath
- XQuery can **structure or sort** query results (not just select elements and attributes)



Processing XQueries



- **Analysis phase:** finds syntax errors and other static errors that do not depend on the input document
- **Evaluation phase:** may raise dynamic errors (e.g., missing input document or division by zero)
- A number of implementations available - <http://www.w3.org/XML/Query>

XQuery at First Glance

```
<courses>
  <course semester="Summer">
    <title> SSD </title>
    <day> Thursday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
  <course semester="Winter">
    <title> Databases </title>
    <day> Tuesday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
</courses>
```

`doc("courses.xml")/courses/course/title`

`<title> Semi-structured Data </title>`

`<title> Databases </title>`

XQuery at First Glance

```
<courses>
  <course semester="Summer">
    <title> SSD </title>
    <day> Thursday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
  <course semester="Winter">
    <title> Databases </title>
    <day> Tuesday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
</courses>
```

```
doc("courses.xml")/
  courses/course[@semester="Winter"]
```

```
<course semester="Winter">
  <title> Databases </title>
  <day> Tuesday </day>
  <time> 09:15 </time>
  <location> HS8 </location>
</course>
```

XQuery at First Glance

```
<courses>
  <course semester="Summer">
    <title> SSD </title>
    <day> Thursday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
  <course semester="Winter">
    <title> Databases </title>
    <day> Tuesday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
</courses>
```

```
doc("courses.xml")/
  courses/course[@semester="Winter"]/title
```

```
<title> Databases </title>
```


XQuery at First Glance

```
<courses>
  <course semester="Summer">
    <title> SSD </title>
    <day> Thursday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
  <course semester="Winter">
    <title> Databases </title>
    <day> Tuesday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
</courses>
```

```
for $x in doc("courses.xml")/courses/course
where $x/@semester="Winter"
return $x/title
```

```
<title> Databases </title>
```

Equivalent to the query

```
doc("courses.xml")/
  courses/course[@semester="Winter"]/title
```

XQuery at First Glance

```
<courses>
  <course semester="Summer">
    <title> SSD </title>
    <day> Thursday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
  <course semester="Winter">
    <title> Databases </title>
    <day> Tuesday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
</courses>
```

```
for $x in doc("courses.xml")/courses/course
where $x/@semester="Winter"
order by $x/title
return $x/title
```

```
<title> Databases </title>
```

XQuery at First Glance

```
<courses>
  <course semester="Winter">
    <title> SSD </title>
    <day> Thursday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
  <course semester="Winter">
    <title> Databases </title>
    <day> Tuesday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
</courses>
```

```
for $x in doc("courses.xml")/courses/course
where $x/@semester="Winter"
order by $x/title
return $x/title
```

```
<title> Databases </title>
<title> SSD </title>
```

XQuery at First Glance

```
<courses>
  <course semester="Winter">
    <title> SSD </title>
    <day> Thursday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
  <course semester="Winter">
    <title> Databases </title>
    <day> Tuesday </day>
    <time> 09:15 </time>
    <location> HS8 </location>
  </course>
</courses>
```

for \$x in doc("courses.xml")/courses/course
where \$x/@semester="Winter"
order by \$x/title descending
return \$x/title


```
<title> SSD </title>
<title> Databases </title>
```

Up to Now

- **What is XQuery?**
- **XQuery at First Glance**
- FLWOR Expressions
- Element Constructors
- List, Conditional and Quantified Expressions
- Joins
- Aggregating Values

FLWOR Expressions

- The main engine of XQuery is **FLWOR expressions**



for ...
let ...
where ...
order by ...
return ...

- Pronounced “**Flower Expressions**”
- Generalize Select-From-Having-Where in SQL

FLWOR Expressions: A Complete Example

```
for $d in doc("departments.xml")//dept_no
let $e := doc("employees.xml")//employee[dept_no = $d]
where count($e) >= 10
order by avg($e/salary) descending
return
  <large_dept>
    {$d}
    <size> {count($e)} </size>
    <avg_salary> {avg($e/salary)} </avg_salary>
  </large_dept>
```

a list of departments with at least ten employees, sorted by average salary

FLWOR Expressions: Semantics

```
for $d in doc("departments.xml")//dept_no
let $e := doc("employees.xml")//employee[dept_no = $d]
where count($e) >= 10
order by avg($e/salary) descending
return
  <large_dept>
    {$d}
    <size> {count($e)} </size>
    <avg_salary> {avg($e/salary)} </avg_salary>
  </large_dept>
```

- **for** generates bindings of dept_no values to \$d
- **let** associates to each binding a further binding of the list of employee elements with that dept_no to \$e
- **where** filters that list to keep only the desired pairs
- **order by** sorts that lists by the given criteria
- **return** constructs for each pair a resulting value

FLWOR Expressions: General Rules

- **for** and **let** may be used **many times in any order**
- **Only one where** is allowed
- **More than one sorting** criteria can be specified

order by <expression> ascending, <expression> descending, ...

Difference Between for and let

```
for $x in (1,2,3)  
let $y := ("a", "b")  
return ($x, $y)
```

1 a b 2 a b 3 a b

```
let $x := (1,2,3)  
for $y in ("a", "b")  
return ($x, $y)
```

1 2 3 a 1 2 3 b

```
for $x in (1,2,3)  
for $y in ("a", "b")  
return ($x, $y)
```

1 a 1 b 2 a 2 b 3 a 3 b

```
let $x := (1,2,3)  
let $y := ("a", "b")  
return ($x, $y)
```

1 2 3 a b

Element Constructors

- An XQuery expression may construct a **new XML element**
- XML constructs can be used to create elements and attributes that appear in the query result
 - **Wrapping results in a new element**
 - **Adding attributes to results**
- A key difference compared to XPath

Element Constructors

Wrapping results in a new element

```
<sorted_departments> {  
  for $d in doc("departments.xml")//dept_no  
  let $e := doc("employees.xml")//employee[dept_no = $d]  
  where count($e) >= 10  
  order by avg($e/salary) descending  
  return  
    <large_dept>  
      {$d}  
      <size> {count($e)} </size>  
      <avg_salary> {avg($e/salary)} </avg_salary>  
    </large_dept>      } </sorted_departments>
```

Element Constructors

Adding attributes to results

```
for $d in doc("departments.xml")//dept_no
let $e := doc("employees.xml")//employee[dept_no = $d]
where count($e) >= 10
order by avg($e/salary) descending
return
  <large_dept name = "{$d}">
    <size> {count($e)} </size>
    <avg_salary> {avg($e/salary)} </avg_salary>
  </large_dept>
```

List Expressions

- XQuery expressions manipulate **lists of items**
 - Value lists: (1,2,3), ("a", "b")
 - Results of XPath expressions
- Many **operators** are supported
 - Range expressions (e.g., "3 to 10")
 - Concatenation using “,”
 - Set operators (union, intersect, except)
- Many **functions** are supported
 - count, avg, max, min, sum, distinct-values, ...

List Expressions: Example

```
for $d in doc("departments.xml")//dept_no
let $e := doc("employees.xml")//employee[dept_no = $d]
where count($e) >= 10
order by avg($e/salary) descending
return
```

```
  <large_dept>
    {$d}
    <size> {count($e)} </size>
    <avg_salary> {avg($e/salary)} </avg_salary>
  </large_dept>
```

List Expressions: Example

```
<coauthors>
{
  for $coauthor in
    distinct-values(
      doc("SimkusMantas.xml")//author[not(./text()=//dblpperson/@name)]
    )
  return
    <coauthor>
      {$coauthor}
    </coauthor>
}
</coauthors>
```


Conditional Expressions

XQuery supports general **if-then-else expressions**

```
for $b in doc("books.xml")/bookstore/book
return
  if ($b/@category = "children")
  then <child> {$b} </child>
  else <adult> {$b} </adult>
```

ATTENTION: else is required, but it can be just else ()

Quantified Expressions

XQuery allows **quantified expressions** (**exist**, **forall**)

```
for $d in doc("departments.xml")//dept_no  
let $e := doc("employees.xml")//employee[dept_no = $d]  
where some $s in $e/salary satisfies $s > 1000  
return $d
```

```
for $d in doc("departments.xml")//dept_no  
let $e := doc("employees.xml")//employee[dept_no = $d]  
where every $s in $e/salary satisfies $s > 1000  
return $d
```

Joins

Using FLWOR expressions we can **join data from multiple sources**

```
for $d in doc("departments.xml")//dept_no
let $e := doc("employees.xml")//employee[dept_no = $d]
where count($e) >= 10
order by avg($e/salary) descending
return
  <large_dept>
    {$d}
    <size> {count($e)} </size>
    <avg_salary> {avg($e/salary)} </avg_salary>
  </large_dept>
```

Joins

```
for $i in doc("order.xml")//item
let $n := doc("catalog.xml")//product[number = $i/@num]/name
return
```

```
  <item num = "{$i/@num}"
      name = "{$n}"
      quantity = "{$i/@quantity}"/>
```

```
<catalog>
  <product dept="D1">
    <number> 130 </number>
    <name> N1 </name>
  </product>
  <product dept="D2">
    <number> 230 </number>
    <name> N2 </name>
  </product>
</catalog>
```

```
<order>
  <item dept="D1" num="130" quantity="5"/>
  <item dept="D2" num="230" quantity="10"/>
</order>
```

```
<item num="130" name="N1" quantity="5"/>
<item num="230" name="N2" quantity="10"/>
```

Aggregating Values

```
for $d in distinct-values(doc("order.xml")//item/@dept)
```

```
let $i := doc("order.xml")//item[@dept = $d]
```

```
order by $d descending
```

```
return <department name = "{$d}" totalQuantity = "{sum($i/@quantity)}"/>
```

```
<order>
```

```
  <item dept="D1" num="130" quantity="5"/>
```

```
  <item dept="D2" num="230" quantity="7"/>
```

```
  <item dept="D1" num="100" quantity="6"/>
```

```
  <item dept="D2" num="330" quantity="10"/>
```

```
</order>
```

```
<department name="D2" totalQuantity="17"/>
```

```
<department name="D1" totalQuantity="11"/>
```

Sum Up

- What is XQuery?
- XQuery at First Glance
- FLWOR Expressions
- Element Constructors
- List, Conditional and Quantified Expressions
- Joins
- Aggregating Values