S.N.	Model	Product Code	Product	Specifications	Capacity	Dealer Rate	Retail Rate	MRP
1	C1C	CS-C1C-D0-1D1WFR		1MP 720p, Motion Detection, Enhanced Night Vision 40ft/12m, Two Way talk, View from anywhere, 2.4GHz Wi-Fi, Easy Installation, Magnetic Base, Secure Cloud Storage	256GB	3785	4164	5413
2	C1C	CS-C1C-D0-1D2WFR		2MP 1080p, Motion Detection, Enhanced Night Vision 40ft/12m, Two Way talk, View from anywhere, 2.4GHz Wi-Fi, Easy Installation, Magnetic Base, Secure Cloud Storage	256GB	4495	4945	6428
3	C3WN	CS-CV310-A0-1C2WFR		2 MP Full HD, Strong Wi-Fi Connection, Audio Reception, IP66, Night Vision Upto 30 meters, Supports 2.4 GHz	256GB	7160	7876	10239
4	C3W(ezguard)	CS-CV310-A0-1B2WFR		2MP 1080p, H.264 Video Technology, Motion Detection, User Defined alarm tones, IP66, 2.4GHz Wi-Fi, Two way talk	256GB	10750	11825	15373
5	C3N	CS-C3N-A0-3H2WFRL		1/2.7"Progressive Scan CMOS, 4mm@ F2.0, view angle:102°(Diagonal), 86° (Horizontal), IR-Cut filter with auto-switching, 3D DNR, Digital WDR, H.265, H.264, 1920 × 1080,Max: 30fps; Self-Adaptive during network transmission,AI Powered Human Detection,Micro SD card slot (Max. 256G), Wi-Fi 2.4G, IP67, DC 12V/1A.	256GB	7940	8734	11354
6	C6N	CS-C6N-A0-1C2WFR		1/4" Progressive Scan CMOS,4mm, view angle: 85°(Diagonal), 75° (Horizontal), 45°(Vertical),1920x1080@Max 15fps, H.264, 3D DNR,Digital WDR,Motion Detection,Two-way talk,sleep mode, on-board MicroSD card slot 256GB, Wi-Fi 2.4G, DC5V 1A, Max 5W. Working temp -10℃ ~ 45℃, Working Humidity 95% or less.	256GB	4600	5060	6578
7	C6P	CS-CV346-A0-7A3WFR		3MP HD, 360 Panoramic View, Night Vision Up to 25ft, Motion Detection Alert, 2.5 GHz and 5GHz Wi-Fi, Two Way Talk, Secure Cloud Storage	128GB	14455	15901	20671
8	C4W	CS-CV228-A0-3C2WFR 2.8mm		1/2.7" Progressive Scan CMOS, 2.8mm lens, 103° Horizontal, 118° Diagonal, 3D DNR, Digital WDR, H.265/H.264, 1920*1080, Max30fps, Self-Adaptive, Motion Detection, Active defense with Siren and Strobe light, Wi-Fi 2.4G, Max.256G SD card. DC12V/1A, IP67	256GB	7990	8789	11426
9	DP1C	CS-DP1C-A0-4A1WPFBSR		1/3" Processive Scan CMOS, 2.2mm@F2.4, PIR Motion Detection, Night Vision 10ft, 720P Resolution, PIR 8ft, 4.3" touch screen, Wifi 2.4G, Ring Button, Indoor, DC5V±10%, Max2.25W, Two Way Talk, 1MP, Built-in Chime	128GB	20910	23001	29901
10	C8C	CS-C8C-A0-3H2WFL1(4mm)		1/2.7" Progressive Scan CMOS,4mm@ F1.6, view angle:87° (Horizontal), 105°(Diagonal),Pan: 352°, Tilt: 95°,0.2 Lux @(F1.6, AGC ON), 0 Lux with IR ,3D DNR, Digital WDR, IR 30m/100ft, 1920 × 1080, Max:30fps; Self-Adaptive during network transmission, Smart H.265 / H.264, Main Profile, Max bitrate 2Mbps, WiFi 2.4GHz, RJ45 × 1(10M/100M Adaptive Ethernet Port), AI Human Detection , Micro SD card slot (Max. 256G), -30°C ~ 60°C (14°F to 113 °F), Humidity 95% or less (non-condensing), IP65, DC 12V/1A, MAX. 6W, 158mm x 157mm x 149mm, package 197mm x 185mm x 205mm, Product: 510g(1.12 lbs), With Package: 885g(1.95 lbs)	256GB	12300	13530	17589
11	DB2C Kit(With Chime)	CS-DB2C-A0-1E3WPBR		1/2.7" Progressive Scan CMOS (Supports low light sensitivity),2.2mm@F2.4, Ultra FOV 160° Vertical, IR Max.6m (20ft),1536 x 1536 FHD, 2D/3D DNR,H.265/H.264, Max: 15fps; Self-Adaptive during network transmission , PIR Range 100° , Max.5m (16.4ft), User adjustable (High, Medium and Low Sensitivity), Sound and light anti-dismantling alarm (support alarm to mobile phone), two way talk, WiFi 2.4GHz, -10°C to 45°C (14°F to 113 °F), Humidity 95% or less (non-condensing), 146 x 60 x 34mm (5.75" x 2.36" x 1.34"), 5200mAh rechargeable lithium battery, Max.7.5W, DC5V±10%. Chime: 100 x 54 x 37mm (3.94" x 2.13" x 1.46"), AC 100 ~ 240V, Supports TF card up to 256G, 65dB within 3 meters, 120g(0.26lb).	NA	12700	13970	18161
12	Smart Fingerprint Lock with lock card	CS-L2-11FCP		Built in electronic doorbell, four unlock methods, anti- tamper alarm, door handle with clutch mechanism, low battery warning signal, emergency power supply	NA	29700	32670	42471

UPDATED ON AUGUST 18