T-Spice - Tanner SPICE
T-Spice - Tanner SPICE
Version 16.01
Network license
Product Release ID: T-Spice Win64 16.01.20130407.21:15:40
Copyright © 1988-2013 Tanner EDA

Parsing "C:\Users\mahak\AppData\Local\Temp\Cell0.sp"
Including "C:\Users\mahak\Downloads\Tanner_v16\Tanner_v16\BPTM_Models files\180nm.md"

Start of Cell0.sp
Loaded BSIM3v31 model library Berkeley BSIM3 VERSION 3.1 with extensions

Opening simulation database "C:\Users\mahak\AppData\Local\Temp\Cell0.tsim"

General options:
threads = 1

Device and node counts:
MOSFETs - 2
MOSFET geometries - 2
Voltage sources - 2
Subcircuits - 0
Model Definitions - 2
Computed Models - 2
Independent nodes - 1
Boundary nodes - 3
Total nodes - 4

Power Results

vdd from time 0 to 1e-007
Average power consumed -> 1.607995e-006 watts
Max power 7.687342e-004 at time 1.002e-008
Min power 4.124340e-010 at time 0

Measure information will be written to file "C:\Users\mahak\AppData\Local\Temp\Cell0\Cell0.measure"

Measurement result summary
delay = -9.9599n

Parsing 0.01 seconds
Setup 0.01 seconds
DC operating point 0.00 seconds
TransientAnalysis 0.02 seconds
Overhead 0.17 seconds

Total 0.21 seconds

Simulation completed