T-Spice - Tanner SPICE
T-Spice - Tanner SPICE
Version 16.01
Network license
Product Release ID: T-Spice Win64 16.01.20130407.21:15:40
Copyright © 1988-2013 Tanner EDA

Parsing "C:\Users\mahak\AppData\Local\Temp\Cell0.sp"
Including "C:\Users\mahak\Downloads\Tanner_v16\Tanner_v16\BPTM_Models files\180nm.md"

Start of Cell0.sp
Loaded BSIM3v31 model library Berkeley BSIM3 VERSION 3.1 with extensions

Opening simulation database "C:\Users\mahak\AppData\Local\Temp\Cell0.tsim"

General options:
threads = 1

Device and node counts:
MOSFETs - 42
MOSFET geometries - 2
Voltage sources - 4
Subcircuits - 0
Model Definitions - 2
Computed Models - 2
Independent nodes - 23
Boundary nodes - 5
Total nodes - 28

Power Results

Va from time 0 to 1e-007
Average power consumed -> 7.525271e-007 watts
Max power 1.891267e-003 at time 4.001e-008
Min power 0.000000e+000 at time 0

Vb from time 0 to 1e-007
Average power consumed -> 3.591880e-007 watts
Max power 1.707885e-003 at time 4.001e-008
Min power 0.000000e+000 at time 0

Vc from time 0 to 1e-007
Average power consumed -> 3.297465e-007 watts
Max power 1.882265e-003 at time 6.001e-008
Min power 0.000000e+000 at time 0

Parsing	0.01 seconds
Setup	0.01 seconds
DC operating point	0.00 seconds
TransientAnalysis	0.07 seconds
Overhead	0.30 seconds
Total	0.38 seconds

Simulation completed