```
TSpice - Tanner SPICE
Version 16.01
Network license
Product Release ID: TSpice Win64 16.01.20130407.21:15:40
Copyright © 1988-2013 Tanner EDA

  Parsing "C:\Users\mahak\AppData\Local\Temp\Cell0.sp"
  Including "C:\Users\mahak\Downloads\Tanner_v16\Tanner_v16\BPTM_Models files\180nm.md"

Start of Cell0.sp
Loaded BSIM3v31 model library, Berkeley BSIM3 VERSION 3.1 with extensions

  Opening simulation database "C:\Users\mahak\AppData\Local\Temp\Cell0.tsim"

General options:
       threads = 1

 Device and node counts:
            MOSFETs -       4
   MOSFET geometries -       2
     Voltage sources -       3
        Subcircuits -       0
   Model Definitions -       2
     Computed Models -       2
   Independent nodes -       2
     Boundary nodes -       4
       Total nodes -       6

Power Results

Va from time 0 to 1e-007
Average power consumed -> 1.559724e-007 watts
Max power 6.473119e-004 at time 2.001e-008
Min power 0.000000e+000 at time 0

Vb from time 0 to 1e-007
Average power consumed -> 9.025329e-008 watts
Max power 6.629023e-004 at time 4.001e-008
Min power 0.000000e+000 at time 0


Measure information will be written to file "C:\Users\mahak\AppData\Local\Temp\Cell0\Cell0.measure"

Measurement result summary
  delay1         =   20.1465n
  delay2         =  146.4815p

Parsing                  0.05 seconds
Setup                    0.05 seconds
DC operating point       0.02 seconds
TransientAnalysis        0.07 seconds
Overhead                 0.98 seconds
-----------------------------------------
Total                    1.16 seconds

Simulation completed
```