```
T-Spice - Tanner SPICE
T-Spice - Tanner SPICE
Version 16.01
Network license
Product Release ID: T-Spice Win64 16.01.20130407.21:15:40
Copyright © 1988-2013 Tanner EDA

  Parsing "C:\Users\mahak\AppData\Local\Temp\Cell0.sp"
  Including "C:\Users\mahak\Downloads\Tanner_v16\Tanner_v16\BPTM_Models files\180nm.md"

Start of Cell0.sp
Loaded BSIM3v31 model library Berkeley BSIM3 VERSION 3.1 with extensions

  Opening simulation database "C:\Users\mahak\AppData\Local\Temp\Cell0.tsim"

General options:
       threads = 1

 Device and node counts:
            MOSFETs -      12
   MOSFET geometries -       2
     Voltage sources -       4
        Subcircuits -       0
   Model Definitions -       2
     Computed Models -       2
   Independent nodes -       6
     Boundary nodes -       5
       Total nodes -      11

Power Results

Va from time 0 to 1e-007
Average power consumed -> 2.979866e-007 watts
Max power 1.344405e-003 at time 8.001e-008
Min power 0.000000e+000 at time 0

Vb from time 0 to 1e-007
Average power consumed -> 1.311247e-007 watts
Max power 6.407495e-004 at time 4.001e-008
Min power 0.000000e+000 at time 0

Vc from time 0 to 1e-007
Average power consumed -> 4.695464e-008 watts
Max power 6.072892e-004 at time 1e-011
Min power 0.000000e+000 at time 0


Measure information will be written to file "C:\Users\mahak\AppData\Local\Temp\Cell0\Cell0.measure"

Measurement result summary
  delay1        =   50.2014n
  delay2        =   30.2014n
  delay3        =   10.2014n

Parsing                 0.05 seconds
Setup                   0.02 seconds
DC operating point      0.00 seconds
TransientAnalysis       0.14 seconds
Overhead                0.66 seconds
----------------------------------------
Total                   0.87 seconds
```

Simulation completed