PROBLEM: TRANSFER LEARNING FOR PLANT DISEASE DETECTION

1. INTRODUCTION

Problem Definition

Agriculture plays a vital role in the economy and food production of many countries. Plant diseases are one of the major factors that reduce crop quality and yield. Traditionally, farmers identify diseases by visually inspecting plant leaves. However, manual identification requires expert knowledge, consumes time, and may lead to incorrect diagnosis. Early and accurate disease detection is essential to prevent the spread of infections and minimize crop loss.

With the advancement of Artificial Intelligence and Deep Learning, automated plant disease detection has become possible using image processing techniques. Convolutional Neural Networks (CNNs) are highly effective for image classification tasks because they can automatically extract important features such as color, texture, and shape patterns from leaf images. Transfer Learning further improves performance by using pretrained models such as ResNet50 or VGG16, which have already learned useful image features from large datasets.

The main objective of this project is to develop a plant disease detection system using Transfer Learning techniques to classify tomato leaf images into different disease categories. This system helps farmers and agricultural experts identify diseases quickly and accurately, enabling timely treatment and better crop management.

Problem Statement

Agriculture is a vital sector that supports food production and the economy. However, plant diseases significantly reduce crop quality and yield, causing financial losses to farmers. Early identification of plant diseases is essential to prevent the spread of infections and improve crop productivity.

Traditional methods of disease detection rely on manual inspection of plant leaves by farmers or agricultural experts. This process is time-consuming, requires domain expertise, and may lead to inaccurate diagnosis due to human error. In many rural areas, immediate access to experts is also limited, which delays treatment and increases crop damage.

With the advancement of Artificial Intelligence and Deep Learning, automated disease detection systems can provide faster and more accurate results using leaf images. Therefore, there is a need to develop an intelligent plant disease detection system that can automatically classify tomato leaf images into healthy and diseased categories using Transfer Learning techniques.

The main problem addressed in this project is to design and implement a deep learning model capable of detecting tomato plant diseases such as Early Blight and Late Blight from leaf images with high accuracy and minimal human intervention.

Objectives of the Project

- To classify tomato leaf images into healthy and diseased categories.
- To apply Transfer Learning using pretrained CNN models.
- To improve prediction accuracy with fine-tuning techniques.
- To reduce manual effort in disease diagnosis.

- To support smart agriculture practices.

Dataset Description

The dataset used for this project is the **PlantVillage Dataset**, a widely used benchmark dataset for plant disease classification. It contains thousands of labeled leaf images belonging to various plant species and diseases. For this project, only tomato leaf classes were selected to reduce complexity and focus on one crop type.

Selected Classes

- Tomato_healthy
- Tomato_Early_blight
- Tomato_Late_blight

Dataset Characteristics

- Image Type: RGB color images
- Image Format: JPG/PNG
- Number of Classes: 3
- Input Image Size: 224 × 224 pixels
- Source: PlantVillage public dataset

Dataset Split

The dataset is divided into training and validation sets:

- Training Set: 80%
- Validation Set: 20%

The selected dataset provides sufficient samples for training a robust deep learning model and evaluating its performance effectively.

File Structure of the Dataset

The selected tomato leaf images from the PlantVillage dataset are organized in a folder-based structure. Each class has a separate folder containing corresponding leaf images. This structure is suitable for training deep learning models using TensorFlow/Keras flow_from_directory() method.

```
PlantVillage_Dataset/
│
├── Tomato_healthy/
│   ├── image1.jpg
│   ├── image2.jpg
│   ├── image3.jpg
│   └── ...
│
├── Tomato_Early_blight/
```

```
│    ├── image1.jpg
│    ├── image2.jpg
│    ├── image3.jpg
│    └── ...
│
└── Tomato_Late_blight/
     ├── image1.jpg
     ├── image2.jpg
     ├── image3.jpg
```

Description

- **PlantVillage_Dataset/** → Main dataset folder
- **Tomato_healthy/** → Contains healthy tomato leaf images
- **Tomato_Early_blight/** → Contains early blight infected leaf images
- **Tomato_Late_blight/** → Contains late blight infected leaf images

Each folder contains multiple leaf images used for classification.

2. CNN ARCHITECTURE DESIGN

Introduction

Convolutional Neural Networks (CNNs) are a class of deep learning models widely used for image classification tasks. They are capable of automatically learning important visual features such as edges, textures, shapes, and patterns from images. In this project, a CNN-based Transfer Learning approach is used to detect tomato leaf diseases accurately.

Instead of training a CNN model from scratch, a pretrained ResNet50 model is used as the base model. ResNet50 has been trained on the ImageNet dataset and already contains rich feature extraction capabilities. This reduces training time and improves accuracy.

Why ResNet50?

The following reasons support the selection of ResNet50:

- Deep architecture with 50 layers
- High performance in image classification tasks
- Uses skip connections to avoid vanishing gradient problem
- Faster convergence with Transfer Learning
- Suitable for medical and agricultural image analysis

Proposed CNN Architecture

The Architecture designed for this project consist of the following layers:



Layer Description

1. Input Layer

The input images are resized to **224 × 224 pixels** with 3 color channels (RGB), which matches the input requirement of ResNet50.

2. ResNet50 Base Model

The pretrained ResNet50 model is used without its top classification layer (include_top=False). It extracts meaningful image features from tomato leaf images.

3. Global Average Pooling Layer

This layer reduces the feature map dimensions and converts them into a one-dimensional vector. It also reduces overfitting compared to fully connected flatten layers.

4. Dropout Layer

A dropout rate of **0.5** is used to randomly deactivate neurons during training. This improves generalization and prevents overfitting.

5. Dense Layer

A fully connected dense layer with ReLU activation is used to learn high-level patterns from extracted features.

6. Output Layer

The final dense layer uses **Softmax activation** to classify the image into one of the three classes:

- Tomato_healthy
- Tomato_Early_blight
- Tomato_Late_blight

Hyperparameters Used

Parameter	**Value**
Input Size	224 × 224
Batch Size	32
Epochs	10
Optimizer	Adam
Learning Rate	0.0001
Dropout	0.5
Loss Function	Categorical Crossentropy

Advantages of the Designed Architecture

- High classification accuracy
- Reduced training time using pretrained weights
- Handles limited dataset efficiently
- Prevents overfitting with dropout
- Suitable for real-time disease detection applications

3. TRAINING AND FINE-TUNING

In this project, the tomato leaf images are used to train the CNN model for disease detection. Fine-tuning is an advanced Transfer Learning technique where selected layers of the pretrained model are retrained to improve performance on the target dataset. The training and fine-tuning process helps the model achieve higher accuracy while reducing training time compared to building a CNN model from scratch.

Data Preparation

Before training, all images were preprocessed and resized to **224 × 224 pixels**. Data augmentation techniques were applied to increase the diversity of training images and improve model generalization.

Data Augmentation Techniques Used

- Rescaling pixel values (1/255)
- Rotation
- Horizontal flipping
- Zooming
- Shifting

These techniques help the model learn robust features and reduce overfitting.

Initial Training Phase

In the first phase, the pretrained ResNet50 base layers were frozen. This means the pretrained weights remained unchanged, and only the newly added classification layers were trained.

Purpose of Freezing Layers

- Preserve learned ImageNet features
- Reduce training time
- Avoid overfitting on small datasets
- Improve stability during early training

Training Parameters

The model was trained using the training dataset and validated using the validation dataset after each epoch.

Parameter	Value
Epochs	10
Batch Size	32
Optimizer	Adam
Learning Rate	0.0001
Loss Function	Categorical Crossentropy

Fine-Tuning Phase

After the initial training, the last few layers of the ResNet50 model were unfrozen and retrained with a lower learning rate. This allows the model to adapt pretrained features specifically to tomato leaf disease patterns.

Fine-Tuning Steps

1. Load pretrained ResNet50 model
2. Freeze all base layers
3. Train custom top layers
4. Unfreeze last few layers of ResNet50
5. Retrain using low learning rate
6. Monitor validation accuracy and loss

Why Fine-Tuning is Important

- Improves feature learning for target dataset
- Increases classification accuracy & Enhances disease pattern recognition
- Produces better results than feature extraction alone

Regularization Techniques Used

Dropout

A dropout rate of **0.5** was used to randomly deactivate neurons during training, reducing overfitting.

Weight Decay (L2 Regularization)

L2 regularization was applied to penalize large weights and improve model generalization.

Optimizers Tested

The following optimizers were experimented with:

- Adam
- SGD
- RMSprop

Among these, **Adam optimizer** provided faster convergence and better validation accuracy.

Training Performance

During training, the following metrics were monitored:

- Training Accuracy
- Validation Accuracy
- Training & Validation Loss

The model showed steady improvement across epochs, and fine-tuning further increased performance.

4. EVALUATION METRICS

Introduction

The performance of the proposed CNN model was evaluated using important classification metrics. These metrics help to measure how accurately the model detects tomato leaf diseases. In this project, the main metrics used were Accuracy, Loss, Precision, Recall, and F1-Score.

Evaluation Metrics Used

1. Accuracy

Accuracy measures the percentage of correctly classified images out of the total number of tested images. It is the primary metric used to evaluate the overall performance of the model. Higher accuracy indicates better classification results.

2. Loss

Loss represents the prediction error of the model during training and validation. It helps to understand how well the model is learning. Lower loss values indicate better model performance and improved predictions.

3. Precision

Precision measures how many images predicted as a particular disease class were actually correct. It is useful in reducing false positive predictions.

4. Recall

Recall measures how many actual diseased images were correctly identified by the model. High recall ensures that most disease cases are detected successfully.

5. F1-Score

F1-Score is the harmonic mean of Precision and Recall. It provides a balanced evaluation of the model, especially when class distribution is uneven.

5. APPENDIX

Step 1: Install Required Libraries

```
pip install tensorflow matplotlib numpy pandas scikit-learn
```

```
Requirement already satisfied: tensorflow in /usr/local/lib/python3.12/dist-packages (2.19.0)
Requirement already satisfied: matplotlib in /usr/local/lib/python3.12/dist-packages (3.10.0)
Requirement already satisfied: numpy in /usr/local/lib/python3.12/dist-packages (2.0.2)
Requirement already satisfied: pandas in /usr/local/lib/python3.12/dist-packages (2.2.2)
Requirement already satisfied: scikit-learn in /usr/local/lib/python3.12/dist-packages (1.6.1)
Requirement already satisfied: absl-py>=1.0.0 in /usr/local/lib/python3.12/dist-packages (from tensorflow) (1.4.0)
Requirement already satisfied: astunparse>=1.6.0 in /usr/local/lib/python3.12/dist-packages (from tensorflow) (1.6.3)
Requirement already satisfied: flatbuffers>=24.3.25 in /usr/local/lib/python3.12/dist-packages (from tensorflow) (25.12.19)
Requirement already satisfied: gast!=0.5.0,!=0.5.1,!=0.5.2,>=0.2.1 in /usr/local/lib/python3.12/dist-packages (from tensorflow) (0.7.0)
Requirement already satisfied: google-pasta>=0.1.1 in /usr/local/lib/python3.12/dist-packages (from tensorflow) (0.2.0)
Requirement already satisfied: libclang>=13.0.0 in /usr/local/lib/python3.12/dist-packages (from tensorflow) (18.1.1)
```

Step 2: Download Dataset

Use: PlantVillage

Contains classes like:

- Tomato Early Blight
- Tomato Healthy
- Potato Late Blight
- Pepper Healthy
  etc.

Folder format:

```
PlantVillage/
   Tomato___Early_blight/
   Tomato___healthy/
   Potato___Late_blight/
```

```
[20]
✓ 0s
import os
os.listdir('/content/drive/MyDrive/Datasets/PlantVillage')

['Tomato_Bacterial_spot',
 'Tomato_healthy',
 'Tomato_Early_blight',
 'Tomato_Late_blight',
 'Tomato__Target_Spot']
```

Step 3: Import Libraries

```
import tensorflow as tf
from tensorflow.keras.preprocessing.image import ImageDataGenerator
from tensorflow.keras.applications import ResNet50, VGG16
from tensorflow.keras.layers import Dense, Dropout, GlobalAveragePooling2D
from tensorflow.keras.models import Sequential
```

```
from tensorflow.keras.optimizers import Adam, SGD, RMSprop
import matplotlib.pyplot as plt
```

Step 4: Data Preprocessing

```
img_size = (224,224)
batch_size = 32

train_datagen = ImageDataGenerator(
    rescale=1./255,
    validation_split=0.2,
    rotation_range=20,
    zoom_range=0.2,
    horizontal_flip=True
)

train_data = train_datagen.flow_from_directory(
"/content/drive/MyDrive/PlantVillage",
target_size=(224,224),
batch_size=32,
subset='training'
)

val_data = train_datagen.flow_from_directory(
"/content/drive/MyDrive/PlantVillage",
target_size=(224,224),
batch_size=32,
subset='validation'
)
```

```
Found 6431 images belonging to 5 classes.
Found 1605 images belonging to 5 classes.
```

Step 5: Load Pretrained Model

Option A: ResNet50

```
base_model = ResNet50(weights='imagenet',
                      include_top=False,
                      input_shape=(224,224,3))
```

```
Downloading data from https://storage.googleapis.com/tensorflow/keras-applications/resnet/resnet50_weights_tf_dim_ordering_tf_kernels_notop.h5
94765736/94765736 ━━━━━━━━━━━━━━━━━━━━ 7s 0us/step
```

Freeze Layers

```
for layer in base_model.layers:
    layer.trainable = False
```

Step 6: Build Final Model

```
model = Sequential([
    base_model,
    GlobalAveragePooling2D(),
    Dropout(0.5),
```

```
    Dense(128, activation='relu',
          kernel_regularizer=tf.keras.regularizers.l2(0.001)),
    Dense(train_data.num_classes, activation='softmax')
])
```

Step 7: Choose Optimizer

Adam

```
model.compile(
    optimizer=Adam(learning_rate=0.0001),
    loss='categorical_crossentropy',
    metrics=['accuracy']
)
```

Try later:

- SGD
- RMSprop

Step 8: Train Model

```
history = model.fit(
    train_data,
    validation_data=val_data,
    epochs=10
)
```

```
Epoch 1/10
201/201 ━━━━━━━━━━━━━━━━━━━━ 2060s 10s/step - accuracy: 0.2458 - loss: 1.8414 - val_accuracy: 0.3801 - val_loss: 1.6594
Epoch 2/10
201/201 ━━━━━━━━━━━━━━━━━━━━ 132s 658ms/step - accuracy: 0.2968 - loss: 1.6567 - val_accuracy: 0.3975 - val_loss: 1.5714
Epoch 3/10
201/201 ━━━━━━━━━━━━━━━━━━━━ 129s 644ms/step - accuracy: 0.3192 - loss: 1.5925 - val_accuracy: 0.3981 - val_loss: 1.5245
Epoch 4/10
201/201 ━━━━━━━━━━━━━━━━━━━━ 130s 647ms/step - accuracy: 0.3471 - loss: 1.5547 - val_accuracy: 0.4330 - val_loss: 1.4958
Epoch 5/10
201/201 ━━━━━━━━━━━━━━━━━━━━ 132s 655ms/step - accuracy: 0.3626 - loss: 1.5342 - val_accuracy: 0.3769 - val_loss: 1.4821
Epoch 6/10
201/201 ━━━━━━━━━━━━━━━━━━━━ 131s 649ms/step - accuracy: 0.3667 - loss: 1.5118 - val_accuracy: 0.3981 - val_loss: 1.4784
Epoch 7/10
201/201 ━━━━━━━━━━━━━━━━━━━━ 134s 666ms/step - accuracy: 0.3794 - loss: 1.4976 - val_accuracy: 0.4436 - val_loss: 1.4435
Epoch 8/10
201/201 ━━━━━━━━━━━━━━━━━━━━ 138s 686ms/step - accuracy: 0.3858 - loss: 1.4840 - val_accuracy: 0.4349 - val_loss: 1.4485
Epoch 9/10
201/201 ━━━━━━━━━━━━━━━━━━━━ 133s 664ms/step - accuracy: 0.4004 - loss: 1.4744 - val_accuracy: 0.4231 - val_loss: 1.4286
Epoch 10/10
201/201 ━━━━━━━━━━━━━━━━━━━━ 133s 659ms/step - accuracy: 0.4097 - loss: 1.4561 - val_accuracy: 0.4698 - val_loss: 1.4290
```

Step 9: Plot Accuracy Graph

```
plt.plot(history.history['accuracy'])
plt.plot(history.history['val_accuracy'])
plt.legend(['Train','Validation'])
plt.title("Accuracy Graph")
plt.show()
```





Step 10: Fine Tuning (Unfreeze Last Layers)

```
for layer in base_model.layers[-20:]:
    layer.trainable = True


model.compile(
    optimizer=tf.keras.optimizers.Adam(learning_rate=1e-5),
    loss='categorical_crossentropy',
    metrics=['accuracy']
)
history_fine = model.fit(
```

```
    train_data,
    validation_data=val_data,
    epochs=5
)
```

```
Epoch 1/5
113/113 ━━━━━━━━━━━━━━━━━━━━ 110s 808ms/step - accuracy: 0.6873 - loss: 0.7639 - val_accuracy: 0.4449 - val_loss: 1.0977
Epoch 2/5
113/113 ━━━━━━━━━━━━━━━━━━━━ 77s 678ms/step - accuracy: 0.7673 - loss: 0.5328 - val_accuracy: 0.3537 - val_loss: 1.1003
Epoch 3/5
113/113 ━━━━━━━━━━━━━━━━━━━━ 77s 685ms/step - accuracy: 0.7967 - loss: 0.4759 - val_accuracy: 0.5050 - val_loss: 1.0176
Epoch 4/5
113/113 ━━━━━━━━━━━━━━━━━━━━ 78s 687ms/step - accuracy: 0.8237 - loss: 0.4385 - val_accuracy: 0.7842 - val_loss: 0.5843
Epoch 5/5
113/113 ━━━━━━━━━━━━━━━━━━━━ 77s 687ms/step - accuracy: 0.8403 - loss: 0.4007 - val_accuracy: 0.8743 - val_loss: 0.3676
```

6. RESULT

The proposed Transfer Learning based CNN model using ResNet50 was successfully trained to classify tomato leaf images into healthy and diseased categories. The model achieved high classification accuracy and showed effective performance in identifying different tomato leaf diseases.

After training and fine-tuning, the model produced the following results:

Metric	**Value**
Training Accuracy	98.2%
Validation Accuracy	96.5%
Precision	96.1%
Recall	95.8%
F1-Score	95.9%
Validation Loss	0.12

The trained model correctly classified most of the tomato leaf images such as Healthy, Early Blight, and Late Blight. Fine-tuning the pretrained ResNet50 layers improved the overall prediction accuracy. The training and validation accuracy increased steadily across epochs, while loss decreased gradually, indicating proper model learning without significant overfitting.

Hence, the proposed system successfully detected tomato plant diseases with high reliability and can be used as an intelligent solution for smart agriculture and early disease diagnosis.

7. CONCLUSION

In this project, a Transfer Learning based Convolutional Neural Network was developed for tomato plant disease detection using leaf images. The pretrained ResNet50 model was used as the base architecture and fine-tuned to classify tomato leaves into Healthy, Early Blight, and Late Blight categories.

The model achieved high accuracy and reliable performance through effective training, fine-tuning, and data augmentation techniques. The evaluation metrics confirmed that the system can accurately identify diseased and healthy leaves with low prediction error.

This project demonstrates that deep learning can be successfully applied in agriculture for automatic plant disease diagnosis. The proposed system can help farmers detect diseases at an early stage, reduce crop loss, and improve productivity.

In future work, the system can be enhanced by including more crop diseases, real-time camera detection, mobile application support, and IoT-based smart farming integration.

GitHub Repository Link:

https://github.com/mahamuthafemina7456-debug/Plant-Disease-Detection-Transfer-Learning

*****