

SIMATS ENGINEERING

ASSESSMENT TOOL 1

COURSE NAME: COMPUTER NETWORKS
COURSE CODE: CSA0716

COURSE OUTCOME COVERED

CO2: Configure IP addressing schemes, subnetting, and basic routing techniques using simulation tool, for efficient network design and topology. (BL3)

Assessment Tool Weightage: 40%

Annexure A

ANALYTICAL PROBLEM SOLVING

1. A university network is assigned the IP address block 192.168.20.0/24 for its internal communication. The network administrator has decided to divide this network into subnets for three different labs using fixed subnet masks. Lab A is assigned a /26 subnet, Lab B is assigned a /27 subnet, and Lab C is assigned a /28 subnet. Based on the given subnet masks, apply subnetting concepts to determine the network address of each lab. Further, identify the valid range of host IP addresses and the broadcast address for each subnet. Finally, calculate the total number of usable host IP addresses available in each lab's subnet.

2. A network administrator has configured two systems with the following details: System 1 has IP address 192.168.1.130 with subnet mask 255.255.255.192, and System 2 has IP address 192.168.1.190 with subnet mask 255.255.255.192. Using the given configuration, apply subnetting techniques to determine the subnet range, network address, and broadcast address for each system. Identify the valid host IP range for both subnets based on the given subnet mask. Calculate whether

each IP address falls within its respective subnet range. Also, determine the number of usable host addresses available in each subnet.

3. An organization has been allocated the IP block **172.16.0.0/16** for its internal network. The network administrator has already decided the subnet masks for each department as follows: HR → /25, Sales → /26, IT → /27, and Admin → /28. Using the given subnet masks, apply subnetting techniques to assign suitable subnet addresses for each department. Determine the network address, valid host IP range, and broadcast address for each subnet. Based on the allocation, calculate the number of usable host addresses in each department. Finally, identify the remaining unused IP address range within the given network block.

4. A company uses the IP address **172.16.10.0/24** and has implemented subnetting using a **/27 subnet mask** for its internal departments. Using the given subnet mask, apply subnetting techniques to calculate the total number of subnets created and the number of usable hosts per subnet. Determine the subnet to which the IP address **172.16.10.78** belongs. Identify the network address and broadcast address for that subnet. Also, determine whether the IP address **172.16.10.95** falls within the same subnet range based on the given configuration.

5. A network uses the Internet Protocol version 6 address **2001:0db8:0000:0000:ff00:0042:8329**. Apply IPv6 addressing rules to compress the given address into its shortest form and then expand the compressed address back to its full notation. Using a prefix length of **/64**, determine the network prefix of the given address. Also, calculate the total number of possible host addresses available within this network based on the given prefix length.

Answers

1.

Subnetting of 192.168.20.0/24

Given Network: 192.168.20.0/24

Allocate subnets from the beginning of the network in order:

Lab	Subnet Mask	Network Address	Valid Host Range	Broadcast Address	Usable Hosts
Lab A	/26 (255.255.255.192)	192.168.20.0	192.168.20.1 – 192.168.20.62	192.168.20.63	62
Lab B	/27 (255.255.255.224)	192.168.20.64	192.168.20.65 – 192.168.20.94	192.168.20.95	30
Lab C	/28 (255.255.255.240)	192.168.20.96	192.168.20.97 – 192.168.20.110	192.168.20.111	14

Host Calculations

- /26
 - Total addresses = 64
 - Usable = $64 - 2 = 62$
- /27
 - Total addresses = 32
 - Usable = $32 - 2 = 30$
- /28
 - Total addresses = 16
 - Usable = $16 - 2 = 14$

2.

Subnet Analysis :

Subnet Mask = 255.255.255.192 (/26)

A /26 subnet has:

- Block size = 64
- Subnets:
 - 192.168.1.0–63
 - 192.168.1.64–127
 - 192.168.1.128–191
 - 192.168.1.192–255

System 1

IP: 192.168.1.130

Falls in subnet 128–191

- Network Address: 192.168.1.128
- Host Range: 192.168.1.129 – 192.168.1.190
- Broadcast: 192.168.1.191
- Usable Hosts: 62

Verification

192.168.1.130 lies between 129 and 190.

Therefore, it is a valid host address.

System 2

IP: 192.168.1.190

Also lies in subnet 128–191

- Network Address: 192.168.1.128
- Host Range: 192.168.1.129 – 192.168.1.190
- Broadcast: 192.168.1.191
- Usable Hosts: 62

Verification

192.168.1.190 is the last usable host.

Therefore, it is valid.

Summary

System	IP Address	Network	Host Range	Broadcast	Valid?	Usable Hosts
System 1	192.168.1.130	192.168.1.128	129–190	191	Yes	62
System 2	192.168.1.190	192.168.1.128	129–190	191	Yes	62

3.

Subnetting 172.16.0.0/16

Given Network:

172.16.0.0/16

Assign sequentially.

Department	Prefix	Network Address	Host Range	Broadcast	Usable Hosts
HR	/25	172.16.0.0	172.16.0.1 – 172.16.0.126	172.16.0.127	126
Sales	/26	172.16.0.128	172.16.0.129 – 172.16.0.190	172.16.0.191	62
IT	/27	172.16.0.192	172.16.0.193 – 172.16.0.222	172.16.0.223	30
Admin	/28	172.16.0.224	172.16.0.225 – 172.16.0.238	172.16.0.239	14

Remaining Unused Address Range

Allocated addresses:

- 172.16.0.0 – 172.16.0.239

Remaining in first /24:

- 172.16.0.240 – 172.16.0.255

Remaining in the /16 network:

- 172.16.1.0 – 172.16.255.255

4.

Subnetting 172.16.10.0/24 Using /27

Given:

Network = 172.16.10.0/24

Subnet Mask = /27

Total Subnets

Borrowed bits:

$$27 - 24 = 3$$

Subnets:

$$2^3 = 8$$

Total subnets = 8

Hosts Per Subnet

Host bits:

$$32 - 27 = 5$$

Total addresses:

$$2^5 = 32$$

Usable hosts:

$$32 - 2 = 30$$

Usable hosts = 30

Subnet List

Network	Host Range	Broadcast
172.16.10.0	1–30	31
172.16.10.32	33–62	63
172.16.10.64	65–94	95
172.16.10.96	97–126	127
172.16.10.128	129–158	159
172.16.10.160	161–190	191
172.16.10.192	193–222	223
172.16.10.224	225–254	255

IP Address 172.16.10.78

Falls in:

172.16.10.64/27

- Network Address = 172.16.10.64
- Host Range = 172.16.10.65 – 172.16.10.94
- Broadcast = 172.16.10.95

Does 172.16.10.95 Belong to Same Subnet?

No.

172.16.10.95 is the broadcast address of subnet 172.16.10.64/27, so it cannot be assigned to a host.

Summary

- Total Subnets = 8
- Hosts per Subnet = 30
- IP 172.16.10.78 belongs to 172.16.10.64/27
- Network Address = 172.16.10.64
- Broadcast Address = 172.16.10.95
- 172.16.10.95 is the broadcast address, not a valid host.

5.

IPv6 Addressing

Given IPv6 Address:

2001:0db8:0000:0000:0000:ff00:0042:8329

(a) Compressed Form

Rules:

- Remove leading zeros.
- Replace the longest consecutive sequence of zero groups with ::.

Compressed address:

2001:db8::ff00:42:8329

(b) Expanded Form

Expanded back to full notation:

2001:0db8:0000:0000:0000:ff00:0042:8329

(c) Network Prefix (/64)

Prefix length = /64

First 64 bits:

2001:0db8:0000:0000::/64

(d) Total Host Addresses

Host bits:

$128 - 64 = 64$

Total possible interface addresses:

$$2^{64} = 18,446,744,073,709,551,616$$

Approximately 18.4 quintillion host addresses.

Final Summary

Question Key Result

- 1 Lab A: 62 hosts, Lab B: 30 hosts, Lab C: 14 hosts
- 2 Both systems belong to subnet 192.168.1.128/26 with 62 usable hosts
- 3 HR: 126 hosts, Sales: 62, IT: 30, Admin: 14; remaining addresses: 172.16.0.240–172.16.255.255
- 4 8 subnets, 30 usable hosts/subnet; 172.16.10.78 belongs to 172.16.10.64/27; 172.16.10.95 is the broadcast address
- 5 Compressed IPv6: 2001:db8::ff00:42:8329; Network Prefix: 2001:db8:0:0::/64; Hosts: $2^{64} = 18,446,744,073,709,551,616$

RUBRICS FOR CALCULATION

Criteria	Weightage	Level 4 (Exemplary)	Level 3 (Proficient)	Level 2 (Developing)	Level 1 (Beginning)
Problem Understanding	20%	Clearly interprets problem, identifies all parameters and requirements accurately	Understands problem with minor gaps	Partial understanding; misses key elements	Misinterprets or unable to understand problem
Method Selection	20%	Selects most appropriate method/formula with strong justification	Selects correct method with minor errors	Inappropriate or partially correct method	Unable to select method
Solution Process	25%	Logical, systematic steps with correct approach throughout	Mostly correct steps with minor mistakes	Disorganized steps; multiple errors	No clear process

Accuracy of Calculation	20%	All calculations accurate; correct final answer	Minor calculation errors	Frequent errors; incorrect final answer	No valid calculations
Interpretation of Results	15%	Clearly interprets results with units and engineering relevance	Basic interpretation with minor omissions	Limited or unclear interpretation	No interpretation