

REFERENCE NO.

MTI/DSBP/2026/001

15 / 09 / 2026

DATA SECURITY & BACKUP PLAN

Mahaprabhu Tech Innovation Private Limited | Version 1.2 | Supabase Backup & Replication Integration

Document Reference	MTI/DSBP/2026/001
Version	1.2 - formatted on official company letterhead; Supabase automatic backup, PITR and replication process included
Effective Date	15 September 2026
Document Owner	Management / Information Security & Technology Team
Applicability	Company-managed web, mobile, API, database, GPS/location and cloud systems, including Supabase-hosted production databases
Review Cycle	At least annually and after any major security, infrastructure, provider or architecture change

1. Purpose

This plan defines the minimum data-security, backup, recovery and incident-response controls to be followed for systems developed, hosted or operated by Mahaprabhu Tech Innovation Private Limited. Its objective is to protect confidentiality, integrity and availability of operational and user data while ensuring that critical services can be restored after accidental deletion, hardware failure, cyber incident or service disruption.

2. Scope

- Production, staging and administrative web applications and mobile applications.
- Application APIs, databases, file/object storage, GPS or location data and system logs.
- Cloud infrastructure, hosting accounts, source-code repositories and deployment configurations.
- Supabase Postgres databases, project settings, backups, Point-in-Time Recovery (PITR), read replicas and Storage buckets where used.
- Company employees, administrators, developers, authorized vendors and support personnel with system access.

3. Security Principles

Least privilege	Users and administrators receive only the access required for their assigned duties.
Defense in depth	Identity, application, database, network, backup and monitoring controls are applied in layers.
Need-to-know handling	Sensitive records are exposed only to authorized roles and legitimate operational processes.
Secure recovery	Backups are protected, independently retained and routinely tested for restoration.

REFERENCE NO.

MTI/DSBP/2026/001

15 / 09 / 2026

DATA SECURITY CONTROLS

4. Identity & Access Management

- Role-based access control (RBAC) shall be used for administrative, medical/operations, support and development functions where applicable.
- Multi-factor authentication shall be enabled for privileged cloud, repository and administrative accounts wherever supported.
- Shared administrator accounts are avoided. Access is issued to named individuals and reviewed periodically.
- Access for resigned, transferred or inactive personnel shall be revoked promptly. Privileged credentials and API keys shall be rotated after suspected exposure.
- Supabase dashboard access, service-role keys, database credentials and access tokens shall be restricted to authorized technical personnel.

5. Data Protection & Encryption

- Data in transit shall use HTTPS/TLS. Administrative access shall use encrypted channels and trusted devices.
- Sensitive data at rest shall use encryption provided by the operating system, database, storage or cloud platform where available.
- Passwords shall never be stored in plain text. Authentication secrets and OTP-related values shall be protected using secure hashing or equivalent controls.
- API keys, database passwords and service credentials shall be kept outside source code in environment/secret-management controls.
- Only data required for the service shall be collected and retained. Sensitive values shall be masked in logs and support screenshots where practical.
- Supabase Row Level Security (RLS) policies shall be enabled and tested for tables exposed through client-facing APIs where the application architecture requires direct client access.

6. Application, Network & Infrastructure Security

- Production and development environments shall be separated, with restricted production access and controlled deployment procedures.
- Security patches for operating systems, frameworks, libraries and server software shall be reviewed and applied based on risk and urgency.
- Public APIs shall use authentication, authorization, validation and rate-limiting controls appropriate to the service.
- Database and administrative services shall not be exposed publicly unless technically required and protected by strong access controls.
- Secure development practices shall include code review, input validation, error handling, dependency review and testing against common web/mobile risks.

7. Monitoring, Logs & Audit Trail

- Authentication, privileged actions, critical data changes, deployment events, backup failures and major application errors shall be logged where technically feasible.
- Logs shall be time-stamped, access-restricted and retained long enough to support operational troubleshooting, security investigation and contractual requirements.
- High-risk events such as repeated login failures, unusual privileged activity, backup failures, replication lag or infrastructure downtime should generate alerts for review.

REFERENCE NO.

MTI/DSBP/2026/001

15 / 09 / 2026

BACKUP, RETENTION & DISASTER RECOVERY

8. Backup Strategy

The company shall follow a 3-2-1-oriented backup approach where practical: maintain multiple copies of critical information, use more than one storage location or storage class, and keep at least one logically separate or off-account recovery copy for major incidents. Backup data must be encrypted and access-restricted.

Asset / Data	Backup Frequency	Retention Target	Priority
Primary production database	Automated daily backup; PITR or frequent incremental recovery where supported	Policy target: 30 days daily; 8 weeks weekly; 12 months monthly. If provider retention is shorter, supplement with external exports.	Critical
Uploaded files / object storage	Daily incremental/snapshot, versioning or scheduled copy	30-90 days based on project requirement	High
Source code	Every committed change in private version-control repository	Full repository history; protected branches/tags	High
Configuration / deployment records	On each approved change; encrypted export after material changes	Minimum 90 days plus current baseline	High
System and security logs	Continuous collection where supported; periodic archive	30-180 days based on operational/contract need	Medium
Off-account / disaster copy	At least monthly for critical production data	Minimum 3 monthly generations	Critical

9. Recovery Objectives & Restore Testing

- Critical systems target Recovery Point Objective (RPO): up to 4 hours where platform capabilities permit; otherwise the latest successful scheduled backup.
- Critical systems target Recovery Time Objective (RTO): within 8 hours after infrastructure access is available, subject to incident severity and external-provider availability.
- Backup-job status shall be checked automatically where supported, and failures shall be investigated without waiting for a restore request.
- A sample restore test shall be performed at least quarterly for critical databases/files. Results, issues and corrective actions shall be documented.

Backup Integrity Rule: A backup is not considered reliable merely because the job completed. It is considered usable only when the company can verify the backup, protect it from unauthorized change, and successfully restore representative data during periodic testing.

REFERENCE NO.

MTI/DSBP/2026/001

15 / 09 / 2026

INCIDENT RESPONSE & GOVERNANCE

10. Security Incident & Recovery Procedure

Step	Action
1. Detect & Record	Open an incident record with time, affected system, reporter, observed symptoms and initial severity.
2. Contain	Restrict compromised accounts, keys, endpoints or services while preserving necessary evidence and logs.
3. Assess	Determine affected data, attack path or failure cause, business impact and whether backup restoration is required.
4. Recover	Restore from the most recent verified clean backup, rotate exposed credentials, patch the root cause and validate service operation.
5. Notify & Review	Notify the relevant client/department and authorities when required by contract or applicable law. Complete root-cause analysis and preventive actions.

11. Roles & Responsibilities

Role	Primary Responsibility
Management	Approve policy, assign responsible personnel, review major incidents and business-continuity risks.
Technology / Development	Secure coding, deployment controls, patching, secrets protection, backup configuration and recovery support.
System / Cloud Administrator	Account security, infrastructure hardening, monitoring, backup-job checks, Supabase replication/PITR checks and restore execution.
Project / Department Administrator	Use authorized accounts, protect credentials, report suspicious activity and follow data-access rules.
Authorized Vendors	Meet contractual security requirements and receive only limited access necessary for the assigned service.

12. Review, Compliance & Continuous Improvement

- This plan shall be reviewed at least once every 12 months and after a major incident, platform migration, material architecture change or new contractual security requirement.
- The company shall maintain evidence of backup checks, restore tests, access reviews and incident actions appropriate to project size and risk.
- This document describes company security controls and targets; it does not represent an ISO, SOC or other external certification unless a separate valid certificate has been issued.

REFERENCE NO.


MTI/DSBP/2026/001

15 / 09 / 2026

SUPABASE AUTOMATIC BACKUP & REPLICATION PROCESS

13. Supabase Production Data Protection Architecture

Where a Mahaprabhu Tech Innovation project uses Supabase for production data, the following layered process shall be used. Read replicas improve read availability and performance, but they are not treated as a substitute for independently retained backups.



14. Automatic Backup / PITR Process

Control	Supabase behavior / company process
Daily automated backups	For Pro, Team and Enterprise projects, Supabase automatically creates daily database backups. Provider retention depends on the active plan and must be checked in the project settings.
Point-in-Time Recovery (PITR)	For projects needing a lower RPO, enable PITR where plan/compute requirements are met. PITR provides much finer restore-point granularity than a once-daily backup.
External logical backup	Schedule a company-controlled logical export (for example, Supabase CLI db dump / pg_dump) to encrypted storage in a separate account/location. This supports company retention targets when provider retention is shorter.
Storage objects	Database backups cover database records and Storage metadata but do not by themselves restore deleted file objects. Critical uploaded files therefore require a separate object backup/versioning/copy process.

Company implementation rule: If the active Supabase plan provides less than the company policy retention target, the Technology Team shall keep additional encrypted exports or off-account copies to meet the required retention period.

REFERENCE NO.

MTI/DSBP/2026/001

15 / 09 / 2026

SUPABASE REPLICATION, RESTORE & MONITORING

15. Read Replica Process

- **Primary database:** receives normal application reads and writes.
- **Read replica:** is a read-only database kept synchronized with the Primary using asynchronous replication; a small replication lag can exist.
- **Replication method:** the platform uses PostgreSQL replication mechanisms and WAL-based recovery infrastructure. Read replicas are availability/performance tools, not backup replacements.
- **Use:** send suitable read-heavy reporting/analytics requests to a replica and keep create/update/delete operations on the Primary.
- **Monitoring:** review replication lag and replica health in the available infrastructure/database monitoring views. Alert and investigate if lag exceeds application tolerance.
- **Prerequisite check:** confirm the active Supabase plan, compute size, PostgreSQL version and infrastructure eligibility before enabling read replicas.

16. Supabase Restore Procedure

Step	Recovery action
1. Declare incident	Record affected project, time window, suspected cause and whether database, Storage objects, credentials or application code are impacted.
2. Stop harmful writes	Temporarily disable affected jobs/endpoints or place the application in maintenance mode when needed to prevent additional corruption.
3. Select restore point	Choose the latest known-good Daily Backup or PITR timestamp before the incident.
4. Restore database	Use the Supabase recovery process. Plan for project downtime during a restore and validate the database after completion.
5. Recover Storage objects	Restore required objects from the separate object-storage backup/versioning process because database restore alone does not restore deleted Storage objects.
6. Recreate dependencies	Re-check replication/integrations, secrets and external jobs as required after restore. Re-deploy read replicas if they were affected by recovery.
7. Validate and reopen	Run integrity checks, test critical app flows, compare record counts, verify authentication, then reopen service under monitoring.

17. Operational Checklist

Frequency	Required check
Daily	Confirm project availability; review backup/PITR status; review failed jobs and security alerts.
Weekly	Review privileged access, project configuration changes and unusual database/security events.
Monthly	Create/verify off-account logical export for critical projects; verify Storage object-copy job; review retention.
Quarterly	Perform a documented restore test using representative data; record RPO/RTO achieved and corrective actions.
After major change	Re-check backup coverage, RLS/security policies, replica status, monitoring and recovery documentation.

18. Approval

This Data Security & Backup Plan, including the Supabase automatic backup, off-account copy, replication monitoring and recovery controls, is approved for implementation within applicable company-managed systems.

For MAHAPRABHU TECH INNOVATION PRIVATE LIMITED

Authorized Signatory

Name / Designation: _____

Date: _____