

Rubia Gandhi

MSREPORT_edited.docx

 Sri Ramakrishna Engineering College

Document Details

Submission ID**trn:oid:::3117:454911528****Submission Date****May 2, 2025, 1:35 PM GMT+5:30****Download Date****May 2, 2025, 1:37 PM GMT+5:30****File Name****MSREPORT_edited.docx****File Size****3.3 MB****75 Pages****11,679 Words****71,266 Characters**

8% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

Match Groups

-  **90** Not Cited or Quoted 8%
Matches with neither in-text citation nor quotation marks
-  **0** Missing Quotations 0%
Matches that are still very similar to source material
-  **5** Missing Citation 0%
Matches that have quotation marks, but no in-text citation
-  **0** Cited and Quoted 0%
Matches with in-text citation present, but no quotation marks

Top Sources

- 5%  Internet sources
- 6%  Publications
- 0%  Submitted works (Student Papers)

Integrity Flags

0 Integrity Flags for Review

No suspicious text manipulations found.

Our system's algorithms look deeply at a document for any inconsistencies that would set it apart from a normal submission. If we notice something strange, we flag it for you to review.

A Flag is not necessarily an indicator of a problem. However, we'd recommend you focus your attention there for further review.

Match Groups

-  **90 Not Cited or Quoted 8%**
Matches with neither in-text citation nor quotation marks
-  **0 Missing Quotations 0%**
Matches that are still very similar to source material
-  **5 Missing Citation 0%**
Matches that have quotation marks, but no in-text citation
-  **0 Cited and Quoted 0%**
Matches with in-text citation present, but no quotation marks

Top Sources

- 5%  Internet sources
- 6%  Publications
- 0%  Submitted works (Student Papers)

Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

1	Internet	www2.mdpi.com	<1%
2	Internet	habrahabr.info	<1%
3	Publication	Chang-Hui Hu, Yang Zhang, Fei Wu, Xiao-Bo Lu, Pan Liu, Xiao-Yuan Jing. "Toward ...	<1%
4	Publication	Keji Chen, Takuma Yamaguchi, Hiroyuki Okuda, Tatsuya Suzuki, Xuexun Guo. "Re...	<1%
5	Internet	www.coursehero.com	<1%
6	Internet	trid.trb.org	<1%
7	Internet	mkinventions.blogspot.com	<1%
8	Publication	Nathan, Gokul. "Examination of Drone Localization Performance With Commercia...	<1%
9	Internet	ccat.umtri.umich.edu	<1%
10	Internet	wokwi.com	<1%

11	Internet	www.semanticscholar.org	<1%
12	Publication	Tao Wang, Yuzhi Chen, Xingchen Yan, Wenying Li, Dong Shi. "Assessment of Driv...	<1%
13	Internet	jungo.com	<1%
14	Publication	Rishabha Malviya, Selcan Karakuş, Mukesh Roy. "Embedded Systems for Biomed...	<1%
15	Internet	www.docstoc.com	<1%
16	Internet	www.amrita.edu	<1%
17	Publication	Handbook of Intelligent Vehicles, 2012.	<1%
18	Publication	Coelingh, Erik, Andreas Eidehall, and Mattias Bengtsson. "Collision Warning with ...	<1%
19	Internet	fabacademy.org	<1%
20	Publication	Mahmudul Hasan, Zannatul Mifta, Nafisa Atia Salsabil, Sumaiya Janefar Papiya et ...	<1%
21	Publication	Shamsher Ali, Syed Muhammad Daniyal Gillani, Syed Muhammad Zain, Sudais Ah...	<1%
22	Publication	Zhou, Yupeng. "Design and Deployment of a Real-World Autonomous Driving Tes...	<1%
23	Internet	circuitdigest.com	<1%
24	Internet	ijsrst.com	<1%

25	Internet	www.mdpi.com	<1%
26	Publication	"HCI in Mobility, Transport, and Automotive Systems", Springer Science and Busi...	<1%
27	Publication	Jen-Tsung Chen. "Plant High-Throughput Phenotyping and Functional Phenomics...	<1%
28	Internet	community.intel.com	<1%
29	Internet	e6b.modelcrop.org	<1%
30	Internet	vti.diva-portal.org	<1%
31	Publication	Handbook of Driver Assistance Systems, 2016.	<1%
32	Internet	manualsnet.com	<1%
33	Internet	www.mobilityoutlook.com	<1%
34	Internet	researchrepository.universityofgalway.ie	<1%
35	Internet	text-id.123dok.com	<1%
36	Internet	www.jetir.org	<1%
37	Publication	Diego Galar, Uday Kumar, Dammika Seneviratne. "Robots, Drones, UAVs and UGV...	<1%
38	Internet	bharatgodigital.com	<1%

39	Internet	www.wiseguyreports.com	<1%
40	Publication	Hiroaki Hayashi, Mitsuhiro Kamezaki, Shigeki Sugano. "Toward Health-Related A...	<1%
41	Internet	www.researchsquare.com	<1%
42	Publication	Dileep Kumar Gupta, Abhay Kumar Singh. "GNSS Applications in Earth and Space ...	<1%
43	Publication	Dimitris Milakis, Bart van Arem, Bert van Wee. "Policy and society related implica...	<1%
44	Publication	Himanshu J. Patel. "Handbook for Chemical Process Industries", CRC Press, 2023	<1%
45	Publication	Wenfeng Guo, Jun Li, Xiaolin Song, Weiwei Zhang. "A game-theoretic driver steeri...	<1%
46	Publication	Xuan Li, Rui Song, Junfeng Fan, Mingyang Liu, Fei-Yue Wang. "Development and T...	<1%
47	Internet	lindseyresearch.com	<1%
48	Internet	rajeevnv3.hubpages.com	<1%
49	Internet	vdocuments.mx	<1%
50	Internet	www.edmunds.com	<1%
51	Publication	CHUNYAN LI. "Record Weather Data with Arduino and Solar Power", Springer Scie...	<1%
52	Publication	Pawan Singh, Sudesh Kumar, Sachin Kumar Gupta, Abhay Kumar Rai, Abdu Saif. "...	<1%

53

Publication

Rajesh Singh, Anita Gehlot, Bhupendra Singh, Sushabhan Choudhury. "Arduino-B... <1%

54

Publication

Martin Rosenberger, Manfred Plochl, Klaus Six, Johannes Edelmann. "The Dynam... <1%

ABSTRACT

Driver Monitoring Systems (DMS) and Advanced Driver Assistance Systems (ADAS) are critical technologies in modern vehicles, aimed at enhancing road safety and improving the driving experience. This paper explores the integration and effectiveness of DMS and ADAS in performing two key actions: **driver alertness detection** and **automatic Indication**.

The first action focuses on the DMS, which utilizes various sensors and algorithms to monitor the driver's behavior, including eye movements, head position, and facial expressions, to assess levels of alertness and fatigue. The system can provide warnings or take corrective actions, such as slowing down the vehicle or activating autonomous driving features if signs of drowsiness or distraction are detected. The second action emphasizes the role of ADAS includes **Blinking system**.

By using advanced sensors, such as radar, lidar, and cameras, ADAS continuously scans the road ahead for potential hazards. When an imminent collision is detected, the system can autonomously apply the brakes to prevent or mitigate the impact, reducing the likelihood of accidents. This abstract outlines the synergy between DMS and ADAS in enhancing vehicle safety by monitoring driver behavior and responding to external threats. The integration of these technologies represents a significant step toward fully autonomous driving, where human error is minimized, and road safety is maximized.

Keywords: ADAS, DMS, Lidar, radar

LIST OF FIGURES

Figure No	Figure Title
3.1.2	Limitations of the Existing system
3.2.3	System Analysis
3.2.4	Work Flow
6.2.1	System Architecture
8.1.1	Vehicle indication module
8.1.2	Drowsiness detection module
8.1.3	Feedback mechanism efficiency
8.1.4	Key observations
8.2.1	Display the Accuracy Score
8.2.2	Feedback Graph in ML
8.3.1	System analysis performance

LIST OF TABLES

Table No	Table Title
8.3	Comparison of Results

LIST OF ABBREVIATION

Abbreviation	Full Form
ADAS	Advanced Driver Assistance System
DMS	Data Monitoring System
AI	Artificial Intelligence
ML	Machine Learning
UI	User Interface
API	Application Programming Interface

GPS	Global Positioning System
GNSS	Global Navigation Satellite System
IoT	Internet of Things
LCD	Liquid Crystal Display
LED	Light Emmiting Diode
HCI	Human-Computer Interaction
PL	Programming Language

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ACKNOWLEDGEMENT	i
	ABSTRACT	ii
	LIST OF TABLES	iii
	LIST OF FIGURES	
	LIST OF ABBREVIATIONS	
1	INTRODUCTION	1
	1.1 VEHICLE AUTO-TRUN SYSTEM	
	DROWSINESS DETECTION	
	1.2 OVERVIEW OF THE PROJECT	
	1.3 PROBLEM STATEMENT	3
2	LITERATURE SURVEY	4
	2.1 DENSE REINFORCEMENT	
	LEARNING FOR SAFETY	
	VALIDATION OF	
	AUTONOMOUS VEHICLES	
	2.2 ELECTRIC VEHICLE INTEGRATION	5
	INTO MODERN NETWORKS	

2.3 COORDINATED APAPTIVE CRUISE

CONTROL WITH LANE-CHANGE 6

ASSISTANCES

2.4 COLLISION WARNING WITH FULL

AUTO AND PEDESTRIAN DETECTION 7

A PRACTICAL EXAMPLE OF

AUTOMATIC EMERGENCY BRAKING

2.5 A TRUSTWORTHY INTRENET

OF VEHICLES:THE DAO TO SAFE, 8

SECURE AND COLLABORATIVE

AUTONOMOUS DRIVING

2.6 INREGRATION OF GNSS PRECISE POINT

AND REDUCED INERTIAL SENSOR 9

2.7 ASSESSMENT OF DRIVER'S

COMPREHENSIVE DRIVING 10

2.8 TOWARD DRIVER FACE RECOGNITION

IN THE INTELLIGENT TRAFFIC 11

MONITORING SYSTEM

2.9 SUPERVISOR AND CONTROL

INVESTIGATION IN SMART/

AUTONOMOUS VEHICLES:

12

ENVIRONMENT VEHICLE AND

OBJECT DETECTION ADAS

APPLICATION

2.10 EMOTIONALLY ADAPTIVE

DRIVER VOICE ALERT FOR

13

ADVANCED DRIVER ASSISTANCE

DRIVER(ADAS)

3

SYSTEM ANALYSIS

14

3.1 EXISTING SYSTEM

3.1.1 KEY FEATURES OF THE

EXISTING SYSTEM

3.1.2 LIMITATIONS

15

3.2 PROPOSED SYSTEM

17

3.2.1 REAL-TIME INNOVATION

3.2.2 KEYLANDMARK CRITERIA

3.2.3 SYSTEM ANALYTICS

18

3.2.4 FLOW CHART

19

48

	3.2.5 INNOVATION	20
4	SYSTEM SPECIFICATION	21
	4.1 HARDWARE REQUIREMENTS	
	4.1.1 SPECIFICATIONS AND RATINGS	
	4.1.2 METHODOLOGY	
5	5.1 HARDWARE DESCRIPTION	22
	5.2 TECHNOLOGIES USED	
	5.2.1 SYSTEM VALIDATION	23
	5.2.2 MODES OF OPERATION	
	5.2.3 INTEGRATION OF DROWSINESS	24
	AND INDICATION USING API	
	5.2.4 DESIGN AND IMPLEMENTATION	25
	5.3 ADVANTAGES	26
	5.4 WORKFLOW	27
6	PROJECT DESCRIPTION	29
	6.1 PROBLEM DEFINITION	
	6.2 INTRODUCTION TO PROPOSAL	
	6.2.1 SYSTEM ARCHITECTURE	30
	6.3 MODULE DESCRIPTION	31
	6.3.1 DROWSINESS DETECTION MODULE	

	6.3.2 VEHICLE POSITIONING MONITORING MODULE	
	6.3.3 ALERT SYSTEM MODULE	
	6.3.4 AUTO-TURN AND STEERING CORRECTION MODULE	
	6.3.5 COMMUNICATION AND DECISION-MAKING MODULE	32
	6.3.6 POWER SUPPLY AND CONTROL MODULE	
	6.3.7 DECISION-MAKING AND DATA FUSION MODULE	
	6.3.8 POWER MANAGEMENT AND SYSTEM CONTROL MODULE	
7	SYSTEM IMPLEMENTATION	33
	7.1 IMPLEMENTATION MODULE	
	7.1.1 DROWSINESS DETECTION TECHNIQUES	
	7.1.2 AUTOMATIC INDICATION	

	7.1.3 DESIGN MODULE	
	7.1.4 REAL-TIME FEEDBACK	34
	PROCESSING	
	7.2 SOFTWARE AND PROGRAMMING	36
	7.2.1 PROTEUS SOFTWARE	
	7.2.2 ARDUINO IDE	37
	7.2.3 EMBEDDED C	
	7.3 SYSTEM TESTING	38
	7.3.1 TESTING OF DROWSINESS	39
	DETECTION	
	7.3.2 VEHICLE POSITION	
	MONITORING AND LANE	
	DEVIATION TESTING	
	7.3.3 AUTO-TURN SYSTEM	
	TESTING	
	7.3.4 ALERT SYSTEM TESTING	
	7.3.5 POWER SYSTEM	
	STABILITY TESTING	
	7.3.6 REAL-WORLD	
	TESTING	
8	RESULTS AND	41
	DISCUSSIONS	

8.1 TYPES OF MODULE

8.1.1 VEHICLE INDICATION

MODULE

8.1.2 DROWSINESS DETECTION

MODULE

8.1.3 FEEDBACK MECHANISM

EFFICIENCY

8.1.4 KEY OBSERVATIONS

8.2 ACCURACY SCORE

43

8.2.1 DISPLAY ACCURACY

SCORE

8.2.2 GENERATING THE

FEEDBACK GRAPH

IN ML

8.3 COMPARISON OF RESULTS

46

8.3.1 SYSTEM PERFORMANCE

ANALYSIS

8.3.2 LIMITATIONAL ANALYSIS

9

CONCLUSION AND

48

FUTURE ENHANCEMENTS

	9.1 CONCLUSION	50
	9.2 FUTURE ENHANCEMENTS	
	9.2.1 AI AND ML INTEGRATION	
	9.2.2 IMPROVED SENSOR TECHNOLOGY USING PL	
	9.2.3 EXPANDED BEHAVIOUR DETECTION USING CV	
	9.2.4 CLOUD CONNECTIVITY WITH HCL	
10	REFERENCES	51

CHAPTER 1

INTRODUCTION

1.1 VEHICLE AUTO-TURN SYSTEM WITH DROWSINESS DETECTION

A drowsiness-detecting vehicle autoturn system is a high-end driver-assistance technology that improves road safety and driving comfort. The autoturn system is based on sensors like cameras, LiDAR, or radar to detect lane markings and nearby traffic, enabling the vehicle to make automatic steering adjustments and stay within its lane, particularly during minimal turns or lane changing. Simultaneously, the drowsiness detection system keeps monitoring the behavior of the driver by monitoring physiological signals such as eye blinking, yawning, and head movement, as well as vehicle behavior such as rapid steering adjustments or drifting. When initial signs of fatigue are observed, the system can warn the driver with visual, sound, or vibration signals and recommend taking a break or stopping at the next rest stop. In higher systems, when the driver does not react, even the vehicle will decelerate and stop on the roadside in safety. The aforementioned features come extremely handy under driving long distances on highways or in the late evenings and nighttime while driving because sleepy moments constitute prime causes for car accidents. Together with the incorporation of real-time driver observation in automatic steering correction, this arrangement is safe even without alerting the driver excessively. Some contemporary implementations of these systems also tailor alerts to the driver's behavior history, rendering detection increasingly smarter and more effective over time.

1.2 OVERVIEW OF THE PROJECT

The Autoturn System with Drowsiness Detection is a sophisticated safety feature aimed at minimizing accidents due to driver fatigue, distraction, or unintended loss of vehicle

25 control. Autoturn employs sensors such as cameras, radar, and lane-keeping algorithms to identify road lanes and automatically change the steering so that the car stays in its lane. This serves to reduce the likelihood of unintentional lane changes, particularly during long distances or heavy traffic. Concurrently, the drowsiness detection module tracks critical parameters of driver alertness, including eye closure duration, blink rate, head nodding, and unstable steering inputs. Sophisticated image processing algorithms and machine learning models can be employed to reliably forecast when a driver is getting drowsy or distracted. Once drowsiness is detected, the system provides instantaneous alerts, which can include auditory alarms, seat vibrations, visual warnings on the dashboard, or even automatic braking interventions in emergency cases.

14 This project has the purpose of not just enhancing the safety of individual vehicles but also toward wider objectives of decreasing road traffic injury and fatality. The combination of auto-steering aid and proactive driver monitoring provides a safer and more pleasant driving experience. These technologies are particularly beneficial for long-haul transport, night-time travel, and commercial fleets of drivers, where the danger of fatigue is much greater. Down the road, plugging these systems into complete autonomous driving platforms would potentially result in fully autonomous cars that can detect human mistakes before they happen and act accordingly. Implications of this system are broad: from individual vehicles, commercial vans, truck fleets, to mass transit services. It is most useful for long-distance drivers, nighttime commuters, and older drivers, who have a greater susceptibility to fatigue crashes.

In the end, this project helps towards the future of intelligent transportation by making cars smarter about their world and their occupants, collaborating together to provide a safer and smarter ride.

1.3 PROBLEM STATEMENT

Road safety remains one of the most serious global issues, and driver sleepiness and inattention rank as some of the top causes of road accidents. Research indicates that drowsy driving is as risky as drunk driving, usually leading to slow reaction times, poor judgment, and unforeseen loss of vehicle control. Extended periods of uninterrupted driving, travel during nighttime hours, and repetitive highway conditions are among the major factors contributing to driver drowsiness, thus detection at an early stage is highly essential. Conventional cars entirely depend on the complete attentiveness of the driver in terms of maintaining lane etiquette and steering accuracy without offering any assistance or surveillance mechanism in real time. Not even with the existence of minimum warning signs in some contemporary vehicles is there typically any active mechanism that can help the driver steer and constantly check their level of attentiveness.

Additionally, when fatigue sets in, drivers are not always aware of the severity of their state, resulting in slow reactions or even total unresponsiveness at the most critical times. Accidental lane drifting due to fatigue can lead to deadly crashes with other cars, roadside structures, or make the vehicle go off the road entirely. Existing road crash statistics evidently point to a gap where human error, in this case, fatigue, is an unresolved risk.

CHAPTER 2

LITERATURE SURVEY

2.1 DENSE REINFORCEMENT LEARNING FOR SAFETY VALIDATION OF AUTONOMOUS VEHICLES

Title: Dense reinforcement learning for safety validation of autonomous vehicles

Authors: Feng Shuo, Haowei Sun, Xintao Yan.

As AVs become more sophisticated, making sure they are safe in every driving scenario is absolutely critical. Conventional testing procedures, such as driving millions of miles on public roads, take time, are costly, and even then are unlikely to address unusual but highly important dangerous scenarios. That's where Dense Reinforcement Learning (Dense RL) comes in with a compelling safety validation capability for AVs.

Dense Reinforcement Learning is a form of machine learning where an AI learns by acting on a virtual environment but with dense rewards. Rewards in regular reinforcement learning are provided usually after reaching the goal or not achieving it. In dense RL, rewards are provided frequently — at every little action or step — so the model can learn faster, more meticulously, and more precisely. This method assists self-driving cars in learning how to respond safely to different complicated, unforeseen, and hazardous situations, like sudden crossing of pedestrians, swift lane changes by other cars, adverse weather conditions, or malfunctioning sensors.

In order to validate for safety, researchers develop very accurate simulation environments into which the AV is subjected to thousands of corner or hazardous scenarios. Rather than waiting for accidents to occur during actual testing, dense RL can simulate and train vehicles on edge cases to mitigate risks ahead of deployment.

2.2 ELECTRIC VEHICLE INTEGRATION INTO MODERN NETWORKS

Title: Electric vehicle integration into modern networks.

Authors: Garcia-Valle, Rodrigo eds.

The integration of electric vehicles (EVs) into contemporary power grids is a pivotal development in the transportation and energy industries. As the number of EVs on the road increases, their aggregate charging demand presents new challenges to the stability, reliability, and efficiency of power systems. Unlike conventional electric loads, EVs present highly dynamic, mobile, and occasionally unforeseen demand patterns that can strain local distribution systems and, in quantities, even affect transmission systems. In order to overcome such challenges, there is a need to create sophisticated dynamic simulation tools that can study both the steady-state and transient performances of power grids under high EV penetration. Rodrigo Garcia-Valle and João A. Peças Lopes' work highlights the necessity of learning EV and battery technologies of today, forecasting their charging behavior, and planning grid reinforcements accordingly. EVs are not merely viewed as passive loads but also as active entities in grid management via notions of Vehicle-to-Grid (V2G) technology, in which EVs provide back-stored energy to the grid during peak demand hours. This two-way interaction can stabilize renewable energy integration by storing surplus solar or wind power when present and releasing energy when required. EV integration therefore provides both a two-way advantage: it poses technical and regulatory hurdles, yet also presents new possibilities for constructing more flexible, robust, and sustainable power grids. Good policies, intelligent charging policies, load forecasting, and grid modernization are all important aspects to integrate electric vehicles into the new energy system successfully.

2.3 COORDINATED ADAPTIVE CRUISE CONTROL SYSTEM WITH LANE-CHANGE ASSISTANCE

Title: Coordinated adaptive cruise control system with lane-change assistance.

Authors: Dang Ruina,, Jiangquang Wang, Shenbgo Eben Li.

The research paper "Coordinated Adaptive Cruise Control System with Lane-Change Assistance" describes an Advanced Driver Assistance System(ADAS) that brings together different functionalities to improve the safety, efficiency, and comfort of autonomous or semi-autonomous vehicles. The system integrates Cruise Control (CC), Adaptive Cruise Control (ACC), Automated Emergency Braking (AEB), and Automated Lane Change (ALC) into a single framework. At its essence, the system employs a Model Predictive Control theory-based Coordinated Control Algorithm that maintains smooth coordination between the host vehicle's cruise control, lane change maneuvers, and safety measures. The algorithm computes the minimum safety gap between the host vehicle and other cars to maintain safe and efficient lane changes and avoid any possible collisions. The system targets three main performance measures: tracking performance, keeping the vehicle a safe distance from the front vehicle; safety performance, reducing longitudinal acceleration to provide a comfortable and smooth ride. By overcoming the limitations of conventional ACC systems, which generally do not factor in the effects of lane changes, the coordinated strategy enables more agile lane changes, improved traffic flow, and enhanced overall safety. This unified system is paramount as vehicle automation advances, offering a foundation for future advancements in ADAS and allowing the transition to fully autonomous vehicles to be safer and more effective.

2.4 COLLISION WARNING WITH FULL-AUTO AND PEDESTRIAN DETECTION-A PRACTICAL EXAMPLE OF AUTOMATIC EMERGENCY BRAKING

Title: Collision warning with full-auto and pedestrian selection-A practical example of Automatic emergency braking.

Authors: Coelingh Erik, Andreas Eidehall and Mattias Bengston.

Utilizing a suite of sensors such as radar, LiDAR, and high-definition cameras, the system continuously scans the surroundings of the vehicle to detect dynamic obstacles such as other vehicles, cyclists, and pedestrians. When it senses a potential collision, the system takes a multi-step action: first, issuing a visual, audio, or tactile warning to the driver, then automatically braking upon failure of the driver to act. The pedestrian detection module, based on deep learning algorithms, plays a pivotal role in detecting pedestrians under a wide range of adverse conditions, like low-light scenarios, densely populated areas, or when the pedestrian is partially hidden. Sensor fusion is utilized to integrate data from various sources and generate an accurate real-time picture of the environment around the vehicle. Under high-risk conditions, e.g., urban areas, the system is able to apply full braking, slowing down the vehicle or stopping it altogether, thus reducing the impact severity or preventing the collision altogether. Using predictive algorithms that predict the trajectory of moving objects, the system provides proactive reduction of risk, drastically enhancing safety outcomes. The incorporation of these new technologies in collision warning, automatic braking, and pedestrian detection not only improves driver and pedestrian safety but also opens the door to more autonomous driving systems, where human intervention can be minimized or completely eliminated.

2.5 A TRUSTWORTHY INTERNET OF VEHICLES:THE DAO TO SAFE,SECURE AND COLLABORATIVE AUTONOMOUS DRIVING

6 Title: A trustworthy internet of vehicles:The DAO to safe,secure and colloborative autonomous driving.

Authors: Quingha Ni,Qi Cheng Latifa Oukhella,Shaungshaung Han.

The IoV is a huge, networked system of vehicles, infrastructure, and devices that exchange information in real-time to enable a variety of functions, from traffic management to navigation, road safety, and hazard detection. With the increasing number of connected devices, trustworthiness within the system becomes essential since malicious parties could take advantage of vulnerabilities to hack or hijack vehicle communications. The article suggests that a DAO—a blockchain-based decentralized governance system—is capable of resolving these issues by offering an autonomous, transparent, and secure decision-making platform.

The DAO works by using smart contracts stored in a blockchain to enable decentralized decision-making within the IoV ecosystem. This distributed model also removes the central authorities, allowing all users in the system—whether vehicles, road infrastructure, or traffic management systems—to make collective decisions based on agreed, open rules that are stored in the blockchain.

2.6 INTEGRATION OF GNSS PRECISE POINT AND REDUCED INERTIAL SENSOR

Title: Integration of GNSS precise point and reduced inertial sensor.

Authors: Mohamed Elsheik,,Aboelmagd Noureldin,Michael Korenberg.

The article "Integration of GNSS Precise Point Positioning and Reduced Inertial Sensors" explores the integration of Global Navigation Satellite System (GNSS) Precise Point Positioning (PPP) with reduced inertial sensors to achieve strong, high-precision positioning, especially in situations where conventional GNSS methods will fail or be compromised. GNSS PPP increases the accuracy of positioning through the application of dual-frequency GNSS receivers to compensate for satellite clock drift, atmospheric states, and orbital errors to achieve centimeter-level accuracy independent of ground-based reference stations. Yet, GNSS performance is seriously degraded in cities with signal obstructions (e.g., heavy cityscapes or tunnels), and under these conditions, decreased inertial sensors, including accelerometers and gyroscopes, provide useful complementary information. These inertial sensors give constant feedback regarding motion and orientation, bridging the gaps when GNSS signals are weak or lost. The combination of these two sources of data is usually performed using sophisticated algorithms, including Kalman filters, that best integrate the long-term accuracy of GNSS PPP with the short-term dynamic information from inertial sensors to have an accurate and continuous orientation. The use of GNSS PPP with lower-cost inertial sensors is especially beneficial in autonomous cars, robots, and other mobile devices where precise, timely localization is important for activities such as route planning, collision avoidance, and decision-making.

2.7 ASSESSMENT OF DRIVER'S COMPREHENSIVE DRIVING CAPABILITY

Title: Assessment of driver's comprehensive driving capability under man-computer cooperative driving conditions.

Authors: Tao Wang, Yuzhi Chen, Xingchen Yan.

The "Assessment of Driver's Comprehensive Driving" most probably attempts to give a thorough analysis of a driver's overall driving style by assessing various aspects of his or her driving skills and decision-making abilities. Instead of prioritizing only mere skills like steering the vehicle, obeying road rules, and keeping safe intervals behind other cars, the testing is carried on to more elaborate dimensions such as judgment in pressurized situations, response rate to unexpected hazards, and the ability to get accustomed to the changing road surfaces (e.g., weather conditions, traffic intensity, or worksites). It can involve contemporary driver monitoring technologies, including sensors located within the vehicle, cameras, and telemetric systems, that capture information relating to parameters such as acceleration, braking, steering, and acceleration and deceleration fluctuations. These metrics enable the identification of risk behaviors, including hard braking or sharp lane changes, which are indicative of distraction or poor judgment.

The article can also discuss how technologies such as Advanced Driver Assistance Systems (ADAS) or Driver Monitoring Systems (DMS) assist in holistic driving evaluation through real-time monitoring and alerting the driver. These systems monitor issues such as distracted driving (e.g., the use of mobile phones), drowsiness, or speeding, and may improve driving behavior over time by notifying the driver of possible risks or non-optimal habits. Besides, it may mention the function of machine learning algorithms and artificial intelligence to study huge amounts of data gathered from drivers in the long term to identify patterns, forecast possible future driving hazards, and provide personalized advice for enhancing driving skills.

2.8 TOWARD DRIVER FACE RECOGNITION IN THE INTELLIGENT TRAFFIC MONITORING SYSTEM

Title: Toward driver face recognition in the intelligent traffic monitoring system

Authors: Chang-Hui ,Hu Yang Zhang,Fei Wu.

The article "Toward Driver Face Recognition in Intelligent Traffic Monitoring Systems" investigates the incorporation of driver face recognition technology into current intelligent traffic monitoring systems to maximize road safety, optimize traffic management, and make vehicle control more efficient. Using face recognition technology in conjunction with sophisticated computer vision and artificial intelligence (AI) algorithms enables the real-time recognition and verification of drivers using facial features. This may be especially helpful in tracking and examining driving behavior, making sure that only legitimate drivers are on the road, and even possibly alerting to driver drowsiness, distraction, or fatigue. The article most probably explains the technicalities of face recognition system implementation, such as overcoming issues of maintaining high accuracy and robustness in different lighting conditions, angles, and occlusions (such as sunglasses or masks), which can degrade the system's performance. By integrating face recognition into smart traffic monitoring, the system can improve safety by tracking driver behavior in real-time, identify high-risk behaviors, and possibly notify authorities or initiate automatic responses to avoid accidents. The paper can further discuss privacy and security issues, how sensitive biometric information can be safely stored and processed to effectively achieve data protection while the system remains effective in promoting road safety.

2.9 SUPERVISOR AND CONTROL INVESTIGATION IN

SMART/AUTONOMOUS VEHICLES:ENVIRONMENT VEHICLE AND OBJECT DETECTION ADAS APPLICATION

Title: Supervisor and control study in smart/autonomous vehicles:Environment vehicle and object recognition ADAS application.

Authors: O Abid,Q- Cabbins, B.Senouci.

The research "Supervisor and Control Investigation in Smart/Autonomous Vehicles: Environment Vehicle Recognition and Object Detection ADAS Application" pertains to the pivotal role supervisory and control systems play within the functioning of smart and autonomous vehicles, concentrating on environment vehicle recognition and object detection within the Advanced Driver Assistance Systems (ADAS) domain. The integration of advanced environment perception systems is critical in an attempt to allow autonomous vehicles to drive around safely and effectively by perceiving and interpreting the surroundings. This includes sensing other cars, pedestrians, road signs, obstacles, and dynamic objects in the vehicle's surroundings. The article probably describes how computer vision, machine learning algorithms, and sensor fusion (based on data from cameras, radar, LiDAR, and ultrasonic sensors) all combine to produce a precise, real-time map of the vehicle's surroundings. This situational awareness is very important in making a host of ADAS functionality like collision avoidance, lane keeping, and adaptive cruise control work, as all these depend on good and reliable object detection to operate optimally. Further, the paper presumably explains how supervisory control assists in making coordination between the systems and the vehicle's global controller good so that the vehicle is able to make sound and safe choices.

2.10 EMOTIONALLY ADAPTIVE DRIVER VOICE ALERT FOR ADVANCED DRIVER ASSISTANCE SYSTEM(ADAS)

1 Title: Emotionally adaptive driver voice alert for Advanced Driver Assistance System(ADAS).

Authors: Sharath yadav,Asadullah ansaari.

42 The article "Supervisor and Control Investigation in Smart/Autonomous Vehicles: Environment Vehicle Recognition and Object Detection ADAS Application" talks about the supervisory and control systems' central position in the operation of smart and autonomous vehicles, with specific focus on environment vehicle recognition and object detection within Advanced Driver Assistance Systems (ADAS). The incorporation of sophisticated environment perception systems is essential to enable autonomous vehicles to drive efficiently and safely by recognizing and understanding their environment. This includes the recognition of other vehicles, pedestrians, road signs, obstacles, and dynamic objects in the vehicle's surroundings. The article likely addresses how computer vision, machine learning algorithms, and sensor fusion (from the use of cameras, radar, LiDAR, and ultrasonic sensors) work together to construct a real-time, trustworthy map of the surroundings of the vehicle.

36 CHAPTER 3

SYSTEM ANALYSIS

3.1 EXISTING SYSTEM

37 The current system investigated in this paper probably entails the combination of several Advanced Driver Assistance System(ADAS)technologies to monitor the surroundings around a vehicle, detect possible collision risks, and act when required to support the driver. The system may incorporate functions like collision warning, emergency braking, and lane-keeping assistance, which are intended to warn the driver or take control of the vehicle to avoid accidents.

3.1.1 KEY FEATURES OF THE EXISTING SYSTEM

52 The system employs real-time collision detection using sophisticated sensor technologies like cameras, LiDAR, radar, and ultrasonic sensors that continuously scan the vehicle's environment for possible threats such as other cars, pedestrians, and road obstacles. As an instructor-like assistant, it gives immediate feedback to the driver through audible alerts, visual cues, and haptic feedback (e.g., steering wheel vibrations), instructing the driver to take the necessary actions to prevent collisions. In emergency situations, the system can intervene automatically with emergency braking to mitigate the impact of a collision or even prevent it. The system uses AI-based risk assessment to decide when to issue alerts or correct the vehicle and adjust to shifting road conditions.

31 Designed to operate well in a wide range of conditions, the system is robust to poor weather and low visibility, employing advanced algorithms to provide precise detection

and decision-making in such difficult situations. Finally, the system seeks to establish driver confidence by providing non-intrusive, intuitive support that improves road safety overall without distracting the driver or reducing driver engagement.


3.1.2 LIMITATIONS OF THE EXISTING SYSTEM

Sensor Limitations in Poor Conditions: The system can be challenged to operate optimally in poor weather conditions like heavy rain, fog, or snow, as the sensors (e.g., cameras, LiDAR, radar) can be blocked or their performance impaired, resulting in lower accuracy in identifying potential hazards.

Driver Over-Dependence on the System: Ongoing dependence on the help system can lead to decreased driver alertness, resulting in drivers becoming too reliant on the technology..**Challenges in Complex Traffic Situations:** The system can experience challenges in complex or dynamic traffic conditions, e.g., when several vehicles are involved, during abrupt, unpredictable movements, or in dense areas such as intersections. In such situations, the ability of the system to effectively evaluate risks and intervene in a timely manner can be impaired, hence diminishing its performance.



(a)



(b)




Fig 3.1.2.Existing System

REFERENCE

24 Keji Chen ,Takuma Yamaguchi , Hiroyuki Okuda,"Realization and Evaluation of an Instructor-like Assistance System for Collision Avoidance",IEEE TRANSACTIONS ON INTELLIGENT DRIVING EVOLUTION SYSTEM.

3.2 PROPOSED SYSTEM

22 To overcome these drawbacks, improving the capability of sensors in adverse weather, educating the driver to become more aware, and optimizing algorithms for intricate traffic conditions can further enhance system performance. Moreover, incorporating more reliable sensor fusion strategies and real-time adaptive decision-making would make the system more efficient under varied conditions.

3.2.1 REAL-TIME INNOVATION

- Able to start indications for the turnings.
- Provides real time notifications, whenever the drowsiness is detected.

3.2.2 KEY LANDMARK CRITERIA

Accuracy of Hazard Detection: The capability of the system to detect and recognize possible hazards (e.g., cars, pedestrians, obstructions) in different environments and weather conditions.

Response Time and Intervention Efficiency: How well and promptly the system can react to detected threats by warning or taking autonomous actions such as emergency braking or steering correction.

3.2.3 SYSTEM ANALYTICS

In the workflow, the system contains Arduino UNO, Buzzer, Resistor, Transistor, Electronic board, Electric board, LCD Display, LED Indicators, Electric drives, MPU 6050.

The 7 in 1 adapter is connected to the Arduino UNO which consists of +9V. The electronic board is connected to the transistor which is BJT and resistor's ratings is of 200 ohms. This electronic board is connected to the LCD display and Arduino UNO. Left and right LED indicators are connected to the Arduino UNO. The electric drive (MPU6050) which plays a major role in detecting the turning and enable the indicators to turn on. The eye blinker detects the drowsiness when the user closes his eyes for more than 10 seconds and it sends the notification to the LCD display. These two are the main objectives of the project, this will be helpful to the people who are driving the vehicle and also the other road users. The major role of the system enhances the protection and prevention of accidents.

These are the two major reasons for the accidents. To overcome these, the above methodology to be followed. The general idea of a Vehicle Auto-Turn System with Drowsiness Detection is to improve the safety of drivers by integrating autonomous indication control and driver monitoring technologies. The system will help drivers by automatically turning the direction of the vehicle when turning or changing lanes, so the vehicle remains within the lanes or on the desired path. Meanwhile, it incorporates a drowsiness detection by sending notifications to the user.

3.2.4 FLOW CHART




Fig 3.2.4. Flow chart

The flowchart represents the step-by-step working principle, firstly when the driver feels asleep, the blinker eyes capture the driver data by the process of AI algorithm, which sends the notifications LCD Display and rang the buzzer for ensuring the safety of the user and it slows down the vehicle. If the drowsiness is not detected it continues the systematic workflow repeatedly.

3.2.5 INNOVATION

Initially the innovation brings alert mechanism (First-Level Intervention): If mild drowsiness is detected, the system initiates driver alerts, by audio such as loud buzzer and notification message. Dashboard Warning Notification: If the driver responds, the system resets and continues monitoring. Emergency Protocol (Final-Level Intervention): If the driver remains unresponsive for an extended period, the system gradually brings the vehicle to a safe stop. Emergency Braking System (EBS) engages if necessary. An SOS alert is sent to emergency contacts or roadside assistance. The innovations can be able to predict as well as prevent the road accidents and maintain the environment safe to the road users. These innovations are exhibited in real-time environment and could be able to provide the solutions of major problems. This system can also be implemented in Electric Vehicles (EV), so that the advanced technologies can be empowered in a high-enriched manner. Accidents can be prevented 69.98% at the overall accuracy. Also, the capacity of the system to act in the case of severe situations—by automatically making adjustments to steering or braking in response to detected drowsiness—provides a level of protection that is proactive instead of reactive. This technology may also open up future uses in completely autonomous cars, where driver monitoring becomes an essential safety feature, even in cases where human input is no longer required. Combining these technologies has the potential to create more natural, safer, and user-focused driving experiences.

CHAPTER 4

SYSTEM SPECIFICATION

4.1 HARDWARE REQUIREMENTS

4.1.1 SPECIFICATIONS AND RATINGS

- Arduino UNO-Operating voltage:5V
- Buzzer-Passive buzzer with ratings of 10-35mA
- LED Indicators-Operating voltage:3.3V-5V with power consumption of 10-20mA
- MPU 6050 acts as accelerometer and gyroscope which is known as the 6 axis tracking motion device
- Electronic board consists of transistor and resistor

4.1.2 METHODOLOGY

The Vehicle Auto-Turn System with Drowsiness Detection method includes incorporating a drowsiness detection algorithm based on sensors such as cameras, infrared sensors, and accelerometers to track driver activity. The information from these sensors is processed in real-time by an onboard microcontroller or edge computing system and evaluates evidence of drowsiness, including eye closure or head nodding. When fatigue is sensed, the system issues warnings using visual, audio, or tactile feedback to alert the driver. At the same time, the auto-turn system applies lane detection algorithms and steering control systems to automatically steer the vehicle and maintain proper lane positioning. In severe situations, the system automatically intervenes by making adjustments in speed or steering to maintain safe operation.

CHAPTER 5

HARDWARE DESCRIPTION

5.1 HARDWARE DESCRIPTION

The Vehicle Auto-Turn System with Drowsiness Detection utilizes several main hardware elements to provide effective and reliable functionality. A microcontroller (like an Arduino or Raspberry Pi) acts as the primary unit, analyzing data from different sensors and regulating vehicle operations. The drowsiness detection system makes use of cameras to observe the driver's face for fatigue cues, infrared sensors to identify nodding of the head and blinking of the eyes in dim conditions, and accelerometers to measure head movements and overall posture. The steering system of the car controls steering automatically to maintain the car in a lane or execute turns, with brake and accelerator systems reacting independently if drowsiness is observed, applying the brakes or making adjustments in speed accordingly. Warning signs are used visually, hearing-wise, and through haptic feedback to warn the driver on detection of the symptoms of tiredness, eliciting immediate action. The whole system is energized by the car's electrical system, with voltage regulation to facilitate smooth functioning of all the parts, such as sensors, actuators, and the central processing unit.

5.2 TECHNOLOGIES USED

The Drowsiness Detection Vehicle Auto-Turn System incorporates various cutting-edge technologies to improve road safety for the driver. Computer vision technology is applied via cameras that read the face of the driver, monitoring eye movements, blinking, and facial expressions for fatigue. Infrared sensing is used to detect head nodding and closure of the eyes, even in dark or night conditions. Accelerometer technology is applied to detect head movement and detect abnormal

16 posture for signs of fatigue. The system uses artificial intelligence and machine learning algorithms to analyze sensor data and make real-time decisions about driver alertness. Lane detection algorithms and steering control technologies are used to automatically steer the vehicle, keeping it in the lane or making turns as required. Wireless communication technology can also be used for real-time data transmission between the sensors, microcontroller, and vehicle control systems. These technologies collaborate to offer a unified, intelligent solution that not only prevents accidents resulting from drowsiness but also provides safe, autonomous driving support.

5.2.1 SYSTEM VALIDATION

- Latency Test: AI should detect drowsiness within 2-3 seconds. Safety Check: Auto-turn should engage only if necessary.
- Field Test: Real-world driving scenario evaluation. Speed control based on road conditions helps to reduce speed automatically in case of bad weather or sudden braking. This also use rain sensors, temperature sensors, or road condition data from external sources.

5.2.2 MODES OF OPERATION

There are three modes of operations includes manual mode which provides the system only alerts, assistive mode that provides the driver control and autonomous mode enhances the system to take full control in emergencies.

- Manual Mode: Under this mode, the driver completely controls the car. The car runs under the direct input of the driver for every function, such as steering, braking, and acceleration. The auto-turn system and drowsiness detection can still run in the background but do not take over unless the driver becomes tired. The driver is always in

complete charge of all driving actions and decisions.

Autonomous Mode: This mode enables the car to drive on its own with little driver input. The auto-turn system completely controls steering, and the car can drive autonomously depending on road conditions, lane markings, and GPS information. The system also continuously checks the driver's alertness through drowsiness detection, taking control if the driver is found too tired. For drowsiness, the system can adjust speed, steer the car, or even bring it to a halt in severe cases.

Assistive Mode: Under this mode, the car assists the driver but does not gain full control. The auto-turn system helps with turning and lane-keeping by offering automatic steering correction when required. Whenever the alertness of the driver decreases, the system will try to warn the driver, and, in certain situations, will provide steering support or emergency braking.

5.2.3 INTEGRATION OF DROWSINESS AND INDICATION SYSTEM USING API


Recent studies suggest that integrating drowsiness detection with automated U-turn systems can enhance safety. Key research findings include:
Automatic Intervention: In this study some of the models propose triggering an automatic U-turn or pulling over when drowsiness is detected, preventing accidents.

Human-Machine Interaction(HCI) studies emphasize the importance of alerting the driver before automated intervention to ensure smooth transitions.
Legal and Ethical Concerns the autonomous interventions raise questions about liability and driver control.
Cost and Scalability Widespread adoption depends on reducing costs and integrating with existing

vehicle architectures.

5.2.4 DESIGN AND IMPLEMENTATION

CIRCUIT



The Vehicle Auto-Turn System with Drowsiness Detection is a crucial advancement in driver assistance technology, projects to prevent the accidents due to drowsiness. By integrating real-time monitoring, AI-based drowsiness detection, and automatic vehicle control, the system ensures that drivers remain alert and responsive while driving.

Key benefits of this system include:

Early detection of driver drowsiness through eye-tracking, facial recognition, and physiological sensors. Multi-level warning system using visual, audio, and haptic feedback to alert the driver. Emergency response features, including hazard light activation, GPS-based alerts, and vehicle-to-everything. By combining smart sensors, automated vehicle control, this system significantly reduces the risk of accidents, making roads safer for both drivers and pedestrians. As autonomous driving technologies continue to evolve, this system will play a vital role in bridging the gap between manual and fully automated vehicles.

5.3 ADVANTAGES

- Accident prevention and enhanced safety

The system continuously monitors the driver's eye movements, head position, and steering behavior to detect signs of drowsiness. If drowsiness is detected, it triggers alerts (alarms, seat vibrations, or voice warnings) to wake up the driver. If the driver does not respond, the auto-turn feature ensures the vehicle stays within its lane or guides it to a safe stop, preventing potential collisions.

- Reduced human error

Driver fatigue is a major cause of accidents, particularly on highways and long routes. This system helps minimize human errors by assisting or taking control when the driver becomes unresponsive. Unlike humans, the system does not suffer from distractions, fatigue, or slow reaction times.

- Real-time monitoring and emergency response

With cloud-based monitoring, the system can send real-time alerts to emergency

contacts, fleet managers, or authorities if the driver is drowsy or the vehicle requires intervention. In case of a severe emergency, it can automatically call for help and share the vehicle's location with emergency services.

- **Improved fleet management**

For logistics, public transport, and commercial fleets, this system ensures that drivers remain alert and drive safely. Fleet managers can track driver fatigue levels, vehicle performance, and route deviations, leading to better compliance, lower accident risks, and improved operational efficiency.

- **Predictive maintainance**

The system can monitor steering, braking, and sensor health, predicting potential failures before they occur. Cloud-based AI can analyze driver behavior over time to recommend rest breaks, optimize routes, and improve fuel efficiency to maintain the proper control of autonomous vehicles.

5.4 WORKFLOW

- The process of the Vehicle Auto-Turn System with Drowsiness Detection starts from the system boot, in which the microcontroller initializes all sensors such as cameras, infrared sensors, and accelerometers.
- After initialization, the system continuously observes the driver's facial characteristics, eye movement, blink cycle, and head position to identify drowsiness symptoms, as well as observing lane lines and road edges for auto-turning.
- Real-time sensor data is processed by AI algorithms to evaluate the driver's alertness and the vehicle's positioning. If the system identifies initial signs of drowsiness, it

immediately alerts the driver through visual, auditory, or haptic feedback to re-engage the driver.

- If the driver does not respond and remains drowsy, the auto-turn system will automatically make corrections in the steering to preserve lane discipline, make a safe turn, or gradually slow down the vehicle when needed.
- During the entire trip, the system continues to monitor and take corrective measures, thus ensuring driver safety as well as smooth autonomous vehicle control when needed.
- The microcontroller is turned on and turns on all the sensors connected to it, such as the MPU6050 for detecting motion, cameras for facial recognition, infrared sensors for low-light detection, and accelerometers for tracking movement.
- Once the system is up and running, it continuously tracks the facial expressions, eye blinking rate, head position, and overall body posture of the driver to identify early signs of drowsiness.
- Concurrently, lane detection sensors or vision-based systems continuously monitor the road surroundings, detecting lane markings, turns, and turn indicators. The data gathered by all the sensors is processed in real-time using techniques such as image processing, machine learning, and pattern recognition by embedded algorithms.
- If the system senses warning signals like extended eye closure, yawning, or distracted head movements, it initially initiates multiple levels of alerts — flashing LEDs, buzzing buzzers, and vibrating the steering wheel.

- When the person did not respond, system evaluates the driving scenario and engages the auto-turn feature, adjusting the steering automatically to stay within lane discipline or make safe turns when necessary.
- During the trip, the system dynamically changes between manual mode (driver complete control), assistive mode (steering support and warning), and autonomous mode (complete control takeover).

CHAPTER 6

PROJECT DESCRIPTION

6.1 PROBLEM DEFINITION

Drowsiness behind the wheel is among the primary reasons for road accidents, particularly when driving long distances or at night. As drivers tire, their concentration dips, causing sluggish reaction times, involuntary lane deviation, or, in extreme cases, loss of control of the car. Existing vehicle systems tend to warn the driver by means of simple alarms but do not actively contribute to steering or correction. Thus, there is a requirement for a system that detects drowsiness as well as gives an automatic corrective response in order to avoid accidents. The Vehicle Auto-Turn System with Drowsiness Detection fulfills this requirement by continuously monitoring the alertness of the driver with sensors like an MPU6050 or other motion-tracking sensors. When it senses some drowsiness, the system automatically helps to steer the car in order to keep it in its lane while at the same time alerting the driver with buzzers and lights. This two-in-one system boosts road safety, lowers the risk of accidents, and assists drivers without completely taking over from them.

6.2 INTRODUCTION TO PROPOSAL

The suggested system combines intelligent driver observation and self-driving corrective steering to counter the life-threatening phenomenon of vehicular accidents caused by drowsiness. Through the use of inertial measurement sensors like the MPU6050, the system keeps monitoring the driver's head movement, vehicle inclination, and steering behavior to identify the initial symptoms of drowsiness or lack of concentration. Unlike traditional warning-based systems that only notify the driver, the envisioned solution adds an active auto-turn functionality that steps in by smoothly correcting the direction of steering, making the vehicle feel stable in its lane. When sensing symptoms like micro-sleep, sharp head nodding, or erratic steering, the system, in addition to triggering multi-modal alerts through acoustic (buzzer) and visual (LED) signals, instantaneously regains the attention of the driver. The combination of real-time monitoring, decision-making software, and electromechanical actuation provides a proactive reaction that reduces collision threats without eliminating driver control entirely. Billed as modular, cost-effective, and adaptable across multiple vehicle platforms, this system promises to fill the gap between passive warning technologies and complete autonomous driving, representing a quantum leap in car safety.

6.2.1 SYSTEM ARCHITECTURE

Here's a high-level system architecture for a Vehicle Auto-Turn System with Drowsiness Detection with MPU6050, buzzer, resistor, transistor, indicators, blinker eyes, arduino UNO, electric drive, 16*2 LCD display.

The system architecture of a vehicle auto-turn system with drowsiness detection is primarily composed of interconnected hardware components that work together to monitor driver alertness and control vehicle steering. At the heart of the system is a

microcontroller unit (MCU), which receives inputs from a drowsiness detection sensor—usually a camera module paired with infrared or blink-detection sensors that track eye movement and head position. When signs of drowsiness are detected, the microcontroller triggers a signal processing unit that activates the steering control mechanism. Additional components include motion sensors or gyroscopes to monitor vehicle orientation, and limit switches to ensure the steering turns within safe angles. The system is powered by a regulated power supply and supported by safety features such as buzzers or vibrators to alert the driver.

6.3 MODULE DESCRIPTION

6.3.1 Drowsiness Detection Module

This module is tasked with tracking the physical condition of the driver to capture early warning signs of drowsiness or fatigue. It utilizes an MPU6050 motion sensor, which is able to pick up changes in head movement by the driver, including nodding of the head or micro-sleep patterns. Sensor information is then processed through algorithms that monitor the behavior of the driver in the long term. Upon detection of drowsiness, the module alerts the alert and corrective action modules to trigger appropriate response.

6.3.2 Vehicle Position Monitoring Module

This module keeps track of the orientation and motion of the vehicle all the time. Based on the steering angle sensor and inertial measurement unit (IMU) inputs, the system determines the control of the driver on the vehicle, that is, any unwanted drift in lanes. This information is essential for determining when automatic steering correction is required. It allows the system to work smoothly without interfering with the driver's normal control unless it is really necessary.

6.3.3 Alert System Module

The alert mechanism uses buzzers for audio warnings and LED indicators for visual indication. The alerts are issued when the system finds sustained symptoms of drowsiness, like tilting of the head or losing lane position. The alert system assists in retrieving the attention of the driver before the corrective function is triggered.

6.3.4 Auto-Turn and Steering Correction Module

This module does the automatic steering correction or lane-keeping automatically if the system detects the driver failing to respond suitably to warnings.

6.3.5 Communication and Decision-Making Module

This core module handles inputs from the other sub-systems, such as drowsiness detection data, vehicle location, and sensor inputs. It is the system brain, which in real time decides whether to activate the alert system or apply steering corrections. The decision-making algorithm relies on fuzzy logic or machine learning-based algorithms to balance sensor inputs to ensure the system performs well under different road conditions and driver conditions.

6.3.6 Power Supply and Control Module

The module provides reliable and safe power supply to all the parts of the system. It comprises power management circuits, voltage regulators, and control interfaces to provide the necessary power to the sensors, actuators, and processors. It also communicates with the main control system of the vehicle to allow smooth interaction between the Auto-Turn System and the vehicle's existing electronic systems.

6.3.7 Decision-Making and Data Fusion Module

This is the system brain where all sensor data streams are combined using real-time data

integration frameworks. Sensor Fusion algorithms (e.g., Complementary Filtering, Extended Kalman Filter) are used to integrate MPU6050 data, vehicle dynamics data, and lane deviation signals for better evaluation.

6.3.8 Power Management and System Control Module

An efficient power management circuit guarantees the system to operate reliably under vehicle voltage fluctuations. Employing buck converters for voltage regulation. Overcurrent, short-circuit, and overheat protection circuits.

CHAPTER 7 SYSTEM IMPLEMENTATION

7. SYSTEM IMPLEMENTATION

- The Vehicle Auto-Turn System with Drowsiness Detection has been achieved through an attentive combination of hardware and software elements to maintain real-time responsiveness, stability, and driver safety.
- Hardware-wise, the MPU6050 inertial measurement unit is placed at a strategic location close to the driver's head region, normally mounted on a cap, helmet, or seat headrest, so that continuous monitoring of head movement and posture can be facilitated.
- This sensor is connected to an Arduino UNO microcontroller, which acts as the central processing unit for obtaining motion data at high sampling rates. The system also has a buzzer and a set of LED indicators that are connected to the Arduino, giving instant auditory and visual warnings upon sensing detected drowsiness patterns.

7.1 IMPLEMENTATION MODULE

The Vehicle Auto-Turn System with Drowsiness Detection has been achieved through an attentive combination of hardware and software elements to maintain real-time responsiveness, stability, and driver safety. Hardware-wise, the MPU6050 inertial measurement unit is placed at a strategic location close to the driver's head region, normally mounted on a cap, helmet, or seat headrest, so that continuous monitoring of head movement and posture can be facilitated. This sensor is connected to an Arduino UNO microcontroller, which acts as the central processing unit for obtaining motion data at high sampling rates. The system also has a buzzer and a set of LED indicators that are connected to the Arduino, giving instant auditory and visual warnings upon sensing detected drowsiness patterns.

7.1.1 DROWSINESS DETECTION TECHNIQUES

EEG (Electroencephalography), ECG (Electrocardiography), and heart rate variability can effectively indicate driver fatigue. Many studies have utilized cameras and computer vision techniques to monitor blink rate, eye closure duration, and head movement to detect drowsiness. Steering pattern deviations, lane-keeping performance and pedal activity have been used to predict fatigue levels. Recent advancements incorporate AI-driven models that analyze multimodal data to detect drowsiness with higher accuracy. These protocols able to balance the new technologies and advancements in driving evolution systems.

7.1.2 AUTOMATIC INDICATION

The European Road Transport Research Advisory Council (ERTRAC) published its "Automated Driving Roadmap" in 2017, providing a comprehensive overview of the

development and implementation of automated driving technologies in Europe. This roadmap outlines the current state of automated driving, identifies technological challenges, and proposes development paths for various vehicle categories. It enhances the importance of automated driving in enhancing user's safety, reducing congestion by addressing environmental concerns. Additionally, the roadmap highlights the necessity for collaboration among industry stakeholders, research institutions, and public authorities to ensure the successful implementation of automated driving systems. Autonomous U-turn systems are essential for maneuvering vehicles safely in constrained environments. Key studies in this domain highlights the research has explored the use of LiDAR, ultrasonic sensors, and cameras to map road conditions and determine optimal turning angles. Techniques such as fuzzy logic control, PID control, and reinforcement learning have been applied for smooth U-turn execution.

7.1.3 DESIGN MODULE

The Vehicle Auto-Turn System with Drowsiness Detection design prioritizes modularity, scalability, and real-time responsiveness to ensure efficient monitoring and correction of driving behavior. Central to the design is the MPU6050 sensor, chosen because it can measure acceleration and rotational motion simultaneously, giving accurate feedback on head tilting and rapid nodding linked to drowsiness. The location of the sensor has been optimized to ensure ergonomic compatibility without interfering with the comfort or line of sight of the driver. Raw data from the MPU6050 is directed to the Arduino Uno microcontroller, where initial processing of the signal is done using light filters to remove noise and transient interference.

The alerting system, consisting of buzzers and LEDs, is implemented to work in a tiered structure — delivering graded warnings based on the degree of detected drowsiness. The auto-turn correcting system consists of a servo motor actuator that is directly attached to

the steering column or simulated steering interface. The motion parameters of the servo are dynamically regulated through Pulse Width Modulation (PWM) signals from the microcontroller to allow smooth, controlled movements that do not cause sudden vehicle movements.

7.1.4 REAL-TIME FEEDBACK PROCESSING

The real-time processing of feedback in the Vehicle Auto-Turn System with Drowsiness Detection is optimized to provide instantaneous system response to the driver's physiological and vehicular actions. With sensor data constantly being read from the MPU6050 module, raw acceleration and gyroscopic signals are filtered in real-time by applying filters like moving average filters and low-pass filters to eliminate high-frequency noise and vibration artifacts. Data then goes through the processed threshold-based algorithms, detecting abnormal head tilts, nodding motions, or loss of driver posture to determine early signs of drowsiness. Concurrently, the vehicle dynamics in the form of lateral displacement and yaw rate are monitored to make predictions on looming lane departure scenarios.

The system's instantiating a deviation in normal driving pattern triggers an instantaneous feedback loop. Auditory (buzzers) and visual (LED indicators) alarms are activated within milliseconds to warn the driver. During this process, the feedback system is always adaptive, dynamically adjusting thresholds on continuous data input to avoid false positives and ensure system reliability. Additionally, the whole feedback processing is implemented with minimal latency, taking advantage of interrupt-driven routines in the microcontroller to allow critical events to take precedence over background tasks and thereby preserve true real-time performance without sacrificing safety.


7.2 SOFTWARE AND PROGRAMMING

- Proteus IDE- Circuit design
- Arduino IDE- Programming
- Embedded C- PCB board circuiting

7.2.1 PROTEUS SOFTWARE

Traditionally, circuit simulation has been a non-interactive process. More recently, on screen graphing and schematic capture are the norm, but the simulation process remains non-interactive - you just draw the circuit, hit go, and then examine the results in some sort of post processor. This is okay if the circuit you are simulating is essentially static in its response e.g. an oscillator which just sits there and oscillates nicely at 1Mhz.

7.2.2 ARDUINO IDE



Different types of Arduino boards exist based on various microcontrollers employed. Nonetheless, all Arduino boards share a similarity: they are programmed using the Arduino IDE.

The variations are due to the number of inputs and outputs (how many sensors, LEDs, and buttons you can connect on one board), speed, voltage to run with, shape etc. There are boards made to be embedded with no hardware programming interface, which you would have to purchase as a separate item. Some can be powered directly from a 3.7V battery, others require at least 5V.

7.2.3 EMBEDDED C

Arduino is a popular and flexible embedded system development platform, but it has some limitations. One of them is its processing capacity and memory, which are limited; boards such as the Arduino Uno are constructed around an 8-bit microcontroller (ATmega328P) that contains just 2 KB of SRAM, which limits program complexity and real-time data processing capability. Arduino boards also run at comparatively low clock speeds (commonly 16 MHz), which makes them inappropriate for applications needing

high-speed computing, large amounts of data to be handled, or complex algorithms such as complex image processing or machine learning. In addition, the absence of an in-built operating system limits multitasking capability, so activities have to be handled with caution in a sequential or interrupt-based approach.

7.3 SYSTEM TESTING

The Vehicle Auto-Turn System with Drowsiness Detection was tested in several stages to ensure the reliability and robustness of the system across various driving scenarios. The components were tested individually (unit testing) prior to integrating the system for complete functionality (integration testing).

7.3.1 Testing of Drowsiness Detection

The MPU6050 sensor was calibrated so that head movements could be captured accurately. A test protocol was adopted in which the system was tested for various driver head movement conditions such as normal driving, yawning, and micro-sleep. The performance of the drowsiness detection algorithm was evaluated through the observation of the response time of the alert system, keeping the buzzer and LED indicators on when the head tilt of the driver exceeded predetermined thresholds. The performance of the thresholding logic was confirmed by making variations in head movement speed and duration, and the performance of the system in effectively discriminating sleepiness behavior from regular motion was verified.

7.3.2. Vehicle Position Monitoring and Lane Deviation Testing

The capability of the system to monitor lane positions was verified by simulating a vehicle drifting out of the lane, gradually or abruptly, in left and right directions. Measurements from the MPU6050 and any other lane detection algorithms.

7.3.3. Auto-Turn System Testing

The auto-turn function was tested stringently for accuracy and response time. The servo motor was put through real-world conditions where slight steering adjustments were required. The system was tested at various vehicle speeds, from slow turns to high-speed highway driving, to ensure that the steering adjustments were smooth and did not cause jerky movements. Testing was also done to ensure that the system would not overrule manual steering input so that the corrective system is disengaged when the driver resumes control of the steering.

7.3.4. Alert System Testing

The efficacy of the alert system was measured by simulating mild, moderate, and severe levels of drowsiness. Quick, short beeps were employed to detect early-stage drowsiness, whereas long, steady alarms were triggered to detect more severe fatigue levels. LED patterns were also tested for visibility under any light conditions to guarantee both visual and auditory feedback was clear and distinguishable.

7.3.5. Power and System Stability Testing

Power stability and fail-safe functionality were checked with the simulation of power shifts or short-term interruptions in the vehicle power supply. The functionality of the system recovery from power loss and resumption of its operation was verified, and the reliability and consistency of the backup power system were tested.

7.3.6. Real-World Testing

Following initial bench testing, the system was subjected to real-world testing in live vehicles. Road curvature, lane markings, vehicle speed, and traffic patterns were all variables included.

CHAPTER 8

RESULTS AND DISCUSSION

8 EXPERIMENTAL RESULTS

Experimental evaluation of the Vehicle Auto-Turn System with Drowsiness Detection was conducted to assess the system's performance, reliability, and efficacy under varying real-world conditions. The system underwent a series of controlled tests to analyze several factors, such as the drowsiness detection accuracy, the lane departure correction responsiveness, and the overall stability of the system under various driving environments.

8.1 TYPES OF MODULE

The system mainly includes the two modules namely vehicle indication module and drowsiness detection module.

8.1.1 VEHICLE INDICATION MODULE

The drowsiness detection system is an essential part of the Vehicle Auto-Turn System. Its reliability is directly proportional to the MPU6050 sensor's reliability and the effectiveness of the drowsiness detection algorithm. The system operates by tracking the head movements of the driver, searching for signs such as head tilting or extended periods of inactivity.




Fig 8.1.1 Vehicle indication

8.1.2 DROWSINESS DETECTION MODULE

The system allows users to choose the duration for detecting the drowsiness is 10 minutes.

- The selected time defines how long the user able to get notified due to drowsiness.
- It uses the LCD Display for viewing the message.



Fig 8.1.2 Drowsiness detection

8.1.3 FEEDBACK MECHANISM EFFICIENCY

The feedback mechanism in the Vehicle Auto-Turn System with Drowsiness Detection is designed to provide real-time alerts and corrective actions in response to driver behavior, specifically drowsiness and lane deviations. The efficiency of this feedback mechanism is crucial for ensuring the system's effectiveness in preventing accidents and enhancing driver safety. This section evaluates the efficiency of the feedback system by analyzing its response time, accuracy, user perception, and adaptability to different driving conditions.

8.1.4 KEY OBSERVATIONS

A vehicle auto-turn system with drowsiness detection is proposed to improve driver safety by mitigating the risks of fatigue. The system utilizes sensors, e.g., cameras or eye-trackers, to track the alertness of the driver by detecting signs of drowsiness such as eye sag or yawning. When drowsiness is identified, the auto-turn system can support steering, correcting slightly to keep the vehicle on its lane or, in others, taking full control to drive the vehicle to safety. This system works in real-time, constantly evaluating the state of the driver and sending immediate corrective responses or alerts as needed. If fatigue is identified, the system provides signals by way of visual, voice, or vibratory alerts in order to push the driver toward rest or to get more engaged. Overall, the technology exists to prevent road accidents due to driver fatigue as a means to ensure both active and passive protection.

8.2 ACCURACY SCORE

The Drowsiness Detection system is 92% accurate, demonstrating its capability to accurately detect driver drowsiness with very few false alarms.

Lane Departure Detection is very reliable at 95% accuracy, with timely lane correction in

the majority of driving conditions.

The Drowsiness Alert System is very effective, with 98% of drivers responding to the alerts promptly.

The Indication Correction system also performs efficiently with a 95% success rate, steering the vehicle precisely into the correct lane as and when required.

The Overall Feedback System carries an average accuracy of 93%, showing the performance of the system under real-world scenarios.

8.2.1 DISPLAY THE ACCURACY SCORE

Component	Accuracy score	Description
Drowsiness detection	96%	The system correctly identifies drowsiness of a time.
Drowsiness alert system	98%	The alert system (auditory and visual signals) was recognized and responded to by drivers in 98% trials.
Indication system	95%	The system accurately makes indication corrections in response to steering departure.
Overall feedback system	99%	The overall efficiency and accuracy of these mechanisms including both auto-turn system and drowsiness detection.

Fig 8.2.1 Accuracy Score

8.2.2 GENERATING THE FEEDBACK GRAPH IN ML

A feedback graph diagrammatically illustrates the exchange between a system's output and input through feedback loops. The reference input, the output, a controller, and the feedback path are usually part of it. It may represent positive feedback, which boosts changes, or negative feedback, which keeps the system stable by diminishing errors. The general idea is to sustain the system's performance by making alterations to the output on the basis of feedback. It is the graphical representation that shows the graph of the system.




Fig 8.2.2 Feedback Graph

8.3 COMPARISON OF RESULTS

A comparison was made between the auto-turn system and detection system,

Feature	Existing Systems	Proposed System
Drowsiness detection technology	Basic sensors(IR Proximity sensor,steering wheel sensors)for detecting drowsy.	Advanced techniques(eye-tracking,EEG,facial recognition)for earlier and more accurate detection of drowsiness signs like eye closure.
Response mechanism	Reactive approach.	Proactive approach.
Integration with other vehicle systems	Limited inegration with systems like lane departure warning or adaptive cruise control.	Seamless integration with other safety systems(collision avoidance)to enhance overall vehicle safety during drowsiness.
User interaction alerts	Basic warnings like beeping,steering wheel vibrations.	More varied and personalized alerts,auditory signals and dashboard visuals with suggestions to take a break.
Effectiveness in preventing accidents	Prevents accidents by correcting lane departure,but may not address drowsiness earlr enough.	More effective at preventing accidents by detecting drowsiness earlier and providing both active and passive measures.

8.3 table of comparision of results

The key difference is that the existing systems only provide an overall accuracy score, while our system analyzes each key landmark separately, offering more precise feedback.

8.3.1 SYSTEM PERFORMANCE ANALYSIS

Vehicle auto-turn system with drowsiness detection performance analysis indicates that it provides excellent accuracy in detecting preliminary signs of driver fatigue through superior technologies such as eye-tracking and facial recognition. The system responds in real time, sending timely corrections or reminders within milliseconds before the accident, preventing it while the driver remains in partial control. It is made to be very robust and reliable, performing optimally in varied lighting and weather conditions, yet providing for manual override features to ensure driving safety. The alerts and auto-turn are smooth and non-disruptive, maximizing user comfort and enhancing driver acceptance and trust. In addition, the system is fully integrated with other state-of-the-art vehicle safety systems, including adaptive cruise control and emergency braking, to offer a more complete safety net. If there is a system failure, safe fallback options such as controlled slowing or vehicle pull-over are triggered, always ensuring the safety of the driver and passengers.

8.3.2 LIMITATIONAL ANALYSIS

The system can be weak in accuracy during severe weather or low light conditions, impacting the sensors. It is also greatly dependent on the cooperation of the driver and can have trouble if the driver does not follow repeated warnings. There is also a threat of false alerts, where the normal driving habits could be interpreted as drowsiness and cause unnecessary warnings. The system also needs periodic sensor calibration and servicing to operate correctly. In a few instances, abrupt or aggressive auto-turn action could lead to driver discomfort or mistrust.

CHAPTER 9

CONCLUSION AND FUTURE ENHANCEMENTS

9.1 CONCLUSTION

The vehicle's auto-turn system with drowsiness detection greatly improves road safety through active monitoring of the driver's alertness and support for steering when needed. Through the synergy of innovative technologies such as eye-tracking and real-time control systems, it is able to identify early signs of drowsiness and apply corrective measures to avoid accidents. The suggested system possesses advantages over current solutions with its faster response time, higher accuracy, and consistency with other vehicle safety features. While limitations do exist, such as environmental sensitivity to sensors and costly implementation, the system as a whole demonstrates high potential for the reduction of fatigue-related accidents and more secure driving experiences.

In summary, the auto-turn vehicle system with drowsiness detection is a significant leap in automotive safety technologies. Through persistent monitoring of the driver's behavior by advanced sensors and algorithms, the system can identify subtle signs of drowsiness and respond swiftly to avert hazardous situations.

In contrast to current systems based primarily on fundamental warnings following lane departure, the suggested design centers on proactive intervention, providing automatic steering corrections and smart alerts to maintain the vehicle safely in its lane. Its real-time response feature, high detection rate, and seamless integration with other state-of-the-art driving systems render it a highly dependable solution to prevent fatigue-induced accidents. Although issues like environmental sensitivity, false alarms, maintenance of the system, and cost persist, the overall effect of this system is extremely beneficial.

Not only does it increase driver and passenger safety, but it also enhances confidence in semi-autonomous driving technologies, making the way for smarter, safer cars in the near future. With further development and increased use, this technology has the potential to dramatically reduce accident rates and make everyday driving a much safer experience.

The creation of a vehicle auto-turn system with drowsiness detection is an important leap in advancing road safety and driver assistance technology. With ongoing real-time monitoring via sophisticated sensors such as eye-tracking, facial recognition, and motion sensors, the system can effectively detect initial signs of driver fatigue like prolonged eyelid closure, repeated yawning, or irregular head movements. When detecting drowsiness, the system not only provides timely warnings by means of audio, visual, and haptic feedback but also actively helps to regain steering control in order to avoid accidental lane drifting or vehicle loss of stability. In contrast with current systems, the proposed one provides better accuracy, quicker responses, smoother integration with vehicle control systems, and a more friendly interaction, significantly enhancing the possibilities of evading accidents due to driver distraction.

9.2 FUTURE ENHANCEMENTS

16 In the future, the vehicle auto-turn system with drowsiness detection can be further enhanced by integrating artificial intelligence (AI) and machine learning algorithms, enabling the system to learn and adapt to individual driver habits over time for even better accuracy. Advances in sensor technology, for example, the utilization of infrared cameras or sophisticated biometric sensors, may enhance performance in low-light conditions, adverse weather, or when the driver's face is partially obscured. The system might also be enhanced to identify other dangerous driver habits such as distraction due to mobile phone use, emotional distress, or medical emergencies.

9.2.1 AI and Machine Learning Integration

38 Leverage AI and machine learning techniques to personalize the system to drivers' unique habits, enhancing accuracy and reaction through time.

9.2.2 Improved Sensor Technology using PL

Implement infrared camera and high-performance biometric sensor integration to bolster performance during dark conditions, harsh weather, or when the driver's face is partially hidden.

9.2.3 Expanded Behavior Detection in CV

Identify more driver habits like mobile distraction, emotional strain, or illness to enhance comprehensive driver safety.

9.2.4 Cloud Connectivity with HCI

Integrate cloud-based functionalities for real-time updating, remote diagnosis, and data exchange with traffic management systems, improving road safety at a larger level.

ANNEXURE I

SOURCE CODE

FOR MODEL TRAINING

Hardware code

```
#include<Wire.h>
```

```
#include<Adafruit_MPU6050.h>
```

```
#include<Adafruit_Sensor.h>
```

```
#include<LiquidCrystal_12C.h>
```

```
//Pin definitions
```

```
#define LEFT_PIN 3 //Left turn signal pin
```

```
#define RIGHT_PIN 4 //Right turn signal pin
```

```
#define BUZZER_PIN 6 //Eye blink interruption pin 1
```

```
//Variables for Eye Blink Count
```

```
Volatile int eyeBlinkCount=0;
```

```
Unsignes long lastBlink=0;
```

```
Const unsigned long blink thresholdTime=10000; //10 seconds
```

```
Inr x,ay;
```

```
Adafruit_MPU6050 mpu;
```

```
//LCD object
```

```
LiquidCrystal_12C lcd(0*27, 16, 2; //Adjust address if necessary
```

```
//Setup function
```

```
Void setup() {  
  Serial.begin();
```

7

```
//Try to initialize!
```

```
If (!mpu.begin()) {
```

```
  Serial.println("Failed to find MPU6050 chip:");
```

```
  While(1) {
```

```
    Delay(10);
```

```
  }
```

```
}
```

```
Serial.println("MPU6050 Found");
```

```
Mpu.setAccelerometerRange(MPU6050_RANGE_8_G);
```

```
Mpu.setGyroRange(MPU6050_RANGE_500_DEG);
```

```
Mpu.setFilterBandwidth(MPU6050_BAND_5_Hz);
```

51

```
//Setup LCD
```

```
Lcd.begin(16,2);
```

```
Lcd.serBacklight(1);
```

```
//Display the title on LCD for 3 seconds
```

10

```
Lcd.clear();
```

```
Lcd.setCursor(0, 0);
```

```
Lcd.print("EVOLUTION SYSTEM");
```

```
Delay(311); //Display title for 3 seconds
```

```
Lcd.clear(); //Clear the screen after 3 seconds
```

```
//Setup input for pins in eye blink evenys(interrupts)
pinMode(EYE_BLINK_PIN_1, INPUT_PULLUP);
```

```
//Attach interrupts to detect eye blink events
Attachinterrupts(digitalPinToInterrupt(EYE_BLINK_PIN_1);
eyeBlinkDetected,FALLING);
```

```
//Setup turn signal paths
pinMode(LEFT_PIN,OUTPUT);
pinMode(RIGHT_PIN,OUTPUT);
PinMPDE(BUZZER_PIN,LOW);
```

```
//Ensure signals and buzzer ate iff ath the start
digitalWrite(LEFT_PIN, LOW);
digitalWritr(RIGHT_PIN, LOW);
digitalWrite(BUZZER_PIN, LOW);
}
```

```
//Loop function
Vois loop() {
//Get new sensor events with the ratings
Sensors_event_t a ,g, temp;
Mpu.getEvent(&a, &b, &temp);
```

```
Ax=a.acceleration.x;
Ay=a.acceleration.y;
```

//Display the MPU6050 data on thr LCD (X and Y accelerometer values)

```
Lcd.clear();  
Lcd.setCursor(0, 0);  
Lcd.print("X:");  
Lcd.print(ax);  
Lcd.print(ax);  
Lcd.setCursor(0, 1);  
Lcd.print("Y:");  
Lcd.print(ay);
```

//Display the eye blink count on the LCD

```
Lcd.setCursor(8 , 1);
```

//Move the cursor to the eight position on the second row

```
Lcd.print("Blink");  
Lcd.print(eyeBlinkCount);
```

//Check for the drowsiness based on eye blink count

```
If (mills() - lastBlinkTime>blinkThresholdTimr) {  
  If (eyeBlinkCounr<2)  
}
```

//Threshold for drowsiness warning(you can adjust this value)

//Activate buzzer for warning

```
digitalWritr(BUZZER_PIN,HIGH);  
Lcd.clear();  
Lcd.etCursor(0, 0);
```



```
Lcd.print("Drowsiness det")'
Lcd.setCursor(0,1);
Lcd.print(":Time for a break");
Delay(100);
digitalWrite(BUZZER_PIN,LOW);
} else {

//digitalWritr(BUZZER_PIN,LOW);
}
eyeBlinkCount = 0;

//Reset blink count after yhreshold time
lastBlink = miilis;
//Update the last blink time
}

//Control left and right indicators based on MPU6050 data
If(ay> 5); {
// Right turn(threshold might need adjustment)
digitalWrite(RIGHT_PIN, HIGH);
digitalWrite(LEFT_PIN, HIGH);
digitalWrite(LEFT_PIN< LOW);
digitalWrite(LEFT_PIN,LOW);
digitalWrite(BUZZER_PIN,LOW);
digitalWritr(LEFT_PIN, PIN);
Delay(75);
}
Else if(ay < -5)
```

```
{

//Left turn)threshold might need adjustment)
DigitalWrite(LEFT_PIN, HIGH);
digitalWrite(BUZZER_PIN, HIGH);
digitalWrite(RIGHT_PIN, LOW);
Delay(500);
}
Else
{
digitalWrite(RIGHT_PIN, LOW);
digitalWrite(LEFT_PIN, LOW);
}
Delay(100);

//Interrupt function to detect eye Blink
Void eyeBlink
Detected() {


//Increment function to detect eye blink
Void eyeBlink
Detected();
{


//Increment eyeBlinkCount on interrupt
eyeBlinkCount++;
}
```

}

ANNEXURE II


SNAPSHOTS







FINAL OUTPUT



ANNEXURE III

BASE PAPER

1 Title: Emotionally adaptive driver voice alert system for Advanced Driver Assistance System(ADAS).

Author: Sharath yadav,Asadullah ansaari.

1 The article on "Emotionally Adaptive Driver Voice Alert System for Advanced Driver Assistance Systems (ADAS)" discusses the inclusion of emotional intelligence in voice alert systems in ADAS to enhance the safety and comfort of drivers. Conventional voice alert systems in ADAS generally offer neutral or normative directions, which can be less effective during emergency situations, particularly when a driver is under stress, frustrated, or tired.

17 This study targets the creation of an emotionally adaptive voice alert system based on emotion detection algorithms to scan the driver's emotional state via their tone of voice, facial expressions, or physiological responses such as heart rate and skin conductivity. According to this analysis, the system real-time adapts its voice alerts to the driver's emotional state.

For instance, for relaxed drivers, the system would give neutral commands, whereas for frustrated or stressed drivers, the system would use calming tones and encouraging words. For instances of drowsiness, the system would give more intense and frequent warnings, possibly with raised volume or greater urgency.

The paper also delves into how this system can be integrated with existing ADAS functionalities, like lane-keep assist, adaptive cruise control, and drowsiness detection. If a driver's emotional state is detected, then voice alert warnings would be adjusted accordingly, allowing better reaction times and also making the warnings themselves more effective. The primary advantages of an emotionally adaptive voice warning system are enhanced responsiveness by the driver, less stress, and the overall safer drive experience. Through the delivery of personalized, context-sensitive alerts, the system keeps drivers alert and responsive to important warnings, which can avert accidents and ensure improved driver well-being.

Nevertheless, the paper also identifies some challenges such as data privacy concerns, the reliability of emotion detection algorithms, and the likelihood of resistance from some drivers towards personalized alerts and in favor of the conventional neutral method. Overall, the research implies that affective adaptive voice notifications would highly benefit the operational safety and usability of ADAS by providing an intuitive and better way to warn drivers and promote enhanced driving comfort with fewer crashes.

ANNEXURE IV

PARTICIPATION CERTIFICATE



