
Started on Monday, 27 April 2026, 7:00 PM

State Finished

Completed on Monday, 27 April 2026, 7:49 PM

Time taken 49 mins 3 secs

Grade 9.00 out of 10.00 (90%)

Question 1 | Correct Mark 1.00 out of 1.00

Program to print all the distinct elements in an array. Distinct elements are nothing but the unique (non-duplicate) elements present in the given array.

Input Format:

First line take an Integer input from stdin which is array length n.

Second line take n Integers which is inputs of array.

Output Format:

Print the Distinct Elements in Array in single line which is space Separated

Example Input:

5

1 2 2 3 4

Output:

1 2 3 4

Example Input:

6

1 1 2 2 3 3

Output:

1 2 3

For example:

Input	Result
5	1 2 3 4
1	
2	
2	
3	
4	

Answer: (penalty regime: 0 %)

```
import sys
def solve():
    data = sys.stdin.read().split()
    if not data:
        return
    n = int(data[0])
    elements = data[1:n+1]
    seen = set()
    distinct_element = []
    for item in elements:
        if item not in seen:
            distinct_element.append(item)
            seen.add(item)
    print(*distinct_element)
if __name__ == "__main__":
    solve()
```

	Input	Expected	Got	
✓	5 1 2 2 3 4	1 2 3 4	1 2 3 4	✓
✓	6 1 1 2 2 3 3	1 2 3	1 2 3	✓
✓	5 11 22 11 22 11	11 22	11 22	✓
✓	10 1 2 3 4 5 1 2 3 4 5	1 2 3 4 5	1 2 3 4 5	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 2 | Correct Mark 1.00 out of 1.00

The **DNA sequence** is composed of a series of nucleotides abbreviated as 'A', 'C', 'G', and 'T'.

- For example, "ACGAATTCG" is a **DNA sequence**.

When studying **DNA**, it is useful to identify repeated sequences within the DNA.

Given a string **s** that represents a **DNA sequence**, return all the **10-letter-long** sequences (substrings) that occur more than once in a DNA molecule. You may return the answer in **any order**.

Example 1:

Input: s = "AAAAACCCCCAAAAACCCCCAAAAAGGGTTT"

Output: ["AAAAACCCCC", "CCCCAAAAA"]

Example 2:

Input: s = "AAAAAAAAAAAA"

Output: ["AAAAAAAAA"]

For example:

Input	Result
AAAAACCCCCAAAAACCCCCAAAAAGGGTTT	AAAAACCCCC CCCCAAAAA

Answer: (penalty regime: 0 %)

```
s = input().strip()
seen = set()
repeated = []
for i in range(len(s) - 9):
    seq = s[i:i+10]
    if seq in seen:
        if seq not in repeated:
            repeated.append(seq)
    else:
        seen.add(seq)
for seq in repeated:
    print(seq)
```

	Input	Expected	Got	
✓	AAAAACCCCCAAAAACCCCCAAAAAGGGTTT	AAAAACCCCC CCCCAAAAA	AAAAACCCCC CCCCAAAAA	✓
✓	AAAAAAAAAAAA	AAAAAAAAA	AAAAAAAAA	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 3 | Correct Mark 1.00 out of 1.00

There is a malfunctioning keyboard where some letter keys do not work. All other keys on the keyboard work properly.

Given a string text of words separated by a single space (no leading or trailing spaces) and a string brokenLetters of all distinct letter keys that are broken, return the number of words in text you can fully type using this keyboard.

Example 1:

Input: text = "hello world", brokenLetters = "ad"

Output:

1

Explanation: We cannot type "world" because the 'd' key is broken.

For example:

Input	Result
hello world ad	1
Faculty Upskilling in Python Programming ak	2

Answer: (penalty regime: 0 %)

```
import sys
def solve():
    input_data = sys.stdin.read().strip().splitlines()
    if not input_data:
        return
    text = input_data[0]
    broken_keys = input_data[1].lower() if len(input_data) > 1 else ""
    broken_set = set(broken_keys)
    words = text.split()
    count = 0
    for word in words:
        if all(char.lower() not in broken_set for char in word):
            count += 1
    print(count)
if __name__ == "__main__":
    solve()
```

	Input	Expected	Got	
✓	hello world ad	1	1	✓
✓	Welcome to REC e	1	1	✓
✓	Faculty Upskilling in Python Programming ak	2	2	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4 | Correct Mark 1.00 out of 1.00

Given an array of integers **nums** containing $n + 1$ integers where each integer is in the range $[1, n]$ inclusive. There is only **one repeated number** in **nums**, return *this repeated number*. Solve the problem using set.

Example 1:

Input: nums = [1,3,4,2,2]

Output: 2

Example 2:

Input: nums = [3,1,3,4,2]

Output: 3

For example:

Input	Result
1 3 4 4 2	4

Answer: (penalty regime: 0 %)

```
import sys
def solve():
    data = sys.stdin.read().split()
    if not data:
        return
    nums = [int(x) for x in data]
    seen = set()
    for num in nums:
        if num in seen:
            print(num)
            return
        seen.add(num)
if __name__ == "__main__":
    solve()
```

	Input	Expected	Got	
✓	1 3 4 4 2	4	4	✓
✓	1 2 2 3 4 5 6 7	2	2	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 5 | Correct Mark 1.00 out of 1.00

Given a tuple and a positive integer k , the task is to find the count of distinct pairs in the tuple whose sum is equal to K .

Examples:

Input: $t = (5, 6, 5, 7, 7, 8)$, $K = 13$

Output: 2

Explanation:

Pairs with sum $K (= 13)$ are $\{(5, 8), (6, 7), (6, 7)\}$.

Therefore, distinct pairs with sum $K (= 13)$ are $\{(5, 8), (6, 7)\}$.

Therefore, the required output is 2.

For example:

Input	Result
1,2,1,2,5 3	1
1,2 0	0

Answer: (penalty regime: 0 %)

```
import sys
def solve():
    input_data = sys.stdin.read().replace(',', ' ').replace('(', ' ').replace(')', ' ').split()
    if not input_data:
        return
    k = int(input_data[-1])
    nums = [int(x) for x in input_data[:-1]]
    seen_elements = set()
    distinct_pairs = set()
    for val in nums:
        target = k - val
        if target in seen_elements:
            pair = tuple(sorted((val, target)))
            distinct_pairs.add(pair)
            seen_elements.add(val)
    print(len(distinct_pairs))
if __name__ == "__main__":
    solve()
```

	Input	Expected	Got	
✓	5,6,5,7,7,8 13	2	2	✓
✓	1,2,1,2,5 3	1	1	✓
✓	1,2 0	0	0	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 6 | Correct Mark 1.00 out of 1.00

You are given an integer tuple **nums** containing distinct numbers. Your task is to perform a sequence of operations on this tuple until it becomes empty. The operations are defined as follows:

1. If the first element of the tuple has the smallest value in the entire tuple, remove it.
2. Otherwise, move the first element to the end of the tuple.

You need to return an integer denoting the number of operations required to make the tuple empty.

Constraints

- The input tuple **nums** contains distinct integers.
- The operations must be performed using tuples and sets to maintain immutability and efficiency.
- Your function should accept the tuple **nums** as input and return the total number of operations as an integer.

Example:

Input: nums = (3, 4, -1)

Output: 5

Explanation:

Operation 1: [3, 4, -1] -> First element is not the smallest, move to the end -> [4, -1, 3]

Operation 2: [4, -1, 3] -> First element is not the smallest, move to the end -> [-1, 3, 4]

Operation 3: [-1, 3, 4] -> First element is the smallest, remove it -> [3, 4]

Operation 4: [3, 4] -> First element is the smallest, remove it -> [4]

Operation 5: [4] -> First element is the smallest, remove it -> []

Total operations: 5

For example:

Test	Result
<code>print(count_operations((3, 4, -1)))</code>	5

Answer: (penalty regime: 0 %)

Reset answer

```
def count_operations(nums: tuple) -> int:
    # Your implementation here
    lst = list(nums)
    operations = 0
    while lst:
        operations += 1
        smallest = min(lst)
        if lst[0] == smallest:
            lst.pop(0)
        else:
            first_elements = lst.pop(0)
            lst.append(first_elements)
    return operations
```

	Test	Expected	Got	
✓	<code>print(count_operations((3, 4, -1)))</code>	5	5	✓

	Test	Expected	Got	
✓	print(count_operations((1, 2, 3, 4, 5)))	5	5	✓
✓	print(count_operations((5, 4, 3, 2, 1)))	15	15	✓
✓	print(count_operations((42,)))	1	1	✓
✓	print(count_operations((-2, 3, -5, 4, 1)))	11	11	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 7 | Correct Mark 1.00 out of 1.00

Check if a set is a subset of another set.

Example:

Sample Input1:

mango apple

mango orange

mango

output1:

yes

set3 is subset of set1 and set2

input2:

mango orange

banana orange

grapes

output2:

no

For example:

Test	Input	Result
1	mango apple mango orange mango	yes set3 is subset of set1 and set2
2	mango orange banana orange grapes	No

Answer: (penalty regime: 0 %)

```

try:
    s1 = input().strip()
    s2 = input().strip()
    s3 = input().strip()
    set1 = set(s1.split())
    set2 = set(s2.split())
    set3 = set(s3.split())
    if set3.issubset(set1) and set3.issubset(set2):
        print("yes")
        print("set3 is subset of set1 and set2")
    else:
        print("No")
except EOFError:
    pass

```

	Test	Input	Expected	Got	
✓	1	mango apple mango orange mango	yes set3 is subset of set1 and set2	yes set3 is subset of set1 and set2	✓
✓	2	mango orange banana orange grapes	No	No	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 8 | Correct Mark 1.00 out of 1.00

Coders here is a simple task for you, Given string str. Your task is to check whether it is a binary string or not by using python set.

Examples:

Input: str = "01010101010"

Output: Yes

Input: str = "REC101"

Output: No

For example:

Input	Result
01010101010	Yes
010101 10101	No

Answer: (penalty regime: 0 %)

```
input_str = input().strip()
string_set = set(input_str)
binary_set = {'0', '1'}
if string_set <= binary_set and len(input_str) > 0:
    print("Yes")
else:
    print("No")
```

	Input	Expected	Got	
✓	01010101010	Yes	Yes	✓
✓	REC123	No	No	✓
✓	010101 10101	No	No	✓

Passed all tests! ✓

Correct


Marks for this submission: 1.00/1.00.

Question 9 | Correct Mark 1.00 out of 1.00

Given an array of strings `words`, return *the words that can be typed using letters of the alphabet on only one row of American keyboard like the image below.*

In the **American keyboard**:

- the first row consists of the characters `"qwertyuiop"`,
- the second row consists of the characters `"asdfghjkl"`, and
- the third row consists of the characters `"zxcvbnm"`.



Example 1:

Input: `words = ["Hello", "Alaska", "Dad", "Peace"]`

Output: `["Alaska", "Dad"]`

Example 2:

Input: `words = ["omk"]`

Output: `[]`

Example 3:

Input: `words = ["adsdf", "sfd"]`

Output: `["adsdf", "sfd"]`

For example:

Input	Result
4	Alaska
Hello	Dad
Alaska	
Dad	
Peace	
2	adsfd
adsfd	afd
afd	

Answer: (penalty regime: 0 %)

```

n = int(input())
words = []
for _ in range(n):
    words.append(input().strip())
row1 = set("qwertyyuiop")
row2 = set("asdfghjkl")
row3 = set("zxcvbnm")
result = []
for word in words:
    w = word.lower()
    if set(w) . issubset(row1) or set(w) . issubset(row2) or set(w) . issubset(row3):
        result.append(word)
if result:
    for w in result:
        print(w)
else:
    print("No words")

```

	Input	Expected	Got	
✓	4 Hello Alaska Dad Peace	Alaska Dad	Alaska Dad	✓
✓	1 omk	No words	No words	✓
✓	2 adsfd afd	adsfd afd	adsfd afd	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 10 | Incorrect Mark 0.00 out of 1.00

Write a program to eliminate the common elements in the given 2 arrays and print only the non-repeating elements and the total number of such non-repeating elements.

Input Format:

The first line contains space-separated values, denoting the size of the two arrays in integer format respectively.

The next two lines contain the space-separated integer arrays to be compared.

Sample Input:

```
5 4
1 2 8 6 5
2 6 8 10
```

Sample Output:

```
1 5 10
3
```

Sample Input:

```
5 5
1 2 3 4 5
1 2 3 4 5
```

Sample Output:

```
NO SUCH ELEMENTS
```

For example:

Input	Result
5 4 1 2 8 6 5 2 6 8 10	1 5 10 3
5 5 1 2 3 4 5 1 2 3 4 5	NO SUCH ELEMENTS

Answer: (penalty regime: 0 %)

```
import sys
def solve():
    input_data = sys.stdin.read().split()
    if not input_data:
        return
    try:
        n = int(input_data[0])
        m = int(input_data[1])
        arr1 = input_data[2 : 2 + n]
        arr2 = input_data[2 + n : 2 + n + m]
        set1 = set(arr1)
        set2 = set(arr2)
        result = [x for x in arr1 if x not in set2] + [y for y in arr2 if y not in set1]
        if not result:
            print("NO SUCH ELEMENTS")
        else:
            print(" ".join(result))
            print(len(result))
```

Syntax Error(s)

File "__tester__.python3", line 19

except (ValueError, IndexError):

^^^^^^

SyntaxError: invalid syntax

Incorrect

Marks for this submission: 0.00/1.00.