
Started on Tuesday, 12 May 2026, 9:32 PM

State Finished

Completed on Tuesday, 12 May 2026, 10:14 PM

Time taken 42 mins 3 secs

Grade 10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two Strings s1 and s2, remove all the characters from s1 which is present in s2.

Constraints

1<= string length <= 200

Sample Input 1

experience
enc

Sample Output 1

xpri

Answer: (penalty regime: 0 %)

```
a = input()
b = input()
c=""
for i in a:
    if i not in b:
        c+=i
print(c)
```

	Input	Expected	Got	
✓	experience enc	xpri	xpri	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 2 | Correct Mark 1.00 out of 1.00

Balanced strings are those that have an equal quantity of 'L' and 'R' characters.

Given a balanced string *s*, split it in the maximum amount of balanced strings.

Return the maximum amount of split balanced strings.

Example 1:

Input:

RLRRLRLRL

Output:

4

Explanation: *s* can be split into "RL", "RRL", "RL", "RL", each substring contains same number of 'L' and 'R'.

Example 2:

Input:

RLLLLRRRLR

Output:

3

Explanation: *s* can be split into "RL", "LLLLRR", "LR", each substring contains same number of 'L' and 'R'.

Example 3:

Input:

LLLLRRRR

Output:

1

Explanation: *s* can be split into "LLLLRRRR".

Constraints:

$1 \leq s.length \leq 1000$

s[*i*] is either 'L' or 'R'.

s is a balanced string.

For example:

Test	Result
<code>print(BalancedStrings('RLRRLRLRL'))</code>	4
<code>print(BalancedStrings('RLLLLRRRLR'))</code>	3

Answer: (penalty regime: 0 %)

[Reset answer](#)

```
def BalancedStrings(s,l=0, r=0, count=0):  
    for i in s:  
        if i == 'L':  
            l+=1  
        elif i== 'R':  
            r+= 1  
        if l==r:  
            count+=1  
    return count
```

	Test	Expected	Got	
✓	print(BalancedStrings('RLRRLRLRL'))	4	4	✓
✓	print(BalancedStrings('RLLLRRRLR'))	3	3	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 3 | Correct Mark 1.00 out of 1.00

Given an array **nums** containing **n** distinct numbers in the range **[0, n]**, return *the only number in the range that is missing from the array*.

Example 1:

Input: nums = [3,0,1]

Output: 2

Explanation: n = 3 since there are 3 numbers, so all numbers are in the range [0,3]. 2 is the missing number in the range since it does not appear in nums.

Example 2:

Input: nums = [0,1]

Output: 2

Explanation: n = 2 since there are 2 numbers, so all numbers are in the range [0,2]. 2 is the missing number in the range since it does not appear in nums.

Example 3:

Input: nums = [9,6,4,2,3,5,7,0,1]

Output: 8

Explanation: n = 9 since there are 9 numbers, so all numbers are in the range [0,9]. 8 is the missing number in the range since it does not appear in nums.

For example:

Test	Result
print(missingNumber([3,0,1]))	2
print(missingNumber([0,1]))	2

Answer: (penalty regime: 0 %)

Reset answer

```
def missingNumber(n):
    count = 0
    flag = 0
    p = len(n)-1
    for i in range(p):
        count += 1
        if count not in n:
            flag = 1
        if flag == 1:
            break
    if flag == 1:
        return count
    else:
        return n[p] + 1
```

	Test	Expected	Got	
✓	print(missingNumber([3,0,1]))	2	2	✓

	Test	Expected	Got	
✓	print(missingNumber([0,1]))	2	2	✓
✓	print(missingNumber([9,6,4,2,3,5,7,0,1]))	8	8	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4 | Correct Mark 1.00 out of 1.00

An list contains N numbers and you want to determine whether two of the numbers sum to a given number K. For example, if the input is 8, 4, 1, 6 and K is 10, the answer is yes (4 and 6). A number may be used twice.

Input Format

The first line contains a single integer n , the length of list

The second line contains n space-separated integers, list[i].

The third line contains integer k.

Output Format

Print Yes or No.

Sample Input

```
7
0 1 2 4 6 5 3
1
```

Sample Output

Yes

For example:

Input	Result
5 8 9 12 15 3 11	Yes
6 2 9 21 32 43 43 1 4	No

Answer: (penalty regime: 0 %)

```
a = int(input())
p = input()
b = list(map(int,p.split()))
count = 0
c = int(input())
for i in range(len(b)):
    for j in range(i+1, len(b)):
        if(b[i] + b[j]) == c:
            print("Yes")
            count = 1
            break
    if count == 1:
        break
if count == 0:
    print("No")
```

	Input	Expected	Got	
✓	5 8 9 12 15 3 11	Yes	Yes	✓
✓	6 2 9 21 32 43 43 1 4	No	No	✓
✓	6 13 42 31 4 8 9 17	Yes	Yes	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 5 | Correct Mark 1.00 out of 1.00

You are given an $m \times n$ integer matrix `matrix` with the following two properties:

- Each row is sorted in non-decreasing order.
- The first integer of each row is greater than the last integer of the previous row.

Given an integer `target`, return `True` if `target` is in `matrix` or `False` otherwise.

You must write a solution in $O(\log(m * n))$ time complexity.

Example 1:

1	3	5	7
10	11	16	20
23	30	34	60

Input: `matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]]`, `target = 3`

Output: `True`

Example 2:

1	3	5	7
10	11	16	20
23	30	34	60

Input: `matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]]`, `target = 13`

Output: `False`

For example:

Test	Result
<code>print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 13))</code>	False
<code>print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 3))</code>	True

Answer: (penalty regime: 0 %)

[Reset answer](#)

```
def searchMatrix(matrix: list[list[int]], target: int) -> bool:
    for i in range(len(matrix)):
        for j in range(len(matrix)):
            if matrix[i][j] == target:
                return True
    return False
```

	Test	Expected	Got	
✓	print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 13))	False	False	✓
✓	print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 3))	True	True	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 6 | Correct Mark 1.00 out of 1.00

String should contain only the words are not palindrome.

Sample Input 1

Malayalam is my mother tongue

Sample Output 1

is my mother tongue

Answer: (penalty regime: 0 %)

```
w = input().split(' ')
u=""
for i in w:
    i= i.lower()
    if i!=i[::-1]:
        u+=i+" "
print(u)
```

	Input	Expected	Got	
✓	Malayalam is my mother tongue	is my mother tongue	is my mother tongue	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 7 | Correct Mark 1.00 out of 1.00

Two string values S1, S2 are passed as the input. The program must print first N characters present in S1 which are also present in S2.

Input Format:

The first line contains S1.

The second line contains S2.

The third line contains N.

Output Format:

The first line contains the N characters present in S1 which are also present in S2.

Boundary Conditions:

$2 \leq N \leq 10$

$2 \leq \text{Length of S1, S2} \leq 1000$

Example Input/Output 1:

Input:

```
abcbde
cdefghbb
3
```

Output:

```
bcd
```

Note:

b occurs twice in common but must be printed only once.

Answer: (penalty regime: 0 %)

```
a = input()
b = input()
c = int(input())
d=""
count= 0
for i in a:
    if count>=c:
        break
    if i in b and i not in d:
        d+=i
        count+= 1
print(d)
```

	Input	Expected	Got	
✓	abcbde cdefghbb 3	bcd	bcd	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 8 | Correct Mark 1.00 out of 1.00

Given an array of integers `nums` which is sorted in ascending order, and an integer `target`, write a function to search `target` in `nums`.
 If `target` exists, then return its index. Otherwise, return `-1`.
 You must write an algorithm with $O(\log n)$ runtime complexity.

Example 1:

Input: `nums = [-1,0,3,5,9,12]`, `target = 9`

Output: 4

Explanation: 9 exists in `nums` and its index is 4

Example 2:

Input: `nums = [-1,0,3,5,9,12]`, `target = 2`

Output: -1

Explanation: 2 does not exist in `nums` so return -1

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-10^4 < \text{nums}[i], \text{target} < 10^4$
- All the integers in `nums` are **unique**.
- `nums` is sorted in ascending order.

For example:

Test	Result
<code>print(search([-1,0,3,5,9,12],9))</code>	4

Answer: (penalty regime: 0 %)

Reset answer

```
def search(num: list[int], target: int) -> int:
    count = 0
    flag= 0
    for i in range(len(num)):
        if num[i]==target:
            count=i
            flag=1
            break
    if flag==1:
        return count
    else:
        return -1
```

	Test	Expected	Got	
✓	<code>print(search([-1,0,3,5,9,12],9))</code>	4	4	✓

	Test	Expected	Got	
✓	print(search([-1,0,3,5,9,12],2))	-1	-1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 9 | Correct Mark 1.00 out of 1.00

Write a Python program for binary search.

For example:

Input	Result
1,2,3,5,8 6	False
3,5,9,45,42 42	True

Answer: (penalty regime: 0 %)

```
a = list(map(int, input().split(',')))
b = int(input())
c = 0
flag = 0
d = len(a)
a.sort()
while c<d:
    p= (c+d)//2
    if a[p]==b:
        print("True")
        flag=1
        break
    elif b<a[p]:
        d= p
    else:
        c= p+1
if flag==0:
    print("False")
```

	Input	Expected	Got	
✓	1,2,3,5,8 6	False	False	✓
✓	3,5,9,45,42 42	True	True	✓
✓	52,45,89,43,11 11	True	True	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 10 | Correct Mark 1.00 out of 1.00

Given an list, find peak element in it. A peak element is an element that is greater than its neighbors.

An element $a[i]$ is a peak element if

$A[i-1] \leq A[i] \geq A[i+1]$ for middle elements. $[0 < i < n-1]$

$A[i-1] \leq A[i]$ for last element $[i=n-1]$

$A[i] \geq A[i+1]$ for first element $[i=0]$

Input Format

The first line contains a single integer n , the length of A .

The second line contains n space-separated integers, $A[i]$.

Output Format

Print peak numbers separated by space.

Sample Input

5

8 9 10 2 6

Sample Output

10 6

For example:

Input	Result
4 12 3 6 8	12 8

Answer: (penalty regime: 0 %)

```
a= int(input())
b= list(map(int, input().split()))
c= []
d= len(b)- 1
if a>1:
    if b[0]>b[1]:
        c.append(b[0])
    if b[d]>b[d-1]:
        c.append(b[d])
for i in range(1, d-1):
    m= i-1
    n= i+1
    if b[i]>b[m] and b[i]>b[n]:
        c.append(b[i])
c.sort(reverse=True)
print(*c)
```

	Input	Expected	Got	
✓	7 15 7 10 8 9 4 6	15 10 9 6	15 10 9 6	✓

	Input	Expected	Got	
✓	4 12 3 6 8	12 8	12 8	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.