# Santra Seller App

## Backend API Specification

Version 1.0 • July 2026

---

**Base URL:** `https://api.santra.ae`

**Content-Type:** `application/json`

**Authentication:** Bearer JWT token in the `Authorization` header

**Response Envelope:** All responses are wrapped in a standard JSON envelope (see Section 1)

# Table of Contents


**1. Response Envelope & Error Handling**

**2. Authentication**

- 2.1 Request OTP
- 2.2 Verify OTP
- 2.3 Forgot Password
- 2.4 Reset Password
- 2.5 Logout

**3. Orders**

- 3.1 List Orders
- 3.2 Get Order Detail
- 3.3 Accept Order
- 3.4 Reject Order
- 3.5 Advance Order
- 3.6 Delete Order

**4. Notifications**

- 4.1 List Notifications
- 4.2 Mark Notification Read
- 4.3 Mark All Notifications Read

**5. Profile**

- 5.1 Get Seller Profile

**6. AI Assistant**

- 6.1 Send Message

**7. Data Models Reference**

# 1. Response Envelope & Error Handling

Every API response MUST be wrapped in this standard envelope. The mobile app parses all responses through a single generic handler that expects this shape.

**Success Response (HTTP 200):**

```
{
"success": true,
"message": "Operation successful",
"data": { ... }
}
```

**Validation Error (HTTP 422):**

```
{
"success": false,
"message": "Validation failed",
"errors": {
"phone": ["Phone number is invalid"],
"password": ["Password is too short"]
}
}
```

**General Error (HTTP 4xx/5xx):**

```
{
"success": false,
"message": "Human-readable error description"
}
```

**Standard HTTP Status Codes:**

| Code | Meaning | App Behavior |
|---|---|---|
| `200` | Success | Parse data field |
| `401` | Unauthorized / Token expired | Clear token, redirect to Welcome screen |
| `403` | Forbidden | Show error message to user |
| `404` | Not found | Show error message to user |
| `422` | Validation error | Parse errors map, show field-level messages |
| `500` | Server error | Show generic error toast |

# 2. Authentication

Phone-based OTP authentication. No password login for the main flow. After successful OTP verification, the server returns a JWT token that the app stores and sends as a Bearer token in the Authorization header for all subsequent requests.

## POST /api/seller/auth/request-otp

Send an OTP code to the seller's phone number.

**Headers:** None required (public endpoint)

**Request Body:**

| Field | Type | Required | Description |
|---|---|---|---|
| phone | string | Yes | Phone number with country code, e.g. "+9715XXXXXXXX" |

**Success Response (200):**

```
{
"success": true,
"message": "OTP sent",
"data": null
}
```

---

## POST /api/seller/auth/verify-otp

Verify the OTP code and return a JWT token on success.

**Headers:** None required (public endpoint)

**Request Body:**

| Field | Type | Required | Description |
|---|---|---|---|
| phone | string | Yes | Phone number with country code |
| code | string | Yes | The OTP code (e.g. "1234") |

**Success Response (200):**

```
{
"success": true,
"message": "Verified",
"data": {
"token": "eyJhbGciOiJIUzI1NiIs..."
}
}
```

**Validation Error (422) - Invalid code:**

```
{
"success": false,
```

```
"message": "Validation failed",
"errors": { "code": ["Invalid code"] }
}
```

---

## POST /api/seller/auth/forgot-password

Send a password reset code to the seller's phone number.

**Headers:** None required (public endpoint)

**Request Body:**

| Field | Type | Required | Description |
|---|---|---|---|
| phone | string | Yes | Phone number with country code |

**Success Response (200):**

```
{
"success": true,
"message": "Reset code sent",
"data": null
}
```

---

## POST /api/seller/auth/reset-password

Reset the seller's password using the verification code.

**Headers:** None required (public endpoint)

**Request Body:**

| Field | Type | Required | Description |
|---|---|---|---|
| phone | string | Yes | Phone number with country code |
| code | string | Yes | The verification code received via SMS |
| password | string | Yes | New password (min 6 characters) |

**Success Response (200):**

```
{
"success": true,
"message": "Password reset successful",
"data": null
}
```

**Validation Error (422):**

```
{
"success": false,
"message": "Validation failed",
```

```
"errors": { "password": ["Too short"] }
}
```

---

## POST /api/seller/auth/logout

Invalidate the current session/token on the server.

**Headers:** `Authorization: Bearer <token>`

**Request Body:** None

**Success Response (200):**

```
{
"success": true,
"message": "Logged out",
"data": null
}
```

# 3. Orders

Order management endpoints. All require authentication. Orders flow through the lifecycle: pending -> accepted -> on_way -> delivered. A pending order can also be rejected.

**All endpoints below require:** `Authorization: Bearer <token>`

## GET /api/seller/orders

Fetch all orders for the authenticated seller. Optionally filter by status.

**Query Parameters:**

| Field | Type | Required | Description |
|---|---|---|---|
| `status` | `string` | No | Filter by status. Values: "pending", "accepted", "on_way", "delivered", "cancelled", "rejected". Omit for all. |

**Success Response (200):**


```
{
"success": true,
"data": {
"orders": [
{
"id": 1042,
"customer": "Mariam Al Hosani",
"status": "pending",
"total": 245,
"placed": 8,
"deliver": "Today . 6:00 PM",
"date": "2026-06-23",
"payment": "paid",
"tags": ["gift"],
"due": 78,
"sla": 120,
"items": [
{
"name": "Pistachio Celebration Cake",
"ar": "...",
"qty": 1,
"img": "https://..."
}
],
"note": "Please write Happy Birthday...",
"noteAr": "...",
"images": ["https://...", "https://..."]
}
]
}
}
```

## GET /api/seller/orders/:id

Fetch a single order by ID. Same order shape as the list endpoint.

**Path Parameters:**

| Field | Type | Required | Description |
|---|---|---|---|
| id | integer | Yes | The order ID |

**Success Response (200):**

```
{
"success": true,
"data": { <single order object> }
}
```

*Note: The `data` field contains the order object directly (not wrapped in an "orders" array).*

---

## POST /api/seller/orders/:id/accept

Accept a pending order. Changes status from pending to accepted.

**Path Parameters:**

| Field | Type | Required | Description |
|---|---|---|---|
| id | integer | Yes | The order ID |

**Request Body:** None

**Success Response (200):**

```
{
"success": true,
"message": "Order accepted",
"data": null
}
```

---

## POST /api/seller/orders/:id/reject

Reject a pending order. Changes status from pending to rejected.

**Path Parameters:**

| Field | Type | Required | Description |
|---|---|---|---|
| id | integer | Yes | The order ID |

**Request Body:**

| Field | Type | Required | Description |
| --- | --- | --- | --- |
| reason | string | No | Optional rejection reason |

**Success Response (200):**

```
{
"success": true,
"message": "Order rejected",
"data": null
}
```

---

## POST /api/seller/orders/:id/advance

Advance an order to the next status in the lifecycle: accepted -> on_way -> delivered.

**Path Parameters:**

| Field | Type | Required | Description |
| --- | --- | --- | --- |
| id | integer | Yes | The order ID |

**Request Body:** None

**Success Response (200):**

```
{
"success": true,
"message": "Order advanced",
"data": {
"status": "on_way"
}
}
```

---

## DELETE /api/seller/orders/:id

Delete a completed/cancelled/rejected order from the seller's list.

**Path Parameters:**

| Field | Type | Required | Description |
| --- | --- | --- | --- |
| id | integer | Yes | The order ID |

**Request Body:** None

**Success Response (200):**

```
{
"success": true,
"message": "Order deleted",
```

```
"data": null
}
```

# 4. Notifications

Notification management endpoints. All require authentication.

**All endpoints below require:** `Authorization: Bearer <token>`

## GET /api/seller/notifications

Fetch all notifications for the authenticated seller.

**Request Body:** None

**Success Response (200):**


```
{
"success": true,
"data": {
"notifications": [
{
"id": 1,
"group": "today",
"tone": "brand",
"icon": "bag",
"unread": true,
"title": "New order #1042",
"titleAr": "...",
"body": "Mariam placed an order for AED 245.",
"bodyAr": "...",
"time": "8m",
"timeAr": "..."
}
]
}
}
```


---

## POST /api/seller/notifications/:id/read

Mark a single notification as read.

**Path Parameters:**

| Field | Type | Required | Description |
|---|---|---|---|
| `id` | `integer` | Yes | The notification ID |

**Request Body:** None

**Success Response (200):**


```
{
"success": true,
"data": null
}
```

## POST /api/seller/notifications/read-all

Mark all notifications as read for the authenticated seller.

**Request Body:** None

**Success Response (200):**


```
{
"success": true,
"data": null
}
```

# 5. Profile

Seller profile endpoint. Requires authentication.

**All endpoints below require:** `Authorization: Bearer <token>`

## GET /api/seller/profile

Fetch the authenticated seller's profile.

**Request Body:** None

**Success Response (200):**

```
{
"success": true,
"data": {
"store_name": "Layla's Sweets",
"store_name_ar": "...",
"avatar": "https://...",
"open_now": true
}
}
```

**Profile fields:**

| Field | Type | Required | Description |
|---|---|---|---|
| `store_name` | `string` | Yes | Store name in English |
| `store_name_ar` | `string` | Yes | Store name in Arabic |
| `avatar` | `string` | Yes | URL to the store's avatar/logo image |
| `open_now` | `boolean` | Yes | Whether the store is currently open |

# 6. AI Assistant

AI-powered assistant for sellers. The app sends the conversation history and live order context. The backend should proxy this to an LLM (e.g. Claude) server-side. Never embed model API keys in the mobile app.

**Requires:** `Authorization: Bearer <token>`

## POST /api/seller/assistant/complete

Send a message to the AI assistant and receive a reply.

**Request Body:**

| Field | Type | Required | Description |
|---|---|---|---|
| `lang` | `string` | Yes | Language code: "en" or "ar" |
| `order_context` | `string` | No | Compact text summary of the seller's current order board. One line per order with ID, customer, status, payment, tags, total, due time, items. |
| `messages` | `array` | Yes | Chat history. Each item: { "role": "user"\|"assistant", "content": "..." } |

**Example Request Body:**

```
{
"lang": "en",
"order_context": "#1042 . Mariam . pending . paid . gift . AED245 . due in 78m .
items: Pistachio Cake x1, Date Maamoul x2\n#1041 . Khalid . pending . cod .
express . AED120 . due in 27m . items: Kunafa x1",
"messages": [
{ "role": "user", "content": "Summarize my orders" },
{ "role": "assistant", "content": "You have 3 pending..." },
{ "role": "user", "content": "Which one is most urgent?" }
]
}
```

**Success Response (200):**

```
{
"success": true,
"data": {
"reply": "Order #1041 is most urgent - it's an Express order due in 27
minutes..."
}
}
```

# 7. Data Models Reference

Detailed field definitions for all JSON objects used in responses.

## Order Object

| Field | Type | Required | Description |
|---|---|---|---|
| `id` | `integer` | Yes | Unique order ID |
| `customer` | `string` | Yes | Customer full name |
| `status` | `string` | Yes | Order status. One of: "pending", "accepted", "on_way", "delivered", "cancelled", "rejected" |
| `total` | `integer` | Yes | Order total in AED (integer, no decimals) |
| `placed` | `integer` | Yes | Minutes since the order was placed |
| `deliver` | `string` | Yes | Human-readable delivery window, e.g. "Today . 6:00 PM" |
| `date` | `string` | Yes | ISO date string, e.g. "2026-06-23" |
| `payment` | `string` | Yes | Payment method: "cod" (cash on delivery) or "paid" (prepaid) |
| `tags` | `string[]` | Yes | Order type tags. Values: "vip", "express", "gift", "scheduled", "pickup". Can be empty array. |
| `due` | `integer?` | No | Minutes until delivery deadline. Negative = overdue. Null if not time-bound. |
| `sla` | `integer?` | No | Full SLA window in minutes (denominator for countdown). Null if not time-bound. |
| `items` | `array` | Yes | Array of OrderItem objects (see below) |
| `note` | `string` | Yes | Customer note in English (can be empty string) |
| `noteAr` | `string` | Yes | Customer note in Arabic (can be empty string) |
| `images` | `string[]` | Yes | Array of image URLs (reference photos from customer). Can be empty. |

## OrderItem Object

| Field | Type | Required | Description |
|---|---|---|---|
| `name` | `string` | Yes | Item name in English |
| `ar` | `string` | Yes | Item name in Arabic |
| `qty` | `integer` | Yes | Quantity ordered |
| `img` | `string` | Yes | URL to the product image |

## Notification Object

| Field | Type | Required | Description |
|---|---|---|---|
| id | integer | Yes | Unique notification ID |
| group | string | Yes | Grouping: "today" or "earlier" |
| tone | string | Yes | Color tone: "brand", "green", or "amber" |
| icon | string | Yes | Icon key: "bag", "clock", "wallet", "star", "checkCircle", "bell" |
| unread | boolean | Yes | Whether this notification is unread |
| title | string | Yes | Title in English |
| titleAr | string | Yes | Title in Arabic |
| body | string | Yes | Body text in English |
| bodyAr | string | Yes | Body text in Arabic |
| time | string | Yes | Relative time in English, e.g. "8m", "1h", "Yesterday" |
| timeAr | string | Yes | Relative time in Arabic, e.g. "...d", "...s" |

## SellerProfile Object

| Field | Type | Required | Description |
|---|---|---|---|
| store_name | string | Yes | Store name in English |
| store_name_ar | string | Yes | Store name in Arabic |
| avatar | string | Yes | URL to the store's avatar/logo image |
| open_now | boolean | Yes | Whether the store is currently accepting orders |

## ChatMessage Object (in request)

| Field | Type | Required | Description |
|---|---|---|---|
| role | string | Yes | "user" or "assistant" |
| content | string | Yes | The message text |

# Quick Reference: All Endpoints

| Method | Endpoint | Auth | Description |
|---|---|---|---|
| POST | `/api/seller/auth/request-otp` | No | Send OTP to phone |
| POST | `/api/seller/auth/verify-otp` | No | Verify OTP, get JWT token |
| POST | `/api/seller/auth/forgot-password` | No | Send password reset code |
| POST | `/api/seller/auth/reset-password` | No | Reset password with code |
| POST | `/api/seller/auth/logout` | Yes | Invalidate session |
| GET | `/api/seller/orders` | Yes | List orders (optional ?status= filter) |
| GET | `/api/seller/orders/:id` | Yes | Get single order |
| POST | `/api/seller/orders/:id/accept` | Yes | Accept pending order |
| POST | `/api/seller/orders/:id/reject` | Yes | Reject pending order |
| POST | `/api/seller/orders/:id/advance` | Yes | Advance order status |
| DELETE | `/api/seller/orders/:id` | Yes | Delete order |
| GET | `/api/seller/notifications` | Yes | List notifications |
| POST | `/api/seller/notifications/:id/read` | Yes | Mark notification read |
| POST | `/api/seller/notifications/read-all` | Yes | Mark all read |
| GET | `/api/seller/profile` | Yes | Get seller profile |
| POST | `/api/seller/assistant/complete` | Yes | AI assistant chat |