

HR_Database - https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBMDeveloperSkillsNetwork-DB0201EN-SkillsNetwork/labs/MySQL/week2/HR_Database_Create_Tables_Script.sql

1. **Department.csv(load data)**- https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBMDeveloperSkillsNetwork-DB0201EN-SkillsNetwork/labs/Labs_Coursera_V5/datasets/HR_Database/Departments.csv
2. **Employees.csv (load data)**- https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBMDeveloperSkillsNetwork-DB0201EN-SkillsNetwork/labs/MySQL/week2/data/Employees_updated.csv
3. **Jobs.csv** - https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBMDeveloperSkillsNetwork-DB0201EN-SkillsNetwork/labs/Labs_Coursera_V5/datasets/HR_Database/Jobs.csv
4. **Locations.csv** - https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBMDeveloperSkillsNetwork-DB0201EN-SkillsNetwork/labs/Labs_Coursera_V5/datasets/HR_Database/Locations.csv
5. **JobsHistory.csv** - <https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBMDeveloperSkillsNetwork-DB0201EN-SkillsNetwork/labs/MySQL/week2/data/JobsHistory.csv>

SAMPLE HR DATABASE TABLES

EMPLOYEES

EMP_ID	F_NAME	L_NAME	SSN	B_DATE	SEX	ADDRESS	JOB_ID	SALARY	MANAGER_ID	DEP_ID
E1001	John	Thomas	123456	1976-01-09	M	5631 Rice, OakPark,IL	100	100000	30001	2
E1002	Alice	James	123457	1972-07-31	F	980 Berry Ln, Elgin,IL	200	80000	30002	5
E1003	Steve	Wells	123458	1980-08-10	M	291 Springs, Gary,IL	300	50000	30002	5

JOB_HISTORY

EMPL_ID	START_DATE	JOBS_ID	DEPT_ID
E1001	2000-01-30	100	2
E1002	2010-08-16	200	5
E1003	2016-08-10	300	5

JOBS

JOB_IDENT	JOB_TITLE	MIN_SALARY	MAX_SALARY
100	Sr. Architect	60000	100000
200	Sr.SoftwareDeveloper	60000	80000
300	Jr.SoftwareDeveloper	40000	60000

DEPARTMENTS

DEPT_ID_DEP	DEP_NAME	MANAGER_ID	LOC_ID
2	Architect Group	30001	L0001
5	Software Development	30002	L0002
7	Design Team	30003	L0003

LOCATIONS

LOCT_ID	DEP_ID_LOC
L0001	2
L0002	5
L0003	7

How does a CROSS JOIN (also known as Cartesian Join) statement syntax look?

SELECT column_name(s)

FROM table1

CROSS JOIN table2;

How does an INNER JOIN statement syntax look?

SELECT column_name(s)

FROM table1 INNER JOIN table2

ON table1.column_name = table2.column_name;

WHERE condition;

Example 1:

- *Select the names and job start dates of all employees who work for the department number 5.*

Hint – Use the Inner join operation with the EMPLOYEES table as the left table and the JOB_HISTORY table as the right table.

Select E.F_NAME,E.L_NAME, JH.START_DATE

from EMPLOYEES as E INNER JOIN JOB_HISTORY as JH

on E.EMP_ID=JH.EMPL_ID

where E.DEP_ID ='5';



--- Query1A --- select E.F_NAME,E.L_NAME, JH...

Run time: 0.010 s

Result set 1

Search



F_NAME	L_NAME	START_DATE
Alice	James	2001-08-01
Steve	Wells	2001-08-16
Santosh	Kumar	2000-08-16
Ann	Jacob	2016-08-16

- **Select the names, job start dates, and job titles of all employees who work for the department number 5.**

Hint - Perform an INNER JOIN with 3 tables ☐ EMPLOYEES, JOB_HISTORY, JOBS.

select E.F_NAME,E.L_NAME, JH.START_DATE, J.JOB_TITLE

from EMPLOYEES as E

INNER JOIN JOB_HISTORY as JH on E.EMP_ID=JH.EMPL_ID

INNER JOIN JOBS as J on E.JOB_ID=J.JOB_IDENT

where E.DEP_ID ='5';



--- Query1B --- select E.F_NAME,E.L_NAME, JH...

Run time: 0.007 s

Result set 1

Search



F_NAME	L_NAME	START_DATE	JOB_TITLE
Alice	James	2001-08-01	Sr.Software Dev
Ann	Jacob	2016-08-16	Sr. Designer
Steve	Wells	2001-08-16	Jr.Software Dev
Santosh	Kumar	2000-08-16	Jr.Software Dev

How does a LEFT OUTER JOIN statement syntax look?

SELECT column_name(s)

FROM table1

LEFT OUTER JOIN table2

ON table1.column_name = table2.column_name

WHERE condition;

- ***Perform a Left Outer Join on the EMPLOYEES and DEPARTMENT tables and select employee id, last name, department id and department name for all employees.***

Hint – Use the Left Outer Join operation with the EMPLOYEES table as the left table and the DEPARTMENTS table as the right table.

Select E.EMP_ID,E.L_NAME,E.DEP_ID,D.DEP_NAME

from EMPLOYEES AS E

LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP;



--- Query 2A --- select E.EMP_ID,E.L_NAME,E.D...

Run time: 0.004 s

Result set 1

Search



EMP_ID	L_NAME	DEP_ID	DEP_NAME
E1001	Thomas	2	Architect Group
E1006	Allen	2	Architect Group
E1005	Hussain	2	Architect Group
E1002	James	5	Software Group
E1010	Jacob	5	Software Group
E1004	Kumar	5	Software Group
E1003	Wells	5	Software Group
E1007	Thomas	7	Design Team
E1009	Jones	7	Design Team
E1008	Gupta	7	Design Team

Show Less

- **Re-write the previous query but limit the result set to include only the rows for employees born before 1980.**

Hint – Use a WHERE clause and Left Outer Join operation. Alternatively, you could also use an INNER JOIN.

```
Select E.EMP_ID,E.L_NAME,E.DEP_ID,D.DEP_NAME
```

```
from EMPLOYEES AS E
```

```
LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP
```

```
where YEAR(E.B_DATE) < 1980;
```



--- Query 2B --- select E.EMP_ID,E.L_NAME,E.D...

Run time: 0.003 s

Result set 1

Search



EMP_ID ▲	L_NAME	DEP_ID	DEP_NAME
E1001	Thomas	2	Architect Group
E1006	Allen	2	Architect Group
E1002	James	5	Software Group
E1007	Thomas	7	Design Team

- ***Re-write the previous query but have the result set include all the employees but department names for only the employees who were born before 1980.***

Hint- Use an AND in the LEFT OUTER JOIN clause.

```
select E.EMP_ID,E.L_NAME,E.DEP_ID,D.DEP_NAME
```

```
from EMPLOYEES AS E
```

```
LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP
```

```
AND YEAR(E.B_DATE) < 1980;
```



--- Query 2C --- select E.EMP_ID,E.L_NAME,E.D...

Run time: 0.002 s

Result set 1

Search



EMP_ID	L_NAME	DEP_ID	DEP_NAME
E1001	Thomas	2	Architect Group
E1002	James	5	Software Group
E1003	Wells	5	
E1004	Kumar	5	
E1005	Hussain	2	
E1006	Allen	2	Architect Group
E1007	Thomas	7	Design Team
E1008	Gupta	7	
E1009	Jones	7	
E1010	Jacob	5	

Show Less

How does a RIGHT OUTER JOIN statement syntax look?

SELECT column_name(s)

FROM table1

RIGHT OUTER JOIN table2

ON table1.column_name = table2.column_name

WHERE condition;

How does a FULL OUTER JOIN statement syntax look?

SELECT column_name(s)

FROM table1

LEFT OUTER JOIN table2

ON table1.column_name = table2.column_name

WHERE condition

UNION

SELECT column_name(s)

FROM table1

RIGHT OUTER JOIN table2

ON table1.column_name = table2.column_name

WHERE condition

- ***Perform a Full Join on the EMPLOYEES and DEPARTMENT tables and select the First name, Last name and Department name of all employees.***

Hint – Use the Full Outer Join operation with the EMPLOYEES table as the left table and the DEPARTMENTS table as the right table.

Select E.F_NAME,E.L_NAME,D.DEP_NAME

from EMPLOYEES AS E

LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP

UNION

select E.F_NAME,E.L_NAME,D.DEP_NAME

from EMPLOYEES AS E

RIGHT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP



--- Query 3A --- select E.F_NAME,E.L_NAME,D...

Run time: 0.003 s

Result set 1

Search



F_NAME	L_NAME	DEP_NAME
John	Thomas	Architect Group
Alice	James	Software Group
Steve	Wells	Software Group
Santosh	Kumar	Software Group
Ahmed	Hussain	Architect Group
Nancy	Allen	Architect Group
Mary	Thomas	Design Team
Bharath	Gupta	Design Team
Andrea	Jones	Design Team
Ann	Jacob	Software Group

Show Less

- **Re-write the previous query but have the result set include all employee names but department id and department names only for male employees.**

Hint- Add an AND in Query 3A to filter on male employees in the ON clause. Alternatively, you can also use Left Outer Join.

```
select E.F_NAME,E.L_NAME,D.DEPT_ID_DEP, D.DEP_NAME
```

```
from EMPLOYEES AS E
```

```
LEFT OUTER JOIN DEPARTMENTS AS D ON E.DEP_ID=D.DEPT_ID_DEP AND E.SEX = 'M'
```

UNION

```
select E.F_NAME,E.L_NAME,D.DEPT_ID_DEP, D.DEP_NAME
```

from EMPLOYEES AS E

RIGHT OUTER JOIN DEPARTMENTS AS D ON E.DEPT_ID=D.DEPT_ID_DEP AND E.SEX = 'M';

✓ --- Query 3B --- select E.F_NAME,E.L_NAME,D....

Run time: 0.003 s

Result set 1

Search



F_NAME	L_NAME	DEPT_ID_DEP	DEP_NAME
John	Thomas	2	Architect Group
Steve	Wells	5	Software Group
Santosh	Kumar	5	Software Group
Ahmed	Hussain	2	Architect Group
Bharath	Gupta	7	Design Team
Alice	James		
Nancy	Allen		
Mary	Thomas		
Andrea	Jones		
Ann	Jacob		

Show Less

Union operator

The UNION operator is used to combine the result-set of two or more SELECT statements.

Every SELECT statement within UNION must have the same number of columns

The columns must also have similar data types

The columns in every SELECT statement must also be in the same order

```
SELECT column_name(s) FROM table1
```

```
UNION
```

```
SELECT column_name(s) FROM table2;
```

How does a SELF JOIN statement syntax look?

```
SELECT column_name(s)  
FROM table1 T1, table1 T2  
WHERE condition;
```