

Types of Recurrent Neural Networks (RNNs)

1 One-to-One RNN

This is the simplest form of RNN, where you have a single input and a single output. It does not exploit the sequential nature of the data, as there is no temporal relationship between inputs.

Mathematical Formulation: Let x_t represent the input at time step t , h_t be the hidden state, and y_t be the output at time step t .

The update rule for the hidden state is:

$$h_t = \sigma(W_{xh}x_t + W_{hh}h_{t-1} + b_h)$$

The output is:

$$y_t = W_{hy}h_t + b_y$$

Code Implementation:

Listing 1: many-to-one

```
1 import torch
2 import torch.nn as nn
3
4 class SimpleRNNOneToOne(nn.Module):
5     def __init__(self, input_size, hidden_size, output_size):
6         :
7         super(SimpleRNNOneToOne, self).__init__()
8         self.rnn = nn.RNN(input_size, hidden_size)
9         self.fc = nn.Linear(hidden_size, output_size)
10
11     def forward(self, x):
12         out, h = self.rnn(x)
13         out = self.fc(out)
14         return out
```

2 One-to-Many RNN

In a one-to-many RNN, you have a single input but multiple outputs. This is useful in tasks like generating a sequence (e.g., generating text or music) from an initial condition (e.g., a starting token).

Mathematical Formulation: The hidden state is updated as:

$$h_t = \sigma(W_{xh}x_t + W_{hh}h_{t-1} + b_h)$$

The output sequence is generated for each time step t :

$$y_t = W_{hy}h_t + b_y$$

Code Implementation:

Listing 2: One-to-many

```
1 class SimpleRNNOneToMany(nn.Module):
2     def __init__(self, input_size, hidden_size, output_size):
3         super(SimpleRNNOneToMany, self).__init__()
4         self.rnn = nn.RNN(input_size, hidden_size)
5         self.fc = nn.Linear(hidden_size, output_size)
6
7     def forward(self, x):
8         out, h = self.rnn(x)
9         out = self.fc(out) # Each time step has an output
10        return out
```

3 Many-to-One RNN

In a many-to-one RNN, you have a sequence of inputs and a single output. This architecture is used for tasks where you process an entire sequence and produce one output based on the sequence, such as sentiment analysis or classification.

Mathematical Formulation: For a sequence of inputs $\{x_1, x_2, \dots, x_T\}$, the hidden state is updated at each time step t :

$$h_t = \sigma(W_{xh}x_t + W_{hh}h_{t-1} + b_h)$$

At the end of the sequence, the output is:

$$y = W_{hy}h_T + b_y$$

Code Implementation:

Listing 3: many-to-one

```
1 class SimpleRNNManyToOne(nn.Module):
2     def __init__(self, input_size, hidden_size, output_size):
3         :
4         super(SimpleRNNManyToOne, self).__init__()
5         self.rnn = nn.RNN(input_size, hidden_size,
6                             batch_first=True)
7         self.fc = nn.Linear(hidden_size, output_size)
8
9     def forward(self, x):
```

```

8         out, h = self.rnn(x)
9         out = self.fc(h[-1]) # Use the last hidden state
10        for prediction
        return out

```

4 Many-to-Many RNN

In this case, both the input and the output are sequences. This is used in tasks like sequence-to-sequence (seq2seq) models for machine translation or summarization, where the input and output sequences have the same length or different lengths.

Mathematical Formulation: For an input sequence $\{x_1, x_2, \dots, x_T\}$, the hidden state is updated at each time step t :

$$h_t = \sigma(W_{xh}x_t + W_{hh}h_{t-1} + b_h)$$

At each time step t , an output is produced:

$$y_t = W_{hy}h_t + b_y$$

Code Implementation:

Listing 4: many-to-many

```

1 class SimpleRNNManyToMany(nn.Module):
2     def __init__(self, input_size, hidden_size, output_size)
3         :
4         super(SimpleRNNManyToMany, self).__init__()
5         self.rnn = nn.RNN(input_size, hidden_size,
6                             batch_first=True)
7         self.fc = nn.Linear(hidden_size, output_size)
8
9     def forward(self, x):
10        out, h = self.rnn(x)
11        out = self.fc(out) # Each time step produces an
12        output
13        return out

```

5 Summary of RNN Architectures

- **One-to-One:** Single input and output, typically used in simple prediction tasks.
- **One-to-Many:** Single input with multiple outputs, used in generative models.
- **Many-to-One:** Multiple inputs with a single output, often used in classification tasks.

- **Many-to-Many:** Multiple inputs with multiple outputs, used in tasks like machine translation or summarization.

These RNN architectures differ in terms of how input and output sequences are structured and are typically chosen based on the specific task and data type.