



Merge Sort


Like **QuickSort**, Merge Sort is a **Divide and Conquer** algorithm. It divides input array in two halves, calls itself for the two halves and then merges the two sorted halves. **The merge() function** is used for merging two halves. The merge(arr, l, m, r) is key process that assumes that arr[l..m] and arr[m+1..r] are sorted and merges the two sorted sub-arrays into one. See following C implementation for details.

```
MergeSort(arr[], l, r)
```

```
If r > l
```

1. Find the middle point to divide the array into two halves:
middle m = (l+r)/2
2. Call mergeSort for first half:
Call mergeSort(arr, l, m)
3. Call mergeSort for second half:
Call mergeSort(arr, m+1, r)
4. Merge the two halves sorted in step 2 and 3:
Call merge(arr, l, m, r)

The following diagram from [wikipedia](#) shows the complete merge sort process for an example array {38, 27, 43, 3, 9, 82, 10}. If we take a closer look at the diagram, we can see that the array is recursively divided in two halves till the size becomes 1. Once the size becomes 1, the merge processes comes into action and starts merging arrays back till the complete array is merged.



Recommended: Please solve it on "**PRACTICE**" first, before moving on to the solution.

C/C++

```
/* C program for Merge Sort */
#include<stdlib.h>
#include<stdio.h>

// Merges two subarrays of arr[].
// First subarray is arr[l..m]
// Second subarray is arr[m+1..r]
void merge(int arr[], int l, int m, int r)
{
    int i, j, k;
    int n1 = m - l + 1;
    int n2 = r - m;

    /* create temp arrays */
    int L[n1], R[n2];

    /* Copy data to temp arrays L[] and R[] */
    for (i = 0; i < n1; i++)
        L[i] = arr[l + i];
    for (j = 0; j < n2; j++)
        R[j] = arr[m + 1 + j];

    /* Merge the temp arrays back into arr[l..r]*/
    i = 0; // Initial index of first subarray
    j = 0; // Initial index of second subarray
    k = l; // Initial index of merged subarray
    while (i < n1 && j < n2)
    {
        if (L[i] <= R[j])
        {
            arr[k] = L[i];
            i++;
        }
        else
        {
            arr[k] = R[j];
            j++;
        }
        k++;
    }

    /* Copy the remaining elements of L[], if there
    are any */
    while (i < n1)
    {
        arr[k] = L[i];
        i++;
        k++;
    }

    /* Copy the remaining elements of R[], if there
    are any */
    while (j < n2)
    {
        arr[k] = R[j];
        j++;
        k++;
    }
}

/* l is for left index and r is right index of the
sub-array of arr to be sorted */
void mergeSort(int arr[], int l, int r)
{
    if (l < r)
    {
        // Same as (l+r)/2, but avoids overflow for
        // large l and h
        int m = l+(r-l)/2;

        // Sort first and second halves
        mergeSort(arr, l, m);
        mergeSort(arr, m+1, r);

        merge(arr, l, m, r);
    }
}
```

```

/* UTILITY FUNCTIONS */
/* Function to print an array */
void printArray(int A[], int size)
{
    int i;
    for (i=0; i < size; i++)
        printf("%d ", A[i]);
    printf("\n");
}

/* Driver program to test above functions */
int main()
{
    int arr[] = {12, 11, 13, 5, 6, 7};
    int arr_size = sizeof(arr)/sizeof(arr[0]);

    printf("Given array is \n");
    printArray(arr, arr_size);

    mergeSort(arr, 0, arr_size - 1);

    printf("\nSorted array is \n");
    printArray(arr, arr_size);
    return 0;
}

```

Java

```

/* Java program for Merge Sort */
class MergeSort
{
    // Merges two subarrays of arr[].
    // First subarray is arr[l..m]
    // Second subarray is arr[m+1..r]
    void merge(int arr[], int l, int m, int r)
    {
        // Find sizes of two subarrays to be merged
        int n1 = m - l + 1;
        int n2 = r - m;

        /* Create temp arrays */
        int L[] = new int [n1];
        int R[] = new int [n2];

        /*Copy data to temp arrays*/
        for (int i=0; i<n1; ++i)
            L[i] = arr[l + i];
        for (int j=0; j<n2; ++j)
            R[j] = arr[m + 1+ j];

        /* Merge the temp arrays */

        // Initial indexes of first and second subarrays
        int i = 0, j = 0;

        // Initial index of merged subarray array
        int k = l;
        while (i < n1 && j < n2)
        {
            if (L[i] <= R[j])
            {
                arr[k] = L[i];
                i++;
            }
            else
            {
                arr[k] = R[j];
                j++;
            }
            k++;
        }

        /* Copy remaining elements of L[] if any */
        while (i < n1)
        {
            arr[k] = L[i];
            i++;

```



```

        k++;
    }

    /* Copy remaining elements of R[] if any */
    while (j < n2)
    {
        arr[k] = R[j];
        j++;
        k++;
    }
}

// Main function that sorts arr[l..r] using
// merge()
void sort(int arr[], int l, int r)
{
    if (l < r)
    {
        // Find the middle point
        int m = (l+r)/2;

        // Sort first and second halves
        sort(arr, l, m);
        sort(arr, m+1, r);

        // Merge the sorted halves
        merge(arr, l, m, r);
    }
}

/* A utility function to print array of size n */
static void printArray(int arr[])
{
    int n = arr.length;
    for (int i=0; i<n; ++i)
        System.out.print(arr[i] + " ");
    System.out.println();
}

// Driver method
public static void main(String args[])
{
    int arr[] = {12, 11, 13, 5, 6, 7};

    System.out.println("Given Array");
    printArray(arr);

    MergeSort ob = new MergeSort();
    ob.sort(arr, 0, arr.length-1);

    System.out.println("\nSorted array");
    printArray(arr);
}
/* This code is contributed by Rajat Mishra */

```

Python3

```

# Python program for implementation of MergeSort
def mergeSort(arr):
    if len(arr) > 1:
        mid = len(arr)//2 #Finding the mid of the array
        L = arr[:mid] # Dividing the array elements
        R = arr[mid:] # into 2 halves

        mergeSort(L) # Sorting the first half
        mergeSort(R) # Sorting the second half

        i = j = k = 0

        # Copy data to temp arrays L[] and R[]
        while i < len(L) and j < len(R):
            if L[i] < R[j]:
                arr[k] = L[i]
                i+=1
            else:
                arr[k] = R[j]
                j+=1
            k+=1

```

```

# Checking if any element was left
while i < len(L):
    arr[k] = L[i]
    i+=1
    k+=1

while j < len(R):
    arr[k] = R[j]
    j+=1
    k+=1

# Code to print the list
def printList(arr):
    for i in range(len(arr)):
        print(arr[i],end=" ")
    print()

# driver code to test the above code
if __name__ == '__main__':
    arr = [12, 11, 13, 5, 6, 7]
    print ("Given array is", end="\n")
    printList(arr)
    mergeSort(arr)
    print("Sorted array is: ", end="\n")
    printList(arr)

# This code is contributed by Mayank Khanna

```

Output:

Given array is
12 11 13 5 6 7

Sorted array is
5 6 7 11 12 13

Time Complexity: Sorting arrays on different machines. Merge Sort is a recursive algorithm and time complexity can be expressed as following recurrence relation.

$$T(n) = 2T(n/2) + \Theta(n)$$

The above recurrence can be solved either using Recurrence Tree method or Master method. It falls in case II of Master Method and solution of the recurrence is $\Theta(n \log n)$.

Time complexity of Merge Sort is $\Theta(n \log n)$ in all 3 cases (worst, average and best) as merge sort always divides the array into two halves and take linear time to merge two halves.

Auxiliary Space: $O(n)$

Algorithmic Paradigm: Divide and Conquer

Sorting In Place: No in a typical implementation

Stable: Yes

Applications of Merge Sort

1. **Merge Sort is useful for sorting linked lists in $O(n \log n)$ time.** In the case of linked lists, the case is different mainly due to the difference in memory allocation of arrays and linked lists. Unlike arrays, linked list nodes may not be adjacent in memory. Unlike an array, in the linked list, we can insert items in the middle in $O(1)$ extra space and $O(1)$ time. Therefore merge operation of merge sort can be implemented without extra space for linked lists.

In arrays, we can do random access as elements are contiguous in memory. Let us say we have an integer (4-byte) array A and let the address of A[0] be x then to access A[i], we can directly access the memory at $(x + i*4)$. Unlike arrays, we can not do random access in the linked list. Quick Sort requires a lot of this kind of access. In linked list to access i'th index, we have to travel each and every node from the head to i'th node as we don't have a continuous block of memory. Therefore, the overhead increases for quicksort. Merge sort accesses data sequentially and the need of random access is low.

2. **Inversion Count Problem**
3. **Used in External Sorting**



Merge Sort | GeeksforGeeks



Snapshots:

l = left index

r = right index

38	27	43	3	9	82	10
----	----	----	---	---	----	----

Is $l < r$
Yes
 $m = l + (r - 1) / 2$

- [Recent Articles on Merge Sort](#)
- [Coding practice for sorting.](#)
- [Quiz on Merge Sort](#)

Other Sorting Algorithms on GeeksforGeeks:

[3-way Merge Sort](#), [Selection Sort](#), [Bubble Sort](#), [Insertion Sort](#), [Merge Sort](#), [Heap Sort](#), [QuickSort](#), [Radix Sort](#), [Counting Sort](#), [Bucket Sort](#), [ShellSort](#), [Comb Sort](#)

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



l = left index

r = right index

38	27	43	3	9	82	10
----	----	----	---	---	----	----

l = left index


r = right index

38	27	43	3	9	82	10
----	----	----	---	---	----	----


38	27	43	3
----	----	----	---


9	82	10
---	----	----

 $l \leq r$



After dividing the array into smallest units merging starts, based on comparison of elements.





Recommended Posts:

[Merge Sort with \$O\(1\)\$ extra space merge and \$O\(n \lg n\)\$ time](#)

[Why Quick Sort preferred for Arrays and Merge Sort for Linked Lists?](#)

[Quick Sort vs Merge Sort](#)

[3-way Merge Sort](#)

[Iterative Merge Sort](#)

[In-Place Merge Sort](#)

[Merge Sort using Multi-threading](#)

[Merge Sort for Linked Lists](#)

[C Program for Iterative Merge Sort](#)

[Merge Sort for Linked Lists in JavaScript](#)

[Count Inversions in an array | Set 1 \(Using Merge Sort\)](#)

[Merge Sort for Doubly Linked List](#)

[Java Program for Iterative Merge Sort](#)

[Python Program for Iterative Merge Sort](#)

[Union and Intersection of two linked lists | Set-2 \(Using Merge Sort\)](#)

Improved By : [Ita_c](#), [Mayank Khanna 2](#)

Article Tags : [Divide and Conquer](#) [Sorting](#) [Amazon](#) [Boomerang Commerce](#) [Goldman Sachs](#) [Grofers](#) [Microsoft](#) [Oracle](#) [Paytm](#) [Qualcomm](#)

[Target Corporation](#)

Practice Tags : [Paytm](#) [Amazon](#) [Goldman Sachs](#) [Microsoft](#) [Oracle](#) [Qualcomm](#) [Boomerang Commerce](#) [Grofers](#) [Target Corporation](#) [Divide and Conquer](#)

[Sorting](#)



89

☐ To-do ☐ Done

2.7

Based on 217 vote(s)

[Feedback/ Suggest Improvement](#)[Notes](#)[Improve Article](#)

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Important Update

When you log in with Disqus, we process personal data to facilitate your authentication and posting of comments. We also store the comments you post and those comments are immediately viewable and searchable by anyone around the world.

Please access our [Privacy Policy](#) to learn what personal data Disqus collects and your choices about how it is used. All users of our service are also subject to our [Terms of Service](#).

Proceed


















GAMING BROWSER
With RAM & CPU Limiters, VPN and Ad blocker

Get Opera GX





A computer science portal for geeks

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

[About Us](#)
[Careers](#)
[Privacy Policy](#)
[Contact Us](#)

PRACTICE

[Courses](#)
[Company-wise](#)
[Topic-wise](#)
[How to begin?](#)

LEARN

[Algorithms](#)
[Data Structures](#)
[Languages](#)
[CS Subjects](#)
[Video Tutorials](#)

CONTRIBUTE

[Write an Article](#)
[Write Interview Experience](#)
[Internships](#)
[Videos](#)

@geeksforgeeks, Some rights reserved

