

#### **Related Articles**

# Recursion

Difficulty Level: Easy • Last Updated: 31 Mar, 2021

#### What is Recursion?

The process in which a function calls itself directly or indirectly is called recursion and the corresponding function is called as recursive function. Using recursive algorithm, certain problems can be solved quite easily. Examples of such problems are <u>Towers of Hanoi (TOH)</u>, <u>Inorder/Preorder/Postorder Tree Traversals</u>, <u>DFS of Graph</u>, etc.

### A Mathematical Interpretation

Let us consider a problem that a programmer have to determine the sum of first n natural numbers, there are several ways of doing that but the simplest approach is simply add the numbers starting from 1 to n. So the function simply looks like,

approach(1) - Simply adding one by one 
$$f(n) = 1 + 2 + 3 + \dots + n$$

but there is another mathematical approach of representing this,

approach(2) – Recursive adding
$$f(n) = 1 \qquad n=1$$

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

There is a simple difference between the approach (1) and approach(2) and that is in **approach(2)** the function "**f()**" itself is being called inside the function, so this phenomenon is named as recursion and the function containing recursion is called recursive function, at the end this is a great tool in the hand of the programmers to code some problems in a lot easier and efficient way.

#### What is base condition in recursion?

In the recursive program, the solution to the base case is provided and the solution of the bigger problem is expressed in terms of smaller problems.

```
int fact(int n)
{
    if (n < = 1) // base case
        return 1;
    else
        return n*fact(n-1);
}</pre>
```

In the above example, base case for n < = 1 is defined and larger value of number can be solved by converting to smaller one till base case is reached.

# How a particular problem is solved using recursion?

The idea is to represent a problem in terms of one or more smaller problems, and add one or more base conditions that stop the recursion. For example, we compute factorial n if we know factorial of (n-1). The base case for factorial would be n = 0. We return 1 when n = 0.

# Why Stack Overflow error occurs in recursion?

If the base case is not reached or not defined, then the stack overflow problem may arise. Let us take an example to understand this.

```
int fact(int n)
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

```
if (n == 100)
        return 1;

else
        return n*fact(n-1);
}
```

If fact(10) is called, it will call fact(9), fact(8), fact(7) and so on but the number will never reach 100. So, the base case is not reached. If the memory is exhausted by these functions on the stack, it will cause a stack overflow error.

#### What is the difference between direct and indirect recursion?

A function fun is called direct recursive if it calls the same function fun. A function fun is called indirect recursive if it calls another function say fun\_new and fun\_new calls fun directly or indirectly. Difference between direct and indirect recursion has been illustrated in Table 1.

```
// An example of direct recursion
void directRecFun()
{
    // Some code...
    directRecFun();
    // Some code...
}

// An example of indirect recursion
void indirectRecFun1()
{
    // Some code...
    indirectRecFun2();
    // Some code...
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

```
// Some code...
indirectRecFun1();
// Some code...
}
```

#### What is difference between tailed and non-tailed recursion?

A recursive function is tail recursive when recursive call is the last thing executed by the function. Please refer tail recursion article for details.

### How memory is allocated to different function calls in recursion?

When any function is called from main(), the memory is allocated to it on the stack. A recursive function calls itself, the memory for a called function is allocated on top of memory allocated to calling function and different copy of local variables is created for each function call. When the base case is reached, the function returns its value to the function by whom it is called and memory is de-allocated and the process continues. Let us take the example how recursion works by taking a simple function.

### **CPP**

```
// A C++ program to demonstrate working of
// recursion
#include <bits/stdc++.h>
using namespace std;
void printFun(int test)
    if (test < 1)
        return;
    else {
        cout << test << " ";
        printFun(test - 1); // statement 2
        cout << test << " ";
        return:
    }
}
// Driver Code
int main()
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

#### Java

```
// A Java program to demonstrate working of
// recursion
class GFG {
    static void printFun(int test)
    {
        if (test < 1)
             return;
        else {
             System.out.printf("%d ", test);
             printFun(test - 1); // statement 2
             System.out.printf("%d ", test);
             return;
        }
    }
    // Driver Code
    public static void main(String[] args)
        int test = 3;
        printFun(test);
}
// This code is contributed by
// Smitha Dinesh Semwal
Python3
# A Python 3 program to
# demonstrate working of
# recursion
def printFun(test):
    if (test < 1):
        return
    else:
        print(test, end=" ")
        printFun(test=1) # statement 2
        print(test, end=" ")
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

```
printFun(test)
# This code is contributed by
# Smitha Dinesh Semwal
C#
// A C# program to demonstrate
// working of recursion
using System;
class GFG {
    // function to demonstrate
    // working of recursion
    static void printFun(int test)
        if (test < 1)
             return;
        else {
             Console.Write(test + " ");
             // statement 2
             printFun(test - 1);
             Console.Write(test + " ");
             return;
        }
    }
    // Driver Code
    public static void Main(String[] args)
    {
        int test = 3;
        printFun(test);
    }
}
// This code is contributed by Anshul Aggarwal.
PHP
<?php
```

```
// PHP program to demonstrate
// working of recursion
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our Cookie Policy & Privacy **Policy** 

function printFun(\$test)


```
{
    if ($test < 1)
         return;
    else
    {
         echo("$test ");
         // statement 2
         printFun($test-1);
         echo("$test ");
         return;
    }
}
// Driver Code
test = 3;
printFun($test);
// This code is contributed by
// Smitha Dinesh Semwal.
?>
Javascript
<script>
// JavaScript program to demonstrate working of
// recursion
function printFun(test)
    {
         if (test < 1)
             return;
         else {
             document.write(test + " ");
             printFun(test - 1); // statement 2
             document.write(test + " ");
             return;
         }
    }
// Driver code
    let test = 3;
    printFun(test);
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

### Output:

#### 3 2 1 1 2 3

When **printFun(3)** is called from main(), memory is allocated to **printFun(3)** and a local variable test is initialized to 3 and statement 1 to 4 are pushed on the stack as shown in below diagram. It first prints '3'. In statement 2, **printFun(2)** is called and memory is allocated to **printFun(2)** and a local variable test is initialized to 2 and statement 1 to 4 are pushed in the stack. Similarly, **printFun(2)** calls **printFun(1)** and **printFun(1)** calls **printFun(0)**. **printFun(0)** goes to if statement and it return to **printFun(1)**. Remaining statements of **printFun(1)** are executed and it returns to **printFun(2)** and so on. In the output, value from 3 to 1 are printed and then 1 to 3 are printed. The memory stack has been shown in below diagram.



Now, let's discuss a few practical problems which can be solved by using recursion and understand its basic working. For basic understanding please read the following articles.

# Basic understanding of Recursion.

**Problem 1:** Write a program and recurrence relation to find the Fibonacci series of n where n>2.

Mathematical Equation:

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

Recurrence Relation:

```
T(n) = T(n-1) + T(n-2) + O(1)
```

### **Recursive program:**

```
Input: n = 5
Output:
Fibonacci series of 5 numbers is : 0 1 1 2 3
```

## Implementation:

#### C++

```
// C++ code to implement Fibonacci series
#include <bits/stdc++.h>
using namespace std;
// Function for fibonacci
int fib(int n)
    // Stop condition
    if (n == 0)
        return 0;
    // Stop condition
    if (n == 1 || n == 2)
        return 1;
    // Recursion function
    else
        return (fib(n - 1) + fib(n - 2));
}
// Driver Code
int main()
{
    // Initialize variable n.
    int n = 5;
    cout<<"Fibonacci series of 5 numbers is: ";</pre>
    // for loop to print the fiboancci series.
    for (int i = 0 \cdot i < n \cdot i + 1)
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

```
return 0;
}
C
// C code to implement Fibonacci series
#include <stdio.h>
// Function for fibonacci
int fib(int n)
{
    // Stop condition
    if (n == 0)
        return 0;
    // Stop condition
    if (n == 1 || n == 2)
        return 1;
    // Recursion function
    else
        return (fib(n - 1) + fib(n - 2));
}
// Driver Code
int main()
{
    // Initialize variable n.
    int n = 5;
    printf("Fibonacci series "
            "of %d numbers is: ",
            n);
    // for loop to print the fiboancci series.
    for (int i = 0; i < n; i++) {</pre>
         printf("%d ", fib(i));
    }
    return 0;
}
Java
// Java code to implement Fibonacci series
import java.util.*;
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

```
// Function for fibonacci
static int fib(int n)
{
    // Stop condition
    if (n == 0)
        return 0;
    // Stop condition
    if (n == 1 || n == 2)
        return 1;
    // Recursion function
    else
        return (fib(n - 1) + fib(n - 2));
}
// Driver Code
public static void main(String []args)
{
    // Initialize variable n.
    int n = 5;
    System.out.print("Fibonacci series of 5 numbers is: ");
    // for loop to print the fiboancci series.
    for (int i = 0; i < n; i++)</pre>
    {
        System.out.print(fib(i)+" ");
    }
}
}
// This code is contributed by rutvik_56.
```

## Python3

```
# Python code to implement Fibonacci series
# Function for fibonacci
def fib(n):

    # Stop condition
    if (n == 0):
        return 0

# Stop condition
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

```
else:
        return (fib(n - 1) + fib(n - 2))
# Driver Code
# Initialize variable n.
n = 5;
print("Fibonacci series of 5 numbers is :",end=" ")
# for loop to print the fiboancci series.
for i in range(0,n):
    print(fib(i),end=" ")
C#
using System;
public class GFG
  // Function for fibonacci
  static int fib(int n)
  {
    // Stop condition
    if (n == 0)
      return 0;
    // Stop condition
    if (n == 1 | | n == 2)
      return 1;
    // Recursion function
      return (fib(n - 1) + fib(n - 2));
  }
  // Driver Code
  static public void Main ()
  {
    // Initialize variable n.
    int n = 5;
    Console.Write("Fibonacci series of 5 numbers is: ");
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

```
}
}

// This code is contributed by avanitrachhadiya2155
```

### **Javascript**

```
<script>
// JavaScript code to implement Fibonacci series
// Function for fibonacci
function fib(n)
   // Stop condition
   if(n == 0)
     return 0;
   // Stop condition
   if(n == 1 || n == 2)
      return 1;
   // Recursion function
   else
      return fib(n-1) + fib(n-2);
}
// Initialize variable n.
let n = 5;
document.write("Fibonacci series of 5 numbers is: ");
// for loop to print the fiboancci series.
for(let i = 0; i < n; i++)</pre>
    document.write(fib(i) + " ");
}
</script>
```

# Output

Fibonacci series of 5 numbers is: 0 1 1 2 3

Here is the recursive tree for input 5 which shows a clear picture of how a big problem


We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

 $fib(n) \rightarrow level\ CBT\ (UB) \rightarrow 2^n-1\ nodes \rightarrow 2^n\ function\ call \rightarrow 2^n*O(1) \rightarrow T(n) = O(2^n)$ 

For Best Case.

$$T(n) = \theta(2^n \geq 0)$$

# Working:



**Problem 2:** Write a program and recurrence relation to find the Factorial of n where n>2

# **Mathematical Eqution:**

#### Recurrence Relation:

$$T(n) = 1 \text{ for } n = 0$$
  
 $T(n) = 1 + T(n-1) \text{ for } n > 0$ 

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

### **Output:**

```
factorial of 5 is: 120
```

### Implementation:

```
C++
```

```
// C++ code to implement factorial
#include <bits/stdc++.h>
using namespace std;
// Factorial function
int f(int n)
{
    // Stop condition
    if (n == 0 | | n == 1)
        return 1;
    // Recursive condition
    else
         return n * f(n - 1);
}
// Driver code
int main()
{
    int n = 5;
    cout<<"factorial of "<<n<<" is: "<<f(n);</pre>
    return 0;
}
C
// C code to implement factorial
#include <stdio.h>
// Factorial function
int f(int n)
    // Stop condition
    if (n == 0 | | n == 1)
         return 1;
    // Recursive condition
    else
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

```
int main()
{
    int n = 5;
    printf("factorial of %d is: %d", n, f(n));
    return 0;
}
Java
// Java code to implement factorial
public class GFG
{
  // Factorial function
  static int f(int n)
  {
    // Stop condition
    if (n == 0 || n == 1)
       return 1;
    // Recursive condition
    else
       return n * f(n - 1);
  }
  // Driver code
  public static void main(String[] args)
    int n = 5;
    System.out.println("factorial of " + n + " is: " + f(n));
  }
}
// This code is contributed by divyesh072019.
Python3
# Python3 code to implement factorial
# Factorial function
def f(n):
    # Stop condition
    if (n == 0 \text{ or } n == 1).
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

```
else:
        return n * f(n - 1);
# Driver code
if __name__=='__main__':
    n = 5;
    print("factorial of",n,"is:",f(n))
    # This code is contributed by pratham76.
C#
// C# code to implement factorial
using System;
class GFG {
  // Factorial function
  static int f(int n)
    // Stop condition
    if (n == 0 || n == 1)
      return 1;
    // Recursive condition
    else
      return n * f(n - 1);
  }
  // Driver code
  static void Main()
  {
    int n = 5;
    Console.WriteLine("factorial of " + n + " is: " + f(n));
  }
}
// This code is contributed by divyeshrabadiya07.
Javascript
<script>
```

```
<script>
// JavaScript code to implement factorial
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

```
// Stop condition
if(n == 0 || n == 1)
    return 1;

// Recursive condition
else
    return n*f(n-1);
}

// Initialize variable n.
let n = 5;
document.write("factorial of "+ n +" is: " + f(n));

// This code is contributed by probinsah.
</script>
```

### Output

```
factorial of 5 is: 120
```

## Working:




Diagram of factorial Recursion function for user input 5.

# What are the disadvantages of recursive programming over iterative programming?

Note that both recursive and iterative programs have the same problem-solving powers, i.e., every recursive program can be written iteratively and vice versa is also true. The recursive program has greater space requirements than iterative program as all functions will remain in the stack until the base case is reached. It also has greater time requirements because of function calls and returns overhead

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <a href="Cookie Policy">Cookie Policy</a> & <a href="Privacy">Privacy</a> <a href="Policy">Policy</a>

recursive like tree traversals, <u>Tower of Hanoi</u>, etc. For such problems, it is preferred to write recursive code. We can write such codes also iteratively with the help of a stack data structure. For example refer <u>Inorder Tree Traversal without Recursion</u>, <u>Iterative</u> Tower of Hanoi.

# Output based practice problems for beginners:

Practice Questions for Recursion | Set 1

Practice Questions for Recursion | Set 2

Practice Questions for Recursion | Set 3

Practice Questions for Recursion | Set 4

Practice Questions for Recursion | Set 5

Practice Questions for Recursion | Set 6

Practice Questions for Recursion | Set 7

### **Quiz on Recursion**

### **Coding Practice on Recursion:**

#### **All Articles on Recursion**

Recursive Practice Problems with Solutions

This article is contributed by **Sonal Tuteja**. If you like GeeksforGeeks and would like to contribute, you can also write an article using <u>contribute.geeksforgeeks.org</u> or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.


Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

Attention reader! Don't stop learning now. Get hold of all the important DSA concepts with the **DSA Self Paced Course** at a student-friendly price and become industry ready. To complete your preparation from learning a language to DS Algo and many more, please refer **Complete Interview Preparation Course**.

In case you wish to attend live classes with industry experts, please refer <u>Geeks</u> <u>Classes Live</u> and <u>Geeks Classes Live USA</u>

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>

**Previous** Next



# RECOMMENDED ARTICLES

**Practice questions for Linked List** Practice Questions for Recursion and Recursion Set 2 22, Apr 10 19, May 10 Practice Questions for Recursion Reverse a stack using recursion Set 4 27, Apr 10 28, Oct 10 **Practice Questions for Recursion** Practice Questions for Recursion Set 1 Set 5 12, May 10 18, Mar 11 **Practice Questions for Recursion** Practice Questions for Recursion Set 3 Set 6 24. Oct 11

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our Cookie Policy & Privacy **Policy** 

Got It!

Page: 1 2 3

18. Jun 10

# **Article Contributed By:**



# Vote for difficulty

Current difficulty: Easy

Medium Easy Normal Hard Expert

Anshul\_Aggarwal, Kirti\_Mangal, Ashish\_rana, akashkumarsen4, Improved By:

> iamartyayadav, divyesh072019, divyeshrabadiya07, rutvik\_56, avanitrachhadiya2155, pratham76, chinmoy1997pal, probinsah

tail-recursion, Algorithms, Recursion **Article Tags:** 

Recursion, Algorithms **Practice Tags:** 

Report Issue Improve Article

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

**Load Comments** 

ADVERTISEMENT BY ADRECOVER

ADVERTISE ON GEEKSFORGEEKS





We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our Cookie Policy & Privacy **Policy** 



5th Floor, A-118, Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Company

About Us

Careers

Privacy Policy

Contact Us

Copyright Policy

Practice

Courses

Company-wise

Topic-wise

How to begin?

Learn

**Algorithms** 

Data Structures

Languages

**CS** Subjects

Video Tutorials

Contribute

Write an Article

Write Interview Experience

Internships

Videos

@geeksforgeeks, Some rights reserved

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our <u>Cookie Policy</u> & <u>Privacy</u> <u>Policy</u>