



Binary Search

Given a sorted array `arr[]` of `n` elements, write a function to search a given element `x` in `arr[]`.

A simple approach is to do **linear search**. The time complexity of above algorithm is $O(n)$. Another approach to perform the same task is using Binary Search.

Binary Search: Search a sorted array by repeatedly dividing the search interval in half. Begin with an interval covering the whole array. If the value of the search key is less than the item in the middle of the interval, narrow the interval to the lower half. Otherwise narrow it to the upper half. Repeatedly check until the value is found or the interval is empty.

Example :

Binary Search

	0	1	2	3	4	5	6	7	8	9
Search 23	2	5	8	12	16	23	38	56	72	91
	L=0	1	2	3	M=4	5	6	7	8	H=9
23 > 16 take 2 nd half	2	5	8	12	16	23	38	56	72	91
	0	1	2	3	4	L=5	6	M=7	8	H=9
23 > 56 take 1 st half	2	5	8	12	16	23	38	56	72	91
	0	1	2	3	4	L=5, M=5	H=6	7	8	9
Found 23, Return 5	2	5	8	12	16	23	38	56	72	91

The idea of binary search is to use the information that the array is sorted and reduce the time complexity to $O(\log n)$.

Recommended: Please solve it on “PRACTICE” first, before moving on to the solution.

We basically ignore half of the elements just after one comparison.

1. Compare `x` with the middle element.
2. If `x` matches with middle element, we return the mid index.
3. Else If `x` is greater than the mid element, then `x` can only lie in right half subarray after the mid element. So we recur for right half.
4. Else (`x` is smaller) recur for the left half.

Recursive implementation of Binary Search

C

```
// C program to implement recursive Binary Search
#include <stdio.h>

// A recursive binary search function. It returns
// location of x in given array arr[l..r] is present,
// otherwise -1
int binarySearch(int arr[], int l, int r, int x)
{
    if (r >= l) {
        int mid = l + (r - l) / 2;

        // If the element is present at the middle
        // itself
        if (arr[mid] == x)
            return mid;

        // If element is smaller than mid, then
        // it can only be present in left subarray
        if (arr[mid] > x)
            return binarySearch(arr, l, mid - 1, x);

        // Else the element can only be present
        // in right subarray
        return binarySearch(arr, mid + 1, r, x);
    }

    // We reach here when element is not
    // present in array
    return -1;
}

int main(void)
{
    int arr[] = { 2, 3, 4, 10, 40 };
    int n = sizeof(arr) / sizeof(arr[0]);
    int x = 10;
    int result = binarySearch(arr, 0, n - 1, x);
    (result == -1) ? printf("Element is not present in array")
                  : printf("Element is present at index %d",
                          result);

    return 0;
}
```

C++

```
// C++ program to implement recursive Binary Search
#include <iostream>
using namespace std;

// A recursive binary search function. It returns
// location of x in given array arr[l..r] is present,
// otherwise -1
int binarySearch(int arr[], int l, int r, int x)
{
    if (r >= l) {
        int mid = l + (r - l) / 2;

        // If the element is present at the middle
        // itself
        if (arr[mid] == x)
            return mid;

        // If element is smaller than mid, then
        // it can only be present in left subarray
        if (arr[mid] > x)
            return binarySearch(arr, l, mid - 1, x);

        // Else the element can only be present
        // in right subarray
        return binarySearch(arr, mid + 1, r, x);
    }

    // We reach here when element is not
    // present in array
    return -1;
}
```

```

}

int main(void)
{
    int arr[] = { 2, 3, 4, 10, 40 };
    int x = 10;
    int n = sizeof(arr) / sizeof(arr[0]);
    int result = binarySearch(arr, 0, n - 1, x);
    (result == -1) ? cout << "Element is not present in array"
                  : cout << "Element is present at index " << result;

    return 0;
}

```

Java

```

// Java implementation of recursive Binary Search
class BinarySearch {
    // Returns index of x if it is present in arr[l..
    // r], else return -1
    int binarySearch(int arr[], int l, int r, int x)
    {
        if (r >= l) {
            int mid = l + (r - l) / 2;

            // If the element is present at the
            // middle itself
            if (arr[mid] == x)
                return mid;

            // If element is smaller than mid, then
            // it can only be present in left subarray
            if (arr[mid] > x)
                return binarySearch(arr, l, mid - 1, x);

            // Else the element can only be present
            // in right subarray
            return binarySearch(arr, mid + 1, r, x);
        }

        // We reach here when element is not present
        // in array
        return -1;
    }

    // Driver method to test above
    public static void main(String args[])
    {
        BinarySearch ob = new BinarySearch();
        int arr[] = { 2, 3, 4, 10, 40 };
        int n = arr.length;
        int x = 10;
        int result = ob.binarySearch(arr, 0, n - 1, x);
        if (result == -1)
            System.out.println("Element not present");
        else
            System.out.println("Element found at index " + result);
    }
}
/* This code is contributed by Rajat Mishra */

```

Python

```

# Python Program for recursive binary search.

# Returns index of x in arr if present, else -1
def binarySearch (arr, l, r, x):

    # Check base case
    if r >= l:

        mid = l + (r - l)/2

        # If element is present at the middle itself
        if arr[mid] == x:
            return mid

```

```

# If element is smaller than mid, then it
# can only be present in left subarray
elif arr[mid] > x:
    return binarySearch(arr, l, mid-1, x)

# Else the element can only be present
# in right subarray
else:
    return binarySearch(arr, mid + 1, r, x)

else:
    # Element is not present in the array
    return -1

# Test array
arr = [ 2, 3, 4, 10, 40 ]
x = 10

# Function call
result = binarySearch(arr, 0, len(arr)-1, x)

if result != -1:
    print "Element is present at index % d" % result
else:
    print "Element is not present in array"

```

C#

```

// C# implementation of recursive Binary Search
using System;

class GFG {
    // Returns index of x if it is present in
    // arr[l..r], else return -1
    static int binarySearch(int[] arr, int l,
                           int r, int x)
    {
        if (r >= l) {
            int mid = l + (r - l) / 2;

            // If the element is present at the
            // middle itself
            if (arr[mid] == x)
                return mid;

            // If element is smaller than mid, then
            // it can only be present in left subarray
            if (arr[mid] > x)
                return binarySearch(arr, l, mid - 1, x);

            // Else the element can only be present
            // in right subarray
            return binarySearch(arr, mid + 1, r, x);
        }

        // We reach here when element is not present
        // in array
        return -1;
    }

    // Driver method to test above
    public static void Main()
    {
        int[] arr = { 2, 3, 4, 10, 40 };
        int n = arr.Length;
        int x = 10;

        int result = binarySearch(arr, 0, n - 1, x);

        if (result == -1)
            Console.WriteLine("Element not present");
        else
            Console.WriteLine("Element found at index "
                              + result);
    }
}

// This code is contributed by Sam007.

```

PHP

```
<?php
// PHP program to implement
// recursive Binary Search

// A recursive binary search
// function. It returns location
// of x in given array arr[l..r]
// is present, otherwise -1
function binarySearch($arr, $l, $r, $x)
{
    if ($r >= $l)
    {
        $mid = ceil($l + ($r - $l) / 2);

        // If the element is present
        // at the middle itself
        if ($arr[$mid] == $x)
            return floor($mid);

        // If element is smaller than
        // mid, then it can only be
        // present in left subarray
        if ($arr[$mid] > $x)
            return binarySearch($arr, $l,
                                $mid - 1, $x);

        // Else the element can only
        // be present in right subarray
        return binarySearch($arr, $mid + 1,
                            $r, $x);
    }

    // We reach here when element
    // is not present in array
    return -1;
}

// Driver Code
$arr = array(2, 3, 4, 10, 40);
$n = count($arr);
$x = 10;
$result = binarySearch($arr, 0, $n - 1, $x);
if (($result == -1))
    echo "Element is not present in array";
else
    echo "Element is present at index ",
        $result;

// This code is contributed by anuj_67.
?>
```

Output :

Element is present at index 3

Iterative implementation of Binary Search

C

```
// C program to implement iterative Binary Search
#include <stdio.h>

// A iterative binary search function. It returns
// location of x in given array arr[l..r] if present,
// otherwise -1
int binarySearch(int arr[], int l, int r, int x)
{
    while (l <= r) {
        int m = l + (r - l) / 2;

        // Check if x is present at mid
```

```

    if (arr[m] == x)
        return m;

    // If x greater, ignore left half
    if (arr[m] < x)
        l = m + 1;

    // If x is smaller, ignore right half
    else
        r = m - 1;
}

// if we reach here, then element was
// not present
return -1;
}

int main(void)
{
    int arr[] = { 2, 3, 4, 10, 40 };
    int n = sizeof(arr) / sizeof(arr[0]);
    int x = 10;
    int result = binarySearch(arr, 0, n - 1, x);
    (result == -1) ? printf("Element is not present"
                          " in array")
                  : printf("Element is present at "
                          "index %d",
                          result);

    return 0;
}

```

C++

```

// C++ program to implement recursive Binary Search
#include <iostream>
using namespace std;

// A iterative binary search function. It returns
// location of x in given array arr[l..r] if present,
// otherwise -1
int binarySearch(int arr[], int l, int r, int x)
{
    while (l <= r) {
        int m = l + (r - l) / 2;

        // Check if x is present at mid
        if (arr[m] == x)
            return m;

        // If x greater, ignore left half
        if (arr[m] < x)
            l = m + 1;

        // If x is smaller, ignore right half
        else
            r = m - 1;
    }

    // if we reach here, then element was
    // not present
    return -1;
}

int main(void)
{
    int arr[] = { 2, 3, 4, 10, 40 };
    int x = 10;
    int n = sizeof(arr) / sizeof(arr[0]);
    int result = binarySearch(arr, 0, n - 1, x);
    (result == -1) ? cout << "Element is not present in array"
                  : cout << "Element is present at index " << result;

    return 0;
}

```

Java

```
// Java implementation of iterative Binary Search
class BinarySearch {
    // Returns index of x if it is present in arr[],
    // else return -1
    int binarySearch(int arr[], int x)
    {
        int l = 0, r = arr.length - 1;
        while (l <= r) {
            int m = l + (r - l) / 2;

            // Check if x is present at mid
            if (arr[m] == x)
                return m;

            // If x greater, ignore left half
            if (arr[m] < x)
                l = m + 1;

            // If x is smaller, ignore right half
            else
                r = m - 1;
        }

        // if we reach here, then element was
        // not present
        return -1;
    }

    // Driver method to test above
    public static void main(String args[])
    {
        BinarySearch ob = new BinarySearch();
        int arr[] = { 2, 3, 4, 10, 40 };
        int n = arr.length;
        int x = 10;
        int result = ob.binarySearch(arr, x);
        if (result == -1)
            System.out.println("Element not present");
        else
            System.out.println("Element found at "
                               + "index " + result);
    }
}
```

Python

```
# Python code to implement iterative Binary
# Search.

# It returns location of x in given array arr
# if present, else returns -1
def binarySearch(arr, l, r, x):

    while l <= r:

        mid = l + (r - l)/2;

        # Check if x is present at mid
        if arr[mid] == x:
            return mid

        # If x is greater, ignore left half
        elif arr[mid] < x:
            l = mid + 1

        # If x is smaller, ignore right half
        else:
            r = mid - 1

    # If we reach here, then the element
    # was not present
    return -1

# Test array
arr = [ 2, 3, 4, 10, 40 ]
x = 10

# Function call
```

```

result = binarySearch(arr, 0, len(arr)-1, x)

if result != -1:
    print "Element is present at index % d" % result
else:
    print "Element is not present in array"

```

C#

```

// C# implementation of iterative Binary Search
using System;

class GFG {
    // Returns index of x if it is present in arr[],
    // else return -1
    static int binarySearch(int[] arr, int x)
    {
        int l = 0, r = arr.Length - 1;
        while (l <= r) {
            int m = l + (r - l) / 2;

            // Check if x is present at mid
            if (arr[m] == x)
                return m;

            // If x greater, ignore left half
            if (arr[m] < x)
                l = m + 1;

            // If x is smaller, ignore right half
            else
                r = m - 1;
        }

        // if we reach here, then element was
        // not present
        return -1;
    }

    // Driver method to test above
    public static void Main()
    {
        int[] arr = { 2, 3, 4, 10, 40 };
        int n = arr.Length;
        int x = 10;
        int result = binarySearch(arr, x);
        if (result == -1)
            Console.WriteLine("Element not present");
        else
            Console.WriteLine("Element found at "
                               + "index " + result);
    }
}
// This code is contributed by Sam007

```

PHP

```

<?php
// PHP program to implement
// iterative Binary Search

// A iterative binary search
// function. It returns location
// of x in given array arr[l..r]
// if present, otherwise -1
function binarySearch($arr, $l,
                      $r, $x)
{
    while ($l <= $r)
    {
        $m = $l + ($r - $l) / 2;

        // Check if x is present at mid
        if ($arr[$m] == $x)
            return floor($m);
    }
}

```



```
// If x greater, ignore
// left half
if ($arr[$m] < $x)
    $l = $m + 1;

// If x is smaller,
// ignore right half
else
    $r = $m - 1;
}

// if we reach here, then
// element was not present
return -1;
}

// Driver Code
$arr = array(2, 3, 4, 10, 40);
$n = count($arr);
$x = 10;
$result = binarySearch($arr, 0,
                      $n - 1, $x);
if(($result == -1))
echo "Element is not present in array";
else
echo "Element is present at index ",
    $result;

// This code is contributed by anuj_67.
?>
```

Output :

Element is present at index 3

Time Complexity:

The time complexity of Binary Search can be written as

$$T(n) = T(n/2) + c$$

The above recurrence can be solved either using Recurrence Tree method or Master method. It falls in case II of Master Method and solution of the recurrence is $\Theta(\log n)$.

Auxiliary Space: $O(1)$ in case of iterative implementation. In case of recursive implementation, $O(\log n)$ recursion call stack space.

Algorithmic Paradigm: Decrease and Conquer.

Binary Search | GeeksQuiz**Interesting articles based on Binary Search.**

- [The Ubiquitous Binary Search](#)
- [Interpolation search vs Binary search](#)
- [Find the minimum element in a sorted and rotated array](#)
- [Find a peak element](#)

- Find a Fixed Point in a given array
- Count the number of occurrences in a sorted array
- Median of two sorted arrays
- Floor and Ceiling in a sorted array
- Find the maximum element in an array which is first increasing and then decreasing

Coding Practice Questions on Binary Search

Recent Articles on Binary Search.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



Recommended Posts:

Meta Binary Search | One-Sided Binary Search
Why is Binary Search preferred over Ternary Search?
Linear Search vs Binary Search
Interpolation search vs Binary search
Binary Search in PHP
The Ubiquitous Binary Search | Set 1
Binary Search a String
Binary Search using pthread
Variants of Binary Search
Binary Search in Java
Binary Search In JavaScript
Uniform Binary Search
Randomized Binary Search Algorithm
A Problem in Many Binary Search Implementations
Binary Search Tree | Set 2 (Delete)

Improved By : vt_m, RishabhPrabhu, DhruvJain6



Article Tags :

Divide and Conquer Searching Accenture Binary Search Infosys Oracle Qualcomm TCS Wipro

Practice Tags :

Infosys Oracle Qualcomm TCS Wipro Accenture Searching Divide and Conquer Binary Search



62

☐ To-do ☐ Done

1.6

Based on 214 vote(s)

Feedback/ Suggest Improvement

Notes

Improve Article

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments



A computer science portal for geeks

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

About Us
Careers
Privacy Policy
Contact Us

PRACTICE

Courses
Company-wise
Topic-wise
How to begin?

LEARN

Algorithms
Data Structures
Languages
CS Subjects
Video Tutorials

CONTRIBUTE

Write an Article
Write Interview Experience
Internships
Videos

@geeksforgeeks, Some rights reserved