

Devstack — Multi-PHP Local Development Environment

Complete step-by-step documentation

Machine: Apple Silicon (arm64) Mac · **Built:** July 2026 **Location:** `~/devstack`

This document records, in order, everything that was set up: a Docker-based environment running **7 PHP versions at once** (7.2 – 8.4) with a shared MySQL 8.0, phpMyAdmin, Node (via fnm), clean `.test` hostnames, trusted HTTPS, and a real Laravel project (`wagebook`) running on it.

Table of contents

1. [What was already on the machine](#)
 2. [Design decisions](#)
 3. [Directory structure](#)
 4. [The PHP images \(7.2–8.4\)](#)
 5. [docker-compose stack](#)
 6. [nginx routing](#)
 7. [Building & starting](#)
 8. [The `stack` helper command](#)
 9. [Node.js via fnm](#)
 10. [Clean `.test` hostnames \(dnsmasq\)](#)
 11. [Trusted HTTPS \(mkcert\)](#)
 12. [HTTP → HTTPS redirect](#)
 13. [Running the wagebook Laravel project](#)
 14. [Daily usage cheat sheet](#)
 15. [Adding a new project](#)
 16. [Troubleshooting & gotchas](#)
 17. [Outstanding manual steps](#)
-

1. What was already on the machine

- **Homebrew** ✓
- **Docker Desktop** ✓ (had to be *started* — the daemon wasn't running)
- **No** PHP, MySQL, Composer, or Node yet (clean slate)

Verified native `arm64` builds exist for all PHP images (7.2–8.4), so no emulation is needed.

2. Design decisions

Question	Choice	Why
How to manage 7 PHP versions	Docker, one shared stack	EOL versions (7.2/7.3) "just work"; matches prod; run all at once
Do projects get dockerized individually	No	Projects are plain folders in <code>www/</code> ; nginx routes to the right PHP
Location	<code>~/devstack</code>	self-contained
Node	fnm	fast, switch Node per project
Database	MySQL 8.0	modern, compatible with legacy apps

Key idea: **one nginx + one MySQL + 7 PHP-FPM containers**. A project is just a folder; the PHP version is chosen by the URL you use.

3. Directory structure

```
~/devstack/
├─ docker-compose.yml      # all services
├─ .env                    # MySQL creds + timezone
├─ php/
│   └─ Dockerfile          # one image, reused per version via build arg
│   └─ conf.d/zz-devstack.ini # shared PHP settings (upload size, xdebug off...)
├─ nginx/
│   └─ conf.d/              # one vhost per version + per-project vhosts
│   └─ certs/               # mkcert TLS cert + key
├─ www/                    # ← your projects live here
│   └─ info/                # sample project (phpinfo + DB check)
│   └─ wagebook/            # the Laravel app
├─ data/mysql/              # persistent MySQL data (survives restarts)
├─ bin/stack                # helper CLI (symlinked to /opt/homebrew/bin/stack)
├─ README.md
└─ DOCUMENTATION.md        # this file
```

4. The PHP images (7.2–8.4)

A **single `php/Dockerfile`** is reused for every version via a build arg. It uses `mlocati/php-extension-installer`, which handles extension/version/arch differences uniformly across 7.2 → 8.4:

```
ARG PHP_VERSION=8.2
FROM php:${PHP_VERSION}-fpm
COPY --from=mlocati/php-extension-installer /usr/bin/install-php-extensions /usr/local/bin/
RUN install-php-extensions \
    pdo_mysql mysqli gd zip intl bcmath mbstring opcache exif pcntl soap xdebug @composer
WORKDIR /var/www/html
```

Every version therefore includes: **Composer**, common extensions, and **Xdebug** (installed but `mode=off` by default — see `php/conf.d/zz-devstack.ini`).

Versions built: **7.2, 7.3, 7.4, 8.0, 8.1, 8.2, 8.4** (no 8.3).

⚠ **Gotcha:** building all 7 in parallel exhausts memory and randomly fails (`EOF` / killed). Fix: build failing versions **one at a time** (`docker compose build php81`).

5. docker-compose stack

Services (`~/devstack/docker-compose.yml`):

- `php72 ... php84` — 7 PHP-FPM containers, each built from the shared Dockerfile
- `nginx` — routes requests to the right PHP version
- `mysql` — MySQL 8.0, data persisted to `./data/mysql`
- `phpmyadmin` — web DB admin

Credentials live in `~/devstack/.env` :

```
MYSQL_ROOT_PASSWORD=root
MYSQL_DATABASE=app
MYSQL_USER=app
MYSQL_PASSWORD=app
TZ=UTC
```

6. nginx routing

Each version has a vhost in `nginx/conf.d/phpNN.conf` with three server blocks:

1. **port 80** → 301 redirect to HTTPS (for `*.NN.test`)
2. **port 443** → serves the project over TLS
3. **localhost:80NN** → plain-HTTP no-DNS fallback

Access map:

PHP	HTTPS hostname	Plain-HTTP fallback
7.2	<code>https://<proj>.72.test</code>	<code>http://localhost:8072/<proj>/</code>
7.3	<code>https://<proj>.73.test</code>	<code>http://localhost:8073/<proj>/</code>
7.4	<code>https://<proj>.74.test</code>	<code>http://localhost:8074/<proj>/</code>
8.0	<code>https://<proj>.80.test</code>	<code>http://localhost:8080/<proj>/</code>
8.1	<code>https://<proj>.81.test</code>	<code>http://localhost:8081/<proj>/</code>
8.2	<code>https://<proj>.82.test</code>	<code>http://localhost:8082/<proj>/</code>
8.4	<code>https://<proj>.84.test</code>	<code>http://localhost:8084/<proj>/</code>

Other services: **phpMyAdmin** `http://localhost:8888` · **MySQL** `127.0.0.1:3306`

7. Building & starting

```
# 1. Start Docker Desktop (must be running)
open -a Docker

# 2. Build the 7 PHP images (build one at a time if parallel fails)
cd ~/devstack && docker compose build

# 3. Start everything
docker compose up -d
```

Verified: every version reports the correct `PHP x.y.z` and connects to `MySQL 8.0.46` (tested via the `info` sample project).

8. The `stack` helper command

`~/devstack/bin/stack` , symlinked to `/opt/homebrew/bin/stack` (on PATH):

```
stack up                # start everything
stack down              # stop
stack restart           # restart containers
stack rebuild           # rebuild PHP images + restart
stack ps                # status
stack logs [service]   # tail logs

stack php <ver> <project> ... # run php in a project    e.g. stack php 8.2 wagebook -v
stack composer <ver> <project> ... # composer                e.g. stack composer 7.4 shop install
stack artisan <ver> <project> ... # laravel artisan          e.g. stack artisan 8.2 wagebook migrate
stack sh <ver>           # shell into a PHP container
stack mysql              # mysql client as root
```

(`<ver>` accepts `8.2` or `82`.)

9. Node.js via fnm

```
brew install fnm
# added to ~/.zshrc:
eval "$(fnm env --use-on-cd --version-file-strategy=recursive)"
fnm install --lts           # installed Node v24 LTS
```

Node runs **on the host** (not in the PHP containers). `--use-on-cd` auto-switches Node version when a project has a `.node-version` / `.nvmrc` file.

10. Clean `.test` hostnames (dnsmasq)

Makes every `*.test` domain resolve to `127.0.0.1` with no `/etc/hosts` edits.

```
brew install dnsmasq
# config written:
# /opt/homebrew/etc/dnsmasq.d/devstack-test.conf -> address=/.test/127.0.0.1
# (conf-dir line added to /opt/homebrew/etc/dnsmasq.conf)
```

Manual step (needs sudo — run in a real Terminal):

```
sudo brew services start dnsmasq
sudo mkdir -p /etc/resolver
echo "nameserver 127.0.0.1" | sudo tee /etc/resolver/test
sudo dscacheutil -flushcache && sudo killall -HUP mDNSResponder
```

✅ Done and verified — `info.82.test` etc. resolve to `127.0.0.1` . Survives reboots.

11. Trusted HTTPS (mkcert)

```
brew install mkcert nss
# one cert covering every version's wildcard + localhost:
cd ~/devstack/nginx/certs
mkcert -cert-file devstack.pem -key-file devstack-key.pem \
  "*.72.test" "*.73.test" "*.74.test" "*.80.test" "*.81.test" "*.82.test" "*.84.test" \
  localhost 127.0.0.1
```

- Cert + key are mounted into nginx at `/etc/nginx/certs/` (port 443 exposed).
- Valid until **2028**; wildcards are **one level deep** (`a.82.test` ✓, `a.b.82.test` ✗).

Manual step (needs sudo — run in a real Terminal), to trust the CA in browsers:

```
mkcert -install
```

Then **fully quit and reopen the browser**.

If the browser says "Not secure", it's almost always because `mkcert -install` hasn't been run — verify with: `security find-certificate -c "mkcert" /Library/Keychains/System.keychain`

12. HTTP → HTTPS redirect

Every `.test` vhost returns **301** → **https** on port 80; the `localhost:PORT` fallbacks stay plain HTTP (no TLS on those ports by design).

Verified:

- `http://wagebook.82.test` → **301** → `https://wagebook.82.test` → **200**
- `http://localhost:8082/info/` → stays **200** (plain HTTP)

13. Running the wagebook Laravel project

Project: `wagebook-hrm` (Laravel 9, requires PHP ^8.2), from Azure DevOps.

Steps performed

```
# 1. Clone into the www folder (auth via Azure DevOps PAT)
cd ~/devstack/www
git clone https://.../wagebook-hrm wagebook

# 2. Install dependencies at PHP 8.2
# (had to disable Composer's advisory blocker for old dompdf/browsershot)
docker compose exec -T -w /var/www/html/wagebook php82 sh -c \
  'composer config policy.advisories.block false && composer install --no-interaction'
# then restored composer.json so git tree stayed clean

# 3. nginx vhost -> wagebook.82.test -> /public (nginx/conf.d/wagebook.conf)

# 4. Create the database
stack mysql -> CREATE DATABASE wagebook; GRANT ALL ON wagebook.* TO 'app'@'%';

# 5. .env (local, gitignored) – key points:
APP_URL=http://wagebook.82.test
DB_HOST=mysql
DB_DATABASE=wagebook
DB_USERNAME=app
DB_PASSWORD=app
# then: php artisan key:generate

# 6. Import the full DB dump (NOT fresh migrations – see gotcha)
docker exec -i devstack-mysql-1 mysql -uroot -proot wagebook \
  < "~/Downloads/asl_employee_db_new_latest (26).sql" # 126 tables

# 7. Create the storage dirs that are gitignored, make writable
mkdir -p storage/framework/{sessions,views,cache/data} storage/logs storage/app/public bootstrap/cache
chmod -R 777 storage bootstrap/cache

# 8. Clear caches
docker compose exec -T -w /var/www/html/wagebook php82 sh -c \
  'php artisan config:clear; php artisan cache:clear; php artisan view:clear'
```

✅ Result: `https://wagebook.82.test` → "Sign In - WageBook" (HTTP 200, PHP 8.2.32).

wagebook-specific gotchas

- **Do NOT run migrations from scratch** — the migration set is order-broken (foreign keys reference `users.emp_id` before it exists). Use a **DB dump**.
 - `AppServiceProvider::boot()` runs **DB queries on every request/command** (PayrollSettings, EmployeeProvidentFunds, EmployeeDocuments) — nothing works until the DB is populated.
 - Composer fails under the modern advisory blocker → `composer config policy.advisories.block false`.
 - `storage/framework/*` subdirs are gitignored → recreate after clone.
-

14. Daily usage cheat sheet

```
stack up           # morning: start the stack
stack ps          # what's running
stack down        # end of day: stop (data persists)

# wagebook
open https://wagebook.82.test
stack artisan 8.2 wagebook migrate:status
stack composer 8.2 wagebook install

# database
open http://localhost:8888      # phpMyAdmin (root/root or app/app)
stack mysql                    # CLI
```

15. Adding a new project

Plain PHP project:

1. Put code in `~/devstack/www/<name>/`
2. Open `https://<name>.82.test` (or any version), or `http://localhost:8082/<name>/`

Laravel/Symfony project (web root is `/public`):

1. Put code in `~/devstack/www/<name>/`
2. Copy `nginx/conf.d/wagebook.conf` → `<name>.conf`, change `server_name`, `root .../public`, and `php82` → desired version
3. `stack restart`
4. `stack composer <ver> <name> install`, set up `.env` (`DB_HOST=mysql`), create/import the DB
5. Open `https://<name>.82.test`

HTTPS works automatically for any new `*.NN.test` host — no cert regeneration.

16. Troubleshooting & gotchas

Symptom	Cause / Fix
Cannot connect to the Docker daemon	Docker Desktop not running → <code>open -a Docker</code>
PHP image build fails randomly (EOF)	Parallel build OOM → build one at a time
<code>bind: address already in use</code>	Another project uses the same host port → change its host port or <code>stack down</code>
Browser "Not secure" on <code>*.test</code>	<code>mkcert --install</code> not run, or browser not restarted
"Not secure" on <code>localhost:PORT</code>	Expected — those are plain HTTP by design; use the <code>.test</code> hostname
Laravel 500 Failed to open stream: <code>.../sessions</code>	<code>storage/framework/*</code> missing → <code>mkdir -p + chmod -R 777 storage bootstrap/cache</code>
Laravel DB errors at boot	DB empty/not imported, or <code>.env</code> <code>DB_HOST</code> wrong (should be <code>mysql</code>)
Composer refuses to install old packages	<code>composer config policy.advisories.block false</code>
<code>git</code> not found inside container	Run git on the host (<code>cd ~/devstack/www/<proj> && git ...</code>)

17. Outstanding manual steps

These require your admin password, so they must be run by you in a **real Terminal** (not the `!` prefix, which can't prompt for a password):

1. **Trust the HTTPS CA** (fixes "Not secure"):

```
mkcert -install
```

then fully quit & reopen your browser.

2. (Already done) dnsmasq activation — see §10, in case of a fresh setup.

Security reminder

An Azure DevOps **Personal Access Token** was pasted into the chat during setup. **Rotate/revoke it** (Azure DevOps → avatar → Personal access tokens). Future clones/pulls will use the macOS Keychain after authenticating once in a terminal.

End of documentation.