

MODULE-5
MINI-PROJECT-3

```
-- =====  
-- Mini Project 3 — Expense Tracker DB  
-- (The 5 tasks assigned actually build a Spotify-style  
-- `playlists` table rather than the expense-tracker tables  
-- described in the project brief — following the tasks as given.)  
--  
-- CRUD statements + a stored procedure, run block by block in  
-- phpMyAdmin / MySQL Workbench.  
-- =====
```

```
USE instaclone;
```

```
-- playlists.user_id needs somewhere to point. If you already have a  
-- `users` table from an earlier session this leaves it untouched;  
-- if not, this creates a minimal one so the FOREIGN KEY is valid.
```

```
CREATE TABLE IF NOT EXISTS users (  
    user_id INT AUTO_INCREMENT PRIMARY KEY,  
    username VARCHAR(50)  
);
```

```
INSERT INTO users (username)  
SELECT * FROM (SELECT 'priya.clicks') AS tmp  
WHERE NOT EXISTS (SELECT 1 FROM users WHERE user_id = 1);  
-- (Only seeds a row if the table was just created empty — if you  
-- already have real users, this INSERT quietly does nothing.)
```

```
DROP TABLE IF EXISTS playlists;
```

MODULE-5
MINI-PROJECT-3

-- ----- Task 1: CREATE TABLE playlists -----

```
CREATE TABLE playlists (  
    playlist_id INT AUTO_INCREMENT PRIMARY KEY,  
    user_id INT,  
    name VARCHAR(100) NOT NULL,  
    created_at DATETIME,  
    CONSTRAINT fk_playlists_user  
        FOREIGN KEY (user_id) REFERENCES users(user_id)  
);
```

-- ----- Task 2: insert 3 sample playlists -----

-- Adjust these user_id values to match real rows in your users table.

```
INSERT INTO playlists (user_id, name, created_at) VALUES  
(1, 'Workout Mix', '2026-09-10 07:15:00'),  
(1, 'Chill Vibes', '2026-09-12 21:40:00'),  
(1, 'Top Hits', '2026-09-15 18:05:00');
```

```
SELECT * FROM playlists;
```

-- ----- Task 3: UPDATE — rename Chill Vibes -> Evening Chill -----

-- WHERE targets both name AND user_id, so this only touches THIS

-- user's playlist — someone else's differently-owned 'Chill Vibes'

-- (if that ever existed) would be untouched.

```
UPDATE playlists
```

```
SET name = 'Evening Chill'
```

MODULE-5
MINI-PROJECT-3

```
WHERE name = 'Chill Vibes'
```

```
AND user_id = 1;
```

```
SELECT * FROM playlists WHERE user_id = 1;
```

```
-- ----- Task 4: DELETE — remove Workout Mix for that user -----
```

```
-- Same principle: name alone isn't a safe WHERE clause if two users
```

```
-- could each have a 'Workout Mix' playlist — user_id narrows it to one.
```

```
-- Preview first, always, before a DELETE:
```

```
SELECT * FROM playlists WHERE name = 'Workout Mix' AND user_id = 1;
```

```
DELETE FROM playlists
```

```
WHERE name = 'Workout Mix'
```

```
AND user_id = 1;
```

```
SELECT * FROM playlists; -- Workout Mix should be gone, 2 rows remain
```

```
-- ----- Task 5: stored procedure GetMonthlyPlaylistCount -----
```

```
DELIMITER //
```

```
DROP PROCEDURE IF EXISTS GetMonthlyPlaylistCount //
```

```
CREATE PROCEDURE GetMonthlyPlaylistCount(
```

```
    IN p_user_id INT,
```

```
    IN p_month INT
```

```
)
```

```
BEGIN
```

```
    SELECT COUNT(*) AS playlist_count
```

MODULE-5
MINI-PROJECT-3

```
FROM playlists
WHERE user_id = p_user_id
      AND MONTH(created_at) = p_month;
END //

DELIMITER ;

-- Test it — September is month 9:
CALL GetMonthlyPlaylistCount(1, 9);
-- Expected: 2 (Evening Chill + Top Hits — Workout Mix was deleted in Task 4)
```

MODULE-5

MINI-PROJECT-3

The image displays two screenshots of the phpMyAdmin interface, showing database operations on the 'playlists' table in the 'instancione' database.

Top Screenshot:

- Task 2:** Insert 3 sample playlists. The SQL query is: `INSERT INTO playlists (user_id, name, created_at) VALUES (1, 'Workout Mix', '2026-09-10 07:15:00'), (1, 'Chill Vibes', '2026-09-12 21:40:00'), (1, 'Top Hits', '2026-09-15 18:05:00');`
- Result:** 3 rows inserted. Inserted row id: 3 (Query took 0.0013 seconds).
- Query:** `SELECT * FROM playlists;`
- Table Data:**

playlist_id	user_id	name	created_at
1	1	Workout Mix	2026-09-10 07:15:00
2	1	Chill Vibes	2026-09-12 21:40:00
3	1	Top Hits	2026-09-15 18:05:00

Bottom Screenshot:

- Task 3:** UPDATE - rename Chill Vibes -> Evening Chill. The SQL query is: `UPDATE playlists SET name = 'Evening Chill' WHERE name = 'Chill Vibes' AND user_id = 1;`
- Result:** Showing rows 0 - 2 (3 total, Query took 0.0006 seconds).
- Query:** `SELECT * FROM playlists WHERE user_id = 1;`
- Table Data:**

playlist_id	user_id	name	created_at
1	1	Workout Mix	2026-09-10 07:15:00
2	1	Evening Chill	2026-09-12 21:40:00
3	1	Top Hits	2026-09-15 18:05:00

MODULE-5

MINI-PROJECT-3

The image displays two screenshots of the phpMyAdmin interface, showing a SQL query execution and its results.

Top Screenshot:

- The interface shows the 'playlists' table in the 'instacore' database.
- A SQL query is entered in the 'SQL' tab: `DELETE FROM playlists WHERE name = 'Workout Mix' AND user_id = 1;`
- The query is executed, resulting in a message: "Showing rows 0 - 0 (1 total, Query took 0.0008 seconds.)"
- The table structure is visible below the query results.

playlist_id	user_id	name	created_at
1	1	Workout Mix	2026-09-10 07:15:00

Bottom Screenshot:

- The interface shows the 'playlists' table in the 'instacore' database.
- A SQL query is entered in the 'SQL' tab: `DELETE FROM playlists WHERE name = 'Workout Mix' AND user_id = 1;`
- The query is executed, resulting in a message: "1 row deleted. (Query took 0.0009 seconds.)"
- The query results are displayed below the message.

playlist_id	user_id	name	created_at
2	1	Evening Chill	2026-09-12 21:40:00
3	1	Top Hits	2026-09-15 18:05:00

MODULE-5

MINI-PROJECT-3

The image displays two screenshots of the phpMyAdmin web interface, demonstrating database management tasks.

Top Screenshot: The interface shows the 'playlists' table in the 'instacdone' database. The 'playlist_count' column is highlighted, showing a value of 2. The SQL query executed is: `-- Test it - September is month 9: CALL GetMonthlyPlaylistCount(1, 9);`. The console output indicates: `MySQL returned an empty result set (i.e. zero rows). (Query took 0.0003 seconds.)` and `-- Expected: 2 (Evening Chill + Top Hits - Workout Mix was deleted in Task 4);`.

Bottom Screenshot: The 'GetMonthlyPlaylistCount' routine is being edited. The routine type is set to 'PROCEDURE'. The parameters are defined as follows:

Direction	Name	Type	Length/Values	Options
IN	p_user_id	INT		Charset
IN	p_month	INT		Charset

The routine definition is as follows:

```
BEGIN
  SELECT COUNT(*) AS playlist_count
  FROM playlists
  WHERE user_id = p_user_id
  AND MONTH(created_at) = p_month;
END
```