

MODULE 5 SESSION 3

1. Create a SQL table called Restaurants with columns: id (INT, auto-increment), name (VARCHAR), cuisine (VARCHAR), rating (DECIMAL), and city (VARCHAR). Insert 5 sample restaurants into the table, each with a different cuisine and rating.

Run SQL query/queries on database restaurant: ?

```
1 CREATE TABLE Restaurants (  
2     id INT AUTO_INCREMENT PRIMARY KEY,  
3     name VARCHAR(100),  
4     cuisine VARCHAR(50),  
5     rating DECIMAL(2,1),  
6     city VARCHAR(50)  
7 );
```

 Browse  Structure  SQL  Search  Insert  Export  Import

✓ MySQL returned an empty result set (i.e. zero rows). (Query took 0.0006 seconds.)

```
SELECT * FROM `restaurants`
```

☐ Profiling [\[Edit inline \]](#) [\[Edit \]](#) [\[Explain SQL \]](#) [\[Create PHP code \]](#) [\[Refresh \]](#)

id	name	cuisine	rating	city
----	------	---------	--------	------

Run SQL query/queries on table restaurant.restaurants: ?

```
1 INSERT INTO Restaurants (name, cuisine, rating, city)  
2 VALUES  
3 ('Spice Villa', 'Indian', 4.5, 'Ahmedabad'),  
4 ('Pizza Hub', 'Italian', 4.2, 'Ahmedabad'),  
5 ('Sushi World', 'Japanese', 4.6, 'Mumbai'),  
6 ('Taco Point', 'Mexican', 3.2, 'Rajkot'),  
7 ('Burger House', 'American', 3.8, 'Surat');
```

Extra options

				id	name	cuisine	rating	city
☐				1	Spice Villa	Indian	4.5	Ahmedabad
☐				2	Pizza Hub	Italian	4.2	Ahmedabad
☐				3	Sushi World	Japanese	4.6	Mumbai
☐				4	Taco Point	Mexican	3.2	Rajkot
☐				5	Burger House	American	3.8	Surat

2. Write a SQL UPDATE statement to change the rating of the restaurant named 'Spice Villa' to 4.7 in the Restaurants table.

	Browse		Structure		SQL		Search		Insert		Export		Import
---	--------	---	-----------	---	-----	---	--------	---	--------	---	--------	---	--------

Run SQL query/queries on table restaurant.restaurants: 

```
1 UPDATE Restaurants
2 SET rating = 4.7
3 WHERE name = 'Spice Villa';
```

Extra options

				id	name	cuisine	rating	city
☐				1	Spice Villa	Indian	4.7	Ahmedabad
☐				2	Pizza Hub	Italian	4.2	Ahmedabad
☐				3	Sushi World	Japanese	4.6	Mumbai
☐				4	Taco Point	Mexican	3.2	Rajkot
☐				5	Burger House	American	3.8	Surat

3.Delete all restaurants from the Restaurants table where the rating is less than 3.5 using a SQL DELETE statement.

Browse

Structure

SQL

Search

Insert

Export

Import

Run SQL query/queries on table restaurant.restaurants:

```
1 DELETE FROM Restaurants
2 WHERE rating < 3.5;
```

Extra options

id

name

cuisine

rating

city

☐

Edit

Copy

Delete

1

Spice Villa

Indian

4.7

Ahmedabad

☐

Edit

Copy

Delete

2

Pizza Hub

Italian

4.2

Ahmedabad

☐

Edit

Copy

Delete

3

Sushi World

Japanese

4.6

Mumbai

☐

Edit

Copy

Delete

5

Burger House

American

3.8

Surat

4.Use a SELECT query with WHERE and LIMIT to fetch the top 2 restaurants in the city 'Ahmedabad' with a rating above 4.0 from the Restaurants table Hint: Combine WHERE for city and rating, and LIMIT to restrict the number of results.

Browse

Structure

SQL

Search

Insert

Export

Import

Run SQL query/queries on table restaurant.restaurants:

```
1 SELECT *
2 FROM Restaurants
3 WHERE city = 'Ahmedabad'
4 AND rating > 4.0
5 LIMIT 2;
```

Extra options

id

name

cuisine

rating

city

☐

Edit

Copy

Delete

1

Spice Villa

Indian

4.7

Ahmedabad

☐

Edit

Copy

Delete

2

Pizza Hub

Italian

4.2

Ahmedabad

