

Front End Technologies

Javascript - Day 16

Agenda

- **LocalStorage**

LocalStorage

It's a feature available in the browser where we can store key value pairs to make data persistent.

Max Storage supported is up to 10MB .

We can make the data persistent on the client side using localStorage.

Example:

```
<body id="body">
  <label for="">First Name</label> <input type="text" id="firstName">
  <button id="btn">Submit</button>

  <br/>
  <br/>

  <h3>The FirstName is </h3><span id="setFname"></span>
  <script src="./script.js"></script>
</body>
```

```
var firstName = "";
document.getElementById('setFname').textContent = localStorage.getItem('name');

document.getElementById('firstName').addEventListener('keydown',(event) => {
  firstName = event.target.value;
})

document.getElementById('btn').addEventListener('click',()=> {
  localStorage.setItem('name',firstName);
  document.getElementById('setFname').textContent =
  localStorage.getItem('name');
})
```



Script.js

```
'use strict';

var colors = ['white', 'red', 'blue', 'green', 'yellow','violet'];
var len = colors.length - 1;


var buttonControl = document.getElementById('btn');
var spanControl = document.querySelector('.color');

buttonControl.addEventListener('click', () => {
  var index = generateRandomNumber();
  document.body.style.backgroundColor = colors[index];
  spanControl.textContent = colors[index];
})

function generateRandomNumber(){
  return Math.round(Math.random() * len);
}
```

Style.css

```
main {
  min-height: 100vh;
  display: grid;
  place-items: center;
}

.container {
  text-align: center;
}

.container h2 {
  background-color: #222;
  color: #fff;
```

```
padding: 10px;  
border-radius: 10px;  
margin-bottom: 25px;  
}
```

```
.btn-hero {  
  text-transform: uppercase;  
  background: transparent;  
  color: #222;  
  font-weight: 700;  
  border: 2px solid #222;  
  cursor: pointer;  
  border-radius: 10px;  
  padding: 8px;  
}
```

```
.btn-hero:hover {  
  color: #fff;  
  background: #222;  
}
```