

Fleet preventive maintenance checklist

Typical kilometre-based intervals for light commercial vehicles.



Item	Interval	Notes	Last done (km / date)
Engine oil & oil filter	Every 5,000–10,000 km	Shorter end for mineral oil, heat, dust or stop-start driving.	
Air filter	Inspect every 10,000 km; replace every 20,000–30,000 km	Check more often in dusty or desert conditions.	
Cabin (AC) filter	Every 15,000–20,000 km	Replace sooner if airflow drops or there is a smell.	
Fuel filter	Every 20,000–40,000 km	Diesel vehicles often need it more often.	
Tyre rotation	Every 10,000 km	Check pressure and tread at the same time.	
Wheel alignment & balancing	Every 10,000–20,000 km	Also after hitting a pothole or kerb, or if tyres wear unevenly.	
Brake pads & discs inspection	Every 10,000 km	Replace pads by wear, not by distance alone.	
Brake fluid	Replace every 40,000 km or 2 years	Brake fluid absorbs moisture over time.	
Coolant	Check level every service; replace every 40,000–60,000 km	Critical in hot climates; use the specified coolant type.	
Transmission fluid	Every 40,000–80,000 km	Varies widely between manual and	

Item	Interval	Notes	Last done (km / date)
		automatic gearboxes.	
Spark plugs (petrol engines)	Every 30,000–60,000 km	Iridium or platinum plugs usually last longer.	
Battery check	Every 10,000 km	Heat shortens battery life; test before summer.	
Drive belts	Inspect every 20,000 km	Timing belts have their own replacement interval in the manual.	
Suspension & steering check	Every 20,000 km	Shock absorbers, bushes, ball joints and tie-rod ends.	
AC service	Every 20,000–30,000 km or before summer	Check gas pressure, condenser and fan.	

General examples — always follow the manufacturer's instructions and local regulations.

axpense.net