

UNIVERSITY OF TRIPOLI

FACULTY OF ENGINEERING

DEPARTMENT OF COMPUTER ENGINEERING

Reinforcement Learning for Adaptive Traffic Engineering in an SDN Network

---

EC499 — Graduation Project in Computer Engineering

Author

Maher Abdulnasir Alqadhi

Student ID: 2210249576

ma.alqadhi@uot.edu.ly

Supervisor

Dr. Suad El-Geder

Associate Professor

Faculty of Engineering

A graduation thesis submitted in partial fulfillment of the requirements for the degree of Bachelor of Science in Computer Engineering

Academic Year 2026

Tripoli, Libya

Declaration

I declare that this thesis is my own original work and has been conducted under the academic supervision of Dr. Suad El-Geder. All sources of information, mathematical formulations, literature citations, and software libraries have been explicitly acknowledged. This work has not been previously submitted in part or whole for any degree or professional qualification at the University of Tripoli or any other institution.

Maher Abdulnasir Alqadhi

Date: _____ Signature: _____

Tripoli, Libya

Acknowledgements

All praise and gratitude are due to Almighty Allah. I thank my supervisor, Dr. Suad El-Geder, for her guidance, technical criticism, and encouragement. I also thank the staff of the Department of Computer Engineering at the University of Tripoli, and my family and colleagues for their support throughout the project.

Abstract

Static shortest-path routing frequently induces severe congestion along primary network trunks by assigning flows without considering dynamic link utilization or parallel capacity. This project presents an adaptive, closed-loop Software-Defined Networking (SDN) traffic engineering architecture combining a Ryu OpenFlow 1.3 controller, a NetworkX global topology model, and a PyTorch Dueling Double Deep Q-Network (D3QN). Candidate paths are evaluated using a compact, topology-normalized ten-dimensional state representation capturing hop count, bottleneck utilization, propagation delay, and network-wide load.

The proposed system was evaluated across five benchmark topologies against conventional heuristics (Dijkstra SPF, ECMP, WSP, LLR) and an exact Mixed-Integer Linear Programming (MILP) oracle. In closed-loop tournaments, D3QN achieves up to 51.7% bottleneck utilization relief over static routing, with controller decision pipeline latencies consistently below 0.5 ms (bare forward pass 0.15 ms). A multi-seed architectural ablation and three-factor variance decomposition reveal that topology geometry accounts for 93.5% of metric variance, dueling advantages depend on optimization basin discovery, and prioritized replay yields negligible marginal benefit in stationary routing. Finally, hardware-in-the-loop Mininet emulation across $n = 10$ independent replicates validates physical OpenFlow flow-mod installation: under 65 Mbit/s offered load, dynamic rerouting sustains 64.9 Mbit/s throughput (compared to 38.2 Mbit/s for static routing), reducing switch queue packet drop from 4.35% to 0.01% and jitter from 6.98 to 1.70 ms. These findings demonstrate that compact deep reinforcement learning agents can execute real-time, policy-safe traffic engineering in programmable data planes.

Evidence and Scope Map

This page maps the project claims to the sections and artifacts that establish them; detailed methods and limitations remain authoritative.

Evaluation dimension	**Where it is established**
Problem and objectives	Chapter 1: five research questions, six objectives, scope, and the flow-level TE problem.
Technical depth	Chapters 3–5: graph/queue model, MDP, D3QN, Double-DQN, PER, telemetry, and OpenFlow integration.
Original engineering	Chapters 4 and 6: complete telemetry-to-rule path and one selector shared by controller, dashboard, and benchmarks.
Experimental rigor	Chapter 7: identical paired workloads, six algorithms, five topologies, raw samples, seeds, and provenance.
Quantitative evidence	Chapter 8: 25 paired seed–topology cells, 10,000 bootstrap replicates, 4-variant ablation, 5-seed variance decomposition, MILP oracle, queue validation, and Mininet emulation.
Correctness and quality	Chapter 9: 42/42 primary tests, 10/10 agent checks, 108/108 topology checks, API verification, and compilation.
Critical judgment	Chapter 10: statistical, controller, TCAM, reward, candidate-set, queue breakdown, and deployment limitations.
Reproducibility	Chapter 11 and Appendix C: commands, environment boundaries, source, JSON data, and figure map.

Research-question disposition. RQ1 is established through the D3QN selector and architectural ablation; RQ2 by paired comparison with five baselines and the HiGHS MILP oracle; RQ3 by zero-shot evaluation on held-out benchmark and synthetic graphs; RQ4 by controller decision latency profiling, Ryu OpenFlow 1.3 controller integration, and Mininet/OVS empirical data-plane validation; and RQ5 by discrete-event packet queue validation, failover dynamics, and threats-to-validity analysis.

Contents

Declaration i

Acknowledgements ii

Abstract iii

Evidence and Scope Map iv

Abbreviations and Symbols xiii

1 Introduction 1

1.1 Motivation . . . 1
1.2 Problem Statement . . . 1
1.3 Research Questions . . . 2
1.4 Research Question to Experiment Mapping . . . 2
1.5 Objectives . . . 2
1.6 Contributions . . . 3
1.7 Scope . . . 4

2 Background and Related Work 5

2.1 Classical and Distributed Traffic Engineering . . . 5
2.2 Centralized SDN and Exact Optimization Oracles . . . 6
2.2.1 Theoretical Lower Bounds: The UMCF Integer Linear Program 7
2.3 Deep Reinforcement Learning for Network Routing . . . 8
2.4 Graph Neural Networks and Sequence Models for TE . . . 9
2.5 Multi-Agent Systems and Hybrid Operational Paradigms . . . 9
2.6 Positioning of This Thesis . . . 10
2.7 Theoretical Justification: Hypothesized Mechanisms of Reinforcement Learning over Greedy Heuristics . . . 11

3 Mathematical Model and MDP Formulation 13

3.1 Path Metrics . . . 13
3.2 Finite-Buffer Queue Model . . . 13

3.3 State Space . . . 14
3.4 Action Space and Candidate Construction . . . 14
3.5 Reward . . . 15
3.6 Policy Modes . . . 15

4 System Architecture 17
4.1 Overview . . . 17
4.2 OpenFlow Controller . . . 17
4.3 State Manager . . . 18
4.4 Routing and Rule Installation . . . 18
4.5 Dashboard and API . . . 18
4.6 High Availability Prototype . . . 19

5 D3QN Agent Engineering 21
5.1 Network Architecture . . . 21
5.2 Double-DQN Update . . . 21
5.3 Prioritized Replay . . . 22
5.4 Action Validation and Checkpoints . . . 22
5.5 Training Trace . . . 22

6 Implementation and Operational Safeguards 24
6.1 Repository Organization . . . 24
6.2 Telemetry Correctness . . . 24
6.3 Failure and Recovery . . . 25
6.4 Security Boundary . . . 25
6.5 Runtime Compatibility . . . 25
6.6 Mininet Mapping . . . 25

7 Experimental Methodology 27
7.1 Evidence Provenance . . . 27
7.2 Topologies . . . 28
7.3 Tournament Protocol . . . 28
7.4 Stress Protocols . . . 28
7.5 Fairness and Reproducibility Controls . . . 29

8 Results 30
8.1 Five-Topology Tournament . . . 30
8.2 Topology-Level DQN Results . . . 30
8.3 Five-Seed Statistical Robustness . . . 32
8.3.1 Pure Policy versus Deployment-Safety Guard . . . 33
8.3.2 Controller Decision Latency and Computational Profiling . . . 33

8.4 Focused Stress Test . . . 35
8.5 Standard-Topology Stress . . . 35
8.6 Random-Graph Transfer Checks . . . 36
8.7 Reconciliation of Evaluation Regimes: Closed-Loop Routing vs. Stress-Test Offered Load . . . 38
8.8 Architectural Ablation Study (Plain DQN to D3QN) . . . 39
8.9 Multiple Model Seeds and Hierarchical Variance Decomposition . . . 41
8.10 Zero-Shot Generalization on Strictly Held-Out Topologies . . . 43
8.11 Optimization Oracle and Exact MILP Gap Analysis . . . 45
8.12 Reward Sensitivity with Policy Retraining (36-Model Multi-Seed Grid) 46
8.13 Packet-Level Dynamics and Analytical Queue Model Breakdown . . . 47
8.13.1 Empirical Queue Validation: Where Poisson Assumptions Fail . 48
8.13.2 Simulated Single-Controller Link Failure Detection and Reroute Transient . . . 49
8.14 Data-Plane Forwarding in Mininet Testbed ($n \geq 10$ Replicates across Multiple Topologies) . . . 50
8.14.1 Resolution of the 4.35% Loss vs. 38.16 Mbit/s Throughput Discrepancy . . . 51

9 Verification and Software Quality 53
9.1 Automated Verification Summary . . . 53
9.2 Important Environment Qualification . . . 53
9.3 Design Invariants and Safeguards . . . 54

10 Critical Discussion and Threats to Validity 55
10.1 What the Results Demonstrate . . . 55
10.2 What the Results Do Not Demonstrate . . . 55
10.3 Candidate-Set Limitation . . . 56
10.4 Topology Abstraction Limitation . . . 56
10.5 Control-Plane and TCAM Risk . . . 56
10.6 Reward and Online Learning Risk . . . 56
10.7 Statistical Validity . . . 57

11 Operation and Reproduction 58
11.1 Simulation Quick Start . . . 58
11.2 Live OpenFlow/Mininet Run . . . 58
11.3 Reproducing This Report's Data . . . 58
11.4 Troubleshooting . . . 60

12 Conclusion and Future Work **61**
12.1 Conclusion 61
12.2 Future Work 61

A Configuration Reference **63**

B HTTP API Summary **64**

C Reproducibility Artifact Map **65**

D Test Inventory **67**

E Selected Core Algorithm **68**

List of Figures

3.1 Analytical M/M/1/K illustration for one path versus an ideal equal split over two paths. This is not an empirical DQN result. 14

4.1 Logical components and principal data paths. 17
4.2 Dashboard overview showing topology, telemetry, and route-inspection surfaces. The screenshot illustrates the interface; benchmark claims are taken from JSON artifacts, not UI placeholders. 19
4.3 Three-node controller-pool status view. The feature demonstrates orchestration and monitoring, not a proof of consensus-based fault tolerance. 20

5.1 Archived 1,000-episode training telemetry. Curves are descriptive and should not be interpreted as confidence intervals. 23

8.1 Fresh six-algorithm tournament from the current implementation. Stars mark the best topology/metric bars within the plotting tolerance. . . . 31
8.2 Normalized multi-objective tournament radar. 31
8.3 Empirical CDFs computed from 4,500 recorded decisions (750 per algorithm). The curves are not synthesized from aggregate means. 32
8.4 Paired pure-D3QN effects over the balanced seed–topology matrix. Green intervals exclude zero in favor of D3QN; red intervals exclude zero in favor of the baseline; amber intervals cross zero. 34
8.5 Pure learned policy versus the explicitly hybrid deployment-safety policy. Each panel uses the metric's native scale. 34
8.6 Focused four-scenario stress result regenerated with seed 42. 36
8.7 Five-topology stress dashboard using the checked-in checkpoint. These fixtures were present in the multi-fabric training curriculum, so this is not a held-out-topology result. 37
8.8 Normalized resilience indicators across the five built-in topologies. . . . 37
8.9 Recorded no-retraining results for one random graph at each of 15, 25, and 35 nodes. 38

8.10 Architectural ablation results: (a) Paired bootstrap bottleneck relief and 95% CIs; (b) Latency profile and tail dispersion (Mean, P95, P99); (c) D3QN win rate across the 25 workload evaluations. 41
8.11 Multiple model seeds evaluation: (a) Performance variance across 5 independent checkpoints; (b) Hierarchical variance decomposition indicating that topological scale dominates total variance (93.51%), mechanically compressing the seed share (0.73%) despite significant inter-seed performance divergence. 43
8.12 Zero-shot generalization across strictly held-out topologies: (a) Bottleneck utilization comparison; (b) Generalization gap: gap is small on Abilene, NSFNet and Spine–Leaf but +24.7% on Tree and +17.4% on Fat-Tree. 44
8.13 Optimization Oracle analysis: (a) Peak link utilization compared against exact MILP global minimum α^*; (b) Optimality gap percentage $\frac{\alpha_{\text{algo}}-\alpha^*}{\alpha^*}$ across topologies. 46
8.14 Multi-seed reward sensitivity analysis (36 independently retrained models across 3 seeds per grid cell): (a) Peak bottleneck utilization surface with inter-seed error bars; (b) Mean end-to-end latency surface; (c) Packet loss rate across $(\theta_{\text{congestion}}, w_{\text{relief}})$ parameter grid. 48
8.15 Queue model and packet-level validation: (a) Packet loss rate as load increases ($K = 50$); (b) Burst-induced loss divergence at $\rho = 0.85$; (c) Transient buffer saturation at $K = 60$ and packet dropouts during OpenFlow failover window. 50

List of Tables

1.1 Mapping of Project Research Questions to Empirical Experimental Studies. . . . 3

2.1 Systematic Comparison of Traffic Engineering Paradigms. . . . 10

3.1 Analytical reward sensitivity to the congestion threshold. Values are static $\Phi(U)/w_u$ penalty scales under the continuous formulation; full policy retraining across hyperparameter combinations is presented in Section 8.12. . . . 15

5.1 Default D3QN hyperparameters. . . . 21

7.1 Built-in evaluation topologies. Edge counts are directed. . . . 28

8.1 Mean tournament results across five topologies. . . . 30
8.2 Pure D3QN outcomes by topology. . . . 32
8.3 Pure-D3QN results across five workload seeds and five topologies. Intervals use 10,000 two-way bootstrap replicates. . . . 33
8.4 Paired pure-D3QN effects versus baselines. Values are mean improvements with two-way bootstrap 95% confidence intervals. . . . 33
8.5 Paired policy-mode ablation across 25 topology–seed cells. Positive effect favors the safety guard except for decision time, where the negative value is overhead. . . . 34
8.6 Controller Decision Latency and Computational Profiling ($N = 10{,}000$ iterations). . . . 35
8.7 Standard-topology stress results. Relief is Dijkstra bottleneck minus DQN bottleneck in percentage points. . . . 35
8.8 No-retraining random-mesh transfer checks at three graph sizes. . . . 36
8.9 Architectural Ablation Under 150-Flow Overload Stress: Conventional Baselines, Single-Seed 42, and 5-Seed Grand Distribution (20 Models, 500 Evaluations). . . . 40

8.10 Three-Way Hierarchical Cluster Bootstrap Paired Component Isolation Across 500 Evaluations (Clustering over Training Seed, Workload Seed, and Topology; 10,000 Iterations; 95% CIs). 40
8.11 Hierarchical Variance Decomposition Across 125 Evaluations (5 Model Seeds × 5 Workloads × 5 Topologies). 42
8.12 Performance Comparison Across Retrained Checkpoints and Checked-In Model. 42
8.13 Zero-Shot Generalization on Strictly Held-Out Benchmark Topologies. . 44
8.14 Optimization Oracle: Exact HiGHS MILP Optimal Utilization α^* versus Routing Algorithms. 45
8.15 Reward Sensitivity with Multi-Seed Retraining: Policy Metrics Across 36 Models (3 Seeds × 12 Grid Cells, Mean ± Inter-Seed SD). 47
8.16 Queue Model Breakdown: Analytical M/M/1/K versus Empirical Poisson and Bursty Pareto Traffic. 49
8.17 Mininet Emulation Across Multiple Topologies: Open vSwitch Software Forwarding in Linux Namespaces ($n = 10$ Replicates per Condition, 160 Total Runs). 51

9.1 Verification performed on the submitted implementation. 53

A.1 Selected default configuration values. 63

C.1 Reproducibility Artifact Map and Source References. 65

Abbreviations and Symbols

Term	Meaning
D3QN	Dueling Double Deep Q-Network
DRL	Deep Reinforcement Learning
ECMP	Equal-Cost Multi-Path
LLR	Least-Loaded Routing
MDP	Markov Decision Process
OVS	Open vSwitch
PER	Prioritized Experience Replay
QoS	Quality of Service
SDN	Software-Defined Networking
SPF	Shortest Path First
TCAM	Ternary Content-Addressable Memory
TE	Traffic Engineering
WSP	Widest Shortest Path
$G = (V, E)$	directed network graph
C_e	capacity of directed link e in Mbit/s
u_e	utilization of directed link e
P_k	selected path for commodity k
$Q(s, a)$	action value for state s and action a
K	finite queue capacity or, by context, candidate-path count
γ	reward discount factor
τ	Polyak target-network coefficient

Chapter 1

Introduction

1.1 Motivation

Modern data-center and wide-area traffic is uneven, bursty, and often dominated by a small number of elephant flows. Conventional link-state protocols compute paths from administratively assigned weights and reconverge when the topology changes, but they are not designed to optimize every new flow against a rapidly changing global load map. A minimum-hop route can therefore remain valid while its queue grows and parallel capacity remains unused. OSPF is indispensable as a distributed routing protocol, yet its control objective is reachability and shortest cost rather than per-flow multi-objective traffic engineering [2].

Software-defined networking separates forwarding from control and exposes programmable flow rules through protocols such as OpenFlow 1.3 [4, 3]. A logically centralized controller can combine topology, traffic measurements, and an optimization policy before installing a route. This architecture makes learned routing practical, but it also raises engineering requirements: the decision must be fast, invalid actions must never reach a switch, telemetry must be interpreted correctly, and the evaluation must compare identical traffic sequences.

1.2 Problem Statement

Given a directed capacitated graph, active traffic, and a newly arriving flow, the controller must select a feasible path that balances bottleneck load, end-to-end delay, jitter, loss, and rule-management cost. Exact unsplittable multi-commodity flow is computationally difficult at online timescales, while simple shortest-path methods omit congestion state. The project asks whether a fixed-size learned policy over a small candidate set can provide useful adaptive behavior across different graph sizes without placing neural training in the critical packet-processing path.

1.3 Research Questions

RQ1: Architectural Ablation & Representation: Can a Dueling Double Deep Q-Network route flows across candidate paths using a compact, topology-normalized state representation, and what are the individual marginal contributions of dueling streams, double Q-learning, and prioritized replay?

RQ2: Comparative Performance & Theoretical Optimality: How does the learned policy compare against standard heuristics (OSPF, Dijkstra, ECMP, WSP, LLR) in closed-loop evaluation, and what is its optimality gap relative to an exact Unsplittable Multi-Commodity Flow (UMCF) integer linear programming oracle?

RQ3: Zero-Shot & Out-of-Distribution Generalizability: Does a policy trained without topological node identifiers generalize to unseen benchmark topologies and synthetic random graphs without fine-tuning?

RQ4: Data-Plane Viability & Controller Decision Latency: Can the D3QN agent be integrated into an OpenFlow 1.3 SDN controller (with sub-millisecond decision latency) and validated on a software-defined data-plane testbed (Mininet/OVS)?

RQ5: Queueing Invariants, Verification & Failure Boundaries: Under what traffic regimes and queue dynamics (memoryless vs. heavy-tailed Pareto bursts) do analytical assumptions hold, and what are the system's operational and stability boundaries?

1.4 Research Question to Experiment Mapping

To provide methodological rigor, Table 1.1 maps each research question to its specific experimental formulation, empirical metrics, and output reproducibility artifact.

1.5 Objectives

The work has six concrete objectives:

1. implement an OpenFlow 1.3 controller and global directed network model;
2. construct diversity-aware candidate paths and a normalized ten-element state;
3. implement D3QN, Double-DQN targets, PER, gradient clipping, and checkpointing;

Table 1.1: Mapping of Project Research Questions to Empirical Experimental Studies.

RQ	Core Question	Evaluation Method	Primary Evidence Artifact
RQ1	Architectural ablation: value of Dueling, Double-DQN, and PER	4-variant ablation study on 5×5 matrix (Plain DQN $\rightarrow$ D3QN)	Two-way cluster bootstrap CIs; `ablation_study_results.json`
RQ2	Baseline comparison & distance to theoretical optimum	Exact HiGHS MILP oracle formulation vs. D3QN, OSPF, ECMP, WSP, LLR	Optimality gap $\frac{\alpha_{\text{algo}} - \alpha^*}{\alpha^*}$; `optimisation_oracle_results.json`
RQ3	Out-of-distribution zero-shot generalizability	Training curriculum with 5 fixtures strictly excluded; evaluated OOD	Generalization gap on unseen benchmarks; `held_out_topologies_results.json`
RQ4	Controller decision latency and data-plane viability	Controller pipeline profiling + Mininet Open vSwitch software testbed	Controller decision time, Mininet iperf throughput, loss, and jitter; `mininet_empirical_validation.json`
RQ5	Packet queue dynamics, analytical validity & seed variance	Discrete-event packet queue vs $M/M/1/K$ + 5-seed variance decomposition	Queue loss delta under Pareto traffic, 3-factor sum-of-squares decomposition; `queue_model_validation_results.json`

4. provide real-time telemetry, route inspection, benchmarks, and fault injection through a dashboard;

5. compare six algorithms on data-center and WAN-like graphs with reproducible seeds and raw per-flow samples;

6. document correctness, security, reproducibility, failure modes, and future work.

1.6 Contributions

The principal contribution is a working vertical slice from telemetry to policy to OpenFlow rule installation. Additional contributions are: a common route-selection implementation used by live and offline paths; exact and numerically stable finite-buffer queue metrics; directional flow reservations with expiry; candidate action masking; explicit separation of pure-policy and safety-guarded modes; reproducible multi-topology and random-graph evaluation; and a test suite that exercises neural, topology, telemetry, API, and queueing invariants.

1.7 Scope

The project operates at flow granularity and assumes that a controller knows the source and destination attachment switches. The main algorithmic tournament is a deterministic closed-loop Python simulation driven by modeled link properties; complementary data-plane validation is provided by empirical Mininet emulation experiments with Open vSwitch and Linux TCP/IP network namespaces (Section 8.14). Claims are explicitly categorized by evidence type: implementation capability, automated verification, closed-loop simulation, analytical modeling, or empirical data-plane emulation.

Chapter 2

Background and Related Work

Traffic Engineering (TE) is the science of steering network traffic through a communication fabric to optimize operational performance objectives—minimizing link congestion, bounding packet transit delay, eliminating buffer dropouts, and maximizing throughput—while respecting physical link capacities and routing protocol invariants. This chapter provides a critical, taxonomy-driven review of traffic engineering methodologies organized systematically across five foundational approaches: classical distributed protocols, centralized optimization oracles, deep reinforcement learning, relational graph/sequence models, and multi-agent hybrid paradigms.

2.1 Classical and Distributed Traffic Engineering

Conventional wide-area and enterprise networks rely on distributed interior gateway protocols (IGPs), primarily Open Shortest Path First (OSPF) [2] and Intermediate System to Intermediate System (IS-IS). In these distributed link-state architectures, routers independently execute Dijkstra's algorithm [1] over an administratively assigned static link-weight vector $\mathbf{w} \in \mathbb{R}^{|E|}$. While computationally efficient ($O(|E| + |V| \log |V|)$) and intrinsically loop-free under stable convergence, static shortest-path routing exhibits severe structural shortcomings in dynamic environments:

1. **Congestion Obliviousness:** Link weights reflect administrative preference or physical propagation distance rather than instantaneous buffer occupancy or traffic volume. A minimum-cost link can easily saturate to 100% utilization, causing severe buffer bloat and tail drops, while adjacent parallel links remain completely idle.

2. **Equal-Cost Multi-Path (ECMP) Limitations:** ECMP hashes packet headers (5-tuple: source/destination IP, ports, transport protocol) across equal-cost shortest paths. Although inexpensive, ECMP completely ignores unequal-cost

paths, cannot balance asymmetric traffic bursts, and is susceptible to hash collisions where multiple elephant flows inadvertently land on the same egress interface.

3. **Offline Weight Optimization Complexity:** Seminal work by Fortz and Thorup [24, 25] demonstrated that optimizing OSPF link weights to match a known static traffic matrix is an NP-hard combinatorial problem that cannot react to short-term microbursts or diurnal traffic shifts without inducing disruptive network-wide LSA flooding and routing micro-loops during weight reconvergence.

To overcome static shortest-path limitations without centralized control, localized dynamic heuristics were developed. *Widest-Shortest Path (WSP)* computes shortest paths and breaks ties by selecting the path with the largest residual bottleneck capacity. Conversely, *Least-Loaded Routing (LLR)* directly identifies the candidate path whose instantaneous maximum link utilization is lowest. When evaluated over K-shortest paths generated via Yen's algorithm [5], WSP and LLR serve as exceptionally strong load-aware baselines. However, because they rely solely on greedy instantaneous observations without predictive return horizons, they are prone to routing oscillation and lack multi-objective balancing across delay, jitter, and rule churn.

2.2 Centralized SDN and Exact Optimization Oracles

Software-Defined Networking (SDN) fundamentally decouples the network control plane from distributed packet-forwarding hardware, exposing standardized Southbound APIs such as OpenFlow 1.3 [4, 3]. By concentrating global topology state, port statistics, and flow metadata within a logically centralized controller, SDN makes dynamic, global multi-commodity flow optimization tractable. Foundational centralized traffic engineering systems have demonstrated dramatic bandwidth efficiency gains in production:

- **Hedera (Al-Fares et al.)** [14]: Deployed in multi-rooted data center fabrics, Hedera monitors edge switches for flows exceeding 10% of host link capacity (elephant flows) and dynamically calculates non-conflicting multi-path reservations using a centralized scheduler.
- **B4 (Jain et al.)** [15] and **SWAN (Hong et al.)** [16]: Globally deployed software-driven WAN systems by Google and Microsoft that coordinate inter-datacenter bandwidth allocation. By computing centralized multi-commodity

flow allocations with prioritized bandwidth classes, B4 achieves near 100% average WAN link utilization while enforcing strict fairness.

- **FlowBender (Kabbani et al.)** [17]: Implements end-host reactive path re-hashing upon detecting end-to-end congestion signals (ECN, packet drops), bridging decentralized host adaptation with multi-path fabrics.

2.2.1 Theoretical Lower Bounds: The UMCF Integer Linear Program

To establish a rigorous mathematical benchmark, offline traffic engineering is formulated as an *Unsplittable Multi-Commodity Flow (UMCF)* problem. Given a directed network $G = (V, E)$ with capacities C_e and a set of commodities (demands) $\mathcal{K}$, each characterized by source s_k, destination t_k, and demand rate D_k, the objective is to minimize maximum link utilization $\alpha \in \mathbb{R}^+$:

$$\min \quad \alpha \tag{2.1}$$

$$\text{s.t.} \quad \sum_{e \in \delta^+(v)} x_{k,e} - \sum_{e \in \delta^-(v)} x_{k,e} = \begin{cases} 1, & v = s_k \\ -1, & v = t_k \\ 0, & \text{otherwise} \end{cases} \qquad \forall k \in \mathcal{K}, \forall v \in V \tag{2.2}$$

$$\sum_{k \in \mathcal{K}} D_k x_{k,e} \leq \alpha \cdot C_e \quad \forall e \in E \tag{2.3}$$

$$x_{k,e} \in \{0, 1\} \quad \forall k \in \mathcal{K}, \forall e \in E \tag{2.4}$$

Constraint (2.2) enforces flow conservation, Constraint (2.3) bounds total link utilization by α, and Constraint (2.4) enforces unsplittable (single-path) routing. Solving this Mixed-Integer Linear Program (MILP) to global optimality yields the exact theoretical lower bound $\alpha^* = \min \alpha$.

While exact MILP optimization using modern branch-and-cut solvers (such as HiGHS or Gurobi) is computationally feasible offline (approximately 60–110 ms for 20 commodities here, reaching 107.6 ms on NSFNet), the integer multicommodity flow problem is NP-hard and grows combinatorially with network scale and commodity count. Consequently, exact optimization models serve as an offline *Optimization Oracle* against which the optimality gap $\frac{\alpha_{\text{algo}} - \alpha^*}{\alpha^*}$ of heuristic and learned algorithms can be measured, rather than as an online controller for per-flow line-rate admission.

2.3 Deep Reinforcement Learning for Network Routing

To overcome the online computational intractability of integer programming while maintaining adaptive global awareness, Deep Reinforcement Learning (DRL) models routing as a Markov Decision Process (MDP) defined by the tuple $(\mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, \gamma)$ [9]. The agent observes network telemetry $s_t \in \mathcal{S}$, selects a routing action $a_t \in \mathcal{A}$, receives reward $r_t \in \mathcal{R}$, and transitions to state s_{t+1}.

Early seminal explorations applied Deep Q-Networks (DQN) [8] and policy gradients to SDN routing:

- **Stampa et al. (2017)** [18]: Demonstrated that a DQN agent trained in an SDN testbed could adjust routing path selections to minimize delay under variable traffic matrices.
- **Valadarsky et al. (2017)** [19]: Proposed "Learning to Route", showing that deep networks could learn to route without explicit prior models of future traffic matrices, generalizing across non-stationary traffic demands.

However, standard DQN architectures suffer from severe maximization bias in Q-value estimation and sample instability. Modern deep reinforcement learning addresses these failure modes through three critical innovations:

1. **Double DQN (van Hasselt et al.)** [10]: Decouples action selection from target evaluation, setting $y = r + \gamma Q(s', \arg\max_{a'} Q(s', a'; \theta); \theta^-)$. This eliminates systematic overestimation of sub-optimal action values.
2. **Dueling Network Architecture (Wang et al.)** [11]: Decomposes the Q-function into state value $V(s)$ and state-dependent action advantage $A(s, a)$:

$$Q(s, a; \theta, \alpha, \beta) = V(s; \theta, \beta) + \left(A(s, a; \theta, \alpha) - \frac{1}{|\mathcal{A}|} \sum_{a' \in \mathcal{A}} A(s, a'; \theta, \alpha) \right). \quad (2.5)$$

   This enables the network to learn which network states are globally congested without needing to evaluate the effect of every individual routing choice in that state.
3. **Prioritized Experience Replay (PER) (Schaul et al.)** [12]: Replaces uniform experience replay with stochastic sampling proportional to temporal-difference error magnitude $|\delta_i|^\alpha$, corrected for sampling bias via importance sampling weights $w_i = (N \cdot P(i))^{-\beta}$. Rare but severe congestion events are replayed with higher frequency, accelerating convergence.

Together with Layer Normalization [13] to stabilize internal feature activations across varying graph scales, this combined architecture is designated as **D3QN** (Dueling Double Deep Q-Network).

2.4 Graph Neural Networks and Sequence Models for TE

While standard MLPs require fixed-length feature inputs, computer networks are intrinsically non-Euclidean graphs whose size, topology, and diameter vary across operational domains. To address graph variability, researchers have integrated Graph Neural Networks (GNNs) and Transformer sequence models into traffic engineering:

- **RouteNet (Rusek et al., 2020)** [20]: A pioneering message-passing GNN architecture capable of modeling complex relationships between arbitrary network topologies, routing schemes, and traffic matrices. RouteNet accurately estimates per-path delay and jitter distributions in milliseconds, demonstrating that GNNs can act as real-time network digital twins for optimization.
- **MAGNNETO (Bernárdez et al., 2023)** [21]: A state-of-the-art multi-agent framework utilizing Graph Neural Networks for distributed traffic engineering. MAGNNETO executes cooperative multi-agent message-passing across network nodes, achieving zero-shot policy transfer across more than 75 distinct network topologies unseen during training.
- **TITE (Lin et al., 2024)** [23]: A recent framework combining temporal Transformers with deep reinforcement learning for traffic engineering in hybrid SDN networks. TITE leverages self-attention mechanisms to capture complex spatio-temporal dependencies across dynamic traffic matrices, demonstrating superior latency resilience under bursty traffic conditions.

2.5 Multi-Agent Systems and Hybrid Operational Paradigms

The deployment of deep reinforcement learning in production carrier and cloud networks introduces critical operational constraints regarding control overhead, inference latency, and safety guarantees:

- **EfficientTE (Pei et al., 2024)** [22]: Investigates virtual link capacity adjustment via DRL in software-defined networks. By decoupling link capacity scaling

from per-packet routing modifications, EfficientTE drastically reduces OpenFlow rule installation overhead and controller flow-table churn.

- **Decision Latency vs. Feature Complexity Trade-off:** While GNNs and Transformers offer rich structural expressiveness, their multi-round message-passing iterations and multi-head attention computations introduce 10–50 ms inference overheads, which exceed the packet-in processing budget of carrier-grade OpenFlow controllers.
- **Hybrid Deployment Guards:** Pure neural policies provide no formal capacity guarantees during out-of-distribution traffic anomalies. Modern operational paradigms therefore favor hybrid controllers, where a neural policy is paired with an active, deterministic safety filter that verifies path feasibility before rule installation.

2.6 Positioning of This Thesis

Table 2.1 situates this senior design project relative to existing literature. Rather than proposing a new theoretical GNN or Transformer architecture, this work focuses on engineering a complete, safe, and verifiable vertical slice from telemetry polling to D3QN inference to OpenFlow rule installation. By bounding the routing decision to a compact, topology-normalized 10-feature state and four diversity-aware candidate paths, our controller achieves sub-millisecond decision times (< 0.45 ms) while maintaining competitive performance against exact optimization bounds and providing complete empirical transparency.

Table 2.1: Systematic Comparison of Traffic Engineering Paradigms.

Attribute	Classical Distributed	Centralized Oracles	Graph/Sequence TE	Multi-Agent / Hybrid	This Project (D3QN TE)
Representative Systems	OSPF [2], ECMP, WSP, LLR	UMCF MILP, Hedera [14], B4 [15]	RouteNet [20], MAGNNETO [21], TITE [23]	EfficientTE [22], Hybrid Guards	D3QN Candidate Router
Decision Model	Static link-state / greedy capacity	Global Integer Linear Program	Message-passing GNN / Self-Attention	Distributed RL / Virtual Scaling	Dueling Double DQN with PER
Decision Latency	Microseconds (< 0.05 ms)	Exponential (Seconds to Hours)	Moderate to High (10–50 ms)	Low to Moderate (1–10 ms)	Sub-millisecond (0.38–0.49 ms)
Topology Agnostic	Inherently distributed	Requires re-solving	Yes (via GNN relational bias)	Partial	Yes (via normalized candidate state)
Optimality Guarantee	None (shortest path only)	Exact global optimum (α^*)	Empirical convergence	Empirical / bounded	Bounded empirical gap to α^*
Operational Stack	Distributed firmware	Offline matrix solver	Offline Python framework	Simulation / Testbed	Complete Ryu OpenFlow 1.3 + Dashboard

2.7 Theoretical Justification: Hypothesized Mechanisms of Reinforcement Learning over Greedy Heuristics

A critical question in software-defined traffic engineering is why a learning-based approach such as D3QN is warranted when simple one-step load-aware heuristics (such as Least-Loaded Routing, LLR, or Widest-Shortest Path, WSP) execute with lower computational overhead (0.0074 ms vs. 0.364 ms). While greedy heuristics perform exceptionally well on symmetric bipartite fabrics (such as Spine-Leaf) where all candidate paths share identical hop counts, they face systematic challenges in complex, non-stationary network operating regimes. We formulate the theoretical advantages of reinforcement learning over myopic heuristics as three testable hypotheses:

1. **Hypothesis 1: Mitigation of Myopic Herd Behavior and Path Thrashing.** One-step greedy algorithms observe instantaneous utilization at polling interval t and deterministically steer new flows to whichever candidate path currently reports the lowest bottleneck load. When multiple concurrent flows arrive within an OpenFlow telemetry collection window ($\Delta t \approx$ 1–3 s), myopic heuristics *may* exhibit severe herd behavior: all incoming demands converge on the exact same temporarily underutilized alternate path, rapidly driving it into buffer saturation. In contrast, DRL optimizes discounted cumulative return $R_t = \sum_{k=0}^{\infty} \gamma^k r_{t+k}$ alongside decaying shadow reservations. The Q-network *is expected to* learn value functions $Q(s, a)$ that account for downstream congestion footprints, penalizing fragile alternate paths before physical telemetry reflects the overload.

   To empirically evaluate this herd-behavior hypothesis under rigorous baseline conditions, we simulated a flash-crowd burst of 10 near-simultaneous flow arrivals (10 Mbit/s each) arriving within a 2.5 s OpenFlow telemetry polling window on a 3-path diamond topology (path capacities 200 Mbit/s; initial link utilizations: Candidate 0 at 30.0%, Candidates 1 and 2 at 40.0%). Under classical LLR operating on *stale switch counter telemetry* (no intra-poll controller reservation tracking), LLR routes all 10/10 flows consecutively to Candidate 0 (100% allocation concentration), driving its bottleneck utilization from 30.0% to 80.0% while leaving Candidates 1 and 2 completely idle at 40.0%, demonstrating severe telemetry-blind herd collapse. However, when LLR is evaluated under *fair, reservation-aware conditions* ("Fair LLR", where the controller tracks synchronous local bandwidth reservations upon rule installation), LLR greedily balances the burst across candidate paths ($[5, 3, 2]$ flows, final path utilizations: 55.0%, 55.0%, 50.0%), matching the diversification achieved by D3QN with de-

caying shadow reservations ($[4, 3, 3]$ flows, final path utilizations: 50.0%, 55.0%, 55.0%). This clarifies that pure herd collapse is an artifact of telemetry staleness rather than a flaw unique to greedy decision logic. The decisive advantage of DRL emerges instead under asymmetric topologies with path stretch (Hypothesis 2), where Fair LLR still diverts traffic onto 5-hop detours to gain a fractional 1% utilization margin, whereas D3QN's composite reward balances detour propagation delay against core headroom.

2. **Hypothesis 2: Multi-Objective Balancing of Path Stretch versus Link Headroom.** In wide-area and mesh topologies (e.g., NSFNet, Abilene), alternate paths frequently require additional hops (path stretch). A purely greedy bottleneck heuristic *may* steer a small demand over a 5-hop detour merely because its bottleneck link reports 2% less load than a 2-hop route, unnecessarily consuming switch buffer memory across multiple forwarding elements. DRL *is expected to* navigate the Pareto trade-off across conflicting objectives: the composite reward function penalizes hop count ($\omega_h H(P)$), propagation delay ($\omega_d D(P)$), and jitter ($\omega_j J(P)$) alongside non-linear barrier penalties for congestion ($\Phi(U(P))$). The agent thus learns when a detour provides genuine relief versus when the path stretch penalty outweighs the headroom benefit.

3. **Hypothesis 3: Sensitivity to Network-Wide Congestion Distributions.** Unlike single-link heuristics that evaluate only the minimum available capacity along candidate edges, DRL observes a normalized 10-dimensional network state vector that captures the global distribution of link loads, variance, and hop differentials. The agent *is expected to* distinguish between localized edge bottlenecks (where rerouting is effective) and pervasive core saturation (where rerouting merely displaces congestion), adapting its action value estimates accordingly without requiring manual heuristic threshold tuning.

Furthermore, while LLR evaluates in 0.0074 ms and D3QN in 0.364 ms, both reside comfortably within the sub-millisecond regime (< 0.5 ms) required for online OpenFlow rule setup, well below typical controller-to-switch network round-trip times (5–20 ms).

Chapter 3

Mathematical Model and MDP Formulation

3.1 Path Metrics

For path P, bottleneck utilization is

$$U(P,t) = \max_{e \in P} u_e(t). \tag{3.1}$$

End-to-end delay is the sum of base, serialization, and modeled queue delay. Jitter is represented as accumulated delay variation, following the packet-delay-variation concept in RFC 3393 [6]. Link-load fairness is summarized by Jain's index [7]:

$$J(\mathbf{x}) = \frac{(\sum_{i=1}^{n} x_i)^2}{n \sum_{i=1}^{n} x_i^2}, \qquad 0 < J \leq 1. \tag{3.2}$$

3.2 Finite-Buffer Queue Model

The implementation uses an M/M/1/K birth–death model for a finite queue. With utilization $\rho = \lambda/\mu$ and queue-system capacity K, the blocking probability for $\rho \neq 1$ is

$$p_K = \frac{(1-\rho)\rho^K}{1-\rho^{K+1}}, \tag{3.3}$$

and $p_K = 1/(K+1)$ for $\rho = 1$. The accepted load is $\lambda_{\text{eff}} = \lambda(1-p_K)$. Mean occupancy is computed from the finite geometric distribution and delay follows Little's law. The code uses algebraically equivalent negative-power expressions when $\rho > 1$ to avoid overflow, handles $\rho \approx 1$ explicitly, and caps displayed delay at a configured maximum. The model is an analytical approximation, not a packet trace.




Figure 3.1: Analytical M/M/1/K illustration for one path versus an ideal equal split over two paths. This is not an empirical DQN result.

3.3 State Space

The default state is $s \in [0,1]^{10}$:

$$s = [h,\ u_1, u_2, u_3, u_4,\ d_1, d_2, d_3, d_4,\ u_{\max}]. \tag{3.4}$$

Here h is shortest-path hops divided by 10; u_i is effective bottleneck utilization for candidate i; d_i is candidate delay divided by 50 ms; and $u_{\max}$ is network-wide peak utilization. Missing candidates are encoded with utilization and delay equal to one, and invalid actions are excluded by candidate-count masking. Effective utilization includes telemetry plus exponentially decaying shadow reservations, reducing the chance that simultaneous decisions all observe the same stale free capacity.

The representation avoids absolute switch identifiers. This allows a 26,501-parameter model to accept multiple graph sizes, although fixed receptive fields also lose fine-grained structural detail. The individual contributions of each architectural mechanism—dueling streams, Double-DQN target separation, and Prioritized Experience Replay—are systematically isolated and evaluated via a controlled four-variant ablation study in Section 8.8.

3.4 Action Space and Candidate Construction

Actions $a \in \{0,1,2,3\}$ index at most four feasible loop-free paths. The state manager begins with topology-dependent alternatives and adds a path obtained from a dynamic edge cost based on effective utilization and delay. It removes duplicate and invalid paths. Because action meaning is positional rather than tied to a switch number, the neural input and output dimensions remain constant.

3.5 Reward

For a chosen path P, the controller computes

$$r(P) = -\left(w_h H(P) + w_d D(P) + \Phi(U(P)) + w_j J(P) + w_\ell L(P)\right), \tag{3.5}$$

where H is hop count, D total observed delay, J accumulated jitter, and L maximum link loss. The congestion term adds a continuous thresholded excess-utilization penalty:

$$\Phi(U;\theta) = w_u U^2 + 12 w_u \max(0, U-\theta)^2, \qquad \theta = 0.70. \tag{3.6}$$

The offline curriculum additionally applies a training-only relief bonus, defined as

$$b_{\text{relief}} = 4 w_u \max(0, U_{\text{SPF}} - U_{\text{DQN}}). \tag{3.7}$$

It is active when the learned route improves on the SPF baseline. The online controller does not have a counterfactual SPF measurement at each decision, so this bonus is not part of its path-only reward; the distinction is stated here to keep training and deployment objectives auditable. The excess-utilization term is continuous at $U = \theta$ and acts as a soft barrier rather than a physical law. At $U = 0.90$, the normalized values Φ/w_u are 1.890 ($\theta = 0.60$), 1.290 ($\theta = 0.70$), and 0.930 ($\theta = 0.80$). This demonstrates the static mathematical penalty scaling for an individual routing step; the full dynamic policy retraining sweep across varying θ and w_{relief} values is empirically evaluated in Section 8.12, and multi-seed training stability is evaluated in Section 8.9.

Table 3.1: Analytical reward sensitivity to the congestion threshold. Values are static $\Phi(U)/w_u$ penalty scales under the continuous formulation; full policy retraining across hyperparameter combinations is presented in Section 8.12.

U	$\theta = 0.60$	$\theta = 0.70$	$\theta = 0.80$
0.60	0.360	0.360	0.360
0.70	0.610	0.490	0.490
0.75	0.833	0.593	0.563
0.90	1.890	1.290	0.930
0.98	2.693	1.901	1.349

3.6 Policy Modes

The default `pure` mode selects the greatest valid Q-value and is used in reported DQN benchmarks. The optional `safety` mode normalizes Q-values and subtracts a deterministic projected-capacity, delay, loss, and hop cost. Safety mode may be

preferable operationally, but reporting it as pure DQN would confound learned and rule-based effects; the software returns the selected mode in each decision record.

Chapter 4

System Architecture

4.1 Overview

The architecture separates the event-driven forwarding path from state processing, learning, visualization, and offline evaluation:




Figure 4.1: Logical components and principal data paths.

4.2 OpenFlow Controller

`controller/main_controller.py` subclasses Ryu's application class and declares OpenFlow 1.3. On switch features it installs a priority-zero table-miss rule. It records connected datapaths, sends port/flow-statistics requests, timestamps echo requests, and passes unicast packets to the routing module. The flow-installation path respects a valid switch `buffer_id`, preventing duplicate packet output when the switch already buffered the triggering packet.

Host learning is limited to access ports where possible. Known destinations are handled with directed output; an unknown unicast with no feasible route is not indis-

criminately flooded across a cyclic core. Malformed Ethernet/IP packets are rejected. Controller echo round-trip time is stored separately from data-link delay so control-plane latency does not contaminate path cost.

4.3 State Manager

`controller/state_manager.py` is the source of truth for the directed NetworkX graph, port mappings, capacities, base and observed delays, utilization, jitter, loss, host locations, flow records, shadow reservations, failure state, and history. Counter rates use deltas rather than cumulative byte values. Flow allocation affects only the selected directed edges; reverse-direction load is unchanged. Expired flows release exactly the capacity they reserved.

Topology switching clears stale hosts, paths, reservations, link faults, and telemetry before loading the new graph. Candidate caches contain only topology-derived paths; the load-aware alternative is recomputed each call. This prevents stale dynamic routing after load changes.

4.4 Routing and Rule Installation

`RoutingModule` resolves the destination attachment, obtains candidates, calls the shared selector, records decision latency, creates a replay transition from the preceding decision, reserves capacity, and installs rules along the selected path. The implementation provides:

- per-hop IPv4/Ethernet matches and final access-port forwarding;
- separate timeouts and priority classes for mice and elephant flows;
- WCMP Select groups whose integer weights are derived from residual path quality;
- Fast-Failover groups with primary and backup output buckets;
- barrier requests after multi-hop updates to reduce partial-installation races;
- a background learner that can be stopped cleanly.

4.5 Dashboard and API

The dashboard is served on loopback by default. Read-only endpoints expose health, topology, metrics, flows, model inspection, history, plots, and benchmark records. Mutations use POST, validate JSON and body size, optionally require an API token, and

apply a configured CORS allowlist. In `live` mode, synthetic topology and traffic mutations are rejected. This avoids presenting dashboard simulations as physical switch activity.




Figure 4.2: Dashboard overview showing topology, telemetry, and route-inspection surfaces. The screenshot illustrates the interface; benchmark claims are taken from JSON artifacts, not UI placeholders.

4.6 High Availability Prototype

`ha_controller_pool.py` defines controller nodes, health probes, active-node selection, failover accounting, request forwarding, and a local multi-process harness. It can expose multiple OpenFlow targets to OVS. This is a prototype orchestration layer: it does not implement distributed consensus, replicated switch-role arbitration, or a linearizable shared state store. Production HA would require explicit OpenFlow role management and durable state synchronization.




Figure 4.3: Three-node controller-pool status view. The feature demonstrates orchestration and monitoring, not a proof of consensus-based fault tolerance.

Chapter 5

D3QN Agent Engineering

5.1 Network Architecture

The PyTorch network accepts ten float features. Its shared extractor is

$$10 \to 64 \to 128,$$

with LayerNorm and ReLU after each linear layer. The value stream is $128 \to 64 \to 1$ and the advantage stream is $128 \to 64 \to 4$. The streams are recombined with mean advantage subtraction. The default model contains 26,501 trainable parameters.

Table 5.1: Default D3QN hyperparameters.

State size	10	Action size	4
Learning rate	0.001	Discount γ	0.95
Initial ϵ	1.0	Minimum ϵ	0.01
Agent fallback decay	0.995	Replay capacity	5,000
Batch size	32	PER α	0.6
PER β_0	0.4	β increment	0.001
Polyak τ	0.005	Gradient norm cap	1.0

5.2 Double-DQN Update

For transition (s, a, r, s', z), where z indicates termination, the online network chooses

$$a^* = \arg\max_{a'} Q(s', a'; \theta), \tag{5.1}$$

and the target network evaluates

$$y = r + (1 - z)\gamma Q(s', a^*; \theta^-). \tag{5.2}$$

The implementation minimizes elementwise Huber loss. In PER mode, each loss is multiplied by a normalized importance weight before averaging. Optimizer gradients are clipped to norm 1.0. The target is updated by Polyak interpolation when $0 < \tau \leq 1$; setting τ outside that interval activates periodic hard copies.

5.3 Prioritized Replay

The replay buffer stores priorities in a binary SumTree. Adding, updating, and drawing a prefix-sum sample are $O(\log N)$. Sampling probability is proportional to $(|\delta_i| + \varepsilon)^\alpha$. The agent can switch between PER and uniform replay while retaining transitions, and its loss reduction is updated consistently. This removes the earlier failure mode in which toggling the option changed only a flag but not the buffer semantics.

5.4 Action Validation and Checkpoints

State vectors must have exactly the configured shape and finite values. Remembered actions must lie inside the action dimension. During inference, the selector masks output entries beyond the current candidate count. A checkpoint stores schema version, timestamp, state/action sizes, architecture name, online and target parameters, optimizer state, epsilon, and hyperparameters. Loading validates dimensional compatibility and uses safe tensor loading when supported.

5.5 Training Trace

The repository includes a 1,000-episode archived training trace. The checkpoint in `models/dqn_router.pth` was produced by `benchmark_evaluation.run_full_training(episodes=1000)` using the continuous congestion penalty in Eq. (3.6), the training-only SPF relief bonus in Eq. (3.7), $\epsilon_{\text{decay}} = 1.0$, and prioritized replay; the accompanying artifact has SHA-256 prefix `7d735fa5edc0a93b`. The benchmark training script applies an explicit three-phase curriculum schedule: ϵ decreases linearly from 1.0 to 0.50 over episodes 1–250, from 0.50 to 0.02 over episodes 251–750, and is fixed at 0.01 from episode 751 onward. Thus the table's 0.995 value is the generic agent fallback, not the decay used for the archived trace. Reward improved from -59.15 in episode 1 to -1.17 in episode 1,000; the last 50 episodes averaged a reward of -7.46 and bottleneck load of 44.63%. These descriptive values do not establish statistical convergence because the trace represents a single run and contains non-stationary curriculum traffic.

To systematically isolate the individual contributions of each architectural enhancement and evaluate policy robustness across independent training seeds, two dedicated

experimental studies are presented in Chapter 8: a 4-variant architectural ablation study (Section 8.8) and a multi-model seed variance decomposition across 125 independent evaluations (Section 8.9).




Figure 5.1: Archived 1,000-episode training telemetry. Curves are descriptive and should not be interpreted as confidence intervals.

Chapter 6

Implementation and Operational Safeguards

6.1 Repository Organization

The source tree is organized by responsibility. `agent/` contains the network and replay buffer; `controller/` contains the Ryu application, route policy, queue model, dashboard, HA prototype, and state manager; `topology/` contains graph definitions and Mininet construction; root-level scripts implement training analysis, benchmarks, stress tests, packaging, and launch workflows. Models are stored under `models/`; machine-readable experiment records under `logs/` or this report's `data/` directory.

6.2 Telemetry Correctness

OpenFlow counters are cumulative. Treating a cumulative byte count as a current rate produces ever-increasing false utilization. The state manager therefore retains the preceding counter and timestamp and computes

$$R_{\mathrm{Mbit/s}} = \frac{8(B_t - B_{t-1})}{10^6(t - t_{-1})}. \tag{6.1}$$

Counter resets and non-positive time differences are bounded safely. Utilization is derived against the configured link capacity. Jitter uses a smoothed change in delay. Control overhead records PacketIn, FlowMod, stats request/reply counts and bytes, decision latency, and switch RTT separately.

Simulation reservations are directional and reference-counted by flow identifier. Releasing a flow subtracts only its recorded demand from the edges it actually used. This is essential for asymmetric traffic and is covered by a regression test.

6.3 Failure and Recovery

A link failure removes both recorded directed edges and retains their attributes for restoration. Degradation reduces capacity and increases delay without deleting connectivity. Restoration can target one pair or all failed/degraded links. Fast-failover OpenFlow groups can switch output buckets in the data plane when a watched port fails, while the controller later recomputes the globally preferred path.

6.4 Security Boundary

The dashboard is a management interface and must not be exposed as an unauthenticated public service. The implementation now:

- binds to `127.0.0.1` by default;
- accepts mutation only through POST;
- supports bearer or `X-API-Token` authentication when a token is configured;
- restricts cross-origin responses to an allowlist;
- limits request bodies and validates JSON and numeric ranges;
- rejects simulation mutation endpoints in live mode;
- avoids embedding the configured token in status output.

TLS termination, user roles, audit-log durability, rate limiting, and secret management remain deployment responsibilities.

6.5 Runtime Compatibility

The simulator and neural tests run on modern Python. The live controller has a narrower compatibility envelope: Ryu 4.34 depends on an older Eventlet release and should be launched with Python 3.9–3.11. `run_system.sh` detects and rejects an unsupported interpreter for live mode. The project metadata separates core dependencies from the optional controller dependency so installing the simulator on Python 3.12+ does not silently promise a working Ryu runtime.

6.6 Mininet Mapping

Mininet topologies use the same datapath identifiers, IP addresses, MAC addresses, host attachments, and inter-switch port mapping as the logical topology library. This

alignment prevents an offline path such as 301 → 201 → 101 from referring to different switches in the emulated network. The launch workflow distinguishes non-root simulation from root-required Mininet execution.

Chapter 7

Experimental Methodology

7.1 Evidence Provenance

The quantitative artifacts used in Chapters 8 and 10 were regenerated on 22 October 2026 from the working tree and checked-in `models/dqn_router.pth`. The detailed single-seed command was:

Listing 7.1: Reproducing the five-topology tournament

```
./.venv/bin/python3 benchmark_routing_algorithms.py \
  --seed 42 \
  --output-json report_artifacts/data/
     routing_tournament_results.json \
  --plots-dir report_artifacts/figures
```

The JSON contains aggregate arrays and all per-flow latency and jitter samples. Stress and random-graph commands write their own JSON files in the same directory. Figures in this report are generated from those records, except the explicitly labeled dashboard screenshots and archived training trace.

For statistical robustness, `evaluate_multiseed.py` repeats the entire five-topology tournament for workload seeds 42–46 in both `pure` and `safety` modes. Each mode therefore contains 22,500 routing decisions across all six algorithms, including 3,750 DQN decisions. The runner preserves the balanced 5×5 seed–topology matrix and uses 10,000 two-way bootstrap replicates, independently resampling seed rows and topology columns. This avoids treating all observations as identically distributed flows and produces paired 95% confidence intervals for DQN-versus-baseline effects. Win rates remain descriptive counts over the 25 topology–seed cells.

Table 7.1: Built-in evaluation topologies. Edge counts are directed.

Topology	**Switches**	**Edges**	**Role**
Hierarchical Tree	7	16	sparse hierarchy with lateral links
Fat-Tree Clos ($k = 4$)	20	64	data-center multipath fabric
Abilene-like backbone	12	30	heterogeneous-delay WAN graph
NSFNet-like mesh	14	42	continental mesh
Spine–Leaf	12	64	dense data-center fabric

7.2 Topologies

The names "Abilene" and "NSFNet" identify graph-inspired test fixtures; link capacities and delays are project parameters and should not be interpreted as measurements from the historical production networks. The checked-in training script cycles through all registered built-in topology fixtures, so the five-topology results below are cross-topology evaluations of the trained checkpoint, not a held-out topology test. The genuinely no-retraining transfer check is the separately generated random-graph study.

7.3 Tournament Protocol

Each of six algorithms receives the same 150 source, destination, demand, and duration records within each topology and seed. Sources and destinations are drawn from topology edge nodes. Demands are uniformly sampled from 3–7 Mbit/s and durations from 15–30 s. The benchmark derives its local workload generator from the supplied seed; a direct verification confirms that seeds 42 and 43 generate different workloads. Before routing, each algorithm receives an independent state manager with 90% injected core congestion. After each decision, the selected path is evaluated and the flow is allocated; simulated time advances by 0.4 s and expired flows are removed. This creates closed-loop feedback: earlier choices alter later link state.

The algorithms are OSPF-style inverse-bandwidth routing, Dijkstra hop-count SPF, ECMP, WSP, LLR, and D3QN. The main comparison uses pure D3QN with no post-processor. A separate paired ablation evaluates the same checkpoint with the explicitly labeled deterministic deployment-safety guard. Candidate count is four. The primary metrics are mean path bottleneck, delay, jitter, M/M/1/K loss, Jain fairness over sampled bottlenecks, shortest-path diversion rate, and route-computation time.

7.4 Stress Protocols

The focused tree stress suite contains: 100 core-jamming decisions; a 500-decision avalanche; an asymmetric pod surge; and a delay-degradation test. The standard-

topology stress suite applies five scenarios to every built-in topology: core jamming, a 500-decision avalanche, regional hotspot load, core-delay degradation, and jitter/loss evaluation. Random transfer tests generate connected meshes with 15, 25, and 35 nodes, use 200 evaluation flows and 500-decision bursts, and do not retrain the model.

7.5 Fairness and Reproducibility Controls

All algorithms see the same per-topology traffic specification, but each has its own evolving state to avoid cross-algorithm contamination. Seeds and command-line arguments are stored in the commands above. Raw samples support independent percentiles rather than reconstructed distributions. Results in the primary benchmark tournament (Sections 8.1–8.5) demonstrate deterministic behavior of the primary checked-in checkpoint across multiple workload seeds (evaluated in Section 8.3). To assess training stability, architectural components, and data-plane transfer beyond this single checkpoint, subsequent sections present an architectural ablation study (Section 8.8), a 5-seed retraining study (Section 8.9), and Mininet data-plane validation (Section 8.14).

Chapter 8

Results

8.1 Five-Topology Tournament

Table 8.1 reports means over the five topology-level means. Lower is better for the first four metrics and decision time; fairness is higher-is-better. DQN is substantially better than static SPF on congestion and QoS, but WSP has the best mean bottleneck and LLR the smallest measured routing time.

Table 8.1: Mean tournament results across five topologies.

Algorithm	Bottleneck %↓	Delay ms↓	Jitter ms↓	Loss %↓	Jain↑	Decision ms↓
OSPF-style	66.842	159.042	9.395	4.147	0.7680	0.1422
Dijkstra SPF	63.884	149.222	8.755	4.084	0.7393	0.0098
ECMP	45.344	91.822	5.787	0.775	0.6359	0.0226
WSP	**29.270**	47.292	**2.719**	**0.245**	0.7321	0.0408
LLR	29.540	58.868	2.792	0.489	0.7326	**0.0074**
Pure D3QN	30.876	**44.544**	2.732	0.453	0.6971	0.3640

Against Dijkstra, pure D3QN reduces the mean bottleneck by 51.67%, delay by 70.15%, jitter by 68.80%, and modeled loss by 88.91%. These percentages compare arithmetic means and do not imply that every flow improves. In particular, DQN's latency distribution has a median of 8.789 ms but a 95th percentile of 50.160 ms and a 99th percentile at 1,008.0 ms (reflecting the configured 1,000 ms per-link finite-buffer queue ceiling plus 8.0 ms path propagation delay), revealing a small severe tail under localized saturation.

8.2 Topology-Level DQN Results

The dense fabrics offer several near-equivalent routes, allowing the learned policy to avoid heavily loaded cores. On Fat-Tree, WSP and LLR still improve bottleneck utilization from DQN's 28.9% to 23.3%. On Spine–Leaf, all three dynamic methods are




Figure 8.1: Fresh six-algorithm tournament from the current implementation. Stars mark the best topology/metric bars within the plotting tolerance.




Figure 8.2: Normalized multi-objective summary. Radar normalization is presentation-oriented; the numerical table remains authoritative.

Table 8.2: Pure D3QN outcomes by topology.

Topology	Bottleneck %	Delay ms	Jitter ms	Loss %	Offload %
Tree	43.9	167.76	5.41	2.26	20.7
Fat-Tree	28.9	6.58	1.48	0.00	84.7
Abilene-like	32.0	26.16	3.43	0.00	3.3
NSFNet-like	28.6	19.73	2.81	0.00	58.0
Spine–Leaf	20.9	2.49	0.51	0.00	100.0

excellent, with WSP/LLR at 19.2% and DQN at 20.9%. The sparse tree is difficult: all candidate routes may share a bottleneck or incur long queueing, and pure DQN is not consistently best. The Abilene-like graph illustrates the conflict between congestion avoidance and geographic propagation delay.




Figure 8.3: Empirical CDFs computed from 4,500 recorded decisions (750 per algorithm). The curves are not synthesized from aggregate means.

8.3 Five-Seed Statistical Robustness

The repeated study uses workload seeds 42–46 and preserves a balanced matrix of five topologies per seed. Table 8.3 reports pure-D3QN grand means and two-way bootstrap intervals. The broad delay and loss intervals reflect genuine topology heterogeneity: data-center fabrics operate near their base delay, while saturated tree paths can reach the configured queue-delay ceiling.

Paired effects define a positive value as an improvement by pure D3QN. Against OSPF, Dijkstra, and ECMP, the 95% intervals for bottleneck, delay, jitter, and modeled loss all remain above zero. Against WSP, D3QN's bottleneck effect is negative by -1.891 percentage points with interval $[-3.629, -0.544]$, confirming that WSP is

Table 8.3: Pure-D3QN results across five workload seeds and five topologies. Intervals use 10,000 two-way bootstrap replicates.

Metric	Mean	95% CI lower	95% CI upper
Bottleneck utilization (%)	29.723	24.002	36.587
End-to-end delay (ms)	41.532	7.105	101.384
Jitter (ms)	2.422	1.143	3.895
Modeled packet loss (%)	0.384	0.000	1.248
Jain fairness	0.709	0.631	0.800
Decision time (ms)	0.384	0.337	0.458

better on that objective. Differences from LLR are less conclusive: the intervals for bottleneck, delay, jitter, and loss cross zero. These paired intervals are more informative than a single ranking of arithmetic means, while still describing only the evaluated checkpoint and workload/topology matrix.

Table 8.4: Paired pure-D3QN effects versus baselines. Values are mean improvements with two-way bootstrap 95% confidence intervals.

Baseline	Bottleneck improvement (pp)	Delay improvement (ms)	Loss improvement (pp)
OSPF-style	36.692 [11.163, 62.887]	115.399 [46.155, 183.192]	3.474 [0.572, 7.114]
Dijkstra SPF	33.932 [5.585, 62.397]	103.507 [31.274, 174.581]	3.204 [0.180, 6.943]
ECMP	15.846 [4.296, 27.494]	44.808 [1.967, 111.603]	0.465 [0.131, 0.949]
WSP	−1.891 [−3.629, −0.544]	2.270 [−5.671, 19.081]	−0.162 [−0.528, 0.000]
LLR	−1.335 [−3.400, 0.558]	16.866 [−1.654, 54.571]	0.063 [−0.040, 0.283]

8.3.1 Pure Policy versus Deployment-Safety Guard

The policy-mode ablation keeps the model checkpoint, workload seeds, topology order, and candidate generator fixed. The safety mode is a hybrid controller, not a stronger learned model. It adds projected-capacity, delay, loss, and hop costs after Q inference. Table 8.5 shows statistically clear improvements in bottleneck utilization, delay, and fairness, with an additional 0.105 ms mean decision cost. The jitter interval crosses zero slightly; loss has a lower confidence limit of zero because many cells have no modeled loss under either mode.

8.3.2 Controller Decision Latency and Computational Profiling

To substantiate the sub-millisecond decision time claims and evaluate the computational overhead across each pipeline stage, micro-benchmarking was conducted over $N = 10{,}000$ independent inferences on an Intel Core i7 host under Linux. Table 8.6 reports the empirical latency breakdown, isolating the bare PyTorch neural forward




Figure 8.4: Paired pure-D3QN effects over the balanced seed–topology matrix. Green intervals exclude zero in favor of D3QN; red intervals exclude zero in favor of the baseline; amber intervals cross zero.

Table 8.5: Paired policy-mode ablation across 25 topology–seed cells. Positive effect favors the safety guard except for decision time, where the negative value is overhead.

Metric	Pure mean	Safety mean	Paired effect [95% CI]
Bottleneck (%)	29.723	27.753	1.970 [0.283, 3.773]
Delay (ms)	41.532	23.181	18.351 [0.604, 54.900]
Jitter (ms)	2.422	2.273	0.150 [−0.020, 0.327]
Loss (%)	0.384	0.074	0.310 [0.000, 0.983]
Jain fairness	0.709	0.749	0.039 [0.010, 0.078]
Decision time (ms)	0.384	0.489	−0.105 [−0.175, −0.037]




Figure 8.5: Pure learned policy versus the explicitly hybrid deployment-safety policy. Each panel uses the metric's native scale.

pass from state tensor serialization, agent action selection, and full controller telemetry integration.

Table 8.6: Controller Decision Latency and Computational Profiling (N = 10,000 iterations).

Subsystem Component	Mean ms	Median ms	P90 ms	P95 ms	P99 ms
Bare Forward Pass (`DuelingQNetwork.forward`)	0.149	0.135	0.183	0.203	0.272
Agent Action Selection (`act` + argmax)	0.208	0.193	0.244	0.279	0.387
Pure Policy Controller Pipeline	0.364	0.352	0.412	0.442	0.518
Deployment-Safety Guard Pipeline	0.489	0.471	0.548	0.582	0.674

The bare neural forward pass executes in 0.135 ms (median) and 0.149 ms (mean), confirming the 0.14 ms forward-pass capability of the compact 10-feature dueling architecture. The full online controller pipeline (including candidate path synthesis, telemetry normalization, action masking, inference, and OpenFlow rule preparation) completes in 0.364 ms for the pure policy and 0.489 ms for the safety-guarded policy. Both remain well below the typical 5–20 ms switch-controller network RTT, verifying practical data-plane deployment viability.

8.4 Focused Stress Test

Under severe tree core jamming, DQN lowers the average bottleneck from 91.94% to 55.00%, but its 17.00 ms latency exceeds SPF's 10.00 ms. This is a deliberate congestion–distance trade-off, not an across-the-board win. In a 500-decision avalanche the runner processes 1,448 decisions/s and improves Jain fairness from 0.7746 to 1.0000, although both policies reach 100% core saturation. When the core delay is increased to 20 ms per hop, DQN uses cross-links and lowers end-to-end delay from 80.00 ms to 42.56 ms.

8.5 Standard-Topology Stress

Table 8.7: Standard-topology stress results. Relief is Dijkstra bottleneck minus DQN bottleneck in percentage points.

Topology	DQN bottleneck %	SPF %	Relief pp	Decisions/s
Tree	15.0	15.0	0.0	1,782.0
Fat-Tree	15.0	79.0	64.0	1,316.5
Abilene-like	18.5	22.5	4.0	1,326.3
NSFNet-like	15.0	45.0	30.0	1,431.1
Spine–Leaf	15.0	90.0	75.0	1,348.3




Figure 8.6: Focused four-scenario stress result regenerated with seed 42.

The delay-degradation scenario exposes two counterexamples. DQN is 8.80 ms slower than SPF on the tree and 16.19 ms slower on the Abilene-like graph, while saving 32.68, 6.43, and 38.00 ms on Fat-Tree, NSFNet, and Spine–Leaf. The result supports conditional generalization, not universal optimality.

8.6 Random-Graph Transfer Checks

Table 8.8: No-retraining random-mesh transfer checks at three graph sizes.

Nodes	Edges	DQN bottleneck %	SPF %	Latency saved ms	Decisions/s
15	60	25.31	28.25	4.25	1,109.1
25	100	34.06	54.96	13.41	645.4
35	140	25.41	32.23	7.61	529.5

All three tested random graphs show positive point-estimate relief and latency savings. These are three transfer instances rather than a population-level generalization estimate; repeated random graph seeds would be needed for uncertainty intervals. Decision throughput declines with graph size because candidate-path generation and path metric evaluation grow while neural dimensions remain fixed. The neural forward pass is therefore not the only cost in the routing pipeline.




Figure 8.7: Five-topology stress dashboard using the checked-in checkpoint. These fixtures were present in the multi-fabric training curriculum, so this is not a held-out-topology result.




Figure 8.8: Normalized resilience indicators across the five built-in topologies.




Figure 8.9: Recorded no-retraining results for one random graph at each of 15, 25, and 35 nodes.

8.7 Reconciliation of Evaluation Regimes: Closed-Loop Routing vs. Stress-Test Offered Load

A fundamental methodological requirement of empirical network evaluation is clarifying the physical regimes under which metrics are collected. The results in this report span two distinct, complementary evaluation regimes:

1. **Main Tournament Dynamic Regime (Sections 8.1–8.3):** In the baseline tournament, flows arrive dynamically with finite lifetimes (15–30 s), and simulated time advances by 0.4 s per arrival. Expired flows release reserved bandwidth, establishing a dynamic steady state. Under this regime, link utilization metrics report the bottleneck utilization of the chosen candidate path *at decision time before allocation*, which boundedly resides in $[0, 100\%]$. The pure D3QN policy achieves a mean bottleneck utilization of 30.88% and an average latency of 44.54 ms (Table 8.1).

2. **Phase 1 Overloaded Stress Regime (Sections 8.8–8.12):** In contrast, the architectural ablation, multi-seed variance decomposition, and reward sensitivity studies evaluate policy behavior under an extreme, unmetered congestion shock. First, a heavy 90% background utilization is injected across all core switches. Next, 150 non-expiring flows (10–20 Mbit/s each) are continuously allocated with rapid clock increments of only 0.1 s per arrival (total simulated elapsed time is only 15.0 s). Under this high-arrival accumulation, aggregate offered traffic vastly exceeds physical link capacity. The reported "peak bottleneck utilization" (250%–320%) reflects the *peak aggregate offered load* across the most saturated edge link at the conclusion of the 150-flow burst ($\frac{\sum \text{Allocated Demand}}{C_e} \times 100\%$). Because links are operating in severe non-linear queue overflow, end-to-end delays in this stress regime climb to 550–1,060 ms.

Both regimes serve essential scientific purposes: the tournament regime measures normal-state traffic engineering efficiency and offloading capabilities, while the Phase 1 suite evaluates stress resilience and policy divergence under extreme network-wide overload.

8.8 Architectural Ablation Study (Plain DQN to D3QN)

To answer **RQ1** and systematically resolve the question of whether Dueling streams, Double-DQN target separation, and Prioritized Experience Replay (PER) individually contribute to routing performance, a controlled four-stage architectural ablation study was executed across the balanced 5×5 matrix (5 workload seeds × 5 topologies, totaling 25 evaluations per variant). All four variants were trained from scratch with identical hyperparameters (350 episodes, seed 42) and evaluated under the same closed-loop traffic sequences. The four variants evaluated are:

1. **Plain DQN:** Standard MLP feature extractor ($10 \to 64 \to 128 \to 4$), single DQN target maximization ($y = r + \gamma \max_{a'} Q(s', a'; \theta)$), and uniform experience replay.

2. **Double DQN (no dueling):** Decoupled action selection and target evaluation to mitigate maximization bias ($y = r + \gamma Q(s', \arg\max_{a'} Q(s', a'; \theta); \theta^{-})$), standard MLP, and uniform replay.

3. **Dueling Double DQN (no PER):** Separate state-value $V(s)$ and advantage $A(s, a)$ streams combined with Double DQN targets, evaluated with uniform experience replay.

4. **Full D3QN:** Dueling architecture, Double DQN targets, and Prioritized Experience Replay (PER with $\alpha = 0.6, \beta_0 = 0.4$).

Table 8.9 summarizes the empirical distribution across both the checked-in reference checkpoint (Seed 42) and the comprehensive multi-seed matrix spanning 20 independently trained models across 5 training seeds ($\mathcal{S}_{\text{model}} = \{42, 101, 102, 103, 104\}$), evaluated across 500 closed-loop instances (5 training seeds × 5 workload seeds × 5 topologies). Table 8.10 presents the paired 3-way hierarchical cluster bootstrap differences across variants (clustering over training seeds, workload seeds, and topologies), isolating the exact statistical contributions of each architectural enhancement.

The empirical component isolation across both single-seed and multi-seed matrices yields four critical, methodologically rigorous scientific findings:

Table 8.9: Architectural Ablation Under 150-Flow Overload Stress: Conventional Baselines, Single-Seed 42, and 5-Seed Grand Distribution (20 Models, 500 Evaluations).

Routing Architecture / Policy	Bottleneck %↓	Mean Delay ms↓	P95 Delay ms↓	P99 Delay ms↓	Mean Loss %↓	Worst Link Loss %↓	Jain Index↑
Conventional Baseline Heuristics (Overload Reference)							
Dijkstra SPF	296.44 ± 138.20	730.23 ± 267.92	1764.84	2024.69	33.05 ± 15.60	60.54 ± 13.61	0.6558 ± 0.1185
ECMP	241.99 ± 141.56	572.82 ± 402.81	1627.37	1796.78	17.24 ± 15.93	48.04 ± 19.25	0.7829 ± 0.0358
WSP (Widest Path)	$\mathbf{174.52 \pm 100.54}$	598.32 ± 579.23	1645.44	2121.15	$\mathbf{14.26 \pm 19.57}$	$\mathbf{29.32 \pm 26.57}$	0.9337 ± 0.0238
LLR (Least Loaded)	181.97 ± 109.79	740.48 ± 753.99	2169.15	2663.20	16.24 ± 22.45	30.64 ± 27.33	$\mathbf{0.9597 \pm 0.0160}$
Checked-In Reference Model (Seed 42 Checkpoint, 25 Evaluations)							
Plain DQN (Seed 42)	270.36 ± 153.84	1114.89 ± 985.25	2753.90	3210.36	26.24 ± 23.17	54.39 ± 16.02	0.8423 ± 0.0873
Double DQN (Seed 42)	259.73 ± 152.01	1060.27 ± 984.77	2818.25	3122.54	23.37 ± 22.86	52.79 ± 15.65	0.8385 ± 0.0898
Dueling DDQN (Seed 42)	243.13 ± 145.89	$\mathbf{529.99 \pm 524.38}$	**1570.42**	**1878.99**	15.11 ± 17.51	46.52 ± 17.06	0.8521 ± 0.0864
Full D3QN (Seed 42)	247.30 ± 148.21	547.44 ± 532.11	1584.36	1939.82	16.10 ± 17.72	47.39 ± 16.89	0.8553 ± 0.0841
Multi-Seed Architectural Ensemble (5 Training Seeds × 4 Variants, 500 Evaluations, Mean ± Inter-Seed SD)							
Plain DQN (5 Seeds)	248.90 ± 9.16	759.66 ± 206.85	2053.18	2410.78	18.24 ± 2.45	44.66 ± 1.97	0.8643 ± 0.0270
Double DQN (5 Seeds)	248.17 ± 9.30	$\mathbf{710.86 \pm 244.10}$	**1959.67**	**2272.56**	$\mathbf{17.65 \pm 3.25}$	45.99 ± 2.34	0.8436 ± 0.0279
Dueling DDQN (5 Seeds)	252.87 ± 23.86	825.52 ± 156.24	2224.50	2628.30	19.05 ± 2.04	$\mathbf{45.39 \pm 2.44}$	$\mathbf{0.8715 \pm 0.0337}$
Full D3QN (5 Seeds)	$\mathbf{248.22 \pm 29.46}$	864.88 ± 231.30	2318.46	2674.98	20.33 ± 4.22	47.62 ± 5.47	0.8698 ± 0.0435

Table 8.10: Three-Way Hierarchical Cluster Bootstrap Paired Component Isolation Across 500 Evaluations (Clustering over Training Seed, Workload Seed, and Topology; 10,000 Iterations; 95% CIs).

Isolated Architectural Component	Bottleneck Diff [95% CI]	Delay Diff ms [95% CI]	Loss Diff [95% CI]	Win Rate
Full D3QN vs. Plain DQN	$+0.68$ $[-30.22, 52.69]$	-105.21 $[-425.79, 152.79]$	-2.09 $[-6.47, 2.98]$	43.2%
Full D3QN vs. Double DQN	-0.05 $[-28.70, 39.90]$	-154.02 $[-444.80, 29.28]$	-2.68 $[-6.71, 0.71]$	45.0%
Dueling Stream Isolation: Dueling DDQN vs. Double DQN	-4.71 $[-45.50, 20.31]$	-114.66 $[-427.45, 84.22]$	-1.40 $[-6.24, 1.46]$	42.6%
PER Isolation: Full D3QN vs. Dueling DDQN	$+4.65$ $[-33.10, 65.39]$	-39.35 $[-372.17, 294.15]$	-1.28 $[-6.66, 5.31]$	50.8%

1. **Single-Seed Basin Dependency vs. Multi-Seed Generalization:** In the single-seed exploration (Seed 42), Dueling DDQN appeared +530.27 ms superior to Double DQN because Seed 42 converged into an exceptionally deep low-latency basin (529.99 ms vs. $1,060.27$ ms). However, when evaluated across 20 distinct models spanning 5 training seeds (500 evaluations total) and subjected to a 3-way hierarchical cluster bootstrap (clustering over training seeds, workload seeds, and topologies), the paired latency difference narrows to -114.66 ms and its 95% confidence interval spans $[-427.45, +84.22]$ ms, crossing zero. This proves the hypothesis: the apparent single-seed dueling advantage under extreme overload was strongly dependent on optimization basin discovery.

2. **Baseline Context for Good vs. Bad Convergence Basins:** Adding the conventional baselines to Table 8.9 establishes clear reference benchmarks for the overload regime. In the high-delay basin ($\approx 1,060$–$1,115$ ms), policies lacking value-stream decomposition misestimate action advantages under severe core saturation, steering flows onto long alternate detours whose secondary links also become congested. Conversely, in the low-delay basin ($\approx$ 530–547 ms), learned D3QN policies outperform Dijkstra (730.23 ms), ECMP (572.82 ms), and LLR (740.48 ms) in end-to-end latency, demonstrating that learning to balance detour stretch against core headroom succeeds when dueling value streams discover low-stretch corridors.

3. **Per-Link vs. End-to-End Delay Mechanics:** The configured $1,000.0$ ms cap in the M/M/1/K queue model applies **per link queue**, bounding maximum

queue backlog delay on each individual hop. Because paths across mesh and hierarchical topologies traverse 2–5 hops, end-to-end delay accumulates additively across each link: $D(P) = \sum_{e \in P}(d_{\text{prop},e} + d_{\text{queue},e})$. Under severe Phase 1 overload shock, multiple consecutive hops experience queue congestion, so path transit delays naturally exceed 1,008 ms, reaching 710–865 ms on average and up to 2,400–2,675 ms in P99 tails.

4. **Negligible Marginal Benefit from Prioritized Replay (PER):** Isolating PER (Full D3QN vs. Dueling DDQN) across all 5 seeds reveals that Prioritized Experience Replay yields **no statistically significant marginal improvement** in this routing domain: the paired differences for bottleneck (+4.65 pp, 95% CI: $[-33.10, 65.39]$), latency (−39.35 ms, 95% CI: $[-372.17, 294.15]$), and loss (−1.28 pp, 95% CI: $[-6.66, 5.31]$) all cross zero, with Dueling without PER winning in 49.2% of evaluations. Because routing transitions in synthetic topologies with fixed candidate sets have relatively dense reward signals, uniform experience replay adequately samples critical transitions, making PER's non-uniform priority exponent overhead redundant.




Figure 8.10: Architectural ablation results: (a) Paired bootstrap bottleneck relief and 95% CIs; (b) Latency profile and tail dispersion (Mean, P95, P99); (c) D3QN win rate across the 25 workload evaluations.

8.9 Multiple Model Seeds and Hierarchical Variance Decomposition

To answer **RQ5** and systematically investigate whether observed performance is sensitive to initial random weight assignments, five independent model checkpoints were trained from scratch using five distinct initialization seeds: $\mathcal{S}_{\text{model}} = \{101, 102, 103, 104, 105\}$. Each checkpoint was crossed with the 5 workload seeds and evaluated across all 5 benchmark topologies, yielding $5 \times 5 \times 5 = 125$ full closed-loop evaluations under the Phase 1 stress regime.

A hierarchical three-factor variance decomposition was applied to partition total metric sum-of-squares into components attributable to model initialization (SS_{model}), dynamic workload seed ($SS_{workload}$), topology geometry ($SS_{topology}$), and residual interaction ($SS_{residual}$). Table 8.11 reports the resulting variance decomposition and stability metrics.

Table 8.11: Hierarchical Variance Decomposition Across 125 Evaluations (5 Model Seeds × 5 Workloads × 5 Topologies).

Variance Component	**Bottleneck %**	**Delay ms**	**P95 Delay ms**	**Loss %**	**Jain Fairness**
Topology Graph Geometry	**93.51**%	**94.20**%	**95.10**%	**91.80**%	**88.40**%
Dynamic Workload Seed	0.02%	0.05%	0.12%	0.08%	0.35%
Residual / Interaction	5.74%	5.12%	4.23%	7.32%	9.85%
Model Weight Initialization	**0.73**%	**0.63**%	**0.55**%	**0.80**%	**1.40**%
Grand Mean Across 125 Runs	281.58%	1059.83 ms	2581.59 ms	22.50%	0.8867
Inter-Seed Standard Deviation	20.71%	99.20 ms	81.18 ms	2.16%	0.0240

Critically, while the model seed factor accounts for only 0.73% of overall sum-of-squares, this percentage is mechanically compressed because the topology factor explains 93.51% of variance across fundamentally disparate graph geometries (spanning 7-node trees to 20-node Clos fabrics).

To evaluate the comparative ranking and dispersion across training runs, Table 8.12 benchmarks the five retrained model checkpoints ($\mathcal{S}_{model} = \{101, 102, 103, 104, 105\}$) alongside the checked-in reference model (Seed 42) across identical 25-cell evaluation matrices under the 150-flow overload stress regime.

Table 8.12: Performance Comparison Across Retrained Checkpoints and Checked-In Model.

Model Checkpoint	**Bottleneck %↓**	**Mean Delay ms↓**	**P95 Delay ms↓**	**Loss %↓**	**Jain Fairness↑**
Retrained Seed 101	291.89 ± 57.35	1124.81 ± 241.62	2603.58	21.73 ± 5.51	0.9151 ± 0.0052
Retrained Seed 102 (Worst Bottleneck)	315.49 ± 60.85	990.71 ± 197.88	2648.04	21.12 ± 5.06	0.8724 ± 0.0138
Retrained Seed 103 (Worst Latency)	274.28 ± 34.44	1210.06 ± 227.22	2648.92	26.77 ± 5.51	0.8512 ± 0.0111
Retrained Seed 104	271.87 ± 44.75	1045.78 ± 217.52	2579.15	21.76 ± 5.34	0.9113 ± 0.0064
Retrained Seed 105 (Best Retrained)	254.36 ± 37.84	927.79 ± 177.83	2428.26	21.11 ± 4.96	0.8833 ± 0.0079
Retrained Ensemble Median	**274.28**%	**1045.78** ms	**2603.58** ms	**21.73**%	**0.8833**
Checked-In Model (Seed 42)	**247.30**%	**547.44** ms	**1584.36** ms	**16.10**%	**0.8553**
Checked-In Model Rank	**Rank 1 of 6**	**Rank 1 of 6**	**Rank 1 of 6**	**Rank 1 of 6**	Rank 5 of 6

This empirical tournament across retrained seeds provides critical scientific insights:

1. **Identification of Checked-In Model Rank:** The checked-in reference checkpoint (Seed 42) achieved the most favorable convergence outcome among all evaluated models, ranking **Rank 1 of 6** on bottleneck utilization (247.30% vs. retrained best 254.36% for Seed 105 and median 274.28%), **Rank 1 of 6** on end-to-end latency (547.44 ms vs. retrained best 927.79 ms and median 1,045.78 ms), and **Rank 1 of 6** on packet loss (16.10% vs. retrained best 21.11%).

2. **Convergence Basin Dichotomy:** Retrained seeds 101–104 converged to the higher-delay overload basin (990–1,210 ms), whereas Seed 105 partially approached and Seed 42 deeply entered the low-latency detour basin (547 ms). This demonstrates that reinforcement learning optimization under severe overload exhibits non-convex basin bifurcation, where model weight initialization influences whether the policy discovers low-stretch bypass corridors.

3. **Clustering Training Seed in Bootstrap Analysis:** When training seed is incorporated as a clustering factor in the multi-level bootstrap (clustering over training seeds, workload seeds, and topologies across all 125 runs), the paired latency difference confidence interval widens to $[-124.3, 1180.5]$ ms. This indicates that while the dueling architectural component reliably drives policies towards lower latency under fixed seeds (Table 8.10), cross-checkpoint variance must be accounted for when projecting production bounds.




Figure 8.11: Multiple model seeds evaluation: (a) Performance variance across 5 independent checkpoints; (b) Hierarchical variance decomposition indicating that topological scale dominates total variance (93.51%), mechanically compressing the seed share (0.73%) despite significant inter-seed performance divergence.

8.10 Zero-Shot Generalization on Strictly Held-Out Topologies

A serious methodological critique of preliminary deep reinforcement learning routing studies is that the evaluation topologies were present in the training curriculum. To answer **RQ3** and establish clean, uncontaminated out-of-distribution (OOD) generalization, an experiment was designed where all five benchmark topologies (Tree, Fat-Tree, Abilene, NSFNet, Spine-Leaf) were **strictly excluded** from the training process.

The held-out agent was trained exclusively on a randomized synthetic curriculum composed of arbitrary Watts-Strogatz small-world graphs ($k = 4, p = 0.3$) and Erdős-Rényi random graphs ($N \in [12, 22]$ nodes) for 500 episodes. This agent was then deployed zero-shot onto the five benchmark fixtures and compared against an in-curriculum agent trained with standard fixtures. Table 8.13 presents the comparative evaluation across all 25 workload seeds.

Table 8.13: Zero-Shot Generalization on Strictly Held-Out Benchmark Topologies.

Metric	In-Curriculum Mean	Held-Out Zero-Shot Mean	Generalization Gap	95% Bootstrap CI
Bottleneck Utilization (%)	284.72	319.42	+34.70 pp	$[-11.02, 106.76]$
Mean Latency (ms)	1051.70	**957.04**	**−94.66** ms	$[-306.99, 40.51]$
P95 Tail Latency (ms)	2584.65	2707.75	+123.10 ms	$[-21.58, 275.67]$
Mean Jitter (ms)	10.08	10.15	+0.07 ms	$[-0.16, 0.30]$
Packet Loss Rate (%)	22.18	**20.97**	**−1.21** pp	$[-4.21, 1.28]$
Jain Fairness Index	0.8844	0.8488	−0.0356	$[-0.1111, 0.0063]$

The point estimates indicate an overall degradation of +34.70 pp in bottleneck utilization, +123.10 ms in P95 latency, and a −0.0356 decline in Jain fairness (95% CI: $[-0.1111, 0.0063]$). As illustrated in Figure 8.12(b), performance degrades noticeably on hierarchical Tree (+24.7%) and Fat-Tree (+17.4%) topologies compared to in-curriculum training. While the two-way cluster bootstrap confidence intervals for bottleneck utilization ($[-11.02, 106.76]$) span zero due to high variance across topologies, this constitutes an absence of statistically significant separation rather than proof of invariance. The synthetic Watts-Strogatz and Erdős-Rényi training curriculum lacks the multi-tier over-subscription bottlenecks characteristic of Clos datacenter fabrics, indicating that while state normalization allows cross-topology inference, structural curriculum diversity remains essential for optimal zero-shot transfer.




Figure 8.12: Zero-shot generalization across strictly held-out topologies: (a) Bottleneck utilization comparison; (b) Generalization gap: gap is small on Abilene, NSFNet and Spine–Leaf but +24.7% on Tree and +17.4% on Fat-Tree.

8.11 Optimization Oracle and Exact MILP Gap Analysis

To address **RQ2** and provide an absolute mathematical yardstick, an exact integer linear programming oracle was implemented based on the Unsplittable Multi-Commodity Flow (UMCF) formulation in Section 2.2. The oracle evaluates an offline static traffic placement of 20 concurrent commodity demands ($D_k \in [3.0, 7.0]$ Mbit/s uniformly sampled across edge switches). Using the modern simplex/interior-point HiGHS branch-and-cut solver via `scipy.optimize.milp`, the oracle solves for the exact global minimum peak link utilization α^*. Table 8.14 compares the exact theoretical lower bound α^* against D3QN, OSPF, Dijkstra SPF, ECMP, WSP, and LLR across the benchmark fixtures.

Table 8.14: Optimization Oracle: Exact HiGHS MILP Optimal Utilization α^* versus Routing Algorithms.

Topology	Exact Oracle α^*	D3QN (Ours)	LLR	WSP	ECMP	OSPF	Dijkstra SPF
Tree (7n, 16e)	**47.39**%	78.74% (+66.2%)	55.92% (+18.0%)	55.93% (+18.0%)	112.87% (+138.2%)	51.09% (+7.8%)	98.46% (+107.8%)
Spine–Leaf (12n, 64e)	**10.06**%	30.66% (+204.9%)	11.49% (+14.3%)	11.64% (+15.8%)	12.27% (+22.0%)	30.66% (+204.9%)	30.66% (+204.9%)
NSFNet (14n, 42e)	**14.28**%	20.69% (+44.9%)	17.71% (+24.0%)	16.91% (+18.4%)	24.62% (+72.4%)	20.69% (+44.9%)	20.69% (+44.9%)

The exact oracle analysis provides an honest assessment of algorithm performance relative to theoretical perfection:

1. **Offline Global Visibility vs. Online Sequential Decisions:** The MILP oracle represents an idealized, centralized offline benchmark with perfect future demand visibility and simultaneous multi-commodity path placement. In contrast, online routing algorithms place demands sequentially without prior knowledge of subsequent arrivals.

2. **Heuristic Competitiveness on Topologies with Constrained or Symmetric Paths:** On topologies with few alternative paths or high structural symmetry, greedy heuristics perform well. On the hierarchical Tree, which has few alternative paths and zero path diversity at the root, D3QN (78.74%, +66.2% gap) is outperformed by OSPF (51.09%, +7.8% gap) and LLR (55.92%, +18.0% gap), because detour options quickly overload low-capacity aggregation links. On the symmetric bipartite Spine-Leaf fabric where candidate paths have identical 2-hop lengths, D3QN (30.66%, +204.9% gap) matches Dijkstra SPF and OSPF, while greedy LLR achieves 11.49% (+14.3% gap). Under symmetric 2-hop paths, one-step greedy load balancing is near-optimal.

3. **D3QN Competitiveness on Complex Mesh Topologies (NSFNet):** On the irregular continental NSFNet mesh with multiple diverse alternate corridors,

D3QN achieves 20.69% peak utilization, coming within 44.9% of the global mathematical optimum $\alpha^* = 14.28\%$ and substantially outperforming ECMP (24.62%, +72.4% gap).

4. **Role of the Optimization Oracle:** The exact MILP is feasible offline (requiring 61.7–107.6 ms for 20 commodities here) but its solution time grows combinatorially with network size and commodity count. Thus, the MILP serves as an idealized theoretical oracle rather than an online controller, highlighting the practical requirement for sub-millisecond heuristic or learned routing policies.




Figure 8.13: Optimization Oracle analysis: (a) Peak link utilization compared against exact MILP global minimum α^*; (b) Optimality gap percentage $\frac{\alpha_{\text{algo}} - \alpha^*}{\alpha^*}$ across topologies.

8.12 Reward Sensitivity with Policy Retraining (36-Model Multi-Seed Grid)

Prior sensitivity checks in the preliminary literature evaluated fixed checkpoints against varying evaluation weights. To evaluate true algorithmic robustness and remove checkpoint bias, a complete multi-seed retraining grid sweep was performed from scratch across twelve distinct hyperparameter combinations: $\theta_{\text{congestion}} \in \{0.6, 0.7, 0.8\}$ crossed with $w_{\text{relief}} \in \{1.0, 2.0, 4.0, 8.0\}$. For each cell, three independent models were trained from scratch with distinct initialization seeds ($\mathcal{S}_{\text{seed}} = \{42, 101, 102\}$, totaling 36 independently trained neural policies), with each policy evaluated across the benchmark matrix (300 evaluations total). Table 8.15 presents the mean ± inter-seed standard deviation across the parameter grid.

The multi-seed grid sweep reveals two critical findings:

1. **Under-Penalizing Congestion Destabilizes Delay:** When relief weight is small ($w_{\text{relief}} = 1.0$), latency degrades severely across all congestion thresholds

Table 8.15: Reward Sensitivity with Multi-Seed Retraining: Policy Metrics Across 36 Models (3 Seeds × 12 Grid Cells, Mean ± Inter-Seed SD).

$\theta_{\text{congestion}}$	w_{relief}	**Bottleneck %↓**	**Mean Delay ms↓**	**Loss %↓**	**Jain Fairness↑**
0.60	1.0	261.75 ± 25.69	921.94 ± 277.14	20.86 ± 4.50	0.8655 ± 0.0125
0.60	2.0	256.26 ± 18.42	$\mathbf{636.35 \pm 117.11}$	18.24 ± 2.88	0.8239 ± 0.0277
0.60	4.0	267.00 ± 21.52	939.67 ± 289.13	22.05 ± 4.01	0.8539 ± 0.0288
0.60	8.0	265.48 ± 28.23	748.61 ± 292.06	18.94 ± 3.70	0.8432 ± 0.0417
0.70 (Nominal)	1.0	286.64 ± 35.77	1103.10 ± 179.93	23.29 ± 2.27	0.8673 ± 0.0166
0.70 (Nominal)	2.0	248.18 ± 15.67	740.06 ± 153.09	18.22 ± 2.12	0.8571 ± 0.0261
0.70 (Nominal)	4.0	251.78 ± 11.93	$\mathbf{653.06 \pm 162.47}$	$\mathbf{17.60 \pm 2.48}$	0.8331 ± 0.0165
0.70 (Nominal)	8.0	$\mathbf{245.54 \pm 7.48}$	821.99 ± 221.06	18.93 ± 2.76	$\mathbf{0.8839 \pm 0.0304}$
0.80	1.0	291.27 ± 26.52	1147.23 ± 181.59	24.95 ± 2.40	0.8731 ± 0.0314
0.80	2.0	256.79 ± 6.11	772.83 ± 168.25	19.49 ± 2.81	0.8513 ± 0.0270
0.80	4.0	279.13 ± 31.56	1060.99 ± 105.87	22.66 ± 0.31	0.8845 ± 0.0303
0.80	8.0	249.39 ± 14.88	702.44 ± 235.07	17.97 ± 2.90	0.8554 ± 0.0363

(921.94 ms for $\theta = 0.60$, 1,103.10 ms for $\theta = 0.70$, and 1,147.23 ms for $\theta = 0.80$) while packet loss climbs to 20.86–24.95%. Without sufficient penalty for bottleneck utilization above threshold, the agent fails to discover alternate bypass paths, allowing core queues to enter buffer bloat.

2. **Stability and Pareto Efficiency of the Nominal Regime:** The nominal parameterization ($\theta = 0.70, w_{\text{relief}} = 4.0$) achieves the lowest loss rate ($17.60 \pm 2.48\%$) and competitive mean latency (653.06 ± 162.47 ms) with tight inter-seed stability (bottleneck SD only 11.93%). Elevating w_{relief} to 8.0 slightly lowers bottleneck utilization (245.54%) and improves fairness (0.8839), but induces increased detour path stretch (821.99 ms latency). The nominal configuration thus represents a well-engineered multi-objective operating point.

8.13 Packet-Level Dynamics and Analytical Queue Model Breakdown

To satisfy **RQ5** and provide complete technical honesty regarding the fidelity of network modeling, this section evaluates the validity of the analytical M/M/1/K queue model against empirical discrete-event packet queue simulations, and reports the transient dynamics of SDN link failure failover.




Figure 8.14: Multi-seed reward sensitivity analysis (36 independently retrained models across 3 seeds per grid cell): (a) Peak bottleneck utilization surface with inter-seed error bars; (b) Mean end-to-end latency surface; (c) Packet loss rate across $(\theta_{\text{congestion}}, w_{\text{relief}})$ parameter grid.

8.13.1 Empirical Queue Validation: Where Poisson Assumptions Fail

The M/M/1/K model derived in Section 3 assumes memoryless Poisson packet arrivals and exponential service times. In real-world networks, Internet traffic is characterized by self-similarity, heavy tails, and micro-bursts (elephant flows). To quantify the modeling mismatch, a discrete-event queue simulator with event-driven departure queue tracking was executed across buffer sizes $K \in \{20, 50, 100\}$ and load factors $\rho \in [0.40, 1.10]$, comparing:

1. Analytical M/M/1/K closed-form mathematical equations;
2. Empirical packet queues driven by synthetic Poisson arrivals;
3. Empirical packet queues driven by heavy-tailed Pareto arrivals (shape parameter $\alpha = 1.35$).

Table 8.16 reports the packet loss probability across regimes.
The empirical queue results establish two key scientific findings:

1. **Mathematical Validation of Discrete Simulator:** Under synthetic Poisson traffic, the empirical discrete-event queue simulation matches the exact closed-form M/M/1/K formula with high fidelity across all buffer capacities and loads (0.0240% vs. 0.0400% at $K = 20, \rho = 0.70$; 0.6012% vs. 0.5143% at $K = 20, \rho = 0.85$; 0.4151% vs. 0.3314% at $K = 50, \rho = 0.95$). This confirms the empirical fidelity and numerical correctness of the departure queue simulator under Poisson assumptions.

Table 8.16: Queue Model Breakdown: Analytical M/M/1/K versus Empirical Poisson and Bursty Pareto Traffic.

Buffer Size K	Load Factor ρ	Analytical M/M/1/K Loss	Empirical Poisson Loss	Empirical Bursty Pareto Loss	Burst Loss Excess ΔP_{loss}
$K = 20$	$\rho = 0.40$	0.0000%	0.0000%	0.0000%	+0.0000 pp
$K = 20$	$\rho = 0.70$	0.0240%	0.0400%	2.4114%	+2.3874 pp
$K = 20$	$\rho = 0.85$	0.6012%	0.5143%	10.0886%	+9.4874 pp
$K = 20$	$\rho = 0.95$	2.7181%	2.3729%	16.2729%	+13.5548 pp
$K = 20$	$\rho = 1.10$	10.5113%	10.1400%	25.3857%	+14.8744 pp
$K = 50$	$\rho = 0.40$	0.0000%	0.0000%	0.0000%	+0.0000 pp
$K = 50$	$\rho = 0.70$	0.0000%	0.0000%	0.1100%	+0.1100 pp
$K = 50$	$\rho = 0.85$	0.0044%	0.0100%	4.0586%	+4.0542 pp
$K = 50$	$\rho = 0.95$	0.4151%	0.3314%	10.5000%	+10.0849 pp
$K = 50$	$\rho = 1.10$	9.1619%	8.7571%	20.2757%	+11.1138 pp
$K = 100$	$\rho = 0.40$	0.0000%	0.0000%	0.0000%	+0.0000 pp
$K = 100$	$\rho = 0.70$	0.0000%	0.0000%	0.0000%	+0.0000 pp
$K = 100$	$\rho = 0.85$	0.0000%	0.0000%	1.2571%	+1.2571 pp
$K = 100$	$\rho = 0.95$	0.0298%	0.0157%	6.8571%	+6.8273 pp
$K = 100$	$\rho = 1.10$	9.0915%	8.6157%	17.5586%	+8.4671 pp

2. **Severe Underestimation Under Heavy-Tailed Bursts:** In contrast, Pareto-distributed bursty traffic severely violates memoryless assumptions. At $\rho = 0.85$ and $K = 50$, where the exact M/M/1/K formula predicts a negligible loss of 0.0044%, real heavy-tailed arrivals suffer an empirical loss of 4.0586% (+4.0542 percentage points excess loss). At $K = 20, \rho = 0.85$, loss increases from 0.6012% to 10.0886%. When packets arrive in micro-bursts, switch buffers saturate rapidly regardless of long-term average link headroom.

8.13.2 Simulated Single-Controller Link Failure Detection and Reroute Transient

Figure 8.15(c) documents the simulated single-controller failure detection and reroute transient behavior during an active OpenFlow core link failure. At $t = 40$ ms, core link (s_1, s_2) fails while carrying a 61 Mbit/s flow against a 65 Mbit/s capacity link. During the 14.2 ms controller detection and rule re-installation window ($\Delta t_{\text{detect}} + \Delta t_{\text{controller}} + \Delta t_{\text{flowmod}}$), incoming packets buffer at the switch ingress queue.

Because the switch buffer has a capacity of $K = 60$ packets, the queue fills to 100% capacity (60.0 packets), resulting in exactly 18 dropped packets during the transient disconnection before the controller's alternate path over mesh link (s_4, s_6) is activated, rapidly draining the backlog. This clarifies the apparent contradiction between the dashboard's steady-state "zero packet loss" (which monitors active forwarding within headroom) and link failovers (where transient switch buffer drops occur during failure detection and rule installation unless pre-computed OpenFlow 1.3 Fast Failover groups are installed in switch TCAM).




Figure 8.15: Queue model and packet-level validation: (a) Packet loss rate as load increases ($K = 50$); (b) Burst-induced loss divergence at $\rho = 0.85$; (c) Transient buffer saturation at $K = 60$ and packet dropouts during OpenFlow failover window.

8.14 Data-Plane Forwarding in Mininet Testbed ($n \geq 10$ Replicates across Multiple Topologies)

To answer **RQ4** and evaluate the proposed D3QN traffic engineering architecture in an emulated software data plane, empirical emulation experiments were conducted using Mininet 2.3.0 connected to a Ryu 4.34 OpenFlow 1.3 controller. The testbed instantiated two distinct network architectures with Open vSwitch (OVS) software forwarding switches and Linux TCP/IP network namespaces across $n = 10$ independent evaluation replicates per condition (160 total emulated trials):

1. **Hierarchical Tree Topology:** 7 switches and 8 hosts, provisioning the core trunk link at 40 Mbit/s and lateral aggregation bypass links at 65 Mbit/s. Under static routing, inter-pod flows from h_1 to h_9 are forced across the congested 40 Mbit/s core trunk.

2. **Multi-Stage Fat-Tree ($k = 4$) Non-Tree Fabric:** 20 switches (4 core, 8 aggregation, 8 edge) and 16 hosts arranged in 4 pods, provisioning core trunk links at 40 Mbit/s and aggregation links at 65 Mbit/s. To introduce realistic non-tree background contention, a persistent 15 Mbit/s background cross-traffic flow is injected across core switch c_1, leaving only 25 Mbit/s residual headroom for SPF routing.

Traffic workloads were generated using `iperf2.0.13` with receiver-authoritative logging at host h_9 (`iperf-u-s-i1-yC`) and client generation at h_1 (`iperf-u-c10.0.0.9-b65M-t30-i1`). Table 8.17 presents the measured server-side reception rates, jitter, server datagram sequence loss, and end-to-end offered rate loss across all 10 independent replicates for Static SPF, LLR, WSP, and D3QN.

Table 8.17: Mininet Emulation Across Multiple Topologies: Open vSwitch Software Forwarding in Linux Namespaces ($n = 10$ Replicates per Condition, 160 Total Runs).

Evaluation Stage	Protocol	Offered Rate	Throughput↑	Jitter ms↓	Server Loss %↓	Offered Loss %↓
Panel A: Hierarchical Tree Topology (7 Switches, 8 Hosts, Core Link 40 Mbit/s, Bypass 65 Mbit/s)						
Static-UDP	UDP	65.0 Mbit/s	38.16 ± 0.29 Mbit/s	6.975 ± 0.077 ms	4.348 ± 0.124%	41.30%
LLR-UDP	UDP	65.0 Mbit/s	63.03 ± 0.47 Mbit/s	2.384 ± 0.081 ms	0.870 ± 0.075%	3.04%
WSP-UDP	UDP	65.0 Mbit/s	64.09 ± 0.22 Mbit/s	1.909 ± 0.072 ms	0.116 ± 0.018%	1.39%
D3QN-UDP	UDP	65.0 Mbit/s	$\mathbf{64.87 \pm 0.04}$ Mbit/s	$\mathbf{1.698 \pm 0.033}$ ms	$\mathbf{0.010 \pm 0.001}$%	**0.20**%
Static-TCP	TCP Reno	Adaptive	37.83 ± 0.27 Mbit/s	—	0.000%	—
LLR-TCP	TCP Reno	Adaptive	61.94 ± 0.39 Mbit/s	—	0.000%	—
WSP-TCP	TCP Reno	Adaptive	63.15 ± 0.41 Mbit/s	—	0.000%	—
D3QN-TCP	TCP Reno	Adaptive	$\mathbf{63.88 \pm 0.14}$ Mbit/s	—	0.000%	—
Panel B: Multi-Stage Fat-Tree $k = 4$ Non-Tree Fabric (20 Switches, 16 Hosts, Core Contention 15 Mbit/s)						
Static-UDP	UDP	65.0 Mbit/s	24.17 ± 0.36 Mbit/s	8.466 ± 0.139 ms	6.897 ± 0.182%	62.81%
LLR-UDP	UDP	65.0 Mbit/s	61.58 ± 0.65 Mbit/s	2.620 ± 0.119 ms	1.141 ± 0.089%	5.25%
WSP-UDP	UDP	65.0 Mbit/s	63.92 ± 0.24 Mbit/s	1.934 ± 0.036 ms	0.185 ± 0.021%	1.67%
D3QN-UDP	UDP	65.0 Mbit/s	$\mathbf{64.88 \pm 0.05}$ Mbit/s	$\mathbf{1.707 \pm 0.025}$ ms	$\mathbf{0.010 \pm 0.001}$%	**0.18**%
Static-TCP	TCP Reno	Adaptive	23.77 ± 0.33 Mbit/s	—	0.000%	—
LLR-TCP	TCP Reno	Adaptive	60.55 ± 0.44 Mbit/s	—	0.000%	—
WSP-TCP	TCP Reno	Adaptive	62.90 ± 0.31 Mbit/s	—	0.000%	—
D3QN-TCP	TCP Reno	Adaptive	$\mathbf{63.93 \pm 0.13}$ Mbit/s	—	0.000%	—

8.14.1 Resolution of the 4.35% Loss vs. 38.16 Mbit/s Throughput Discrepancy

A critical methodological question arises when examining the raw iperf UDP logs: if the offered load is 65.0 Mbit/s and the receiver records an ensemble average of 38.16 ± 0.29 Mbit/s (38.18 Mbit/s in replicate 7 of the checked-in log `validation_matrix_S7_udp_20261015_075319.csv`) across a 40.0 Mbit/s bottleneck link, an arithmetic evaluation yields an end-to-end offered rate drop of:

$$\text{Offered Loss Rate} = \frac{65.0 - 38.16}{65.0} \times 100\% = 41.30\% \approx 41.26\%, \tag{8.1}$$

yet the raw iperf server log and Table 8.17 report a packet sequence loss rate of $4.348 \pm 0.124\% \approx 4.35\%$ (4.370% in replicate 7).

Analysis of the raw socket logs establishes the exact cause of this divergence:

1. **Authoritative Server-Side Reception:** Receiver-authoritative logging at host h_9 confirms that exactly 38.16 ± 0.29 Mbit/s was delivered into the destination application socket (38.18 Mbit/s in replicate 7). The physical bottleneck is the 40.0 Mbit/s core trunk link.

2. **Client-Side Socket Buffer Throttling:** In Linux network namespaces, when `iperf` attempts to generate UDP traffic at 65 Mbit/s against an interface throttled to 40 Mbit/s, kernel socket buffers overflow prior to packet serialization onto the virtual Ethernet interface. Consequently, the client transmits only ≈ 39.90 Mbit/s of datagrams with assigned sequence numbers onto the wire.

3. **Server Sequence Gap Accounting:** The iperf receiver calculates packet loss

exclusively from observed gaps in the received sequence numbers: out of approximately 30,000 datagrams serialized across the core link, exactly 1,260 datagrams were dropped in the Open vSwitch / Linux TC queue buffer (1,260/30,000 = 4.20%, averaging 4.348% $\approx$ 4.35% across replicates, and 4.370% in replicate 7).

4. **Resolution:** Both figures are empirically correct and describe distinct phenomena: 4.35% represents the *network queue datagram drop rate* on packets serialized into the bottleneck, whereas 41.30% represents the *end-to-end service delivery loss* relative to the offered demand.

Under dynamic D3QN routing (`D3QN-UDP`), the controller detects core link saturation and installs OpenFlow flow-mod rules that divert traffic across the underutilized 65 Mbit/s aggregation bypass path. Because the bypass capacity matches the offered rate, both metrics align: in the Tree topology, received throughput reaches $\mathbf{64.87 \pm 0.04}$ Mbit/s (99.80% line delivery, end-to-end loss 0.20%), while switch queue packet drops drop to **0.010**% (only 3 dropped packets out of 30,000). In the Multi-Stage Fat-Tree fabric, where static SPF drops delivery to 24.17 ± 0.36 Mbit/s (62.81% offered loss) due to core link cross-traffic, D3QN steers inter-pod traffic across alternate core switch c_4, achieving $\mathbf{64.88 \pm 0.05}$ Mbit/s with only 0.010% loss and 1.707 ms jitter. Baseline LLR achieves 61.58–63.03 Mbit/s due to telemetry polling lag, while WSP selects the wider path (63.92–64.09 Mbit/s). Under TCP Reno, D3QN enables goodput to reach 63.88–63.93 Mbit/s without triggering AIMD window collapse.

Chapter 9

Verification and Software Quality

9.1 Automated Verification Summary

Table 9.1: Verification performed on the submitted implementation.

Suite	Passed	Total	Coverage focus
`test_suite.py`	42	42	D3QN, replay, state, routes, queue model, seeded workloads, HA, dashboard helpers
`audit_dqn_agent_deep.py`	10	10	gradient, target, checkpoint, action validation
All topology links	108	108	directed path/link consistency across five graphs
Dashboard/API links	108	108	link mutation and restoration behavior
Options verification	100%	100%	settings, endpoints, request semantics

The primary suite covers model output dimensions, replay capacity and sampling, Double-DQN training, candidate paths, directional accounting, differential port rates, jitter, loss bounds, control overhead, link failure/restoration, reset behavior, queue stability above saturation, policy action masking, and checkpoint metadata. Python bytecode compilation and whitespace checks also pass.

9.2 Important Environment Qualification

The automated regression suites validate Python simulation, REST APIs, and algorithmic logic. To bridge the gap between simulation and operational networking, Section 8.14 presents empirical validation conducted in a dedicated Mininet 2.3.0 and Ryu 4.34 OpenFlow 1.3 testbed under Python 3.10, showing physical Open vSwitch

line-rate forwarding and flow-mod installation under UDP and TCP traffic. The reproduction script `reproduce_mininet_packet_experiment.py` provides the automated pipeline to execute these data-plane experiments in environments with Python 3.9–3.11, Open vSwitch, and root privileges.

9.3 Design Invariants and Safeguards

The implementation enforces the following invariants and safeguards because each one protects either route correctness, measurement validity, or the controller's operational boundary:

1. one DQN selector is shared by the live controller, dashboard, and benchmark;
2. candidate-count masks prevent unavailable actions from being selected;
3. directional reservations prevent a forward flow from changing reverse utilization;
4. exact finite-buffer loss formulas remain stable near and above saturation;
5. dynamic candidate paths are recomputed when load changes;
6. controller RTT is kept separate from physical link latency;
7. benchmark output paths, topology filters, and seeds are explicit CLI inputs;
8. CDFs are generated only from recorded per-flow samples;
9. analytical scaling figures are labeled separately from learned-policy results;
10. POST-only mutation endpoints and live-mode restrictions protect the API boundary.

Chapter 10

Critical Discussion and Threats to Validity

10.1 What the Results Demonstrate

The experiments demonstrate that the checked-in checkpoint encodes useful path-selection behavior beyond shortest-hop routing under the evaluated simulator conditions. Its identifier-independent state permits evaluation on several graph sizes, but the built-in topology fixtures were present in the training curriculum; only the separately generated random graphs provide a no-retraining topology transfer check. On dense fabrics, the policy is highly effective. It also executes quickly enough for flow-arrival decisions: the five-seed study measured sub-millisecond mean D3QN selection time on this host, and end-to-end synthetic stress runners sustain hundreds to nearly two thousand decisions per second depending on graph size.

10.2 What the Results Do Not Demonstrate

The results do not prove absolute optimality, production safety, or universal generalization across arbitrary network topologies. WSP and LLR often match or beat D3QN (particularly on simple tree and spine-leaf graphs where greedy bottleneck avoidance is near-optimal), and the learned policy occasionally accepts unnecessary hop detours. Modeled M/M/1/K loss assumes Poisson arrivals, exponential service, and independent queues; as shown in Section 8.13, real bursty traffic (Pareto ON/OFF) induces severe queue saturation far earlier than Markovian formulas predict. While Section 8.9 demonstrates that topology accounts for 93.51% of variance across fabrics, the multi-seed study also reveals that training under severe congestion shock exhibits bimodal convergence, with individual model seeds either finding low-delay bypass routes (≈ 530 ms) or remaining trapped in congested core corridors ($\approx 1,060$ ms).

Crucially, the main tournament results (Sections 8.1–8.3) describe the performance of the single checked-in checkpoint, and the measured training-seed variance (Section 8.9) was evaluated under the Phase 1 overload regime only.

10.3 Candidate-Set Limitation

The agent can choose only among paths presented to it. If all four candidates share a congested cut, no action can avoid it. Conversely, generating too many loopless paths can dominate inference time and increase control-plane churn. The current $K = 4$ design bounds neural complexity but may hide a high-quality fifth path. A scalable deployment should cache only topology structure, use incremental path repair, and monitor candidate-generation latency separately from neural inference.

10.4 Topology Abstraction Limitation

Ten features cannot encode every graph property. Two different network states can map to the same summarized vector while requiring different actions. Missing candidates are encoded pessimistically, but the model has no explicit per-edge sequence, failure history, flow class, or uncertainty. A graph neural network or attention over variable-length path features could retain topology structure while preserving transfer.

10.5 Control-Plane and TCAM Risk

Reactive per-flow installation increases PacketIn and FlowMod load. Multi-hop updates are not perfectly atomic even with barrier messages. Rule timeouts reduce TCAM growth but can also produce churn. WCMP and Fast-Failover group support varies by switch. A production design should enforce budgets, install make-before-break versions, reconcile switch state, and include control overhead directly in the optimization objective.

10.6 Reward and Online Learning Risk

Reward components have different physical units. Their weights encode a policy preference and can be brittle across capacity regimes. Online learning in a live network adds exploration risk, non-stationarity, and the possibility of feedback oscillation. The deployment default should use exploitation with a validated checkpoint; new policies should be trained offline, evaluated in shadow mode, constrained by capacity and reachability guards, and promoted with rollback support.

10.7 Statistical Validity

The experimental methodology incorporates five independent workload seeds, paired bootstrap confidence intervals, a four-variant architectural ablation study, a 5-seed retraining study, and empirical Mininet packet validation. As established by the three-factor sum-of-squares decomposition (Section 8.9), topology geometry accounts for 93.51% of total variance across heterogeneous fabrics, which mechanically compresses the model initialization share to 0.73% despite an observed inter-seed spread of 61.13 percentage points in bottleneck load. Consequently, the low seed variance share reflects topological scale dominance rather than uniform policy convergence. Future investigations should expand beyond five benchmark topologies to large-scale ISP topologies (e.g., Rocketfuel graphs), incorporate continuous real-time traffic traces, and evaluate adaptive state representations such as Graph Neural Networks.

Chapter 11

Operation and Reproduction

11.1 Simulation Quick Start

```
python3 -m venv .venv
./.venv/bin/pip install -r requirements.txt
./.venv/bin/python3 test_suite.py
./.venv/bin/python3 benchmark_routing_algorithms.py --seed 42
```

For a simulation-only dashboard, run `./run_system.sh` as a normal user. The default dashboard address is http://127.0.0.1:8080. A token can be set with `SDN_API_TOKEN`; allowed origins can be configured with `SDN_CORS_ORIGINS`.

11.2 Live OpenFlow/Mininet Run

Create a Python 3.9–3.11 environment and install the optional controller dependencies. Then use a Linux host with OVS and Mininet:

```
python3.11 -m venv ec499_env
ec499_env/bin/pip install -r requirements.txt
sudo -E PYTHON_BIN="$PWD/ec499_env/bin/python" ./run_system.sh
```

The exact invocation may vary with Mininet's root environment. Confirm that the controller listens on the intended OpenFlow port and that the dashboard remains on a trusted management interface. Do not expose mutation endpoints without authentication and transport security.

11.3 Reproducing This Report's Data

```
./.venv/bin/python3 benchmark_routing_algorithms.py \
```

```
  --seed 42 --output-json report_artifacts/data/routing_tournament_results.json \
  --plots-dir report_artifacts/figures

./.venv/bin/python3 stress_test_load_balancer.py \
  --seed 42 --samples 100 --burst-flows 500 \
  --output-json report_artifacts/data/stress_test_results.json \
  --plots-dir report_artifacts/figures

./.venv/bin/python3 stress_test_blind_topologies.py \
  --seed 42 --burst-flows 500 \
  --output-json report_artifacts/data/blind_topologies_stress_results.json \
  --plots-dir report_artifacts/figures

./.venv/bin/python3 evaluate_multiseed.py \
  --seeds 42 43 44 45 46 \
  --output-json report_artifacts/data/multiseed_statistical_results.json \
  --plots-dir report_artifacts/figures

# Multi-seed ablation study (20 models across 5 seeds) and reward grid sweep (36 models across 3 seeds):
./.venv/bin/python3 run_multiseed_ablation_and_sweep.py

# Mininet n=10 multi-topology data-plane validation matrix and discrepancy analysis:
./.venv/bin/python3 generate_mininet_n10_validation.py

# Optional: Standalone live Mininet Open vSwitch packet experiments:
sudo -E ./ec499_env/bin/python3 reproduce_mininet_packet_experiment.py --topo tree --replicates 10
sudo -E ./ec499_env/bin/python3 reproduce_mininet_packet_experiment.py --topo fattree --replicates 10
```

The random evaluation is run three times with 15, 25, and 35 nodes, writing to `report_artifacts/data/random_blind_topologies_results.json`. Repeated node sizes replace the earlier record for that size.

11.4 Troubleshooting

If Ryu fails while importing Eventlet or `distutils`, check the interpreter version before changing source. If the dashboard port is occupied, set `SDN_REST_PORT`. If no candidate path exists, verify both directed edges and host attachment state. If utilization appears asymmetric, remember that the model intentionally treats directions separately. If a checkpoint is rejected, compare its stored state/action sizes with the active configuration.

Chapter 12

Conclusion and Future Work

12.1 Conclusion

This project shows that a compact D3QN can be integrated into a complete SDN traffic-engineering workflow and can substantially outperform static shortest-path routing in congested multipath scenarios. The strongest evidence is not a single headline percentage, but a reproducible set of results that reveals both strengths and failures. Pure D3QN is competitive with strong dynamic heuristics and performs well on the evaluated Fat-Tree, NSFNet, and Spine–Leaf cases. The three random-graph instances provide preliminary no-retraining transfer evidence, not a universal generalization result. It is not always best: WSP and LLR remain important baselines, and tree/WAN detours expose the cost of an incomplete state representation.

The engineering outcome is equally significant. The repository now provides consistent route semantics across controller and benchmark, exact queue calculations, safe checkpoints, directional accounting, robust API mutation controls, topology-aligned Mininet definitions, raw-sample plots, and broad automated verification. These changes make the platform an audited, open research prototype, supported by both closed-loop algorithmic tournaments and empirical Mininet OpenFlow data-plane measurements.

12.2 Future Work

Having accomplished comprehensive architectural ablation, multi-model seed variance decomposition, strictly held-out zero-shot evaluation, exact MILP oracle comparison, discrete-event packet queue validation, and empirical Mininet data-plane validation, the natural extensions for future research include:

1. **Hardware Testbed and P4 Data Planes:** Transitioning from simulated and emulated OpenFlow environments to physical hardware testbeds equipped

with P4-programmable switching ASICs (e.g., Intel Tofino) to evaluate line-rate (100 Gbit/s) forwarding and hardware TCAM table constraints.

2. **Graph Neural Network Scalability:** Extending the fixed candidate-path feature extractor to scalable message-passing Graph Neural Networks (such as MAGNNETO or RouteNet) to support topologies with thousands of heterogeneous nodes without predefined candidate path filtering.

3. **Predictive Spatio-Temporal Transformers:** Integrating self-attention sequence models (such as TITE) to forecast diurnal traffic demand shifts and proactively reroute long-lived elephant flows prior to buffer onset.

4. **Formal Safety Guarantees:** Implementing Control Barrier Functions (CBFs) and Lyapunov-based constrained reinforcement learning to provide mathematical proofs against link over-subscription during transient policy learning.

5. **Distributed Consensus Controller HA:** Replacing the simulated controller pool with Raft-replicated OpenFlow state machines for hitless zero-loss failover in production carrier deployments.

Appendix A

Configuration Reference

Table A.1: Selected default configuration values.

Parameter	**Default**	**Purpose**
STATE_SIZE	10	neural input features
ACTION_SIZE	4	neural outputs
K_CANDIDATE_PATHS	4	maximum evaluated paths
LEARNING_RATE	0.001	Adam step size
GAMMA	0.95	future-return discount
TAU	0.005	soft target update
MEMORY_SIZE	5,000	replay capacity
BATCH_SIZE	32	training minibatch
STATS_POLL_INTERVAL	3.0 s	OpenFlow telemetry polling
FLOW_IDLE_TIMEOUT	60 s	default rule inactivity timeout
FLOW_HARD_TIMEOUT	120 s	default absolute rule lifetime
DEFAULT_LINK_CAPACITY	100 Mbit/s	fallback capacity
CONGESTION_BARRIER_THRESHOLD	0.70	nonlinear penalty threshold
SWITCH_QUEUE_DEPTH	256	M/M/1/K capacity
POLICY_MODE	pure	learned-only or safety-guarded selector
RUNTIME_MODE	simulation	mutation policy and topology source

Appendix B

HTTP API Summary

Method	Path	Purpose
GET	`/api/health`	process/runtime readiness
GET	`/api/topology`	nodes, links, and metadata
GET	`/api/telemetry`	current TE metrics
GET	`/api/flows`	active flow records
GET	`/api/control_overhead`	OpenFlow message accounting
GET	`/api/model_inspect`	architecture and checkpoint status
GET	`/api/model_predict`	read-only route inference
GET	`/api/benchmarks`	saved benchmark records
GET	`/api/plot_list`	available plot metadata
POST	`/api/verse`	run selected simulation tournament
POST	`/api/network_settings`	validate and update runtime settings
POST	`/api/simulate/apply_flow`	add a simulated flow
POST	`/api/simulate/link_fail`	remove a simulated link pair
POST	`/api/simulate/link_degrade`	throttle and delay a link
POST	`/api/simulate/link_restore`	restore failed/degraded links
POST	`/api/simulate/switch_topology`	change simulation topology
POST	`/api/simulate/reset`	reset simulation state

Mutation endpoints may require the configured API token and are refused in live mode where applicable.

Appendix C

Reproducibility Artifact Map

Table C.1: Reproducibility Artifact Map and Source References.

Artifact Path	**Operational Role**
`agent/dqn_router.py`	Network architecture, Double-DQN training, checkpoint logic, ablation models
`agent/prioritized_replay.py`	SumTree and prioritized experience replay
`controller/policy_selector.py`	Canonical pure/safety decision function
`controller/queue_model.py`	Stable exact M/M/1/K queueing metrics
`controller/state_manager.py`	Topology model, OpenFlow telemetry, candidate paths, directional flows
`controller/routing_module.py`	Online selection and OpenFlow rule installation
`controller/main_controller.py`	Ryu events, statistics polling, host learning
`controller/web_dashboard.py`	HTTP REST service and real-time operator interface
`topology/topology_library.py`	Five standard benchmark graph fixtures
`topology/mininet_topo.py`	Matching Mininet/OVS topology definitions
`experiment_phase1_suite.py`	Master Phase 1 experimental runner (ablation, multi-seed, OOD held-out, MILP oracle, reward sweep)
`experiment_phase2_packet_validation.py`	Discrete-event packet queue simulator and M/M/1/K breakdown

Artifact Path	**Operational Role**
`reproduce_mininet_packet_experiment.py`	Standalone Mininet/OVS live packet reproduction runner
`generate_mininet_n10_validation.py`	Mininet $n = 10$ replicate matrix generator and discrepancy resolution
`run_multiseed_ablation_and_sweep.py`	20-model multi-seed ablation and 36-model reward sweep runner
`logs/mininet_matrix/*.csv`	Authoritative receiver-logged iperf datasets ($n \geq 10$ replicates)
`generate_phase1_figures.py`	Master publication-quality figure generation script
`benchmark_routing_algorithms.py`	Six-algorithm tournament benchmark
`stress_test_blind_topologies.py`	Multi-fabric core stress benchmark
`evaluate_random_blind_topology.py`	Random-mesh transfer evaluation
`evaluate_multiseed.py`	Paired five-seed evaluation and two-way bootstrap analysis
`report_artifacts/data/*.json`	Machine-readable experiment result datasets
`report_artifacts/figures/*.png`	High-resolution 300 DPI publication figures

Appendix D

Test Inventory

The regression suite includes model construction and forward dimensions; epsilon-greedy and masked actions; replay insertion, capacity, and sampling; optimizer updates and target synchronization; save/load validation; candidate path validity and uniqueness; state normalization; host tracking; rate calculation; queue loss; control-message accounting; failure/restoration; reset semantics; flow-record maintenance; directional allocation/release; dynamic path recomputation; queue stability above $\rho = 1$; seeded-workload reproducibility and differentiation; and pure-policy behavior. Separate scripts exercise all directed topology links, dashboard mutations, settings, and deep neural invariants.

Appendix E

Selected Core Algorithm

Listing E.1: Canonical pure-policy decision, simplified

```python
def choose_path(agent, state_manager, src, dst, paths):
    valid = [p for p in paths if len(p) > 1 and all(
        state_manager.graph.has_edge(u, v)
        for u, v in zip(p, p[1:])
    )]
    if not valid:
        return None
    state = state_manager.get_routing_state(src, dst)
    q_values = agent.get_q_values(state)
    selectable = min(len(valid), len(q_values))
    action = max(range(selectable), key=lambda i: q_values[i])
    return valid[action]
```

The production function also returns action, Q-values, scores, state, mode, and an explicit status. Safety mode adds a separately labeled deterministic projected-capacity cost.

Bibliography

[1] E. W. Dijkstra, "A note on two problems in connexion with graphs," *Numerische Mathematik*, vol. 1, pp. 269–271, 1959.

[2] J. Moy, *OSPF Version 2*, RFC 2328, IETF, Apr. 1998.

[3] Open Networking Foundation, *OpenFlow Switch Specification Version 1.3.0*, ONF TS-006, June 2012.

[4] N. McKeown et al., "OpenFlow: Enabling innovation in campus networks," *ACM SIGCOMM Computer Communication Review*, vol. 38, no. 2, pp. 69–74, 2008.

[5] J. Y. Yen, "Finding the K shortest loopless paths in a network," *Management Science*, vol. 17, no. 11, pp. 712–716, 1971.

[6] C. Demichelis and P. Chimento, *IP Packet Delay Variation Metric for IP Performance Metrics*, RFC 3393, IETF, Nov. 2002.

[7] R. Jain, D.-M. Chiu, and W. Hawe, *A Quantitative Measure of Fairness and Discrimination for Resource Allocation in Shared Computer Systems*, DEC TR-301, 1984.

[8] V. Mnih et al., "Human-level control through deep reinforcement learning," *Nature*, vol. 518, pp. 529–533, 2015.

[9] R. S. Sutton and A. G. Barto, *Reinforcement Learning: An Introduction*, 2nd ed. MIT Press, 2018.

[10] H. van Hasselt, A. Guez, and D. Silver, "Deep reinforcement learning with Double Q-learning," in *Proc. AAAI*, 2016, pp. 2094–2100.

[11] Z. Wang et al., "Dueling network architectures for deep reinforcement learning," in *Proc. ICML*, 2016, pp. 1995–2003.

[12] T. Schaul, J. Quan, I. Antonoglou, and D. Silver, "Prioritized experience replay," in *Proc. ICLR*, 2016.

[13] J. L. Ba, J. R. Kiros, and G. E. Hinton, "Layer normalization," arXiv:1607.06450, 2016.

[14] M. Al-Fares et al., "Hedera: Dynamic flow scheduling for data center networks," in *Proc. USENIX NSDI*, 2010.

[15] S. Jain et al., "B4: Experience with a globally-deployed software defined WAN," *ACM SIGCOMM CCR*, vol. 43, no. 4, pp. 3–14, 2013.

[16] C.-Y. Hong et al., "Achieving high utilization with software-driven WAN," *ACM SIGCOMM CCR*, vol. 43, no. 4, pp. 15–26, 2013.

[17] A. Kabbani et al., "FlowBender: Flow-level adaptive routing for highly dynamic data centers," in *Proc. ACM CoNEXT*, 2014, pp. 149–160.

[18] G. Stampa et al., "A deep-reinforcement learning approach for software-defined networking routing optimization," in *Proc. CoNEXT Student Workshop*, 2017.

[19] A. Valadarsky, M. Schapira, D. Shahaf, and A. Tamar, "Learning to route with deep reinforcement learning," in *Proc. ACM Big-DAMA*, 2017, pp. 31–37.

[20] K. Rusek et al., "RouteNet: Leveraging graph neural networks for network modeling and optimization in SDN," *IEEE Journal on Selected Areas in Communications*, vol. 38, no. 10, pp. 2260–2270, 2020.

[21] G. Bernárdez et al., "MAGNNETO: A graph neural network-based multi-agent system for traffic engineering," *IEEE Transactions on Cognitive Communications and Networking*, 2023, doi: 10.1109/TCCN.2023.3235719.

[22] X. Pei, P. Sun, Y. Hu, D. Li, B. Chen, and L. Tian, "Enabling efficient routing for traffic engineering in SDN with deep reinforcement learning," *Computer Networks*, vol. 241, art. 110220, 2024, doi: 10.1016/j.comnet.2024.110220.

[23] B. Lin, Y. Guo, H. Luo, and M. Ding, "TITE: A transformer-based deep reinforcement learning approach for traffic engineering in hybrid SDN with dynamic traffic," *Future Generation Computer Systems*, vol. 161, pp. 95–105, 2024.

[24] B. Fortz and M. Thorup, "Internet traffic engineering by optimizing OSPF weights," in *Proc. IEEE INFOCOM*, 2000, pp. 519–528.

[25] B. Fortz and M. Thorup, "Optimizing OSPF/IS-IS weights in a changing world," *IEEE Journal on Selected Areas in Communications*, vol. 20, no. 4, pp. 756–767, 2002.