

9-PIN WIDE CARRIAGE IMPACT PRINTER

LX-1170II

EPSON
EXCEED YOUR VISION



The Versatile Data Reporter

- Improved processing speed with a 64KB Input Data Buffer
- Fast print speed of up to 337 Characters Per Second (12 CPI)
- Achieve optimum efficiency with 5 Part Forms printout (1 original + 4 copies)
- Greater connectivity with built-in USB, Serial and Parallel Interface options
- Choice of 8 Built-in Bar Code formats for maximum versatility

SPECIFICATIONS

Weight – approx. 6.6 kg



OPTIONS

FABRIC RIBBON CARTRIDGE (BLACK)
FABRIC RIBBON PACK (BLACK)
SINGLE BIN CUT SHEET FEEDER
PULL TRACTOR UNIT
ROLL PAPER HOLDER

9-PIN WIDE CARRIAGE IMPACT PRINTER

LX-1170 II

PRINT DIRECTION			Bi-directional with logic seeking
PRINT SPEED	HIGH SPEED DRAFT HIGH SPEED DRAFT CONDENSED DRAFT DRAFT CONDENSED NLQ	10/12/15 CPI 17/20 CPI 10/12/15 CPI 17/20 CPI 10/12/15/17/20 CPI	300/337/337 cps 321/300 cps 225/270/225 cps 191/225 cps 56/67/56/47/56 cps
PRINT CHARACTERISTICS	CHARACTER SETS BITMAP FONTS BAR CODE FONT	13 International character sets; 13 character code tables (Standard); Italic, PC437, PC850, PC860, PC861, PC863, PC865, Abicomp, BRASCI, Roman 8, ISO Latin 1, PC858, ISO 8859-15 Epson Draft: 10, 12, 15 CPI; Epson Roman and Sans Serif: 10, 12, 15 CPI, Proportional EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, PostNet	
PRINTABLE COLUMNS	PITCH(CPI) 10 CPI 12 CPI 15 CPI 17 CPI CONDENSED 20 CPI CONDENSED		Character per line 136 163 204 233 272
PAPER HANDLING			
PAPER PATH	MANUAL INSERTION: PUSH TRACTOR: PULL TRACTOR: CUT SHEET FEEDER:		Rear in, Top out Rear in, Top out Rear/Bottom in, Top out Rear in, Top out
PAPER SIZE CUT SHEET	MANUAL INSERTION	Width: Length: Thickness:	148 ~ 420 mm (5.8 ~ 16.5") 100 ~ 364 mm (3.9 ~ 14.3") 0.065 ~ 0.14 mm (0.0025 ~ 0.0055")
	CSF SINGLE-BIN	Width: Length: Thickness:	182 ~ 420 mm (7.2 ~ 16.5") 210 ~ 364 mm (8.3 ~ 14.3") 0.07 ~ 0.14 mm (0.0028 ~ 0.0055")
	MULTI PART	Width: Length: Thickness:	148 ~ 420 mm (5.8 ~ 16.5") 100 ~ 364 mm (3.9 ~ 14.3") 0.12 ~ 0.39 mm (0.0047 ~ 0.015") (Total)
ENVELOPE	No. 6	Width: Length: Thickness:	165 mm (6.5") 92 mm (3.6") 0.16 ~ 0.52 mm (0.0063 ~ 0.0205") (Total)
	No. 10	Width: Length: Thickness:	241 mm (9.5") 105 mm (4.1") 0.16 ~ 0.52 mm (0.0063 ~ 0.0205") (Total)
CONTINUOUS PAPER		Width: Length: Thickness:	101.6 ~ 406.4 mm (4.0 ~ 16.0") 101.6 ~ 558.8 mm (4.0 ~ 22.0") 0.065 ~ 0.39 mm (0.0025 ~ 0.015") (Total)
LABEL		Width: Length: Thickness:	101.6 ~ 406.4 mm (4.0 ~ 16.0") 101.6 ~ 558.8 mm (4.0 ~ 22.0") 0.07 ~ 0.09 mm (0.0028 ~ 0.0035") (Base) 0.16 ~ 0.19 mm (0.0063 ~ 0.0075") (Total)
ROLL PAPER		Width: Length: Thickness:	216 mm (8.5") — 0.07 ~ 0.09 mm (0.0028 ~ 0.0035")
PAPER FEEDING	STANDARD	Friction: Push Tractor: Pull Tractor:	Rear in, Top out Rear in, Top out Rear/Bottom in, Top out
	OPTIONAL	Cut Sheet Feeder: Push-Pull Tractor:	Rear in, Top out Rear in, Top out Original + 4 copies
COPIES LINE SPACING			1/6 inch or programmable by 1/216 inch
INPUT DATA BUFFER			64 KByte
INTERFACE	STANDARD		Bi-directional parallel interface (IEEE-1284 nibble mode supported); Serial interface; USB interface (ver1.1)
RIBBON CARTRIDGE	STANDARD	FABRIC RIBBON CARTRIDGE (BLACK)	RIBBON LIFE: Approx. 3 million characters (Draft 10 CPI, 14 dots/character)
ACOUSTIC NOISE			Approx. 49dB (A) (ISO 7779 pattern) Approx. 55dB (A) (ISO 7779 pattern) only for India model
RELIABILITY	MVBF (Mean Print Volume Between Failure) MTBF (Mean Time Between Failure) PRINT HEAD LIFE		12 million lines (Except print head) 6000 POH (25% duty cycle) Approx. 400 million strokes/wire
CONTROL PANEL			4 switches, 4 LEDs
ENVIRONMENTAL CONDITIONS (OPERATING)	TEMPERATURE HUMIDITY		5 ~ 35 °C 10 ~ 80 % RH
ELECTRICAL SPECIFICATIONS	RATED VOLTAGE RATED FREQUENCY POWER CONSUMPTION		AC 120 V, AC 220 ~ 240 V 50 ~ 60 Hz Approx. 23 W (ISO/IEC 10561 Letter Pattern); ENERGY STAR compliant
DIMENSIONS (D X W X H)			275 x 546 x 164 mm
WEIGHT			Approx. 6.6 kg
PRINTER DRIVER /UTILITY	OS UTILITY		Microsoft® Windows® 98/2000/Me/XP and Microsoft® Windows® NT® 4.0 Epson Status Monitor 3(Microsoft® Windows® 98/2000/Me/XP and Microsoft® Windows® NT® 4.0 environment only)

Epson is the registered trademark of SEIKO EPSON CORPORATION.

All other product names and other company names used herein are for identification purposes only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Scan/Print samples shown herein are simulations. Specifications are subject to change without notice.

EPSON
EXCEED YOUR VISION

INDIA – (91) 80-305-15000, CALCUTTA – 228 31589/90,
CHENNAI – 302 77500, MUMBAI – 282 61515/16/17, NEW DELHI – 306 15000
INDONESIA – (62) 21-572-3161
MALAYSIA – (60) 3-562-88288
PHILIPPINES – (632) 813-6567
SINGAPORE – (65) 6586-5500, (65) 6586-3111
THAILAND / INDOCHINA – (662) 670-0680

Dealer's Stamp