

P-335WT

Wireless Firewall Router with Print Server

Double Speed Double Security

Enabling the ZyXEL Wireless g+ SuperSpeed technology, the P-335WT boosts the connection speed between routers and notebooks to an astounding *125Mbps.

Sharing Wireless connectivity and printing resource on a protected Home Network with its unlimited freedom.

Benefits

The True 5-in-1 Wireless Firewall Router

ZyXEL P-335WT Firewall Router integrates everything you need to surf the Internet at home: router, switch, print server, firewall, and even the 802.11g Wireless AP.

When enabling ZyXEL Wireless g+ SuperSpeed technology, the ZyXEL P-335WT boosts the wireless connection speed between routers and notebooks to an astounding *125Mbps, as opposed to the standard 54Mbps speed of 802.11g and 11Mbps speed of 802.11b.

Sharing Internet Connectivity and Printing Resource

And a built-in USB print server allows you to share a printer on the network without leaving a host PC on. With four auto-sensing, switched LAN ports and Network Address Translation (NAT) routing, as many as home LAN users can access one broadband connection at the same time.

Double Protecting Your Home Network

This fully equipped, broadband-capable device is a true firewall with the utmost in business class security - Denial of Service (DoS) protection and Intrusion Detection using Stateful Packet Inspection (SPI), URL access and content filtering, logging, reporting, real-time alerts; in addition to VPN pass-through that maximizes network security.

The TMSS featured from Trend Micro, the leading software security solution provider, provides additional protection such as antivirus and parental control to protect and monitor computer usage as they access the Internet securely.

Specification

System Specifications

Standard

- IEEE 802.3 and 802.3u 10Based-T and 100Based-TX
- IEEE 802.11g

Memory size

4MB Flash, 16MB DRAM

System Requirement

- Broadband (cable, DSL, satellite or wireless) Internet service and modem with Ethernet
- Ethernet connection (adapter or cable)
- Windows, Mac or Linux based operating system
- Internet Explorer 5.0 or later

Physical Specifications

Interface

- LAN: Four 10/100Base-T Ethernet, full duplex RJ-45 connector with auto MDI/MDIX support.
- WAN: One 10/100Base-T Ethernet, full duplex RJ-45 connector with auto MDI/MDIX support.
- One USB 1.1 Printer Port
- Power Supply: 12V AC, 1 A
- Reset Button
- OTIST Stick Out Button
- RJ-45 connector

Dimensions

• 190(W) x 150(D) x 32(H) mm

Weight

• 424.4g

Environmental Specifications

Operating environment

- Temperature: 0°C ~ 50°C
- Humidity: 20% ~ 95% (non-condensing)

Storage environment

- Temperature: -30°C ~ 60°C
- Humidity: 20% ~ 95%