

Python Dictionaries

Dictionary

A dictionary is a collection which is unordered, changeable and indexed. In Python dictionaries are written with curly brackets, and they have keys and values pair.

Example

Create and print a dictionary:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
print(thisdict)
```

Accessing Items

You can access the items of a dictionary by referring to its key name, inside square brackets:

Example

Get the value of the "model" key:

```
x = thisdict["model"]
```

There is also a method called **get()** that will give you the same result:

Example

Get the value of the "model" key:

```
x = thisdict.get("model")
```

Change Values

You can change the value of a specific item by referring to its key name:

Example

Change the "year" to 2018:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
thisdict["year"] = 2018
```

Loop Through a Dictionary

You can loop through a dictionary by using a for loop.

When looping through a dictionary, the return value are the *keys* of the dictionary, but there are methods to return the *values* as well.

Example

Print all key names in the dictionary, one by one:

```
for x in thisdict:  
    print(x)
```

Print all *values* in the dictionary, one by one:

```
for x in thisdict:  
    print(thisdict[x])
```

Continued

You can also use the `values()` function to return values of a dictionary:

```
for x in thisdict.values():  
    print(x)
```

Loop through both *keys* and *values*, by using the `items()` function:

```
for x, y in thisdict.items():  
    print(x, y)
```

Check if Key Exists

To determine if a specified key is present in a dictionary use the in keyword:

Example

Check if "model" is present in the dictionary:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
if "model" in thisdict:  
    print("Yes, 'model' is one of the keys in the thisdict dictionary")
```


Dictionary Length

To determine how many items (key-value pairs) a dictionary has, use the `len()` method.

Example

Print the number of items in the dictionary:

```
print(len(thisdict))
```


Adding Items

Adding an item to the dictionary is done by using a new index key and assigning a value to it:

Example

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
thisdict["color"] = "red"  
print(thisdict)
```

Removing Items

There are several methods to remove items from a dictionary:

Example

The **pop()** method removes the item with the specified key name:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
thisdict.pop("model")  
print(thisdict)
```

The `popitem()` method removes the last inserted item (in versions before 3.7, a random item is removed instead):

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
thisdict.popitem()  
print(thisdict)
```

The **del** keyword removes the item with the specified key name:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
del thisdict["model"]  
print(thisdict)
```

The del keyword can also delete the dictionary completely:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
del thisdict  
print(thisdict) #this will cause an error because "thisdict"  
no longer exists.
```

The `clear()` keyword empties the dictionary:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
thisdict.clear()  
print(thisdict)
```

Copy a Dictionary

You cannot copy a dictionary simply by typing `dict2 = dict1`, because: `dict2` will only be a *reference* to `dict1`, and changes made in `dict1` will automatically also be made in `dict2`.

There are ways to make a copy, one way is to use the built-in Dictionary method `copy()`.

Example

Make a copy of a dictionary with the `copy()` method:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
mydict = thisdict.copy()  
print(mydict)
```


Another way to make a copy is to use the built-in method `dict()`.

Example

Make a copy of a dictionary with the `dict()` method:

```
thisdict = {  
    "brand": "Ford",  
    "model": "Mustang",  
    "year": 1964  
}  
mydict = dict(thisdict)  
print(mydict)
```

Nested Dictionaries

A dictionary can also contain many dictionaries, this is called nested dictionaries.

Example

Create a dictionary that contain three dictionaries:

```
myfamily = {  
  "child1" : {  
    "name" : "Emil",  
    "year" : 2004  
  },  
  "child2" : {  
    "name" : "Tobias",  
    "year" : 2007  
  },  
  "child3" : {  
    "name" : "Linus",  
    "year" : 2011  
  }  
}
```

Create three dictionaries, then create one dictionary that will contain the other three dictionaries:

```
child1 = {  
  "name" : "Emil",  
  "year" : 2004  
}
```

```
child2 = {  
  "name" : "Tobias",  
  "year" : 2007  
}
```

```
child3 = {  
  "name" : "Linus",  
  "year" : 2011  
}
```

```
myfamily = {  
  "child1" : child1,  
  "child2" : child2,  
  "child3" : child3  
}
```

3/6/2020

The dict() Constructor

It is also possible to use the dict() constructor to make a new dictionary:

Example

```
thisdict = dict(brand="Ford", model="Mustang",  
year=1964)  
# note that keywords are not string literals  
# note the use of equals rather than colon for the  
assignment  
print(thisdict)
```

Dictionary Methods

Method	Description
<u>clear()</u>	Removes all the elements from the dictionary
<u>copy()</u>	Returns a copy of the dictionary
<u>fromkeys()</u>	Returns a dictionary with the specified keys and values
<u>get()</u>	Returns the value of the specified key
<u>items()</u>	Returns a list containing the a tuple for each key value pair
<u>keys()</u>	Returns a list containing the dictionary's keys
<u>pop()</u>	Removes the element with the specified key
<u>popitem()</u>	Removes the last inserted key-value pair
<u>setdefault()</u>	Returns the value of the specified key. If the key does not exist: insert the key, with the specified value
<u>update()</u>	Updates the dictionary with the specified key-value pairs
<u>values()</u>	Returns a list of all the values in the dictionary