SALES (Oracle)
Source Definition

K...	Name	Datatype
	SALE_ID	number(p,s)
	REGION	nvarchar2
	PRODUCT	nvarchar2
	SALES_AMOUNT	number(p,s)
	QUANTITY	number(p,s)
	SALE_DATE	nvarchar2

SQ_SALES
Source Qualifier

Name	Datatype	L
SALE_ID	decimal	2
REGION	nstring	2
PRODUCT	nstring	2
SALES_AMOUNT	decimal	2
QUANTITY	decimal	2
SALE_DATE	nstring	2

AGGTRANS
Aggregator

Name	Expression
SALE_ID	SALE_ID
REGION	REGION
PRODUCT	PRODUCT
SALES_AMOUNT	SALES_AMOUNT
QUANTITY	QUANTITY
SALE_DATE	SALE_DATE
TOTAL_SALES	sum(SALES_AMO
TOTAL_QUANTITY	sum(QUANTITY)
AVERAGE_SALES	avg(SALES_AMO
MAX_SALES	max(SALES_AMO
MIN_SALES	min(SALES_AMO
SALE_COUNT	count(SALE_ID)

SALES_T (Oracle)
Target Definition

K...	Name
	SALES_ID
	REGION
	TOTAL_SALES
	TOTAL_QUANTITY
	AVERAGE_SALES
	MAX_SALES
	MIN_SALES
	SALE_COUNT

de)
n

	Datatype
	number(p,s)
	nvarchar2
	number(p,s)
Y	number(p,s)
S	number(p,s)
	number(p,s)
	number(p,s)
	number(p,s)